



UNIVERSITI PUTRA MALAYSIA

**DESIGN ASSESSMENT OF THERMAL COMFORT USING COMPUTATIONAL
SIMULATION OF A TERRACE HOUSE IN
KUALA LUMPUR, MALAYSIA**

NASIBEH SADAFI

FRSB 2008 5



**DESIGN ASSESSMENT OF THERMAL COMFORT USING
COMPUTATIONAL SIMULATION OF A TERRACE HOUSE IN
KUALA LUMPUR, MALAYSIA**

By

NASIBEH SADAFI

Thesis Submitted to the School of Graduate Studies, University Putra Malaysia, in
Fulfilment of the Requirements for the Degree of Master

September 2008



Abstract of the thesis presented to the Senate of Universiti Putra Malaysia in fulfillment
of the requirement for degree of Master

**DESIGN ASSESSMENT OF THERMAL COMFORT USING
COMPUTATIONAL SIMULATION OF A TERRACE HOUSE IN
KUALA LUMPUR, MALAYSIA**

By

NASIBEH SADAFI

September 2008

Chairman: Prof. Dato' Ar. Elias @ Ilias Bin Salleh

Faculty: Design and Architecture

Terrace housing is the most common type of housing in Malaysia. They have been increasingly common in cities and towns in comparison to the detached single-family houses. However, comfort conditions in such house types vary according to the designs, modifications and adaptations of the occupants. Meanwhile, indoor environment studies in Malaysia revealed that most of the modern terrace houses are above upper thermal comfort level during day and night. The cause is simply because of unsuitable climatic design. In fact bioclimatic design considerations in terrace houses of Malaysia are not fully exploited according to occupant's comfort needs. This study investigates the influence of different design factors in enhancing thermal condition of the house.

Firstly, current condition of thermal comfort sensation for a case study terrace house in Kuala Lumpur Malaysia is investigated, using Fanger's Predicted Mean Vote thermal



comfort index. The case study was chosen in ‘Oversea Union Garden’ (OUG) area where field measurement was conducted during a three-day recording of air temperature, humidity, globe temperature and air velocity in naturally-ventilated spaces of the house. The study shows that the house is thermally comfortable for almost 15 hours during day and night, when comfort conditions mostly occurred during night hours. For improving the thermal conditions during the day, ceiling fan was used to increase the air velocity in the building. When the air temperature reaches its maximum amount, reducing the absorption of sun radiation will help more to enhance the thermal comfort condition of the house.

Baseline model for the computational experiment was developed according to the results from field measurement as well as selection and adjustment of the tool. In the next step ECOTECT software has been applied for constructing the computer model of the case study terrace house. Consequently, thermal analysis part in ECOTECT has been used to assess internal thermal properties of the house in three different months of the year including: March, Jun and December. Testing of the model consists of evaluating the existing condition, testing for the shading condition and testing for the effects of including internal courtyard in the house. These evaluations revealed that suitable shading design will improve the thermal conditions, especially during noon hours when the house has the most penetration of the sun from the windows as well as highest internal temperature. Introducing the internal courtyard will increase the thermal interactions between the building and outdoor environment especially in adjacent zones. However it can improve the thermal condition by applying suitable shading design as well as suitable materials for the fabrics.



According to the results of the study care should be taken for designing terrace houses in order to provide an optimal solar protection while considering the values of natural light. In courtyard buildings, the potential of courtyards to act as passive cooling can be correlated with the building composition in terms of air flow pattern.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia bagi memenuhi
keperluan ijazah Sarjana

**PENILAIAN REKABENTUK BAGI KESELESAAN SUHU DENGAN
MENGUNAKAN SIMULASI KOMPUTER UNTUK RUMAH TERES DI
KUALA LUMPUR, MALAYSIA**

Oleh

NASIBEH SADAFI

September 2008

Pengerusi: Prof. Dato' Ar. Elias @ Ilias Bin Salleh

Fakulti: Rekabentuk dan Senibina

Rumah teres adalah rumah yang paling banyak didapati di Malaysia. Hari semakin hari rumah teres lebih biasa dilihat di bandar-bandar dan pekan jika dibandingkan dengan rumah sebuah. Walaubagaimanapun, keselesaan sesebuah rumah bergantung kepada rekabentuk, pengubahsuaian dan penyesuaian penghuninya. Selain daripada itu, kajian tentang suasana dalaman di Malaysia menunjukkan kebanyakan rumah teres berada pada paras keselesaan suhu yang tinggi pada siang dan malam. Hal ini disebabkan hanya oleh rekabentuk persekitaran yang tidak sesuai. Hakikatnya di Malaysia, pertimbangan bioclimatic tidak memenuhi keselesaan penghuni. Kajian ini telah mencari pengaruh

kepada faktor perbezaan rekabentuk untuk meningkatkan keadaan terma sesebuah rumah.

Kajian keadaan terma rumah teres di Kuala Lumpur telah dilakukan menggunakan indeks keselesaan suhu Fanger's Predicted Mean Vote. Kajian kes telah dilakukan di Oversea Union Garden (OUG) di mana pengukuran suhu udara, kelembapan, suhu bumi, dan halaju udara diukur didalam rumah yang pengudaraannya neutral. Pengukuran dijalankan selama 3 hari. Hasil kajian menunjukkan, rumah dalam keadaan selesa selama hampir 14 jam sehari dimana keselesaan ini cenderung berlaku pada waktu malam. Bagi meningkatkan keselesaan pada waktu siang, kipas siling digunakan untuk menambah halaju udara didalam rumah. Apabila suhu udara mencapai jumlah maksimum, pengurangan penyerapan radiasi matahari akan membantu peningkatan keselesaan suhu di dalam rumah.

Berdasarkan penemuan tolok-ukur pada langkah berikutnya, program Ecotect telah digunakan untuk membina model komputer pada kes ini. Analisis suhu pada Ecotect digunakan bagi menilai ciri-ciri terma dalam rumah bagi 3 bulan yang berbeza: Mac, Jun, dan Disember. Penilaian keatas model termasuklah pertimbangan suasana semasa, ujian keredupan, dan ujian terhadap kesan taman di dalam rumah. Penilaian-penilaian ini menunjukkan keredupan yang sesuai mempengaruhi keadaan terma, terutamanya pada waktu siang dimana rumah menerima cahaya matahari dan seterusnya meningkatkan haba. Penggunaan taman di dalam rumah juga akan meningkatkan interaksi haba diantara bangunan dan kawasan luar rumah. Terutama sekali pada zon berlawanan. Walaubagaimanapun, ia boleh meningkatkan suhu dengan menggunakan rekabentuk teduhan yang sesuai dan juga bahan fabrik yang sesuai.

Acknowledgements

First of all; I am extremely grateful and thankful to GOD- ALLAH, for without his mercy and guidance none of this work would have been accomplished.

Next I would like to express my thanks and appreciate to each one of the following:

Great thanks to the University Putra Malaysia and Faculty of Design and Architecture.

My sincere and deepest thanks to my supervisor Prof. Dato' Ar. Elias @ Ilias Bin Salleh for his through supervision and encouragements that greatly inspired this work.

To Ar. Lim Chin Haw and Dr. Mohamad Fakri Zaky Bin Jaafar for their invaluable comments and insightful suggestions that further made this study meaningful.

To Mdm. Nor Shahrene Mohd.Ibrahim , I acknowledge her assistance for valuable explanations to understand Ecotect software and model preparation.

Special Thanks and great appreciate to my husband and my family for their support and assistant during this study.



This thesis was submitted to the Senate of the Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Master. The members of the Supervisory Committee were as follows:

Dato' Ar. Elias @ Ilias Bin Salleh, PhD

Professor
Faculty of Design and Architecture
Universiti Putra Malaysia

Ar. Lim Chin Haw

Senior lecturer
Faculty of Design and Architecture
Universiti Putra Malaysia

Mohamad Fakri Zaky Bin Jaafar, PhD

Lecturer
Faculty of Design and Architecture
Universiti Putra Malaysia

AINI IDERIS, PhD
Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 13 November 2008



DECLARATION

I declare that the thesis is my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously, and is not concurrently, submitted for any other degree at Universiti Putra Malaysia or at any other institution.

NASIBEH SADAFI

Date:



TABLE OF CONTENTS

	Page
ABSTRACT	ii
ABSTRAK	v
ACKNOWLEDGMENTS	vii
APPROVAL	viii
DECLARATION	x
LIST OF TABLES	xiv
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xix
CHAPTER	
1 INTRODUCTION	1
1.1 Introduction	1
1.2 Background	2
1.3 Problem Statement	3
1.4 Objectives of the research	5
1.5 Scope of the study	5
1.6 Research Methodology	6
1.7 Research Framework	7
1.8 Chapters over view	8
2 CLIMATIC DATA AND BIOCLIMATIC DESIGN	10
2.1 Introduction	10
2.2 General Climatic Consideration	10
2.2.1 Temperature Distribution	11
2.2.2 Relative Humidity	12
2.2.3 Sunshine and Solar Radiation	13
2.2.4 Wind flow in Malaysia	15
2.2.5 Rainfall Distribution	16
2.3 Bioclimatic design in warm-humid climate	18
2.3.1 Thermal impacts of shading conditions	19
2.3.2 Insulation and thermal heat gain	24
2.3.3 Thermal impacts of ventilation conditions	27
2.4 Summary	32
3 TERRACE HOUSES IN MALAYSIA	34
3.1 Introduction	34
3.2 Historical background	34
3.2.1 Terrace houses in Malaysia	34
3.3 The modern terrace houses	37
3.3.1 Design factors of Terrace Houses.	37



3.4	Summary	45
4	THERMAL COMFORT PRINCIPLES AND STUDIES	46
4.1	Introduction	46
4.2	Comfort terminologies	47
4.2.1	Thermal vote	47
4.2.2	Thermal Neutrality	47
4.2.3	Thermal acceptability	48
4.2.4	Thermal preference	48
4.3	Conditions for Thermal Comfort	49
4.3.1	Comfortable core body temperature	49
4.3.2	Comfortable skin temperature	50
4.3.3	Comfortable perspiration rate	50
4.4	Comfort Prediction	50
4.4.1	Early thermal comfort indices	51
4.4.2	Fanger's model: Predicted Mean Vote	53
4.4.3	Adaptive comfort	61
4.5	The importance of thermal comfort in architectural design	64
4.5.1	Investigation methods in thermal comfort studies	65
4.5.2	Computer modeling	66
4.5.3	Thermal Comfort Studies in South East Asia	67
4.5.4	Thermal comfort studies in Malaysia	71
4.5.5	Courtyard building studies	74
4.6	Summary	76
5	DEVELOPMENT OF BASELINE MODEL	78
5.1	Introduction	78
5.2	Prevailing climatic condition for April	78
5.3	Field measurement	81
5.3.1	The investigated building/Unit of analysis	82
5.3.2	Data Collection	84
5.3.3	Assumptions of the study	86
5.4	Results	87
5.4.1	Recorded Data	87
5.4.2	Discussions	89
5.5	Thermal improvement investigation	94
5.5.1	Using ceiling fan to promote the air velocity	94
5.5.2	Mean Radiant Temperature	95
5.5.3	Results and discussion	95
5.6	Baseline model	98
5.7	Tool selection process	99
5.8	ECOTECT	100
5.9	Procedure	101
5.9.1	Baseline modeling parameters	103



5.9.2	Assumptions	107
5.9.3	Sun shading	108
5.10	ECOTECH results validation	118
5.11	Summary	119
6	COMPUTATIONAL BIOCLIMATIC DESIGN ASSESSMENT EXPERIMENTATION	120
6.1	Introduction	120
6.2	Analysis	121
6.2.1	Mode A: Existing condition	121
6.2.2	Mode B: Openings and Sun Shading	123
6.2.3	Mode C: Introducing internal courtyard	123
6.3	Results and Discussion	126
6.3.1	Comparative analysis mode A and B	127
6.3.2	Comparative analysis mode A and C	127
6.3.3	Variations for Mode C	131
6.4	Summary	135
7	RESULTS AND ANALYSIS	137
7.1	Introduction	137
7.2	Baseline model development	137
7.2.1	Predicted Mean Vote (PMV)	138
7.2.2	Potential PMV improvements	139
7.2.3	Modeling	141
7.2.4	Simulation of solar penetration	142
7.3	Computational experiment method	143
7.3.1	Shading analysis	144
7.3.2	Simulation of introducing internal courtyard	145
7.4	Validation of the results	150
8	CONCLUSION AND RECOMMENDATION FOR FURTHER RESEARCH	151
8.1	Objectives of the study	151
8.2	Results and Conclusion	151
8.3	Recommendation	154
8.3.1	Future research	155
	REFERENCES	156
	APPENDICES	163
	BIODATA OF STUDENT	205
	LIST OF PUBLICATIONS	206



LIST OF TABLES

Table	Page
2-1 Station: The Values of Rainfall Intensity for Various Return Period	18
4-1 Summary of some early indices of thermal comfort	51
4-2 Met Value Table	58
4-3 Expectancy factor for non-air-conditioned buildings in warm climate.	64
4-4 thermal comfort studies in tropical South East Asia region	70
4-5 Results from various thermal comfort studies in Malaysia.	74
5-1 Material description for the case study building.	83
5-2 Assumptions in PMV calculation	86
5-3 Summary of thermal comfort condition according to PMV variations.	93
5-4 variation of air velocity in different settings of the ceiling fan	96
5-5 PMV variation according to changes in air velocity	97
5-6 PMV variations according to changes in Mean Radiant Temperature	98
5-7 Material description for the case study building	104
5-8 Assumptions in ECOTECH analysis.	107
5-9 Sun penetration in the kitchen –SE orientation	110
5-10 Sun penetration in the living area –NW orientation	110
7-1 Analysis of the recorded data for three days of experiment	138
7-2 Division of comfort condition in the house according to PMV variations	139
7-3 HSA and VSA angles	143
7-4 Internal temperature variations in living area according the height of courtyard shading roof	148
8-1 Summary of the recommendations.	154

LIST OF FIGURES

Figure	Page
2-1 Rectangular sun path	14
2-2 wind rose for Kuala Lumpur	15
2-3 The derivation of horizontal shadow angle (HSA)	22
2-4 The derivation of the VSA based on the plane containing the Sun	23
2-5 Width, depth and height as they apply to this simple method of horizontal shading device design	24
2-6 Placing your hand against the interior surface of a window pane will cause the adjacent air to become warmer, buoyant and to rise.	28
2-7 A single-banked layout for a residence will readily enable airflow across its width.	31
2-8 Opening up the vertical envelope for cross-ventilation	32
3-1 Jonker's Street in Malacca, Malaysia.	35
3-2 The range of building lot size	39
3-3 setback of building lines	40
3-4 building height of the terrace house	41
3-5 Possible position of the staircase.	41
3-6 The position of car park and car porch.	42
3-7 common views and zoning in the terrace houses.	42
3-8 Possible positions of courtyard/ air well in terrace houses	43
3-9 Modern Terrace houses façade	44
3-10 Modern Terrace houses design	44
3-11 Terrace houses new design	44
4-1 Thermal sensation	49

4-2 Predicted percentage of dissatisfied (PPD) as a function of predicted mean vote	53
4-3 Thermal sensation indicator	55
4-4 Insulation for clothing value	57
4-5 PMV and PPD relation and variation.	61
5-1 Dry Bulb Temp variation during 10 th -13 th April 2007.	79
5-2 Relative Humidity variation during 10 th -13 th April 2007.	80
5-3 Wind speed variation during 10 th -13 th April 2007.	81
5-4 floor plans and longitudinal section of the case study terrace house.	82
5-5 North facade of the case study Terrace house. (a), (b) and(c)	83
5-6 (a, b): field measurement tool INNOVA.	85
5-7 Air temperature variation during three days field measurement	87
5-8 Globe temperature and air temperature variations during three days field measurement	88
5-9 Relative humidity variation during three days field measurement	88
5-10 Recorded Air velocity during three days experiment	89
5-11 variation of PMV and PPD (ground floor)	89
5-12 Variation of PMV during 3 days- ground floor family area: condition (1)	90
5-13 PMV variations during 3 days experiment: condition (2)	92
5-14 PMV variations during 3 days experiment: condition (3)	93
5-15 Air velocity measurement in different settings fan	95
5-16 variation of PMV and PPD after changing air velocity to “1m/s” in uncomfortable conditions for three days measurement	96
5-17 Case study building ground floor plan	105
5-18 Case study building first floor plan	105
5-19 Case study building section	106



5-20 Zone division for the case study building	106
5-21 Sun penetration in ground floor area at 9:00 am on 15 th of March 2007.	108
5-22 HSA angle for the rear façade of the case study building at 9am 15 th March 2007	109
5-23 VSA for the rear facade at 9am 15 th March 2007	109
5-24 Sun pass diagram for KL in 15 th Jun 3pm	111
5-25 VSA angle at 3pm 15 th Jun for front façade	112
5-26 Sun pass diagram for KL in 15 th Dec 9am	112
5-27 VSA angle at 9am 15 th December for rear facade	113
5-28 Shading device and VSA for living area	114
5-29 After applying the horizontal shading device there are some penetration in the kitchen	115
5-30 HSA and vertical shading device for kitchen (plan)	115
5-31 Dividing the wide shading device to two narrower	116
5-32 Suggested egg-crate shading device for the kitchen window	117
5-33 (a and b) narrow shading devices and VSA for rear facade (kitchen).	117
5-34 Temperature variations comparison between field measurement data and ECOTECH simulation	118
6-1 Hourly temperature-living area-15 th March 2007	121
6-2 Hourly temperature-living area-15 th Jun 2007	122
6-3 Hourly temperature-living area-15 th December	122
6-4 Temperature variation of the living area in mode B 15 th Jun	123
6-5 Case study terrace house after introducing the courtyard	124
6-6 Hourly temperatures for the living area in 15 th March	125
6-7 Hourly temperatures for the living area in 15 th Jun model C	125



6-8 Thermal performance of the living area in 15 th of December	126
6-9 Temperature difference of living area before and after using shading device	127
6-10 Temperature difference between mode A and C in March	128
6-11 Conduction gains difference of mode A and C for living area in March	128
6-12 Heat gain and loss through ventilation for mode A and C	129
6-13 Temperature difference between mode A and C for living area in Jun.	129
6-14 Temperature difference between mode A and C for dining area in Jun	130
6-15 Solar gains difference of dining area for mode A and C in Jun	130
6-16 Temperature difference between mode A and C in December for living area	131
6-17 Temperature difference for living area when different height for courtyard shading roof	132
6-18 Shading roof for the court yard with 500mm height	132
6-19 Solar gain difference in courtyard area mode C and C-1 (courtyard with shading roof)	133
6-20 Temperature difference for the living area mode C and C1 in March	133
6-21 temperature difference of the living area for mode C and C2	135
7-1 Temperature difference of living area before and after using shading device	144
7-2 PMV variation difference for mode A and B	145
7-3 Ground floor of the case study terrace house after introducing the courtyard, living area can release the heat through the windows	146
7-4 Ground floor of the case study terrace house after introducing the courtyard, there is no way for the entered heat in the dining area to be released	146
7-5 PMV variation difference in living area mode A and C	147
7-6 PMV variation difference for mode A and C in dining area	147



ABBREVIATIONS

ASHRAE	American Society of Heating, Refrigerating and Air-Conditioning Engineers
Clo	Clothing Level
C	degree Celsius
DBT	Dry Bulb Temperature
DOSM	Department Of Statistics Malaysia
ET	Effective Temperature
F	degree Fahrenheit
f_{cl}	the ratio of a person's surface when area while clothed, to the surface area while nude
h_c	convective heat transfer coefficient
I_{cl}	thermal resistance of clothing
Met	Metabolic Rate
MRT	Mean Radiant Temperature
PMV	Predicted Mean Vote
PPD	Predicted Percent of Dissatisfied
p_a	partial water vapor pressure
RH	Relative Humidity
T_a	Air Temperature
T_n	Thermal neutrality
T_{ave}	monthly mean outdoor Temperature



T_o	operative Temperature
T_{eq}	equivalent Temperature
t_{cl}	surface temperature of clothing
t_r	mean radiant temperature
Vel	Air Movement
V_{ar}	relative air velocity
W	external Work

CHAPTER 1

INTRODUCTION

1.1 Introduction

As a developing country, Malaysia is facing problems to accommodate the urban population. The migration of rural population to cities caused the government and private agencies to built 1.8 millions units of house from 1976 to 1995. Most of the houses were built in rows, called terrace houses with façade of 20-24 feet and depth of 70-80 feet , constructed either one or two story high and openings only on the front and back elevations; actually they are an efficient vertical use of scarce urban space (Mohammed Ali, 2003).

In architectural aspects, similar forms and facades resulted in the urban landscapes without variety and character (Said, 1994), also since 1981 several researchers have determined that these buildings are not designed in response to the country's inclement climate which is characterized by four main features; seasonal uniformity, low wind velocities and small diurnal temperature range as well as high humidity. In fact most terrace house designs have ignored the importance of thermal comfort zone in the interiors (Takahashi, 1981).



1.2 Background

The first major issue of most discussions about climate is the thermal comfort level (Salleh E, 2004). Thermal comfort can be defined as ‘the state of mind, which expresses satisfaction with the thermal environment’ (ASHRAE, 1985); the definition quickly perceived, but hard to exploit in physical parameters. Air temperature, air movement, radiation and humidity are not the only climatic characteristics that affect human comfort but they are the dominant ones. Thermal-comfort problems are varied and as they may be caused by different factors such as conversion of building operational and physical characteristics and occupant behavior and interference, they can be difficult to identify and solve (Van Hoof J, 2007).

For buildings in tropical regions with warm-humid climate various strategies have been suggested in previous studies in order to handle the warmth and humidity in relation to thermal comfort (Koenigsberger et al, 1971, Evans, 1979 and Salleh E, 2004). As Koenigsberger et al (1971) suggested in warm humid climate indoor comfort is largely dependent on the control of air movement and radiant heat. Maximum air movement passing over the body must be encouraged and solar gain must be prevented from reaching the building’s occupants either directly through doors and windows or indirectly by heating the structure. But exploitation of these various strategies seems to be neglected in contemporary modern constructions.

In Malaysia, as a country located in warm-humid tropics, the new type of modern housing sprang up after its independence, called “terrace housing” which brought about

a new and alien life style (Salleh R, 1989). Large numbers of terrace houses have been constructed in Malaysia. In cities and towns the terrace houses have been increasingly common in comparison to the detached single-family houses. They are attached houses with similar façade treatment. Found in the inner city they look similar to the row housing of Europe, which are built on a rectangular plot and the frontage form is the narrow section of the lot.

The terrace house is low-rise, but it can be built at a very high density in a regimented layout. About 40 units can be built on one-hectare area (Mohammed Ali, 2003). However, in spite of their adaptability, the climate and urban conditions of the country has not been considered in the design stage of their construction, so air-conditioning systems are common ways for controlling indoor comfort despite their increase of energy demands (Pattaranan, 2006).

1.3 Problem Statement

Bioclimatic design considerations in terrace houses of Malaysia have not been fully explored according to occupant's comfort needs.

Thermal comfort should be considered as the main concern apart from other comfort criteria such as visual, acoustic and indoor air quality. Passive means should be given priority first and active systems should also be provided whenever they are required to minimize the thermal stress. To achieve this aim, it is important to consider climate at all design stages (Pattaranan, 2006). In spite of the importance of comfort sensation on the

indoor environmental quality perception, climatic, behavioral and adaptive factors affecting thermal comfort requirements are normally being neglected by the architects and systems designer at the time of designing buildings. In the process, a significant opportunity to save energy and providing the optimum environmental settings for thermal satisfaction will be missed out (Mahdavi A et al, 2001).

Indoor environment studies in Malaysia revealed that most of the modern terrace houses are above upper thermal comfort level during day and night (Davis et al, 1998). The mass housing programs resulted in dwelling units which are not designed suitable for the warm-humid tropical climate of the country. The importance of thermal comfort of the house has been ignored in most of the common housing designs (Said et al, 1994).

So this study is intended to investigate the effects of suitable bioclimatic designing in preventing indoor overheating conditions and lowering maximum indoor temperature below the ambient, in warm humid climates. It is hypothesized here that applying such strategies in modern terrace houses can enhance indoor comfort conditions.

In this case the following research questions are deemed relevant:

1. How to apply suitable bioclimatic design principles to ameliorate the thermal conditions of terrace houses in hot-humid climate of Malaysia?
 - a. What are the current thermal comfort conditions in existing Terrace house of Malaysia?

- b. What is the relationship between shading design and thermal sensation?
- c. What are the effects of introducing internal courtyard on indoor comfort conditions in terrace houses?

1.4 Objectives of the research

The main objectives of this research are:

- To investigate the thermal performances of an existing terrace house under warm- humid climate.
- To examine the effects of different aspects of climatic design to improve the current condition.
- To propose appropriate design measures in ensuring indoor thermal comfort in terrace houses of warm-humid climate.

1.5 Scope of the study

The study focuses on the effects of design variables on thermal comfort, under naturally ventilated conditions, with reference to the family area in a terrace house.

These design variables are limited to:

1. Shading device
2. Internal courtyard