



UNIVERSITI PUTRA MALAYSIA

**DEVELOPMENT OF CAPACITIVE COMPOSITE MATERIALS USING
ALKALINE TITANATES AND KAOLINITE CLAY**

ALEX SEE

FS 2009 8



**DEVELOPMENT OF CAPACITIVE COMPOSITE MATERIALS USING
ALKALINE TITANATES AND KAOLINITE CLAY**

By

ALEX SEE

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of Master of Science**

August 2009



This thesis is dedicated to God and my family.



Abstract of thesis presented to the Senate of University Putra Malaysia in fulfilment of requirement for the degree of Master of Science In Material Science.

**DEVELOPMENT OF CAPACITIVE COMPOSITE MATERIALS USING
ALKALINE TITANATES AND KAOLINITE CLAY**

By

ALEX SEE

August 2009

Chairman: Associate Professor Dr. Jumiah Hassan, PhD

Faculty: Faculty Science

This research was designed to form a better dielectric composite material using one stable state dielectric matrix material and a good dielectric material as filler powder. The hypothesis is that the encapsulation of the filler powder by the matrix material, thus providing a bridge between the net polarizations of the composites. There are some limitations to the hypothesis, namely in the reactions and the limited control of the encapsulation process.

Distinct dielectric composites were successfully produced using locally sourced kaolinite clay and chemically produced alkaline titanates for example, Barium Titanate (BT) and Strontium Titanate (ST). The samples were made using kaolinite as the base matrix and alkaline titanate added in varying ratios. The alkaline titanate were synthesized via solid-state reaction using a carbonate derivative of the alkaline

cation and rutile titanium (IV) oxide sintered at 1200°C to 1300°C. White kaolinite was used to fuse the alkaline titanate material in varying weight ratios. The powders were dry-mixed and made into pellets for calcination at 1000°C.

The XRD data of BT-kaolinite type composites revealed a chemical reaction between the matrix and the filler powder at various combinations. Thus, BT additives reacted with the mullite and silica components and produced celsian feldspar in the composite system. This suggests that the system polarization contains the sum of four interfacial polarization processes at different temperatures. ST-mullite composites showed distinct varying interfacial cladding and dipolar relaxation for all composites.

SEM micrographs revealed fused and flaky parts formed in the BT composite samples whereby the powders were melted together. ST composite samples only showed inter-grain formation of the filler and matrix material. EDX, however, showed that there was some contamination in the matrix powder with potassium and carbon elements in the system.

Dielectric properties for both BT and ST composites exhibited low dielectric constant values ranging from 10 to 20 in the frequency range 10 Hz to 1 MHz. Dielectric modelling showed that the BT composite samples displayed single relaxation processes for the sample series whereas the ST composite samples exhibited multiple thermally activated dielectric relaxations. The modelling of the

dielectric data was done using the Havriliak-Negami equation to show two distinct dielectric processes occurring within the same framework.

Impedance plots showed significant varied impedance based on the measured temperatures with both composite series exhibiting high resistance. DC conductivity measurements were carried out on the samples, yielding very high activation exothermic and endothermic activation of energy of reactions in the medium. Dielectric modulus plots, however showed varied dispersion due to deformations in dielectric stresses in the composite series. Microwave frequency measurements showed dielectric properties of the medium without the interfacial polarization.

**Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Master Sains dalam Sains Bahan**

**KAJIAN TENTANG BAHAN KOMPOSIT JENIS KAPASITOR
MENGUNAKAN TITANATE BERALKALI DAN KAOLINITE**

Oleh

ALEX SEE

Ogos 2009

Pengerusi: Profesor Madya Dr. Jumiah Hassan, PhD

Faculti: Faculti Sains

Kajian ini telah direka untuk membentuk bahan komposit dielektrik yang lebih baik dengan menggunakan bahan matriks bersifat dielektrik stabil dan bahan dielektrik yang tinggi sebagai serbuk pengisi. Hipotesis adalah bahawa penglitupan serbuk pengisi oleh bahan matriks membentuk jambatan di antara jumlah pengutuban dalam komposit tersebut. Terdapat beberapa had dari kajian ini, antaranya dalam tindakbalas-tindakbalas dan kekurangan kawalan dalam proses pelitupan.

Komposit dielektrik tertentu telah berjaya dihasilkan daripada kaolinit tempatan and titanat beralkali yang dibuat secara kimia, iaitu, barium titanat dan strontium titanat. Sampel telah dibentuk menggunakan kaolinite sebagai matriks asas and titanat beralkali dicampur dalam nisbah tertentu. Titanat beralkali telah disintesis menggunakan bahan karbonat berkation alkali dan titanium (IV) oksida yang dipanaskan pada suhu 1200°C hingga 1300°C. Kaolinit tempatan yang putih telah

digunakan untuk menggabungkan bahan titanat beralkali yang nisbah berat tertentu. Bahan serbuk telah dicampur secara kering dan dibentukkan kepada cakera kecil untuk dipanaskan pada suhu 1000°C.

Data XRD bagi komposit jenis BT-kaolinit telah menunjukkan tindakbalas kimia antara bahan matriks dan bahan pencampur dalam beberapa sampel yang digabungkan. Ini menunjukkan bahawa bahan pencampur BT telah bertindakbalas dengan mullit dan seterusnya membentuk ‘celsian felspar’ dalam sistem komposit tersebut. Oleh yang demikian, pengutuban sistem ini mungkin 4 jenis pengutuban sifat antaramukaan pada suhu berlainan. Komposit ST-mullit menunjukkan sifat pelitupan antaramukaan yang berlainan dan santaian dielektrik jenis dwikutub untuk semua sampel kompositnya.

Mikrograf SEM menunjukkan bahagian lakur dan leper terbentuk dalam sampel komposit BT di mana serbuk tersebut telah tergabung. Manakala sampel komposit ST hanya menunjukkan perbentukan butiran antara bahan pencampur dan matriks. EDX telah menunjukkan bahawa terdapat sedikit pencemaran unsur kalium dan karbon dalam sistem bahan matriks.

Sifat dielektrik untuk kedua-dua komposit BT dan ST menunjukkan nilai pemalar dielektrik yang rendah berukuran 10 hingga 20 pada frekuensi 10 Hz hingga 1 MHz. Pemodelan dielektrik telah menunjukkan bahawa sampel komposit BT mempunyai hanya sejenis proses santaian dielektrik manakala sampel ST menunjukkan variasi

dalam pengenduran dielektrik berganda teraktif secara terma. Pemodelan data dielektrik telah dibuat berpadukan model Havriliak-Negami untuk memperlihatkan dua proses dielektrik yang ketara berlaku serentak dalam sistem yang sama.

Plot impedans menunjukkan nilai impedans berubah dengan ketara berlandaskan suhu yang diambil dengan kedua-dua kumpulan komposit tersebut menunjukkan sifat kerintangan yang tinggi. Kajian sampel dalam sifat konduktiviti arus terus menunjukkan sifat tenaga pengaktifan eksotermik dan endotermik yang tinggi dalam bahan tersebut. Plot modulus dielektrik telah menunjukkan bahawa terdapat sebaran data yang tidak konsisten disebabkan oleh kewujudan kecacatan disebabkan oleh tekanan dielektrik di dalam siri komposit tersebut. Kajian dalam frekuensi mikro-gelombang hanya menunjukkan sifat dielektrik bahan medium tanpa pengutuban antara-mukaan di antara butiran.

Acknowledgement

I would like say thanks to my supervisors, Associate Professor Dr. Jumiah Hassan, Associate Professor Dr. Mansor Hashim and Associate Professor Dr. Wan Daud Wan Yusoff for their patience and assistance in guiding me throughout the entire research process.

I would also like to thank my seniors, Khe Cheng Siong, Walter Primus and Josephine Liew for their exchanges in information and discussions. I would like to thank also Wong Swee Ying, Liew Seng Choy, Mazni Mustapha, Tan Foo Khoon and Leow Chun Yan for their help.

I would like express my gratitude to the undergraduate students Sin Swee Keng, Yap Wen Khong, Thoo Kar How, Lee Kian Keong, Cheong Wei Oeng, Goh Shu Yee, Chan Choo Lian, Tan Wei Soon, Chen Sze Nee, Lee Yin Cheak and Liew Kjin Jau for helping me learn more about teaching and conducting research.

I would like to thank Professor Dr. Lisa Heller-Kallai for providing me with assistance and some of her articles in the heated reactions kaolinite with earth salts. Her kind assistance is greatly appreciated.

Finally, I would like to thank my father, my mother and family for their financial and guidance throughout the entire research period. Their understanding and encouragement is essential to the success of this research project.



I certify that a Thesis Examination Committee has met on **24th August 2009** to conduct the final examination of **Alex See** on his master thesis entitled **Development of Capacitive Composite Materials Using Alkaline Titanates and Kaolinite Clay** in accordance with Universities and University Colleges Act 1971 and the Constitution of Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Masters of Science in Material Science.

Members of the Examination Committee were as follows:

Dr. Mohd. Maarof H. A. Moxsin, PhD

Professor
Faculty of Science
Universiti Putra Malaysia
(Chairman)

Dr. Azmi Zakaria, PhD

Professor
Faculty of Science
Universiti Putra Malaysia
(Internal Examiner)

Dr. Zaidan Abdul Wahab, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Internal Examiner)

Dr. Ibrahim Abu Talib, PhD

Professor
Faculty of Science and Technology
Universiti Kebangsaan Malaysia
(External Examiner)

BUJANG BIN KIM HUAT, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 15 October 2009

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Jumiah Hassan, Phd

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Chairman)

Mansor Hashim, Phd

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Member)

Wan Daud Wan Yusoff, Phd

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Member)

HASANAH MOHD GHAZALI, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 16 November 2009



DECLARATION

I declare that the thesis is my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously, and is not concurrently, submitted for any other degree at Universiti Putra Malaysia or at any other institution.

(Signature)

ALEX SEE

Date:

I certify that a Thesis Examination Committee has met on **24th August 2009** to conduct the final examination of **Alex See** on his master thesis entitled **Development of Capacitive Composite Materials Using Alkaline Titanates and Kaolinite Clay** in accordance with Universities and University Colleges Act 1971 and the Constitution of Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Masters of Science in Material Science.

Members of the Examination Committee were as follows:

Dr. Mohd. Maarof H. A. Maksin, Phd

Title: Professor

Name of Faculty: Faculty of Science, Physics Department
Universiti Putra Malaysia
(Chairman)

Dr. Azmi Zakaria, Phd

Title: Professor

Name of Faculty: Faculty of Science, Physics Department
Universiti Putra Malaysia
(Internal Examiner)

Dr. Zaidan Abdul Wahab, Phd

Title: Associate Professor

Name of Faculty: Faculty of Science, Physics Department
Universiti Putra Malaysia
(Internal Examiner)

Dr. Ibrahim Abu Talib, Phd

Title : Professor

Name of Department and/or Faculty
Universiti Kebangsaan Malaysia
(External Examiner)

BUJANG BIN KIM HUAT, Phd

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:



This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of **Master of Science In Material Science**. The members of the Supervisory Committee were as follows:

Dr. Jumiah Hassan, Phd

Title: Associate Professor

Name of Faculty: Faculty of Science, Physics Department

Universiti Putra Malaysia

(Chairman)

Dr. Mansor Hashim, Phd

Title: Associate Professor

Name of Faculty: Faculty of Science, Physics Department

Universiti Putra Malaysia

(Member)

Dr. Wan Daud Wan Yusoff, Phd

Title: Associate Professor

Name of Faculty: Faculty of Science, Physics Department

Universiti Putra Malaysia

(Member)

HASANAH MOHD GHAZALI, PhD

Professor and Dean

School of Graduate Studies

Universiti Putra Malaysia

Date :



TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	vi
ACKNOWLEDGEMENT	ix
APPROVAL	x
DECLARATION	xii
LIST OF TABLES	xvi
LIST OF FIGURES	xvii
LIST OF ABBREVIATION	xxiii
CHAPTER	
1 INTRODUCTION	
1.1 Introduction	1
1.2 Objectives	2
1.3 Research Limitation	3
1.4 Kaolinite	3
1.5 Mullite	6
1.6 Alkaline Titanates	6
2 LITERATURE REVIEW	
2.1 History of Traditional Ceramics	8
2.2 Recent Development of Kaolinite and Mullite Composite Derivatives	9
2.3 Reactions of kaolinite with alkaline cation compounds	11
2.3 Recent Development of Alkaline Titanates and Composite Derivatives	12
2.4 Composite formation involving Barium Titanate	13
2.5 Dielectric Properties of the Materials	14
3 THEORY	
3.1 Alkaline Titanates	16
3.2 Kaolinite	18
3.3 Definition of Dielectrics	19
3.4 Definition of Dielectric Polarization	20
Dielectric Models	
3.5.1 Debye Expression	24
3.5.2 Cole-Cole Expression	25
3.5.3 Havriliak-Negami Expression	26
3.6 Equivalent Circuit Analysis	28
3.7 Complex Plane Analysis	29
3.8 DC Conductivity	31



4	METHODOLOGY	
4.1	Introduction	34
4.2	Preparation of Filler Powder via Conventional Solid State Reaction	35
4.2.1	Weighing	35
4.2.2	Dry Milling and Mixing	36
4.2.3	Pre-sintering	36
4.2.4	Grinding and Sieving	38
4.2.5	Final Sintering	39
4.3	Preparation of Kaolinite-Barium Titanate and Kaolinite-Strontium Titanate Pellets	40
4.3.1	Weighing	40
4.3.2	Mixing	41
4.3.3	Pre-sintering	41
4.3.4	Crushing and Sieving	42
4.3.5	Addition of Binder and Molding	42
4.3.5	Final Sintering	42
4.4	Structure Analysis	43
4.4.1	X-Ray Diffraction (XRD)	43
4.4.2	Scanning Electron Microscopy (SEM) and Energy Dispersive X-rays (EDX) Analysis	44
4.4.3	Low Frequency Dielectric Measurements	44
4.4.4	Microwave Range Dielectric Measurement	45
4.4.5	DC Conductivity Measurements	45
5	RESULTS AND DISCUSSION	
	PART 1: MICROSTRUCTURE, PHYSICAL AND CHEMICAL MEASUREMENTS	
5.1	X-Ray Diffraction (XRD) Analysis	46
5.1.1	Rough Estimation of the Feldspar By-products	52
5.2	Energy Dispersive X-ray (EDX) Elemental Analysis	52
5.3	Scanning Electron Microscopy (SEM) Analysis	54
5.4	Estimation of Crystalline Size by Scherrer's Equation	65
6	RESULTS AND DISCUSSION	
	PART 2: DIELECTRIC MEASUREMENTS AND ANALYSIS	
6.1	Dielectric Properties of BT Composites	67
6.2	Dielectric Properties of ST Composites	76
6.3	Stability of the Dielectric Response	84
6.4	Dielectric Modeling and Equivalent Circuit for BT Composites	105
6.5	Dielectric Modeling and Equivalent Circuit for ST Composites	124
6.6	Complex Plots of Z Parameter for BT Composites	140
6.7	Complex Plots of Z Parameter for ST Composites	151
6.8	Complex Dielectric Modulus Properties of BT Composites	161
6.9	Complex Dielectric Modulus Properties of ST Composites	172
6.10	Dielectric Response in The Microwave Frequency Region	

	(1MHz –1.8GHz)	182
6.11	DC Conductivity Plots for BT Composites	186
6.12	DC Conductivity Plots for ST Composites	192
7	CONCLUSION	
7.1	Conclusion	197
7.2	Future Research	200
	REFERENCES	201
	APPENDICES	206
	BIODATA OF STUDENT	211



LIST OF TABLES

Table		Page
3.1	List of Minerals Based on the ABO_3 formula, with varying ions configurations (Klein and Dutrow, 2008)	16
4.1	Weight of $BaTiO_3$	36
4.2	Weight of $SrTiO_3$	36
4.3	Composition of Barium Titanate added to Kaolinite	40
4.4	Composition of Strontium Titanate added to Kaolinite	40
5.1	BT By-product Estimation	52
5.2	EDX Elemental Composition for the BT-Kaolinite Composites	53
5.3	EDX Elemental Composition for the ST-Kaolinite Composites	53
5.4	Crystalline Size for the BT and ST Composite	65
6.1	Dielectric Permittivity for 1 kHz and 1 MHz Responses for BT Composites	103
6.2	Dielectric Permittivity for 1 kHz and 1 MHz Responses for ST Composites	104
6.3	Standard Deviation Calculation for 1 kHz and 1 MHz Responses for Both BT and St Composites	104
6.4	HN Fitting Parameters for Pure Kaolinite Matrix	105
6.5	HN Fitting Parameters for 10% BT	106
6.6	HN Fitting Parameters for 20% BT	107
6.7	HN Fitting Parameters for 30% BT	108
6.8	HN Fitting Parameters for 40% BT	109
6.9	HN Fitting Parameters for 50% BT	110
6.10	HN Fitting Parameters for 60% BT	111
6.11	HN Fitting Parameters for 70% BT	112
6.12	HN Fitting Parameters for 80% BT	113
6.13	HN Fitting Parameters for 10% ST	124
6.14	HN Fitting Parameters for 20% ST	125
6.15	HN Fitting Parameters for 30% ST	126
6.16	HN Fitting Parameters for 40% ST	127
6.17	HN Fitting Parameters for 50% ST	128
6.18	HN Fitting Parameters for 60% ST	129
6.19	HN Fitting Parameters for 70% ST	130
6.20	HN Fitting Parameters for 80% ST	131
6.21	Calculated Activation Energies for the BT Composites	187
6.22	Calculated Activation Energies for the ST Composites	193



LIST OF FIGURES

Figure		Page
1.1	3D representation of kaolinite structure	4
1.2	US consumption of Kaolinite in various sectors. Courtesy of U.S. Geological Survey (Kelly and Matos, 2008)	5
3.1	Typical Perovskite Structure (Kingery et al, 1971)	17
3.2	Crystal Structure of Kaolinite	18
3.3	Crystal Structure for Mullite	19
3.4	Basic Capacitor Experiment Illustrating the Theory in Section 3.3 (Grimnes and Martinsen 2008).	20
3.5	Various types of polarizations (Cho et al, 2001)	23
3.6	The probable occurrence of the various types of the polarization and the dependence of the permittivity with respect to frequency (Cho et al, 2001)	24
3.7	The frequency dependence of the real and imaginary parts of the permittivity of an ideal Debye system corresponding to equation (3.4). The loss peak is symmetric. (Jonscher, 1983).	25
3.8	The frequency dependence of the real and imaginary parts of the permittivity corresponding to the Cole-Cole expression (3.5). The loss peak is symmetric but is broader than Debye peak (Jonscher, 1983).	26
3.9	The frequency dependence of the real and imaginary parts of the permittivity corresponding to the Havriliak-Negami expression (Kremer and Schönhals 2003).	27
3.10	Comparisons of the various dielectric fitting equations and the parameters involved. (Kremer and Schönhals, 2003).	27
3.11	Equivalent dielectric circuits for 1R-2C model: a) parallel version, b) serial version (Kremer and Schönhals, 2003)	28
3.12	Differences in Dielectric Fitting Response for Ohmic and Non-ohmic Materials (Kremer and Schönhals, 2003)	29
3.13	Differences in Complex Plane Graphs and Their Respective Equivalent Modeling Circuits (Jonscher, 1983)	31
4.1	Preparation of Barium Titanate and Strontium Titanate Powders	35
4.2	Pre-sintering graph of Barium Titanate and Strontium Titanate with their respective heating and cooling rates	37
4.3	Preparation of sample (Kaolinite + BT and Kaolinite + ST)	39
5.1	XRD Spectra for BT Samples	46
5.2	XRD Spectra for ST Samples	49
5.3	Cross Section SEM images of the BT Composite Samples; (a) BT 0%, (b) BT 10%, (c) BT 20%, (d) BT 30%, (e) BT 40%, (f) BT 50%, (g) BT 60%, (h) BT 70%, and (i) BT 80%	56 60
5.4	Cross Section SEM images of the BT Composite Samples; (a) ST 10%, (b) ST 20%, (c) ST 30%, (d) ST 40%, (e) ST 50%, (f) ST 60%, (g) ST 70%, and (h) ST 80%	61 65



6.1	Dielectric Permittivity of Pure Kaolinite Matrix	67
6.2	Dielectric Permittivity of 10% BT	68
6.3	Dielectric Permittivity of 20% BT	69
6.4	Dielectric Permittivity of 30% BT	70
6.5	Dielectric Permittivity of 40% BT	71
6.6	Dielectric Permittivity of 50% BT	72
6.7	Dielectric Permittivity of 60% BT	73
6.8	Dielectric Permittivity of 70% BT	74
6.9	Dielectric Permittivity of 80% BT	75
6.10	Dielectric Permittivity of 10% ST	76
6.11	Dielectric Permittivity of 20% ST	77
6.12	Dielectric Permittivity of 30% ST	78
6.13	Dielectric Permittivity of 40% ST	79
6.14	Dielectric Permittivity of 50% ST	80
6.15	Dielectric Permittivity of 60% ST	81
6.16	Dielectric Permittivity of 70% ST	82
6.17	Dielectric Permittivity of 80% ST	83
6.18	Temperature Variations of Relative Dielectric Permittivity for pure Kaolinite at 1 kHz and 1MHz	84
6.19	Temperature Variations of Relative Dielectric Permittivity for 10% BT at 1 kHz and 1MHz	85
6.20	Temperature Variations of Relative Dielectric Permittivity for 20% BT at 1 kHz and 1MHz	86
6.21	Temperature Variations of Relative Dielectric Permittivity for 30% BT at 1 kHz and 1MHz	87
6.22	Temperature Variations of Relative Dielectric Permittivity for 40% BT at 1 kHz and 1MHz	88
6.23	Temperature Variations of Relative Dielectric Permittivity for 50% BT at 1 kHz and 1MHz	89
6.24	Temperature Variations of Relative Dielectric Permittivity for 60% BT at 1 kHz and 1MHz	90
6.25	Temperature Variations of Relative Dielectric Permittivity for 70% BT at 1 kHz and 1MHz	91
6.26	Temperature Variations of Relative Dielectric Permittivity for 80% BT at 1 kHz and 1MHz	92
6.27	Temperature Variations of Relative Dielectric Permittivity for 10% ST at 1 kHz and 1MHz	93
6.28	Temperature Variations of Relative Dielectric Permittivity for 20% ST at 1 kHz and 1MHz	94
6.29	Temperature Variations of Relative Dielectric Permittivity for 30% ST at 1 kHz and 1MHz (Response for 30°C is reduced to fit the graph)	95
6.30	Temperature Variations of Relative Dielectric Permittivity for 40% ST at 1 kHz and 1MHz	96
6.31	Temperature Variations of Relative Dielectric Permittivity for 50% ST at 1 kHz and 1MHz	97
6.32	Temperature Variations of Relative Dielectric Permittivity for 60% ST at 1 kHz and 1MHz	98



6.33	Temperature Variations of Relative Dielectric Permittivity for 70% ST at 1 kHz and 1MHz	99
6.34	Temperature Variations of Relative Dielectric Permittivity for 80% ST at 1 kHz and 1MHz	100
6.35	Standard Deviations of Temperature Dependency for BT samples at 1 kHz and 1MHz (Maximum ratio = 1)	101
6.36	Standard Deviations of Temperature Dependency for ST samples at 1 kHz and 1MHz (Maximum ratio = 1)	102
6.37	Equivalent Circuit for pure Kaolinite Matrix	106
6.38	Equivalent Circuit for 10% BT	107
6.39	Equivalent Circuit for 20% BT	108
6.40	Equivalent Circuit for 30% BT	109
6.41	Equivalent Circuit for 40% BT	110
6.42	Equivalent Circuit for 50% BT	111
6.43	Equivalent Circuit for 60% BT	112
6.44	Equivalent Circuit for 70% BT	113
6.45	Equivalent Circuit for 80% BT	114
6.46	Fitted Dielectric Models and Experimental Data for Pure Kaolinite Matrix. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	115
6.47	Fitted Dielectric Models and Experimental Data for 10% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	116
6.48	Fitted Dielectric Models and Experimental Data for 20% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	117
6.49	Fitted Dielectric Models and Experimental Data for 30% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	118
6.50	Fitted Dielectric Models and Experimental Data for 40% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	119
6.51	Fitted Dielectric Models and Experimental Data for 50% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	120
6.52	Fitted Dielectric Models and Experimental Data for 60% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	121
6.53	Fitted Dielectric Models and Experimental Data for 70% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	122
6.54	Fitted Dielectric Models and Experimental Data for 80% BT Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	123
6.55	Equivalent Circuit for 10% ST Sample	124
6.56	Equivalent Circuit for 20% ST Sample	125
6.57	Equivalent Circuit for 30% ST Sample	126



6.58	Equivalent Circuit for 40% ST Sample	127
6.59	Equivalent Circuit for 50% ST Sample	128
6.60	Equivalent Circuit for 60% ST Sample	129
6.61	Equivalent Circuit for 70% ST Sample	130
6.62	Equivalent Circuit for 80% ST Sample	131
6.63	Fitted Dielectric Models and Experimental Data for 10% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	132
6.64	Fitted Dielectric Models and Experimental Data for 20% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	133
6.65	Fitted Dielectric Models and Experimental Data for 30% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	134
6.66	Fitted Dielectric Models and Experimental Data for 40% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	135
6.67	Fitted Dielectric Models and Experimental Data for 50% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	136
6.68	Fitted Dielectric Models and Experimental Data for 60% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	137
6.69	Fitted Dielectric Models and Experimental Data for 70% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	138
6.70	Fitted Dielectric Models and Experimental Data for 80% ST Sample a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, I) 400°C	139
6.71	Impedance Plots for Pure Kaolinite Matrix. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	142
6.72	Impedance Plots for 10% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	143
6.73	Impedance Plots for 20% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	144
6.74	Impedance Plots for 30% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	145
6.75	Impedance Plots for 40% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	146
6.76	Impedance Plots for 50% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	147
6.77	Impedance Plots for 60% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	148
6.78	Impedance Plots for 70% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	149
6.79	Impedance Plots for 80% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	150



6.80	Impedance Plots for 10% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	153
6.81	Impedance Plots for 20% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	154
6.82	Impedance Plots for 30% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	155
6.83	Impedance Plots for 40% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	156
6.84	Impedance Plots for 50% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	157
6.85	Impedance Plots for 60% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	158
6.86	Impedance Plots for 70% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	159
6.87	Impedance Plots for 80% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	160
6.88	Complex Dielectric Modulus Plot for Pure Kaolinite Matrix. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	163
6.89	Complex Dielectric Modulus Plot for 10% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	164
6.90	Complex Dielectric Modulus Plot for 20% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	165
6.91	Complex Dielectric Modulus Plot for 30% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	166
6.92	Complex Dielectric Modulus Plot for 40% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	167
6.93	Complex Dielectric Modulus Plot for 50% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	168
6.94	Complex Dielectric Modulus Plot for 60% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	169
6.95	Complex Dielectric Modulus Plot for 70% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	170
6.96	Complex Dielectric Modulus Plot for 80% BT. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	171
6.97	Complex Dielectric Modulus Plot for 10% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	174
6.98	Complex Dielectric Modulus Plot for 20% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	175
6.99	Complex Dielectric Modulus Plot for 30% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	176
6.100	Complex Dielectric Modulus Plot for 40% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	177
6.101	Complex Dielectric Modulus Plot for 50% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	178
6.102	Complex Dielectric Modulus Plot for 60% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	179



6.103	Complex Dielectric Modulus Plot for 70% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	180
6.104	Complex Dielectric Modulus Plot for 80% ST. a) 30°C, b) 50°C, c) 100°C, d) 150°C, e) 200°C, f) 250°C, g) 300°C, h) 350°C, i) 400°C	181
6.105	Relative Dielectric Permittivity ϵ_r' for BT Composites in Microwave Frequency	182
6.106	Relative Dielectric Loss ϵ_r'' for BT Composites in Microwave Frequency	183
6.107	Relative Dielectric Permittivity ϵ_r' for ST Composites in Microwave Frequency	183
6.108	Relative Dielectric Loss ϵ_r'' for ST Composites in Microwave Frequency	185
6.109	Ln DC Conductivity against 100/T for Pure Kaolinite Matrix	188
6.110	Ln DC Conductivity against 100/T for 10% BT	188
6.111	Ln DC Conductivity against 100/T for 20% BT	189
6.112	Ln DC Conductivity against 100/T for 30% BT	189
6.113	Ln DC Conductivity against 100/T for 40% BT	190
6.114	Ln DC Conductivity against 100/T for 50% BT	190
6.115	Ln DC Conductivity against 100/T for 60% BT	191
6.116	Ln DC Conductivity against 100/T for 70% BT	191
6.117	Ln DC Conductivity against 100/T for 80% BT	192
6.118	Ln DC Conductivity against 100/T for 10% ST	194
6.119	Ln DC Conductivity against 100/T for 20% ST	194
6.120	Ln DC Conductivity against 100/T for 30% ST	195
6.121	Ln DC Conductivity against 100/T for 40% ST	195
6.122	Ln DC Conductivity against 100/T for 50% ST	196
6.123	Ln DC Conductivity against 100/T for 60% ST	196
6.124	Ln DC Conductivity against 100/T for 70% ST	197
6.125	Ln DC Conductivity against 100/T for 80% ST	197

