



UNIVERSITI PUTRA MALAYSIA

**CLASSIFICATION OF TYPED CHARACTERS USING
BACKPROPAGATION NEURAL NETWORK**

SUBBIAH ALAMELU

FK 2001 2

**CLASSIFICATION OF TYPED CHARACTERS USING BACKPROPAGATION
NEURAL NETWORK**

By

SUBBIAH ALAMELU

**Thesis Submitted in the Partial Requirement for the Degree of Master of Science
in the Faculty of Engineering
Universiti Putra Malaysia**

September 2001



Dedicated to Family members and my sister's Family



Abstract of the thesis presented to the Senate of Universiti Putra Malaysia in the fulfilment of the requirement for the degree of Master of Science

CLASSIFICATION OF TYPED CHARACTER USING BACKPROPAGATION NEURAL NETWORK

By

SUBBIAH ALAMELU

September 2001

Chairman: Roslizah Ali, M.Sc.

Faculty: Engineering

This thesis concentrates on classification of typed characters using a neural network. Recognition of typed or printed characters using intelligent methods like neural network has found much application in the recent decades. The ability of moment invariants to represent characters independent of position, size and orientation have caused them to be proposed as pattern sensitive features in classification and recognition of these characters. In this research, uppercase English characters is represented by invariant features derived using functions of regular moments, namely Hu invariants. Moments up to the third order have been used for the recognition of these typed characters. A single layer perceptron artificial neural network trained by the backpropagation algorithm is used to classify these characters into their respective categories. Experimental study conducted with three different fonts commonly used in word processing applications shows good classification results. Some suggestions for further work in this area have also been presented.



Abstrak tesis yang diserahkan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

CLASSIFICATION OF TYPED CHARACTER USING BACKPROPAGATION NEURAL NETWORK

Oleh

SUBBIAH ALAMELU

September 2001

Pengerusi : Roslizah Ali, M.Sc.

Fakulti : Kejuruteraan

Tesis ini memberikan fokus kepada klasifikasi abjad yang ditaip dengan menggunakan rangkaian neural. Pengenalan abjad yang ditaip atau dicetak dengan menggunakan kaedah pintar seperti rangkaian neural banyak digunakan kebelakangan ini. Kebolehan invarian momen untuk mewakili abjad tanpa bergantung kepada kedudukan, saiz dan orientasi menyebabkan ia dianggap sebagai sensitif kepada corak dalam klasifikasi dan pengenalan abjad-abjad ini. Dalam kajian ini, abjad rumi hurufbesar diwakili oleh huruf invarian yang diterbitkan menggunakan fungsi 'Regular Momen' yang dinamakan invarian Hu. Momen sehingga ke tertib ketiga telah digunakan untuk pengenalan abjad abjad yang ditaip ini. Satu lapisan perseptron rangkaian neural buatan yang dilatih dengan algoritma backpropagation digunakan untuk mengklasifikasikan abjad-abjad ini ke dalam kategori masing-masing. Kajian yang dilakukan dengan menggunakan tiga bentuk huruf berlainan yang biasanya digunakan dalam pemproses perkataan telah menunjukkan keputusan klasifikasi yang baik. Beberapa cadangan untuk kajian lanjut dalam bidang ini juga telah di sertakan.



ACKNOWLEDGEMENTS

I am very grateful to my supervisor Puan Roslizah Ali for her invaluable guidance, advice and support during the entire course of my project. I also thank my supervisory committee members for their timely support and advice that helped me to complete the thesis successfully.

I sincerely thank my two sisters' families and my family members for their endless love, affection and moral support. I thank my friend Senthil who encouraged me to realize this work into a reality.

Lastly, I am indebted to God who gave me the necessary strength and endurance to survive in all the trials and tribulations throughout the project.



I certify that an Examination Committee met on 26th September 2001 to conduct the final examination of Subbiah Alamelu on her Master of Science thesis entitled "Classification of Typed Characters Using Backpropagation Neural Network" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

NOR KAMARIAH NOORDIN, M.Sc.

Department of Computer and Communication System Engineering,
Faculty of Engineering,
Universiti Putra Malaysia,
(Chairman)

ROSLIZAH ALI, M.Sc.

Department of Computer Communication System Engineering,
Faculty of Engineering,
Universiti Putra Malaysia,
(Member)

ABD RAHMAN RAMLI, Ph.D.

Department of Computer and Communication System Engineering,
Faculty of Engineering,
Universiti Putra Malaysia,
(Member)

WAN AZIZUN WAN ADNAN, M.Sc.

Department of Computer and Communication System Engineering,
Faculty of Engineering,
Universiti Putra Malaysia,
(Member)



AINI IDERIS, Ph.D.

Professor,
Dean of Graduate School,
Universiti Putra Malaysia

Date: 19 NOV 2001



This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science.



AINI IDERIS, Ph.D.
Professor,
Deputy Dean of Graduate School,
Universiti Putra Malaysia

Date: 10 JAN 2002

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

M. SP

SUBBIAH ALAMELU

Date: 18 NOV 2001



TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	iv
ACKNOWLEDGEMENTS	v
APPROVAL SHEETS	vi
DECLARATION FORM	viii
LIST OF TABLES	xi
LIST OF FIGURES	xii
LIST OF SYMBOLS AND ABBREVIATIONS	xiv
CHAPTER	
I INTRODUCTION	1
1.1 Classification of Typed Characters using BP Neural Network	1
1.2 Objectives of the Project	2
1.3 Organization of the Thesis	3
II BACKGROUND AND LITERATURE REVIEW	4
2.1 Literature review	4
2.2 Data Acquisition	5
2.3 Feature Extraction	6
2.3.1 Moments and Moment Invariants	6
2.3.2 Properties of Moments	8
2.3.3 Invariance to Translation	9
2.3.4 Invariance to Scaling	10
2.3.5 Invariance to Rotation	10
2.4 Image classification	11
2.5 Artificial Neural Network (ANN)	11
2.5.1 Biological Neural Network	12
2.5.2 Artificial Neural Network	13
2.5.3 ANN Architecture	14
2.5.4 Backpropagation Algorithm	15
2.6 Applications of Pattern Recognition of Characters	19
III METHODOLOGY	23
3.1 System Overview	23
3.2 Creation of characters	23



3.3	Calculation of Co-ordinates of 1's in the Characters	27
3.4	Moment Calculation	28
3.5	Neural Network Classifier	30
IV	EXPERIMENTAL RESULTS AND DISCUSSION	36
4.1	Experimental Results	36
4.2	Variation of number of Hidden Units	37
4.3	Variation of number of images for training	39
4.4	Discussion	43
V	CONCLUSIONS	48
5.1	Conclusion	48
5.2	Suggestions for Future Work	48
	REFERENCES	50
	APPENDICES	54
	VITA	79



LIST OF TABLES

Table	Page
2.1 Backpropagation algorithm	17
3.1 Moment files of few characters of TNR	28
3.2 Moment files of TNR font A	30
3.3 Type of text files used by the computer to fetch the character file	34
3.4 Extension format of files	34
3.5 Some of the file names of characters	35
4.1 Variation of number of hidden units Vs % classification rate for TNR and Copperplate gothic light fonts	37
4.2 Results of different number of input images for training for different hidden units	41
4.3 Variation of number of hidden units Vs % classification rate for 3 individual fonts	42
4.4 Variation of hidden units Vs % classification rate for 2 fonts combined	42



LIST OF FIGURES

Figure		Page
1.1	General flow of the Project	2
2.1	ANN as a "black box device"	12
2.2	A Biological neuron	12
2.3	A simple ANN- a Multilayer with a single hidden unit	14
2.4	A MultiLayer Perceptron	16
3.1	Flowchart of creation of typed uppercase English characters	25
3.2	Some alphabets from TNR font	25
3.3	Some alphabets of Arial font	26
3.4	Some alphabets of Copperplate gothic light font	26
3.5	Some of the rotated images	27
3.6	Flowchart of calculation of l's coordinates	28
3.7	Part of A1s70.pbm file	29
3.8	Flowchart of moment calculation	30
3.9	Part of the origin.inp file (A1s70.org)	31
3.10	ANN Classifier	32
3.11	BP Training process	33



4.1	Graphical representation of variation of number of hidden units Vs classification rate (%) for the Arial font used for training	38
4.2	Graphical representation of variation of number of hidden units Vs classification rate (%) for the TNR font used for training	38
4.3	Graphical representation of variation of number of hidden units Vs classification rate (%) for the CGL font used for training	38
4.4	Graphical representation of variation of number of hidden units Vs classification rate (%) for the all 3 fonts combined	39
4.5	Graphical results of different number of input images for training for different hidden units	41
4.6	The result file of nn40_12.res	46
4.6	The report file of nn40_12.rpt	47



LIST OF SYMBOLS AND ABBREVIATIONS

ANN	:	Artificial Neural Network
ASCII	:	American Standard Code Information Interchange
B	:	Bias input to the hidden unit
b	:	connection weights of hidden unit
BP	:	Backpropagation
CAIRO	:	Center for Artificial Intelligence and Robotics of Universiti Technology Malaysia
CCD	:	charge- coupled device
E _{min}	:	minimum error
f(x)	:	binary sigmoid function
f(Z(i/p))	:	continuous function
g(x)	:	continuous function
HMI	:	Hu Moment Invariants
IC	:	Image classification
MLP	:	Multi Layer Perceptron
NN	:	Neural Network
OCR	:	Optical character recognition
O _i	:	input neurons, i=1,2...n

O_j	:	hidden neurons, $j=1,2,\dots p$
O_k	:	output neurons, $k=1,2,\dots q$
PDP	:	Parallel Distributed Processing
PBM	:	Portable Bit map
TNR	:	Time New Roman
t_k	:	target output, $k=1,2,\dots q$
v_1, v_2	:	connection weights between hidden and output unit
w_1, w_2 and w_3	:	connection weights between input and hidden unit
W_{ji}	:	weight of the connection from O_i to O_j , $i=1,2,\dots n$ and $j=1,2,\dots p$
W_{kj}	:	weight of the connection from O_j to O_k , $k=1,2,\dots q$ and $j=1,2,\dots p$
$X_1, X_2,$ and X_3	:	Input neurons that form the input unit
x_1, x_2, x_3	:	Input activation level
Z	:	hidden layer neuron that forms the hidden unit
Y_1, Y_2	:	Output neurons that form the output unit
Y_1 (i/p), Y_2 (i/p)	:	input to neurons Y_1 and Y_2
Y_1 (o/p), Y_2 (o/p)	:	output to neurons Y_1, Y_2
y_1, y_2	:	output activation level
z	:	hidden layer activation level

$Z (i/p)$:	net weight to the neuron Z
$Z (o/p)$:	output of the neuron Z
θ_j	:	Bias on hidden unit $O_j, j=1,2,\dots p$
θ_k	:	Bias on output unit $O_k, k=1,2,\dots q$
η	:	Learning rate
α	:	Momentum term
δ_k, δ_j	:	error signal due to an error at the output unit O_k and from output layer to the hidden unit O_j
ΔW_{kj}	:	weight correction term for W_{kj}
ΔW_{ji}	:	weight correction term for W_{ji}

CHAPTER ONE

INTRODUCTION

1.1 Classification of Typed Characters using BP Neural Network

Automatic classifications of typed or printed characters have found very important applications in the recent years like Optical Character Recognition (OCR) for automatic postal code sorting, document processing and vehicle registration number identification system. In this work, the classification or recognition of typed English alphabets is concentrated.

A major difficulty in this work lies in classifying characters independent of position, size, and orientation. The invariant capabilities of functions of regular moments are utilized. A number of modifications are made to the original regular moments to make them completely invariant to position, size and orientation as suggested by Hu in 1961 [1].

In general, pattern recognition systems receive raw data, which are preprocessed and features are extracted and classified. The thesis starts with the stage of data set creation i.e. creating rotated, scaled, translated English alphabets in the computer. Next, we move on to invariant feature extraction using regular moment functions. The extracted features are then used in the classification stage where the alphabets are classified according to their categories with an artificial neural network (ANN). ANN is chosen due to its ability to incorporate “intelligence” in the classification process [2,3]. This is where the ANN comes in useful since it can improve



classification although with approximate invariance provided it is trained properly. A multilayer perceptron trained by the backpropagation algorithm is used in the thesis. This particular ANN is chosen since many researchers in the field of character recognition have opted for this type of ANN structure. Figure 1.1 shows the general flow of the methodology of the thesis.




Figure 1.1: General flow of the Project.

Some of the areas, which can benefit indirectly from the thesis project, are document processing like in the government departments and Optical Character Recognition (OCR), which is especially useful for converting scanned text image into documents like the archival of books and journals.

1.2 Objectives of the Project

The objective of the thesis is to classify the typed uppercase English alphabets that are scaled, translated and rotated using Backpropagation Neural Network. The characters are represented by Hu moment invariant features, a type of regular

moment that are invariant to scaling, rotation and translation. In addition using Hu moment invariants, the input size is reduced.

1.3 Organization of the Thesis

The thesis is divided into five chapters. Chapter One gives the introduction. Chapter Two provides a general background review to the topic. This chapter consists of four main sections. The first section introduces imaging systems. The next section discusses the regular moments with focus on Hu Moment Invariants (HMI). The mathematical foundations behind the moments and their development to achieve invariance to translation, scaling and rotation are also covered in this section. The third section involves the discussion on the ANN classifier. The final section of this chapter gives a brief discussion of some possible applications of pattern recognition.

Chapter Three describes the methodology followed in this thesis. Chapter Four discusses the experimental study and the results obtained from the proposed system. It also contains the results obtained from computer simulations using C language. Chapter Five concludes the thesis. In addition, it also comprises some suggestions of possible areas of improvements that can be done in the future.

CHAPTER TWO

BACKGROUND AND LITERATURE REVIEW

2.1 Literature Review

The use of moment based methods for pattern recognition has received considerable attention. The method of moments is used to recognize targets of interest, such as aircraft and ship identification. Moments and functions of moments have been utilized as pattern features in a number of applications to achieve invariant recognition of two-dimensional image patterns. Hu first introduced moment invariants in 1961, based on methods of algebraic invariants.

Conventional regular moment functions have been proposed as pattern sensitive features in image classification and recognition applications. But conventional regular moments remain no longer invariant when the image is scaled unequally in the x- and y- axis directions NN and a Fuzzy ARTMAP is used to classify these images into their respective classes [4]. Regular moment functions are very sensitive to noise especially the higher order moments. The new moment invariants [5] that solve the symmetrical problem faced with regular moment functions and in addition, it is also shown that these new moments are less sensitive to noise and digitization error than both of the regular moment functions derived by Hu.

The initial results of an initiative to construct a system for automatically identifying structural features and applying Standard Generalized Markup Language (SGML) tagging, based on the Text Encoding Initiative Document Type Definition (TEI



DTD), to text captured from print documents via optical character recognition (OCR) is been presented [6].

Classification of printed or digitized gujarati characters were done by using classifiers with regular and invariant moments [7]. Moment descriptors have been developed as features in pattern recognition since the moment method was first introduced. New moment features for Chinese character recognition is proposed. These provide significant improvements in terms of Chinese character recognition, especially for those characters that are very close in shape [8]. Automatic recognition of Arabic printed text using an artificial neural network is one of the work done in this area [9]. An efficient neural classifier is used to solve the handwritten Chinese character recognition problem as well as other pattern recognition problems of large scale. Experiments are conducted to evaluate the performance of the proposed approach and results are promising [10-12].

The three fundamental problems encountered in image classification are data acquisition, feature extraction and classification.

2.2 Data Acquisition

Data acquisition is a process of converting a scene into an array of numbers that can be manipulated by the computer. Sensor signals are 'digitized' i.e., converted to an array of numerical values, each value representing a small area of the scene. The digitized values are called picture elements or 'pixels' in short and are stored in computer memory for further processing [13].

2.3 Feature Extraction

Feature extraction is the representation of a character by a set of numerical features to remove redundancy from the data and reduce its dimensions. The selected feature set must possess much of the useful information (in the sense of discriminability) present in the original data.

Selection of "good" features is a crucial step in the process, since the next stages look only on these features and further action on them. Good features satisfy the requirements below:

- **Small interclass variance** - The numerical values of slightly different shapes with similar general characteristics should be closer.
- **Large interclass variance** - different class features should be quite different numerically.

In addition, a flexible recognition system must be able to recognize the images regardless of its size, orientation and location in the field of view. Functions of regular moment satisfy all these properties and therefore suitable to be used in the feature extraction stage.

2.3.1 Moments and moment invariant

The use of invariants in computer vision has been motivated by the studies. These studies indicate that invariants construction belongs to pre-attentive stage in human visual system. This could explain why we can so easily recognize objects in different illumination conditions, from different viewpoints and viewing distances. Although it is not directly known how the human visual system extracts and utilizes

invariants, the inevitable performance of the human visual system has been an adequate reason to attempt to use invariants in recognition applications.

Numerous papers have introduced invariants and reported their application to a variety of tasks [14-18]. Invariants have been used in character recognition, fingerprint identification, indexing image databases, texture characterization, and recognition under blur, to mention a few.

Character recognition is a classical pattern recognition task, which has become increasingly important along with the evolution of palm top computers. As an indication of popularity, a search for IEL (IEEE/IEE Electronic library) electronic library (years 1988-1999) would find over 500 papers that share the term character recognition in their titles. Additionally, character recognition often serves as a standard application against which pattern recognition methods are tested.

The term character recognition covers actually a wide range of totally different pattern recognition applications. The characters in question are the English letters A-Z and the task is to recognize their deformed versions using only the original character images.

Moment invariant functions are a set of non-linear functions based on geometrical moments, which are invariant to translation, scaling and orientation. Hu in 1961 was the first to introduce the moment invariants. He derived a set of invariants based on combinations of regular moments using algebraic invariants. Extensive work on these invariants were performed by Palaniappan et. al. [5,18] to classify typed

characters. Dudani *et al.* applied these invariants to aircraft identification. Wong and Hall used them to match radar images to optical images. Khotanzad and Hong [19] utilized them in texture classification.

The term "invariant" denotes an image or a character, which remains unchanged if that image or shape undergoes one or more combination of the following changes:

- Change in size (scale)
- Change in position (translation)
- Change in orientation (rotation)

In addition to being invariant to the above changes, using moment functions also reduces the number of inputs to the ANN, therefore speeding up the process of training the network, which allows a larger number of patterns for training. Moreover the problems with the computer memory allocations are also reduced. By using moment invariants the input features are fewer than the total image size.

2.3.2 Properties of Moments

The regular moments are defined as:

$$m_{pq} = \int_{-\alpha}^{\alpha} \int_{-\alpha}^{\alpha} x^p y^q f(x, y) dx dy, \quad (2.1)$$

Where m_{pq} is the two-dimensional moment of a continuous function $f(x, y)$. The order of the moment is $(p+q)$ for $p, q = 0, 1, 2, \dots$. For a two-dimensional digital $M \times M$ character, equation (2.1) becomes

$$m_{pq} = \sum_{x=0}^{M-1} \sum_{y=0}^{M-1} x^p y^q f(x, y) \quad \text{for } p, q = 0, 1, 2, \dots, M. \quad (2.2)$$