



**UNIVERSITI PUTRA MALAYSIA**

**PRETREATMENT OF SANITARY LANDFILL LEACHATE WITH A  
NATURAL POLYMER MORINGA OLEIFERA (KACANG KELOR)  
SEEDS EXTRACT AND HOLLOW FIBRE  
MICROFILTRATION MEMBRANE**

**EMAD SALIM MOHD. AMEEN**

**FK 2001 51**

**PRETREATMENT OF SANITARY LANDFILL LEACHATE WITH A  
NATURAL POLYMER MORINGA OLEIFERA (KACANG KELOR)  
SEEDS EXTRACT AND HOLLOW FIBRE  
MICROFILTRATION MEMBRANE**

**By**

**EMAD SALIM MOHD. AMEEN**

**Thesis Submitted Fulfilment of the Requirement for the Degree of  
Master of Science in the Faculty of Engineering  
Universiti Putra Malaysia**

**June 2001**



**This Work is Dedicated  
To  
My Parents, Sister and Brothers**

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

**PRETREATMENT OF SANITARY LANDFILL LEACHATE WITH A  
NATURAL POLYMER *MORINGA OLEIFERA* (KACANG KELOR)  
SEEDS EXTRACT AND HOLLOW FIBRE  
MICROFILTRATION MEMBRANE**

By

**EMAD SALIM MOHD. AMEEN**

**June 2001**

**Chairman: Ir. Dr. Suleyman A. Muyibi**

**Faculty: Engineering**

Due to population growing affluence, the fast development in industrial sector and improved standard of living, a huge volume of solid waste is being produced. The disposal of this numerous quantity of material in a sanitary landfill conveys with it an inherent potential for pollution of indigenous water resources. A major environmental impact resulting from the disposal of solid waste into a sanitary landfill occurs when water either from rainfall or groundwater passing through the refuse accumulates various contaminants including dissolved organic and inorganic components and decomposition products. This percolated liquid is called 'Leachate'. It is considered very harmful and toxic. Biological treatment is the most common system used to handle the leachate before discharge to water sources. Presence of toxic heavy metal in the leachate limit the activity of microorganisms, resulting in the decrease of the efficiency of the biological treatment to produce high effluent quality that will meet Malaysian Effluent Standard. Therefore a laboratory study using a bench scale model of three unit operations / processes of coagulation using

*Moringa oleifera* seeds as a natural coagulant, flocculation-sedimentation and micro-filtration was adopted to treat the leachate from Air Hitam Sanitary Landfill at Puchong, Selangor state of Malaysia. *Moringa oleifera* had achieved 43.75% Cadmium removal, 21.17% Total Chromium removal, 66.77% Lead removal, and 16% Iron removal. Also 55.42% of Total Suspended Solids, 9.98% of Total Dissolved Solids, and 24.16% of Volatile Suspended Solids were removed from the leachate after coagulation with an effective *Moringa oleifera* dosage. Micro-filtration hollow fibre membrane used decreased the Turbidity, Colour, Total Suspended Solids, Total Dissolved Solids, Volatile Suspended Solids, and Organic Matter in the leachate by 98.30%, 90.30%, 99.63%, 20.83%, 36.63%, and 21.87 respectively. Also it achieved 94% Cadmium removal, 29.81% Total Chromium removal, 73.2% Lead removal, and 18.28% Iron removal. Overall heavy metals removal from the leachate achieved by the bench scale model was 95.83% for Cadmium, 27% for Total Chromium, 79.9% for Lead, and 29.53% for Iron.

The results shown that *Moringa oleifera* is a promising natural polymer for removing heavy metals from the leachate, and may be used as a pre-treatment stage for biological treatment to eliminate a portion of the toxic heavy metals, which limits the activity of micro-organisms in the leachate.

Abstrak tesis yang dikemukakan kepada Senat Univerisiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Master Sains

**PRA-RAWATAN LEACHATE (AIR RESAPAN) DARI TAPAK PELUPUSAN  
SANITARI DENGAN MENGGUNAKAN EKSTRAK BIJI POLIMER  
*MORINGA OLEIFERA* (KACANG KELOR) DAN HOLLOW  
FIBER MEMBRAN MIKRO TURASAN**

Oleh

**EMAD SALIM MOHD. AMEEN**

**Jun 2001**

**Pengerusi: Ir. Dr. Suleyman A. Muyibi**

**Fakulti: Kejuruteraan**

Dengan bertambahnya populasi penduduk, juga pembangunan yang pesat di dalam sektor industri serta taraf hidup yang semakin baik, mengakibatkan lebih banyak isipadu sisa pepejal dihasilkan. Pembuangan bahan-bahan dengan kuantiti yang banyak di dalam kawalan pembersihan bahan buangan yang membawanya secara semulajadi sebagai potensi kepada pencemaran sumber air tulen. Kesan yang amat besar ke atas alam sekitar akibat daripada pembuangan sisa pepejal yang berlebihan ke tapak pelupusan sanitari berlaku apabila air samada dari jumlah hujan atau air dari bumi yang melewati melalui sisa yang mengandungi bahan organik terlarut dan juga komponen bukan organik dan hasil sisa yang reput. Cecair yang terhasil ini dikenali sebagai leachate (air resapan). Cecair ini sangat berbahaya dan bertoksik. Rawatan secara biologi adalah salah satu sistem yang selalu digunakan untuk mengendalikan leachate sebelum dikeluarkan ke sumber air. Kehadiran logam berat toksik di dalam leachate menghadkan aktiviti mikroorganisma, mengakibatkan pengurangan keupayaan rawatan secara biologi untuk mengeluarkan hasil efluen yang tinggi bagi mencapai Akta Piawaian Kualiti Alam Sekitar Malaysia. Oleh yang

demikian, ujian makmal dijalankan dengan menggunakan model bench scale daripada tiga unit operasi / proses pengentalan menggunakan biji *Moringa oleifera* sebagai bahan kental semulajadi, flocculation-sedimentation dan mikro turasan, yang telah digunakan sebagai rawatan kepada leachate dari Tapak Pelupusan Sanitari, Air Hitam, Puchong, Selangor. *Moringa oleifera* telah mencapai 43.7% penyingkiran Kadmium, 21.17% penyingkiran Kromium, 66.77% penyingkiran Plumbum, dan juga penyingkiran 16% Besi. Juga 55.42% daripada Jumlah Pepejal Terampai, 9.98% daripada Jumlah Pepejal Terlarut, dan 24.16% daripada Pepejal Terampai Terperuwap yang telah disingkirkan daripada leachate selepas proses pengentalan dengan dosej *Moringa oleifera* yang lebih berkesan. Membran mikro turasan Hollow Fiber digunakan untuk mengurangkan Turbiditi, Warna, Jumlah Pepejal Terampai, Jumlah Pepejal Terlarut, Pepejal Terampai Terperuwap dan Bahan Organik di dalam leachate masing-masing ialah 98.30%, 90.30%, 99.63%, 20.83%, 36.63%, dan 21.87%. Ia juga mencapai 94% penyingkiran Kadmium, 29.81% penyingkiran Kromium, 73.2% penyingkirin Plumbum, dan 18.28% penyingkiran Besi. Secara keseluruhan penyingkiran logam berat daripada leachate telah dicapai dengan menggunakan model bench scale iaitu 95.83% Kadmium, 27% Kromium, 79.9% Plumbum, dan 29.53% Besi.

Keputusan telah menunjukkan bahawa *Moringa oleifera* merupakan penghasil polimer semulajadi yang baik untuk menyingkirkan logam berat daripada leachate, dan kemungkinan akan digunakan sebagai peringkat pra-rawatan untuk rawatan secara biologi supaya dapat menghapuskan bahagian toksik logam berat, yang menghadkan aktiviti mikroorganisma di dalam leachate.

## ACKNOWLEDGEMENTS

The author wishes to express his profound appreciation and gratitude to the chairman of the supervisory committee, Dr. Suleyman A. Muyibi and to the members of the supervisory committee, Ass. Prof. Megat J. M. Mohd. Noor and Dr. Fakhru-Razi Ahmadun for their excellent supervision, valuable guidance, continuous encouragement, constructive suggestions and comments throughout the duration of this research study.

A deep thank to the personnel in the Graduate School Office UPM.

A deep thank to Mr. Mohd. Jan Mohd. Daud for his continuous assistance, to the technical staff in the Public Health Engineering Lab, Mr Zainuddin Ismail, and to all who have helped directly or indirectly.



## TABLE OF CONTENTS

		<b>Page</b>
DEDICATION .....		2
ABSTRACT .....		3
ABSTRAK .....		5
ACKNOWLEDGEMENTS .....		7
APPROVAL SHEETS .....		8
DECLARATION FORM .....		10
LIST OF TABLES .....		14
LIST OF FIGURES .....		18
LIST OF ABBREVIATIONS .....		20
<b>CHAPTER</b>		
I	INTRODUCTION .....	21
	Objectives .....	22
	Scope of Study .....	22
	Justification of The Study .....	23
	Potential Benefits .....	24
II	LITERATURE REVIEW .....	26
	Introduction .....	26
	Settling Characteristics of Suspensions .....	32
	Colloidal Suspensions .....	32
	Coagulation and Flocculation .....	35
	Polymers .....	38
	Natural Coagulants .....	40
	<i>Moringa oleifera</i> .....	40
	Filtration .....	42
	The Membrane Filtration Process (Cross-flow and dead-end flow) .....	43
	Cake Formation .....	45
	Preparation Stages for Filtration .....	46
	Precoat and Filter Aids .....	46
	Coagulation .....	46
	Temperature Control .....	47
	pH .....	47
	Membrane Filters .....	47
	Membrane Fouling .....	50
	Prompt Fouling .....	51
	Cumulative Fouling .....	51
	Destructive Fouling .....	51
	Fouling Control .....	52
	Application of Micro-filtration Hollow Fibre Membrane in Wastewater Treatment (Past Experiments) .....	53

	Water and Wastewater Treatment by <i>Moringa oleifera</i> (Past Experiments) .....	58
	Biological-Physical Treatment of Leachate (Past Experiments) .....	76
III	MATERIALS AND METHODS .....	89
	Materials .....	89
	Preparation of <i>Moringa oleifera</i> Seed Suspension .....	93
	Description of Air Hitam Leachate Treatment Plant, Sample Collection and Preservation .....	95
	Description of the Experimental Bench Scale Model .....	96
	Bench Scale Model Design .....	98
	Basic Data .....	98
	Design Calculation for Flux and Length of Membrane .....	98
	Characteristics of the Hollow Fibre Membrane .....	98
	Methods .....	99
	Description of the Experimental Jar Test Trials .....	99
	Preliminary Jar Test Trials .....	100
	Optimisation of Speed and Time for Rapid and Slow Mixing .....	102
	Effect of pH Adjustment on the Efficiency of <i>Moringa oleifera</i> in Leachate Treatment .....	103
	Optimisation of <i>Moringa oleifera</i> Stock Solution .....	104
	Experimental Runs of the Bench Scale Model (Batch Process) .....	105
	Experimental Runs of the Bench Scale Model (Continuous Process) .....	106
	Membrane Fouling Problems .....	107
IV	RESULTS AND DISCUSSION .....	108
	Introduction .....	108
	Experimental Jar Test Trials .....	110
	Preliminary Jar Test Trials .....	110
	Discussion of the Preliminary Jar Test Trials .....	113
	Summary of Findings .....	117
	Optimization of Speed and Time for Rapid and Slow Mixing .....	117
	Trials No. 1, 2, 3 .....	118
	Discussion of the Results .....	118
	Trials No. 4, 5, 6 .....	119
	Discussion of the Results .....	119
	Trials No. 7, 8, 9 .....	120
	Discussion of the Results .....	120
	Summary of Findings .....	121
	Effect of pH Adjustment on the Efficiency of <i>Moringa oleifera</i> in Leachate Treatment .....	122
	Summary of Findings .....	123
	Experimental Runs of the Bench Scale Model (Batch Process) .....	123
	Characteristics of Raw Leachate Samples .....	124

Control Jar Test No.1 .....	125
1 <sup>st</sup> Experimental Trial .....	126
Discussion of the Results .....	127
Control Jar Test No. 2 .....	133
2 <sup>nd</sup> Experimental Trial .....	134
Discussion of the Results .....	134
Control Jar Test No. 3 .....	140
3 <sup>rd</sup> Experimental Trial .....	142
Discussion of the Results .....	142
Control Jar Test No. 4 .....	149
4 <sup>th</sup> Experimental Trial .....	150
Discussion of the Results .....	150
Summary of Findings .....	156
Experimental Runs of the Bench Scale Model (Continuous Process) .....	157
Control Jar Test .....	158
Characteristics of Raw Leachate and the Effluent after Coagulation Process .....	159
Discussion of the Results .....	159
Summary of Findings .....	175
Comparison Between Gravity Settling and Coagulation with <i>Moringa oleifera</i> Using Jar Test .....	176
General Discussion .....	177
Mechanisms of <i>Moringa oleifera</i> with Contaminant Removal .....	177
Mechanisms of Micro-filtration with Contaminant Removal .....	180
Comparison Between the Results of this Study and the Previous Work .....	183
Comparison of the Results of this Study with the Effluent Characteristics of Air Hitam Sanitary Landfill Treatment Plant .....	185
The Benefit of this Study .....	187
 V CONCLUSION AND RECOMMENDATIONS .....	 189
Conclusion .....	189
Recommendations .....	192
 REFERENCES .....	 194
 APPENDICES .....	 200
Appendix A (Tables) .....	201
Appendix B (Lab Tests Required for This Research) .....	212
 VITA .....	 236

## LIST OF TABLES

Table		Page
1	Properties of Hazardous Waste Landfill Leachate .....	27
2	Elemental Analysis of <i>Moringa</i> (% by mass) .....	41
3	Percentage (by mass) of Proteins, Lipids and Sugars in <i>Moringa oleifera</i> .....	42
4	Classification of Pressure-driven Membrane Separation Processes .....	48
5	Characteristics of the Crude Water Extract of <i>Moringa oleifera</i> Seeds (Ndabigengesere and Narasiah, 1998) .....	73
6	Initial Performance Data of the BKK Leachate Treatment Plant .	79
7	Supernatant Quality After Activated Sludge Treatment (Gua and Chang, 1996) .....	83
8	Mean Values of Relevant Physical Parameters in Raw Leachate (Cossu <i>et al.</i> (1998) .....	85
9	Different Dosage of <i>Moringa oleifera</i> Seed Suspension, Used in Preliminary Jar Tests ..	101
10	Different Dosage of <i>Moringa oleifera</i> Seed Suspension, Used in Preliminary Jar Tests .....	101
11	Different <i>Moringa oleifera</i> Dosages Used in Jar Test to Determine the Optimum Speed and Time for Rapid and Slow Mixing and the effective Dosage .....	102
12	Varying Mixing Speed and Time Used in Jar Tests for the Optimisation of Rapid and Slow Mixing .....	103
13	Preliminary Jar Test to Investigate the Efficiency of <i>Moringa oleifera</i> to Remove Organic Matter from the Leachate (Trial no. 1) .....	111
14	Preliminary Jar Test to Investigate the Efficiency of <i>Moringa oleifera</i> to Remove Organic Matter from the Leachate (Trial no. 2) .....	111

15	Preliminary Jar Test to Investigate the Efficiency of <i>Moringa oleifera</i> to Remove Organic Matter from the Leachate (Trial no. 3) .....	112
16	Preliminary Jar Test to Investigate the Efficiency of <i>Moringa oleifera</i> to Remove Organic Matter from the Leachate (Trial no. 4) .....	112
17	Preliminary Jar Test to Investigate the Efficiency of <i>Moringa oleifera</i> to Remove Heavy Metals from the Leachate (Trial no. 5) .....	113
18	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 1) .....	201
19	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 2) .....	201
20	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 3) .....	202
21	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 4) .....	202
22	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 5) .....	203
23	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 6) .....	203
24	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 7) .....	204
25	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 8) .....	204
26	Cadmium Removal after Using Jar Test to Determine the Optimum Speed and Time for Slow and Rapid Mixing (Trial no. 9) .....	205
27	Cadmium and Chromium Removal After pH Adjustment of Raw Leachate (pH = 4) .....	205

28	Cadmium and Chromium Removal After pH Adjustment of Raw Leachate (pH = 6).....	206
29	Cadmium and Chromium Removal After pH Adjustment of Raw Leachate (pH = 9) .....	206
30	Cadmium and Chromium Removal After pH Adjustment of Raw Leachate (pH = 11).....	207
31	Cadmium Removal After Jar Test To Determine The Effective <i>Moringa oleifera</i> Dosage (Control jar test no. 1) .....	207
32	Raw Leachate Characteristics and Operating Parameters (1 <sup>st</sup> Sample) .....	126
33	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (1 <sup>st</sup> sample-1 <sup>st</sup> Run) .....	128
34	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (1 <sup>st</sup> sample-2 <sup>nd</sup> Run) .....	129
35	Cadmium Removal After Jar Test To Determine The Effective <i>Moringa oleifera</i> Dosage (Control jar test no. 2) .....	208
36	Raw Leachate Characteristics and Operating Parameters (2 <sup>nd</sup> Sample) .....	134
37	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (2 <sup>nd</sup> Sample-1 <sup>st</sup> Run) .....	136
38	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (2 <sup>nd</sup> Sample-2 <sup>nd</sup> Run) .....	137
39	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (2 <sup>nd</sup> Sample-3 <sup>rd</sup> Run) .....	138
40	Cadmium Removal After Jar Test To Determine The Effective <i>Moringa oleifera</i> Dosage (Control jar test no. 3) .....	208
41	Raw Leachate Characteristics and Operating Parameters (3 <sup>rd</sup> Sample) .....	142
42	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (3 <sup>rd</sup> Sample-1 <sup>st</sup> Run) .....	144
43	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (3 <sup>rd</sup> Sample-2 <sup>nd</sup> Run) .....	145
44	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (3 <sup>rd</sup> Sample-3 <sup>rd</sup> Run) .....	146

45	Cadmium Removal After Jar Test To Determine The Effective <i>Moringa oleifera</i> Dosage (Control jar test no. 4) .....	209
46	Raw Leachate Characteristics and Operating Parameters (4 <sup>th</sup> Sample) .....	150
47	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (4 <sup>th</sup> Sample-1 <sup>st</sup> Run) .....	153
48	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (4 <sup>th</sup> Sample-2 <sup>nd</sup> Run) .....	154
49	Analysis of Treated Leachate after Coagulation Process and after Micro-filtration Process (4 <sup>th</sup> Sample-3 <sup>rd</sup> Run) .....	155
50	Turbidity Removal after Jar Test to Determine the Effective Dosage of <i>Moringa oleifera</i> (Control jar test) .....	209
51	Characteristics of Raw Leachate and of the Effluent after Coagulation Process with <i>Moringa oleifera</i> . .....	159
52	Effluent Characteristics after Micro-filtration Process (1 <sup>st</sup> Day) ..	210
53	Effluent Characteristics after Micro-filtration Process (2 <sup>nd</sup> Day) .	210
54	Effluent Characteristics after Micro-filtration Process (3 <sup>rd</sup> Day) ..	211
55	Analysis of Raw Leachate and of the Leachate after Coagulation with <i>Moringa oleifera</i> dosage and after stirring .....	177
56	Leachate Effluent Characteristics of the Air Hitam Sanitary Landfill Leachate Treatment Plant (1 <sup>st</sup> sample, 2 <sup>nd</sup> sample) .....	186

## LIST OF FIGURES

Figure		Page
1	Microfiltration Hollow Fibre Membrane .....	90
2	Schematic Diagram of the Bench Scale Model for Leachate Treatment with <i>Moringa oleifera</i> Seeds and Micro-filtration Hollow Fibre Membrane .....	97
3	Residual Organic Matter in the Leachate after Coagulation with Different <i>Moringa oleifera</i> dosages (3 <sup>rd</sup> Preliminary Jar Test Trial) .....	114
4	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (5 <sup>th</sup> Preliminary Jar Test Trial) .....	115
5	Chromium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (5 <sup>th</sup> Preliminary Jar Test Trial) .....	116
6	Lead Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (5 <sup>th</sup> Preliminary Jar Test Trial) .....	116
7	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (1 <sup>st</sup> , 2 <sup>nd</sup> , 3 <sup>rd</sup> Jar Test Trials) .	119
8	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (4 <sup>th</sup> , 5 <sup>th</sup> , 6 <sup>th</sup> , Jar Test Trials) .	120
9	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (7 <sup>th</sup> , 8 <sup>th</sup> , 9 <sup>th</sup> , Jar Test Trials) .	121
10	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (control jar test no. 1) .....	125
11	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (control jar test no. 2) .....	133
12	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (control jar test no. 3) .....	141
13	Cadmium Removal from the leachate after Coagulation with Different <i>Moringa oleifera</i> Dosages (control jar test no. 4) .....	149



14	Variation of Suction Pressure with Time (1 <sup>st</sup> day operation) .....	160
15	Variation of Flux with Suction Pressure (1 <sup>st</sup> day operation) .....	161
16	Variation of Turbidity and Colour with Suction Pressure (1 <sup>st</sup> day operation) .....	162
17	Variation of TSS with Suction Pressure (1 <sup>st</sup> day operation) .....	163
18	Variation of TDS and VSS with Suction Pressure (1 <sup>st</sup> day operation) .....	164
19	Variation of Suction Pressure with Time (2 <sup>nd</sup> day operation) .....	166
20	Variation of Flux with Suction Pressure (2 <sup>nd</sup> day operation) .....	166
21	Variation of Turbidity and Colour with Suction Pressure (2 <sup>nd</sup> day operation) .....	167
22	Variation of TSS with Suction Pressure (2 <sup>nd</sup> day operation) .....	168
23	Variation of TDS and VSS with Suction Pressure (2 <sup>nd</sup> day operation) .....	169
24	Variation of Suction Pressure with Time (3 <sup>rd</sup> day operation) .....	171
25	Variation of Flux with Suction Pressure (3 <sup>rd</sup> day operation) .....	171
26	Variation of Turbidity and Colour with Suction Pressure (3 <sup>rd</sup> day operation) .....	172
27	Variation of TSS with Suction Pressure (3 <sup>rd</sup> day operation) .....	173
28	Variation of TDS and VSS with Suction Pressure (3 <sup>rd</sup> day operation) .....	174

**LIST OF ABBREVIATIONS**

TSS	Total Suspended Solids
TDS	Total Dissolved Solids
VSS	Volatile Suspended Solids
COD	Chemical Oxygen Demand
BOD	Biochemical Oxygen Demand
CFMF	Cross Flow Micro-filtration
Cd	Cadmium
Cr	Chromium
Pb	Lead
Fe	Iron
MF	Micro-filtration
UF	Ultra-filtration
NF	Nano-filtration
RO	Reverse Osmosis

## CHAPTER I

### INTRODUCTION

A considerable amount of solid waste is produced in most of the industrialized countries. Most of this waste is deposited in controlled sanitary landfills. As water percolates through solid domestic wastes, which have been deposited in a landfill, it dissolves organic and inorganic components and decomposition products, giving rise to a polluted liquid known as leachate. Two major sources of environmental pollution are typically associated with solid waste landfilling. These include surface and groundwater pollution from leachate formation and the production of volatile gases. Leachates are defined as hazardous wastewater. Their disposal is recognized as one of the most difficult tasks associated with the operation of landfills.

The composition of leachate is variable and depends on many factors, but leachates from relatively recent emplaced waste often contain high levels of COD, BOD and Ammoniacal nitrogen, in addition to high concentrations of metals such as Iron, Manganese, Calcium and sometimes Zinc (Robinson and Maris, 1979). Organic and inorganic matter present in the refuse and the products of decomposition can be leached by water, either rainfall or groundwater, passing through the wastes. This is a potential cause of serious water pollution. The containment and treatment of leachate may therefore be necessary, to avoid or minimize contamination of adjacent ground or surface water resources.

Lu *et al.* (1985) considered that in some cases it will not be economically feasible to eliminate leachate production from these refuse areas and treatment of the leachate will be necessary. Either chemical or biological treatment should be

effective. It is also possible that a combined treatment system in which the major treatment is done by chemical and physical means, with the polishing being done in lagoons or other biological processes being the most economical.

### Objectives

The objectives of this study were:

1. To investigate the treatability of landfill leachate, using *Moringa oleifera* (*Kacang Kelor*) seed for pretreatment of the leachate.
2. To evaluate the efficiency of the physical-chemical processes viz. coagulation-flocculation-sedimentation and filtration using hollow fiber micro-filtration membrane in the pretreatment of leachate.

### Scope of Study

A laboratory study using a bench scale model of three unit operations involved processes of coagulation-flocculation using *Moringa oleifera* (*Kacang Kelor* seeds as a natural coagulant), sedimentation and micro-filtration, have been adopted to treat Air Hitam sanitary landfill leachate. The leachate was analyzed before treatment, after coagulation process and after micro-filtration process, for the parameters: pH, Temperature, Turbidity, Alkalinity, Acidity, Total Suspended Solids (TSS), Total Dissolved Solids (TDS), Volatile Suspended Solids (VSS), Chemical Oxygen Demand (COD) using Standard Methods (APHA et al., 1998), and Heavy Metals viz. Cadmium (Cd), Chromium (C), Lead (Pb), and Iron (Fe) using

Inductively Coupled Plasma Mass Spectrometer. These heavy metals were chosen due to its serious impact on the environment as it was mentioned in the Indah Water report (1997) on Trenching (Environmental Protection-Monitoring of Completed Trench-fills). The results of the analyzed leachate before and after treatment for the parameters mentioned above have been compared to evaluate the success and efficiency of the laboratory study which included: bench scale model, coagulation-flocculation process with *Moringa oleifera* as a coagulant and filtration process using micro-filtration hollow fiber membrane.

Jar test have been used to determine the effective concentrations of *M. oleifera* and the optimum speed and time for rapid and slow mixing. It was also adopted to determine the effective dosage of *M. oleifera* seed suspension (stock solution) before each batch run.

### **Justification of the Study**

In an effort to minimize the environmental impacts resulting from leachate contamination, many treatment processes have been studied. Biological treatment (aerobic and anaerobic), physical treatment by Micro-filtration, Ultra-filtration, Nano-filtration and Reverse osmosis, also the combination of these two processes and other special methods have been adopted to treat landfill leachate. Each process has different cost and efficiency in treating the leachate to remove unacceptable parameters in it in order to minimize the environmental pollution. Biological methods are very effective for the treatment of landfill leachate with a high value of BOD, but are ineffective if recalcitrant organic compounds are present, so that they must be supported by physical-chemical process (Chiang et al.,

existence of heavy metals viz. Cadmium, Chromium, and Lead...etc in the leachate which are considered very toxic limits the activity of microorganisms and decrease the efficiency of the biological treatment. In this study the feasibility of using *Moringa oleifera* (the natural organic polymer available in Malaysia) as a coagulant, as a new and economic method, followed by filtration process using hollow fiber Micro-filtration membrane to pretreat the leachate for the parameters: pH, Turbidity, Acidity, Alkalinity, Chemical Oxygen Demand (COD), Total Suspended Solids (TSS), Total Dissolved Solids (TDS), Volatile Suspended Solids (VSS), and Heavy metals viz. Cadmium (Cd), Chromium (C), Lead (Pb), and Iron (Fe) were investigated.

### **Potential Benefits**

*Moringa oleifera* is considered as one of environmentally acceptable coagulant to be used in water and wastewater treatment instead of alum and synthetic polymers. In addition to this use, *Moringa oleifera* will provide many other benefits like: creation of new job opportunities, establishment of seed processing industries, while activated carbon can be produced from the husks and shell of *M. oleifera*. Oil extract from *Moringa oleifera* seeds can be used for edible or industrial, also the *M. oleifera* trees will provide protection to the soil from erosion and desertification.

Using of the natural coagulant '*Moringa oleifera*' in developing countries could effectively alleviate their economic situation and allow further extension of water supply to rural areas. Also it can be used as an efficient alternative to the chemical materials in the entire world.