



UNIVERSITI PUTRA MALAYSIA

FABRICATION OF A SEALED OFF CO₂ GAS LASER

SHAHID IQBAL

FK 2002 36

FABRICATION OF A SEALED OFF CO₂ GAS LASER

SHAHID IQBAL

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia
in Fulfilment of the Requirements for the Degree of Master of Science**

August 2002



DEDICATION

To my beloved parents, wife and sisters.



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of requirement for the degree of Master of Science

FABRICATION OF A SEALED OFF CO₂ GAS LASER

By

SHAHID IQBAL

August 2002

Chairman : Nasrullah Khan, Ph.D.

Faculty : Engineering

This study consists of two parts. In the first part a mathematical model for sealed-off CW CO₂ laser is developed. The developed model based on the four-temperature model and is developed by modifying the steady state CO₂ laser model presented by Scott et al. [28]. The equations relating the modes energy verses intra cavity optical intensity in equilibrium are used for modelling. An energy balance equation involving the terms of power loading, optical power removed and power loss in the form of the heat removed through the laser tube walls is derived. The variation in the output power as the power loading is varied is predicted using the model. The predicted results of output power respective to the power loading are found to show the similar response as found experimentally.

In second part a sealed off CO₂ laser is fabricated using custom-made air-cooled laser tube with internal mirror design and power supply. Both laser tube and power supply are placed in custom made wooden box. The box is especially built for housing the laser components. The cooling of the laser tube and power supply is

achieved by using four fans. An electronic circuitry to measure the laser tube temperature is developed. The laser is operated both in continuous wave mode as well as in pulse mode. A maximum power of 12.2 Watts is measured during continuous wave mode operation at a current of 14 mA. The output power is found to decrease with further increase in current. During pulsed operation, the energy of the optical pulses is found to be maximum at 100 Hz and a decrease in the pulse energy is detected with further increase in the pulse repetition rate.

The temperature is found to be the major factor effecting the laser power. Without fans the temperature of the laser tube is found to reach to 85°C in 10 minutes. The output power is also found to drop to zero at 85°C . However with running fans, the maximum temperature that laser tube wall could reach is found to be 55°C independent of the time. The laser power at 55°C is found to be 9 Watts.

The threshold and steady state voltage at the laser tube electrodes is also measured and is found to be 15640 volts and 8160 volts respectively. The CO_2 laser is useful for industrial drilling, welding, cutting and for air ionization or discharge applications. The purpose of this research is to design 14 Watt CO_2 gas laser for air ionisation and high voltage sphere gap triggering in the subsequent research.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

FABRIKASI PENUTUPAN LASER GAS CO₂

Oleh

SHAHID IQBAL

August 2002

Pengerusi : **Nasrullah Khan, Ph.D.**

Fakulti : **Kejuruteraan**

Kajian ini merangkumi dua peringkat utama. Pada peringkat pertama model matematik utk sealed off CW CO₂ telah dihasilkan. Model ini berasaskan kepada model 4 suhu disamping menggunakan beberapa persamaan yang menghubungkan mode tenaga berlawanan dengan keamatan optikal di dalam cavity. Persamaan keseimbangan tenaga yg melibatkan aspek kuasa muatan, pengasingan kuasa optikal dan kehilangan kuasa dalam bentuk haba melalui dinding tiub juga telah di dibuktikan . Perubahan pada kuasa yg dikeluarkan di samping kuasa muatan dpt ditentukan menggunakan model ini. Hasilnya, kuasa output yg dijangkakan berdasarkan kuasa mutan didapati menunjukkan kesamaan tidakbalas sebagaimana yg di dapati melalui ekseperimen.

Pada peringkat kedua, laser sealed off CO₂ telah dihasilkan menggunakan tiub laser khas yg mempunyai sistem penyejukan udara dengan binaan cermin dan sistem bekalan kuasa dalaman. Kedua-dua tiub laser dan sistem bekalan kuasa di letakkan di dalam kotak kayu khas. Kotak ini di buat khas sebagai pelindung kepada komponen laser. Sistem penyejukan utk tiub laser dan sistem bekalan kuasa dihasilkan

menggunakan empat buah kipas. Litar elektronik utk mengukur suhu tiub laser juga telah direka. Laser ini beroperasi dalam dua bentuk mode, mode gelombang berterusan iaitu pada penggunaan arus sebanyak 14 mA. Kuasa output pula didapati menurun dengan pertambahan kadar ulangan pulse.

Suhu adalah factor utama pada perubahan kuasa laser. Dalam keadaan dimana kipas tidak digunakan, suhu laser itu didapati menjangkau 85°C dalam masa 10 minit. Walaubagaimanapun, kuasa output jatuh kepada sifar pada suhu ini. Sebaliknya, dengan penggunaan kipas suhu maxima dinding tiub laser hanyalah menjangkau 55°C dan ianya tidak dipengaruhi oleh masa. Kuasa laser pada suhu ini adalah 9 Watt dan ianya juga tidak bergantung pada masa.

Voltan threshold pada elektrod tiub laser juga dapat diukur iaitu 15640 volt, manakala peringkat stabil voltan pula pada 8610 volt. Laser CO_2 berguna kepada industri penggerudian, pengimpalan dan pemotongan dan juga berguna kepada pengionan udara atau aplikasi-aplikasi menyahcas. Tujuan penyelidikan ini ialah untuk merekabentuk laser gas CO_2 untuk digunakan di dalam eksperimen pengionan udara dan voltan pencetus tinggi berjarak sfera di dalam penyelidikan seterusnya.

ACKNOWLEDGEMENTS

First of all, with the humble gratitude, I would like to express my thanks and deepest praise to Most Gracious and Most Merciful ALLAH who has given me all strength, faith, confidence and patience to complete this project.

It would be my pleasure to express my most sincere thanks to my supervisor Dr. Nasrullah Khan, and members of my supervisory committee Dr. Norman Mariun, Dr. Senan Mahmood Bashi, Dr Sayyed Javed Iqbal for their advice, understanding, support, criticism, guidance and co-operation in completing this project.

I would like to express my appreciation to the management and technical staff of Universiti Putra Malaysia for allowing me to conduct research on design of sealed off CO₂ laser.

Finally I would like to thanks the technical staff of the Electrical and Electronic Engineering Department and to all those who directly or indirectly helped me in completing this project.



TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENTS	vii
APPROVAL SHEETS	vii
DECLARATION FORM	x
LIST OF TABLES	xiii
LIST OF FIGURES	xiv
LIST OF ABBREVIATIONS	xvi
 CHAPTER	
1 INTRODUCTION	
1.1 Introduction	1
1.2 Aims and Objectives	3
1.3 Scope of Work	3
2 LITERATURE SURVEY	
2.1 Introduction	5
2.2 Literature Review on CO ₂ Laser	5
2.3 Theory of the Lasing Process in CO ₂ Gas	9
2.4 Factors Effecting the Scaling of the Laser Power and Methods to Overcome	14
2.4.1 Effect of Gas Temperature on the Laser Performance	15
2.4.2 Effect of Dissociation of CO ₂ on Laser Power	17
2.4.3 Effect of the Growth of instability of the Glow Discharge	18
2.5 Sealed-off CO ₂ Laser Design Procedure	23
3 METHDOLOGY	
3.1 Introduction	25
3.2 Development of Mathematical Model	26
3.3 Fabrication of Sealed-off CO ₂ Laser	35
3.3.1 Circuit at the Interface of Power Supply for CW Operation	38
3.3.2 Circuit at the Interface of Power Supply for Pulsed Operation	39
3.3.3 Description of Control Panel	40
3.3.4 Measurement of Tube Wall Temperature	42
3.3.5 Measurement of Threshold and Steady State Voltage	44
3.3.6 Calculation of Excitation Voltage	46
4 RESULTS AND DISCUSSIONS	
4.1 Introduction	50
4.2 Results of Mathematical Model	50
4.3 Experimental Results	52



4.3.1	Output Power as a Function of Discharge Current	54
4.3.2	Pulse Energy as Function of Pulse Repetition Rate	56
4.3.3	Power as Function of Wall Temperature	57
4.3.4	Wall Temperature as a Function of Time	58
4.3.5	Threshold and Steady State Voltage	59
4.3.6	Power Loss	61
4.3.7	Efficiency of the Laser	62
4.3.8	Determination of Pressure of Gas inside the Laser Tube	63
4.3.9	Laser Burn Patterns	64
4.4	Discussion of Results	67
4.4.1	Discussion of Results of Mathematical Modelling	67
4.4.2	Discussion of Experimental Results	68
5	CONCLUSIONS	
5.1	Conclusion	73
5.2	Future Work	75
	REFERENCES	76
	APPENDIX A	79
	APPENDIX B	84
	BIOGRAPHY OF THE AUTHOR	122

LIST OF TABLES

Table		Page
3.1	Characteristics of the sealed off CO ₂ laser used in the model	32
5.1	Results of the C++ Program for the gas temperature as a function of discharge current	80
5.2	Results of the C++ program for output power as function of discharge current	83

LIST OF FIGURES

Figure		Page
1.1	Stimulated emission process	1
2.1	The CO ₂ molecule	10
2.2	Symmetric vibration mode	10
2.3	Bending vibration mode	10
2.4	Asymmetric vibration mode	11
2.5	Rotation of CO ₂ molecule	12
2.6	Energy states of CO ₂ molecule	12
3.1	Energy level diagram of lasing mechanism in CO ₂ laser	26
3.2	Flow chart of algorithm used to calculate the laser output	31
3.3	Top view of fabricated sealed-off CO ₂ laser	35
3.4	Block diagram of power supply	36
3.5	Circuit diagram of 555 timer	37
3.6	Circuit used at the interface of power supply for CW operation	38
3.7	Circuit used at the interface of power supply for CW operation	39
3.8	Control panel	41
3.9	Circuit diagram of temperature measuring circuitry	42
3.10	Experimental diagram of temperature measuring circuitry	43
3.11	Circuit diagram of voltage divider	44
3.12	Experimental diagram of voltage divider circuit	45
3.13	The α/N vs. E/N for various ratios of gases in the mixture	48
3.14	The values of a/N vs. E/N for various ratios of gases in the mixture	48

4.1	Gas temperature T as a function of discharge current	51
4.2	Output power as a function of discharge current (model)	52
4.3	Power meter measuring laser power	53
4.4	Energy meter measuring energy of pulses	54
4.5	Output power as function of discharge current (Exp.)	55
4.6	Pulse energy as function of pulse repetition rate	56
4.7	Output power as a function of wall temperature	57
4.8	Wall temperature as function of time	58
4.9	Voltage across laser tube as a function of discharge current	60
4.10	Input Power as a function of discharge current	60
4.11	Power loss as a function of discharge current	61
4.12	Efficiency of laser as function of discharge current	62
4.13	Efficiency of laser as function of discharge current	63
4.14	Spot-size of laser beam on the black sheet of rubber	65
4.15	Burning effects of laser beam on paper	65
4.16	Burning of wood by laser beam	66

LIST OF ABBREVIATIONS

CW	Continuous Wave
CO ₂	Carbon Dioxide
FIR	Far – infrared
N_{CO_2}	Number of Molecules of Carbon
N_{N_2}	Number of Molecules of Nitrogen
X_i	Rate of Energy Transfer to the Four Vibrational modes of CO ₂
hf_i	Energies of Vibrational Modes of CO ₂
N_e	Number of Electrons per unit Volume
I_{ν}	Intra-cavity Optical Intensity
h	Planks Constant
f_L	Laser Frequency
τ_c	Life time of Photon inside the Cavity
W	Stimulated Emission on line Center
S	Spontaneous Emission
c	Velocity of Light
HV	High Voltage
VM	Voltmeter
N	Fresnel Number
LED	Light Emitting Diode
DPDT	Double Pole Double Through

CHAPTER 1

INTRODUCTION

1.1 Introduction

The word “laser” stands for “Light amplification by stimulated emission of radiation”. The stimulated emission is the process in which a photon of energy $h\nu$, stimulates the electron of an excited atom, to make transition from higher energy level to lower energy level, yielding another photon of same wavelength, same polarization, in phase and in same direction [1]. The process of stimulated emission is illustrated in the Figure 1.1.




Figure 1.1: Stimulated emission process

Many types of lasers have been designed since their discovery in 1961. However the CO_2 laser was first time discovered by Patel in Bell Laboratories in 1964 [1,2]. The CO_2 laser uses carbon dioxide gas as active medium and like other gas lasers it consumes electrical power and deliver less power in its radiation form at about $10.6\mu\text{m}$ wavelength. The difference between input and output power is waste heat that must be consumed. It operates by exchanging energy between low-lying vibrational-rotational energy level of CO_2 molecule. The radiation field transfers molecule being in the higher energy state into vibrational energy mode with lower-energy state. The difference of energy between upper and lower energy state is converted into far-infrared radiation [3].

The stimulated emission in CO₂ laser is different in the sense that it is due molecular transitions (vibrational-rotational transitions of molecules). The CO₂ laser has high efficiency and power output as compared to other lasers. The CO₂ lasers are of many types e.g. sealed off, flowing gas, axially excited, transversely excited etc. The maximum output power of a CO₂ laser is limited only by the damage threshold values of transmitting and reflecting optical components. A power output of 40kW in case CW CO₂ laser and 100MW from pulsed CO₂ laser has becomes possible with today's technology. The wavelength of CO₂ laser light is 10.6 μm , which falls in far-infrared region of the electromagnetic spectrum and is referred as thermal radiations. This radiation can be focused on a diameter of 10.6 μm . So the CO₂ laser makes it possible to concentrate high heat radiation on the exact point [2].

The CO₂ lasers have many applications depending upon the output power. The high power CO₂ lasers are widely used in industry for various purposes e.g. for material processing and for laser hardening. The CO₂ lasers are used for cutting and welding of metals. Steel plates of several centimetres thick can be cut very easily with 10kW CO₂ laser. The high-energy short pulses are used for the fusion confinement. It has many applications in medicine e.g. operation of high blood organs, reduction of bleeding and neurosurgery [3].

The earth atmosphere has low-loss optical window for the wavelength ranges between 8 μm to 14 μm [2]. Thus the high, efficiency, output power of CO₂ lasers and less retardation of earth atmosphere at 10.6 μm , makes the CO₂ laser most suitable for earth atmosphere ionisation experiment. Hence the design is carried out to use the laser for the

ionisation experiment. However the intended design of sealed off CO₂ laser has been selected and carried out, because of its more compactness, easy to operate, less expensive, and its ability to render more stable output spectrum and power than other CO₂ laser types.

1.2 Aims and Objectives

Aim of this project is to develop a mathematical model for sealed off CW CO₂ laser and fabricate CO₂ gas laser. The fabrication is aimed to get 14-Watt output power in CW mode and high-energy short duration pulses in the pulsed operational mode. The laser yields such an output power at 10.6 μm wavelength range. This wavelength falls in far-infrared (FIR) region of electromagnetic spectrum.

The main objective of this research are,

- to develop mathematical model for sealed off CO₂ gas laser
- to fabricate a sealed-off CO₂ laser and
- to operate the laser both in CW and pulsed mode.

1.3 Scope of Work

A mathematical model for the sealed off CW CO₂ laser is developed. The output power as a function of discharge current is determined for an arbitrary sealed off CW CO₂ laser. The maximum power of fabricated laser is measured to be 12.2 Watts at 14 mA. The further increase in current results in the decrease of power. The energy of output optical pulses is measure as a function of pulse repetition rate. The energy of the optical

pulses is found to be maximum at 100 Hz. The output power as function of wall temperature is determined and it is found that the power dropped to zero at $85^{\circ}C$. The threshold and steady state voltage is also measure. The burning and cutting effects of the laser beam have also been analysed. It has been found that the laser beam can cut very easily the half centimetre thick plastic and wooden sheets.

CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

This chapter comprises the literature review, theory of lasing action in CO₂ gas, the factors effecting the scaling of the output power and the methods to overcome. The design criteria of sealed off CO₂ has also been described briefly.

2.2 Literature Review on CO₂ Laser

The lasing action in CO₂ gas discharge was first time reported by Patel in 1964. The output power of this first reported CO₂ laser was around 1 MW. The laser was CW type [4]. However, within a year, CO₂ laser output powers had reached 10W, with an efficiency of 10%, while in 1967, CW operation at 500W was achieved. The subsequent substantial increase in CO₂ laser output power was made possible by cooling the active mixture convectively. A CO₂ laser with effective gas cooling by transverse circulation has produced an output power of around 1kW in 1969 [5]. There are many different types of design for CO₂ laser, which generally can be divided into three different groups on the basis of gas flowing as, fast flow, slow flow and sealed-off laser systems.

For a fast flow system, mass transfer or the flowing gas removes the heat produced by the electric discharge. The output power is largely dependent on the mass flow rate (amount of laser gas medium flow per second) of the gas, which can be as high as 120 to 150W of output power for each gram per second of mass flow [3]. The fast flow system can be divided into two major types as the fast-axial-flow and fast-transverse-flow system. The fast axial flow laser is the one in which the optical axes, current and gas flow are in the same direction. Since the discharge length for gas

molecule to traverse is relatively long in the axial direction, the gas flow velocity must be relatively high in order to minimize the transit time. A high flow velocity means high pressure-drop, which in turn requires more power for driving the gas pumping system. Roots type gas pumps are usually used in these lasers. Discharge currents are perpendicular to the optical axis. In this system, a lower flow velocity is needed remove the discharge heat. These fans used are simpler, consume less power and are more reliable when compared with the roots pumps used in fast axial flow lasers.

The slow flow types of lasers are reliable, robust, and easy to operate, and are produced by the industry in many versions with powers ranging from tens of watts to a kilowatt. The heat generated by the electrical discharge is removed by heat conduction through a water jacket surrounding the laser discharge tube. To continuously refresh the mixture, the gas is slowly pumped through the tube.

A sealed-off CO₂ laser offers convenient application because there are no vacuum pumps and gas bottles needed. The cooling of this laser is the same as in the conventional slow flow type by the enclosing water jackets. The output power of sealed-off CO₂ lasers can only increased be by increasing the discharge tube length. The one major problem associated with sealed-off CO₂ is their short operating lifetime, which is of the order of several thousand hours [3]. From the invention of the CO₂ laser onwards, research has been carried out to decrease the dissociation of the laser gas and its interactions with surface of the materials in order to find appropriate conditions for a sealed-off laser.

Witteman [6] designed a sealed off CO₂ laser by using ordinary materials for the tube and electrodes. A decrease in output power was found with passage of time. It was

supposed that either some of the gas components were absorbed or impurities released during the discharge. The materials used for the laser tube and electrodes and also the shape of the electrodes were found to have important role. Water vapours were added to the gas mixture, which reduced the problem to much extent.

Fahlen [7] designed a 5-W CW CO₂ laser and developed an expression for the small signal gain of the sealed off CO₂ laser given as

$$g_s = 0.012 - 0.0025D_T cm^{-1}$$

An increase in optimum output coupling (%) with the increase in single pass gain was found. The methods to calculate the output power of the sealed off CO₂ laser was described. Graphical representation of relation between the diffraction losses and the Fresnel Number was presented.

Macken et al. [8] designed a sealed off CO₂ laser with inner sides of the discharge tube walls coated by discontinuous gold film to reduce the degree of disassociation of CO₂ molecules. The gold film at walls was used to acts as catalyst to reform the decomposed CO₂. The gold was found to exhibits detectable catalytic action only in the presence of the discharge. With distributed gold film both sealed-off and flowing gas CO₂ lasers achieved 122 W/m output power. Therefore the output power of the laser was increased by 93 percent in case of sealed-off CO₂ laser and 47 percent in case of flowing gas CO₂ laser than identical laser without gold catalyst. The catalytic activity of the gold was found to decrease with the temperature.

Tripathi et al. [9] reported that that if the temperature of the “Au(5 atom %)/Fe₂O₃” catalyst is maintained to an optimized value then the absorption of the CO₂ is prevented in the bulk of the catalyst and result in a required level of CO oxidation

activity. An outer jacket with inner walls coated with the “Au(5 atom %)/Fe₂O₃” catalyst was used. The arrangement was made such so as to expose the gas mixture to catalyst surface, which in turn responsible for the recombination of the dissociation products. The performance of the laser was compared with the one without catalyst. Both of the lasers were operated with interruptions during nighttime and during weekends. It was found that the output power of the laser without catalyst dropped to zero in 17 days. While the initial output power of the laser with catalyst was found steady even after five months of operation.

According to Knapp [10] the use of silver-copper material for the cathode design reduces the gas consumption by sputter pumping through chemisorption and physisorption. The laser tube was constructed of Pyrex, fabricated on the Boulder Campus by the Master Glass Blower. The design was made to incorporate a laser bore nested in a water cooling jacket, with a feed through the water jacket so that the discharge can go to an external cathode and anode. The external electrodes lower than the axis of the laser tube bore were used to reduce the possibility that sputtering or oxidation products at the electrodes will contaminate the optics.

Nevdakh [11] optimised the output power of a sealed-off tunable cw CO₂. The dependences of the small-signal gain for the 10P(20) line and of the output powers for different transmittances of the cavity on the discharge current were determined. The distributed loss coefficient and the saturation parameter were measured. The saturation parameter increased continuously with increase in the discharge current, leading to a mismatch between the output power and gain maxima. It was established that the principal factor limiting the output power of cw electric-discharge CO₂ lasers is not an increase in the temperature of the active medium but the dissociation of CO₂