



UNIVERSITI PUTRA MALAYSIA

**ADAPTIVE QUALITY OF SERVICE CALL ADMISSION CONTROL
WITH USER MOBILITY PREDICTION FOR MULTIMEDIA TRAFFIC
OVER WIRELESS NETWORKS**

PRIHANDOKO

FK 2003 36



**ADAPTIVE QUALITY OF SERVICE CALL ADMISSION CONTROL
WITH USER MOBILITY PREDICTION FOR MULTIMEDIA TRAFFIC
OVER WIRELESS NETWORKS**

By

PRIHANDOKO

**Thesis Submitted to the School of Graduate Studies, Universiti Putra
Malaysia, in Fulfilment of the Requirement for the Degree of Doctor of
Philosophy**

April 2003



To All I Love

My Mother

Ibu Siti Maryatun

My Father

Bapak Katimin Hadisutopo

My Wife and the Mother of My Children

Desy Hertinsyana

My Lovely Children

Muhammad Umar Abdul Aziz

Khairina Azmi Zahidah

Muhammad Salman Alfarisi



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirements for the degree of Doctor of Philosophy

**ADAPTIVE QUALITY OF SERVICE CALL ADMISSION CONTROL
WITH USER MOBILITY PREDICTION FOR MULTIMEDIA TRAFFIC
OVER WIRELESS NETWORKS**

By

PRIHANDOKO

April 2003

Chairman: Professor Borhanuddin Mohd. Ali, Ph.D.

Faculty: Engineering

Multimedia traffic is expected to be supported in the next generation wireless networks. As in wireline networks, the wireless network must also be capable of providing guaranteed quality of service (QoS) over the lifetime of mobile connections. Some challenging problems that appear in multimedia wireless networks, such as user mobility and shortage of bandwidth, influence the QoS provisioning for the users.

In this thesis, we propose a new framework called Adaptive quality of service (AdQoS) to guarantee the QoS of multimedia traffic. The objectives that AdQoS framework tries to accomplish are minimum new call blocking and handoff dropping rates. The key feature of this framework is the bandwidth



reallocation scheme. This scheme is developed to control the bandwidth operation of ongoing connections when the system is overloaded.

The other key feature is the bandwidth reservation scheme incorporating a user mobility prediction to manage the QoS of the networks. Based on the mobility prediction, bandwidth is reserved to guarantee the uninterrupted handoff process. A comparison between existing user mobility prediction and the proposed scheme is also presented.

An integrated system, which combines the Bandwidth Allocation Level technique and the user mobility prediction, is also proposed. The proposed user mobility prediction algorithm integrates the Received Signal Strength (RSS) measurements for the mobile terminal's intra-cell movement and aggregate history of mobile terminals for inter-cell movement.

When compared with the conventional scheme proposed in the literature, the simulation results show that our proposed scheme reduces the new call blocking probabilities, the handoff dropping probabilities and reduces significantly the probability of terminating calls while still maintaining efficient bandwidth usage.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Doktor Falsafah

**KAWALAN PENERIMAAN PANGGILAN MUTU PERKHIDMATAN
ADAPTIF DENGAN TELAHAN KEMUDAHALIHAN PENGGUNA
UNTUK TRAFIK MULTIMEDIA DALAM RANGKAIAN WAYARLES**

By

PRIHANDOKO

April 2003

Pengerusi: Profesor Borhanuddin Mohd. Ali, Ph.D.

Faculti: Kejuruteraan

Trafik multimedia dijangkakan akan disokong ke dalam rangkaian wayarles generasi masa depan. Sebagaimana dalam rangkaian berwayar, rangkaian wayarles juga harus berupaya untuk menyediakan Kualiti Perkhidmatan terjamin sepanjang hayat penyambungan mudahalih. Beberapa masalah yang mencabar di dalam rangkaian berwayar seperti kemudahalihan pengguna dan kekurangan lebar jalur mempengaruhi penyediaan Kualiti Perkhidmatan kepada pengguna.

Dalam tesis ini, kami mencadangkan satu kerangka kerja yang baru, dinamakan Kualiti Perkhidmatan Boleh Adaptasi (AdQoS). Ia bertujuan

menjamin Kualiti Perkhidmatan bagi trafik multimedia yang secara umumnya diklasifikasikan sebagai trafik masa nyata dan bukan masa nyata.

Tujuan yang ingin dicapai oleh kerangka kerja AdQoS adalah mendapatkan halangan panggilan baru dan kadar pengguguran pindah-sel yang minimum. Ciri utama kerangka kerja ini ialah skim pengagihan semula lebar jalur. Skim ini dibangunkan untuk mengawal operasi lebar jalur panggilan semasa apabila sistem mengalami lebihan beban. Satu skim rizab lebar jalur yang mengambil kira ramalan kemudahalihan pengguna juga dicadangkan dalam tesis ini untuk menguruskan Kualiti Perkhidmatan rangkaian. Skim ramalan kemudahalihan dibangunkan berasaskan sejarah terkumpul pengguna mudahalih. Berasaskan ramalan kemudahalihan, lebar jalur dirizabkan untuk menjamin proses pemindahan-sel yang licin.

Bila dibandingkan dengan skim yang dicadangkan dalam literatur, keputusan simulasi kami menunjukkan bahawa skim yang dicadangkan berjaya mengurangkan kebarangkalian halangan panggilan baru dan kebarangkalian pengguguran pindah-sel. Ia juga berjaya mengurangkan secara jelas kebarangkalian penamatan panggilan disamping mengekalkan penggunaan lebar jalur yang efisien.

ACKNOWLEDGEMENTS

Praise is to ALLAH the Almighty, for his help and support during the course of life and moments of truth. Peace be upon our Prophet Muhammad SAW, his companions, his families and his followers.

I would like to thank my dear supervisor Professor Dr Borhanuddin Mohd Ali for his continual support and endless encouragement and patience, for his supervision that never ends. Without all that nothing would have been accomplished.

My very special thanks go to my dear brother, who is also my co-supervisor Dr Muhamed Hadi Habaebi for his very close help and guidance, his endless patient and his brilliant ideas; Dr. V Prakash for his encouragement and discussions; Dr Sabira Khatun for her support and discussions.

My special thanks also go to my colleagues at the wireless laboratory, especially to my brother Hisham Zuhudy bin Musthapa for his attentions and supports, my best friend Saravanan Kandasamy for his assistance and reviews, and others in the nice laboratory.



Special thanks also go to my closest friend and my teacher Ust Muhamad Ajir, and his family for their endless support and help; to my Indonesian brothers and friends in PPI-UPM; to my brothers in UKM, UM, UIA and UTM who have presented million of flowers during my life in this country; and also to all who have contributed directly or indirectly to this thesis.

Finally, very special thanks to my beloved wife, Desy Hertinsyana for always being in my side giving continuous support and spirit, my dear father and mother for all the prayers every single time, and all my brothers for all attentions and supports. Thanks to all of you.



I certify that an Examination Committee met on 2nd April 2003 to conduct the final examination of Prihandoko on his Doctor of Philosophy thesis entitled "Adaptive Quality of Service Call Admission Control with User Mobility Prediction for Multimedia Traffic over Wireless Networks" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded a relevant degree. Members of the Examination Committee are as follows:

Mohamad Khazani Abdullah, Ph.D.,
Associate Professor,
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Borhanuddin Mohd Ali, Ph.D.,
Professor,
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

M Hadi Habaebi, Ph.D.,
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

V. Prakash, Ph.D.,
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

Mahamod Ismail, Ph.D.,
Associate Professor,
Universiti Kebangsaan Malaysia
(Independent Examiner)



GULAM RUSUL RAHMAT ALI, Ph.D.
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 21 APR 2003

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory Committee are as follows:

Borhanuddin Mohd Ali, Ph.D.,
Professor,
Faculty of Engineering,
Universiti Putra Malaysia
(Chairman)

M Hadi Habaebi, Ph.D.,
Faculty of Engineering,
Universiti Putra Malaysia
(Member)

V. Prakash, Ph.D.,
Faculty of Engineering,
Universiti Putra Malaysia
(Member)




AINI IDERIS, Ph.D.,
Professor/Dean
School of Graduate Studies,
Universiti Putra Malaysia

Date: **12** JUN 2003

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or currently submitted for any other degree at UPM or other institutions.



PRIHANDOKO

Date: 17 April 2003

TABLE OF CONTENTS

	Page
DEDICATION.....	ii
ABSTRACT.....	iii
ABSTRAK.....	v
ACNOWLEDGEMENTS.....	vii
APPROVAL SHEET.....	ix
DECLARATION FORM.....	xi
TABLE OF CONTENTS	xii
LIST OF TABLES.....	xv
LIST OF FIGURES.....	xvi
LIST OF ABBREVIATIONS	xx
 CHAPTER	
1 QUALITY OF SERVICE (QoS) FOR MULTIMEDIA WIRELESS NETWORKS	1.1
1.1 Introduction	1.1
1.2 Motivations and Objectives	1.2
1.3 Contributions of this Thesis.....	1.5
1.4 Publications.....	1.8
1.5 The Structure of the Thesis.....	1.8
1.6 Summary.....	1.11
 2 REVIEW OF QoS IN MULTIMEDIA WIRELESS NETWORKS	2.1
2.1 Introduction	2.1
2.2 QoS in Multimedia Wireless Networks.....	2.2
2.3 Call Admission Control	2.6
2.4 Bandwidth Reservation.....	2.13
2.5 User Mobility Prediction.....	2.20
2.6 Comparative and Critical Review.....	2.28
2.7 Conclusion.....	2.34
 3 ADAPTIVE QOS SYSTEM MODEL.....	3.1
3.1 Network Model.....	3.1
3.2 AdQoS System Model.....	3.5
3.3 Mathematical Model	3.13



3.3	Simulation Model.....	3.16
4	ADAPTIVE FRAMEWORK OF CALL ADMISSION CONTROL AND BANDWIDTH RESERVATION SCHEMES	4.1
4.1	Introduction	4.1
4.2	Call Admission Control	4.2
4.2.1	CAC for CBR Traffic	4.3
4.2.2	CAC for Real-time VBR Traffic	4.6
4.2.3	CAC for Non Real-time Traffic	4.8
4.3	Bandwidth Reallocation Algorithm.....	4.9
4.3.1	Bandwidth Reallocation for Non Real-time Traffic	4.11
4.3.2	Bandwidth Reallocation for Real-time VBR Traffic	4.13
4.4	Mobile Location Control and Bandwidth Reservation	4.16
4.5	Simulation Results	4.18
4.6	Conclusion	4.30
5	USER MOBILITY PREDICTION TECHNIQUES FOR BANDWIDTH RESERVATION SCHEMES	5.1
5.1	Introduction	5.1
5.2	Utilizing Received Signal Strength Measurement for Mobility Prediction	5.4
5.3	Utilizing User Mobility Pattern for Mobility Prediction	5.7
5.3.1	UMP Algorithm	5.10
5.3.2	UMP Handoff Algorithm	5.16
5.4	Simulation Results.....	5.17
5.4.1	RSS Simulation Results	5.18
5.4.2	UMP Simulation Results	5.34
5.4.3	Comparison Between RSS and UMP	5.45
5.5	Discussion.....	5.50
5.6	Conclusion	5.53
6	INTEGRATED SYSTEM, AN INTEGRATION OF USER MOBILITY PREDICTION AND BAL SYSTEM (UMP, RSS, AND BAL)	6.1
6.1	Introduction	6.1
6.2	Integrated Scheme	6.3
6.3	Simulation Results	6.5
6.4	Conclusion	6.16
7	CONCLUSION AND FUTURE WORK	7.1
7.1	Conclusion	7.1



7.2	Future Work	7.5
REFERENCES.....		R.1
BIODATA OF THE AUTHOR.....		A.1



LIST OF TABLES

Table		Page
2.1	Table 2.1 A comparison of the CAC methods	2.29
2.2	Table 2.1 A comparison of the Bandwidth Reservation methods	2.31
2.3	Table 2.1 A comparison of the User Mobility Prediction methods	2.33
3.1	The characteristics of the traffic sources	3.19



LIST OF FIGURES

Figure	Page
1.1 The structure of this thesis	1.10
3.1 A typical Wireless ATM network	3.4
3.2 AdQoS Architecture	3.8
3.3 The partitions of bandwidth in a cell	3.11
3.4 A sample topology with 30 cells cluster	3.17
4.1 Bandwidth Allocation Level	4.10
4.2 Reservation and handoff region	4.17
4.3 Real-time New Call Blocking & Handoff Dropping Probability	4.23
4.4 Real-time New Call Blocking and Handoff Dropping Probability for Reservation Ratio = 100%	4.24
4.5 Non real-time New Call Blocking & Handoff Dropping Probability	4.25
4.6 Non real-time Forcibly Terminated Calls	4.27
4.7 Bandwidth Usage of the schemes	4.28
4.8 Handoff Dropping Probability with different reservation ratio	4.29
4.9 Bandwidth Usage for different BAL index	4.30
5.1 The scope of each UMP	5.9
5.2 Reservation to cells with frequency of $UMP_2 > 0$	5.11
5.3 Reservation to six neighbouring cells	5.12



5.4	Reservation to cells with frequency of $UMP5 > 0$	5.14
5.5	RSS-1 Scheme Prediction	5.18
5.6	RSS-3 Scheme Prediction	5.19
5.7	Bandwidth Usage for directional movement	5.20
5.8	Bandwidth Usage for random movement	5.21
5.9	New Call Blocking Probability for directional movement.....	5.22
5.10	New Call Blocking Probability for random movement	5.23
5.11	Handoff Call Dropping Probability for directional movement ..	5.24
5.12	Handoff Call Dropping Probability for random movement	5.25
5.13	Non real-time New Call Blocking Probability for directional movement	5.26
5.14	Non real-time Handoff Call Dropping Probability for directional movement	5.27
5.15	The accuracy of cell prediction for directional movement	5.28
5.16	The accuracy of cell prediction for random movement	5.28
5.17	Handoff Dropping Probability due to wrong cell prediction for directional movement	5.30
5.18	Handoff Dropping Probability due to wrong cell prediction for random movement	5.30
5.19	Handoff Dropping Probability due to insufficient bandwidth reservation for directional movement	5.32
5.20	Handoff Dropping Probability due to insufficient bandwidth for random movement	5.33
5.21	Bandwidth Usage for directional movement	5.36



5.22	Bandwidth Usage for random movement	5.36
5.23	Real-time Handoff Call Dropping Probability (HCDP) for directional movement	5.37
5.24	Real-time Handoff Call Dropping Probability (HCDP) for random movement	5.37
5.25	Real-time New Call Blocking Probability (NCBP) for directional movement	5.39
5.26	Real-time New Call Blocking Probability (NCBP) random movement	5.40
5.27	Non real-time New Call Blocking Probability (NCBP) for random movement	5.40
5.28	Non real-time Handoff Call Dropping Probability (HCDP) for random movement	5.41
5.29	The accuracy of cell prediction for random movement	5.42
5.30	Handoff drop due to wrong cell prediction	5.44
5.31	Handoff drop due to insufficient bandwidth allocation	5.44
5.32	Bandwidth Usage using UMP vs RSS	5.46
5.33	Real-time Handoff Call Dropping Probability (HCDP) using UMP vs RSS	5.48
5.34	Non real-time Handoff Call Dropping Probability (HCDP) using UMP vs RSS	5.48
5.35	Real-time New Call Blocking Probability (NCBP) using UMP vs RSS	5.49
5.36	Non real-time New Call Blocking Probability (NCBP) using UMP vs RSS	5.50
5.37	Critical positions of MT locations in the cell	5.53



6.1	Bandwidth Usage for random movement	6.7
6.2	Real-time Handoff Call Dropping Probability (HCDP) for directional movement	6.8
6.3	Real-time Handoff Call Dropping Probability (HCDP) for random movement	6.8
6.4	Real-time New Call Blocking Probability (NCBP) for directional movement	6.10
6.5	Real-time New Call Blocking Probability (NCBP) for random movement	6.10
6.6	The accuracy of cell prediction for random movement	6.12
6.7	Non real-time New Call Blocking Probability (NCBP) for random movement	6.14
6.8	Non real-time Handoff Call Dropping Probability (HCDP) for random movement	6.14



LIST OF ABBREVIATIONS

ABR	Available Bit Rate
AdQoS	Adaptive Quality of Service
ATM	Asynchronous Transfer Mode
BS	Base Station
CAC	Call Admission Control
CBR	Constant Bit Rate
HCDP	Handoff Call Dropping Probability
ITU-T	International Telecommunications Union Telecommunications
MT	Mobile Terminal
NCBP	New Call Blocking Probability
PCS	Personal Communications System
QoS	Quality of Service
RSS	Received Signal Strength
UBR	Unspecified Bit Rate
UMP	User Mobility Pattern
VBR	Variable Bit Rate
WATM	Wireless Asynchronous Transfer Mode



CHAPTER 1

QUALITY OF SERVICE FOR MULTIMEDIA WIRELESS NETWORK

1.1 Introduction

A broadband wireless network, such as wireless ATM, is capable of providing adequate multimedia service support for mobile users anywhere at any time. This implies that wireless networks should provide packet-based transport and bandwidth on demand, as well as support multimedia applications. However, the integration of wireline and wireless networks poses significant challenges. This is due to user mobility, limited radio frequency spectrum, radio channel impairment, and so on in the wireless segment [32], [37], [49], [50]. Hence, as what has been achieved in wireline networks, wireless network is also expected to have some mechanisms to provide Quality of Service (QoS) guarantee to the system.



1.2 Motivations and Objectives

Mobile users are expected to operate in an environment in which the quality of service (QoS) can vary significantly within and across different types of wireless networks, ranging from high speed indoor wireless LANs to very low speed outdoor wireless WANs. The continuous support of minimum QoS guarantees of multimedia applications poses a major challenge in heterogeneous wireless environments [15], [16]. Such a support requires the development of a flexible and adaptable network resource management framework. The framework must provide efficient mechanisms to bridge the heterogeneity gap between different types of networks, resolve potential QoS mismatch as mobile units move from one coverage to another, and dynamically accommodate applications with different QoS requirements in response to network performance degradation.

The existing proposals for QoS guarantee over multimedia wireless networks, show some drawbacks, such as inability to adapt to the fluctuating network resources, lack of mechanisms to predict future mobile terminal (MT) movements, and partitioning of the call admission control and bandwidth reservation scheme into two different entities that are isolated from each other.

In cellular networks, an important QoS parameter is the new call blocking probability (NCBP), i.e., the probability that a new connection request will be denied admission



into the network. A similar situation arises when an established connection in one cell attempts to move to a neighbouring cell. If the new cell cannot support the level of resources required by the connection, the handoff attempt is denied and the connection is dropped. The handoff call dropping probability (HCDDP) states the probability that an ongoing connection will be forcibly terminated during a handoff between cells due to the lack of resources in the target cell.

The NCBP and HCDDP together are used as a good indication of a network's quality of service. Another important parameter is the degree to which the network makes an effective use of bandwidth, due to its most limited resources. This parameter, referred to as the bandwidth usage, expresses the ratio of the amount of bandwidth used by various applications admitted into the network to the total bandwidth capacity of the network. Keeping the NCBP and HCDDP low while at the same time make use of bandwidth efficiently is one of the most challenging tasks facing wireless protocol designers [4-8].

In this thesis, call admission control and bandwidth reservation scheme have been developed to assure guaranteed QoS for heterogeneous traffic while maintaining efficient resource usage. To achieve this, a base station must strike a balance between the two conflicting requirements, allowing a maximum number of calls to be admitted into the network, and minimizing the handoff call-dropping rate.



In order to overcome the above problems, this thesis has defined its objectives as follows.

- (i) To study the approaches of current research in dealing with maintaining the QoS guarantees for multimedia wireless networks in the open literature.
- (ii) To design a system model that comprises call admission control and bandwidth reservation scheme that can manage QoS guarantees.
- (iii) To propose novel techniques to be incorporated into the system model to improve the overall network performance.
- (iv) To evaluate the performance of the proposed system in comparison with the current proposals.

In order to meet the objectives, we propose a framework called AdQoS (Adaptive QoS) system. The work conducted in this thesis differs from previous published work in the following ways:

- (i) The proposed system offers a comprehensive solution for multimedia wireless networks by combining the call admission control and the bandwidth reservation scheme into one framework to manage the QoS provisioning.
- (ii) The proposed system is developed to handle different types of traffic instead of only one as proposed in most of the current research.