



**UNIVERSITI PUTRA MALAYSIA**

**STRUCTURAL ASSESSMENT OF DISTRESSED BRIDGES AS AN  
AID TO DEVELOPMENT OF AN EXPERT SYSTEM**

**CHONG KAU PING**

**FK 2001 31**

**STRUCTURAL ASSESSMENT OF DISTRESSED BRIDGES AS AN AID  
TO DEVELOPMENT OF AN EXPERT SYSTEM**

**By**

**CHONG KAU PING**

**Thesis Submitted in Fulfilment of the Requirements for the Degree of  
Master of Science in the Faculty of Engineering  
Universiti Putra Malaysia**

**May 2001**



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirements for the degree of Master of Science.

**STRUCTURAL ASSESSMENT OF DISTRESSED BRIDGES AS AN  
AID TO DEVELOPMENT OF AN EXPERT SYSTEM**

**By**

**CHONG KAU PING**

**February 2001**

**Chairman: Associate Professor Waleed A. Malik Thanoon, Ph.D.**

**Faculty : Engineering**

The aim of this project is to develop a knowledge-base system to provide the rating system in analysing the effect of the various distresses on the structural behaviour of the deteriorated reinforced concrete beams bridge. This knowledge-base system is prepared for the “ Structural Assessment ” part and use in an overall Comprehensive Expert System for bridge conditional assessment and evaluate the residual life of the bridge. In addition, the knowledge-base system can also help the experts in making decision/rating during the early Condition Assessment stage.

In this investigation, the structural response of reinforced concrete beams bridge subjected to loss of concrete under JKR-SV loading is presented. The JKR-SV loading is adopted in this analysis because it provides the most critical load effect on the overall performance of the bridge. The problem most commonly found in bridges that are subjected to high chemical environment or overloaded i.e. cracking, crushing of concrete and spalling of the cover to the reinforcement has been simulated by loss of concrete. The study in this project focuses on the

effect of the location, length of losses and depth of the concrete loss on the structural behaviour of reinforced concrete beam. The effect of the bridge span, dimension of the beams and the amount of tension steel to the structural performance of the reinforced concrete beam under JKR-SV loading were also been taken into consideration.

Non-linear analysis using finite element method (FEM) had been carrying out to take care about the material non-linearity. In the analysis, 2 fields of consideration had been made: i) Yielding stresses of the bottom reinforcement at the location of maximum moment. ii) Vertical displacement,  $D_y$  at the mid-span of the beam. The yielding load has been adopted as a failure criteria and deflection at JKR-SV load were compared with a control beam having no defect.

Based on the results obtained from the finite element analysis, a new rating scheme had been proposed considering the serviceability and strength requirement of the beam. By using Visual basic, a knowledge-base system had been developed to expert opinions on the structural behaviour for the deteriorated reinforced concrete beam bridges. Finally, this user-friendly system is used to assist an engineer in analysing the effect of the variation distress on the load carrying capacity of the bridges.

Abstrak thesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains.

**PENILAIAN STRUKTUR KEATAS JAMBATAN YANG MENGALAMI  
KEROSAKAN DENGAN TUJUAN MEMBANGUNKAN SATU  
SISTEM PAKAR**

Oleh

**CHONG KAU PING**

**Februari 2001**

**Pengerusi : Profesor Madya Waleed A. Malik Thanoon, Ph.D.**

**Fakulti : Kejuruteraan**

Tujuan projek ini ialah untuk membangunkan satu sistem “knowledge-base”. Sistem ini menyediakan satu sistem kadar tersendiri dan ia digunakan untuk menganalisis kesan dari pelbagai kerosakan terhadap tabiat struktur yang dialami oleh jambatan jenis rasuk konkrit. Sistem “knowledge-base” ini disediakan untuk bahagian “penilaian komponen struktur” sahaja, “penilaian komponent struktur” ini merupakan sebahagian daripada keseluruhan “Expert System” yang disediakan untuk penilaian jambatan dan juga penaksiran baki hayat jambatan. Sebagai tambahan, system ini juga boleh membantu pakar-pakar dalam membuat penentuan terhadap penilaian keadaan jambatan pada peringkat awal.

Dalam penyelidikan ini, kesan tindakbalas tabiat struktur dalam jambatan jenis rasuk bertetulang terhadap kehilangan konkrit dibawah beban SV dikemukakan. Beban JKR-SV dipilih dalam analisis ini kerana ia memberi kesan beban yang paling kritikal terhadap keupayaan keseluruhan sesebuah jambatan. Masalah yang paling umum ditemui pada jambatan yang didedahkan kepada persekitaran

yang bersifat kimia tinggi atau lebih beban ialah seperti keretakan, letusan dan hancuran konkrit telah disimulasi sebagai kehilangan konkrit. Kajian dalam projek ini ditumpukan kepada kesan dari kedudukan, panjang dan kedalaman bagi kehilangan konkrit keatas tabiat struktur dalam rasuk bertetulang. Kesan yang disebabkan oleh panjang jambatan, dimensi rasuk dan juga jumlah besi tegangan yang digunakan keatas tabiat struktur rasuk dibawah beban SV juga diberi perhatian.

Analisis tak-linear telah dijalankan dengan bantuan “Finite Element method” untuk mengambil berat tentang sifat ketidak-linear bahan. Di dalam analisis ini, dua bidang telah diberi pertimbangan: i) ketegangan dalam besi tegang di lokasi mana lenturan maksimum. ii) perubahan kedudukan secara menegak,  $D_y$  di kedudukan tengah rasuk. Beban ketegangan di pilih sebagai kriteria kegagalan dan perubahan kedudukan semasa beban SV telah dibandingkan dengan rasuk kawalan yang tidak mengalami sebarang kerosakan.

Bedasar kepada keputusan yang diperolehi daripada analisis berdasarkan teori, kadar baru telah dicadang menimbangkan perkhidmatan and juga kekuatan yang diperlukan dalam rasuk. Dengan menggunakan “Visual basic”, satu “knowledge-base” system telah dibangunkan untuk membekal ulasan dari segi tabiat struktur kepada jambatan jenis rasuk yang mengalami kerosakan dengan berdasarkan tahap kerosakan mereka. Akhirnya, system mesra pengguna ini akan digunakan oleh para jurutera untuk menganalisa kesan terhadap variasi kerosakan keatas keupayaan menanggung beban oleh jambatan.

## **ACKNOWLEDGEMENTS**

The author would like to thank his supervisor, Assoc. Prof. Dr. Waleed A.Malik Thanoon for his kind supervision, guidance, suggestions and advices throughout the course of this project. A special note of grateful thanks and sincere appreciation also goes to his co-supervisors, Prof. D.N. Trikha and Dr. Mohd. Saleh Jaafar for their inspiring guidance and constructive comments towards this project.

The author would also like to express his gratitude to all colleagues and friends for their assistance and help throughout the duration of completing the project. While they are not named here, their contribution has been important as well. Nevertheless, the author would like to express his gratefulness to the research assistants Mr.Idib and Mr. Banonyone for contributing their ideas and advices upon the project.

Sincere appreciation is expressed to the IPRA Research Grant for establish the Bridge Research Group that provide generous facilities and supports for the completion of this project.

Finally, but no the least, a special thanks goes to author's parents, family members and beloved ones who consistently being patience, supports and encouraged during the duration of studying.

**CHONG KAU PING**



I certify that an Examination Committee met on 19<sup>th</sup> February 2001 to conduct the final examination of Chong Kau Ping on his Master of Science thesis entitled “Structural Assessment of Distressed Brigdes as an Aid to Development of an Expert System” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

**Suleyman Avenu Muyibi, Ph.D.**

Lecturer,  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**Waleed A. M. Thanoon, Ph.D.**

Associate Professor,  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**D. N. Trikha, Ph.D.**

Professor,  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**Mohd Saleh Jaafar, Ph.D.**

Lecturer/Head of Department,  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)



---

**AINI IDERIS, Ph.D.**

Professor  
Dean of Graduate School,  
Universiti Putra Malaysia

Date: 28 MAY 2001



This thesis has been submitted to the Senate of Universiti Putra Malaysia and was accepted as fulfilment of the requirements for the degree of Master of Science.



---

AINI IDERIS, Ph.D,  
Professor  
Dean of Graduate School,  
Universiti Putra Malaysia

Date: **14** JUN 2001

## DECLARATION

I hereby declare that the thesis is based on my original work expect for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

Signed



---

Candidate.

Name : CHONG KAU PING

Date : 28.5.2001

## TABLE OF CONTENTS

	<b>Page</b>
<b>ABSTRACT</b>	<b>ii</b>
<b>ABSTRAK</b>	<b>iv</b>
<b>ACKNOWLEDGEMENTS</b>	<b>vi</b>
<b>APPROVAL SHEETS</b>	<b>vii</b>
<b>DECLARATION FORM</b>	<b>ix</b>
<b>LIST OF TABLES</b>	<b>xiii</b>
<b>LIST OF FIGURES</b>	<b>xv</b>
<b>CHAPTER</b>	
<b>1 INTRODUCTION</b>	<b>1.1</b>
1.1 General	1.1
1.2 Scope and Objectives	1.3
1.3 Structural of The Thesis	1.4
<b>2 LITERATURE REVIEW</b>	<b>2.1</b>
2.1 Introduction	2.1
2.2 Deterioration of Reinforced Concrete	2.1
2.3 Load Capacity Evaluation of Existing Bridges.	2.5
2.3.1 Load Factor and Bridge Rating	2.7
2.3.2 Evaluation of Residual Strength and The Resistance Factor, $\phi$	2.9
2.3.3 Check for Serviceability of The Structure	2.13
2.3.4 Evaluation of Stress Resultants Due To Loading	2.13
2.4 Finite Element Modelling and Analysis	2.15
2.4.1 Concepts of Finite Element Analysis	2.15
2.4.2 Modelling Concepts of Reinforced Concrete Elements	2.16
2.4.3 Features Involved in Reinforced Concrete Modelling	2.16
2.4.4 Constitutive Modelling of Concrete	2.18
2.4.5 Modelling of Steel Reinforcement Bars	2.19
2.5 Expert System	
2.5.1 Basic Concept of A Knowledge-based Expert System	2.23
2.5.2 Expert System for Conditional Evaluation of Existing Structures	2.23
2.5.3 Structural Damage Assessment	2.29
<b>3 THEORETICAL CONSIDERATION</b>	<b>3.1</b>
3.1 Analytical Models of Concrete in 2D Problems	3.1
3.1.1 Behaviour of Concrete Under Biaxial Stress	3.1
3.1.2 Uniaxial Tension	3.4



3.2	Failure Criteria	3.5
3.2.1	The Strain Energy Density of Distortion Criterion	3.8
3.2.2	The Octahedral Shearing Stress Criterion	3.11
3.3	LUSAS Finite Element System	3.12
3.3.1	General	3.12
3.3.2	Pre-processing	3.12
3.3.3	Finite Element Solver	3.13
3.3.4	Results-processing	3.14
3.4	Theoretical Modelling by LUSAS FE System	3.14
3.4.1	Selection of LUSAS Element Types	3.14
3.4.2	Geometry	3.17
3.4.3	Model Attributes	3.17
3.4.3.1	Meshing a Model	3.18
3.4.3.2	Geometric Properties	3.19
3.4.3.3	Material Properties	3.19
3.4.3.4	Support Conditions	3.20
3.4.3.5	Loading	3.20
3.4.4	Running An Analysis	3.21
3.4.4.1	LUSAS Analysis Types	3.21
3.4.4.2	Non-linear Solution Procedures	3.22
<b>4</b>	<b>METHODOLOGY AND THEORETICAL ANALYSIS</b>	<b>4.1</b>
4.1	Introduction	4.1
4.2	Loading	4.2
4.2.1	Introduction	4.2
4.2.2	Long Term Axial Loads (LTAL)	4.3
4.2.3	Special Vehicle (SV) Loading	4.5
4.2.4	Span-wise Positions of Loads for Maximum Longitudinal Bending Moment	4.8
4.3	Theoretical Analysis of 2D Reinforced Beam Using F.E.M	4.9
4.3.1	Type of Element and Material model	4.9
4.3.2	Modelling of Steel Reinforcement Bars	4.9
4.3.3	Load and Boundary Conditions	4.10
4.3.4	Properties of Material	4.11
4.3.5	Bonding Between Steel Reinforcement and Concrete	4.12
4.3.6	Modelling Program	4.13
4.3.7	Model of Beams For Theoretical Analysis	4.13
4.3.8	Theoretical Model Procedure	4.17
4.4	Verification of Theoretical Analysis Results	4.18
4.4.1	Introduction	4.18
4.4.2	Experimental Program	4.18
4.4.3	Theoretical Analysis-Nonlinear F.E.M Approach	4.21
4.4.3.1	Theoretical Model Procedure	4.21
4.4.4	Results and Discussion	4.23
4.4.4.1	Ultimate Load	4.23
4.4.4.2	Residual Strength	4.23
4.4.4.3	Deflection	4.24

	4.4.4.4	Yield Load	4.26
	4.4.4.5	Steel Strains	4.27
	4.4.4.6	Conclusion	4.29
4.5		Comprehensive Expert System for Bridge Conditional Assessment	4.30
	4.5.1	Database System for “Structural Assessment” Part in an Overall Comprehensive Expert System	4.31
<b>5</b>		<b>RESULTS AND DISCUSSION</b>	<b>5.1</b>
	5.1	Introduction	5.1
	5.2	The Structural Response of Distressed Reinforced Concrete Beams	5.1
	5.3	The Effect of the Beam Span and Cross Section Dimension on The Structural Response of Distressed Beams	5.18
	5.4	Rating of Distressed Beam	5.30
	5.5	Knowledge-base System	5.32
	5.5.1	Introduction	5.32
	5.5.2	Types of Bridges in Knowledge-Base System	5.33
	5.5.3	Location and Structural Data	5.34
	5.5.4	Types of Distress/Intensity of Distress	5.35
	5.5.5	Rating/Overall Comments on Severity of Distress	5.37
	5.5.6	Recommendations and Summary of Distresses	5.39
	5.5.7	Print-out	5.40
<b>6</b>		<b>CONCLUSIONS &amp; RECOMMENDATIONS</b>	<b>6.1</b>
	6.1	Summary and Conclusion	6.1
	6.2	Knowledge-based Expert System	6.5
	6.2	Recommendation for Future Work	6.6
		<b>REFERENCES</b>	<b>R.1</b>
		<b>APPENDICES</b>	<b>A.1</b>
		<b>BIODATA OF AUTHOR</b>	<b>H.1</b>

## LIST OF TABLES

Table		Page
2.1	Variation of the residual strength, $P_d/P_u$ , with the extent of damage, D for beams with tensile and compressive reinforcement under two point loading	2.4
2.2	Resistance Factor, $\phi$ (AASHTO)	2.10
2.3	The fundamental rating by residual load carrying capacity (Matsui et. al., 1993)	2.12
2.4	Patterns of the loss of concrete cover (Matsui et. al., 1993)	2.12
2.5	Rating by the loss of concrete cover (Matsui et. al., 1993)	2.12
2.6	Rating by crack density of the slab (Matsui et. al., 1993)	2.12
3.1	Six different methods for using data obtained in the tension test	3.7
4.3.1	Model of 2D reinforced concrete beam with dimension 500x500mm	4.12
4.2	The different variables for each beam specimens in first series	4.16
4.3	The different variables for each beam specimens in second series	4.16
4.4	The different variables for each beam specimens in third series	4.16
4.5	The different variables for each beam specimens in fourth series	4.16
4.6	The different variables for each beam specimens in fifth series	4.17
4.7	The different variables for each beam specimens in sixth series	4.17
4.8	The location and depth of concrete loss in the experimental beam specimens	4.19
4.9	Model of 2-D reinforcement concrete beam	4.22
4.10	Comparison between experimental & theoretical analysis results of ultimate load	4.23
4.11	The coefficient of strength of each experimental and theoretical analysis beam specimens	4.24
4.12	The deflection for each experimental theoretical analysis beam specimen at load 80 kN	4.26

4.13	The deflection for each experimental & theoretical analysis beam specimen at yielding loads	4.26
4.14	Comparison of steel tensile strains at mid-span for 80 kN loading	4.28
5.1	Recommendation rating for deflection	5.34
5.2	Recommendation rating for yield load	5.34

## LIST OF FIGURES

<b>Figure</b>		<b>Page</b>
2.1	Small-scale test detail (Raof et.al., 1993)	2.3
2.2	Results for small-scale test (Raof et.al., 1993)	2.3
2.3	Effect of variations in depth of removal of concrete on residual Strength in Large-scale test (Raof et.al., 1993)	2.4
2.4	Effect of the location of damage along the beam in large-scale test (Raof et.al., 1993)	2.5
2.5	Discrete bar element	2.20
2.6	Embedded representation of reinforcement	2.21
2.7	Basic concept of an expert system function	2.23
2.8	Inference network of SPERIL-1 (Ishizuka et.al., 1980)	2.25
2.9	Sourced of soft and hard data for use in damage assessment analysis (Ross,et,al.1986)	2.30
2.10	Combining separate damage concepts into an overall damage assessment (savage, 1986)	2.31
2.11	Scale of classifying damage levels	2.32
2.12	Reducing expert opinion to lower levels of knowledge (savage, 1986)	2.33
2.13	Organizational structure of damage assessment code (savage, 1986)	2.34
2.14	Procedure for safety assessment of r.c.structure (H M Zain Al Abideen, 1998)	2.36
2.15a	Cracks or defects in solid slabs with drop beam (H M Zain Al Abideen, 1998)	2.37
2.15b	Cracks or defects in solid slabs with drop beam (contd)	2.38
2.15c	Cracks or defects in solid slabs with drop beam (contd)	2.39
3.1	Concrete under biaxial stress state in terms of ultimate uniaxial cylinder crushing strength	3.1



3.2	Biaxial stress state strength	3.2
3.3	Typical stress-strain diagram for ductile steel	3.5
3.4	Yield surface of cylinder	3.9
3.5	Incremental-iterative procedures in non-linear solution	3.23
3.6	Common forms of Modified Newton iteration	3.25
3.7	Constrained solution methods (arc-length)	3.27
3.8	Lusas Finite Element analysis	3.31
4.1	Plan of JKR-SV loading	4.6
4.2	The location of the wheel loads that provides maximum longitudinal moment	4.7
4.3	Location of SV loading	4.8
4.4	Location of SV loading	4.8
4.5	Loading and support conditions for 2D reinforced concrete beam	4.10
4.6	Beam specimen and reinforcement details	4.17
4.7	Beam specimen and testing set-up	4.20
4.8	Reinforcement details	4.20
4.9	Loading and support conditions in modelling of experimental tested beam	4.22
4.10	Variation of deflection with applied load at mid-span – control beam	4.25
4.11	Variation of deflection with applied load at mid-span – A1	4.25
4.12	Variation of deflection with applied load at mid-span – A2	4.25
4.13	Variation of steel tensile strain at mid-span with applied load – control beam	4.27
4.14	Variation of steel tensile strain at mid-span with applied load-A1	4.28
4.15	Variation of steel tensile strain at mid-span with applied load-A2	4.28

4.16	Overall Knowledge-base system for structural assessment of concrete beam bridges	4.31
4.17	Flow chart for knowledge-base system on bridge conditional assessment	4.32
4.18a	Data flow diagram for database system on bridge conditional assessment	4.33
4.18b	Data flow diagram for database system on bridge conditional assessment (contd)	4.34
5.1	Percentage of reduction in yield load for 3 different steel ratios beams with loss of concrete along bottom fiber of the beam	5.3
5.2	Percentage of increment in maximum deflection for 3 different steel ratios beams with loss of concrete along bottom fibre of the beam.	5.3
5.3	Percentage of reduction in yield load for 3 different steel ratios Beams with loss of concrete along top fiber of the beam	5.6
5.4	Percentage of increment in maximum deflection for 3 different steel ratios beams with loss of concrete along top fiber of the beam	5.6
5.5	Percentage of reduction in yield load for 3 different steel ratios beams with different length of lost concrete at bottom fiber of the beam	5.8
5.6	Percentage of increment in maximum deflection for 3 different steel ratios beams with the different length of lost concrete at bottom fiber of the beam	5.8
5.7	Percentage of reduction in yield load for 3 different steel ratios beams with different length of lost concrete at top fiber of the beam	5.11
5.8	Percentage of increment in maximum deflection for 3 different steel ratios beams with the different length of lost concrete at top fiber of the beam	5.11
5.9	Percentage of reduction in yield load for 3 different steel ratios beams with lost concrete from the bottom fiber of the beam along beam height	5.14
5.10	Percentage of increment in maximum deflection for 3 different steel ratios beams with lost concrete from the bottom fiber of the beam along beam height	5.14

5.11	Percentage of reduction in yield load for 3 different steel ratios beams with lost concrete from the top fiber of the beam along beam height	5.16
5.12	Percentage of increment in maximum deflection for 3 different steel ratios beams with lost concrete from the top fiber of the beam along beam height	5.17
5.13	Stress Variation diagram for loss of concrete from top fibre along the beam height	5.17
5.14	Percentage of increment in maximum deflection for beams 500x500 & 300x300mm with loss of concrete along bottom fiber of the beam	5.19
5.15	Percentage of increment in maximum deflection for beams 500x500 & 300x300mm with loss of concrete along top fiber of the beam	5.19
5.16	Percentage of increment in maximum deflection for beams 500x500 & 300x300mm with different length of lost concrete at bottom fiber of the beam	5.20
5.17	Percentage of increment in maximum deflection for beams 500x500 & 300x300mm with different length of lost concrete at top fiber of the beam	5.20
5.18	Percentage of increment in maximum deflection for beams 500x500 & 300x300mm with lost concrete from the bottom fiber of the beam along beam height	5.21
5.19	Percentage of increment in maximum deflection for beams 500x500 & 300x300mm with lost concrete from the top fiber of the beam along beam height	5.21
5.20	Percentage of reduction in yield load for beams 500x500 & 300x300mm with loss of concrete along bottom fiber of the beam	5.25
5.21	Percentage of reduction in yield load for beams 500x500 & 300x300mm with loss of concrete along top fiber of the beam	5.25
5.22	Percentage of reduction in yield load for beams 500x500 & 300x300mm with different length of lost concrete at bottom fiber of the beam	5.26
5.23	Percentage of reduction in yield load for beams 500x500 & 300x300mm with different length of lost concrete at top fiber of the beam	5.26

5.24	Percentage of reduction in yield load for beams 500x500 & 300x300mm with lost concrete from the bottom fiber of the beam along beam height	5.27
5.25	Percentage of reduction in yield load for beams 500x500 & 300x300mm with lost concrete from the top fiber of the beam along beam height	5.27
5.26	Types of bridges in knowledge-base system	5.33
5.27	Location data and structural data of the bridges	5.34
5.28	General type of distress that occurred in the bridge members	5.35
5.29	Location and intensity of the distresses	5.36
5.30	Rating/ Overall comments on the severity of distressed bridges	5.38
5.31	Recommendation and the summary of the distresses	5.39
5.32	Printout of the bridge data	5.40

## APPENDIXES

<b>Appendix</b>	<b>Title</b>	<b>Page</b>
APPENDIX A	Span-wise Positions of Loads For Maximum Longitudinal Bending Moment	A1
APPENDIX B	Geometry Feature for Theoretical Analysis Beams	B1
APPENDIX C	Summary of Theoretical Analysis Results	C1
APPENDIX D	Ultimate Moment Resistance of The Beam Sections	D1
APPENDIX E	Beam Specimen and Details For Beams 300x300mm	E1
APPENDIX F	Statistical Data From JKR Survey	F1
APPENDIX G	Maximum Permissible Reinforcement Ratio and Minimum Percentage of Reinforcement in Members	G1

# CHAPTER 1

## INTRODUCTION

### 1.1 General

Evaluation of deterioration, assessment of load carrying capacity and lifetime estimates of reinforced concrete bridges and the selection of counter measures for repairing damaged bridge are very important for the bridge authorities, as well as public. The assessment and repair works have been carried out by the bridge authorities by using their own inspection codes and based on their experiences.

Assessment of distress to a structure from any disturbance, natural or man made is a difficult process that requires significant human judgement. This process is complicated by the fact that the information needed to make a distress assessment with high confidence is incomplete and involves uncertainty.

Although there is objective information available to the expert in the form of test data, the question of damage assessment is strongly tied to expert judgement. Thus the quality of the assessment process is highly dependent on an expert's knowledge of the actual situation under study. With development of an expert system, information and its associated uncertainty can be used in an expert system, which attempts to reach conclusions and recommendations in regard to the conditional assessment about damaged bridge.

Currently, much research effort is being focused on the deterioration of reinforced concrete, particularly in the area of decay processes and repair



technology. This problem is most commonly found in bridges and parking garages that are subjected to high chemical environment. In attack of the chloride ion ( $\text{Cl}^-$ ) and reduction of the alkalinity of the concrete, this will allow oxidation of the reinforcement steel to take place. The oxidation process will lead to cracking of concrete and spalling of the cover to the reinforcement.

The loss of cover will also cause the steel corrosion due to chemical, climate and temperature attack. Debonding of reinforcing steel from its surrounding concrete is an immediate structural consequence of the corrosion of the embedded metal, subsequently leads to changing of flexural response of reinforced concrete elements.

Concrete and steel can only develop their full potentiality with respect to strength and stiffness when bond between them is perfect. The magnitude of steel tensile stress is increased in the region of bond loss, and it cannot be redistributed through bond stress. Therefore, all of the tensile stress is instantaneously directly into reinforcing steel, which results in stress concentration that demonstrated by premature yielding of the reinforcing steel.

The residual strength of the bridge will depend on the amount and location of the concrete loss from the beams and/or the slab. The problem is further aggravated in case of pre-stressed bridges where the losses of concrete affect the stresses in the pre-stressing wires.

## 1.2 Scope and Objectives

- a) To investigate theoretically the structural behaviour and performance of a distressed reinforced concrete beam subjected to the JKR-SV loading (bridge live load).
- b) To determine the effect of the location, length and depth of the concrete loss on the structural performance of reinforced concrete beam bridges having different amounts of tension reinforcement steel.
- c) To propose two different rating systems considering the serviceability (deflection) and yield status of the beam (yield load).
- d) To develop a knowledge-base system to analyse the effect of the concrete loss (spalling) on the structural capacity of the beam bridges.

To achieve the stated objectives, finite element method (FEM) has been used to analyse a number of reinforced concrete rectangular beams subjected to the JKR-SV loading. The analysis considers the non-linear characteristics of concrete and steel reinforcement with their failure mechanism. The structural response of the different beam models has been found in terms of the maximum deflection and yield load.



### 1.3 Structure of The Thesis

The thesis is divided into five chapters. A brief description of the content of these chapters is presented below:

The importance and the definition of the problem chosen for the present investigation have been highlighted in chapter 1 along with the scope of the study.

A literature survey of references in various areas relevant to this research is presented in chapter 2. The survey started with the deterioration of reinforced concrete elements in bridges, which explained the structural effect of the loss of concrete and exposure of the reinforcement to the reinforced concrete elements in bridges. The literature on methodology for evaluating the bridge capacity and the estimation of residual strength of the bridge are also presented. The survey also covered the modelling of distresses using finite element method and finally the application of expert system in safety assessment of existing structure also been included in this chapter of literature.

In chapter 3, the theoretical consideration in analytical models of concrete in 2 dimensional problems and the LUSAS finite Element System have been presented.

The methodology of theoretical analysis using LUSAS Finite Element System is discussed in chapter 4. It consists of selection of bridge live loads according to JKR Specification and modelling of the distressed reinforced concrete beams.

