

## **Voltammetric detection of potassium ferricyanide mediated by multi walled carbon nanotube titanium dioxide composite modified glassy carbon electrode.**

### **ABSTRACT**

The MWCNT/TiO<sub>2</sub> composite was homogeneously coated on the surface of GCE and applied in the electrochemical determination of 0.1 mM potassium ferricyanide in 0.1 M Na<sub>2</sub>HPO<sub>4</sub> (pH 8.5). The redox couple of potassium ferricyanide with current enhancements of 3.0-3.1 folds was obtained using the MWCNT/TiO<sub>2</sub>/GCE when compared with unmodified GCE. A linear calibration plot showed a correlation coefficient of 0.999, with detection limits of 48.6 μM (100 mV/s scan rate) and 1.1 μM (5 mV/s scan rate) in the concentration ranges of 0.01-0.2 mM of potassium ferricyanide. High sensitivity responses of 77.6 μA/mM for the anodic and of 68.9 μA/mM for the cathodic peak currents were also obtained with an excellent correlation coefficient of 0.999. Based on plot of peak current against peak potential, the zero-current potentials were obtained as =209 mV and =189 mV. Diffusion coefficient was found as 1.52x10<sup>-5</sup>cm<sup>2</sup>/s from chronocoulometry study. The effect of temperature study was carried at 10 oC – 80oC and activation energy obtained was 5.8-6 kJ/mol. The morphology of composite surface was examined by scanning electron microscopy.

**Keyword:** Multi-walled carbon nanotubes; Titanium dioxide; Modified electrode; Potassium ferricyanide; Cyclic voltammetry.