



UNIVERSITI PUTRA MALAYSIA

**FUZZY LOGIC-BASED HILL CLIMBING TECHNIQUE FOR
PHOTOVOLTAIC MAXIMUM POWER POINT TRACKING CONVERTER**

MOHAMMAD HOSSEIN TAGHVAEE

FK 2013 52



**FUZZY LOGIC-BASED HILL CLIMBING TECHNIQUE FOR
PHOTOVOLTAIC MAXIMUM POWER POINT TRACKING CONVERTER**

By
MOHAMMAD HOSSEIN TAGHVAEE



**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirement for the Degree of Master of Science**

May 2013

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment
of the requirement for the degree of Master of Science

**FUZZY LOGIC-BASED HILL CLIMBING TECHNIQUE FOR
PHOTOVOLTAIC MAXIMUM POWER POINT TRACKING CONVERTER**

By

MOHAMMAD HOSSEIN TAGHVAEE

May 2013

Chairman: Mohd Amran Mohd Radzi, PhD

Faculty: Engineering

Photovoltaic (PV) is a fast growing segment among renewable energy systems, whose development is owed to depleting fossil fuel and climate-changing environmental pollution. Its weaknesses, however, are its variable generation and non-linear characteristic due to its intermittent nature. These disadvantages contribute to issues of high per-kW installation cost and further low efficiency in PV generators.

An important consideration for achieving high efficiency in PV operation is to match the PV source and load impedance properly for any weather condition. The maximum extractable power from PV panels depends not only to the strength of the solar irradiation but also to the operating point of the energy conversion system. Maximum power point tracking (MPPT) is of paramount importance to the system as it not only maximizes system efficiency but also minimizes the return of investment in the PV installation. The hill climbing algorithm is the most common

method of MPPT due to its simplicity, ease of implementation, and good performance. However, it has issue of perturbation step size and trade off between faster response and steady-state oscillations.

Therefore, in this research work, the hill climbing search method has been modified based on fuzzy logic control for improvement of MPPT operation. This proposed MPPT algorithm is named as fuzzy logic based hill climbing. The proposed MPPT was implemented by fuzzifying the rules of hill climbing search method to reduce its drawbacks, and with this technique, not only the real maximum power point can be readily tracked, but also fast dynamic response and small steady state error can be achieved.

In this study, the characteristics of a PV module (Kyocera KD210GH) were mathematically modeled and simulated using MATLAB simulation tool. Then, the proposed MPPT algorithm and dc-dc boost converter were designed and developed in the same tool. Simulation results are presented to validate performance of the algorithm under different irradiation schemes, and to compare with the results obtained from conventional algorithm. Further experimental setup was carried out for comparative evaluation and the MPPT algorithm was implemented to performance verification of the algorithm by using digital signal processor (TMS320F28335).

The results obtained clearly confirm the proposed MPPT exhibits at least two times faster converging speed than the conventional MPPT in optimum configuration, and

the oscillations around maximum power point under steady state condition show improvement up to 75%.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai
memenuhi keperluan untuk ijazah Master Sains

**TEKNIK LOGIK KABUR BERASASKAN MENDAKI BUKIT BAGI
PENUKAR PENGESANAN TITIK KUASA MAKSIMUM FOTOVOLTA**

Oleh

MOHAMMAD HOSSEIN TAGHVAEE

Mei 2013

Pengerusi: Mohd Amran Mohd Radzi, PhD

Fakulti: Kejuruteraan

Fotovolta merupakan satu segmen yang berkembang pesat di kalangan sistem tenaga boleh diperbaharui, yang mana pembangunannya terjadi akibat semakin berkurangan bahan api fosil dan perubahan iklim kesan pencemaran alam sekitar. Kelemahannya, bagaimanapun, penjanaannya yang berubah-ubah dan ciri-ciri tidak linear yang disebabkan sifatnya yang tidak konsisten. Kelemahan ini menyumbang kepada isu-isu seperti kos pemasangan setiap kW yang tinggi dan seterusnya kecekapan yang rendah dalam penjana fotovolta.

Satu pertimbangan yang penting bagi mencapai kecekapan yang tinggi dalam operasi fotovolta adalah untuk memadankan sumber fotovolta dan galangan beban yang betul dalam sebarang keadaan cuaca. Kuasa maksimum yang diekstrak daripada panel fotovolta bergantung bukan sahaja kepada kekuatan sinaran suria tetapi juga kepada titik operasi sistem penukaran tenaga. Pengesanan titik kuasa maksimum adalah amat penting untuk sistem kerana ia bukan sahaja memaksimumkan kecekapan sistem tetapi juga meminimumkan pulangan pelaburan dalam pemasangan fotovolta. Algoritma mendaki bukit adalah kaedah paling biasa

pengesahan titik kuasa maksimum kerana sifatnya yang ringkas, mudah dilaksanakan, dan prestasi yang baik. Walau bagaimanapun, ia mempunyai isu berkaitan saiz langkah pengusikan dan pengimbangan antara tindak balas yang lebih cepat dan ayunan keadaan mantap.

Oleh yang demikian, dalam kerja penyelidikan ini, kaedah carian mendaki bukit telah diubahsuai berdasarkan kawalan logik kabur untuk memperbaiki operasi pengesahan titik kuasa maksimum. Algoritma pengesahan titik kuasa maksimum yang dicadangkan dinamakan sebagai logik kabur berdasarkan mendaki bukit. Pengesahan titik kuasa maksimum yang dicadangkan telah dilaksanakan dengan mengaburkan aturan kaedah carian mendaki bukit untuk mengurangkan kelemahannya, dan dengan teknik ini, bukan sahaja kuasa maksimum sebenar titik sedia dikesan, tetapi juga tindak balas dinamik yang pantas dan ralat kecil keadaan mantap boleh dicapai.

Dalam kaedah kerja ini, ciri-ciri modul fotovolta (Kyocera KD210GH) secara matematik dimodelkan dan disimulasi menggunakan perkakasan perisian MATLAB. Kemudian, algoritma pengesahan titik kuasa maksimum dan penukar dc-dc penggalak telah direka dan dibangunkan dalam perkakasan yang sama. Keputusan simulasi dibentangkan untuk mengesahkan prestasi algoritma dalam skim penyinaran berbeza, and membandingkannya dengan keputusan yang diperolehi daripada algoritma konvensional. Persediaan eksperimen berikutnya dilakukan bagi penilaian secara bandingan dan algoritma pengesahan titik kuasa maksimum dilaksanakan untuk mengesahkan prestasi algoritma dengan menggunakan pemproses isyarat digital (TMS320F28335).

Keputusan yang diperolehi secara jelas menunjukkan pengesanan titik kuasa maksimum yang dicadangkan mempamerkan kelajuan menumpu yang lebih cepat daripada pengesanan titik kuasa maksimum konvensional dalam konfigurasi optimum, dan ayunan di sekitar titik kuasa maksimum di bawah keadaan mantap menunjukkan peningkatan kepada 75%.



ACKNOWLEDGEMENTS

First of all, praise is to “Allah” the cherisher, and the sustainers of the world for giving me strengths, health and determination to complete this thesis. I wish to express my deep and sincere appreciation to my supervisor, Dr. Mohd Amran Mohd Radzi, for his valuable ideas and endless support during the course of my thesis and also for the direction and guidance provided during the entire period of my studies. My gratitude goes to the members of supervisory committee, Assoc. Prof. Dr. Mohammad Hamiruce Marhaban and Assoc. Prof. Dr. Hashim Hizam for their kind guidance.

Finally, I wish to thank the one dearest to me, my wife, who continues to astonish me with her patience, resilience and love.

I certify that an Examination Committee has met on **May,14th, 2013** to conduct the final examination of Mohammad Hossein Taghvaei on his thesis entitled "**FUZZY LOGIC BASED HILL CLIMBING TECHNIQUE FOR PHOTOVOLTAIC MAXIMUM POWER POINT TRACKING (MPPT) CONVERTER**" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the student be awarded the (Master of Science).

Members of the Examination Committee were as follows:

Nasri Sulaiman, PhD

Senior Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Chairman)

Samsul Bahari Mohd Noor, PhD

Associate Professor

Faculty of Engineering

Universiti Putra Malaysia

(Internal Examiner)

Ir. Raja Mohd Kamil Raja Ahmad, PhD

Senior Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Internal Examiner)

Nowshad Amin, PhD

Professor

Faculty of Engineering and Built Environment

Universiti Kebangsaan Malaysia

(External Examiner)

SEW HENG FONG, PhD

Professor and Deputy Dean

School of Graduate Studies

Universiti Putra Malaysia

Date:

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirements for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Mohd Amran Mohd Radzi, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Mohammad Hamiruce Marhaban, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Hashim Hizam, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

BUJANG BIN KIM HUAT, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

DECLARATION

I declare that the thesis is my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously, and is not concurrently, submitted for any other degree at Universiti Putra Malaysia or at any other institution.

MOHAMMAD HOSSEIN TAGHVAEE

Date: 14 May 2013



TABLE OF CONTENTS

	Page
ABSTRACT	ii
ABSTRAK	v
ACKNOWLEDGEMENTS	viii
APPROVAL	ix
DECLARATION	xi
LIST OF TABLES	xiv
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xviii
LIST OF SYMBOLS	xx
 CHAPTER	
1 INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	3
1.3 Aim and Objectives	5
1.4 Research Scope and Limitations	5
1.5 Thesis Organization	7
2 LITERATURE REVIEW	9
2.1 Introduction	9
2.2 Fundamental of Photovoltaic Energy Generation	10
2.2.1 Introduction	10
2.2.2 Photovoltaic Cell	11
2.2.3 The Ideal Model	12
2.2.4 The Non-Ideal Model	19
2.2.5 Expansion of Cells to Modules and Arrays	21
2.3 Maximum Power Point Tracking	23
2.3.1 Current-Voltage Curve and Maximum Power Point	23
2.3.2 Concept of Maximum Power Point Tracking	24
2.3.3 Maximum Power Point Tracking Algorithms	27
2.4 DC-DC Converters	43
2.4.1 Effect of Duty Cycle on Input Impedance of DC-DC Converters	45
2.5 Summary	47
3 METHODOLOGY	48
3.1 Introduction	48
3.2 Modeling of PV Module	49
3.3 Development of MPPT Algorithm	55
3.3.1 Conventional Hill Climbing Algorithm	56
3.3.2 Fuzzy Logic Based Hill Climbing Algorithm	57
3.4 Development and Operation Analysis of Boost Converter	65
3.5 Control of MPPT	70
3.6 Summary	71
4 SIMULATION AND EXPERIMENTAL RESULTS	73
4.1 Introduction	73

4.2	MATLAB/Simulink Model	73
4.3	Comparison of the Proposed Algorithm with Hill Climbing Algorithm	77
4.4	Dynamic Performance	82
4.5	Experimental Setup	88
4.5.1	Overall Hardware Schematic	88
4.6	Experimental Results	94
4.7	Conclusion	99
5	CONCLUSION AND FUTURE WORKS	100
5.1	Conclusion	100
5.2	Future Works	102
REFERENCES		104
LIST OF PUBLICATIONS		112