



**UNIVERSITI PUTRA MALAYSIA**

***OPTIMIZATION OF GLYCEROL FERMENTATION CONDITIONS  
FOR BIOETHANOL PRODUCTION BY LOCALLY ISOLATED  
Escherichia coli SS1***

**SHERIL NORLIANA BINTI SUHAIMI**

**FBSB 2013 43**



**OPTIMIZATION OF GLYCEROL FERMENTATION CONDITIONS FOR  
BIOETHANOL PRODUCTION BY LOCALLY ISOLATED  
*Escherichia coli* SS1**



By

**SHERIL NORLIANA BINTI SUHAIMI**

**Thesis submitted to the School of Graduate Studies, Universiti Putra  
Malaysia, in fulfilment of the requirements for the degree of Master of  
Science**

**October 2013**

## COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

**OPTIMIZATION OF GLYCEROL FERMENTATION CONDITIONS FOR  
BIOETHANOL PRODUCTION BY LOCALLY ISOLATED  
*Escherichia coli* SS1**

By

**SHERIL NORLIANA BINTI SUHAIMI**

October 2013

**Chairman : Phang Lai Yee, PhD**

**Faculty : Biotechnology and Biomolecular Sciences**

The increase of biodiesel production worldwide lead to the increase of glycerol present in environment. Bioconverting glycerol into various valuable products is one of glycerol's promising applications due to its high availability, lower costs and existence of many glycerol-utilizing microorganisms. Bioethanol is one of the interest products generated and its production is depending on the types of microorganism used and fermentation conditions. The effective screening procedure is needed to screen and isolate broad ranges of bacteria from environment. This study aims to isolate a suitable glycerol-fermenting microorganism and able to produce high ethanol production under optimized condition using crude glycerol as a substrate.

The screening method was modified based on enzymatic oxidation of ethanol which is correlated to reduction of 2,6-dichlorophenol-indophenol dye. The formation of decolourized zone was apparent using modified assay containing 5 ml/L of 0.05 M 2,6-dichlorophenol-indophenol, 10 ml of reaction mixture and 500  $\mu$ l/L of enzyme, respectively. In this study, several isolates were obtained showing capability in producing ethanol. The isolate namely *E. coli* SS1 was obtained after several screening processes. The fermentation of glycerol was carried out in batch fermentation using 120 mL serum bottle, incubated in 37°C with 120 rpm of agitation under anaerobic condition. The maximum ethanol production was achieved at 96 hours with 9.23 g/L, which is corresponding to the yield of 1 mol ethanol per mol glycerol and the productivity of 0.01 mol/molh<sup>-1</sup>. This isolate also showed a higher affinity to glycerol than glucose for bioethanol production.

Response surface methodology (RSM) employed to obtain optimized condition. Six parameters were subjected to two level factorial design which were initial pH, substrate concentration, sodium chloride content, trace element solution, incubation temperature and the concentration of yeast extract and tryptone. The results showed that only 4 parameters were identified as significant factors, i.e initial pH, substrate concentration, sodium chloride content and the mixture of yeast extract and tryptone. The effect of the significant variables was subsequently evaluated in Central Composite Design (CCD) to determine the optimum value for each variable. The optimized conditions obtained were at initial pH of 7.61, substrate concentration of 34.5 g/L, the mixture of yeast extract and tryptone at 6.42 g/L whereas salt content was identified as a non-significant parameter, with predicted maximum ethanol production of 17.05 g/L (1.0 mol/mol). A validation run was performed using crude glycerol based on optimized conditions and maximum ethanol obtained was  $15.72 \pm 0.26$  g/L with the yield of 1.0 mol/mol and productivity at  $0.01 \text{ mol/mol.h}^{-1}$  which was comparable to the predicted ethanol concentration. The isolated E.coli SS1 is a potential ethanol producer from glycerol, where the increased ethanol production is observed under optimized fermentation conditions. The crude glycerol also is feasible to be fermented using this isolate for comparable ethanol production using pure glycerol.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia  
sebagai memenuhi keperluan untuk Ijazah Master Sains

**PENGOPTIMUMAN KEADAAN FERMENTASI GLISEROL UNTUK  
PENGHASILAN ETANOL MENGGUNAKAN *Escherichia coli* SS1  
PENCILAN TEMPATAN**

Oleh

**SHERIL NORLIANA BINTI SUHAIMI**

Oktober 2013

**Pengerusi : Phang Lai Yee, PhD**

**Fakulti : Bioteknologi dan Sains Biomolekul**

Peningkatan pengeluaran biodiesel di seluruh dunia membawa kepada peningkatan gliserol dalam alam sekitar. Bio-penukaran gliserol kepada pelbagai produk yang bernilai tinggi adalah salah satu cara yang berkesan kerana kuantiti gliserol tersedia yang tinggi, kosnya yang rendah dan pelbagai mikroorganisma boleh menggunakan gliserol. Bioetanol merupakan salah satu produk yang boleh dihasilkan daripada bio-penukaran gliserol dan ia bergantung kepada jenis mikroorganisma yang digunakan dan keadaan fermentasi. Prosedur saringan yang berkesan diperlukan untuk menyaring dan mengasingkan bakteria dari persekitaran. Objektif kajian ini adalah untuk mendapatkan bakteria yang mampu menghasilkan etanol yang tinggi dalam keadaan yang optima dengan menggunakan gliserol.

Satu kaedah saringan telah diubahsuai berdasarkan pengoksidaan enzim etanol, yang berkait rapat dengan pemudaran pewarna 2,6-dichlorophenol-indophenol. Pembentukan zon warna yang pudar dapat dilihat dengan jelas apabila menggunakan komposisi yang telah diubahsuai iaitu 5 ml/L 0.05 M 2,6-dichlorophenol-indophenol, 10 ml campuran tindak balas dan 500 µl/L enzim. Dalam kajian ini, beberapa bakteria yang boleh menggunakan gliserol untuk penghasilan etanol telah diperolehi. Bacteria pencilan tempatan, *E. coli* SS1 telah diperolehi selepas beberapa proses saringan. Fermentasi gliserol telah dijalankan di dalam botol serum bersaiz 120 mL, dan difermentasi pada suhu 37°C dan emparan pada 120 rpm, di bawah keadaan anerobik. Pengeluaran etanol maksimum telah dicapai pada 96 jam dengan 9.23 g/L, iaitu bersamaan dgn 1 mol etanol bagi setiap mol gliserol dan kadar

pengeluaran pada  $0.01 \text{ mol/mol.jam}^{-1}$ . Bakteria pencilan tempatan ini juga menunjukkan keupayaan yang lebih tinggi menggunakan gliserol berbanding glukosa dalam penghasilan etanol.

Kaedah rangsangan permukaan (RSM) digunakan untuk mendapatkan keadaan optimum. Enam parameter telah tertakluk kepada dua tahap reka bentuk faktorial iaitu pH awal, kepekatan substrat, kandungan garam, kepekatan unsur surih, suhu fermentasi dan campuran ekstrak yis dan tryptone. Keputusan menunjukkan bahawa hanya 4 parameter telah dikenalpasti sebagai faktor penting, iaitu pH awal, kepekatan substrat, kandungan garam dan campuran ekstrak yis dan tryptone. Kesan pembolehubah penting (dua peringkat reka bentuk faktorial) pada pengeluaran etanol kemudiannya dinilai dalam Rekabentuk Pusat Komposit (CCD) untuk membangunkan model empirikal untuk menentukan nilai optimum setiap pemboleh ubah. Parameter yang optimum diperolehi pada pH awal 7.61, kepekatan substrat pada 34.5 g/L, campuran ekstrak yis dan tryptone pada 6.42 g/L manakala kandungan garam tidak menunjukkan parameter penting, dengan ramalan pengeluaran etanol maksimum pada 17.05 g/L. ( $1.0 \text{ mol/mol}$ ) Pengesahan dijalankan menggunakan gliserol mentah berdasarkan keadaan optimum dan etanol maksimum yang diperolehi adalah  $15.72 \pm 0.26 \text{ g/L}$  iaitu bersamaan dengan  $1.0 \text{ mol/mol}$  dan kadar pengeluaran pada  $0.01 \text{ mol/mol.h}^{-1}$  setanding dengan kepekatan etanol diramalkan. Bakteria *E.coli* SS1 pencilan tempatan ini adalah pengeluar etanol yang berpotensi dari gliserol, di mana pengeluaran etanol meningkat di bawah keadaan fermentasi yang optimum. Dengan menggunakan bakteria ini juga, gliserol mentah juga dapat difermentasi untuk penghasilan etanol yang setanding dengan gliserol tulen.

## ACKNOWLEDGEMENTS

First and foremost, I am very grateful to Allah S.W.T with His permission and Blessing, I have completed my master project entitled “Bioethanol production from crude glycerol by locally isolated *Escherichia coli* SS1”. I wish to express my sincere gratitude and whole-hearted appreciation to my supervisor, Dr Phang Lai Yee for her helps, guidance, suggestions and advices throughout my study for this master project. I also would like to thank to my co-supervisors, Prof Dr Suraini Abd Aziz, Prof Yoshihito Shirai (Kyutech) and Dr Minato Wakisaka (Kyutech) for their guidance, encouragement and support. I gratefully acknowledge Dr Toshinari Maeda (Kyutech) who provide assistance and advice during my attachment in Kyutech.

A special thank to all laboratory members in Biomass Technology Center, MTDC, UPM, laboratory in Biotech 3, friends, coursemate, post-graduate students and all persons involved during my study, for their endless encouragement, guidance and supports. My deepest appreciation for my father (En Suhaimi Nordin), my mother (Pn Anita Kamaludin), all my sisters and most importantly my husband (En Mohd Ashwariey) and my daughter (Mya Zaara Medina) for their sacrifice and endless support throughout these years.



I certify that a Thesis Examination Committee has met on 24 October 2013 to conduct the final examination of Sheril Norliana bt Suhaimi on her thesis entitled "Optimization of Glycerol Fermentation Conditions for Bioethanol Production by Locally Isolated *Escherichia coli* SS1" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

**Ho Chai Ling, PhD**

Associate Professor  
Faculty of Biotechnology and Biomolecular Sciences  
Universiti Putra Malaysia  
(Chairman)

**Norhafizah binti Abdullah, PhD**

Associate Professor  
Faculty of Agriculture  
Universiti Putra Malaysia  
(Internal Examiner)

**Rosfarizan binti Mohamad, PhD**

Associate Professor  
Faculty of Biotechnology and Biomolecular Sciences  
Universiti Putra Malaysia  
(Internal Examiner)

**Jamaliah binti Md Jahim, PhD**

Associate Professor  
Universiti Kebangsaan Malaysia  
Malaysia  
(External Examiner)



**NORITAH OMAR, PhD**  
Associate Professor and Deputy Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date: 21 January 2013

This thesis submitted to the Senate of Universiti Putra Malaysia and has been accepted as the fulfilment of the requirement for the degree of Master of Science.

The members of the Supervisory Committee are as follows:

**Phang Lai Yee, PhD**

Senior Lecturer,  
Faculty of Biotechnology and Biomolecular Sciences  
Universiti Putra Malaysia  
(Chairman)

**Suraini Abd. Aziz, PhD**

Professor,  
Faculty of Biotechnology and Biomolecular Sciences  
Universiti Putra Malaysia  
(Member)

**Yoshihito Shirai, PhD**

Professor,  
Department of Biological Functions and Engineering,  
Kyushu Institute of Technology, Japan  
(Member)

**Minato Wakisaka, PhD**

Professor,  
Department of Biological Functions and Engineering,  
Kyushu Institute of Technology, Japan  
(Member)

---

**BUJANG BIN KIM HUAT, PhD**

Professor and Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date:

## DECLARATION

### Declaration by graduate student

I hereby confirmed that:

- this thesis is my original work
- quotations, illustrations and citations have been duly referenced
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia
- written permission must be obtained from supervisor and Deputy Vice-Chancellor (Research and Innovation) before thesis is published in book form
- there is no plagiarism or data falsification in the thesis, and scholarly integrity was upheld as according to Rule 59 in Rules 2003 (Revision 2012-2013). The thesis has undergone plagiarism detection software.

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Name and Matric No.: SHERIL NORLIANA BINTI SUHAIMI (GS23884)



## Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in Rule 41 in Rules 2003 (Revision 2012-2013) were adhered to.

Signature : \_\_\_\_\_  
Name of chairman  
of Supervisory Committee : \_\_\_\_\_

Signature : \_\_\_\_\_  
Name of Member  
of Supervisory Committee : \_\_\_\_\_

Signature : \_\_\_\_\_  
Name of Member  
of Supervisory Committee : \_\_\_\_\_

Signature : \_\_\_\_\_  
Name of Member  
of Supervisory Committee : \_\_\_\_\_

## TABLE OF CONTENTS

	<b>Page</b>
<b>ABSTRACT</b>	ii
<b>ABSTRAK</b>	iv
<b>ACKNOWLEDGEMENTS</b>	vi
<b>APPROVAL</b>	vii
<b>DECLARATION</b>	ix
<b>LIST OF TABLES</b>	xiv
<b>LIST OF FIGURES</b>	xvi
<b>LIST OF ABBREVIATIONS</b>	xvii
<b>LIST OF APPENDICES</b>	xviii
<b>CHAPTER</b>	
<b>1 INTRODUCTION</b>	<b>1</b>
1.1 Background	1
1.2 Objectives	2
1.3 Scope of works	3
<b>2 LITERATURE REVIEW</b>	<b>4</b>
2.1 Overview of glycerol	4
2.2 Crude glycerol from biodiesel	6
2.3 Anaerobic fermentation of glycerol	9
2.3.1 Microbial pathways	9
2.3.2 Glycerol-fermenting microorganisms and the products	11
2.3.2.1 1,3-propanediol	14
2.3.2.2 Dihydroxyacetone	14
2.3.2.3 Succinic acid	14
2.3.2.4 Propionic acid	14
2.3.2.5 Citric acid	15
2.3.2.6 Lactic acid	15
2.3.2.7 Polyhydroxyalkanoates	16
2.4 Bioethanol production	16
2.4.1 Bioethanol producers using glycerol as substrate	17
2.4.2 Escherichia coli as bioethanol producers	18
2.5 Advantages of using crude glycerol as source of carbon	19
2.6 Design of experiment for optimization process	20
2.6.1 Response Surface Methodology (RSM)	20
2.6.2 Advantages of using statistical tools (RSM)	22
2.7 Concluding remarks	23
<b>3 GENERAL MATERIALS AND METHODS</b>	<b>24</b>
3.1 Chemical reagents	24
3.2 Bioethanol fermentation	24
3.2.1 Inoculum development	24
3.2.2 Fermentation and culture condition	24
3.3 Analytical methods	25

3.3.1	Biomass growth	25
3.3.2	Ethanol determination	25
3.3.3	Glycerol determination	25
3.3.4	Glucose determination	26
3.3.4	Organic acid determination	26
3.4.5	Hydrogen determination	26
<b>4</b>	<b>SCREENING AND ISOLATION OF GLYCEROL-FERMENTING BACTERIA FOR BIOETHANOL PRODUCTION</b>	<b>27</b>
4.1	Introduction	27
4.2	Materials and Methods	28
4.2.1	Pre-screening procedure	28
4.2.1.1	Sample collection and preparation	28
4.2.1.2	Screening for ethanol producer	29
4.2.2	Rapid screening method	30
4.2.2.1	Modification of rapid screening method	30
4.2.2.2	Confirmation test via batch fermentation	30
4.2.3	Identification of isolates	31
4.2.3.1	Colony morphology and gram staining	31
4.2.3.2	Biochemical test	31
4.2.3.3	16s rRNA sequence analysis	31
4.2.4	Ethanol fermentation by <i>E.coli</i> SS1	32
4.2.5	Comparison study of different laboratory culture	32
4.2.6	Comparison study using glucose as carbon source	32
4.2.7	Analytical methods	32
4.3	Results and Discussion	33
4.3.1	Modified screening method	33
4.3.2	Screening, isolation and characterization of ethanol-producer from glycerol	36
4.3.3	Ethanol fermentation profile by <i>E.coli</i> SS1	40
4.3.4	Ethanol fermentation comparative study	42
4.4	Conclusion	48
<b>5</b>	<b>OPTIMIZATION OF ETHANOL PRODUCTION FROM GLYCEROL USING STATISTICAL APPROACH</b>	<b>49</b>
5.1	Introduction	49
5.2	Materials and Methods	50
5.2.1	Substrate	50
5.2.2	Microorganism and fermentation condition	50
5.2.3	Experimental design	50
5.2.3.1	Two level factorial design	50
5.2.3.2	Central composite design	51
5.2.4	Fermentation of crude glycerol for ethanol production	52
5.2.5	Analytical methods	52
5.3	Results and Discussion	52
5.3.1	Two level factorial design	52
5.3.2	Central composite design	55
5.3.3	Validation of optimized condition	66

5.3.4	Fermentation of crude glycerol for ethanol production	68
5.4	Conclusion	71
<b>6</b>	<b>SUMMARY, GENERAL CONCLUSION AND RECOMMENDATION FOR FUTURE RESEARCH</b>	<b>72</b>
6.1	Summary	72
6.2	Conclusion	73
6.3	Recommendations for future research	73
	<b>REFERENCES</b>	<b>75</b>
	<b>APPENDICES</b>	<b>89</b>
	<b>BIODATA OF STUDENT</b>	<b>95</b>
	<b>LIST OF PUBLICATIONS</b>	<b>96</b>

