



UNIVERSITI PUTRA MALAYSIA

***FINITE ELEMENT ANALYSIS FOR CRASHWORTHINESS OF
AUTOMOTIVE SIDE DOOR REINFORCEMENT***

ALI FARHANINEJAD

FK 2014 94



**FINITE ELEMENT ANALYSIS FOR CRASHWORTHINESS OF
AUTOMOTIVE SIDE DOOR REINFORCEMENT**

By

ALI FARHANINEJAD

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfillment of the Requirement for the Degree of Master of Science**

September 2014

All material contained within the thesis, including without limitation text, logos icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the Degree of Master of Science

**FINITE ELEMENT ANALYSIS FOR CRASHWORTHINESS OF
AUTOMOTIVE SIDE DOOR REINFORCEMENT**

By

ALI FARHANINEJAD

September 2014

Chairman: Associate Professor Rizal Bin Zahari, PhD
Faculty: Engineering

Side impact collision is caused 40 percent serious injury during the car accident. In side impact collision, one of the most important concerns for vehicle engineers is allocating sufficient protection to automotive occupants. Although the crash zones which absorbing the energy and decreasing the magnitude of side impact force are less compared with the rear and frontal collision. However, extending the physical space between occupant and door are caused increasing the weight of vehicle. Consequently, the weight reduction of vehicle plays a crucial role to improve fuel efficiency and reducing emission gas. This factor is caused that the thin-wall structures are considered widely in vehicle industry. Side door square beam (SDSB) is one of the important parts in vehicle which plays the important role in absorbing energy of impact force and decreasing deflection. The main objective of this research is to present a practical and systematic methodology for improving the crashworthiness design of vehicle as well as obtaining the optimal design point. This research includes 2 main parts. In the first main part, the importance of side impact collision and the crashworthiness factors (SEA, PL) are investigated for side door square beam (SDSB) subjected to side impact. In the second main part, the proposed methodology is based on respond surface functions including the constrained single objective, weight and geometrical average methods. These optimization methods are employed to get the optimal design point. In this research the crashworthiness improvement and weight reduction of an SDSB are two problems which are considered. Reducing the impact force (PL) and deflection as well as increasing the specific energy absorption (SEA) are three targets which are investigated in this research. The material alloys of aluminium and steel as a reference are assigned to simple structure of SDSB to investigate the maximum SEA. It's observed that aluminium 2011 has the maximum SEA. In addition, the effect of increasing thickness of simple structure made of aluminium 2011 is compared with reinforced structure with the same material to investigate the less deflection and maximum SEA. It's observed that reinforced structure has the less deflection and maximum SEA compared with the simple structure. All the aforementioned comparing steps are performed by LS-DYNA software which is particularly used for finite element crash analysis. A multi-objective optimization is applied to find optimal point design to maintain maximum SEA and minimum PL for reinforced structure. Response surface methodology (RSM) is considered for design optimization in terms

of single optimization and multi-objective optimization. Single –objective optimization is applied to maximize SEA while the impact force is constrained and then minimized impact force while SEA is constrained. In the second part, multi-objective optimization which include the weighted average method and geometrical average method are presented to find the optimal point of structure design. The optimization methods are solved by MATLAB software. The result shows aluminum 2011 is the light weight material to absorb more energy compared with the steel. On the other hand reinforced structure made aluminum 2011 has the less deflection. The achievement structure is optimized to find optimal design point including maximum SEA and minimum PL. The optimal design point of thicknesses is obtained 0.7 mm for the selected reinforced structure and 0.27 mm for the rib. The PL and SEA of this optimal design point is 83171 Kn and N.mm/ton respectively.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Master Sains

FINITE ELEMENT ANALYSIS FOR CRASHWORTHINESS OF AUTOMOTIVE SIDE DOOR REINFORCEMENT

Oleh

ALI FARHANINEJAD

September 2014

Pengerusi: Professor Madya Rizal Bin Zahari, PhD

Faculti: Kejuruteraan

Sehingga kini, pelanggaran akibat hentaman sisi telah menyumbang kepada 40 peratus daripada kecederaan serius sewaktu kemalangan kereta. Di dalam pelanggaran hentaman sisi, salah satu daripada perkara penting kepada jurutera automotif ialah bagaimana untuk menyediakan perlindungan secukupnya kepada penumpang kereta. Seperti yang diketahui, zon remukkan yang menyerap tenaga pada ketika hentaman sisi berlaku adalah lebih kecil berbanding dengan zon remukkan di bahagian hadapan atau belakang kereta. Bagaimanapun, sekiranya ruang sisi kereta di antara penumpang dan pintu kereta diluaskan ianya akan hanya menambahkan berat kenderaan. Oleh yang demikian, pengurangan berat kenderaan memainkan peranan bagi meningkatkan kecekapan bahan api serta mengurangkan pemancaran gas. Faktor tersebut telah menyebabkan penggunaan struktur rasuk berdinding nipis digunakan dengan meluasnya sebagai perlindungan tambahan terhadap hentaman bahagian sisi kenderaan. Rasuk keratan segiempat sama (SDSB) merupakan salah satu struktur terpenting yang sering digunakan pada kenderaan bagi menyerap tenaga akibat daya hentaman di samping mengurangkan pesongan. Di dalam kajian ini, peningkatan kebolehtemakkan dan pengurangan berat pada SDSB merupakan masalah yang dipertimbangkan. Pengurangan daya hentaman (PL) dan pesongan serta penambahan penyerapan tenaga tertentu (SEA) merupakan tiga parameter yang diterokai di dalam kajian ini. Dua jenis bahan alloy iaitu keluli dan aluminium dijadikan sebagai bahan struktur mudah SDSB bagi menyiasat SEA maksima. Hasil pemerhatian telah menunjukkan bahawa aluminium 2011 mempunyai SEA yang maksima jika dibandingkan dengan keluli. Sebagai kajian tambahan, kesan penambahan ketebalan struktur mudah diperbuat oleh aluminium 2011 dibandingkan dengan struktur terkukuh bagi menyiasat pesongan dan SAE maksima. Daripada pemerhatian, didapati struktur terkukuh mempunyai pesongan paling kurang dan SAE tertinggi jika dibandingkan dengan struktur mudah tersebut. Kesemua langkah-langkah tersebut dijalankan dengan menggunakan perisian analisis unsur terhingga LS-DYNA yang sering digunakan secara terperinci untuk analisis remukkan. Seterusnya, pengoptimuman pelbagai-objektif diaplikasikan bagi mencari titik rekabentuk optimum bagi mengekalkan SAE maksima dan pengurangan PL bagi struktur terkukuh. Kaedah permukaan tindakbalas (RSM) dipertimbangkan bagi pengoptimuman rekabentuk dari segi pengoptimuman objektif tunggal dan

pengoptimuman pelbagai-objektif. Pengoptimuman objektif tunggal digunakan bagi memaksimumkan SEA sementara daya hentaman dikekang. Seterusnya, pengoptimuman dijalankan di mana SAE pula dikekang sementara daya hentaman dijadikan minima. Pada bahagian kedua, pengoptimuman pelbagai-objektif termasuk kaedah purata wajaran dan kaedah purata geometri dibentangkan bagi mendapatkan titik optimal rekabentuk struktur. Kaedah pengoptimuman diselesaikan oleh perisian MATLAB. Keputusan menunjukkan bahawa aluminium 2011 adalah lebih ringan dan mempunyai SEA lebih tinggi berbanding dengan keluli. Sebaliknya, struktur terkukuh aluminium 2011 mempunyai pesongan paling minima. Struktur pencapaian dioptimumkan bagi mendapatkan titik rekabentuk optimum termasuk SEA maksima serta PL minima. Titik rekabentuk optimum ketebalan ialah 0.7mm bagi struktur terkukuh yang terpilih manakala 0.27mm untuk struktur rusuk. Titik rekabentuk optimum bagi PL dan SEA ialah masing-masing 83171 kN dan 1.3002×10^9 N.mm/kg.



AKNOWLEDGEMENT

"In the name of Allah, Most gracious, Most merciful"

First of all, great thanks and praises are due to Allah, the Lord of all that exist. My Allah's peace and blessing be upon his final prophet and messenger, Muhammad, his family and his companions. I would like to thank my supervisor, Dr. Rizal Bin Zahari, for guidance in my master research. I would like to appreciate from my supervisory committee, Dr. Barkawi Bin Sahari and Dr. Faieza Abdul aziz for their suggestion and assistance throughout the years. Also thanks to Mrs.Salwani for help me to learn LS-DYNA software. Special thanks to my parents for their support and blessing during my hardness time in completing this research.



This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory committee were as follows:

Rizal Bin Zahari, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(chairman)

Barkawi Bin Sahari, PhD

Professor, IR
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Faieza Abdul Aziz, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

BUANG BIN KIM HUAT, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

DECLARATION

Declaration by the student

I hereby confirm that:

- this thesis is my original work
- quotations, illustrations and citations have been duly referenced
- the thesis has not been submitted previously or concurrently for any other degree at any institutions
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be owned from supervisor and deputy vice –chancellor (Research and innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software

Signature: _____ Date: _____

Name and Matric No.: Ali Farhaninejad GS29520

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENT	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABELS	xiii
LIST OF FIGURES	xiv
LIST OF ABBRIVIATIONS	xvi
CHAPTER	
1 INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	2
1.3 Research Objectives	2
1.4 Research Scope	3
1.5 Thesis Organization	3
2 LITERATURE REVIEW	4
2.1 Overview	4
2.2 Structural Requirements	4
2.3 Crashworthiness Metrics	4
2.3.1 Structure Analysis	4
2.3.2 Injury Analysis	5
2.3.3 Pedestrian Injury Analysis	5
2.4 Accidents Types	5
2.4.1 Frontal Impact	5
2.4.2 Side Impact	5
2.4.3 Rear Impact	6
2.4.4 Rollover Accidents	6
2.5 Mechanical Properties of Materials in Tension	6
2.6 Idealized Material Models	7
2.7 Impact Analysis	9
2.8 Finite Element Formulation	11
2.8.1 Direct integration Method	13
2.8.2 Implicit Method:	13

2.8.3	Explicit Method	13
2.9	Crashworthiness Literature Review	14
2.10	Overview of Two Materials for Crashworthiness	15
2.10.1	Steel	15
2.10.2	Aluminum	15
2.11	RSM Literature Review	16
2.11.1	Response Surface Methodology	16
2.11.2	Response Surface Design	17
2.11.3	Multiple Regression Model	19
2.11.4	Model Adequacy Checking	20
2.11.5	Second Order Model	21
2.11.6	Design for Fitting Second-Order Mode	22
2.12	Crashworthiness Optimization	22
2.12.1	Optimization Problem Description	22
2.12.2	Response Surface Method	24
2.13	Summary	25
3	METHODOLOGY	26
3.1	Overview	26
3.2	Methodology Flow Chart	26
3.3	Determining the Design Requirement	29
3.4	Pre-Processing	29
3.4.1	Features Geometry	31
3.4.2	Meshing	31
3.4.3	Geometric Section	31
3.4.4	Material Properties	31
3.4.5	Contact Interface	31
3.4.6	Boundary Condition	31
3.4.7	Initial Velocity	31
3.4.8	Preparing for Analysis	32
3.5	Running Analysis (solver)	32
3.6	Analysis of Results (post-processing)	32
3.7	Providing RSM Function	33
3.8	Running the Single and Multi-Objective Optimization	34

4	RESULTS AND DISCUSSION	35
4.1	Introduction	35
4.2	Validation	35
4.2.1	Validation of Square Beam	35
4.2.2	Finite Element Data	35
4.2.3	Result and Discussion	37
4.2.4	Mesh Sensitivity Analysis	38
4.2.5	Snapshot of The Deformation History	40
4.2.6	The Effect of Imperfection	41
4.3	Crashworthiness of Side Door Square Beam:	42
4.3.1	Finite Element Modelling	43
4.3.2	Material Properties	43
4.4	The Effects of Material on Crashworthiness	44
4.5	The Consequences of Thickness on Crash Behaviour	45
4.6	The Effects of Reinforced Structure on Crashworthiness:	46
4.7	Performance of SSDB Dimension Geometry	48
4.8	Response Surface Function	49
4.9	Single Optimization Results	49
4.9.1	Constrained Single Objective Optimization	49
4.10	Multi Objective Optimization Results	50
4.10.1	The Weight Average Method	50
4.10.2	The Geometrical Average Method	51
5	CONCLUSION AND RECOMMENDATIONS	53
5.1	Conclusions	53
5.2	Recommendations	53
	REFERENCES	55
	APPENDICES	60
	BIODATA OF STUDENT	71
	LIST OF PUBLICATIONS	72

LIST OF TABLES

Table		Page
4.1	Multiple-Regression Model(Bradley, 2007)	19
4.2	Mechanical Properties of Material (Marzbanrad et al., 2009)	43
4.3	Results of SEA and PL	48
4.4	Optimum Result of Equation (4.3)	50
4.5	Optimum Result of Equation (4.4)	50
4.6	Result of Cost Function	52


LIST OF FIGURES

Figure		Page
2-1	Stress-Strain Curves of Material under Tension	7
2-2	Idealized Stress-Strain Curves of Material under Tension	7
2-3	Idealized Stress-Strain Curves of Material under Tension	9
2-4	Surface Plot (Bradley, 2007)	17
2-5	Contour Plot (Bradley, 2007)	18
2-6	CCD (Bradley, 2007)	22
3-1	Flow Chart of Methodology	27
3-2	Overview of the Process Flow (Matlab and Ls-Dyna)	28
3-3	The Steps of Preparing the Model	30
3-4	Animation Results Using Pos-Processing	32
3-5	PL Function Simulation (MATLAB)	33
3-6	SEA Function Simulation (MATLAB)	34
3-7	Optimization Tool	34
4-1	The Square Beam	36
4-2	Experimental Test of Specimen (Abramowicz & Jones, 1984)	37
4-3	FE of Square Beam after Impact	37
4-4	Comparison Between Experimental and FE of Square Beam for Displacement	38
4-5	Deform Shapes Between Experimental, 700 and 1372 Elements	39
4-6	Displacement Vs Time for Several Number of Elements	39
4-7	Different Snapshot of Deformation	41
4-8	Comparison Between Two Deformation Shapes	41

4-9	View of Moving Rigid Wall	42
4-10	Simplified Beam of Front Side Sill Door	42
4-11	Deformation for Aluminium and Steel SDSB	44
4-12	SEA for Steel and Aluminium SDSB	44
4-13	Deflection for Different Thickness of Aluminum2011	45
4-14	SEA for Different Thickness of Aluminum2011	45
4-15	Reinforced Structure	46
4-16	Deformation of Simple and Rib Structure	47
4-17	SEA of Simple and Rib Structure	47
4-18	Pareto Graph	51

LIST OF ABBREVIATIONS

SDSB	Side Door Square Beam
PL	Peak Load
SEA	Specific Energy Absorption
FE	Finite Element models
RBF	Radial Basis Function
RSM	Response Surface Method
CAE	Computer Aided Engineering



CHAPTER 1

INTRODUCTION

1.1 Background

Side impact becomes a serious problem for protecting occupant during the crash due to a little physical space between the occupant and door. By comparison between the other type of accident, its observed that vehicle during the side impact can absorb five times less energy before injury caused to occupants comparing with frontal accident (Fildes et al., 1991). Meanwhile most of researches have been considered the frontal impact. Bumper is the main part of vehicle which they analyzed (Marzbanrad et al., 2009). However, side door body in side impact required more attention due to less crash zone (Ghadianlou & Abdullah, 2013).

These days vehicle safety has become a significant factor in vehicle sales. Safer vehicle has become a goal that each company attempt to accomplish it. According to Khalil and Du Bois (2004), in modern vehicle design, safer is the first concern. In the past, Vehicle Company spent a lot of money for experimental test to analysis the result. These test are time consuming and so expensive. By applying finite element methods these problems are solved.

Thin wall structure is used widely in Vehicle Company due to their lightweight material. They have a good capacity to absorb energy and resistance to avoid folding and bending during the crash. In this study rectangular beams with simple and reinforced structure are investigated in side impact to analysis the amount of their absorbing energy and deflection. Applying an appropriate thin-walled structure will caused decreasing the amount of peak load. Consequently, the occupant safety will improve. In addition, using these light materials leads to improving fuel efficiency of vehicle.

An optimization method is a numerical approach to find an optimum solution. An approximation method is the approach to collect data of complex design and create approximate models. Hence approximate model is considered to predict crash behaviour. One of the approximated methods is the response surface method (RSM) which is considered mainly in crash responses. Using this method for automotive component bring us crashworthiness improvement. In impact behaviour of vehicle, minimizing the peak load (PL) and maximizing the specific energy absorption (SEA) are two targets which required obtaining simultaneously. In this research work finding the optimal design point is achieved by using RSM optimization methods. This point must meet the maximum SEA and minimum PL.

1.2 Problem Statement

Improving vehicle fuel efficiency is a significant factor in automotive industry. Decreasing 10 % of vehicle weight leads to save more than five percent of fuel (Zhang et al., 2008). Many researches are analyzed crash but without considering the effect of energy absorption capacity through impact collision. According to statistic, it's reported that 35 % of fatalities are occurred by side impact (Dong et al., 2007). Vehicle safety has become a significant factor in vehicle sales. Safer vehicle has become a goal that each company attempt to accomplish it.

The computational cost of nonlinear finite element method is enormously expensive. A type of automotive structure includes many parts with complex geometry and different materials. The whole collision occurs during approximately 100(m/s) and each part go through each other and stresses surpass material elastics. Considering this, each modeling and analysis requires huge calculation. This means, the optimization methods must applied instead of finite element approach.

An acceptable design must meet all aforementioned requirements considering improving fuel efficiency and safer design. A side square door beam plays an important role to absorb the energy of impact force. Consequently, reduction the weight of beam is a significant factor to reduce the fuel consumption. The second problem is improving crashworthiness of the square beam using optimization methods, needs to decrease impact force and increase the energy absorption with respect to limitation of deflection.

1.3 Research Objectives

This research study is present to obtain an optimized reinforced structure of SSDB. A finite element method is employed as a modelling to obtain the PL and SEA. On the other hand single objective and multi-objective optimization tools are used as a means for getting the optimal design point of structure. These objectives of current work are:

- 1- To investigate the effects of material and modifying structure configuration of SSDB subject to side impact
- 2- To determine the optimal design point of modifying structure geometry subjected to side impact by applying optimization methods.

Based on previous research studies mentioned in chapter 2 modifying the structure of beam and changing the material are caused improving SEA and reducing of impact force. Consequently, finding the light weight material is caused improving fuel efficiency. Thus, there are research hypotheses which are analyzed to prove aforementioned goals.

1.4 Research Scope

As it is mentioned, the target of this research is to improve the crashworthiness of SSDB. To achieve this goal, the simple rectangular structure of SSDB is selected for analyzing the impact behaviour. The materials which are used for SSDB are alloy aluminium 3105-HB, 2011 and alloy steel AISI1006. These materials are chosen due to using widely in automotive industry. Analyzing the impact behaviour of the modifying structure of SSDB is another factor to find less deflection. Evaluations of impact test are performed by LS_DYNA 3.1 Beta software. Then the optimization methods are applied to obtain the optimal design point. In this research study, the results are optimized by MATLAB software.

1.5 Thesis Organization

This thesis consists of five chapters. First chapter consists of background, problem statement and thesis organization. In the second chapter, literature review is done that it related to the present study. Next chapter is studied on the nonlinear finite element and optimization methodology of square beam. The results of finite element and optimization methods are presented in chapter four. Finally, the last chapter discussed the recommendations and conclusions.

REFERENCES

- Abramowicz, W., & Jones, N. (1984). Dynamic axial crushing of square tubes. *International Journal of Impact Engineering*, 2(2), 179-208.
- Abramowicz, W., & Wierzbicki, T. (1989). Axial crushing of multicorner sheet metal columns. *Journal of Applied mechanics*, 56(1), 113-120.
- Acar, E., & Rais-Rohani, M. (2009). Ensemble of metamodels with optimized weight factors. *Structural and Multidisciplinary Optimization*, 37(3), 279-294.
- Aitharaju, V., & Gress, J. J. (2009). Non-linear welded blank and method of reducing mass: Google Patents.
- Alghamdi, A. (2001). Collapsible impact energy absorbers: an overview. *Thin-Walled Structures*, 39(2), 189-213.
- Allahbakhsh, H., & Saemi, J. (2011). Design optimization of square and circular aluminium extrusion damage columns with crashworthiness criteria. *Indian Journal of Engineering & Materials Sciences*, 18(5), 341-350.
- Andrews, K., England, G., & Ghani, E. (1983). Classification of the axial collapse of cylindrical tubes under quasi-static loading. *International Journal of Mechanical Sciences*, 25(9), 687-696.
- Athan, T. W., & Papalambros, P. Y. (1996). A note on weighted criteria methods for compromise solutions in multi-objective optimization. *Engineering Optimization*, 27(2), 155-176.
- Box, G. E., & Wilson, K. (1951). On the experimental attainment of optimum conditions. *Journal of the Royal Statistical Society. Series B (Methodological)*, 13(1), 1-45.
- Bradley, N. (2007). *The response surface methodology*. Indiana University South Bend.
- Caliskan, A. G., Jeryan, R. A., Mees, H., & Iregbu, S. (2005). *Experimental and analytical study of the crashworthiness for the 2005 Ford GT aluminum spaceframe*. Paper presented at the ASME 2005 International Mechanical Engineering Congress and Exposition.
- Chen, C.-J., & Usman, M. (2001). Design optimisation for automotive applications. *International Journal of Vehicle Design*, 25(1), 126-141.
- Crash Network. (2010). European Regulations related to Crash Testing. *Crash Network Online* Retrieved 4/1/2012, from www.Crash-network.com/Regulations/ECE-Regulations/ece-Regulations.html
- Dong, G., Wang, D., Zhang, J., & Huang, S. (2007). Side structure sensitivity to passenger car crashworthiness during pole side impact. *Tsinghua Science & Technology*, 12(3), 290-295.

- Fang, H., Rais-Rohani, M., Liu, Z., & Horstemeyer, M. (2005). A comparative study of metamodeling methods for multiobjective crashworthiness optimization. *Computers & Structures*, 83(25), 2121-2136.
- Fildes, B., Bostrom, O., Haland, Y., & Sparke, L. (2003). *COUNTERMEASURES TO ADDRESS FAR SIDE CRASHES: FIRST RESULTS*.
- Fildes, B., Lane, J., Lenard, J., & Vulcan, A. (1991). *Passenger cars and occupant injury*.
- Fildes, B., Lane, J., Lenard, J., & Vulcan, A. (1994). Passenger cars and occupant injury: side impact crashes.
- Ghadianlou, A., & Abdullah, S. B. (2013). Crashworthiness design of vehicle side door beams under low-speed pole side impacts. *Thin-Walled Structures*, 67, 25-33.
- Ghamarian, A., & Zarei, H. (2012). Crashworthiness investigation of conical and cylindrical end-capped tubes under quasi-static crash loading. *International Journal of Crashworthiness*, 17(1), 19-28.
- Hallquist, J. O. (1993). LS-DYNA3D theoretical manual. *Livermore software technology corporation*.
- Hosseini-pour, S., & Daneshi, G. (2003). Energy absorption and mean crushing load of thin-walled grooved tubes under axial compression. *Thin-Walled Structures*, 41(1), 31-46.
- Hou, S., Li, Q., Long, S., Yang, X., & Li, W. (2007). Design optimization of regular hexagonal thin-walled columns with crashworthiness criteria. *Finite elements in analysis and design*, 43(6), 555-565.
- Hou, S., Li, Q., Long, S., Yang, X., & Li, W. (2008). Multiobjective optimization of multi-cell sections for the crashworthiness design. *International Journal of Impact Engineering*, 35(11), 1355-1367.
- Huang, X., & Lu, G. (2005). Bending hinge characteristic of thin-walled square tubes. *International Journal of Crashworthiness*, 10(3), 275-285.
- Ibrahim, H. K. (2009). *Design optimization of vehicle structures for crashworthiness improvement*. Concordia University.
- Jing, Y.-Y., & Barton, D. C. (1998). The response of square cross-section tubes under lateral impact loading. *International Journal of Crashworthiness*, 3(4), 359-378.
- Johnson, W., Soden, P., & Al-Hassani, S. (1977). Inextensional collapse of thin-walled tubes under axial compression. *The Journal of Strain Analysis for Engineering Design*, 12(4), 317-330.
- Kecman, D. (1983). Bending collapse of rectangular and square section tubes. *International Journal of Mechanical Sciences*, 25(9), 623-636.

- Khalil, T., & Du Bois, P. (2004). *Finite element analytical techniques and applications to structural design*. Michigan: American Iron and Steel Institute.
- Kim, T., & Reid, S. (2001). Bending collapse of thin-walled rectangular section columns. *Computers & Structures*, 79(20), 1897-1911.
- Kurtaran, H., Eskandarian, A., Marzougui, D., & Bedewi, N. (2002). Crashworthiness design optimization using successive response surface approximations. *Computational Mechanics*, 29(4-5), 409-421.
- Langseth, M., & Hopperstad, O. (1996). Static and dynamic axial crushing of square thin-walled aluminium extrusions. *International Journal of Impact Engineering*, 18(7), 949-968.
- Langseth, M., Hopperstad, O., & Berstad, T. (1999). Crashworthiness of aluminium extrusions: validation of numerical simulation, effect of mass ratio and impact velocity. *International Journal of Impact Engineering*, 22(9), 829-854.
- Lee, T. H., & Lee, K. (2005). Multi-criteria shape optimization of a funnel in cathode ray tubes using a response surface model. *Structural and Multidisciplinary Optimization*, 29(5), 374-381.
- Lindman, H. R. (1992). *Analysis of variance in experimental design*. New York: Springer-Verlag Publishing.
- Lu, G., & Yu, T. (2003). *Energy absorption of structures and materials*. U.S: Elsevier.
- Mamalis, A., Manolakos, D., Ioannidis, M., & Kostazos, P. (2006). Bending of cylindrical steel tubes: numerical modelling. *International Journal of Crashworthiness*, 11(1), 37-47.
- Marzbanrad, J., Alijanpour, M., & Kiasat, M. S. (2009). Design and analysis of an automotive bumper beam in low-speed frontal crashes. *Thin-Walled Structures*, 47(8), 902-911.
- Meguid, S., Attia, M., & Monfort, A. (2004). On the crush behaviour of ultralight foam-filled structures. *Materials & Design*, 25(3), 183-189.
- Montgomery, D. C. (2008). *Design and analysis of experiments*. Hoboken: John Wiley & Sons.
- Myers, R. H., Montgomery, D. C., & Anderson-Cook, C. M. (2009). *Response surface methodology: Process and product optimization using designed experiments* (Vol. 705). U.S: John Wiley & Sons.
- Peixinho, N., & Pinho, A. (2007). Study of viscoplasticity models for the impact behavior of high-strength steels. *Journal of Computational and Nonlinear Dynamics*, 2(2), 114-123.
- Qiao, J., Chen, J., & Che, H. (2006). Crashworthiness assessment of square aluminum extrusions considering the damage evolution. *Thin-Walled Structures*, 44(6), 692-700.

- Rao, S. S., & Rao, S. (2009). *Engineering optimization: theory and practice*. U.S: John Wiley & Sons.
- Robertson, L. S. (1981). Automobile safety regulations and death reductions in the United States. *American Journal of Public Health*, 71(8), 818-822.
- Sahari, B., Azni, M. M., Wong, S., Ahmad, M. F., Khalid, Y., & Hamouda, A. (2008). Finite element lateral crash analysis of front natural gas vehicle platform with tank mounting structure. *International Journal of Vehicle Safety*, 3(2), 135-148.
- Salehghaffari, S., Rais-Rohani, M., & Najafi, A. (2011). Analysis and optimization of externally stiffened crush tubes. *Thin-Walled Structures*, 49(3), 397-408.
- Salwani, M., Aidy, A., Sahari, B., & Nuraini, A. (2011). Crash of automotive side member subjected to oblique loading. *International Journal of Physical Sciences*, 6(31), 7125-7131.
- Song, H.-W., Wan, Z.-M., Xie, Z.-M., & Du, X.-W. (2000). Axial impact behavior and energy absorption efficiency of composite wrapped metal tubes. *International Journal of Impact Engineering*, 24(4), 385-401.
- Toksoy, A., & Güden, M. (2010). Partial Al foam filling of commercial 1050H14 Al crash boxes: The effect of box column thickness and foam relative density on energy absorption. *Thin-Walled Structures*, 48(7), 482-494.
- Van Slycken, J., Verleysen, P., Degrieck, J., Bouquerel, J., & De Cooman, B. (2006). Crashworthiness characterization and modelling of high-strength steels for automotive applications: Proceedings of the institution of mechanical engineers. *Journal of Automobile Engineering*, 220(4), 391-400.
- Wang, G. G., & Shan, S. (2007). Review of metamodeling techniques in support of engineering design optimization. *Journal of Mechanical Design*, 129(4), 370-380.
- Wierzbicki, T., & Abramowicz, W. (1983). On the crushing mechanics of thin-walled structures. *Journal of Applied mechanics*, 50(4a), 727-734.
- Wierzbicki, T., Recke, L., Abramowicz, W., Gholami, T., & Huang, J. (1994). Stress profiles in thin-walled prismatic columns subjected to crush loading-II. Bending. *Computers & Structures*, 51(6), 625-641.
- Wu, S. R., & Saha, N. (2006). Some challenges to crashworthiness analysis: SAE Technical Paper.
- Xiang, Y., Wang, Q., Fan, Z., & Fang, H. (2006). Optimal crashworthiness design of a spot-welded thin-walled hat section. *Finite Elements in Analysis and Design*, 42(10), 846-855.
- Yamazaki, K., & Han, J. (2000). Maximization of the crushing energy absorption of cylindrical shells. *Advances in Engineering Software*, 31(6), 425-434.

- Yang, R., Wang, N., Tho, C., Bobineau, J., & Wang, B. (2005). Metamodeling development for vehicle frontal impact simulation. *Journal of Mechanical Design*, 127(5), 1014-1020.
- Zarei, H., & Kröger, M. (2006). Multiobjective crashworthiness optimization of circular aluminum tubes. *Thin-Walled Structures*, 44(3), 301-308.
- Zhang, Liu, S., & Tang, Z. (2009). Design optimization of cross-sectional configuration of rib-reinforced thin-walled beam. *Thin-Walled Structures*, 47(8), 868-878.

