



UNIVERSITI PUTRA MALAYSIA

***EVALUATION OF GROUNDWATER POTENTIAL FOR IRRIGATION
AT THE SEBERANG PERAK AQUIFER, MALAYSIA***

MOHD FAUZIE BIN JUSOH

FK 2013 83



**EVALUATION OF GROUNDWATER POTENTIAL FOR IRRIGATION
AT THE SEBERANG PERAK AQUIFER, MALAYSIA**

By

MOHD FAUZIE BIN JUSOH

**Thesis Submitted to the School of Graduate Studies, Universiti Putra
Malaysia, in Fulfillment of the Requirements for the Degree of Master of
Science**

July 2013

DEDICATION

This thesis is dedicated to my beloved father, mother and family who enormously prayed and encouraged me.

The verses in the Holy Koran (year 610 C) are totally true where I realize that:

These verses explained about hydrologic cycle and groundwater existence:

“And We send down water from the sky according to (due) measure, and We cause it to soak in the soil; and We certainly are able to drain it off (with ease)”.

[Surah Al-Mu'minun, Verse 18]

“So We opened the gates of heaven, with water pouring forth. And We caused the earth to gush forth with springs, so the waters met (and rose) to the extent decreed”.

[Surah Al-Qamar, Verse 11-12]

These verses explained about existence of shallow aquifer:

“Seest thou not that Allah sends down rain from the sky, and leads it through springs in the earth? Then He causes to grow, therewith, produce of various colors: then it withers; thou wilt see it grow yellow; then He makes it dry up and crumble away. Truly, in this, is a message of remembrance to men of understanding”.

[Surah Az-Zumar, Verse 21]

“And We produce therein orchard with date-palms and vines, and We cause springs to gush forth therein”.

[Surah Yaasin, Verse 34]

This verse explained about existence of deep / fracture rock aquifer:

“Then your hearts became hardened after that, being like stones or even harder. For indeed, there are stones from which rivers burst forth, and there are some of them that split open and water comes out, and there are some of them that fall down for fear of Allah. And Allah is not unaware of what you do.”

[Surah Al-Baqarah, Verse 74]

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the degree of Master of Science

**EVALUATION OF GROUNDWATER POTENTIAL FOR IRRIGATION
AT THE SEBERANG PERAK AQUIFER, MALAYSIA**

By

MOHD FAUZIE BIN JUSOH

July 2013

Chairman : Associate Professor Hasfalina Che Man, PhD

Faculty : Engineering

The pumping well performance and aquifer performance in a quaternary sediment of Gula Formation at Seberang Perak Integrated Agricultural Development Area (Seberang Perak IADA) has been investigated quantitatively. The study was conducted in the years of 2009 and 2010 at a selected rice cultivation area. Aquifer performance test was carried out by conducting 24 hours constant discharge pumping test in a shallow alluvial aquifer.

The time drawdown data were collected at three different wells. The pumping well performance was evaluated by using continuous step-drawdown pumping test. Time-drawdown data was analyzed by using AquiferTest Pro software version 4.2. The aquifer test enabled the values of hydraulic characteristics of

the aquifer material such as transmissivity, hydraulic conductivity, and specific yield to be determined. Well performance was interpreted through well loss coefficient and specific capacity. The predictive analysis of drawdown through multiple pumping well was based on the results of aquifer performance.

The type of the aquifer up to about 10 m depth from ground surface at the research area is unconfined aquifer. The Neuman model and Boulton model have been used to evaluate the hydraulic characteristic of the aquifer. The transmissivity value from observation wells varied from 581 to 940 $\text{m}^2\text{day}^{-1}$ with the average transmissivity of 761 $\text{m}^2\text{day}^{-1}$. This indicates that the aquifer was categorized as having high groundwater potential. The hydraulic conductivity values obtained from observation well 1 and observation well 2 range from 58.1 mday^{-1} to 94.0 mday^{-1} . This implies that the aquifer materials are developed from coarse grain sand. The specific yield from observation well 1 and observation well 2 are found to be 0.0041 and 0.0135 respectively. The results of aquifer hydraulic characteristic are in agreement with the recovery test analysis.

In term of well performance, the average specific capacity of the pumping well is found to be 6.1223 m^2hr^{-1} . Specific capacity of the tested well is classified as having moderate potential. The average well efficiency of the tested tube well is found to be 92%. This showed that the well has been well designed and the screen was installed at the suitable location in the aquifer. The coefficient of

aquifer loss and well loss are found to be 0.1513 hr m^{-2} and $0.002 \text{ hr}^2 \text{ m}^{-5}$ respectively. In each step, the drawdown inside the pumping well is influenced more by the aquifer loss compared to the well loss.

The potential yield of the pumping well is calculated as $450 \text{ m}^3 \text{ day}^{-1}$. Based on the crop water requirement and groundwater irrigation on the field, it is estimated that 4 hectares of paddy plot requires $260 \text{ m}^3 \text{ day}^{-1}$. However, the pilot project on groundwater irrigation for rice cultivation on the study site use less than the amount of water calculated from crop water requirement. The result of 24 hours constant discharge pumping test shows that the drawdown at the pumping well is 2.2 m with the total abstraction of $240 \text{ m}^3 \text{ day}^{-1}$. Two pumping wells are required to irrigate 4 hectares of paddy plot. The effect of drawdown on multiple pumping well can be predicted through the result of pumping test directly which can save time and minimize the research cost.

Abstrak thesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Master Sains

**PENILAIAN POTENSI AIR BAWAH TANAH UNTUK PENGAIRAN DI
AKUIFER SEBERANG PERAK, MALAYSIA**

Oleh

MOHD FAUZIE BIN JUSOH

Julai 2013

Pengerusi : Profesor Madya Hasfalina Che Man, PhD

Fakulti : Kejuruteraan

Penilaian telaga pengepaman dan prestasi telaga pengepaman dalam sedimen kuartenari bagi Formasi Gula di Kawasan Pembangunan Pertanian Bersepadu Seberang Perak (IADA Seberang Perak) telah dikaji secara kuantitatif. Kajian telah dijalankan pada dari tahun 2009 – 2010 di kawasan penanaman padi terpilih. Prestasi akuifer telah dinilai dengan menjalankan ujian pengepaman luahan tetap selama 24 jam dalam lapisan alluvium cetek.

Data surutan-masa telah diperhatikan daripada 3 telaga berlainan di kawasan kajian. Prestasi telaga pengepaman telah dinilai dengan menggunakan ujian pengepaman surutan berperingkat berpanjangan. Data surutan-masa telah dianalisis dengan menggunakan perisian AquiferTest Pro Versi 4.2. Ujian pengepaman membolehkan nilai sifat-sifat hidraulik seperti keterusan,

kekonduksian hidraulik, dan simpanan tentu dikira. Prestasi telaga diinterpretasi melalui pekali kehilangan telaga dan kapasiti tentu. Analisis jangkaan bagi surutan melalui pengepaman telaga berganda berdasarkan keputusan prestasi akuifer.

Jenis akuifer pada kedalaman sehingga 10 m daripada tanah di kawasan kajian adalah akuifer tidak terkekang. Model Neuman dan model Boulton telah digunakan untuk menilai sifat-sifat hidraulik akuifer tersebut. Nilai keterusan daripada telaga pemantauan berjulat antara 581 hingga 940 $\text{m}^2\text{hari}^{-1}$ dengan purata keterusan 761 $\text{m}^2\text{hari}^{-1}$. Ini menunjukkan akuifer dikategorikan mempunyai potensi yang tinggi. Nilai kekonduksian hidraulik yang diperolehi daripada telaga pemantauan 1 and telaga pemantauan 2 berjulat antara 58.1 mhari^{-1} ke 94 mhari^{-1} . Ini menunjukkan bahan yang membina akuifer terdiri daripada pasir kasar. Simpanan tentu daripada telaga pemantauan 1 dan telaga pemantauan 2 didapati masing-masing berjulat antara 0.0041 dan 0.0135. Keputusan daripada ujian pemulihan adalah berpadanan dengan sifat-sifat akuifer yang diperolehi daripada ujian pengepaman luahan tetap.

Dari segi prestasi telaga, purata hasil tentu bagi telaga pengepaman adalah 6.1223 $\text{m}^2\text{jam}^{-1}$. Hasil tentu bagi telaga yang diuji telah diklasifikasikan sebagai keupayaan pertengahan. Purata kecekapan telaga yang diuji pula adalah 92%. Ini menunjukkan bahawa telaga telah direkabentuk dengan baik dan kedudukan saringan telah diletakkan di kedudukan yang sesuai di dalam akuifer. Pekali

kehilangan akuifer dan pekali kehilangan telaga adalah masing –masing 0.1513 jam^{-2} and $0.002 \text{ jam}^2\text{m}^{-5}$. Bagi setiap langkah, surutan di dalam telaga pengepaman adalah lebih dipengaruhi oleh kehilangan akuifer berbanding kehilangan telaga.

Hasil upaya bagi sebuah telaga pengepaman adalah sebanyak $450 \text{ m}^3\text{hari}^{-1}$. Berdasarkan keperluan air tanaman dan pengairan menggunakan air bawah tanah di kawasan kajian, adalah dianggarkan 4 hektar kawasan padi memerlukan sebanyak $260 \text{ m}^3\text{hari}^{-1}$. Walaubagaimanapun, projek perintis menggunakan air bawah tanah untuk pengairan tanaman padi di tapak kajian menunjukkan air bawah tanah yang digunakan adalah kurang daripada jumlah keperluan air tanaman. Keputusan daripada ujian pengepaman luahan tetap menunjukkan surutan yang terhasil selepas 24 jam adalah 2.2 m dengan jumlah luahan adalah sebanyak $240 \text{ m}^3\text{hari}^{-1}$. Dua telaga pengepaman adalah diperlukan untuk mengairi kawasan seluas 4 hektar kawasan padi. Kesan surutan daripada telaga pengepaman berganda boleh dijangka melalui keputusan ujian pengepaman secara terus dimana ia boleh menjimatkan masa dan meminimumkan kos.

ACKNOWLEDGEMENTS

In the name of Allah, the Most Compassionate and the Most Merciful. Praise and greet upon Prophet Muhammad s.a.w, his family and his friends. Alhamdulillah, praise is upon Allah for his willingness for giving me the strength and confidence in completing this thesis. Thank you God for everything.

My deepest gratitude is dedicated to Dr. Hasfalina Che Man (supervisor) and Mr. Mohamed Azwan Mohamed Zawawi (co-supervisor) for their continuous guidance, kindness, invaluable support and critical review throughout this study.

I am thankful to my committee members, Professor Ir. Dr. Mohd Amin Mohd Soom and Professor Dr. Thamer Ahmad Mohammed for their positive critics and valuable comments regarding this research project.

I also appreciated the financial support for this project provided by UPM Research University Grant Scheme (RUGS). Not forgetting also, I would like to thanks to all the staff and technicians at Department of Biological and Agricultural, Faculty of Engineering, UPM for their technical assistant. Thanks are certainly to my beloved mother, Fatimah Ismail and father, Jusoh Mamat who really understand, inspire and motivate me. They always pray for my success.

I certify that a Thesis Examination Committee has met on 29 July 2013 to conduct the final examination of Mohd Fauzie Bin Jusoh on his thesis entitled “Evaluation of Groundwater Potential for Irrigation at the Seberang Perak Aquifer, Malaysia” in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee commends that the students be awarded the Master of Science (Soil and Water Engineering).

Members of the Thesis Examination Committee were as follows:

Lee Teang Shui, PhD
Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Badronnisa Yusuf, PhD
Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Abdul Halim Ghazali, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Lariyah Mohd Sidek, PhD
Associate Professor
College of Engineering
Universiti Tenaga Nasional
(External Examiner)

NORITAH OMAR, PhD
Associate Professor and
Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 20 November 2013

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Hasfalina Che Man, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Mohd Amin Mohd Soom, PhD, Ir

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Thamer Ahmed Mohammed, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

BUJANG BIN KIM HUAT, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

DECLARATION

I declare that the thesis is my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously, and is not concurrently, submitted for any other degree at Universiti Putra Malaysia or at any other institution.



MOHD FAUZIE BIN JUSOH

Date: 29 July 2013

TABLES OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	vi
ACKNOWLEDGEMENTS	ix
APPROVAL	x
DECLARATION	xii
LIST OF TABLES	xv
LIST OF FIGURES	xvi
LIST OF ABBREVIATIONS AND SYMBOLS	xviii
CHAPTER	
1 INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	6
1.3 Objectives of the Study	7
1.4 Scope of the Study	7
1.5 Limitation of the Study	8
1.6 Organization of the Thesis	8
2 LITERATURE REVIEW	9
2.1 The Role of Groundwater in the Hydrologic Cycle	9
2.2 Early Use of Groundwater	12
2.3 Types of Aquifers	14
2.4 Utilization of Groundwater in the World	16
2.5 Utilization of Groundwater in Malaysia	20
2.5.1 Groundwater Potential Resources in Malaysia	24
2.5.2 Previous Groundwater Investigation in Perak	28
2.6 Water Available and Water Demand in Malaysia	30
2.7 Aquifer Hydraulic Characteristics	32
2.7.1 Hydraulic conductivity, K	32
2.7.2 Transmissivity, T	33
2.7.3 Storativity, S and Specific Yield, S_y	35
2.7.4 Hydraulic Resistance	37
2.7.5 Leakage Factor	37
2.8 Methods to Determine Hydraulic Conductivity	38
2.8.1 Empirical Formula	39
2.8.2 Laboratory Method	40
2.8.3 Tracer Test	40
2.8.4 Slug Test	41
2.8.5 Pumping Test	41
2.9 Software Analysis of Pumping Test Data	44
2.10 Analysis of Aquifer Performance	46
2.11 Analysis of Well Performance	54

	2.11.1 Specific Capacity	54
	2.11.2 Well Loss	55
3	MATERIALS AND METHODS	57
	3.1 Site Description and Climax of the Study Area	57
	3.2 Geology of the Study Area	60
	3.3 Hydrogeology of the Study Area	61
	3.4 Determination of Aquifer Type	62
	3.5 Execution of Constant Discharge Pumping Test	63
	3.6 Execution of Step-Drawdown Pumping Test	66
	3.7 Drawdown Prediction from Multiple Pumping Well	68
4	RESULT AND DISCUSSION	69
	4.1 Aquifer Performance	69
	4.1.1 Water Level and Temperature Trend before Pumping Test	69
	4.1.2 Analysis of Constant Discharge Pumping Test	70
	4.2 Well Performance	77
	4.3 Potential Well Yield and Irrigation Water Demand	81
	4.4 Predictive Analysis	84
5	CONCLUSIONS AND RECOMMENDATIONS	88
	5.1 Conclusions	88
	5.2 Recommendations	89
	REFERENCES	91
	APPENDICES	103
	BIODATA OF STUDENT	118
	LIST OF PUBLICATIONS	119

LIST OF TABLES

Table		Page
2.1	Present groundwater abstraction for water supply in Kelantan	23
2.2	Aquifer potential of Malaysia	27
2.3	Previous groundwater investigations in Perak	28
2.4	Total domestic, industrial and irrigation demand for Peninsular Malaysia	31
2.5	Irrigation water demand for granary schemes in Perak	31
2.6	Values of hydraulic conductivity for sedimentary material	33
2.7	Classification of the aquifer potential	35
2.8	Specific yield of sedimentary formation	37
2.9	Classification of the leakage factor	38
2.10	The size of survey area and pumping test duration	43
2.11	Frequency of water level reading during pumping test	43
2.12	Commercialized pumping test softwares	45
2.13	Specific capacities values and well productivity	55
3.1	Resistivity of selected rocks, minerals and chemical	63
3.2	The well characteristics	66
3.3	Input of the well characteristics to AquiferTest Pro	66
4.1	Hydraulic characteristic of tested aquifer	72
4.2	Results of recovery analysis from tested wells	76
4.3	Well efficiency and specific capacity of the tested well	79
4.4	Scenarios for predictive analysis for further well development	85

LIST OF FIGURES

Figure		Page
2.1	Schematic Representation of the Hydrologic Cycle	9
2.2	Interaction of Groundwater and Surface Water	11
2.3	Diagram of the Qanat	13
2.4	Types of Aquifers	15
2.5	Groundwater Withdrawal and Consumption: The Big Gap	17
2.6	Total Groundwater Production by AKSB from the Year 1990 to 2011	23
2.7	Hydrogeological Map of Peninsular Malaysia	26
2.8	Hydrogeological Balance for Peninsular Malaysia	30
2.9	Illustration of the Coefficients of Hydraulic Conductivity And Transmissivity	34
2.10	The Relationship between Transmissivity and Cone of Depression For Confined and Confined Aquifer	34
2.11	Illustration of Specific Yield in Unconfined Aquifer	36
2.12	Methods used to Determine Hydraulic Conductivity	39
2.13	Log-log and Semi-log Plots of the Theoretical Time-Drawdown Curve of Unconsolidated Aquifer	49
2.14	Drawdown Curve during Pumping and Recovery Period	51
2.15	Formation Loss and Well Loss in a Pumped Well	56
3.1	Location of Study Area in Seberang Perak	57
3.2	Monthly Average Rainfall Distribution from 2001 to 2010 at Sg. Dedap Rainfall Station	58
3.3	The Methodology on the Study of Evaluation of Groundwater Potential for Irrigation at Seberang Perak Aquifer	59

3.4	Geology Map of Perak State	60
3.5	Hydrogeology Map of Perak State	61
3.6	Electrical Resistivity Test during Preliminary Study	62
3.7	The Arrangement of Constant Discharge Pumping Test	64
3.8	Schematic Diagram of the Location of each Well	65
3.9	The Arrangement of Step Drawdown Pumping Test	67
4.1	Water Table Level Trend Three Weeks before Conducting Pumping Test	70
4.2	Time Drawdown Data from Pumping Well and Observation Well on Log-Log Scale	72
4.3	Different Between Actual Drawdown and Theoretical Drawdown of Neuman method for OW1	73
4.4	Different Between Actual Drawdown and Theoretical Drawdown of Neuman method for OW2	73
4.5	Different Between Actual Drawdown and Theoretical Drawdown of Boulton method for OW1	74
4.6	Different Between Actual Drawdown and Theoretical Drawdown of Boulton method for OW2	74
4.7	Curve Fitting of Agarwal and Theis Combination from the Wells	76
4.8	Graph of Drawdown Versus Time at Each Step of Step Drawdown Test	77
4.9	Plot of Drawdown versus Discharge with a Polynomial Trend Line	78
4.10	Observed and Predicted Drawdown of Pumping Well	80
4.11	Volume of Groundwater Abstracted and Rainfall at the Study Area During Rice Cultivation between August and November 2009	83
4.12	The Effect of Groundwater Abstraction on Drawdown	86

LIST OF ABBREVIATIONS AND SYMBOLS

m^3yr^{-1}	: Cubic meter per year
m^3day^{-1}	: Cubic meter per day
m^3hr^{-1}	: Cubic meter per hour
m^2day^{-1}	: Square meter per day
m^2hr^{-1}	: Square meter per hour
$mday^{-1}$: Meter per day
L	: Liters
m	: Meter
m^3	: Cubic meter
mm	: Millimeter
kW	: Kilo watt
Hz	: Hertz
$mmin^{-1}$: Meter per minute
$cmday^{-1}$: Centimeter per day
mg/l	: Milligram per liter
$^{\circ}C$: Degree celsius
T	: Transmissivity
K	: Hydraulic conductivity
S_y	: Specific yield
S	: Storage coefficient
c	: Hydraulic resistance
L	: Leakage factor

kg	: Kilogram
Kg.	: Kampung
Sg.	: Sungai
IADA	: Integrated Agriculture Development Area
DID	: Department of Irrigation and Drainage
MGDM	: Minerals and Geoscience Department of Malaysia
NWRS	: National Water Resources Study (2000 - 2050)
NEAC	: National Economic Action Council
JICA	: Japan International Cooperation Agency
MOA	: Ministry of Agriculture
DOE	: Department of Environment
AKSB	: Air Kelantan Sdn Bhd



CHAPTER 1

INTRODUCTION

1.1 Background

Water is very important in our life and others living things. Water is needed in human activities for domestic, agriculture, recreation and industrial purposes. Two major water resources are surface water and groundwater. Groundwater is the hidden water source where the quantity of groundwater actually is greater than the amount of available surface water. Fitts (2002) mentioned that fresh groundwater is about 100 times more plentiful than fresh surface water, but surface water is commonly used as it is easy to obtain.

Water is important in agriculture sector for plant and livestock growth. It is estimated that 70% of fresh water worldwide is being used for agriculture where 1,000 L of water are required to produce 1 kg of cereal grain and 43,000 L of water are required to produce 1 kg of beef (Pimentel *et al.*, 2004). Rosegrant *et al.* (2002) reported that worldwide cereal demand will grow by a projected 46% between 1995 and 2025 and for developing countries; it is projected by 65%. The demand worldwide is expected to grow by 56% and for developing countries it is projected to be more than double of 1995 production. The development of groundwater resources can increase agricultural production to meet the food needs of a country (Islam, 2006).

Rice is the staple food for most of the Asian country including Malaysia. More than 90% of global rice is produced and consumed in Asia (Akinbile *et al.*, 2011; Lee *et al.*, 2005a). Malaysia is currently ranked 25th of world paddy production with a production capacity of 2.4 million tonne and cultivable land of about 0.7 million hectares since 1980s (Akinbile *et al.*, 2011). Water is a critical element in rice cultivation and this crop need a large amount of water (Rowshon *et al.*, 2012) during pre-saturation and normal growth (Akinbile *et al.*, 2011; Azwan *et al.*, 2010; Lee *et al.*, 2005b; Rosegrant *et al.*, 2002; Mahmud *et al.*, 2000).

Integrated Agricultural Development Area (IADA) was introduced by Ministry of Agriculture and Agro-Based Industry Malaysia in 1965, focusing on development of granary area in Malaysia (Ministry of Agriculture, MOA, 2011). MOA (2011) highlighted three general objectives of IADA which are; i) to increase the income and productivity of farmers, ii) to increase the paddy yield to 6.5 metric tonne per hectare towards 2010 and iii) to modernize the rice agriculture sector. Therefore, in order to achieve the general objective listed, a reliable and proper management of irrigation water on paddy plantation is very important to be stressed.

The average yields of paddy at Seberang Perak IADA, Kerian Sungai Manik IADA, Barat Laut Selangor IADA and Pulau Pinang IADA for 2010 were 3.352, 3.344, 4.979, and 5.029 metric tonne per hectare respectively (MOA, 2010). These indicating that paddy production in granary area in Malaysia are not achieving the target of 6.5 metric tonne per hectare for IADA projects. Munit (2010) mentioned that the paddy yields in Sekinchan area has been successfully achieved to 10 metric tonne per hectare whereas it was not obtained in Tanjung Karang granary area. This

situation was probably happened due to inadequate supply of irrigation water and improper monitoring system of water supply. Akinbile *et al.* (2011) and Keizrul (2006) agreed that the water problems being experienced by Malaysia today is not about having too little water to satisfy our needs especially in agriculture but it is a problem of ineffective water management. Haque *et al.* (2006) supported that poor management of available water for irrigation at the system and farm level caused aggravated water availability and further reduced the benefits of irrigation investments.

Global warming causes climate change and the most affected area of the world is South East Asian which located in the tropical region where it cause productivity loss, varying monsoon pattern and water scarcity (Dewi, 2009). Malaysia is blessed because it receives abundant amount of rainfall each year. The average annual rainfall for Peninsular Malaysia, Sabah and Sarawak are 2400 mm, 2360 mm and 3830 mm respectively (Che-Ani *et al.*, 2009). However, Malaysia is experiencing occasional water shortages (David, 2004).

The largest granary area for Malaysia which is Muda Irrigation Scheme was experienced six incidents of drought in the period of 1977 until 1992 (Mon & Chang, 2008). Water supply for irrigation and domestic use in Perlis is mainly supplied from Muda, Pedu and Timah Tasuh dams. However, the recent severe drought have cause the water level in these dams dropped to the critical level (Issa *et al.*, 2012a). The Muda and Pedu dam have experienced critical low water storage in 1978, 1987, 1991 and 1998 that caused paddy farmer forego the off-season planting (Jamalluddin & Sing, 2003). In early 2006, Kedah and Perlis received less rainfall than normal and

consequently, off-season planting was delayed and almost to be cancelled (Keizrul, 2006). The water shortages in Malaysia caused farmers face deficiencies in water deliveries and further reduce the rice yield (Keizrul, 2006; Mon & Chan, 2008) and reduce farmer's income (Haque *et al.*, 2006).

Lee *et al.* (2005a) proposed a new schedule for cropping calendar of Besut irrigation Scheme to overcome water scarcity during off-season planting. During February 2010, Malaysia again faced the drought. It was estimated that 184 hectares of Melaka paddy plantation area was affected because the canal become dry and therefore, water cannot be supplied to the field block (“Kemarau jejas lima kawasan sawah di Melaka”, 2010). Jamalluddin and Sing (2003) expected that frequency and intensity of drought in Malaysia will increase in the future. Chan (2009) caution that there are now increasingly frequent occurrences of drought and water stress in recent years as happen in Malacca, Selangor and parts of East Malaysia.

The surface water resources in Malaysia also become more polluted from year to year. Haliza (2007) supported that the development of urban area, industrial and commercial activities has contributed to river pollution. Consequently, the number of Malaysia's river categorized in Class I and Class II was decreasing while in Class IV and Class V was increasing. According to National Water Resource Study, NWRS (2000a), the river basins that classified as Class III and need extensive advance treatment prior being used as water supply are Sg. Linggi at Kg. Baru Mambau, Sg. Pahang at Bentong, Sg. Perak at Bagan Datok, Sg. Melaka at Alor Gajah and Sg. Selangor at Batang Berjuntai.

Department of Environment, DOE (2009) reported that from 1063 water quality monitoring stations involved 577 rivers monitored, 578 (54%) monitoring stations were classified as clean, 378 (36%) slightly polluted and remaining 107 (10%) were polluted. The report also shows that there was a reduction in river water quality in 2009 compared to 2008 due to increase numbers of polluting sources for instance sewage treatment plant, manufacturing industries and palm oil mills. The river pollution affecting paddy plantation since most of irrigated water is diverted from river.

The National Economic Action Council (NEAC) has identified groundwater as one of the alternative water resources for Malaysia that has the good potential to be developed (Heng, 2004) including the dry areas like Perlis (Issa *et al.*, 2012b). Mazlin *et al.* (2008) agreed that groundwater resources need to be explored and sustainably developed especially in water stressed and isolated areas. Khardzir (2006) stated that the development of groundwater as alternatives water supply is the right action to satisfy the increasing water demand. Groundwater irrigation is better compared to traditional surface water irrigation in terms of more reliable supplies, less influence by drought and ready accessibility for individual users (Garrido *et al.*, 2006; Lloyd, 1981).

1.2 Problem Statement

Water is very important for agriculture especially for rice cultivation in tropical region. A large amount of water is required for land preparation and growing stage of rice cultivation. Groundwater has been identified as alternative water sources for irrigation in rice cultivation areas during drought and off-season planting. However, studies need to be made in advance to assess the aquifer potential and its hydraulic characteristics. Seberang Perak, Perak, Malaysia is located at the Teluk Intan district. Based on Quaternary Geology Study of Teluk Intan Area, Perak Darul Ridzuan by Hoong (1992), Seberang Perak shallow aquifer has a good potential to be developed and used for irrigation due to existence of available freshwater at the upper part of the aquifer and low water table at this area. However, there is no detail study and systematic study on the shallow aquifer hydraulic characteristics at this area.

The present study was conducted to evaluate the storage and transmissive property of Seberang Perak shallow aquifer by conducting pumping test. Currently, the farmers use surface water as the main water resources for rice cultivation. The study on well performance evaluation as well as simulation approach to investigate the effects of the multiple pumping well on drawdown at the study area was also conducted. The tube well developed can act as point water source near cultivation plot and at the same time, it is suitable to be developed for the plot which is located far away from main canal in order to supply enough water and save irrigation time. The data on aquifer hydraulic characteristics and potential well yield are vital in groundwater monitoring and planning for the future groundwater development.

1.3 Objectives of the Study

The main objective of this research is to evaluate the groundwater potential of Seberang Perak aquifer, Perak, Malaysia. This quantitative study was conducted to meet the demand of groundwater as source of irrigation for paddy cultivation at Seberang Perak Integrated Agricultural Development Area (IADA Seberang Perak).

The specific objectives of this research are:

- i. To determine hydraulic characteristics of the aquifer from pumping test based on constant discharge pumping test.
- ii. To evaluate the performance of the pumping well by using step-drawdown pumping test.
- iii. To predict the effect of water table drawdown pattern from different scenarios of abstracting rate for rice cultivation.

1.4 Scope of the Study

- i. This study will focus on evaluating groundwater potential at Seberang Perak aquifer for rice cultivation by conducting pumping test.
- ii. The pumping test consists of two components which are constant discharge pumping test and step-drawdown pumping test. Constant discharge pumping test was carried out to evaluate aquifer performance of the research area. The step drawdown pumping test was carried out to determine the performance or efficiency of the tube well that have been constructed.
- iii. The results of pumping test data can be used to analyze the effects of groundwater abstraction from multiple pumping well by using AquiferTest Pro V4.2 software.

1.5 Limitations of the Study

Evaluation of groundwater potential is one of the in-situ tests for estimating hydraulic characteristics of the aquifer for irrigation of the paddy crop. The area of study limited to the Seberang Perak area with the shallow aquifer type (less than ten meter depth). This research was only focusing on shallow aquifer only because of the limited tube well at the research area as well as high costing in developing new tube well. The result of pumping test was obtained during off season in order to reduce the dependence on rain water along the season during rice cultivation and to avoid direct recharge to the aquifer system.

1.6 Organization of the Thesis

Five chapters are presented in this thesis. The chapters will include the theoretical part of the study, methodology, result and discussion. Chapter one roughly explains about background of the study, the problem statement, the objectives of the study, the scope as well as the limitation of the study. Chapter two of the thesis is concerned mostly with the role of groundwater in the hydrologic cycle, the utilization of groundwater in Malaysia, parameter of hydraulic characteristic of the aquifer and the method of analyzing pumping test data. Chapter three covers general geology and hydrogeology of the research area, execution of constant discharge pumping test, execution of step drawdown pumping test and drawdown prediction from multiple pumping well. Chapter four describes the analysis of aquifer performance by using AquiferTest Pro V4.2 software, well performance analysis, and estimation of groundwater abstraction from four different selected scenarios. The last chapter contains conclusions and the recommendations for the future research.

REFERENCES

- Abdulaziz, S.A., Saleh, A.A., and Abdulaziz, A.A. (1993). Determination of unconfined parameters using Boulton, Neuman and Streltsova methods. *Journal King Saud University*, 5(2): 155-170.
- Abdullah, M.H, Aris, A.Z. and Praveena, S. M. (2010). A numerical modeling of seawater intrusion into an oceanic island aquifer, Sipadan Island, Malaysia. *Sains Malaysiana*, 39(4): 525-532.
- Agarwal, R.G. (1980). A new method to account for producing time effects when drawdown type curves are used to analyse pressure buildup and other test data, SPE Paper 9289. The paper presented at the 55th SPE Annual Technical Conference and Exhibition, Dallas, Texas, Sept. 21-24.
- Ahmadi, H., Samani, A.N. and Malekian, A. (2010). The qanat: a living history of Iran. In *Water and Sustainability in Arid Region*, G. Schneier-Madanés & M.F. Courel (Eds), pp. 125-138, Netherlands: Springer.
- Akinbile, C.O., Abd El-Latif, K.M., Rozi, A. and Yusoff, M.S. (2011). Rice production and water use efficiency for self-sufficiency in Malaysia: a review. *Trends in Applied Sciences Research*, 6(10): 1127-1140.
- Almayani, M.S., and Şen, Z. (1993). Determination of hydraulic conductivity from complete grain-size distribution curves. *Ground Water*, 31(4): 551-555.
- Amer, K.M. (2008). Groundwater resources sustainability in Qatar: problems and perspective. In *Groundwater for Sustainable Development: Problems, Perspectives and Challenges*, Bhattacharya, P., Ramanathan, A.L., Mukherjee, A.B., Bundschuh, J., Chandrasekharam, D. and Keshari, A.K (Eds). London: Tylor & Francis.
- American Water Works Association, AWWA, (1973). *Ground Water, AWWA Manual M21*. United States of America: American Water Works Association.
- Aqtesolv (2011). AQuifer TESt SOLVer, Advanced Software for Pumping Tests, Slug Tests and Constant-Head Tests. Retrieved from <http://www.aqtesolv.com/> on 20 December, 2011.
- Aris, A.Z., Abdullah, M.H, Ahmad, A., and Woong, K.K. (2007a). Controlling factors of groundwater hydrochemistry in a small island's aquifer. *Int. J. Environ. Sci. Tech.*, 4(4): 441-450.
- Aris, A.Z., Abdullah, M.H, Ahmad, A., and Woong, K.K. (2007b). Hydrogeochemistry of groundwater in Manukan Island, Sabah. *The Malaysian Journal of Analytical Sciences*, 11(2): 407-413.
- Aris, A.Z., Abdullah, M.H, and Praveena, S. M. (2009a). Evolution of groundwater in the shallow aquifer of a small tropical island in Sabah, Malaysia. *Sains Malaysiana*, 38(6): 805-812.

Aris, A.Z., Abdullah, M.H, Kim, K.W., and Praveena, S. M. (2009b). Hydrochemical changes in a small tropical island's aquifer: Manukan Island, Sabah, Malaysia. *Environ Geol*, 56: 1721-1732.

Azuhan, M. (1985). Groundwater Resources for Agricultural use in Malaysia. Paper presented at the Conference of Groundwater and Mineral Exploration, Bangkok. June 1985.

Azwan, M.M.Z., Sa'ari, M. and Zuzana, P. (2010). Determination of water requirement in a paddy field at Seberang Perak rice cultivation area. *Journal-The Institution of Engineers, Malaysia*, 71(4): 32-41.

Azwan, M.Z.Z (2008). Technical study on resistivity test at Seberang Perak, Malaysia. Unpublished report.

Babiker, I. S., Mohamed, M.M.A, and Hiyama, T. (2007). Assessing groundwater quality using GIS. *Water Resource Management*, 21: 699-715.

Bachik, A.R. (2000). Groundwater Potential of Kuala Selangor - Batang Berjuntai - Tanjung Karang, Selangor (Report No: GPH 01/2000). Kuala Lumpur: Department of Minerals and Geoscience Malaysia.

Bierschenk, W.H. (1964). Determining well efficiency by multiple step-drawdown tests. *International Association of Scientific Hydrology*, 64: 493-507.

Biswas, A.K. (1985). Ancient urban water supply. *GeoJournal*, 11(3): 207-213.

Boonstra, J. (1989). *SATEM: Selected Aquifer Test Evaluation Methods*. Netherland: International Institute for Land Reclamation and Improvement, (ILRI).

Boulton, N. S. (1970). Analysis of data from pumping tests in unconfined anisotropic aquifers. *Journal of Hydrology*, 10: 369-378.

Boulton, N. S. (1973). The influence of delayed yield on data from pumping tests in unconfined aquifers. *Journal of Hydrology*, 19: 157-169.

Boulton, N. S. and Pontin, J.M.A. (1971). An extended theory of delayed yield from storage applied to pumping tests in unconfined anisotropic aquifer. *Journal of Hydrology*, 14: 53-65.

Brassington, R. (2007). *Field Hydrogeology* (3rd ed.). London: John Wiley & Sons.

Burmil, S. (2003). Landscape and water in the Oases of Egypt's Western. *Landscape Research*, 28(4): 427-440.

Chan, N.W. (2009). Issues and challenges in water governance in Malaysia. *Iran. J. Environ. Health. Sci. Eng.*, 6(3): 143-152.

Che-Ani A.I., Shaari, N., Sairi, A., Zain, M.F.M. and Tahir, M.M. (2009). Rainwater harvesting as an alternative water supply in the future. *European Journal of Scientific Research*, 34(1): 132-140.

Cheong, J., Hamm, S., Kim, H., Ko, E., Yang, K. And Lee, J. (2008). Estimating hydraulic conductivity using grain-size analyses, aquifer tests, and numerical modeling in a riverside alluvial system in South Korea. *Hydrogeology Journal*, 16: 1129-1143.

Cooper, N.N. and Jacob, C.E. (1946). A generalized graphical method for evaluating formation constants and summarizing well field history. *Trans. Am. Geophys. Union*, 27(4): 526-534.

David, W. P. (2004). Water resources and irrigation policy issues in Asia. *Asian Journal of Agriculture and Development*, 1(1): 83-106.

Department of Environment, DOE (2009). Malaysia Environmental Quality Report 2009, Department of Environment Malaysia. Retrieved from <http://www.doe.gov.my/portal/publication-2/browse/Publication%20%20Penerbitan/> on 15 November 2010.

Dewi, P.P. (2009). Climate change impacts on tropical agriculture and the potential of organic agriculture to overcome these impacts. *As. J. Food Ag-Ind.*, Special Issue: 10-17.

Domenico, P.A. and Schwartz, F.W. (1998). *Physical and Chemical Hydrogeology* (2nd ed.). United States of America: John Wiley & Sons.

Dorsihah, M.J. (2006). Hydrogeological Investigation in the Kompleks Pertanian Titi Gantung, Bota, Perak. Paper presented in JMG Annual Conference.

Dorsihah, M.J. and Azmer, M.A. (1999). *Groundwater Potential in the Villages at Kuala Muda and Padang Terap District, Kedah*. Kuala Lumpur: Department of Minerals and Geoscience Malaysia.

Driscoll, F.G. (1986). *Groundwater and Wells* (2nd ed.). St. Paul, MN: Johnson Division.

Ezeh, C.C. (2011). Geoelectrical studies for estimating aquifer hydraulic properties in Enugu State, Nigeria. *International Journal of the Physical Sciences*, 6(4): 3319-3329.

Fetter, C.W. (2004). Hydrogeology: A Short History Part 1. *Groundwater*, 42(5), 790-792.

Fitts, C.R. (2002). *Groundwater Science*. London: Academic Press.

Gandhi, V.P., and Namboodiri, W.P. (2009). Groundwater Irrigation in India: Gains, Costs and Risks (Report No: 2009-03-08). Indian Institute of Management Ahmedabad, India. Retrieved from <http://www.iimahd.ernet.in/publications/data/2009-03-08Gandhi.pdf>

Garrido, A., Martínez-Santos, P. and Llamas, M.R. (2006). Groundwater irrigation and its implications for water policy in semiarid countries: the Spanish experience. *Hydrogeology Journal*, 14: 340-349.

Gloaguen, E., Chouteau, M., Marcotte, D. And Chapuis, R. (2001). Estimation of hydraulic conductivity of an unconfined aquifer using cokriging of GPR and hydrostratigraphic data. *Journal of Applied Geophysics*, 47: 135-152.

Hakim, M.A., Juraimi, A.S., Begum, M., Hasanuzzaman, M., Uddin, M.K., Islam, M.M. (2009). Suitability Evaluation of Groundwater for Irrigation, Drinking, and Industrial Purposes. *American Journal of Environmental Sciences*, 5(3): 413-419.

Haliza, A.R. (2007). Suatu Tinjauan Terhadap Isu Pencemaran Sungai di Malaysia. Paper presented at Geography Conference 2007, 8-9 September 2007.

Han, Z., Wang, H., and Chai, R. (2006). *Transboundary Aquifers in Asia with Special Emphasis to China*. Beijing: United Nations Educational, Scientific, and Cultural Organization, UNESCO.

Haque, M.A., Lee, T.S. and Bockari-Gevao, S.M. (2006). Water distribution and water use assessment in rice cropping system. *Songklanakarin J. Sci. Technol.*, 28(4): 841-851.

Hasan, D., Norhan, A.R. and Kamarul, A.M.N. (2000). Aquifer simulation model in Tioman Island. *Journal of Civil Engineering*, 12(2): 33-46.

Hatta, M.A.K. (2010). Overview of groundwater resources in Malaysia. 3rd & 5th Groundwater Workshop, 14 – 16 June 2010, National Hydraulic Research Institute Malaysia, NAHRIM.

Heng, C.L (2004). *Groundwater Utilization and Management in Malaysia*. Paper presented at the meeting of the Coordinating Committee for Geoscience Programmes in East and Southeast Asia, Tsukuba. Nov. 2004.

Hiscock, K. (2005). *Hydrogeology Principles and Practice*. United Kingdom: Blackwell Publishing.

Ho, S.C. (1996). Vision 2020: towards an environmentally sound and sustainable development of freshwater resources in Malaysia. *GeoJournal*, 40(1-2): 73-84.

Hoong, L. H. (1992). *Quaternary Geology of the Teluk Intan Area, Perak Darul Ridzuan*. Kuala Lumpur: Geological Survey of Malaysia.

Hosseini, S.A., Shahraki, S.Z., Farhudi, R., Hosseini, S.M., Salari, M. and Pourahmad, A. (2010). Effectt of urban sprawl on a traditional water system (qanat) in the city of Mashhad, NE Iran. *Urban Water Journal*, 7(5): 309-320.

Huat, B.B.K., Hossein, M., Fatimah, M., Afshin, A. and Mohammad, T.A. (2011). Groundwater quality assessment of Labuan Island using GIS. *Electronic Journal of Geotechnical Engineering*, 16: 463-475.

Hudak, P.F. (2005). *Principles of Hydrogeology* (3 rd ed.). United States of America: CRC Press.

Hussain, I., Abu-Rizaiza, O.S., Habib, M.A.A. and Ashfaq, H. (2008). Revitalizing a traditional dryland water supply system: the karezes in Afghanistan, Iran, Pakistan, and the Kingdom of Saudi Arabia. *Water International*, 33(3): 333-349.

IADA Seberang Perak, (2011). Official website of Pejabat Jurutera Projek Kawasan Pembangunan Pertanian Seberang Perak. Retrieved from <http://iadasptb.gov.my/profail.php?&date=5-2008> on 15 January 2011.

Idrissy, E.H.E and Smedt, F. (2007). A comparative study of hydraulic conductivity estimations using geostatistics. *Hydrogeology Journal*, 15: 459-470.

Islam, M. S. (2006). Effect of abstraction on permeability and hydraulic gradient in a simulated unconfined aquifer using sand tank model. *Journal of Agriculture and Rural Development*, 4 (1&2): 143-148.

Ismail, T., Anuar, S. and Saim, S. (2011). Groundwater contamination in North Kelantan: how serious?, In *Geoscientis and Ethics for a Sustainable Society*, Proceeding National Geoscience Conference, Johor Bahru, Johor, June. 11-12, 2011. Ng, T.F. Ed.; Geological Society Malaysia: Kuala Lumpur, 2011.

Issa, A. K. M., Arof, Z. M., Yahaya, A. N., Yusof, K. W., Ibrahim, N. M. and Salleh, M.S (2012a). Using the Arau Model to locate groundwater potential zones in the northern regions of Malaysia. *Journal Intelek UiTM Perlis*, 7(1):15-21.

Issa, A. K. M., Sabariah, B., Shafa, N.E.M., Khairri, A., Juliana, M., Juwita, A., Shazwani, N.M. and Norlia, M.I. (2012b). A review on groundwater quality for domestic consumers' consumption in Perlis. *Journal Intelek UiTM Perlis*, 7(1):22-27.

Jamalluddin, A. S. and Sing, L. K. (2003). Droughts in Malaysia: a look at its characteristics, impacts, related policies and management strategies. Paper presented in Water and Drainage 2003 Conference. April, 28-29, 2003, Kuala Lumpur.

Japan International Cooperation Agency, JICA (1982). Sectoral Report No. 3. National Water Resources Study, Malaysia.

Jha, M.K., Jayalekshmi, K., Machiwal, D., Kamii, Y. and Chikamori, K. (2004). Determination of hydraulic parameters of an unconfined alluvial aquifer by the floodwave-response technique. *Hydrogeology Journal*, 12: 628-642.

Keizrul, A. (2006). *Managing Water Resources in Malaysia: The use of Isotope Technique and its Potential*, Proceedings of Seminar on Water Resources and Environment, Application of Nuclear and Related Technologies, Bukit Merah, Perak, Apr. 3 -5, 2006. Department of Irrigation and Drainage Malaysia: Kuala Lumpur.

Kemarau jejas lima kawasan sawah di Melaka (2010, February, 18). *Utusan Malaysia*, p. 14.

Kemper, K.E. (2004). Groundwater: from development to management. *Hydrogeology Journal*, 12: 3-5.

Khardzir, M. H (2006). The Resistivity Imaging Application in Groundwater Exploration: Resistivity Value and Soil Type. In *Proceedings of Seminar on Water Resources and Environment, Application of Nuclear and Related Technologies*, Bukit Merah, Perak, Apr. 3 -5, 2006. Kuala Lumpur: Department of Irrigation and Drainage Malaysia.

Krásný, J. (1993). Classification of transmissivity magnitude and variation. *Ground Water*, 31(2): 230-236.

Kruseman and de Rider (1994). *Analysis and Evaluation of Pumping Test Data* (2nd ed.). Netherlands: International Institute for Land Reclamation and Improvement (ILRI).

Labadie, J.W. and Helweg, O.T. (1975). Step-drawdown test analysis by computer. *Ground Water*, 13(5): 438-444.

Lee, T.A., Aminul, M.H. and Najim, M.M.M. (2005a). Scheduling the cropping calendar in wet-seeded rice schemes in Malaysia. *Agricultural Water Management*, 71: 71-84.

Lee, T.A., Aminul, M.H. and Najim, M.M.M. (2005b). In-time rice irrigation water management under limited water supply. *Pertanika Journal of Science and Technology*, 13(1): 97-111.

Lightfoot, D.R. (2002). The origin and diffusion of qanats in Arabia: new evidence from northern and southern peninsula. *The Geographical Journal*, 166 (3): 215-226

Lin, C.Y., Abdullah, M.H., Aris, A.Z., and Preevana, S.M. (2009). A baseline study on groundwater quality of the tourist island, Pulau Tiga, Sabah, Malaysia. *Modern Applied Science*, 3(5): 62-74.

Lin, C.Y., Abdullah, M.H., Musta, B., Aris, A.Z., and Preevana, S.M. (2010). Assesment of selected chemical and microbial parameters in groundwater of Pulau Tiga, Sabah, Malaysia. *Sains Malaysiana*, 39(3): 337-345.

Lloyd, J.W. (1981). *Case-Studies in Groundwater Resources Evaluation*. Clarendon Press.

Loáiciga, H.A. (2003). Climate change and ground water. *Annals of the Association of American Geographers*, 93(1): 30-41.

Loganathan, P. (1999). *Brief Introduction to Groundwater Investigations*. Kuala Lumpur: Department of Mineral and Geoscience Malaysia.

Loke, M.H. (1997). Electrical imaging surveys for environmental and engineering studies. Unpublished report.

Mahmad, N.J. Puteh, S. and Arjunan, S.N.V (2000). A computational model for water use efficiency in rice production. *Jurnal Teknologi Maklumat*, 12(1): 1-13.

Mailvaganam, Y., Ramli, M.Z., Rushton, K.R., and Ong, B.Y. (1993). Groundwater exploitation of a shallow coastal sand aquifer in Sarawak, Malaysia. Paper presented at the Symposium of Hydrology of Warm Humid Regions, Yokohama, July, 1993.

Mansell, M.G. and Hussey, S.W. (2005). An investigation of flows and losses within the alluvial sands of ephemeral rivers in Zimbabwe. *Journal of Hydrology*, 314: 192-203.

Mao, D., Wan, L., Yeh, T.J., Lee, C.H., Hsu, K.C., Wen, J.C. and Lu, W. (2011). A revisit of drawdown behaviour during pumping in unconfined aquifers. *Water Resources Research*, 47, W05502.

Mazlin B. M., Mohammad Fawzi, A. A. and Rahma, E. (2008). Integrated water resources management improving Langat Basin ecosystem health. *American Journal of Environmental Sciences*, 4(4): 380-382.

Miah, M.M. and Rushton, K.R. (1997). Exploitation of alluvial aquifers having an overlying zone of low permeability: examples from Bangladesh. *Hydrological Sciences Journal*, 42: 67-79.

Microfem (2011). Multi Layer Unsteady State for Windows. Retrieved from <http://www.microfem.com/> on 20 December 2011.

Millham, N.P. and Howes, B.L. (1995). A comparison of methods to determine K in a shallow coastal aquifer. *Ground Water*, 33(1): 49-57.

Mineral and Geoscience Department of Malaysia, MGD (2005). *Groundwater Manual*. Kuala Lumpur: Department of Mineral and Geoscience of Malaysia.

Ministry of Agriculture, MOA, (2010). Perangkaan Agromakanan 2010. Putrajaya: Ministry of Agriculture and Agro-Based Industry Malaysia.

Ministry of Agriculture, MOA, (2011). IADA: Kawasan Pembangunan Pertanian Bersepadu. Retrieved from <http://www.moa.gov.my/web/guest/pengenalan1> on 18 June 2011.

Mohammad, N. Bin Mahmood, M.A. bin Abdul Wahab, N.A. bin Idris Adam, A. (2011). Water resource management and administration in Malaysia: a case study on Melaka city for sustainability. Paper presented in Business Innovation and Technology Management (APBITM), IEEE International Summer Conference of Asia Pacific, Dalian, July, 2011.

Mohammed, T.A. and Huat, B.B.K. (2004). *Groundwater Engineering and Geotechnique*. Universiti Putra Malaysia: UPM Press.

Mon, L.K. and Chang, C.M. (2008). The impact of drought and flood on paddy cultivation in Muda Irrigation Scheme. Paper presented at 13th Malaysia Conference

on Irrigation and Drainage (13th MANCO), Kota Kinabalu, Sabah, February, 2-3, 2008.

Motiee, H., McBrean, E., Semsar, A., Gharabaghi, B. and Ghomashchi, V. (2006). Assessment of the contributions of traditional qanats in sustainable water resources management. *Water Resources Development*, 22(4): 575-588.

Munit, A. K. (2010). Keluaran Padi 10 Tan Per Hektar Sukar. *Sinar Harian*, Saturday, 31 Julai 2010.

Nasiman, S., Raja Zainariah, R.A., and Hisyam, J. (2010). Quantity and quality of groundwater in fractured metasedimentary rocks of the west coast of Peninsular Malaysia. *Sains Malaysiana*, 40(6): 537-542.

National Water Resources Study, NWRS(2000a). National Water Resources Study 2000 – 2050, Volume 1. SMHB Sdn Bhd, Ranhill and Perunding Zaaba Sdn Bhd.

National Water Resources Study, NWRS(2000b). National Water Resources Study 2000 – 2050, Volume 2. SMHB Sdn Bhd, Ranhill and Perunding Zaaba Sdn Bhd.

National Water Resources Study, NWRS(2000c). National Water Resources Study 2000 – 2050, Volume 4. SMHB Sdn Bhd, Ranhill and Perunding Zaaba Sdn Bhd.

National Water Resources Study, NWRS(2000d). National Water Resources Study 2000 – 2050, Volume 11. SMHB Sdn Bhd, Ranhill and Perunding Zaaba Sdn Bhd.

Nazan, M.A. (1998). *An Overview of Groundwater Resources Potential in Malaysia*. Paper presented at the Seminar World Day for Water 1998 - Groundwater, The Invisible Resources, UPM. March 1998.

Nonner, J.C. (2010). *Introduction to Hydrogeology* (2ed. ed.). London: CRC Press.

Noorain, M.I. and Aris, A.Z. (2012). Preliminary assessment on the hydrogeochemistry of Kapas Island, Terengganu. *Sains Malaysiana*, 41(1):23-32.

Norhan, A.R. and Kuan, W.K. (2004). Simulation of groundwater flow and pollutant transport for alluvial aquifer in Kampung Tekek, Tioman Island. *Jurnal Teknologi*, 41(B): 21-34.

Odong, J. (2008). Evaluation of empirical formulae for determination of hydraulic conductivity based on grain-size analysis. *The Journal of American Science*, 4(1): 1-6.

Oosterbaan, R.J. and Nijland, H.J. (1994). *Drainage Principles and Applications*. Wageningen, Netherlands: International Institute for Land Reclamation and Improvement (ILRI).

Patra, K.C. (2008). *Hydrology and Water Resources Engineering* (2nd. ed.). India: Alpha Science International Ltd.

Pimentel, D., Berger, B., Filiberto, D., Newton, M., Wolfe, B., Karabinakis, E., Clark, S., Poon, E., Abbett, E. and Nandagopal, S. (2004). Water Resources: Agricultural and Environmental Issues. *BioScience*, 54 (10): 909-918.

Prastowo, Hardjoamidjojo, S., Pramudya, B., Murti Laksono, K. (2007). Performance of Shallow Groundwater Irrigation Schemes in Nganjuk-East Java, Indonesia. *CIGR Ejournal*, Manuscript LW 07 013. Vol. IX.

Praveena, S.M. and Aris, A.Z. (2010). Groundwater resources assessment using numerical model: a case study in low-lying coastal area. *Int. J. Environ. Sci. Tech.* 7(1): 135-146.

Praveena, S.M., Aris, A.Z., Harun, M.A. and Kawi, B. (2010a). A brief review of groundwater studies in Malaysia. *Journal of Sustainability Science and Management*, 5(2): 123-133.

Praveena, S.M., Lin, C.Y., Aris, A.Z. and Abdullah, M.H. (2010b). Groundwater assessment at Manukan Island, Sabah: multidisciplinary approaches. *Natural Resources Research*, 19(4): 279-291.

Price, M. (1996). *Introducing Groundwater*. London: Chapman & Hall.

Quilang, E.J.P., Guerra, L., Ramirez, A., Hernandez, J. and Maki, T. (2004). Effect of ground water irrigation on paddy rice yield in Maligaya, Philippines. *J. Agric. Meteorol*, 60(2): 95-104.

Raghunath, H.M. (2007). *Ground Water* (3rd ed.). New Delhi: New Age International Publishers.

Rahman, M. (1981). Ecology of karez irrigation: A case of Pakistan. *GeoJournal*, 5(1): 7-15.

Rosegrant, M.W., Cai, X. and Cline, S.A. (2002). *World Water and Food to 2025: Dealing with Scarcity*. Washington D.C: International Food Policy Research Institute.

Rowshon, M. K., Amin, M. S. M. and Shariff, A. R. M. (2012). Geospatial water productivity index (WPI) for Rice. *Pertanika Journal of Science and Technology*, 20 (2): 381-399.

Sabrina, M.A. (2009). A GIS mapping and development of groundwater database at Seberang Perak rice cultivation area. Bachelor Degree Project. Unpublished report.

Sadashivaiah, C Ramakrishnaiah, C.R. and Ranganna, G. (2008). Hydrochemical analysis and evaluation of groundwater quality in Tumkur Taluk, Karnataka state, India. *Int. J. Environ. Res. Public Health*, 5(3): 158-164.

Saim, S and Zahir, Y. (2009). Overview of hard rock aquifers in Peninsular Malaysia. Paper presented at Joint International Convention of 8th IAHS Scientific Assembly and 37th IAH Congress, September 6-12, 2009.

Samsudin, A.R., Haryono, A., Hamzah, U., and Rafek, A.G. (2008). Salinity mapping of coastal groundwater aquifers using hydrogeochemical and geophysical methods: a case study from north Kelantan, Malaysia. *Environ. Geol.*, 55: 1737-1743.

Sani, K., and Azuhan, M., (1988). Groundwater Exploration for Supplemental Paddy Irrigation For New Rice Area in Bertam: A Case Study. Malaysia Department of Irrigation and Drainage.

Schlumberger (2007). *AquiferTest Pro 4.2 User's Manual*. Canada: Schlumberger Water Services.

Schwartz, F.W., and Zhang, H. (2003). *Fundamentals of Ground Water*. New York: John Wiley & Sons.

Scisoftware (2011). Pump Test and Slug Test Software. Retrieved from www.scisoftware.com on 20 December 2011.

Şen, Z. (1984). Adaptive pumping test analysis. *Journal of Hydrology*, 74: 259-270

Şen, Z. (1985). Volumetric approach to type curves in leaky aquifers. *Journal of Hydraulic Engineering*, 111(3): 467-484.

Şen, Z. (1995). *Applied Hidrogeology for Scientists and Engineers*: United States of America. CRC Press.

Shah, T., Molden, D., Sakthivadivel, R. and Seckler, D. (2001). Global groundwater situation: opportunities and challengers. *Economic and Political Policy*, 36(43): 4142-4150.

Shah, T., Singh, O.P., and Mukherji, A. (2006). Some aspects of South Asia's groundwater irrigation economy: analysis from survey in India, Pakistan, Nepal Terai and Bangladesh. *Hydrogeology Journal*, 14: 286-309.

Shepherd, R.G. (1989). Correlations of permeability and grain size. *Ground Water* 27(5): 633-638.

Siebert, S., Burke, J., Faures, J.M., Frenken, K., Hoogeveen, J., Döll, P. and Portmann, F.T. (2010). Groundwater use for irrigation – a global inventory. *Hydrol. Earth Syst. Sci.*, 14: 1863-1880.

Sime Darby, (2009). Sime Darby unveils its Pilot Groundwater Project in Perak. Retrieved from http://www.simedarby.com/Sime_Darby_Unveils_Its_Pilot_Groundwater_Project_In_Perak.aspx

Taniguchi, M., Burnett, W.C., Cable, J.E. and Turner, J.V. (2002). Investigation of submarine groundwater discharge. *Hydrological Processes*, 16: 2115-2129.

Theis, C.V. (1935). The relation between the lowering of the piezometric surface and the rate and duration of discharge of a well using groundwater storage. *Am. Geophys. Union Trans.*, 16: 519-524.

Todd, D.K. & Mays, L.W. (2005). *Groundwater Hydrogeology* (3rd ed.). United States of America: John Wiley & Sons.

Trincherro, P., Sanchez-Vila, X., Coptly, N. and Findikakis, A. (2008). A new method for the interpretations of pumping tests in leaky aquifers. *Ground Water*, 46(1): 133-143.

Uma, K.O., Egboka, B.C.E., and Onuoha, K.M. (1989). New statistical grain-size method for evaluating the hydraulic conductivity of sandy aquifers. *Journal of Hydrology*, 108: 343-366.

United Nations Environment Programme, UNEP (2011). Water withdrawal and consumption: a big gap. UNEP/GRID-Arendal Maps and Graphics Library. Available at :<http://maps.grida.no/go/graphic/water-withdrawal-and-comsuption-the-big-gap>. Accessed December, 20, 2011.

United States Geological Survey, USGS (2011). Spreadsheets for the Analysis of Aquifer-Test and Slug-Test Data, Version 1.2. Retrieved from <http://pubs.usgs.gov/of/2002/ofr02197/> on 20 December 2011.

Vienken, T. And Dietrich, P. (2011). Field evaluation of methods for determining hydraulic conductivity from grain size data. *Journal of Hydrology*, 400: 58-71.

Villholth, K.G. and Giordano, M. (2007). Groundwater use in a global perspective – can it be manage?. In *The Agricultural Groundwater Revolution: Opportunities and Threats to Development*. CAB International.

Vithijumnonk, K. (1982). Using Groundwater for Irrigation in Small-Scale Farming, Proceeding of Water Technology Towards Rural Development, University of Agriculture, Selangor, Malaysia, Jan. 19-22. Amin, M.M.S, Yan,K.C. and Rosnah, M.Y Ed.; University of Agriculture: Serdang.

Vrba, J. and Lipponen, A. (eds). (2007). *Groundwater Resources Sustainability Indicators*. Paris: United Nations Educational, Scientific and Cultural Organization (UNESCO), IHP-VI Series on Groundwater No. 14.

Walton, W.C. (1960). *Leaky Artesian Aquifer Conditions in Illinois*. Report of Investigation 39, Urbana: Illinois State Water Survey.

Watson, I. and Burnett, A. (1993). *Hydrogeology: An Environmental Approach*. Unites States of America: Hallmark Press.

Weight, W.D. and Sonderegger, J.L. (2001). *Manual of Applied Field Hydrogeology*. United States of America: McGraw-Hill.

Whitlow, R. (1995). *Basic Soil Mechanics* (3rd. ed.). United Kingdom: Pearson Education Limited.

Whitlow, R. (2001). *Basic Soil Mechanics* (4rd. ed.). United Kingdom: Pearson Education Limited.

Winter, T.C., Harvey, J.C., Franke, O.L. and Alley, W.M. (1998). *Groundwater and Surface Water: A Single Resources*. U.S. Geological Survey Circular: 1139. Retrieved from <http://pubs.usgs.gov/circ/circ1139/>

Yahya, Z. (2005a). *Groundwater Potential at Post 5, Wataniah Army Camp, Bukit Kayu Hitam, Kedah* (Report No: JMG.KPPP (HG) 03/2005). Kuala Lumpur: Department of Minerals and Geoscience Malaysia.

Yahya, Z. (2005b). *Groundwater Potential at Kuala Muda District, Kedah* (Report No: JMG.KPPP (HG) 04/2005). Kuala Lumpur: Department of Minerals and Geoscience Malaysia.

Yeh, H.D. (1989). Step-drawdown data analysis. *Journal of Hydraulic Engineering*, 115: 1426-1432.

Zarabadi, Z.S.S. and Haeri, N. (2011). Qanat as the sustainable sign in during time. *International Journal of Academic Research*, 3(5): 425-429.

Zektser, I. S. and Everett, L.G. (eds). (2004). *Groundwater Resources of the World and Their Use*. Paris: United Nations Educational, Scientific and Cultural Organization (UNESCO), IHP-VI Series on Groundwater No. 6.

Zektser, I.S. (2000). *Groundwater and the Environment: Applications for the Global Community*. United States of America: Lewis Publishers.

Zektser, I.S. and Loáiciga, H.A. (1993). Groundwater fluxes in the global hydrologic cycle: past, present and future. *Journal of Hydrology*, 144: 405-427.

Zulherry, I. and Juhari, M.A. (2012). Using remote sensing and geographical information system (GIS) technology for mapping the groundwater potential in Kota Kinabalu, Sabah, Malaysia. *Electronic Journal of Geotechnical Engineering*, 17: 2299-2311.