



UNIVERSITI PUTRA MALAYSIA

***COMPOSTING EVALUATION OF OIL PALM EMPTY FRUIT
BUNCHES WITH PALM OIL EFFLUENT ANAEROBIC SLUDGE***

WAN AIZUDDIN BIN WAN RAZALI

FK 2014 74



UPM
UNIVERSITI PUTRA MALAYSIA
BERILMU BERBAKTI

**COMPOSTING EVALUATION OF OIL
PALM EMPTY FRUIT BUNCHES WITH
PALM OIL EFFLUENT ANAEROBIC
SLUDGE**

WAN AIZUDDIN BIN WAN RAZALI

**MASTER OF SCIENCE
UNIVERSITI PUTRA MALAYSIA**

2014



UPM
UNIVERSITI PUTRA MALAYSIA
BERILMU BERBAKTI

**COMPOSTING EVALUATION OF OIL PALM EMPTY FRUIT BUNCHES
WITH PALM OIL EFFLUENT ANAEROBIC SLUDGE**

By

WAN AIZUDDIN BIN WAN RAZALI

**Thesis Submitted to the School of Graduate Studies,
Universiti Putra Malaysia, in Fulfillment of the
Requirements for the Degree of Master of Science**

March 2014

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

COMPOSTING EVALUATION OF OIL PALM EMPTY FRUIT BUNCHES WITH PALM OIL EFFLUENT ANAEROBIC SLUDGE

By

WAN AIZUDDIN BIN WAN RAZALI

March 2014

Chairman: Azhari Samsu Baharuddin, PhD

Faculty: Engineering

Oil palm empty fruit bunches (OPEFB) are one of the most abundant lignocellulosic biomass produced in palm oil industry throughout the year. With the increasing demand for palm oil worldwide, the amount of oil palm biomass available is expected to grow and composting is one of the best approaches to solve the abundance of this waste. Palm oil mill effluent (POME) is also produced in huge quantities because the ratio of water required to the oil palm fresh fruit bunches (OPFFB) processed is usually 1:1 ratio. Hence, this project was conducted to evaluate the pressed-shredded OPEFB and palm oil mill effluent (POME) anaerobic sludge composting treatment. The project was divided with three stages: 1) Composting process by windrow system at pilot scale; 2) Combinational in-vessel and windrow system at pilot scale; and 3) Composting of OPEFB with formulating palm oil mill effluent biochar solution (POMEBS) aerobic sludge using a lab scale in-vessel composter. All the composting process was completed within 40 days. The process performance was further evaluated by structure degradation analysis using scanning electron microscopy (SEM), Fourier transform infrared (FTIR), Thermogravimetric analysis (TGA) and X-ray diffraction (XRD). The windrow system managed to produce compost with final nutrient contents of N:P:K at 2.6:0.7:3.2 and the final C/N ratio was 14.62. Combinational in-vessel and windrow system produced compost with final N:P:K which stabilized at 2.8:0.4:2.8 and the final C/N ratio was 13.85. Composting OPEFB and POMEBS aerobic sludge managed to produce compost with higher N:P:K which stabilized at 3.7:0.8:6.2 and the final C/N ratio was 10.16. For windrow system, SEM pictures showed that silica bodies were completely removed at day 10 while for combinational in-vessel and windrow system SEM showed silica bodies only partially removed after 7 days after come out from the composter and completely removed after day 20. FTIR results illustrated the chemical reaction of the composting process for transforming OPEFB into mature compost. The results from FTIR were also correlated with XRD and TGA. TGA results showed that composting of OPEFB with POMEBS aerobic sludge have a higher weight reduction of organic matter compared to composting of OPEFB with POME anaerobic sludge which were 21% and 10% respectively. Microbial community analysis by Polymerase Chain Reaction-Denaturing Gel Gradient Electrophoresis (PCR-DGGE) indicated that *bacillus subtilis strain TU2*, *bacillus Sp. MH-16*, uncultured bacterium clone, uncultured firmicutes bacterium, *bacillus Sp. Hs-v2*, *bacterium FA_149* and *bacillus subtilis strain TBR2* were the predominant species at the optimum condition of the POMEBS aerobic sludge. In conclusion, composting

OPEFB with POMEBS succeed in improving the degradation process and produced good quality compost.



© COPYRIGHT UPM

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**PENILAIAN TERHADAP PENGKOMPOSAN TANDAN KELAPA SAWIT
KOSONG DENGAN CECAIR ANAEROBIK ENAP CEMAR KELAPA
SAWIT**

Oleh

WAN AIZUDDIN BIN WAN RAZALI

March 2014

Pengerusi: Azhari Samsu Baharuddin, PhD

Fakulti: Kejuruteraan

Tandan kelapa sawit kosong merupakan salah satu sisa lignoselulosa yang banyak dihasilkan sepanjang tahun di dalam industri kelapa sawit. Dengan peningkatan permintaan terhadap minyak kelapa sawit di seluruh dunia, jumlah biomas yang terbiar dijangka turut bertambah dan pengkomposan merupakan salah satu langkah untuk mengatasi masalah lebihan sisa ini. Cecair enap cemar kilang kelapa sawit juga dihasilkan dalam kuantiti yang banyak dimana kuantiti air yang diperlukan untuk memproses buah kelapa sawit segar adalah 1:1. Oleh itu projek ini adalah untuk menilai pengkomposan ditekan-dicincang tandan kelapa sawit kosong dengan cecair anaerobik enap cemar kilang kelapa sawit. Projek ini dibahagikan kepada tiga peringkat: 1) Pengkomposan menggunakan sistem batas berskala pilot; 2) Pengkomposan menggunakan gabungan kontena tertutup dan sistem batas berskala pilot; dan 3) Pengkomposan sisa tandan kosong dengan formulasi cecair aerobik enap cemar kilang kelapa sawit dan arang menggunakan kontena tertutup kompos berskala kecil. Kesemua proses pengkomposan lengkap dalam tempoh 40 hari. Prestasi proses dinilai selanjutnya melalui analisis struktur degradasi menggunakan *scanning electron microscopy (SEM)*, *Fourier transform infrared (FTIR)*, *Thermogravimetric analysis (TGA)* and *X-ray diffraction (XRD)*. Sistem batas berjaya menghasilkan kompos dengan nutrisi akhir N:P:K pada 2.6:0.7:3.2 dan nisbah C/N ratio akhir sebanyak 14.62. Kombinasi kontena tertutup dan sistem batas berjaya menghasilkan nutrisi akhir N:P:K pada 2.8:0.4:2.8 dan nisbah C/N ratio akhir sebanyak 13.85. Pengkomposan tandan kelapa sawit kosong dan formulasi cecair aerobik enap cemar kilang kelapa sawit dan arang berjaya menghasilkan N:P:K yang lebih tinggi iaitu 3.7:0.8:6.2 dan nisbah C/N ratio akhir 10.16. Untuk sistem batas, gambar *SEM* menunjukkan badan-badan silika telah berjaya dibuang kesemuanya pada hari ke-10 sementara kombinasi kontena tertutup dan sistem batas menunjukkan hanya sebahagian badan-badan silika berjaya dibuang pada hari ke-7 selepas dibawa keluar dari kontena tertutup dan hanya berjaya dibuang keseluruhannya pada hari ke-20. *FTIR* menggambarkan tindak balas kimia yang berlaku semasa proses pengkomposan menukar tandan kelapa sawit kosong kepada kompos yang matang. Hasil dari *FTIR* kemudiannya dikaitkan dengan hasil analisis dari *XRD* dan *TGA*. Hasil *TGA* analisis menunjukkan pengkomposan tandan kelapa sawit kosong dan formulasi cecair aerobik enap cemar kilang kelapa sawit dan arang menunjukkan penguraian bahan organik adalah lebih tinggi berbanding pengkomposan tandan kelapa sawit kosong dengan cecair anaerobik enap cemar kilang kelapa sawit iaitu masing-masing 21% dan 10%. Analisis mikrobial

menggunakan tindak balas rantaian polimerasi-elektroporasi kecerunan gel denaturasi menunjukkan *bacillus subtilis strain TU2*, *bacillus Sp. MH-16*, *uncultured bacterium clone*, *uncultured firmicutes bacterium*, *bacillus Sp. Hs-v2*, *bacterium FA_149* and *bacillus subtilis strain TBR2* adalah jenis-jenis kelompok mikroorganisma mutlak yang berada dalam formulasi cecair aerobik enap cemar kilang kelapa sawit dan arang. Kesimpulannya, pengkomposan tandan kelapa sawit kosong dan formulasi cecair aerobik enap cemar kilang kelapa sawit dan arang berjaya meningkatkan proses degradasi dan menghasilkan kompos yang berkualiti.



ACKNOWLEDGEMENTS

I am making uncounted thanks to Allah the Almighty who has guided me to remember Him at this time. Nothing is possible unless He made it possible.

First and foremost I would like to express my deepest appreciation to my main supervisor, Dr. Azhari Samsu Baharuddin and the members of the supervisory committee, Associate Prof. Dr. Farah Saleena Taip, and Dr.-Ing Mohd Noriznan Mokhtar for their supervision of the research, valuable feedback, advice, encouragement and patience throughout the master study.

My gratitude to the Faculty of Engineering UPM, especially the Department of Process and Food Engineering that has granted me the opportunity to pursue this study.

Special thank you to Prof Ali Hassan and Faculty of Biotechnology and Science Biomolecule for gave me a change to do experimental study at Pilot Scale Composting Plant. Also, thank you is extended to FELDA Serting Hilir, Negeri Sembilan and Seri Ulu Langat Palm Oil Mill Staff that help me by providing materials for this study.

Last but not least, I want to send my heartfelt appreciation to my family and my friends for their constant encouragement and support.

I certify that a Thesis Examination Committee has met on 31 March 2014 to conduct the final examination of Wan Aizuddin bin Wan Razali on his thesis entitled “Composting Evaluation of Oil Palm Empty Fruit Bunches with Palm Oil Effluent Anaerobic Sludge” in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

Siti Mazlina binti Mustapa Kamal, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Rosnah binti Shamsudin, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Norashikin binti Abdul Aziz, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Ling Tau Chuan, PhD

Professor
University of Malaya
Malaysia
(External Examiner)



NORITAH OMAR, PhD

Associate Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 23 June 2014

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Azhari Samsu Baharuddin, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Farah Saleena Taip, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Mohd Noriznan Mokhtar, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Member)

BUJANG BIN KIM HUAT, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

DECLARATION

Declaration by Graduate Student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: _____

Date: 27 May 2014

Name and Matric No.: Wan Aizuddin bin Wan Razali (GS27963)

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: _____

Name of
Chairman of
Supervisory
Committee: _____

Signature: _____

Name of
Member of
Supervisory
Committee: _____

Signature: _____

Name of
Member of
Supervisory
Committee: _____

TABLE OF CONTENTS

	Page
ABSTRACT	ii
ABSTRAK	iv
ACKNOWLEDGEMENTS	vi
APPROVAL	vii
DECLARATION	ix
LIST OF TABLES	xiii
LIST OF FIGURES	xiv
LIST OF ABBREVIATIONS	xvi
CHAPTER	
1. INTRODUCTION	1
1.1. Treats to Climate Change	1
1.2. Overview on Composting of Organic Waste	2
1.3. Problem Statement	3
1.4. Objectives	5
1.5. Scope of Research	5
1.6. Thesis Structure	5
2. LITERATURE REVIEW	7
2.1. Introduction	7
2.2. Oil Palm in Malaysia	7
2.3. Oil Palm Empty Fruit Bunches (OPEFB)	8
2.3.1. Characteristic of OPEFB	8
2.3.2. Pressed-Shredded OPEFB	10
2.4. Palm Oil Mill Effluent (POME)	10
2.4.1. Characteristic of POME	11
2.4.2. POME Anaerobic Sludge	11
2.5. Composting Process	11
2.6. Composting System	12
2.6.1. Windrow Composting System	12
2.6.2. In-vessel Composting System	13
2.6.3. Microbial seeding formulation and modification	15
2.7. Factors Affecting Composting Process	15
2.7.1. Temperature	15
2.7.2. Oxygen level	16
2.7.3. Moisture Content	16
2.7.4. C/N Ratio	16
2.7.5. pH	16
2.8. Chemical Transformation	17
2.9. Compost Maturity and Stability	18
2.10. Summary	19
3. MATERIALS AND METHODS	20
3.1. Flow Chart of Experimental Design	20
3.2. Composting Establishment	21
3.2.1. Material Preparation	21

3.2.2. Composting Process	21
3.2.2.1. Windrow System at Pilot Scale	21
3.2.2.2. Combination In-Vessel Composter and Windrow System at Pilot Scale	23
3.2.2.3. Lab Scale In-Vessel System	25
3.3. Sampling	27
3.4. Analysis Methods	28
3.4.1. Determination of Temperature and Oxygen Level	28
3.4.2. Determination of Moisture Content and pH	28
3.4.3. Determination of Microbial Count	28
3.4.4. Determination of C/N ratio	29
3.4.5. Determination of Elements	29
3.4.6. Determination of Cellulose, Hemicellulose and Lignin	29
3.4.6.1. Determination of Neutral Detergent Fibre (NDF)	29
3.4.6.2. Determination of Acid Detergent Fibre (ADF)	30
3.4.6.3. Determination of Acid Detergent Lignin (ADL)	30
3.4.7. Determination of Chemical Oxygen Demand (COD)	31
3.4.8. Determination of Biological Oxygen Demand (BOD)	31
3.4.9. Determination of Total Solids (TS)	31
3.4.10. Determination of Total Suspended Solids (TSS)	32
3.4.11. Determination of Volatile Suspended Solids (VSS)	32
3.4.12. Scanning Electron Microscope (SEM)	32
3.4.13. X-ray Diffraction (XRD)	32
3.4.14. Fourier Transform Infrared (FTIR)	33
3.4.15. Thermogravimetric Analysis (TGA)	33
3.4.16. Polymerase Chain Reaction (PCR) - Denaturing Gradient Gel Electrophoresis (DGGE)	33
3.5. Summary	34
4. RESULTS AND DISCUSSION	36
4.1. Introduction	36
4.2. Assessment on Stability and Maturity of Oil Palm Empty Fruit Bunches (OPEFB) Composting by a Windrow System at Pilot Scale	37
4.2.1. Final Compost Properties	37
4.2.2. Composting Profiles of OPEFB	38
4.2.3. Lignocellulosic Structure Changes of OPEFB	41
4.2.4. X-ray Diffraction (XRD) Analysis	43
4.2.5. Fourier Transform Infrared (FTIR) Analysis	45
4.2.6. Thermogravimetric Analysis (TGA)	47
4.3. Lignocellulosic Structure Changes of Oil Palm Empty Fruit Bunches (OPEFB) Fibre during Composting Process using Combinational In-Vessel and Windrow System at Pilot Scale	49
4.3.1. Final Compost Properties	49
4.3.2. Composting Profiles of OPEFB	50
4.3.3. Lignocellulosic Structure Changes of OPEFB	53
4.3.4. X-ray Diffraction (XRD) Analysis	55
4.3.5. Fourier Transform Infrared (FTIR) Analysis	56
4.3.6. Thermogravimetric Analysis (TGA)	58
4.4. Effect of Seed Sludge Quality Using Oil Palm Empty Fruit Bunches (OPEFB) Biochar for Composting Process	60

4.4.1. Regression Analysis	60
4.4.2. Model Analysis	61
4.4.3. Optimization and Validation Experiments	63
4.4.4. Scanning Electron Microscopy (SEM)	63
4.4.5. Denaturing Gradient Gel Electrophoresis (DGGE)	64
4.4.6. Fourier Transform Infrared (FTIR) Analysis	65
4.4.7. Composting Profiles of OPEFB	66
4.4.8. Thermogravimetric Analysis (TGA)	68
4.4.9. Comparison of characterisation	70
5. CONCLUSION AND RECOMMENDATIONS FOR FUTURE WORK	72
5.1. Conclusion	72
5.2. Recommendations for Future Work	73
REFERENCES	74
APPENDICES	87
BIODATA OF STUDENT	92
LIST OF PUBLICATIONS	93

LIST OF TABLES

Table		Page
1.1	Mechanical properties of some important natural fibre	2
1.2	Chemical fertilizer consumption and OPEFB compost production estimation quantity	3
1.3	The capital cost of chemical fertilizer and revenue made by OPEFB compost production	4
2.1	Properties of fresh OPEFB and pressed-shredded OPEFB	8
2.2	Advantages and disadvantages with different type of turning equipment	12
2.3	Comparison of final compost properties of previous studies by other researchers	13
2.4	Advantages and disadvantages of in-vessel composter	14
3.1	Experimental design matrix and response results	27
4.1	Characteristics of pressed-shredded OPEFB, POME anaerobic sludge used in current study and properties of final compost at day 40	38
4.2	Weight losses of OPEFB degradation corresponding to the respective peaks shown in the thermograms (Figure 4.5)	48
4.3	Characteristics of pressed-shredded OPEFB, POME anaerobic sludge used in current study and properties of final compost at day 40	49
4.4	Weight losses of OPEFB degradation corresponding to the respective peaks shown in the thermograms (Figure 4.12)	58
4.5	Analysis of variance (ANOVA) for regression equation developed for TS, TSS and VSS	61
4.6	Verified results of model equation	63
4.7	Phylogenetic of affiliation of excised DGGE band for POMEBS aerobic sludge at optimum condition	65
4.8	Weight losses (percentage of total sample weight) corresponding to the main peaks shown in the thermograms (Figure 4.18)	69
4.9	Characteristics of OPEFB biochar, POME anaerobic sludge and POMEBS aerobic sludge at optimum condition (50°C, 10.65 g/L Biochar, 10g/L Urea), Pressed-shredded OPEFB, compost OPEFB + POMEBS aerobic sludge day 40, compost OPEFB + POME anaerobic sludge day 40	71

LIST OF FIGURES

Figure		Page
2.1	Chemical structure of cellulose (Source: Mohammed et al., 2011)	9
2.2	Chemical structure of hemicellulose (Source: Mohammed et al., 2011)	9
2.3	Chemical structure of lignin (Source: Mohammed et al., 2011)	10
3.1	Experimental design	20
3.2	Pressed-shredded OPEFB produced at oil palm mills	21
3.3	Pressed-shredded OPEFB fibre	21
3.4	Schematic diagram of the windrow system at pilot scale	22
3.5	Under shade and cement based at pilot composting plant	22
3.6	Turning process of compost piles using a composting turner	23
3.7	Schematic diagram of the in-vessel composting system at pilot scale	24
3.8	In-vessel composter at pilot scale	24
3.9	Schematic diagram of lab scale in-vessel composting system	25
3.10	Lab Scale in-vessel composter	26
3.11	10 kg of ground OPEFB mixed with palm oil mill biochar solution (POMEBS) and POME anaerobic sludge for each compartment	26
3.12	Flow sheet of the process from sampling to bacterial detection and identification (Source: Hovda 2007 with modification)	34
4.1	Profiles for (a) temperature and total bacterial population, (b) moisture, pH, and oxygen levels, (c) profiles for nitrogen, carbon, and C/N ratios throughout composting process	40
4.2	SEM micrograph (500 and 1000× magnifications) for the raw pressed-shredded OPEFB (a) and (b), OPEFB material at day 1, OPEFB material at day 10 (c) and (d) and OPEFB material at day 40 (e) and (f)	42
4.3	XRD analysis of composting process (a) and a comparison of crystal size by using Scherrer equation (b)	44
4.4	Comparison and assessment of final composts by referring to infrared spectroscopic characteristics	46
4.5	TG data comparison of composed OPEFB with raw OPEFB (a) and DTG data comparison of composed OPEFB with raw OPEFB (b)	48
4.6	Profiles for temperature and total bacterial population during the composting process	51
4.7	Profiles for moisture, pH, and oxygen level during the composting process	51
4.8	Profiles for nitrogen, carbon, and C/N ratio throughout composting process	53
4.9	SEM micrograph (500 and 1000× magnification) for the raw pressed-shredded OPEFB (a) and (b), OPEFB material at day 7 (c) and (d), OPEFB material at day 20 (e) and (f), and OPEFB material at day 40 (g) and (h)	54

4.10	XRD analysis of composting process (a) and a comparison of crystal size by using Scherrer equation (b)	55
4.11	Comparison and assessment of final composts by referring to infrared spectroscopic characteristics	57
4.12	TG data comparison of composed OPEFB with raw OPEFB (a) and DTA data comparison of composed OPEFB with raw OPEFB (b)	59
4.13	Response surface 3D plot indicating the effect of interaction between urea and biochar on a) TS and b) VSS; temperature and biochar on c) TS and d) VSS; and temperature and urea on e) TS and f) VSS	62
4.14	SEM of (a) POME anaerobic sludge at 1000× magnification, (b) POME anaerobic sludge at 10000× magnifications, (c) POMEBS aerobic sludge at 1000× magnification, and (d) POMEBS aerobic sludge at 10000× magnifications	64
4.15	DGGE band	65
4.16	FTIR analysis of POME anaerobic sludge and POMEBS aerobic sludge	66
4.17	Profile comparison between composting of OPEFB with POMEBS aerobic sludge and OPEFB with POME anaerobic sludge for a) temperature, Oxygen and pH; b) carbon, nitrogen and C/N ratio	67
4.18	TG and DTG data comparison of composting a) OPEFB with POMEBS aerobic sludge and b) OPEFB with POME anaerobic sludge	69

LIST OF ABBREVIATIONS

ADF	Acid detergent fibre
ADL	Acid detergent lignin
BLAST	Basic local alignment search tool
BOD	Biological oxygen demand
CDM	Clean development mechanism
CFU	Colony forming unit
COD	Chemical oxygen demand
CPO	Crude palm oil
DNA	Deoxyribonucleic acid
FELDA	Federal land development authority
GHG	Greenhouse gas
ICP	Inductively coupled plasma
IRR	Internal rate return
MPOB	Malaysian palm oil board
NDF	Neutral detergent fibre
NPV	Net present value
OPEFB	Oil palm empty fruit bunches
OPFFB	Oil palm fresh fruit bunches
PBP	Payback period
PCR - DGGE	Polymerase chain reaction - Denature gradient gel electrophoresis
POME	Palm oil mill effluent
POMEBS	Palm oil mill effluent biochar solution
SEM	Scanning electron microscope
TS	Total solids
TSS	Total suspended solids
VSS	Total volatile solids

CHAPTER 1

INTRODUCTION

1.1 Treats to Climate Change

The climate change is one of critical issue affecting the world and has been reported to cause numerous adverse effects on ecosystem such as disruption of clean water and food supply, impacts on human health, natural resources and security of human settlement (Sulaiman, 2010). The increasing emissions of carbon dioxide (CO₂), methane (CH₄) and nitrous oxide (N₂O) has been considered worldwide as the major cause of global warming (Kaewmai et al., 2012).

In Malaysia, serious efforts are being taken to reduce greenhouse gas (GHG) emissions because the major increasing emissions of CO₂, CH₄ and N₂O comes from oil palm industry. The oil palm industry is one of the biggest commodity producers in Malaysia. Malaysia has become the world's second largest oil palm producer and exporter after Indonesia (Shuit et al., 2009). The total oil palm planted area in 2011 reached 5 million hectares, an increase of 3% from the previous year (MPOB, 2011). The primary sources of GHG from palm oil production are: 1) emissions from operations during oil palm growing and oil palm fresh fruit bunches (OPFFB) processing; 2) emissions from changes in carbon stocks, during the development of new plantations and the operations of plantations (RSPO, 2009). The main emissions from operations during oil palm growth is the use of artificial fertilisers such as nitrogen fertilisers which contributed to N₂O emissions. Oil palm is the largest consumer of fertiliser in Malaysia which about 80% of industrial crop's fertiliser used in Malaysia (Sabri, 2009). In addition, the expansion of oil palm plantations increases the usage of fertilisers. Besides that, the escalating increase of world fertiliser price gives attention to find other alternative fertilisers such as compost.

In the meantime, OPFFB processing capacity is 54 tonnes per hour and approximately 300,000 tonnes can be processed in a year (Yoshizaki et al., 2012). It generates a large amount of oil palm biomass and waste materials (Abdul Khalil et al., 2012). In oil palm processing mills, each tonne of processed oil palm fresh fruit bunches (OPFFB) produces OPEFB (23%), oil palm mesocarp fibre (OPMF) (12%), shells (5%) and palm oil mill effluent (POME) (60%) (Baharuddin et al., 2010). Overall, oil palm fronds (OPF) (70%) make up most of the biomass produced, followed by oil palm empty fruit bunches (OPEFB) (10%) and oil palm trunks (OPT) (5%) (Ratnasingam, 2011). This biomass is utilised in many ways, including ruminant food (Abu Hassan et al., 1994), bioplastic (Chen et al., 2009), biochar (Mohd Salleh et al., 2010), composting (Baharuddin et al., 2010), pulp and paper (Wan Rosli et al., 2007) and automotive components (Shuit et al., 2009); waste water which generally refers as palm oil mill effluent (POME) is used to capture biogas (Ahmad et al., 2011; Sulaiman et al., 2009). However, there are still an abundance of biomass left in palm oil mills and the most notable is OPEFB. Therefore, OPEFB still used as mulch in the plantation which leads to CH₄ emissions, as a result of anaerobic decomposition (RSPO, 2009). Whereas, pond treatment system is still being used due to excessive POME generates by palm oil mills besides not all palm oil mills in Malaysia have installed the digestive system to capture biogas. The POME has high biodegradable organic material and the naturally available oxygen in pond treatment system is generally insufficient to cater

all aerobic decomposition of the organic material (RSPO, 2009). As a result, the decomposition of the organic material turns anaerobic hence produced biogas which cause the CH₄ emissions into the atmosphere. Therefore, compost is one of the promising ways to utilise this biomass while enabling low-cost production.

1.2 Overview on Composting of Organic Waste

Composting is a biological process of breaking up organic waste such as food waste, landscaping waste and agricultural waste by various microorganisms into a humus like substance product (Ali Tweib et al., 2011). The decomposition process can naturally happen almost everywhere even without exerting too much effort because it is an element of ecosystem life cycle. However, without the perfect mixture and proper control, the process slows down and eventually results to unpleasant compost. Olive oil industry in the Mediterranean countries also having a similar situation to palm oil mill in Malaysia where the residues derived from olive oil processing namely olive pomace and olive mill wastewater are generated in great amounts, thus making their disposal a major environmental problem (Plaza et al., 2007). According to Vlyssides et al. (1996), the annual olive oil production is in the range of 0.35 to 0.40 million tonnes, resulting in the generation of about 1.5 million tonnes of olive oil wastewater in Greece while Muktadirul Bari Chowdhury et al. (2013) reported that the annual olive oil wastewater worldwide be over 3 million tonnes. Normally, olive oil waste water treatment is based on evaporation in open air ponds system yielding a sludge residue which is rich in readily decomposable organic matter and plant nutrients (Hachicha et al., 2009). Therefore, in order to overcome the problem, olive oil waste water is being mixed with other organic waste such as tree cuttings, wheat straw, wool waste and animal manure to produce compost (Muktadirul Bari Chowdhury et al., 2013).

Table 1.1: Mechanical properties of some important natural fibre

Fibre	Tensile Strength (MPa)	Elongation (%)	Toughness (MPa)
OPEFB	248.0	14.0	2,000
OPMF	80.0	17.0	500
Coconut coir	140.0	25.0	3,200
Banana	540.0	3.0	816
Pineapple leaf	640.0	2.4	970

Source: Hock (2011)

In Malaysia, besides oil palm industry, there are many other organic waste that has been produced in high amount such as from sugarcane, coconut, pineapple and banana (Alwani et al., 2014). These organic wastes can be considered as carbon to produce compost. Composting usually takes months to complete, depending on characteristic materials used and the composting system. Table 1.1 below shows the mechanical properties of some important natural fibre. OPEFB have moderate tensile strength, high percentage of elongation and toughness compared to other natural fibre. It indicates OPEFB is a strong and tough fibre as high energy is required to break the OPEFB fibre. According to Baharuddin et al. (2013), the longer treatment in the composting process corresponds to the phenolic compound in the OPEFB cell walls which could restrict the rate and extent of polysaccharide degradation. There are four types of widely-applied composting systems, namely open static piles, turned windrow and piles, aerated static piles, and the in-vessel system (Hubbe et al., 2010).

The success of the compost stabilisation process depends on a suitable environment created by controlling the moisture content, oxygen level, carbon-nitrogen ratio and temperature (Baharuddin et al., 2009). Furthermore, good quality microbe seeding can fasten the degradation rate of organic waste. According to Zainudin et al. (2014), the continuous supply of microorganisms and also nutrients is one of the factors that promote rapid composting through the effective degradation of lignocellulosic materials.

1.3 Problem statements

Nowadays, much attentions are given towards long standing issued such as improvement in palm oil effluent treatment, better handling and utilisation of oil palm biomass, zero-discharge, water conservation and recycling due to greater demands on the environmental protection issues from the environmentalists, non-government organisation and Federal Land Development Authority (FELDA) (Sulaiman, 2010). FELDA have been implemented Clean Development Mechanism (CDM) Projects consisted three parts which are biomass power plant, compost plant and biogas plant. CDM is supervised by an executive board under the guidance of the United Nations Framework Convention on Climate Change (UNFCCC) and certified emission reduction (CER) could be claimed and converted it into a monetary value (Sulaiman, 2010). Introduction of compost derived from the aerobic degradation process OPEFB and POME was one of the waste management measures to reduce environmental impact in palm oil mills. Compost plant was first commissioned in FELDA Maokil, Malaysia and can produce up to 18,000 tonnes of compost annually. Furthermore, Sime Darby Plantation reported that up to 2012, there were 22 composting plants being operated with the potential production capacity up to 600,000 tonnes of compost annually (Yacob et al., 2010).

Table 1.2: Chemical fertiliser consumption and OPEFB compost production estimation quantity

Nutrients	Chemical fertiliser dry weight basis (tonnes)	Chemical fertiliser consumption (tonnes)	OPEFB compost dry weight basis (tonnes)	OPEFB compost produced (tonnes)
Nitrogen, N	1,448	3,842	488	1,295
Phosphorus, P	858	2,276	76	202
Potassium, K	3,348	8,882	1,065	2,825
Total	5,654	15,000	1,629	4,322

(Source: Yoshizaki et al., 2012)

Table 1.2 shows the chemical fertiliser consumption and OPEFB compost production quantity for 300,000 tonnes OPFFB harvested in the year 2010. The consumption of chemical fertiliser is 15,000 tonnes which comprise 1,448 tonnes of nitrogen, 858 tonnes of phosphorus and 3,348 tonnes potassium in dry weight basis (Yoshizaki et al., 2012). On the other hand, composting of 69,000 tonnes OPEFB with the addition of 207,000 tonnes raw POME as microbial seeding produce 488, 76 and 1,065 tonnes of N, P, and K respectively on dry weight basis (Yoshizaki et al., 2012). The amount of compost produced can only cover 4,322 tonnes of chemical fertiliser which is partly the nutritional demand in the plantation. Thus, 10,678 tonnes are still needed to meet the original demand of chemical fertiliser. Table 1.3 shows the capital cost of chemical

fertiliser and revenue made by OPEFB compost production. The current market price for chemical fertiliser are RM1,150/tonnes, RM600/tonnes and RM1,040/tonnes of urea (21%N), phosphate rock (28-30% P₂O₂) and potassium chloride (60% K₂O) respectively. Then, the compost price is estimated based on the N:P:K amount of compost. OPEFB compost is estimated can save up to RM4,548,450 annually the capital cost to buy chemical fertiliser. Economic analysis reported by Yoshizaki et al. (2012) shows that the internal rate return (IRR) for compost project is 31%, RM 10.87 million of net present values (NPV) and it takes 2.9 years for payback period (PBP). High IRR and NPV shows that the project is highly profitable to reduce the abundance of biomass produced in palm oil mills and also reduce the capital cost of chemical fertiliser.

Table 1.3: The capital cost of chemical fertiliser and revenue made by OPEFB compost production

Nutrients	Market price RM/tonnes	Chemical fertiliser consumption (tonnes)	OPEFB compost production (tonnes)
Urea (21% N)	1,150	3,842	1,295
Phosphate rock (28-30% P ₂ O ₂)	600	2,276	202
Potassium chloride (60% K ₂ O)	1,040	8,882	2,825
Total amount		15,000	4,322
Total price		RM15,021,180	RM4,548,450

(Source: Yoshizaki et al., 2012)

However, the main problem facing by these compost plants was low and inconsistent quality of compost in term of N:P:K values. According to Baharuddin et al. (2010), the quality of the final matured compost was difficult to maintain due to the variation of POME characteristics in the open pond system. Therefore, it is essential to provide consistent nitrogen and microbial source which can contribute to a higher N:P:K values. In biogas plant, the treatment of POME by closed anaerobic digester system generates biogas and at the same time it produces POME anaerobic which is high in nutrient content (Sulaiman et al., 2009). Hence, the quality of compost can be improved by the addition of thicken POME anaerobic sludge during OPEFB composting process (Baharuddin et al., 2010). Moreover, the fluctuation of moisture content due to excessive moisture from high rainfall may extend the composting period. Currently, the OPEFB composting project is conducted by using a windrow system and it required a large space to fully utilised OPEFB generated by the palm oil mill. Alternatively, many palm oil mills are near to oil palm plantation, which can provide enough space for the OPEFB windrow composting process. However, the main concern is the transportation and labour costs to transfer OPEFB and POME from palm oil mills to composting sites. On the contrary, if the main carbon source changes to OPF which is most abundant, high cost is still needed for pre-treatments and collection so that it can be suitable as composting material (Shuit et al., 2009).

Hence, in this study POME anaerobic sludge was mixed with pressed-shredded OPEFB to produce compost. The pressed-shredded OPEFB was used as a main carbon source for the composting process because it was available to be used in oil palm mills.

On the other hand, POME anaerobic sludge generated from biogas production provided consistent nitrogen and microbial source for the composting process. During composting, bacteria obtain their carbon through oxidation of the organic materials. With the consistent nitrogen and microbial source, the degradation can be fastened and the matured and stable composts will be produced. This thesis attempts to contribute to better scientific understanding of OPEFB composting and degradation process and assist in the development of a management system to maximise agronomic benefit and reduce environmental risk.

1.4 Objectives

The objectives of this study are:

- 1) To correlate stability and maturity determined using biological and physicochemical parameters with functional group structure changes during OPEFB composting treatments by windrow system at pilot scale operation.
- 2) To evaluate the changes in lignocellulosic structure of OPEFB during composting by combinational in-vessel and windrow system at pilot scale operation.
- 3) To evaluate the palm oil mill effluent biochar solution (POMEBS) aerobic sludge as microbial seeding for OPEFB composting process by a lab scale in-vessel system.

1.5 Scope of Research

This project was principally concerned about the strategy to produce OPEFB compost with high degradation rate and good quality compost. During the composting process by windrow system at pilot scale, the final ratio of OPEFB to POME anaerobic sludge was 1:2 after having optimise the important factors that affects composting process. While for composting process by a pilot scale combinational in-vessel and windrow system at pilot scale, the ratio of OPEFB to POME anaerobic sludge was initially set 1:3. This is due to the ability of in-vessel system that can fully control the important factors that affect composting process. In the third part of the experiment, the POME anaerobic sludge was formulated and changed to POMEBS aerobic sludge to improve the OPEFB composting process in terms of degraded performance and final compost quality. The ratio of OPEFB and POMEBS aerobic sludge was initially set 1:3. The degradation performance and final compost quality was compared to OPEFB composting with POME anaerobic sludge which was set as control experiment.

1.6 Thesis Structure

Following this brief introduction to the research, Chapter 2 reviews currently available knowledge on pressed-shredded OPEFB and POME anaerobic sludge composting process. Information about composting systems considered in this research is presented in Chapter 3 along with methodology. Based on the objectives, the experimental design was divided into three parts: 1) The first part of the experiment which represent the first objective was the OPEFB composting process by windrow system at pilot scale; 2) the second part which represents the second objective examined the OPEFB composting process by combinational in-vessel and windrow system at pilot scale; and 3) the third part which represents the third objective was effect of POMEBS aerobic sludge for the OPEFB composting process by a lab scale

in-vessel system that were detailed discourses in Chapters 4. Final conclusions and recommendations are summarised in Chapter 5.



© COPYRIGHT UPM

REFERENCES

- Abdul Khalil, H. P. S., Fizree, H. M., Jawaid, M., and Alattas, O. S. (2011). Preparation and characterization of nano-structured materials from oil palm ash: A bio-agricultural waste from oil palm mill. *BioResources* 6(4), 4537-4546.
- Abdul Khalil, H.P.S., Jawaid, M., Hassan, A., Paridah, M.T., and Zaidon, A. (2012). Oil Palm Biomass Fibres and Recent Advancement in Oil Palm Biomass Fibres Based Hybrid Biocomposites. *Intech* Chapter 8.
- Abdullah, N., Sulaiman, F., and Gerhauser, H. (2011). Characterization of oil palm empty fruit bunches for fuel application. *Journal of Physical Science*, 22(1), 1-24.
- Abu Hassan, O., Ishida, M., Mohd Shukri, I., and Ahmad Tajuddin, Z. (1994). Oil-palm fronds as a roughage feed source for ruminants in Malaysia. FFTC for the Asian and Pacific Region.
- Adhikari, B.K. (2005). Urban food waste composting. Master of Science Thesis, McGill University.
- Ait-Baddi, G., Albuquerque, J. A., Gonzalez, J., Cegarra, J., and Hafidi, M. (2004). Chemical and spectroscopic analyses of organic matter transformations during composting of olive mill wastes. *International Biodeterioration and Biodegradation* 54, 39-44.
- Ahmad, M.N., Mokhtar, M.N., Baharuddin, A.S., Hock, L.S., Ahmad Ali, S.R., Abd-Aziz, S., Abdul Rahman, N.A., and Hassan, M.A. (2011). Changes in physicochemical and microbial community during co-composting of oil palm frond with palm oil mill effluent anaerobic sludge. *BioResources* 6(4), 4762-4780.
- Ahmad, S., Ab Kadir, M.Z.A., and Shafie, S., (2011). Current perspective of the renewable energy development in Malaysia. *Renewable and Sustainable Energy Reviews* 15, 897-904.
- Ali, M., Bhatia, A., Kazmi, A. A., and Ahmed, N. (2012). Characterization of high rate composting of vegetable market waste using Fourier transform-infrared (FT-IR) and thermal studies in three different seasons. *Biodegradation* 23, 231-242.
- Ali Tweib, S., Abd Rahman, R., and Kalil, M.S. (2011). A literature review on the composting. *International Conference on Environment and Industrial Innovation, IPCBEE* 12, 124-127.
- Alvarez, V. A., and Vazquez, A. (2004). Thermal degradation of cellulose derivatives, starch blends, and sisal fibre biocomposites. *Polymer Degradation and Stability* 84, 13-21.
- Alwani, M.S., Abdul Khalil, H.P.S., Sulaiman, O., Islam, M.N., and Dungani, R. (2014). An approach to using agricultural waste fibres in biocomposites application: thermogravimetric analysis and activation energy study. *BioResources* 9(1), 218-230.

- Amir, S., Hafidi, M., Merlina, G., and Revel, J. C. (2005). Sequential extraction of heavy metals during composting of sewage sludge. *Chemosphere* 59, 801-810.
- Amir, S., Jouraiphy, A., Meddich, A., Gharous, M.E., Winterton, P., and Hafidi, M. (2010). Structural study of humic acids during composting of activated sludge-green waste: Elemental analysis, FTIR and ¹³C NMR. *Journal of Hazardous Materials* 177(1-3), 524-529.
- Amouzgar, H. P. S., Khalil, F. P. S. A., Salamatinia, B., Abdullah, A. Z., and Issam, A. M. (2010). Optimization of bioresource material from oil palm trunk core drying using microwave radiation: A response surface methodology application. *Bioresource Technology* 101(21), 8396-8401.
- Andersen, J.K. 2010. Composting of organic waste: quantification and assessment of greenhouse gas emissions. PhD Thesis, Technical University of Denmark.
- APHA (2005). Standard Methods for Examination Water and Wastewater, 21th Edition, American Public and Health Association, Washington, D.C.
- Arami-Niya, A., Abnisa, F., Shafeegan, M. S., Wan Daud, W. M. A., and Sahu, J. N. (2012). Optimization of synthesis and characterization of palm shell-based bio-char as a by-product of bio-oil production process. *BioResources* 7(1) 246-264.
- Baffi, C., Dell'Abate, M.T., Nassisi, A., Silva, S., Benedetti, A., Genevini, P.L., and Adani, F. (2007). Determination of biological stability in compost: A comparison of methodologies *Soil Biology & Biochemistry* 39, 1284-1293.
- Baharuddin, A. S., Abdul Rahman, N. A., Md. Shah, U. K., Hassan, M. A., Wakisaka, M., and Shirai, Y. (2011). Evaluation of pressed shredded empty fruit bunch (OPEFB)-palm oil mill effluent (POME) anaerobic sludge based compost using Fourier transform infrared (FTIR) and nuclear magnetic resonance (NMR) analysis. *African Journal of Biotechnology* 10(41), 8082-8089.
- Baharuddin, A. S., Lim, S. H., Md. Yusof., M. Z., Abdul Rahman, N. A., Md. Shah, U. K., Hassan, M. A., Wakisaka, M., Sakai, K., and Shirai, Y. (2010). Effect of palm oil mill effluent (POME) anaerobic sludge from 500 m³ of closed anaerobic methane digestion tank on pressed-shredded empty fruit bunch (OPEFB) composting process. *African Journal of Biotechnology* 9(16), 2427-2436.
- Baharuddin, A. S., Md. Yunos, N. S. H, Nik Mahmud, N. A., Zakaria, R., and Md. Yunos, K. F. (2012). Effect of high-pressure steam treatment on enzymatic saccharification of oil palm empty fruit bunches. *BioResources* 7(3), 3525-3538.
- Baharuddin, A.S., Sulaiman, A., Kim, D.H., Mokhtar, M.N., Hassan, M.A., Wakisaka, M., Shirai, Y., and Nishida, H. (2013). Selective component degradation of oil palm empty fruit bunches (OPEFB) using high-pressure steam. *Biomass and Bioenergy* 55, 268-275.

- Baharuddin, A.S., Wakisaka, M., Shirai, Y., Abd-Aziz, S., Abdul Rahman, N.A., and Hassan, M. A. (2009). Co-composting of empty fruit bunches and partially treated palm oil mill effluent in pilot scale. *International Journal of Agricultural Research* 4(2), 69-78.
- Bahrin, A. K., Baharuddin, A. S., Ibrahim, M. F., Abdul Razak, M. N., Sulaiman, A., Abd-Razak, S., Hassan, M. A., Shirai, Y., and Nishida, H. (2012). Physicochemical property changes and enzymatic hydrolysis enhancement of oil palm oil empty fruit bunches treated with superheated steam. *BioResources* 7(2), 1784-1801.
- Beffa, T. (2002). The composting biotechnology: A microbial aerobic solid substrate fermentation complex process. *The Composting Process and Management*, 1-37.
- Bledzki, A. K., and Gassam, J. (1999). Composites reinforced with cellulose based fibres. *Progress in Polymer Science* 24, 221-274.
- Bernabé, G.A., Almeida, S., Ribeiro, C.A., and Crespi, M. S. (2011). Evaluation of organic molecules originated during composting process. *Journal of Thermal Analysis and Calorimetry*, 106, 773-778.
- Bernal, M.P., Albuquerque, J.A., and Moral, R. (2009). Composting of animal manures and chemical criteria for compost maturity assessment: A review. *Bioresource Technology* 100, 5444-5453.
- Brock, T. D., Madigan, M. T., Martinko, J. M., Stahl, D. A., and Clark, D. P. (2012). *Biology of Microorganisms*, 13rd Edn., Prentice-Hall Inc., Englewood Cliffs, N.J., ISBN-10: 0-321-64963-X, 129.
- Bykov, I. (2008). Characterization of natural and technical lignins using FTIR spectroscopy. Master of Science Thesis, Lulea University of Technology.
- Castaldi, P., Alberti, G., Merella, R., and Melis, P. (2005). Study of the organic matter evolution during municipal solid waste composting aimed at identifying suitable parameters for the evaluation of compost maturity. *Waste Management* 25, 209-213.
- Cegarra, J., Albuquerque, J.A., Gonzalez, J., Tortosa, G., and Chaw, D. (2006). Effects of the forced ventilation on composting of a solid olive-mill by-product (“alperujo”) managed by mechanical turning. *Waste Management* 26(12), 1377-1383.
- Chen, G.Q. (2009). A microbial Polyhydroxyalkanoates (PHA) based bio- and materials industry. *Chemical Society Reviews*, 38, 2424-2446.
- Chiumenti, A., Da Borso, F., Rodar, T. and Chiumenti, R. (2007). Swine manure composting by means of experimental turning equipment. *Waste Management* 27, 1774-1782.
- Clough, T. J., and Condon, L. M. (2010). Biochar and the nitrogen cycle: Introduction *Journal of Environment Quality* 39(4), 1218-1223.

- Corley R H V and Tinker P B (2003). *The Oil Palm*. Blackwell Publishing, Fourth edition.
- Dell'Abate M.T., Canali, S., Trinchera, A., Benedetti, A., and Sequi, P. (1998). Thermal analysis in the evaluation of compost stability: a comparison with humification parameters. *Nutrient Cycling in Agroecosystems* 51,217-224.
- Elango, D., Thinakaran, N., Panneerselvam, P., Sivanesan, S., (2009). Thermophilic composting of municipal solid waste. *Applied Energy* 865, 663–668.
- Embrandiri, A., Singh, R. P., M. Ibrahim, H., and Ramli, A. (2011). Land application of biomass residue generated from palm oil processing: Its potential benefits and threats. *Environmentalist* 32(1), 111-117.
- Esposito, N.C. (2013). Soil nutrient availability properties of biochar. Masters of Science Thesis, Cal Poly State University.
- Evans, G. (2001) *Biowaste and biological waste treatment*. London: James & James.
- FAOSTAT 2013. Online statistical service. Available at: (<http://faostat.fao.org/>).
- Fischer, D., and Glaser, B. (2012). Synergisms between compost and bio-char for sustainable soil amelioration. In: *Management of Organic Waste*, Dr. Sunil Kumar (ed.), InTech, Rijeka, Croatia, pp. 167-198.
- Glaser, B., Lehmann, J., and Zech, W. (2002). Ameliorating physical and chemical properties of highly weathered soils in the tropics with charcoal- A review. *Biology and Fertility of Soils* 35(4), 219-230.
- Forgie, D.J.L., Sasser, L.W., and Neger, M.K. (2004). Compost facility requirements guideline: how to comply with part 5 of the organic matter recycling regulation.
- Graves, R.E., and Hattemer, G.M. (2000). Composting. Part 637- Environmental engineering Chapter 2. United States Department of Agriculture. Natural Resources conservation services, USA, 16-40.
- Goering, H. K., and Van Soest, P. J. (1970). Forage fiber analysis (apparatus, reagents, procedures, and some application). USDA Handbook 379, U.S. Gov. Print. Office, Washington, DC.
- Grube, M., Lin, T. J. G., Lee, P. H., and Kokorevicha, S. (2006). Evaluation of sewage sludge-based compost by FT-IR spectroscopy. *Geoderma* 130, 324-333.
- Haaren, R.V. (2009). Large scale aerobic composting of source separated organic wastes: A comparative study of environmental impacts, costs, and contextual effects. Master of Science Thesis, Columbia University.
- Hachicha, R., Hachicha, S., Trabelsi, I., Woodward, S., and Mechichi, T. (2009). Evolution of the fatty fraction during co-composting of olive oil industry wastes

with animal manure: maturity assessment of the end product. *Chemosphere*, 75 (10), 1382-1386.

Hachicha, S., Sellami, F., Cegarra, J., Hachicha, R., Drira, N., Medhioub, K., and Ammar, E. (2009). Biological activity during co-composting of sludge issued from the OMW evaporation ponds with poultry manure—Physico-chemical characterization of the processed organic matter. *Journal of Hazardous Materials* 162, 402-409.

Haug, R. T. (1993). *The practical handbook of compost engineering*. Lewis Publishers.

Henderson, J. & Osborne, D.J. (2000). The oil palm in our lives: how this came about. *Endeavour*, 24 (2), 63-68.

Henriksen, T. M., and Breland, T. A. (1999). Nitrogen availability effects on carbon mineralization, fungal and bacterial growth, and enzyme activities during decomposition of wheat straw in soil. *Soil Biology and Biochemistry* 31(8), 1121-1134.

Herity, L. (2003). The quality of waste derived compost in Ireland. Master of Science Thesis, Queens University of Belfast.

Himanen, M., and Hänninen, K. (2011). Composting of bio-waste, aerobic and anaerobic sludges – Effect of feedstock on the process and quality of compost. *Bioresource Technology* 102(3), 2842-2852.

Hock, L. S. (2011). Co-composting of oil palm mesocarp fiber and palm oil mill effluent anaerobic sludge. Masters of Science Thesis, Universiti Putra Malaysia.

Hock, L. S., Baharuddin, A. S., Ahmad, M. N., Md Shah, U. K., Rahman, N. A. A., Abd-Aziz, S., Hassan, M. A., and Shirai, Y. (2009). Physicochemical changes in windrow co-composting process of oil palm mesocarp fiber and palm oil mill effluent anaerobic sludge. *Australian Journal of Basic and Applied Sciences* 3(3), 2809-2816.

Hou, X., and Jones, B. T. (2000). Inductively Coupled Plasma/Optical Emission Spectrometry. *Encyclopedia of Analytical Chemistry*, Chichester, John Wiley & Sons Ltd.

Hovda MB (2007) Application of PCR and DGGE to characterise the microflora of farmed fish. PhD Thesis, University of Bergen.

Huang, G. F., Wu, Q. T., Wong, J. W. C., and Nagar, B. B. (2006). Transformation of organic matter during co-composting of pig manure with sawdust. *Bioresource Technology* 97, 1834-1842.

Hubbe, M. A., Nazhad, M., and Sánchez, C. (2010). Composting as a way to convert cellulosic biomass and organic waste into high-value soil amendments: a review. *BioResources* 5(4), 2808-2854.

- Ichim, G.E. (2007). Assessing the challenges and potential of implementing composting as part of a municipal solid waste management system in Baisha, Hainan, China. Master of Environmental Studies Thesis, University of Waterloo.
- Inyang, M., Gao, B., Pullammanappallil, P., Ding, W. C., and Zimmerman, A. R. (2010). Biochar from anaerobically digested sugarcane bagasse. *Bioresource Technology* 101(22), 8868-8872.
- Ishii K, Fukui M, Takii S (2000) Microbial succession during a composting process as evaluated by denaturing gradient gel electrophoresis analysis. *Journal of Applied Microbiology* 89:768–777.
- Jeffries, T. W. (1994). Biodegradation of lignin and hemicelluloses. *Biochemistry of Microbial Degradation*, 233-277.
- Jouraihy, A., Amir, S., El Gharous, M., Revel, J. C., and Hafidi, M. (2005). Chemical and spectroscopic analysis of organic matter transformation during composting of sewage sludge and green plant waste. *International Biodeterioration and Biodegradation* 56, 101-108.
- Kaewmai, R., A. H-Kittikun, et al. (2013). Alternative Technologies for the Reduction of Greenhouse Gases Emission from Palm Oil Mills in Thailand. *Environmental Science and Technology* 47, 12417–12425.
- Kala, D.R., Rosenani, A.B., Fauziah, C.I., and Thohirah, L.A. (2009). Composting oil palm wastes and sewage sludge for use in potting media of ornamental plants. *Malaysian Journal of Soil Science* 13, 77-91.
- Kalamdhad, A.S., and Kazmi, A.A. (2009). Rotary drum composting of different organic waste mixtures. *Waste Management and Research* 27, 129-137.
- Kalamdhad, A.S., Singh, Y.K., Ali, M., Khwairakpam, M., and Kazmi, A.A. (2009). Rotary drum composting of vegetable waste and tree leaves. *Bioresource Technology* 100, 6442-6450.
- Kalia, S., Dufresne, A., Cheria, B. M., Kaith, B.S., Avérous, L., Njuguna, J., and Nassiopoulos, E. (2011). Cellulose-based bio- and nanocomposites: a review. *International Journal of Polymer Science* Article ID 837875.
- Kananam, W., Suksaroj, T. T., and Suksaroj, C. (2011). Biochemical changes during oil palm (*Elaeis guineensis*) empty fruit bunches composting with decanter sludge and chicken manure. *Science Asia* 37, 17-23.
- Kang, N., Liu, Z., Hui, L.F., Si, C.L., Cui, L., Zhao, T., and Mao, S.T. (2012). Study on the optimum process of acid-catalytic ethanol pretreatment of Chinese triploid poplar to enhance sugar recovery by hydrolysis. *BioResources* 7(1) 578-592.
- Kim, J.D., Park, J.S., In, B.H., Kim, D., and Namkoong, W. (2007). Evaluation of pilot-scale in-vessel composting for food waste treatment. *Journal of Hazardous Materials* 154, 272-277.

- Kokkora, M.I. (2008) Biowaste and vegetable waste compost application to agriculture. PhD Thesis, Cranfield University.
- Kumar, M., Ou, Y.L., and Lin, J.G. (2010). Co-composting of green waste and food waste at low C/N ratio. *Waste Management* 30, 602-609.
- Kutzner, H. J. (2001). Microbiology of composting. In: *Biotechnology Set, Vol.11c*, Wiley, New York, 35-100.
- Kuzyakov, Y., Subbotina, I., Chen, H., Bogomolova, I., and Xu, X. (2009). "Black carbon decomposition and incorporation into soil microbial biomass estimated by ¹⁴C labeling," *Soil Biology and Biochemistry* 41(2), 210-219.
- Last, S. (2006). An introduction to waste technologies. *Waste Technologies* UK Associates.
- Law, K. N., Wan Daud, W. R., and Ghazali, A. (2007). Morphological and chemical nature of fiber strands of oil palm empty-fruit-bunch (OPEFB). *BioResources* 2(3), 351-362.
- Lehmann, J., Kinyangi, J., and Solomon, D. (2007). Organic matter stabilization in soil microaggregates: Implications from spatial heterogeneity of organic carbon contents and carbon forms. *Biogeochemistry* 85, 45-57.
- Li, G., Zhang, F., Sun, Y., Wong, J. W. C., and Fang, M. (2001). Chemical evaluation of sewage sludge composting as a mature indicator for composting process. *Water, Air, and Soil Pollution* 132, 333-345.
- Liang, C., Das, K. C., and McClendon, R.W. (2003). The influence of temperature and moisture content regimes on aerobic microbial activity of a biosolids composting blend. *Bioresource Technology* 86, 131-137.
- Lorestani, A.A.Z., (2006). Biological treatment of palm oil effluent (POME) using an up-flow anaerobic sludge fixed film (UASFF) bioreactor. PhD Thesis, Universiti Sains Malaysia (USM).
- Lynd, L. R., Weimer, P. J., van Zyl, W. H., and Pretorius, I. S. (2002). Microbial cellulose utilization: Fundamental and biotechnology. *Microbiology and Molecular Biology Reviews* 66(3), 506-577.
- Ma, A.N. 2000 Management of palm oil industrial effluents. In: Yusof, B., Jalani, B.S. and Chan, K.W. (eds.) *Advances in oil palm research vol. II*, 1439–1461. Malaysian Palm Oil Board, Ministry of Primary Industries, Kuala Lumpur.
- Manios, T. The composting potential of different organic solid wastes, experience from the island of Crete (2004). *Environmental International*, 29, 1079–1089.
- Marhuenda-Egea, F.C., Martínez-Sabater, E., Jordá, J., Sánchez-Sánchez, A., Moral, R., Bustamante, M.A., Paredes, C., and Pérez-Murcia, M.D. (2007). Evaluation of

the aerobic composting process of winery and distillery residues by thermal methods. *Thermochimica Acta* 454, 135-143.

Mohammad, N., Alam, Md. Z., Kabbashi, N. A., and Ahsan, A. (2012). Effective composting of oil palm industrial waste by filamentous fungi: A review. *Resource Conservation and Recycling* 58, 69-78.

Mohammed, M. A. A., Salmiaton, A., Wan Azlina, W. A. K. G., Mohammad Amran, M. S., Fakhru'l-Razi, A., and Taufiq-Yap, Y. H. (2011). Hydrogen rich gas from oil palm biomass as a potential source of renewable energy in Malaysia. *Renewable and Sustainable Energy Reviews* 15, 1258-1270.

Mohd Salleh, M.A., Kisiki, N.H., Yusuf, H.M., and Wan Ab Karim Ghani, W.A. (2010). Gasification of Biochar from Empty Fruit Bunch in a Fluidized Bed Reactor. *Energy* 3, 1344-1352.

Mohee, R., Unmar, G. D., Mudhoo, A., and Khadoo, P. (2008). Biodegradability of biodegradable/degradable plastic materials under aerobic and anaerobic conditions. *Waste Management* 28(9), 1624-1629.

Morán, J. I., Alvarez, V. A., Cyras, V. P., and Vázquez, A. (2008). Extraction of cellulose and preparation of nanocellulose from sisal fibers. *Cellulose* 15, 149-159.

MPOB (2010). Overview of the Malaysian Oil Palm Industry 2010.

MPOB (2011). Overview of the Malaysian Oil Palm Industry 2011.

Muktadirul Bari Chowdhury, A.K.M., Akrotos, C.S., Vayenas, D.V., and Pavlou S. (2013). Olive mill waste composting: a review. *International Biodeterioration and Biodegradation* 85, 108–119.

Muyzer, G. & Smalla, K. 1998. Application of denaturing gradient gel electrophoresis (DGGE) and temperature gradient gel electrophoresis (TGGE) in microbial ecology. *Antonie Van Leeuwenhoek* 73: 127-141.

Ng, Y. F., Yew, K. F., Basiron, Y., and Sundram, K. (2011). A renewable future driven with Malaysian palm oil-based green technology. *Journal of Oil Palm and Environment* 2, 1-7.

Omar, R., Idris, A., Yunus, R., Khalid, K., and Aida Isma, M. I. (2011). Characterization of empty fruit bunch for microwave-assisted pyrolysis. *Fuel* 90, 1536-1544.

Otero, M., Calvo, L. F., Estrada, B., Garcia, A. I., and Morán, A. (2002). Thermogravimetry as a technique for establishing the stabilization progress of sludge from waste water treatment plants. *Thermochimica Acta* 389, 121-132.

Peters, S., Koschinsky, S., Schwieger, F., Tebbe, C.C. (2000). Succession of microbial communities during hot composting as detected by PCR-single-strand-

conformation-polymorphism-based genetic profiles of small-subunit rRNA genes. *Applied and Environmental Microbiology*, 66(3), 930-936.

Petric, I., and Selimbasic, V. (2008). Composting of poultry manure and wheat straw in a closed reactor: Optimum mixture ratio and evolution of parameters. *Biodegradation* 19(1), 53-63.

Phillip, E.A. (2010). The design and construction of a pilot-scale compost reactor for the study of gas emissions from compost under different physical conditions. Masters of Science Thesis, McGill University.

Pietro, M., and Paola, C. (2004). Thermal analysis for the evaluation of the organic matter evolution during municipal solid waste aerobic composting process. *Thermochimica Acta* 413, 209-214.

Plaza, C., Senesi, N., Brunetti, G., and Mondelli, D. (2007). Evolution of fulvic acid fractions during co-composting of olive oil mill wastewater sludge and tree cuttings. *Bioresource Technology* 98, 1964-1971.

Plessis, R.D. (2010). Establishment of composting facilities on landfill sites. Master of Arts Thesis, University of South Africa.

Provenzano, M. R., de Oliveira, S. C., Santiago Silva, M. R., and Senesi, N. (2001). Assessment of maturity degree of composts from domestic solid wastes by fluorescence and Fourier transform infrared spectroscopies. *Journal of Agriculture and Food Chemistry* 49, 5874-5879.

Ramli, R., Shaler, S., and Jamaluddin M., A. (2002). Properties of Medium Density Fibreboard from Oil Palm Empty Fruit Bunch Fibre. *Journal of Oil Palm Research* 14, 2, 34-40.

Ratnasingam, Jegatheswaran. *Oil Palm Biomass Utilization – Counting the Successes in Malaysia*. 2011.

Richards, D.J., Ivanova, L.K., Smallman, D.J., Zheng, B., 2005. Assessment of Waste Degradation using Acid Digestible Fibre Analysis, International Workshop on Hydro-Physico Mechanics of Landfills.

Rihani, M., Malamis, D., Bihaoui, B., Etahiri, S., Loizidou, M., and Assobhei, O. (2010). In-vessel treatment of urban primary sludge by aerobic composting. *Bioresource Technology* 101, 5988-5995.

Ros, M., Garcia, C., and Hernandez, T. (2006). A full-scale study of treatment of pig slurry by composting: Kinetic changes in chemical and microbial properties. *Waste management* 26, 1108-1118.

Roundtable of Sustainable Palm Oil (RSPO). *Greenhouse gas emissions from palm oil production*. Brinkmann Consultancy: Hoevelaken. 2009.

- Rupani, P.F., Singh, R.P., Ibrahim, M.H., and Esa, N. (2010). Review of Current Palm Oil Mill Effluent (POME) Treatment Methods: Vermicomposting as a Sustainable Practice. *World Applied Sciences Journal* 11 (1), 70-81.
- Rupilius, W. and Ahmad, S. (2007). Palm oil and palm kernel oil as raw materials for basic oleo chemicals and biodiesel. *European Journal of Lipid Science and Technology* 109, 433-439.
- Sabri, M.A. (2009). Evolution of fertiliser use by crops in Malaysia: Recent trends and prospects. *Fertiliser Industry Association of Malaysia*.
- Said-Pullicino, D., Erriquens, F.G., and Gigliotti, G. (2007). Changes in the chemical characteristics of water-extractable organic matter during composting and their influence on compost stability and maturity. *Bioresource Technology* 98, 1822-1831.
- Sharma, V. K., Caudatelli, M., Fortuna, F., and Cornacchia, G. (1997). Processing of urban and agro-industrial residues by aerobic composting: Review. *Energy Conservation and Management* 38, 453-478.
- Sheil, D., Casson, A., Meijaard, E., Noordwijk, M.V., Gaskell, J., Sunderland-Groves, J., Wertz, K., and Kanninen, M. (2009). The impacts and opportunities of oil palm in Southeast Asia. *Occasional paper No.51*.
- Shuit, S.H., Tan, K.T., Lee, K.T., and Kamaruddin, A.H. (2009). Oil palm biomass as a sustainable energy source: A Malaysian case study. *Energy* 34, 1225–1235.
- Singh, R. P., Hakimi Ibrahim, M., Norizan, E., and Iliyana, M. S. (2010). Composting of waste from palm oil mill: A sustainable waste management practice. *Reviews in Environment Science and Biotechnology* 9, 331-344.
- Singh, Y.K., Kalamdhad, A.S., Ali, M., and Kazmi, A.A. (2009). Maturation of primary stabilized compost from rotary drum composter. *Resource Conservation and Recycling* 53, 386-392.
- Smidt, E., and Lechner, P. (2005). Study on the degradation and stabilization of organic matter in waste by means of thermal analyses. *Thermochimica Acta* 438, 22-28.
- Smidt, E., and Meissl, K. (2007). The applicability of Fourier transform infrared (FT-IR) spectroscopy in waste management. *Waste Management* 27, 268-276.
- Smidt, E., Eckhardt, K. U., Lechner, P., Hans-RolfSchulten, H. R., and Leinweber, P. (2005). Characterization of different decomposition stages of biowaste using FT-IR spectroscopy and pyrolysis-field ionization mass spectrometry. *Biodegradation* 16, 67-79.
- Som, M.P., Lemée, L., and Amblès, A. (2009). Stability and maturity of a green waste and biowaste compost assessed on the basis of a molecular study using

- spectroscopy, thermal analysis, thermodesorption and thermochemolysis. *Bioresource Technology* 100, 4404-4416.
- Sridhar, M. K. C., and AdeOluwa, O. O. (2009). Palm oil industry residues. *Biotechnol Agro- Industrial Residues* 18, 342-354.
- Stichnothe, H., and Schuchardt, F. (2010). Comparison of different treatment options for palm oil production waste on a life cycle basis. *International Journal Life Cycle Assess* 15, 907-915.
- Suradi, S. S., Yunus, R. M., Beg, M. D. H., and Yusof, Z. A. M. (2009). Influence pre-treatment on the properties of lignocellulose based biocomposite. *National Conference Postgraduate Research (NCON-PGR)*.
- Sulaiman, A. (2010). Enhanced biomethanation of palm oil mill effluent during anaerobic treatment in a closed digester tank. PhD Thesis, Universiti Putra Malaysia.
- Sulaiman, A., Busu, Z., Tabatabaei, M., Yacob, S., Abd-Aziz, S., Hassan, M.A., and Shirai Y. (2009). The effect of higher sludge recycling rate on anaerobic treatment of palm oil mill effluent in a semi-commercial closed digester for renewable energy. *American Journal of Biochemistry and Biotechnology* 5(1), 1-6.
- Sun, R. C. (2008). Detoxification and separation of lignocellulose biomass prior to fermentation for bioethanol production by removal of lignin and hemicelluloses. *BioResources* 4(2), 452-455.
- Sundberg, C. (2005). Improving compost process efficiency by controlling aeration, temperature and pH. PhD Thesis, Swedish University of Agricultural Sciences.
- Tandy, S., Healey, J.R., Mark, A. Nason, M.A., Williamson, J.C., Davey, L., Jones, D.L., Simon, C., and Thain, S. C. (2010). FT-IR as an alternative method for measuring chemical properties during composting. *Bioresource Technology* 101, 5431-5436.
- Themelis, N. J. (2002). Material and energy balances in a large-scale aerobic bioconversion cell. *Waste Management and Research* 20, 234-242.
- Tiquia, S. M. (2003). Evaluation of organic matter and nutrient composition of partially decomposed and composted spent pig litter. *Environmental Technology* 24, 97-207.
- Tumuhairwe, J.B., Tenywa, J.S., Otabbong, E., and Ledin, S. (2009). Comparison of four low-technology composting methods for market crop wastes. *Waste Management* 29, 2274-2281.
- Tuomela, M., Vikman, M., Hatakka, A., and Itaavara, M. (2000). Biodegradation of lignin in a compost environment: A review. *Bioresource Technology* 72, 169-183.

- Vlyssides, A.G., Bouranis, D.L., Loizidou, M., and Karvouni, G. (1996). Study of a demonstration plant for the co-composting of olive-oil processing wastewater and solid residue. *Bioresource Technology* 56, 187–193.
- Wahid, M.B., Abdullah, S.N.A. and Henson, I.E. (2005). Oil palm—achievements and potential. *Plant Production Science* 8: 288–297.
- Wan Rosli, W.D., Zainuddin, Z., Law, K.N. and Asro, R. (2007). Pulp from oil palm fronds by chemical processes. *Industrial Crops and Products* 25: 89–94.
- Wong, K.M, Abdul Rahman, N.A., and Abd-Aziz, S. (2008). Enzymatic hydrolysis of palm oil mill effluent solid using mixed cellulases from locally isolated fungi. *Research Journal of Microbiology* 3 (6), 474-481.
- Wu, H., Zhao, Y., Long, Y., Zhu, Y., Wang, H., and Lu, W. (2011). Evaluation of the biological stability of waste during landfill stabilization by thermogravimetric analysis and Fourier transform infrared spectroscopy. *Bioresource Technology* 102, 9403-9408.
- Wyman, C.E., Decker, S.R., Himmel, M.E., Brady, J.W., Skopec, C.E., Viikari, L. (2004). Hydrolysis of cellulose and hemicellulose. In: Dumitriu, S. (Ed.), *Polysaccharides: Structural Diversity and Functional Versatility*, second ed. Marcel Dekker, Inc., New York, pp. 995–1033, invited.
- Xiao, Y., Zeng, G.M., Yang, Z.H., Shi, W.J., Huang, C., Fan, C.Z., and Xu, Z.Y. (2009). Continuous thermophilic composting (CTC) for rapid biodegradation and maturation of organic municipal solid waste. *Bioresource Technology* 100, 4807-4813.
- Yacob, S., Devi, S., Wok, K., and Kumaran, R. (2010). The use of bio-compost in oil palm plantation-Sime Darby's experience. Retrieved 16 May 2014 from http://www.rt10.rspo.org/ckfinder/userfiles/files/PC8_2%20Kumaran%20Rajago pal%20Abstract.pdf.
- Yadav, A., and Garg, V. K. (2011). Industrial wastes and sludges management by vermicomposting. *Reviews in Environmental Science and Biotechnology* 10, 243-276.
- Yahya, A., Sye, C.P., Ishola, T. A., and Suryanto, H. (2010). Effect of adding palm oil mill decanter cake slurry with regular turning operation on the composting process and quality of compost from oil palm empty fruit bunches. *Bioresource Technology* 101, 8736-8741.
- Yoshizaki, T., Shirai, Y., Hassan, M. A., Baharuddin, A. S., Raja Abdullah, N. M., Sulaiman, A., and Busu, Z. (2012). Economic analysis of biogas and compost projects in a palm oil mill with clean development mechanism in Malaysia. *Environment, Development and Sustainability* 14, 1065–1079.
- Yusoff, S. (2006). Renewable energy from palm oil—innovation on effective utilization of waste. *Journal of Cleaner Production* 14: 87–93.

Zainudin, M.H.M., Hassan, M.A., Shah, U.K.M., Abdullah, N., Tokura, M., Yasueda, H., Shirai, Y., Sakai, K., and Baharuddin, A.S. (2014). Bacterial community structure and biochemical changes associated with composting of lignocellulosic oil palm empty fruit bunch. *BioResources* 9(1), 316-335.

Zwart, R. (2013). Opportunities and challenges in the development of a viable Malaysian palm oil biomass industry. *Journal of Oil Palm and the Environment* 4, 41-46.

