



UNIVERSITI PUTRA MALAYSIA

***SCENE ILLUMINATION CLASSIFICATION BASED ON HISTOGRAM
QUARTERING OF CIE-Y COMPONENT***

MOHAMMAD HESAM HESAMIAN

FK 2014 129



**SCENE ILLUMINATION CLASSIFICATION BASED ON HISTOGRAM
QUARTERING OF CIE-Y COMPONENT**

By

MOHAMMAD HESAM HESAMIAN

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of Master of Science**


July 2014

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia





© COPYRIGHT UPM

Abstract of thesis presented to the Senate of Universiti Putra Malaysia
in fulfilment of the requirement for the Degree of Master of Science

**SCENE ILLUMINATION CLASSIFICATION BASED ON HISTOGRAM
QUARTERING OF CIE-Y COMPONENT**

By

MOHAMMAD HESAM HESAMIAN

July 2014

Chairman: Syamsiah Mashohor, PhD

Faculty: Engineering

Despite the rapidly expanding research into various aspects of illumination estimation methods, there are limited number of studies addressing illumination classification for different purposes. The increasing demand for color constancy process, wide application of it and high dependency of color constancy to illumination estimation makes this research topic challenging. Definitely, an accurate estimation of illumination in the image will provide a better platform for doing correction and finally will lead in better color constancy performance. The main purpose of any illumination estimation algorithm from any type and class is to estimate an accurate number as illumination. In scene illumination estimation dealing with large range of illumination and small variation of it is critical. Those algorithms which performed estimation carrying out lots of calculation that leads in expensive methods in terms of computing resources. There are several technical limitations in estimating an accurate number as illumination. In addition using light temperature in all previous studies leads to have complicated and computationally expensive methods. On the other hand classification is appropriate for applications like photography when most of the images have been captured in a small set of illuminants like scene illuminant. This study aims to develop a framework of image illumination classifier that is capable of classifying images under different illumination levels with an acceptable accuracy. The method will be tested on real scene images captured with illumination level is measured. This method is a combination of physic based methods and data driven (statistical) methods that categorize the images based on statistical features extracted from illumination histogram of image. The result of categorization will be validated using inherent illumination data of scene. Applying the improving algorithm for characterizing histograms (histogram quartering) handed out the advantages of high accuracy. A trained neural network which is the parameters are tuned for this specific application has taken into account in order to sort out the image into predefined groups. Finally, for performance and accuracy evaluation misclassification error percentages, Mean Square Error (MSE), regression analysis and

response time are used. This developed method finally will result in a high accuracy and straightforward classification system especially for illumination concept. The results of this study strongly demonstrate that light intensity with the help of a perfectly tuned neural network can be used as the light property to establish a scene illumination classification system.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Master Sains

**PENKELASAN PENCAHAYAAN Pemandangan BERDASARKAN
PEMBAHAGIAN HISTOGRAM KOMPONEN CIE-Y**

Oleh

MOHAMMAD HESAM HESAMIAN

Julai 2014

Pengerusi: Syamsiah Mashohor, PhD

Fakulti: Kejuruteraan

Di sebalik penyelidikan yang sedang berkembang pesat dari pelbagai aspek dalam kaedah penganggaran pencahayaan, kajian mengenai pengkelasan pencahayaan bagi tujuan tertentu adalah terhad. Permintaan yang tinggi terhadap proses pemalaran warna ('color constancy'), aplikasinya yang luas dan kebergantungan pemalaran warna terhadap anggaran pencahayaan, menjadikan topik ini mencabar. Yang pasti, penganggaran pencahayaan yang tepat dalam sesuatu imej akan menyediakan satu platform yang lebih baik untuk sebarang penambahbaikan dan akhirnya akan menghasilkan prestasi pemalaran warna yang lebih baik. Tujuan utama bagi semua algoritma penganggaran pencahayaan dari sebarang kelas dan jenis ialah untuk menganggar satu nombor yang tepat bagi pencahayaan. Bagi scenario pemandangan, penganggaran pencahayaan berhadapan dengan lingkungan pencahayaan yang besar dan perubahan yang kecil adalah kritikal. Semua algoritma yang melaksanakan penganggaran ini melibatkan banyak pengiraan yang menjadikannya kaedah yang mahal terutamanya dari segi sumber perkomputeran. Terdapat beberapa kekangan teknikal dalam penganggaran satu nombor yang tepat bagi pencahayaan. Tambahan pula, dengan penggunaan suhu cahaya dalam kajian sebelum ini menjadikannya lebih rumit dan memerlukan pengiraan yang berkos tinggi. Di samping itu, pengkelasan ini bersesuaian dengan aplikasi seperti fotografi, apabila kebanyakan imej diambil dalam set pencahayaan yang kecil seperti pencahayaan pemandangan. Kajian ini bertujuan untuk membangunkan satu rangka kerja pengkelasan pencahayaan imej yang berkebolehan untuk mengklasifikasikan imej di bawah tahap-tahap pencahayaan yang berbeza dengan satu ketepatan yang boleh diterima. Kaedah ini akan diuji pada imej pemandangan yang sebenar yang diambil dengan tahap pencahayaan yang telah diukur. Teknik ini ialah gabungan kaedah berasaskan fizik dan kaedah statistik yang mengkategorikan imej berdasarkan data pencahayaan yang diekstrak daripada histogram pencahayaan imej. Keputusan yang di perolehi daripada pengkelasan akan di sahkan menggunakan data

pencahayaan pemandangan. Penggunaan algoritma yang ditambah baik untuk menyifatkan histogram (*‘histogram quartering’*) dapat memberikan kelebihan ketepatan yang tinggi. Satu rangkaian neural (Neural network) terlatih yang mana parameternya telah diubahsuai untuk aplikasi tertentu telah diambil kira untuk mengatur imej kepada beberapa kumpulan yang telah ditetapkan. Akhir sekali, bagi penilaian prestasi dan ketepatan, kaedah *‘misclassification error percentages’*, dan *mean square error* (MSE) telah di gunakan. Kaedah ini akan menghasilkan sistem pengkelasan yang mudah dan mempunyai kadar ketepatan yang tinggi, terutamanya bagi konsep pencahayaan. Hasil kajian menunjukkan bahawa keamatan cahaya dengan bantuan rangkaian neural yang diperkemas secara sempurna dapat digunakan sebagai ciri-ciri cahaya dalam menghasilkan sistem pengkelasan pencahayaan pemandangan.



ACKNOWLEDGEMENTS

All praise and gratitude will be to Allah the almighty for his mercy and support during course of our life and moments of truth.

First and foremost, I would acknowledge to my dear supervisor Dr. Syamsiah Mashohor for her continuous and endless supervisions and encouragements.

My deep gratitude to my co-supervisors Assoc.Prof. Dr. Iqbal Saripan for his pure assistance and brotherly helps not only in study but also in many other aspects which never be forgotten.

I would like to extend my thanks to Dr.Wan Azizun Wan Adnan for her effective guides. I would also like to express my gratitude to Sharifah Farhana, Payam Farzan, Mostafa Behzady and Mohd Hafrizal who given me moral support and all my friends in UPM collage P1 and multimedia/embedded office that I have lots of unforgettable memories with them.



I certify that a Thesis Examination Committee has met on 22 July 2014 to conduct the final examination of Mohammadhesam Hesamian on his thesis entitled "Scene Illumination Classification Based on Histogram Quartering of Cie Y-Component" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U. (A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

Fakhrul Zaman bin Rokhani, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Abd. Rahman bin Ramli, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Sharifah Mumtazah Syed Ahmad Abdul Rahman, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Azizah binti Abdul Manaf, PhD

Professor
Advanced Infomatics School (Ais)
Utm International Campus
(External Examiner)



ZULKARNAIN ZAINAL, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

26 February 2015

This thesis was submitted to the Senate of the Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science.

The members of the Supervisory Committee were as follows:

Syamsiah binti Mahohor, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Mohd Iqbal bin Saripan, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Wan Azizun binti Wan Adnan, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

BUJANG BIN KIM HUAT, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work
- quotations, illustrations and citations have been duly referenced
- the thesis has not been submitted previously or concurrently for any other degree at any institutions
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be owned from supervisor and deputy vice –chancellor (Research and innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software

Signature: _____ Date: _____

Name and Matric No.: Mohammad Hesam Hesamian GS31112

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: _____

Name of
Chairman of
Supervisory
Committee: _____

Signature: _____

Name of
Member of
Supervisory
Committee: _____

Signature: _____


Name of
Member of
Supervisory
Committee: _____

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABLES	xiii
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xix
CHAPTER	
1 INTRODUCTION	1
1.1 Introduction	1
1.2 Background	2
1.3 Problem Statement	2
1.4 Research Aim and Objectives	3
1.5 Scope of Study	3
1.6 Contribution of Thesis	3
1.7 Outline of Thesis	4
2 LITERATURE REVIEW	5
2.1 Introduction	5
2.2 Image Classification	5
2.3 Image Illumination	5
2.4 Scene Illumination Estimation	6
2.4.1 Static Methods	7
2.4.1.1 Low Level Statistic Based Methods	8
2.4.1.2 Physics Based Methods	8
2.4.2 Gamut-Based Methods	8
2.4.3 Learning Based Methods	9
2.4.4 Comparison of Illumination Estimation Methods	10
2.5 Machine Learning Scene Illumination Classification	14
2.6 Neural Network Parameter Tuning	16
2.7 Summary	16
3 METHODOLOGY	18
3.1 Introduction	18
3.2 Data Collection	21
3.3 Image Preprocessing	22
3.4 Feature Selection And Extraction	23
3.4.1 Feature Selection	24
3.4.1.1 Surrounding Illumination Value	24
3.4.1.2 Mean of Image Illumination	25

	3.4.1.3 Mode of Image Illumination	26
	3.4.1.4 Median of Image Illumination	27
	3.4.1.5 Illumination Histogram Quartering	28
3.5	Cluster Definition	32
3.6	Neural Network	32
	3.6.1 Neural Network Classifier Design	33
	3.6.2 Neural Network Implementation	37
	3.6.2.1 Preparing Input Matrixes	37
	3.6.2.2. Creating a Pattern Recognition Network	40
	3.6.2.3. Data Division	40
	3.6.3 Parameter Tuning	41
	3.6.3.1 Learning Rate (LR)	41
	3.6.3.2. Number of Epochs	41
	3.6.3.3. Goal	42
	3.6.3.4. Maximum Validation Check	42
	3.6.3.5. Minimum Gradient Magnitude	42
	3.6.3.6. Momentum Constant (MC)	42
	3.6.3.7. Training Time	42
	3.6.3.8. Weight Update Rate (Mu)	42
3.7	Performance Evaluation	43
	3.7.1 Misclassification Rate	44
	3.7.2 MSE	44
	3.7.3 Regression	44
	3.7.4 Response Time	44
3.8	Summary	45
4	RESULTS AND DISCUSSION	46
	4.1 Introduction	46
	4.2 Sample Distribution	46
	4.3 Feature Selection Results	48
	4.3.1 Testing System Setting	48
	4.3.2 Test Procedure	49
	4.3.3 Test Evaluation	49
	4.3.2 Misclassification Evaluation	50
	4.3.2.1 Single Feature Tests	52
	4.3.2.2. Dual Features Tests	55
	4.3.2.3. Triple Feature Test	59
	4.3.2.4 Histogram Quartering Results	61
	4.3.2.5 Full Feature Set	63
	4.3.3 Mean Square Error Evaluation	66
	4.3.4 Regression Evaluation	70
	4.3.5 Response Time Evaluation	71
	4.4 Parameter Tuning Results	73
	4.4.1 Learning Rate (LR)	73
	4.4.2 Number of Epoch	74
	4.4.3 Maximum Validation Check	76

4.4.4	Minimum Gradient Magnitude	78
4.4.5	Momentum Constant (MC)	79
4.4.6	Weight Update Rate (MU)	80
4.4.7	Best Parameter Tuning Set	81
4.5	Conclusion	83
5	CONCLUSION AND FUTURE WORKS	84
5.1	Conclusion	84
5.2	Future Works	86
	REFERENCES	87
	BIODATA OF STUDENT	93
	LIST OF PUBLICATIONS	94



LIST OF TABLES

Table		Page
2.1	Advantages and disadvantages of various illumination classification methods	11
2.2	The results of using sensor correlation for classification	12
2.3	The results of using sensor response for classification	12
2.4	Results of object based method for classification	14
2.5	Results of using chromaticity histogram for illumination estimation	13
2.6	Performance comparison of some famous illumination estimation methods	13
2.7	Results of testing selected algorithms on specific images	14
2.8	Performance of various illumination estimation methods on real images	15
2.9	Performance ranking of illumination estimation systems	16
3.1	Recommended neural network structure based on problem complexity	34
3.2	Performance of different neural network structures with various number of hidden layers and neurons	34
3.3	A fraction of input matrix	38
3.4	A fraction of target matrix	38
4.1	List of default value for NN parameters during feature selection tests	49
4.2	Number of misclassified samples by their type	54

4.3	Comparing Mean/Median with each individual involving feature	56
4.4	Comparison Mean/Mode with each individual involving feature	58
4.5	Comparison Mean/Mode with each individual involving feature	59
4.6	Comparison histogram Quarter features with Mean/Mode/Median feature	62
4.7	Comparison of full feature set with histogram quartering and 4 feature set	65
4.8	Output matrix for some samples. The highest corresponding cluster of highest value in each column will be the belonging value class of the sample	66
4.9	Target matrix of some samples	67
4.10	Target value and output value for two samples to compare corresponding MSE	68
4.11	Value of NN parameters after parameter tuning	81
5.1	Significant improving effect of histogram quartering	85
5.2	Significant effect of parameter tuning	85

LIST OF FIGURES

Figure		Page
2.1	Process of color constancy	6
2.2	Classification of color constancy methods	7
2.3	Workflow of gamut based methods	9
2.4	Another proposed categorization of color constancy methods	10
3.1	General image classification system steps with subroutines	19
3.2	Flowchart of designed classification system	20
3.3	A: Sample of low illumination image, B: sample of high illumination image	21
3.4	Sample of three different images with their corresponding SIV	25
3.5	Sample of image with their corresponding Mean value	26
3.6	Sample of images with their corresponding Y component histogram and Mode value	27
3.7	Sample of images with their corresponding Y component histogram and Median value	28
3.8	The most ideal illumination histogram	29
3.9	Sample of histograms. The imposed red line refers to the ideal illumination histogram	30
3.10	Sample of image histograms with their corresponding quarter's value. Vertical lines separating quarters from each other and horizontal line refers to ideal histogram level	31
3.11	Result of testing various NN structure	36

3.12	The designed neural network structure	37
3.13	The block diagram of neural network with inputs and outputs	39
4.1	Distribution of samples by number of samples and group share	46
4.2	Sample distribution of low illumination cluster	47
4.3	Sample distribution of ideal illumination cluster	47
4.4	Sample distribution of ideal illumination cluster	48
4.5	Effect of repeating a test on achieved accuracy	50
4.6	Evaluation of feature sets efficiency based on misclassification rate	51
4.7	Two sample of images misclassified by Mean feature	52
4.8	Confusion matrix of single feature tests, the green cells are correctly classified samples, red cells are misclassified samples and blue is total accuracy	53
4.9	Sample of misclassified images using Mode feature	54
4.10	Confusion matrix of all dual feature sets	56
4.11	Sample of misclassified images by using Mean/Median	57
4.12	Sample of misclassified image using Mean/Mode	58
4.13	Sample of misclassified images using Mean/Mode/Median	60
4.14	Confusion matrix of triple feature tests	61
4.15	Confusion matrix of histogram quartering	62

4.16	Sample of misclassified images using histogram quartering feature alone	63
4.17	Confusion matrix of full feature set	64
4.18	Sample of images misclassified by full feature set	65
4.19	Corresponding illumination histogram of misclassified samples shown in Figure 4.18	66
4.20	Evaluation of feature sets efficiency based on MSE	69
4.21	Evaluation of feature sets efficiency based on regression coefficient	71
4.22	Evaluation of feature sets efficiency based on response time	72
4.23	Effect of changing LR on all four performance evaluation parameters. A for misclassification rate, B for MSE, C for regression coefficient, D for response time	74
4.24	Effect of changing number of epochs on all four performance evaluation parameters. A for misclassification rate, B for MSE, C for regression coefficient, D for response time	75
4.25	Effect of increasing the maximum validation check on MSE, $x_1 < x_2 < x_3$ and $n_1 < n_2 < n_3$	76
4.26	Effect of changing maximum fail on all four performance evaluation parameters. A for misclassification rate, B for MSE, C for regression coefficient, D for response time	77
4.27	Effect of changing minimum gradient on all four performance evaluation parameters. A for misclassification rate, B for MSE, C for regression coefficient, D for response time	78
4.28	Effect of changing MC on all four performance evaluation parameters. A for misclassification rate, B for MSE, C for regression coefficient, D for response time	79
4.29	Effect of changing MU on all four performance evaluation parameters. A for misclassification rate, B for MSE, C for regression coefficient, D for response time	80



LIST OF ABBREVIATIONS

ANN	Artificial Neural Network
BP	Back Propagation
CBIR	Content based image retrieval
CIE XYZ	Color model
CPU	Central Processing Unit
E(x)	Estimation of surrounding illumination
GHz	Giga Hertz
HVS	Human Visual System
ISO DATA	Iterative Self Organizing Data Analysis
Klux	Kilo Lux
LR	Learning Rate
MC	Momentum Constant
MSE	Mean Square Error
MU	Weight Update Rate
NN	Neural Network
Q1	First Quarter

Q2	Second quarter
Q3	Third Quarter
Q4	Fourth Quarter
R	Regression Coefficient
$R(\lambda)$	Camera sensor response
RGB	Red, Green and Blue color model
$S(\lambda)$	Surface reflectance
SIV	Surrounding Illumination Value
Y	Illumination component

CHAPTER ONE

INTRODUCTION

1.1 Introduction

Image as a way of collecting data is used widely in many aspects of knowledge. A wide range of applications and systems are applying images as their input material and analysis performed on them[1]. This range cover form home fun applications to medical, military and astronomy applications[2]. But in all of the image applications dealing with illumination is a challenge. From home application in which poor lighting will result in low quality images, to pattern recognition systems which the illumination can affect the result of classification system.

Generally, light sources have a huge effect on the perception of colors. Practically, no color will be exist in the absence of light source. Varying amount of light from a light source makes changes in the perceived colors. For example a dark red surface will appear as a light orange under a high illumination yellow light source. Since human eye has ability of perceiving a constant color of an object under varying illumination, similar color constancy is indispensable for many computer vision and image processing tasks. It can be applied in many fields like object recognition, data base retrieval, color balance, material detection, machine vision and scene classification.

The color constancy process can be defined as transforming source images being taken under different colored light source to a target image captured under a white light source. In other word, color constancy tries to eliminate the effect of light source color and its intensity on the objects color[1].

Any color constancy process or algorithm consists of two critical primary stages: illumination estimation and illumination correction. Highly dependency of color constancy process to illumination estimation proves the importance of illumination estimation.

Definitely, an accurate estimation of illumination in the image will provide a better platform for doing correction and finally will lead in better color constancy performance. On the other hand it is impossible to expect significant results from a color constancy process which is established on not accurate estimation.

Scene classification systems also like other image based systems have been affected widely by illumination variation. Scene classification as one of the subsets of CBIR (content based image retrieval) has many usages in scene recognition, event classification, enquiry and retrieval. Hence, performing a good illumination estimation will increase the efficiency in all above mentioned applications.

1.2 Background

Previously many illumination estimation systems have been proposed in order to estimate the illumination value of the environment in which image captured from. All of them have some common limitation for example using strict assumptions[3], space dependent[4], being limited to some certain illumination condition[5], having complicated calculation or being costly. On account of all short coming of illumination estimation and better performance of illumination classification in case of scene illumination issue, scene illumination classification become a hot research topic in color constancy process. Moreover, illumination classification has been addressed by fewer studies and until now, there is no study focused on light intensity property.

1.3 Problem Statement

Despite the rapidly expanding research into various aspects of illumination estimation methods, still there is an increasing demand for illumination estimation process in order to achieve better results in color constancy[6]. The limited number of studies addressing illumination classification for different purposes highlights the necessity of this study. Hence this study seeks to investigate this area by proposing a new method which aims to classify scene illumination by focusing on light source intensity that is not explored by any study before.

The first step of color constancy process is the illumination estimation[7]. Illumination estimation aims to estimate an accurate number for the illuminant which has huge direct effect on next steps of color constancy process. Finally, illumination estimation performance will affect the results of color constancy and color correction process. Therefore a high performance and effective illumination estimation will provide a high performance color constancy.

Those algorithms which perform illumination estimation by analyzing light source color temperature, carrying out lots of calculation that leads in expensive methods in terms of computing resources and unstable methods[7]. Most of the applications that using the output of illumination estimation systems do not necessarily need an exact illumination number for their further processing. As far as scene images are usually can be divided into some general groups, illumination classification is a better option to replace illumination estimation in order to categorize the illumination data in some classes[8].

Focusing too much on the extracted data from color temperature of light in image and ignoring the intensity property of light can be interpreted as one of the barriers to achieve better performance. Covering this gap by using some data extracted from the intensity of light is proposed as a potential solution.

There are several technical limitations in estimating an accurate number as illumination[9]. For example changing the angle between camera and light source will change the amount of received light. Although no change happens in the surrounding illuminant but we will get a different illumination value. On the other hand, classification is appropriate for applications like photography when most of the images have been captured in a small set of illuminants like scene illuminant.

The point of developing an illumination classification system is to prepare a better platform for color constancy process and decrease the need for illumination estimation and many relevant expensive computations to the minimal level possible[10]. Developing a high accuracy classification method the on image illumination will increase the accuracy color constancy methods.

1.4 Research Aim and Objectives

This study aims to develop a framework of image illumination classifier that is capable of classifying images under different illumination levels with an acceptable accuracy. This developed method finally will result in a high accuracy classification system especially for illumination concept.

The followings are the main objectives of this research:

- I. To use light intensity represented by CIE-Y component for image illumination classification instead of light temperature.
- II. To design the neural network architecture for image illumination classification using statistical and physic based features.
- III. To apply an improving algorithm of histogram quartering which can increase the system performance by offering better histogram matching.
- IV. To tune the neural network parameters to increase the accuracy and finding the best parameter set.

1.5 Scope of Study

This study mainly focused on classifying the scene images based on their illumination. The data which have been used are real scene images captured by a Canon D5 camera in various illumination conditions. More than 800 RGB images in the format of JPEG have collected from Serdang and Putrajaya in Malaysia for this study. Implementation and testing was done on a Core2Duo Intel processor with the power of 2.4 GHz. All the coding and programs were written using Matlab 7.11.0584 (R2010B).

1.6 Contribution of Thesis

In this research an illumination classification system designed and developed. This method performed the classification based on analyzing the light intensity and its related effects in image which previously has not been addressed in other study. It proves that in scene illumination classification light intensity is capable enough to perform high accuracy rate.

In this study benefiting from two main types of classification algorithms results in having less computational load and the high accuracy of classification. On the other hand proposed method does not based on strict assumptions.

There are many well-known illumination estimation algorithms like Gray worlds and Gamut mapping which based on many strict assumptions, computationally expensive and moreover some of them need many detail side information of illumination.

The proposed method in this thesis is carrying out not much huge mathematical computation compare to Gamut mapping approach which reduces the system load and caused in faster response. This method has low complexity and flexible; that with applying very little changes it can be modified for many other applications.

The main contribution of this study lies in the fact that illumination information extracted from the CIE-Y component can be used for illumination classification. The proposed method without requiring any extra information like using specific object in the scene, can classify the image illumination.

1.7 Outline of Thesis

The remaining chapters of this thesis are organized as follow:

Chapter 2 is a critical literature review which will provide the reader with necessary information about image illumination classification methods and neural network based classification, their strengths and weak points.

Chapter 3 is dealing with the applied methodology. It discusses about idea, relevant theory, development of method and improving steps of proposed method. The steps are involved with data collection, preprocessing of image, neural network architecture design, feature extraction, improvement of proposed algorithm and illumination classification.

Chapter 4 is related to analyzing and discussing about the achieved results of classification system. It draws a comparison with the other algorithms introduced in literature in order to highlights the performance of proposed method.

Chapter 5 summarizes the obtained results and makes a conclusion. In the second part it suggest some further ideas for future studies to cover the weak points based on analyzed results.

REFERENCES

- [1] D. Hilbert, "Color constancy and the complexity of color," *Philosophical Topics*, vol. 33, p. 141, 2005.
- [2] L. Zhou, Z. Zhou, and D. Hu, "Scene classification using a multi-resolution bag-of-features model," *Pattern Recognition*, vol. 46, pp. 424-433, 2013.
- [3] A. Gijssenij and T. Gevers, "Color constancy using natural image statistics and scene semantics," *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, vol. 33, pp. 687-698, 2011.
- [4] R. Kimmel, D. Shaked, M. Elad, and I. Sobel, "Space-dependent color gamut mapping: A variational approach," *Image Processing, IEEE Transactions on*, vol. 14, pp. 796-803, 2005.
- [5] A. Ibrahim, T. Horiuchi, and S. Tominaga, "Illumination-invariant representation for natural color images and its application," in *Image Analysis and Interpretation (SSIAI), 2012 IEEE Southwest Symposium on*, 2012, pp. 157-160.
- [6] M. Ebner, "Evolving color constancy," *Pattern recognition letters*, vol. 27, pp. 1220-1229, 2006.
- [7] C.-T. Lin, K.-W. Fan, and W.-C. Cheng, "An illumination estimation scheme for color constancy based on chromaticity histogram and neural network," in *Systems, Man and Cybernetics, 2005 IEEE International Conference on*, 2005, pp. 2488-2494.
- [8] H. Z. Hel-Or and B. A. Wandell, "Object-based illumination classification," *Pattern recognition*, vol. 35, pp. 1723-1732, 2002.
- [9] C. B. Madsen and B. B. Lal, "Outdoor illumination estimation in image sequences for augmented reality," 2011.
- [10] S. Tominaga, S. Ebisui, and B. A. Wandell, "Scene illuminant classification: brighter is better," *JOSA A*, vol. 18, pp. 55-64, 2001.
- [11] D. Lu and Q. Weng, "A survey of image classification methods and techniques for improving classification performance," *International journal of Remote sensing*, vol. 28, pp. 823-870, 2007.
- [12] M. J. De Smith, M. F. Goodchild, and P. A. Longley, *Geospatial analysis: a comprehensive guide to principles, techniques and software tools*: Troubador Publishing Ltd, 2007.

- [13] S. Kang and S. Park, "A fusion neural network classifier for image classification," *Pattern Recognition Letters*, vol. 30, pp. 789-793, 2009.
- [14] J. A. Richards, "Clustering and unsupervised classification," in *Remote Sensing Digital Image Analysis*, ed: Springer, 2013, pp. 319-341.
- [15] S. A. Mingoti and J. O. Lima, "Comparing SOM neural network with Fuzzy means, K-means and traditional hierarchical clustering algorithms," *European Journal of Operational Research*, vol. 174, pp. 1742-1759, 2006.
- [16] G. Krawczyk, K. Myszkowski, and H.-P. Seidel, "Computational model of lightness perception in high dynamic range imaging," in *Proceedings of SPIE*, 2006, pp. 65-76.
- [17] K. Barnard, G. Finlayson, and B. Funt, "Color constancy for scenes with varying illumination," *Computer vision and image understanding*, vol. 65, pp. 311-321, 1997.
- [18] S. D. Hordley and G. D. Finlayson, "Re-evaluating colour constancy algorithms," in *Pattern Recognition, 2004. ICPR 2004. Proceedings of the 17th International Conference on*, 2004, pp. 76-79.
- [19] B. V. Funt, M. S. Drew, and J. Ho, "Color constancy from mutual reflection," *International Journal of Computer Vision*, vol. 6, pp. 5-24, 1991.
- [20] A. Gijsenij, T. Gevers, and J. Van De Weijer, "Computational color constancy: Survey and experiments," *Image Processing, IEEE Transactions on*, vol. 20, pp. 2475-2489, 2011.
- [21] F. Dugay, I. Farup, and J. Y. Hardeberg, "Perceptual evaluation of color gamut mapping algorithms," *Color Research & Application*, vol. 33, pp. 470-476, 2008.
- [22] M. Ebner, *Color constancy* vol. 6: Wiley. com, 2007.
- [23] K. Barnard, V. Cardei, and B. Funt, "A comparison of computational color constancy algorithms. I: Methodology and experiments with synthesized data," *Image Processing, IEEE Transactions on*, vol. 11, pp. 972-984, 2002.
- [24] R. Lenz, P. Meer, and M. Hauta-Kasari, "Spectral-based illumination estimation and color correction," *COLOR research and application*, vol. 24, pp. 98-111, 1999.
- [25] A. Gijsenij, R. Lu, and T. Gevers, "Color constancy for multiple light sources," *Image Processing, IEEE Transactions on*, vol. 21, pp. 697-707, 2012.
- [26] J. Morović, *Color gamut mapping* vol. 10: Wiley. com, 2008.

- [27] G. D. Finlayson, S. D. Hordley, and P. M. Hubel, "Color by correlation: A simple, unifying framework for color constancy," *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, vol. 23, pp. 1209-1221, 2001.
- [28] V. Agarwal, B. R. Abidi, A. Koschan, and M. A. Abidi, "An overview of color constancy algorithms," *Journal of Pattern Recognition Research*, vol. 1, pp. 42-54, 2006.
- [29] K. Barnard and B. Funt, "Camera characterization for color research," *Color Research & Application*, vol. 27, pp. 152-163, 2002.
- [30] S. Tominaga and B. A. Wandell, "Natural scene-illuminant estimation using the sensor correlation," *Proceedings of the IEEE*, vol. 90, pp. 42-56, 2002.
- [31] A. Gijsenij and T. Gevers, "Color constancy using natural image statistics," in *Computer Vision and Pattern Recognition, 2007. CVPR'07. IEEE Conference on*, 2007, pp. 1-8.
- [32] F. Ciurea and B. Funt, "A large image database for color constancy research," in *Color and Imaging Conference*, 2003, pp. 160-164.
- [33] Y. Guo and M. Xie, "Illumination estimation in natural scenes with color gamut mapping algorithm," in *Information Technology in Medicine and Education (ITME), 2012 International Symposium on*, 2012, pp. 1075-1078.
- [34] G. P. Zhang, "Neural networks for classification: a survey," *Systems, Man, and Cybernetics, Part C: Applications and Reviews, IEEE Transactions on*, vol. 30, pp. 451-462, 2000.
- [35] V. C. Cardei, B. Funt, and K. Barnard, "Estimating the scene illumination chromaticity by using a neural network," *JOSA A*, vol. 19, pp. 2374-2386, 2002.
- [36] S. D. Hordley, "Scene illuminant estimation: past, present, and future," *Color Research & Application*, vol. 31, pp. 303-314, 2006.
- [37] K. Suzuki, I. Horiba, and N. Sugie, "A simple neural network pruning algorithm with application to filter synthesis," *Neural Processing Letters*, vol. 13, pp. 43-53, 2001.
- [38] J.-T. Tsai, J.-H. Chou, and T.-K. Liu, "Tuning the structure and parameters of a neural network by using hybrid Taguchi-genetic algorithm," *Neural Networks, IEEE Transactions on*, vol. 17, pp. 69-80, 2006.
- [39] F. H.-F. Leung, H.-K. Lam, S.-H. Ling, and P. K.-S. Tam, "Tuning of the structure and parameters of a neural network using an improved genetic algorithm," *Neural Networks, IEEE Transactions on*, vol. 14, pp. 79-88, 2003.

- [40] M. Bashiri and A. Farshbaf Geranmayeh, "Tuning the parameters of an artificial neural network using central composite design and genetic algorithm," *Scientia Iranica*, vol. 18, pp. 1600-1608, 2011.
- [41] K. Barnard and B. Advertiser-Funt, *Practical colour constancy*: Simon Fraser University, 1999.
- [42] B. Funt, K. Barnard, and L. Martin, "Is machine colour constancy good enough?," in *Computer Vision—ECCV'98*, ed: Springer, 1998, pp. 445-459.
- [43] G. D. Finlayson, S. Hordley, and P. M. Hubel, "Illuminant estimation for object recognition," *Color Research & Application*, vol. 27, pp. 260-270, 2002.
- [44] K. Barnard, L. Martin, A. Coath, and B. Funt, "A comparison of computational color constancy algorithms. II. Experiments with image data," *Image Processing, IEEE Transactions on*, vol. 11, pp. 985-996, 2002.
- [45] M. A. Turk and A. P. Pentland, "Face recognition using eigenfaces," in *Computer Vision and Pattern Recognition, 1991. Proceedings CVPR'91., IEEE Computer Society Conference on*, 1991, pp. 586-591.
- [46] L. Chen, N. Tokuda, A. Nagai, and X. Chen, "Is High Resolution Representation More Effective for Content Based Image Classification?," in *Neural Networks, 2006. IJCNN'06. International Joint Conference on*, 2006, pp. 4045-4050.
- [47] V. C. Design, "Video codec design," 2002.
- [48] G. Paschos and M. Petrou, "Histogram ratio features for color texture classification," *Pattern Recognition Letters*, vol. 24, pp. 309-314, 2003.
- [49] P. A. Devijver and J. Kittler, *Pattern recognition: A statistical approach*: Prentice/Hall International Englewood Cliffs, NJ, 1982.
- [50] C. M. Bishop, *Neural networks for pattern recognition*: Oxford university press, 1995.
- [51] A. K. Jain, R. P. W. Duin, and J. Mao, "Statistical pattern recognition: A review," *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, vol. 22, pp. 4-37, 2000.
- [52] P. T. von Hippel, "Mean, median, and skew: Correcting a textbook rule," *Journal of Statistics Education*, vol. 13, p. n2, 2005.
- [53] E. W. Weisstein, "Mode. From MathWorld," ed.
- [54] E. W. Weisstein, "Statistical Median," *Math World-A*, 2010.

- [55] A. David, "Metric Handbook Planning and Design Data," ed: Reed Educational and Professional Publishing Ltd, 1999.
- [56] K. Hornik, "Approximation capabilities of multilayer feedforward networks," *Neural networks*, vol. 4, pp. 251-257, 1991.
- [57] D. L. Chester, "Why two hidden layers are better than one," in *Proceedings of the international joint conference on neural networks*, 1990, pp. 265-268.
- [58] I. Kanellopoulos and G. Wilkinson, "Strategies and best practice for neural network image classification," *International Journal of Remote Sensing*, vol. 18, pp. 711-725, 1997.
- [59] J. Heaton, *Introduction to neural networks for Java*: Heaton Research, Inc., 2008.
- [60] M. T. Hagan, H. B. Demuth, and M. H. Beale, *Neural network design*: Pws Pub. Boston, 1996.
- [61] Y. LeCun, L. Jackel, L. Bottou, C. Cortes, J. S. Denker, H. Drucker, *et al.*, "Learning algorithms for classification: A comparison on handwritten digit recognition," *Neural networks: the statistical mechanics perspective*, vol. 261, p. 276, 1995.
- [62] Y. LeCun, L. Jackel, L. Bottou, A. Brunot, C. Cortes, J. Denker, *et al.*, "Comparison of learning algorithms for handwritten digit recognition," in *International conference on artificial neural networks*, 1995.
- [63] K. Chellapilla, K. Larson, P. Y. Simard, and M. Czerwinski, "Computers beat Humans at Single Character Recognition in Reading based Human Interaction Proofs (HIPs)," in *CEAS*, 2005.
- [64] R. Salakhutdinov and G. E. Hinton, "Learning a nonlinear embedding by preserving class neighbourhood structure," in *International Conference on Artificial Intelligence and Statistics*, 2007, pp. 412-419.
- [65] D. Claudiu Ciresan, U. Meier, L. M. Gambardella, and J. Schmidhuber, "Deep Big Simple Neural Nets Excel on Handwritten Digit Recognition," *arXiv preprint arXiv:1003.0358*, 2010.
- [66] D. Ciresan, U. Meier, and J. Schmidhuber, "Multi-column deep neural networks for image classification," in *Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on*, 2012, pp. 3642-3649.
- [67] L. Fausett, "Fundamental of neural networks," *Florida Institute of Technology*, vol. 4, 1994.

- [68] D. L. Bailey and D. Thompson, "Developing neural-network applications," *AI expert*, vol. 5, pp. 34-41, 1990.
- [69] J. O. Katz, "Developing neural network forecasters for trading," *Technical Analysis of Stocks and Commodities*, vol. 10, pp. 160-168, 1992.
- [70] C. C. Klimasauskas, "Applying neural networks," *Neural networks in finance and investing*, pp. 47-72, 1993.
- [71] M. T. Hagan and M. B. Menhaj, "Training feedforward networks with the Marquardt algorithm," *Neural Networks, IEEE Transactions on*, vol. 5, pp. 989-993, 1994.
- [72] M. Moreira and E. Fiesler, "Neural networks with adaptive learning rate and momentum terms," *Technique Report 95*, vol. 4, 1995.
- [73] N. Abdul Hamid, N. Mohd Nawi, R. Ghazali, M. Salleh, and M. Najib, "Improvements of back propagation algorithm performance by adaptively changing gain, momentum and learning rate," *International Journal of New Computer Architectures and Their Applications (IJNCAA)*, vol. 1, pp. 889-901.
- [74] B. M. Hudson, T. Hagan Martin, and B. Demuth Howard, "Neural Network Toolbox™ User's Guide," ed: MathWorks, 2012.
- [75] H. R. Maier and G. C. Dandy, "The effect of internal parameters and geometry on the performance of back-propagation neural networks: an empirical study," *Environmental Modelling & Software*, vol. 13, pp. 193-209, 1998.
- [76] D. J. Hand, "Recent advances in error rate estimation," *Pattern Recognition Letters*, vol. 4, pp. 335-346, 1986.
- [77] M. Weintraub, F. Beaufays, Z. e. Rivlin, Y. Konig, and A. Stolcke, "Neural-network based measures of confidence for word recognition," in *Acoustics, Speech, and Signal Processing, 1997. ICASSP-97., 1997 IEEE International Conference on*, 1997, pp. 887-890.
- [78] J. Armstrong, "Illusions in regression analysis," *Available at SSRN 1969740*, 2011.