

UNIVERSITI PUTRA MALAYSIA

EXPERIMENTAL DETERMINATION OF SAFE SERVICE LIFE OF MOTORCYCLE HELMET

AZHAR HAMZAH

FK 2016 123



EXPERIMENTAL DETERMINATION OF SAFE SERVICE LIFE OF MOTORCYCLE HELMET



Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in Fulfillment of the Requirements for the Degree of Master of Science

May 2016

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



DEDICATIONS

I would like to dedicate this work to:

ALLAH SWT for His Blessings

My beloved mother who is always there for me, anytime and every time.....

Zainab Mohamad

My significant other, my dear wife who relentlessly keeps supporting.....

Intina Pandak

My enthusiastic children, who keep asking for answers

Ainaa, Alyaa, Alif

My siblings and friends, who keep the spirit up

Thank you for all the supports, guidance, encouragements and trusts

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the Degree of Master of Science

EXPERIMENTAL DETERMINATION OF SAFE SERVICE LIFE OF MOTORCYCLE HELMET

By

AZHAR HAMZAH

May 2016

Chairman: Professor Wong Shaw Voon, PhDFaculty: Engineering

The most distressing trauma in motorcycle crashes is head injury which has caused over 50% of motorcyclist death. Such rate stresses the importance of an effective protective equipment, the motorcycle safety helmet. Helmet protects by reducing the impact forces from reaching the users' heads upon impact contact. New helmets performance is well assured, however, after a certain period of use, their performance may deteriorate to less than optimum due to environmental and use factors such as ultraviolet exposures and unintentional drops/impacts. There is scarce information on the impact performance of used helmet. This performance is usually measured by headform acceleration in laboratory test.

This study attempts to determine used helmet impact performance with regards to headform acceleration performance in impact test. It intends to determine used helmet headform acceleration performance relative to service age, examine headform acceleration performance at critical side and identify factors affecting used helmet headform acceleration performance.

The study involves performing impact test in an established test facility, SIRIM QAS, Shah Alam. It utilises the Malaysian helmet standards protocol, MS1:1996, as the basis for conducting experiment and acquiring the headform acceleration values. In brief, 65 helmet samples were collected randomly near Kajang and Semenyih townships. These helmet varies in service ages and in a number of physical attributes such as shell and liner thickness, though all were certified to the same test standards when new. 10 of 65 helmets (15.4%) were not tested due to failure in complying with the fit-for test criteria. 55 helmets were impact tested at four sides per helmet (front, right, left and rear) and the variables studied were headform acceleration, service age, helmet mass, shell thickness, liner thickness and density, impact speed and impact energy. Two different impact severities were adopted, impact velocities of 6.4 m/s

onto a flat anvil and 5.8 m/s onto an hemispherical anvil. Helmets were randomly numbered and during test, the test order was systematically change to minimize bias.

The test result indicated the helmets have a wide spectrum of service ages, from 6 months to 167 months with a mean of 65 months. It reveals the retention pattern of helmet in the nearby townships. In addition, almost all helmets were capable of meeting the headform acceleration limit ($\leq 300g$) at different impact severities, despite all the conditions they may have gone through during use tenure. The key reason for the positively high pass to fail rate (96.4%) was possibly the filtering process of helmet samples which had basically removed a substantial number of helmets not fit-for-test (15.4%). Statistically, there were significant correlations of helmet headform acceleration to the service age, helmet mass, liner thickness, shell thickness and impact energy (p<0.05). There was no significant different of impact performance between the four impact sides (p>0.05). Helmet deterioration measurement was not quantified due to lack of baseline information. The samples make and model were not identifiable in many cases and the certification information is confidential.

The study also attempts to model headform acceleration with the assumption that the relationships between all independent variables (service age, helmet mass, shell thickness and liner thickness) and dependent variable (headform acceleration) was linear. Comparison of two aged helmets, 27 and 37 months showed that the prediction for higher impact energy (111J) was relatively closed to the actual test result (around 5%), however for lower impact energy (96J), the variation exceeds 18%. The linear assumption has limit the model applicability to a service age range of 24 months. Moreover, the small sample size of helmets (N=55) may not allow any deduction of conclusive evidence for any generalisation. A strict filtering process to qualify helmet for impact test may have removed important data and should be reconsidered in future work for more representative and conclusive information.

In short, the study has presented meaningful information on used motorcycle helmet impact performances relative to headform acceleration and associated factors. It has also established introductory data on helmet retention and performance pattern for motorcyclists.

Key words: Motorcycle helmet, headform acceleration

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Master Sains

EKSPERIMEN PENENTUAN JANGKA HAYAT SELAMAT TOPI KELEDAR MOTORSIKAL

Oleh

AZHAR HAMZAH

Mei 2016

Pengerusi : Profesor Wong Shaw Voon, PhD Fakulti : Kejuruteraan

Salah satu trauma yang merisaukan ialah kecederaan kepala yang menjangkau lebih 50% sebab kematian pengguna motorsikal. Kadar yang tinggi ini menekankan lagi kepentingan alat perlindungan, iaitu topi keledar keselamatan motorsikal. Topi keledar melindungi dengan cara menyerap daya impak daripada mengenai kepala pengguna ketika impak berlaku. Prestasi helmet baharu adalah terjamin, namun begitu, selepas satu tempoh penggunaan, prestasi topi keledar boleh menurun lebih rendah dari tahap optima disebabkan oleh faktor persekitaran seperti sinar ultraviolet dan impak yang tidak disengajakan. Maklumat berkaitan prestasi impak topi keledar terpakai amat kurang. Pada kebiasaannya, prestasi ini diukur oleh kadar pecutan alat 'headform, didalam ujian makmal.

Kajian ini berusaha untuk menentukan prestasi topi keledar terpakai melalui pecutan 'headform' ketika ujian hentakan. Ia akan cuba menentukan pecutan 'headform' berkait dengan umur penggunaan topi keledar, menguji pecutan dibahagian yang kritikal dan mengenalpasti faktor-faktor yang mempengaruhi pecutan 'headform'.

Kajian ini melibatkan ujian hentakan yang dilaksanakan di makmal ujian, SIRIM QAS, Shah Alam. Ia menggunapakai peraturan ujian standard topi keledar, MS1:1996 sebagai asas dan pengumpulan data pecutan. Secara ringkas, 65 biji topi keledar dikumpul secara rambang dari bandar Kajang dan Semenyih. Topi keledar ini berbeza daripada segi umur dan ciri-ciri fizikal seperti tebal cengkerang dan lapisan penyerap, walaupun semuanya telah lulus pengesahan standard yang sama ketika baharu. 10 dari 65 biji topi keledar (15.4%) tidak diuji kerana kegagalan menepati syarat-syarat layak untuk diuji. 55 biji topi keledar telah diuji, dengan setiap topi keledar dihentak pada 4 sisi (depan, kanan, kiri, belakang) dan pembolehubah yang diuji ialah pecutan 'headform', umur penggunaan, jisim topi keledar, tebal cengkerang, tebal dan ketumpatan lapisan penyerap, kelajuan hentakan dan tenaga hentakan. Dua jenis hentakan, kelajuan hentakan 6.4 m/s keatas tukul rata dan 5.8 m/s keatas tukul separa

bulat. Topi keledar telah dinomborkan secara rambang dan ketika ujian, susunan sisi diubah secara sistematik bagi mengurangkan keputusan yang berat sebelah.

Keputusan ujian menunjukkan sampel topi keledar mempunyai jurang umur penggunaan yang luas, daripada 6 bulan hingga 167 bulan, dengan umur purata 65 bulan. Ia mendedahkan corak penyimpanan topi keledar di bandar berdekatan. Sebagai tambahan, hampir semua topi keledar berjaya melepasi tahap lulus ($\leq 300g$) pada tahap kesukaran berbeza, walaupun telah melalui pelbagai cabaran semasa tempoh penggunaan. Kemungkinan tahap lulus yang tinggi ini (96.4%) berkait dengan proses penapisan kelayakan untuk ujian hentakan yang telah mengeluarkan topi keledar yang tidak layak. Secara statistic, ada perkaitan penting antara pecutan 'headform' dengan umur penggunaan, jisim topi keledar, tebal penyerap hentak, tebal cengkerang dan tenaga hentakan (p<0.05). Tiada perkaitan penting prestasi impak antara empat sisi yang diuji (p>0.05). Kemerosotan kualiti topi keledar tidak dapat disukat disebabkan ketiadaan maklumat asas. Kebanyakan jenama dan jenis topi keledar tidak dapat dikenal pasti dan maklumat persijilan dirahsiakan.

Kajian ini cuba membangunkan model mudah berkaitan pecutan 'headform' dengan andaian perkaitan antara pembolehubah bebas (umur penggunaan, jisim topi keledar, tebal cengkerang dan tebal lapisan penyerap) dan pecutan 'headform' adalah berkadar terus. Perbandingan antara dua biji topi keledar berumur 27 dan 37 bulan menunjukkan anggaran pecutan 'headform' untuk ujian hentakan tenaga tinggi (111J) sangat rapat dengan pecutan 'headform' yang sebenar (sekitar 5%), walaubagaimanapun, untuk ujian hentakan tenaga rendah (96J), perbezaannya melebihi 18%. Andaian berkadar terus telah menyebabkan model ini hanya terpakai untuk umur penggunaan sekitar 24 bulan sahaja. Sampel yang kecil (N=55) tidak membolehkan model yang jitu dibangunkan. Proses tapisan untuk kelayakan untuk diuji telah mengeluarkan maklumat penting dan perlu diberi pertimbangan untuk kajian yang akan datang.

Secara kesimpulannya, kajian ini telah membentang maklumat berguna berkaitan prestasi impak topi keledar terpakai berkaitan dengan pecutan 'headform' dan faktor-faktor berkaitan. Ia juga telah memberi maklumat awal berkaitan tempoh penyimpanan topi keledar terpakai.

Kata kunci: Topi keledar, pecutan 'headform'

ACKNOWLEDGEMENTS

Firstly, I would like to express my greatest praise and gratitude to Allah SWT for giving me the energy to pursue this challenging work. My highest appreciation goes to my wife who keeps believing that I could reach the destination and complete this endeavour. My sincerest gratitude and gratefulness to my supervisors, Prof. Dr Wong Shaw Voon and Associate Prof. Dr. Nawal Aswan Abd. Jalil for their continual supports since the journey began few years back. Not to forget, my appreciation also goes to Mr Muhammad Tashriff of SIRIM STS for the cooperation in performing the helmet test.

I would also like to thank all my superiors and friends in MIROS for the great support and sport, for allowing me the chance to focus on this thesis.



This thesis was submitted to the Senate of the Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Wong Shaw Voon, PhD Professor Faculty of Engineering Universiti Putra Malaysia (Chairman)

Nawal Aswan Abdul Jalil, PhD Associate Professor Faculty of Engineering Universiti Putra Malaysia (Member)

ROBIAH BINTI YUNUS, PhD

Professor and Dean School of Graduate Studies Universiti Putra Malaysia

Date:

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) were adhered to.

Signature: Name of Chairman	
Committee:	Professor Dr. Wong Shaw Voon
Signature:	PM
Name of Member of Supervisory	
Committee:	Associate Professor Dr. Nawal Aswan Abdul Jalil

TABLE OF CONTENTS

ABSTRACT ABSTRAK

ACKNOWLE	EDGEMENTS	v	
APPROVAL	APPROVAL		
DECLARAT	DECLARATION		
LIST OF TA	BLES	xiii	
LIST OF FIG	GURES	xiv	
LIST OF AB	BREVIATIONS	xvi	
CHAPTER			
1 INTE	RODUCTION	1	
1.1	Background	1	
1.2	Problem statement	3	
1.3	Significance of study	4	
1.4	Thesis objectives	4	
	1.4.1 General objectives	4	
	1.4.2 Specific objectives	4	
1.5	Hypothesis	5	
	1.5.1 Headform acceleration is dependent of helmet	5	
	service age		
	1.5.2 Headform acceleration is dependent of helmet mass,	5	
	liner density, liner thickness and shell thickness		
	1.5.3 Headform acceleration is independent of sites and	5	
	impact speed		
1.6	Conceptual framework	5	
1.7	Scope of study	6	
1.8	Study limitations	6	
2 LITE	CRATURE REVIEW	7	
2.1	Introduction	7	
2.2	Overview of crashes and injuries	7	
	2.2.1 Head injury statistics & pattern	8	
2.3	Biomechanics of head injuries	10	
2.4	Head injury mechanism	10	
2.5	Head injury criterion	12	
2.6	Helmet design	13	
	2.6.1 Coverage and protective capability	15	
	2.6.2 Shell and liner	16	
2.7	Helmet effectiveness	16	
2.8	Helmet Legislation and Standards	17	
	2.8.1 Impact attenuation test	17	
	2.8.2 Conditioning for test	17	
2.9	Pattern of helmet replacement among motorcyclists	17	
2.10	Helmet exposure in use environment	18	
	2.10.1 UV and weathering effects	18	

i iii

	2.11	Helmet	performance deterioration	18
	2.12	Helmet	service life estimate	19
	2.13	Helmet	failure mode and mechanism	21
		2.13.1	Failure mode	22
		2.13.2	Failure mechanism	22
		2.13.3	ABS shell	22
		2.13.4	EPS impact liner	23
	2.14	Summa	ry	25
3	МАТ	TERIALS	S AND METHOD	27
-	3.1	Method	ology flowchart	27
	3.2	Experin	nental objectives	28
	3.3	Sample	definition and identification	28
		3.3.1	Inclusion and exclusion criteria	28
		3.3.2	Used helmet collection	28
			3.3.2.1 Certification label	29
			3.3.2.2 Manufacturing date	29
			3.3.2.3 Material properties	30
	3.4	Helmet	components preparation	30
	3.5	Selectio	on of test standards, apparatus and rationales	31
	3.6	Test. co	nditions and constraints	31
	3.7	Test pre	eparation process	33
	3.8	Executi	on of experiments	35
	3.9	Data ac	quisition and collection	35
	3.10	Study v	ariables	35
		3.10.1	Dependent variable	35
			3.10.1.1 Headform acceleration	35
		3.10.2	Independent variables	36
			3.10.2.1 Mass and volume	36
			3.10.2.2 Liner density	37
	3.11	Descrip	tive and statistical analysis	37
		3.11.1	Correlation test	37
		3.11.2	Simple linear regression	38
		3.11.3	Anova	38
		3.11.4	Multivariate linear regression	38
	3.12	Summa	ry	38
	DEC			10
4	RES	ULIS		40
	4.1	Overvie	W 1 4 1 4	40
	4.2	Helmet	sample attributes	40
	4.3	Descrip	tive analysis	41
		4.3.1	Heimet service age selection	41
		4.3.2	l est order	41
		4.3.3	Headform acceleration and service age	42
			4.5.5.1 Headform acceleration summary	45
		121	4.5.5.2 Different impact severity	45
		4.5.4	Heimet acceleration and heimet mass	46
		4.5.5	Heimet acceleration and liner thickness	46
		4.3.0	Helmet acceleration and snell thickness	4/
		4.3./	mennet acceleration and liner density	48

	4.4	Statistical analysis			
		4.4.1 Headform acceleration at impact sides	50		
		4.4.2 Correlation analysis	50		
		4.4.3 Dependent variable	50		
		4.4.4 Correlations of headform acceleration	50		
		4.4.4.1 Service age	51		
		4.4.4.2 Helmet mass	51		
		4.4.4.3 Liner density	51		
		4.4.4.4 Liner thickness	52		
		4.4.4.5 Shell thickness	52		
		4.4.4.6 Impact speed	52		
		4.4.4.7 Impact energy	52		
		4.4.5 Regression analysis	52		
		4.4.5.1 Simple regression	53		
	4.5	Factors associated with headform acceleration	54		
	4.6	Headform acceleration performance	56		
	4.7	Proposed model for headform acceleration	57		
		4.7.1 Multivariate regression	58		
	4.8	Model validation	60		
	4.9	Indicators of good helmet performance	61		
	4.10	Cracked helmet	61		
	4.11	Summary	62		
-	CON				
5	CON 5 1	CLUSION, RECOMMENDATIONS & LIMITATIONS	64		
	5.1	Conclusion	64		
	5.2	Recommendations	64		
	5.5	Limitations	64		
	5.4	Research challenges	65		
	5.5	Future research	65		
REFER	RENCI	ES	66		
APPEN	DICE	CS	74		
BIODA	TAO	F STUDENT	84		
LIST O	F PUI	BLICATIONS	85		

 \bigcirc

LIST OF TABLES

Table		Page
2.1	Road traffic death in selected ASEAN countries	8
2.2	Head injury in motorcycle crashes	9
2.3	Helmet impact damaged side based on crash records	9
2.4	Exposure type and estimated effective life of helmets	20
2.5	Impact energy absorption by helmet shell and liner	22
2.6	Impact properties of EPS	24
4.1	Samples attributes	40
4.2	HA summary at all sides	45
4.3	Normality test result	49
4.4	ANOVA analysis result for impact sides	50
4.5	Bivariate correlation results	51
4.6	Pearson coefficient for SA	53
4.7	Pearson coefficient for LT	53
4.8	Pearson coefficient for ST	53
4.9	Pearson coefficient for HM	54
4.10	Pearson coefficient for IEn	54
4.11	Coefficients for headform acceleration	58
4.12	Headform acceleration based on prediction model	59
4.13	Headform acceleration, actual versus prediction	60

LIST OF FIGURES

Figure		Page
1.1	Motorcyclist fatalities versus other road users	3
1.2	Conceptual framework	6
2.1	A cross-section of helmet response during impact test	10
2.2	X-ray image of skull fracture and epidural haematoma	11
2.3	A headform acceleration trace	12
2.4	Open face, half shell and full face helmet	13
2.5	Minimum extent protection	14
2.6	Sketch of helmet component and EPS impact liner	14
2.7	Comparison of headform acceleration for different relative humidity	21
2.8	The effects of weathering on ABS resin impact strength	23
2.9	Compressive stress strain curves for dry, 1 day and 24-day water immersion	25
3.1	Methodology flowchart	27
3.2	Certification label on used helmet	29
3.3	Manufacturing date sticker	30
3.4	Indication of helmet materials	30
3.5	Impact test machine	31
3.6	Position of impact side on helmet	32
3.7	Sketch of impact sides	32
3.8	Image of flat and hemispherical anvils	33
3.9	Schematic of drop test set up	34
3.10	Triaxial accelerometer and test set up	34
3.11	Display of acceleration curve	36

3.12	Method to measure liner volume	37
4.1	Plot of headform acceleration over service age	42
4.2	Plot of headform acceleration over service age for each impact site	44
4.3	Plot of headform acceleration over helmet mass	46
4.4	Plot of headform acceleration over liner thickness	47
4.5	Plot of headform acceleration over shell thickness	48
4.6	Plot of headform acceleration over liner density	49
4.7	Liner density over service age	56
4.8	Best-fit curve for headform acceleration over service age	57
4.9	Best-fit curve for Log ₁₀ headform acceleration over service age	58
4.10	Plot of headform acceleration, actual versus predicted	60
4.11	Cracked helmet shell, yellow and white	61
4.12	Force over time trace for brittle and tough behaviour of ABS	62

6

LIST OF ABBREVIATIONS



CHAPTER 1

INTRODUCTION

1.1 Background

Motorcycles have been a popular transportation mode in Malaysia for the past decades and are strongly believed to continually persist into the near future, as forecasted by the Malaysian Motorcycle Dealers Association (The Star, 2014). In the regional and global contexts, Malaysia placed second in terms of motorcycle ownership per 1000 population (Laksanakit, 2014). However, the growth in numbers has been seriously marked by a multi-fold numbers of casualties and injuries, which has been showing an upward trend particularly in terms of fatalities and consistently accounts more than 55% of total road fatalities (Sarani et al., 2011). Established data indicated that the numbers have steadily exceeded 3300 deaths since 2000, in which, in most countries, injurious head trauma contributed approximately about 55-85% (Seay et al., 2004). Similarly, recent findings by Ramlia (2014) indicated that 32% of the fatal motorcycle crash cases investigated showed a Maximum Abbreviated Injury Scale (MAIS) score of 5 with head injury being the most common cause of death. The Abbreviated Injury Score (AIS) is scaled from 1 to 6, in which score 5 reflected an injury status of critical and score 6 is denoted as non-survivable (AAAM, 2005). Further away in other continent, the scenario in Nigeria reflected a similar pattern in which more than 50% of motorcyclists suffered head injuries as a result of either vehicular collisions or single vehicle crash (Yusof et al., 2014). With respect to motorcycle riders and pillion passengers, Pruthi (2010) discovered there was no significant difference in terms of head injury risks to both groups, and further stressed that helmet works well to mitigate head injury risks.

Therefore, one of the injury mitigation strategy for motorcyclists is the use of certified motorcycle safety helmets. It has been proven to be effective in minimizing the injury risks especially to the motorcyclists' heads in a number of crash scenarios (Liu *et al.*, 2008; MacLeod *et al.*, 2010 and MAIDS, 2001). Proper use is also comparatively paramount in ensuring the helmets performed optimally when in needs, especially when head impacts occur. Correspondingly, it also means to incorporate, among others, standard-compliant helmets, correct size and good-fit to the wearers' heads, the retention system (chin strap) to be safely secured and preserved helmet structures and integrity. In simple terms, the helmet satisfactory structures and the integrity levels imply the helmet capability to perform as designed when the need arises, at least at par, with its certification performance when new. It was estimated that good appearance of helmet's outer shell that is without recognizable cracks and preserved liner may provide visual cue for reliable crash impact performance (Pruthi *et al.*, 2010).

In Malaysia, new helmets performance compliance is well established and stringently regulated by the road transport authorities (MS1:1996 and RTA). Randomly selected helmet samples will go through destructive mechanical tests such as impact

attenuation, penetration resistance and retention system tests, in a certified laboratory. In particular, impact attenuation test, or commonly referred to as impact test measures the helmet capability to absorb maximal crash impact energy so that the wearer's head only experience minimal contact loads and acceleration. This capability is considered a critical element of helmet protective function, if not the most critical. For certification, each batch of helmets that meet all the minimum performance criteria will be imprinted with a unique seal as sign of approval MS1:1996. The established protocols in the helmet standards ensure helmets are designed and constructed to a pre-determined performance level to optimize their operational functions. Helmets serve to protect the motorcyclists' heads including the face in the event of collision impacts. For normal motorcycle riding, helmets also provide shielding from road debris, winds, rains and also acoustic noise. However, there is a clearly insufficient information and practical advice with regards to helmet retention period.

Once helmets are used by motorcyclists on roads and after a period of exposures, concerns arise on the overall functional performance of these in-service helmets in sustaining the optimal protection to the wearers, particularly their impact performance. During use intervals, helmets are exposed and subjected to weathering factors such as ultraviolet (UV) radiation, heat, moisture and also physical shock violations such as unintentional drops. After a prolonged utilization, these variables are perceived to adversely influence helmet material properties and subsequently its impact energy absorbing and protective capabilities.

Therefore, this particular study is initiated to further understand and fill the gap in current knowledge with respect to motorcycle safety helmet crash-worthiness performance, particularly in Malaysia. Such study is vital due to the facts that motorcycle crashes in the country has been repeatedly shown dominating annual injury and fatality statistics (Figure 1.1).





To get a better understanding of the situation, the following paragraphs provide brief illustration of how prevalent it has been since the last decade and why such work may have the potential to provide leads and clues for policy makers and road authorities to diligently consider when drafting future national traffic safety direction, policies and legislations. It is essential to note that despite the numerous interventions and efforts by authorities and stakeholders, the motorcycle casualties in road traffic remains extremely high (>50%) and it is hoped that this study would be able to disclose new knowledge on motorcyclists' safety for future initiatives and intervention programs.

1.2 Problem statement

Motorcycle safety helmet studies have continually attracted countless researches and experiments, of which most of these works engrossed primarily in helmets use and effectiveness in a macroscopic perspective. In most cases they measure percentage of wearing and not wearing, survivability rate and injury severity in a motorcycle population sample, with little information describing actual helmet crashworthiness performance during impact events. Correspondingly, little distinction is made to the impact energy absorbing performance or alternately, the head acceleration values, with respect to the service ages of these helmets. In other words, in-depth investigation of used helmets (or in-service helmets) performance is rather limited. The used helmets crashworthiness studies relative factors such as service age, physical and mechanical properties were also rarely profiled. Exposures to environmental factors and stresses such as ultra-violet (UV) irradiation, moisture and heat during utilization may, to a certain extent, affect the critical protective factors of the helmets, which include the energy absorbing performance during crash impacts. Impact violations during use such as unintentional drops, if occur frequently, may also influence the shell and liner densities and their energy dispersal and compressive potentials. Such



adversity may potentially result in a relatively lower than optimal protection to the wearers, and may consequently exacerbate the head injury incidences and severities.

In brief, there are scarce information and inadequate details on used helmets crashworthiness performance relative to head acceleration records and also very vague advisory statement on the helmet retention and replacement needs (including disposal). Therefore, it is of significant importance to objectively bridge this knowledge gap and it is highly hoped that this study would be able to provide new information and findings of the used helmets crashworthiness performances by predicting the potential headform acceleration records.

1.3 Significance of study

Having such a high motorcycling population (11.5 million) in the country and with the motorcycle registration records approaching 50% of the total registered vehicles, motorcyclists' protection such as safety helmets become among the vital element for injury risks reduction control tools. Crashworthy helmets provide effective protection to the wearers' head during direct crash impact by dispersing the concentrated impact energy throughout the helmet hard shell surface and allow the inner liner to absorb the remaining loads by experiencing physical deformation. Thus, to be effective, helmets are designed to absorb most of the impact energy in order to affect a significant reduction in the head acceleration potential well below the head injury threshold limits.

The findings and outcome of this study is hoped to provide essential information to consumers, motorcyclists in particular, for their safety precaution when utilizing their motorcycles and helmets on roads. Information such as helmet crashworthiness performances, helmet estimated effective life and determinants affecting helmet performance are important for helmet users.

1.4 Thesis objectives

1.4.1 General objective

To determine used safety helmet crashworthiness performance with regards to headform acceleration performance in impact attenuation test

1.4.2 Specific objectives

- i) To determine used helmet headform acceleration performance relative to service age
- ii) To examine headform acceleration performance at four sides of used helmet
- iii) To identify factors affecting used helmet head acceleration performance

1.5 Hypothesis

It is postulated that helmet crashworthiness performance tends to deteriorate over its service life and significantly influenced by the shell and liner performances, after prolonged utilization and exposures to environmental factors such as Ultraviolet irradiation (UV) and pre-impact factors when in use. In addition, it is expected that the outer shell will undergo significant degradation in terms of mechanical energy dissipation performance and the impact liner deteriorates in performance as a result of frequent use and pre-shock violations which may include unintentional drop of helmet from significant vertical heights, during the use tenure.

It is also postulated that helmet crashworthiness, measures in terms of head acceleration values, tends to deteriorate during its service life. In helmet certification process, the energy absorbing performance is generally measured by the headform peak resultant acceleration records (addressed simply as headform acceleration (HA))) during impact contacts. This headform acceleration is a resemblance of motorcyclist's head acceleration experience when involved in crash impacts.

For this study, the following hypotheses are tested;

- **1.5.1** Headform acceleration is dependent of helmet service age
- **1.5.2** Headform acceleration is dependent of helmet mass, liner density, liner thickness and shell thickness
- **1.5.3** Headform acceleration is independent of sites and impact speed

1.6 Conceptual framework

Figure 1.2 explains the whole process of the study. It starts with definition and characteristics of helmet to be collected and measured. Then performance evaluation will be conducted to identify potential and significant determinants affecting helmet head acceleration. Execution of impact tests including data measurement and collection of the dependent variable, headform acceleration are performed for all the identified helmet samples.



Headform acceleration trend Identified factors Service life

Figure 1.2 : Conceptual framework

1.7 Scope of study

This particular study involves standard-compliant motorcycle safety helmet collected randomly from the public and concerns only the open-face helmet type. Additionally, used helmets refer to helmets from public which have been used on roads and exposed to utilization and environmental factors. The performance tests were limited to headform acceleration records and excluded penetration resistance and the retention system tests. Furthermore, the test method is restricted to standard test protocols, Malaysian Standards MS1:1996 in particular, which reflected some fractional similarities to United Nations Regulations No. 22 (UN R22.05). For information, at time this report was produced, there was no request for helmet certification to the latest standard, MS1:2011, from the local helmet manufacturers.

1.8 Study limitations

The study analyses real world helmet samples for the physical test. Thus, all data pertaining to designs, materials characteristics and physical properties are subjected to common industrial practices and establish standards, in this case Malaysian Standards for motorcycle helmets, MS1:1996. In other words, the succeeding analysis and findings originated from this work is rather limited and may need further studies, if generalisation is desired.



REFERENCES

- Aare M., (2003). Prevention of head injuries focusing specifically on oblique impacts, KTH, Doctoral thesis.
- Abd Rahim M. N. (2009). Statistical methods in research, Prentice-Hall, ISBN 978-983-3927-95.
- ACEM (2004). MAIDS: In depth investigations of accidents involving powered two-wheelers. Final Report. Available from http://MAIDS.acembike.org.
- AIS, www.aaam.org, accessed April, 2015.
- Bair H. E., Boyle D. J., & Kelleher P. G. (1980). The effects of light and heat on the rubber content and impact strength of acrylonitrile-butadiene-styrene, Poly Eng and Sci, 1980 20(15) 995–1001.
- Bambach M.R., Grzebieta R.H., Tebecisand Friswel R. R. (2012).Crash characteristics and causal factors of motorcycle fatalities in Australia, Aus. Road Safety Research Policing and Education Conference 2012. 4-6 October 2012, Wellington, New Zealand.
- Beng O. B., Krishnan R., Lee P., (2000). Pattern of head injury in motorcycle fatalities. JUMMEC.
- Bogerd, C. P., Walker, I., Brühwiler, P. A., & Rossi, R. M. (2014). The effect of a helmet on cognitive performance is, at worst, marginal: A controlled laboratory study. Applied Ergonomics, 45(3), 671–676.
- Caserta, G. D., Iannucci, L., & Galvanetto, U. (2011). Shock absorption performance of a motorbike helmet with honeycomb reinforced liner. Composite Structures, 93(11), 2748–2759.

Cadex, http://www.cadexinc.com/anvils.php, accessed 1 June 2016.

- Chen W., Hao H., Hughes D., Shi Y., Cui J., Li ZX. (2015).Static and dynamic mechanical properties of expanded polystyrene. Materials & Design, v69, 170–180.
- Cini, M. A., Prado, B. G., de Fragas Hinnig, P., Fukushima, W. Y., & Adami, F. (2014). Influence of type of helmet on facial trauma in motorcycle accidents. *British Journal of Oral and Maxillofacial Surgery*, 52(9), 789–792.
- Coelho, R. M., Alves de Sousa, R. J., Fernandes, F. A. O., & Teixeira-Dias, F. (2013). New composite liners for energy absorption purposes. Materials & Design, 43, 384–392.

- COST327 (2001), Motorcycle safety helmets, Final Report of the Action, European Commission.
- Dadkhah, A., Saied-Moallemi, Z., & Sadegh, A.-R. M. (2015). Head and face injuries and helmet use among injured motorcyclists with road accidents in Isfahan, Iran. Journal of Oral Health and Oral Epidemiology, 4(2).
- Davis A. and Sims D., Weathering of polymers, Kluwer, Academic Pub; 1983.
- Davis, P., Tiganis, B. E., & Burn, L. S. (2004). The effect of photo-oxidative degradation on fracture in ABS pipe resins. Polymer Degradation and Stability, 84(2), 233–242.
- Deck C. and Willinger R. (2008). Improved head injury criteria based on head FE model. International Journal of Crashworthiness, 2008. V13, 6.
- Dee T.S. (2009). Motorcycle helmets and traffic safety', J Health Econ, 28(2) 398–412.
- DeMarco, A. L., Chimich, D. D., Gardiner, J. C., Nightingale, R. W., & Siegund, G.
 P. (2010). The impact response of motorcycle helmets at different impact severities. Accident Analysis & Prevention, 42(6), 1778–1784.
- Denning A, and Mills N. J. (1992). The deterioration of thermoplastic motorcycle helmet shells after outdoor exposure. Plastics, Rub &Comp Proc and App UK,18, 67–77.
- Deutermann, W. (2004). Motorcycle helmet effectiveness revisited. Retrieved from http://trid.trb.org/view.aspx?id=697922
- Di Landro, L., Sala, G., & Olivieri, D. (2002). Deformation mechanisms and energy absorption of polystyrene foams for protective helmets. Polymer Testing, 21(2), 217–228.
- Fernandes, F. A. O., & de Sousa, R. A. (2013). Motorcycle helmets—A state of the art review. Accident Analysis & Prevention, 56, 1–21.
- Gale A., Mills N. J. (1985).Effect of polystyrene foam liner density on motorcycle helmet shock absorption. Plastics and rubber processing and applications. 5(2):101–108.
- Ghajari M., Galvanetto U, Iannucci L, and Willinger R. (2011), Influenceof the body on the response of the helmeted head during impact, Int. J. Crashworthiness 16, pp. 285–295.
- Ghaemy M, Scott, G. (1981). Photo- and thermal oxidation of ABS: Correlation of loss of impact strength with degradation of the rubber component, Polymer Degradation and Stability. 3(3) 233-242.

- Gibson L. J., Ashby M. F, Cellular solids: structure and properties, Cambridge University Press, 1999, pg 38.
- Gilchrist A, Mills N. J. (1987). Fast fracture of rubber-toughened thermoplastics used for the shells of motorcycle helmets. J of Mat Sci, 22(7) 2397–2406.
- Gilchrist A. and Mills N.J. (1994). Modelling of the impact response of motorcycle helmets', Int J Imp Eng, 15(3), 201–218.
- Gimbel, G. M., & Hoshizaki, T. B. (2008). Compressive properties of helmet materials subjected to dynamic impact loading of various energies. European Journal of Sport Science, 8(6), 341–349
- Henn, H. W. (1998). Crash tests and the head injury criterion. Teaching mathematics and its applications, 17(4), 162-170.
- Hopes P. D. and Chinn B. P. (1989). Helmets: a new look at design and possible protection. Proc.1989 international ircobi, Stockholm. p. 39-54
- Hoshizaki, T., Blaine P., Andrew P, Oeur, R., Anna Brien, Susan E. (2014). Current and future concepts in helmet and sports injury prevention, Neurosurgery, V75 (p S136–S148).
- Hui Z., Huang W, Yang G, Chen R, Liu SX. (2012). Analysis of 86 fatal motorcycle frontal crashes in China. Chinese Journal of Traumatology, Vol 15, No 3
- Hutchinson, T. P. (2014). Peak acceleration during impact with helmet materials: Effects of impactor mass and speed. European Journal of Sport Science, 14(sup1), S377–S382. http://doi.org/10.1080/17461391.2012.705334
- Hurt, H. H., Ouellet, J. V., & Thom, D. R. (1981). Motorcycle Accident Cause Factors and Identification of Countermeasures: NHTSA, U.S.Dept. of Transportation, HS-5-01160.
- Kasantikul, V., Ouellet, J. V., & Smith, T. A. (2003). Head and neck injuries in fatal motorcycle collisions as determined by detailed autopsy. *Traffic Injury Prevention*, 4(3), 255–262.
- Kaviyarasu V. (2011), Prevalence and determinants of standard motorcycle crash helmet use among rural postal delivery riders in Peninsular Malaysia, Master Thesis, Universiti Putra Malaysia (www.upm.edu.my)
- Kim, G. H., Lee, O. S., & Yoo, S. S. (1997). Experimental study on impact absorbing performance of motorcycle helmets. *KSME International Journal*, 11(3), 292– 299.
- King, A. I., Yang, K. H., Zhang, L., Hardy, W., & Viano, D. C. (2003). Is head injury caused by linear or angular acceleration. In *IRCOBI conf.* (pp. 1–12). Retrieved from http://snell-elmets.org/docs/articles/hic/King_IRCOBI_2003.

- Kirk P. (2000). Effect of outdoor weathering on the effective life of forest industry safety helmets. Int J Industrial Ergo, 25 1 51–58.
- Kostopoulos, V., Markopoulos, Y. P., Giannopoulos, G., & Vlachos, D. E. (2002). Finite element analysis of impact damage response of composite motorcycle safety helmets. *Composites Part B: Engineering*, 33(2), 99–107.
- Laksanakit, C. (2014). Impact of motorcycle defects on motorcycle safety in Thailand. Journal of Society for Transportation and Traffic Studies, 5(1), 1–15.
- Lin, M.-R., & Kraus, J. F. (2009). A review of risk factors and patterns of motorcycle injuries. Accident Analysis & Prevention, 41(4), 710–722.
- Liu, B., Ivers, R., Norton, R., Boufous, S., Blows, S., Lo, S.K., (2008). Helmets for preventing injury in motorcycle riders. Cochrane Database of Systematic Reviews, CD004333.
- Liu, D.S., Chang, C.Y., Fan, C.M. & Hsu, S.L. (2003)., Influence of environmental factors on energy absorption degradation of polystyrene foam in protective helmets, Eng Failure Anal, 10(5) 581–591.
- MacLeod, J. B., DiGiacomo, J. C., & Tinkoff, G. (2010). An evidence-based review: helmet efficacy to reduce head injury and mortality in motorcycle crashes: EAST practice management guidelines. Journal of Trauma and Acute Care Surgery, 69(5)
- MAIDS. (2004). In depth investigations of accidents involving powered two wheelers.Final Report 1.2, Brussels. http://ec.europa.eu/transport/roadsafety library/publications/maids report 1 2 september 2004.pdf
- Manan, M.M. and Varhelyi, A. (2011), Motorcycle fatalities in Malaysia, IATSS Research 36, 30-39.
- McHenry, B. (2004). Head Injury Criterion and the Articulated Total Body, ATB users' group, accessed 12 May 2016.
- McKnight, A. J., & McKnight, A. S. (1995). The effects of motorcycle helmets upon seeing and hearing. Accident Analysis & Prevention, 27(4), 493–501.
- Mills N. J. (1996), Accident investigation of motorcycle helmets, Impact. 5:46-51.
- Mills N.J. and Kang, P. (1994). The effect of water immersion on the mechanical properties of polystyrene bead foam used in soft shell cycle helmets', Journal of Cellular Plastics, 30(3):196.
- Mills, N. J., and Gilchrist, A. (1991). The effectiveness of foams in bicycle and motorcycle helmets. Accident Analysis & Prevention, 23(2), 153-163.
- Mills N. J., Wilkes S., Derler S., Flisch A. (2009). FEA of oblique impact tests on a motorcycle helmet, Int J Impact Eng, 36(7) 913–925.

- Mohd Hafzi M. I., Rohayu S., Noor Faradila P., Wong S. V. (2009), 'Prevalence and risk factors of musculoskeletal disorders of motorcyclists', Nat Symp on Advancement in Ergon and Safety, Malaysia.
- Morice, A. H., Sevrez, V., Gray, R., & Montagne, G. (2015). Investigating the interaction between helmet field of view and steering behavior in a novel motorcycle simulator. 8th International Driving Symposium on Human Factors in Driver Assessment, Training, and Vehicle Design.
- MS1:1996, Malaysian Standard, Specifications for protective helmets for vehicle users. 2nd Revision, SIRIM.
- MS1:2011, Malaysian Standard, Protective helmets and visors for vehicle users-Specifications.
- NHTSA, 1972. Occupant Crash Protection Head Injury Criterion S6.2 of MVSS 571.208, Docket 69-7, Notice 17. National Highway Traffic Safety Administration, Washington, DC.
- NHTSA, 2008. Traffic Safety Facts, Data: Motorcycles. DOT HS 811 159, National Highway Traffic Safety Administration, Washington, DC, http://wwwnrd.nhtsa.dot.gov/Pubs/811159.pdf
- Newman, J., Beusenberg, M., Fournier, E., Shewchenko, N., Withnall, C., King, A., ... others. (1999). A new biomechanical assessment of mild traumatic brain injury. Part I: Methodology. In 1999 IRCOBI, SPAIN. Retrieved from http://trid.trb.org/view.aspx?id=676460
- O'Connor, P.J. (2002) -Motorcycle helmets and spinal cord injury: helmet usage and type. Traffic injury prevention, v6:1.
- Ommaya, A. K., Goldsmith, W., & Thibault, L. (2002). Biomechanics and neuropathology of adult and paediatric head injury. *British Journal of Neurosurgery*, 16(3), 220–242.
- Ouellet, J.V., Kasantikul, V. (2006), 'Motorcycle helmet effect on a per-crash basis in Thailand and the United States', Traffic Injury Prevention, 2006 7(1) 49–54.
- Pang, T. Y. (2000). Injury Characteristics of Motorcyclists involved in Motorcycle Crashes in Klang Valley, Malaysia. Universiti Putra Malaysia. Retrieved from http://psasir.upm.edu.my/10455/
- Pearsall, D.J., Dowler, P.M., Johnson, R.J., Shealy, J., Langran, M. and Dean, S. W. (2008). A longitudinal study of ice hockey helmet shelf life', J of ASTM Int, 5(8).
- Pickett, J.E., Gibson, D.A, Rice, S.T., and Gardner, M. M. (2008).,'Effects of temperature on the weathering of engineering thermoplastics', Polymer Degradation and Stability, 93:684–691.

- Post, A., & Hoshizaki, T. B. (2012). Mechanisms of brain impact injuries and their prediction: a review. *Trauma*, 14(4), 327–349.
- Pruthi, N., Chandramouli, B. A., and Devi, B. I. (2010). Patterns of head injury among drivers and pillion riders of motorised two-wheeled vehicles in Bangalore. The Indian Journal of Neurotrauma, 7(2), 123–127.
- Ramli_a, R., Oxley, J., Noor, F. M., Abdullah, N. K., Mahmood, M. S., Tajuddin, A. K., & McClure, R. (2014). Fatal injuries among motorcyclists in Klang Valley, Malaysia. J Forensic and Legal Medicine. Retrieved from
- Ramlib, R., Oxley, J., Hillard, P., Sadullah, A. F. M., & McClure, R. (2014). The effect of motorcycle helmet type, components and fixation status on facial injury in Klang Valley, Malaysia: a case control study. Bmc Emergency Medicine, 14(1), 17.
- Rohayu S, Sharifah Allyana, S.M.R., Jamilah, M.M., and Wong, S.V. (2012), Predicting Malaysian Road Fatalities for Year 2020, MRR 06/2012, Kuala Lumpur: Malaysian Institute of Road Safety Research.
- Roslan, A., Sarani, R., Hashim, H.H., & Saniran, N. (2011). *Motorcycle ADSA Fact sheet Vol. 2*, [Fact Sheet]. Retrieved from http://www.miros.gov.my
- Richter M, Otte D, Lehmann U, Chin B, Schuller E, Doyle D, Sturrock K et al. (2001), Head injury mechanisms in helmet-protected motorcyclists: prospective multicenter study. J of Trauma, 51(5) 949.
- RTA 1987 (Road Transport Act 1987), Motorcycles (Safety Helmets) (Amendment) Rules 2012, accessed 20 Dec 2013, www. lawnet.com,my.
- Sarani, R., Roslan, A & Saniran, N. (2011). Motorcycle ADSA Fact sheet Vol. 1, [Fact Sheet]. Retrieved from http://www.miros.gov.my
- Sampers J, (2002).Importance of weathering factors other than UV radiation and temperature in outdoor exposure. Polymer Degradation and Stability,76(3) 455-465.
- Santos R. M., Pimenta A., Botelho G., Machado A. V. (2013). Influence of the testing conditions on the efficiency and durability of stabilizers against ABS photo-oxidation. Polymer Testing, v32:1.
- Seay, A.,(2004), The global impact, in World report on road traffic injury prevention.World Health Organization, M. Peden, et al.,Editors.
- Sheeju, P. A., & Prasannan, K. (2015). A Descriptive Study of Pattern of Injuries in Driver and Pillion Rider Victims of Fatal Two Wheeler Accidents. Asian Journal of Biomedical and Pharmaceutical Sciences, 5(45), 29–32.
- SIRIM QAS (2010), Used helmet test result (unpublished), Standards Industrial Research Institute Malaysia.

- Tan K. S, (2014), Personal communication, Director, Solidgold Helmets Sdn Bhd, Malaysia.
- Thai K.T., McIntosh A.S., Pang T.Y. (2015). Factors Affecting Motorcycle Helmet Use: Size Selection, Stability, and Position. Traffic injury prevention, v16:3.
- The Star, 2013, http://star-motoring.com/News/2013/Motorcycle-association-upbeat, accessed 27 June 2014.
- The Star, 2015 http://mystar.newspaperdirect.com/epaper/viewer.aspx, accessed 13 Mar 2015.
- Tiganis B. E, Burn L. S, Davis P., Hill A. J. (2002). Thermal degradation of acrylonitrile-butadiene-styrene (ABS) blends, Polymer degradation and stability. 76(3):425–434.
- UN Regulations No 22, (2001), Uniform provisions concerning the approval of protective helmets and their visors for drivers and passengers of motor cycles and mopeds. United Nations.
- van den Bosch, H. L. A. (2006). *Crash helmet testing and design specifications* (Vol. 68). Retrieved from http://alexandria.tue.nl/extra2/200611939
- Vetter L, Vanderby R, Broutman L.J. (1987).Influence of materials and structure on performance of a football helmet, Polymer Engineering and Science, 27(15):1113–1120.
- Viano, D. C., King, A. I., Melvin, J. W., & Weber, K. (1989). Injury biomechanics research: an essential element in the prevention of trauma. *Journal of Biomechanics*, 22(5), 403–417.
- WHO(2013), Global Status Report on Road Safety, Supporting a decade of action, http://www.who.int/gho/publications/world_health_statistics, accessed 15 June 2015.
- Whyte, T., Gibson, T., Anderson, R. W. G., Eager, D., & Milthorpe, B. (2015). Mechanisms of head and neck injuries sustained by helmeted motorcyclists in fatal real world crashes-Analysis of 47 in-depth cases. *Journal of Neurotrauma*, (ja).
- Willinger, R., & Baumgartner, D. (2003). Human head tolerance limits to specific injury mechanisms. International Journal of Crashworthiness, 8(6), 605–617.
- Yoganandan N, Pintar F. A. (2004), Biomechanics of temporo-parietal skull fracture., Clinical Biomechanics 19, 225–239
- Yusuf AS, Odebode TO, Adeniran JO, Salaudeen AG, Adeleke NA, Alimi MF. (2014) Pattern and outcome of motorcyclists head injury in Ilorin, Nigeria. Niger J Basic Clin Sci;11:80-4.

- Yu WY, Chen CY, Chiu WT, Lin MR. (2011), Effectiveness of different types of motorcycle helmets and effects of their improper use on head injuries, Int.J Epidemiology, 2011.
- WHO,http://www.who.int/violence_injury_prevention/publications/road_traffic/hel met_manual.pdf, accessed 9 May 2016.
- Zulkipli Z H, Hamzah A, Mohammed S, Abdul Rahman M A. (2015), Short communication: Injury pattern among motorcyclists involved in traffic crashes, IRCOBI 2015, Lyon.



LIST OF PUBLICATIONS

Journal papers

- Hamzah, A., Ariffin, A. H., Solah, M. S., Isa, M., Hafzi, M., Ahmad, Y., & Voon, W. S. (2014). Comparative study of motorcycle helmets impact performance, Applied Mechanics and Materials (Vol. 575, pp. 306–310). Trans Tech Publ.
- H Azhar, AH Ariffin, MS Solah, SV Wong. (2014), Estimating energy absorbing performance of motorcycle safety helmet, Applied Mechanics and Materials (Vol. 663, pp. 574-578).

Conference/Proceeding papers

- H Azhar, AH Ariffin, MS Solah, MI Mohd Hafzi, A Yahaya and SV Wong, Comparative study of motorcycle helmets impact performance, Proc. of 2nd Int. Conf. Mech, Auto. and Matl. Eng, May 26-28, 2014: Singapore, Paper ID M2014-1-154.
- H Azhar, AH Ariffin, MS Solah, SV Wong., Estimating energy absorbing performance of motorcycle safety helmet, In: Proc. of the 2nd Int. Conf. on Recent Adv. in Auto Eng & Mobility Res., December16-18, 2013: Kuala Lumpur, Malaysia, Paper ID: P074.
- H Azhar, SV Wong, Degradation of helmet protective performance: an overview, In: Proc. of Int. Conf. Crashworthiness, September 22-24, 2010: Washington DC, USA.



UNIVERSITI PUTRA MALAYSIA

STATUS CONFIRMATION FOR THESIS / PROJECT REPORT AND COPYRIGHT

ACADEMIC SESSION : SECOND SEMESTER 2015/2016

TITLE OF THESIS / PROJECT REPORT :

EXPERIMENTAL DETERMINATION OF SAFE SERVICE LIFE OF MOTORCYCLE HELMET

NAME OF STUDENT: <u>AZHAR HAMZAH</u>

I acknowledge that the copyright and other intellectual property in the thesis/project report belonged to Universiti Putra Malaysia and I agree to allow this thesis/project report to be placed at the library under the following terms:

- 1. This thesis/project report is the property of Universiti Putra Malaysia.
- 2. The library of Universiti Putra Malaysia has the right to make copies for educational purposes only.
- 3. The library of Universiti Putra Malaysia is allowed to make copies of this thesis for academic exchange.

I declare that this thesis is classified as :

*Please tick (V)



CONFIDENTIAL



RESTRICTED



OPEN ACCESS

(Contain confidential information under Official Secret Act 1972).

(Contains restricted information as specified by the organization/institution where research was done).

I agree that my thesis/project report to be published as hard copy or online open access.

This thesis is submitted for :



Embargo from_____ until (date)

(date)

Approved by:

(Signature of Student) New IC No/ Passport No.: (Signature of Chairman of Supervisory Committee) Name:

Date :

Date :

[Note : If the thesis is CONFIDENTIAL or RESTRICTED, please attach with the letter from the organization/institution with period and reasons for confidentially or restricted.]