



UNIVERSITI PUTRA MALAYSIA

***EFFECTS OF SAMPLE LOCATION AND SAWING METHOD ON
QUALITY OF OIL PALM WOOD***

NURUL NABILAH BINTI HAMZAH

FH 2016 32



**EFFECTS OF SAMPLE LOCATION AND SAWING METHOD ON
QUALITY OF OIL PALM WOOD**

By

NURUL NABILAH BINTI HAMZAH

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of Master of Science**

December 2016

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

EFFECTS OF SAMPLE LOCATION AND SAWING METHOD ON QUALITY OF OIL PALM WOOD

By

NURUL NABILAH BINTI HAMZAH

December 2016

Chair: Associate Professor Edi Suhaimi Bakar, PhD

Faculty: Forestry

Decreasing of the rubberwood supply and increasing of world demand towards palm oil, significantly cause the abundant oil palm trunk which is consider as an agriculture waste were investigate as a possible alternative as a future source of timber. In establishing oil palm wood as a potential wood substitute its own imperfection need to be enhance. To solve the problems, it is treated using chemical modification method known as Com-press. Continuation of the method done before, improvement was made and new method was invented known as Integrated Treatment Process. It consists of a six-step processing method (sawing, steaming and compression, drying, resin soaking, heating, and hot-pressing). In this study, effect of sample location and sawing method using Integrated Treatment Process was highlighted. The thickness of both slab shape was cut to 40 to 80 mm with 150 mm width and 300 mm in length. All slabs were treated with Low molecular weight phenol formaldehyde. This process used a reversed cant sawing method that not only produce normal square slab but also wane slab. Steaming was applied as pre-treatment before the sample compressed to avoid excessive cracking. The formation of the micro-cracks facilitates resin inclusion. The sample then soaked instead of impregnation. The sample heated by semi-cured in an oven and finally compressed by using hot-press. The slab then tested to see it mechanical and physical properties. For mechanical properties static bending, compression parallel to grain, and shear tests were done and for physical properties water absorption and thickness swelling tests were applied. Result was analysis using computer statistical program, Statistical Package for the Social Sciences (SPSS) and complete randomized design analysis of variance (ANOVA). The results show that waney slab treated oil palm wood have better properties than square slab treated oil palm wood by almost 7 % for weight percentage gain, 113 kg/m³ higher for wood density, 0.9 % lower for water absorption percentage, and 0.3 % slightly lower for thickness swelling. Same goes for mechanical properties, waney slab treated oil palm wood have better mechanical

properties compared to square slab treated oil palm wood. For bending strength, value of modulus of elasticity is 2325 N/mm² better than square slab treated oil palm wood, and value of modulus of rupture is 18 N/mm² higher. 1.9 N/mm² better value of shear strength of waney slab of treated oil palm wood calculated compared to square slab treated oil palm wood. Only compression strength parallel to grain for square slab found to be better than wane slab treated oil palm wood by 16 N/mm². As a whole, wane slab of treated oil palm wood have higher values of all tests but no specific slab thickness were obtained and gave the best result. Contradictory, value of compression parallel to grain gave result that is not complied as what was expected. In conclusion, the Integrated Treatment and Process do give effect on the quality of oil palm wood. It is proven fast, practical and economically viable for the industry.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Sarjana Sains

KESAN LOKASI SAMPLE DAN KAEDAH PENGGERGAJIAN PADA KUALITI KAYU KELAPA SAWIT

Oleh

NURUL NABILAH BINTI HAMZAH

Disember 2016

Pengerusi: Profesor Madya Edi Suhaimi Bakar, PhD

Fakulti: Perhutanan

Penurunan bekalan kayu getah dan peningkatan permintaan dunia terhadap minyak kelapa sawit, secara tidak langsung menyebabkan kebanjiran kayu kelapa sawit yang dilihat sebagai bahan buangan agrikultur dijadikan bahan penyelidikan sebagai satu cara alternatif untuk digunakan sebagai sumber kayu masa hadapan. Dalam memperkukuhkan kayu kelapa sawit sebagai kayu gantian berpotensi kekurangannya harus diperbaiki. Bagi menyelesaikan masalah kekurangan sifat kayu kelapa sawit, kayu tersebut diubahsuai secara kimia melalui kaedah Com-press. Namun peningkatan dibuat dan kaedah baru dicipta dan dikenali sebagai Proses Rawatan Bersepadu. Ia mempunyai 6 langkah iaitu melalui proses kukusan, pemampatan, pengeringan, rendaman fenol formaldehide molekul berketumpatan rendah, pemanasan dan pemampatan panas. Ketebalan kedua-dua bentuk papan kayu tersebut dipotong bermula dari 40 ke 80 mm dengan 150 mm lebar dan 300 mm panjang. Semua papan kayu dirawat dengan fenol formaldehide molekul berketumpatan rendah. Kaedah ini menggunakan cara penggergajian kayu yang baru yang bukan hanya menghasilkan papan kayu bersegi empat tetapi juga kayu beralun. Kaedah pengukusan telah digunakan sebagai pra-rawatan sebelum sampel dimampatkan untuk mengelakkan keretakan yang berlebihan. Pembentukan retakan-mikro memudahkan kemasukan resin. Sampel kemudian telah direndam. Sampel dipanaskan di dalam ketuhar dan akhirnya dimampatkan dengan menggunakan tekanan panas. Papan kayu itu kemudiannya diuji untuk melihat sifat mekanikal dan fisikalnya. Bagi sifat mekanikal, ujian statik lentur, mampatan selari dengan ira, dan ricih dilakukan. Bagi sifat fisikal, ujian penyerapan air dan tahap kebengkakan kayu dijalankan. Hasil ujian dianalisis menggunakan program statistik komputer, SPSS dan analisis rekabentuk rawak lengkap bervariasi, ANOVA. Keputusan mendapati, papan kayu beralun yang telah dirawat mempunyai sifat lebih baik berbanding papan kayu biasa iaitu 7 % baik untuk peratus pertambahan kayu, 113 kg/m³ lebih tinggi pada ketumpatan kayu, 0.9 % pengurangan dari segi penyerapan air, dan 0.8 % lebih rendah untuk pembengkakan ketebalan. Begitu juga dengan sifat mekanikal kayu, papan kayu beralun mempunyai sifat lebih baik berbanding papan kayu biasa. Untuk

sifat kekuatan kelunturan kayu, nilai modulus keanjalan ialah 2325 N/mm² lebih tinggi dan nilai modulus keampuhan 18 N/mm² lebih baik. 1.9 N/mm² nilai lebih tinggi untuk kekuatan ricihan papan kayu beralun berbanding dengan papan kayu biasa. Hanya nilai kekuatan mampatan untuk papan kayu biasa didapati lebih tinggi berbanding papan kayu beralun dengan nilai 16 N/mm² lebih baik. Secara keseluruhan, papan kayu beralun yang telah dirawat memberi keputusan lebih baik di dalam semua ujian kecuali nilai kekuatan. Kesimpulannya, Kaedah Rawatan Bersepadu ini memberi kesan kepada kualiti kayu kelapa sawit. Kaedah baru ini dibuktikan lebih cepat, praktikal dan berdaya maju dari segi ekonomi untuk industri perindustrian.



ACKNOWLEDGEMENTS

Thank God the Almighty ALLAH S.W.T as permission given to complete this task. I would like to express my deepest appreciation to my advisor, Assoc. Prof. Dr. Edi Suhaimi bin Bakar who always be an advisor who really committed with his job and never give up and do not hesitate in guiding me up until this stage. My gratitude to my co-advisor, Prof. Dr. Zaidon bin Ashaari for his assistance and a big thanks to my entire friend and lab mate. I dedicated this dissertation to my lovely parents Hamzah bin Ariffin and Zainab Bee Bee binti Abdul Aziz, my dear siblings, Prof. Dr. Nurul Huda binti Hamzah, Dr. Nurul Akmal bin Hamzah and Nurul Nadia binti Hamzah and my niece and nephew, Eiffy Hanna binti Eiffy Haziq, Rayyan bin Rahmat and Rayhan bin Rahmat. Not forgotten my dear, Mohamad Hanif bin Md Arshad. All of your prayers, remembrance, support and love give me strength. Nothing is impossible, so just do it!

Nurul Nabilah binti Hamzah

I certify that a Thesis Examination Committee has met on 27 December 2016 to conduct the final examination of Nurul Nabilah binti Hamzah on her thesis entitled "Effects of Sample Location and Sawing Method on Quality of Oil Palm Wood using Integrated Treatment" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

Jegatheswaran a/l Ratnasingam, PhD

Professor
Faculty of Forestry
Universiti Putra Malaysia
(Chairman)

Rasmina binti Halis, PhD

Associate Professor
Faculty of Forestry
Universiti Putra Malaysia
(Internal Examiner)

Othman Sulaiman, PhD

Professor
Universiti Sains Malaysia
Malaysia
(External Examiner)



NOR AINI AB. SHUKOR, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 8 August 2017

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Edi Suhaimi Bakar, PhD

Associate Professor
Faculty of Forestry
Universiti Putra Malaysia
(Chairman)

Zaidon Ashaari, PhD

Professor
Faculty of Forestry
Universiti Putra Malaysia
(Member)

ROBIAH BINTI YUNUS, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: _____ Date: _____

Name and Matric No.: Nurul Nabilah Binti Hamzah, GS24126

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature:



Name of Chairman
of Supervisory
Committee:

Signature:



Name of Member
of Supervisory
Committee:

Signature:

Name of Member
of Supervisory
Committee:

Signature:

Name of Member
of Supervisory
Committee:

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABLES	xii
LIST OF FIGURES	xiii
LIST OF ABBREVIATIONS	xiv
CHAPTER	
1 INTRODUCTION	1
1.1 Background of study	1
1.2 Problem statements	1
1.3 Justifications of study	2
1.4 Objectives of study	3
1.5 Significance of study	3
2 LITERATURE REVIEW	4
2.1 History of Oil Palm Wood in Malaysia	4
2.1.1 Oil Palm	6
2.1.2 Description of Oil Palm	6
2.1.3 Oil Palm Wood	8
2.1.4 Oil Palm Wood and Environment	9
2.1.5 Furniture made up of Oil Palm Wood	9
2.2 Wood Treatment	10
2.2.1 Oil Palm Wood Treatment	11
2.3 Phenol Formaldehyde	12
2.3.1 Phenol Formaldehyde Properties	13
2.3.2 Low molecular weight Phenol Formaldehyde	14
2.4 Quality Enhancement of Oil Palm Wood	15
2.4.1 The 5-Step Processing Method of Oil Palm wood	15
2.4.2 The 6-Step Processing Method of Oil Palm Wood	16
2.4.2.1 Sawing Patten	17
2.4.2.2 Steaming and Compression	18
2.4.2.3 Drying	18
2.4.2.4 Soaking	18
2.4.3 The differences between 5-Step and 6-Step Processing Method	19

3	METHODOLOGY	20
3.1	Materials	20
3.2	Methods	20
3.2.1	Sample Material Preparation	20
3.2.2	Oil Palm Wood Treatment	21
3.3	Tests	22
3.3.1	Physical Test	22
3.3.1.1	Density and Density Gain	22
3.3.1.2	Weight Percentage Gain	23
3.3.1.3	Dimensional Stability	23
3.3.2	Mechanical Test	24
3.3.2.1	Static Bending Test	25
3.3.2.2	Compression Test	26
3.3.2.3	Shear Test	27
3.4	Data Analysis	27
3.5	Flow Process	28
4	RESULTS AND DISCUSSION	29
4.1	Physical Properties	29
4.1.1	Treatability of treated oil palm wood	29
4.1.1.1	WPG of treated oil palm wood	30
4.1.1.2	Density of treated oil palm wood	31
4.1.2	Dimensional Stability of treated oil palm wood	32
4.1.2.1	Water absorption of treated oil palm wood	33
4.1.2.2	Thickness swelling of treated oil palm wood	34
4.2	Mechanical Properties	35
4.2.1	Bending strength of treated oil palm wood	36
4.2.2	Compression parallel to grain of treated oil palm wood	38
4.2.3	Shear strength of treated oil palm Wood	39
5	CONCLUSION AND RECOMMENDATIONS	42
5.1	Conclusion	42
5.2	Recommendation	43
	REFERENCES	44
	BIODATA OF STUDENT	51

LIST OF TABLES

Table		Page
2.1	Area of oil palm plantation in Malaysia	5
3.1	Test evaluation and sample specimen size	22
4.1	Summary of ANOVA for WPG and density of treated oil palm wood	29
4.2	Summary of ANOVA for water absorption and thickness swelling of treated oil palm wood	32
4.3	Summary of ANOVA for mechanical properties of treated oil palm wood	35
4.4	Summary of physical and mechanical properties of treated oil palm wood	40

LIST OF FIGURES

Figure		Page
2.1	Oil palm trunk	8
2.2	Structure of PF resin	13
2.3	The 5-step processing method	15
2.4	The 6-step processing method	16
2.5	Three sawing method	17
2.6	Reversed cant sawing	17
2.7	The comparison between 5-step and 6-step processing method	19
3.1	Oil palm trunk processing	21
3.2	Water absorption and thickness swelling tests	23
3.3	Static bending test	25
3.4	Compression parallel to grain test	26
3.5	Shear test	27
4.1	WPG of treated oil palm wood	30
4.2	Density of treated oil palm wood	31
4.3	Water absorption of treated oil palm wood	33
4.4	Thickness swelling of treated oil palm wood	34
4.5	MOE of treated oil palm wood	36
4.6	MOR of treated oil palm wood	37
4.7	Compression parallel to grain of treated oil palm wood	38
4.8	Mean of shear strength of treated oil palm wood	39

LIST OF ABBREVIATIONS

ANOVA	Analysis of Variance
ASE	Anti Swelling Efficiency
ASTM	American Society for Testing and Materials
BS	British Standards
FSP	Fibre Saturation Point
h	Hours
kN	Kilo Newton
LmwPF	Low Molecular Weight Phenol Formaldehyde
MC	Moisture Content
Min	Minutes
MOE	Modulus of Elasticity
MOR	Modulus of Rupture
MPa	Mega Pascal
M_w	Molecular Weight
OPW	Oil Palm Wood
PF	Phenol Formaldehyde
ST	Soaking Time
TS	Thickness Swelling
UPM	Universiti Putra Malaysia
WPG	Weight Percent Gain

CHAPTER 1

INTRODUCTION

1.1 Background of study

Oil palm, *Elaeis guineensis* Jacq., was first grown in Africa (Corley *et al.*, 1976). It is endemic to a wide coastal belt stretching from Senegal to Angola, extending further along the Congo River (Moll, 1987). Evidence show in Egyptian tombs, people buried in casks of palm oil, reflecting the high societal value attributed to the product. Needless to say with the origins in West Africa and evident consumption in Egypt, palm oil can be considered one of the earliest traded commodities (Reade, 1872)

European settlers and entrepreneurs, see the opportunity for commercial palm oil production to produce soaps, lubricants and edible oils had lead to a dramatic expansion of oil palm productions throughout Sub-Saharan and Southeast Asia (Arif, 2015).

The palm oil industry in Malaysia has evolved dramatically since the first commercial planting took place in Tennamaran Estate in Selangor in 1917, laying the brass tacks for the industry in Malaysia. The astonishing development of the oil palm that started off as ornate into a multibillion ringgit industry makes Malaysia among as the largest oil palm producing country. Currently, there are about 5.74 million hectares of oil palm had been planted (MPOC, 2017).

The phenomenal growth of this crops in Malaysia, led to the new challenge where the rapid increase of the oil palm plantation resulted to environmental pollution. Being sensitive to environmental concerns is becoming important to sustain the environment well-being by changing a so called waste to wealth.

1.2 Problem Statements

The oil palm trunk is one of the forms of residues and waste generated from the oil palm industry. Malaysia currently holds a backlog of 365,414 hectares of oil palm trees older than 25 years old (Dompok, 2014). Decreasing of rubberwood supply cause by the plant is replacing by the oil palm plantation furthermore will result decreasing of solid wood supply for furniture industry and increase massive residue and waste in the future if the oil palm waste does not use efficiently.

To cater the lost of source by the decreasing of rubberwood supply, the oil palm trunk seems to be the preferred choice. Palm waste is abundant and readily available

(Salmiyati *et al.*, 2016). It is accessible in large amount throughout the year but this material has not been fully utilized yet. This is due to not only variation but also quality inferior. It is why the quality improvement needed. The great variations in physical and mechanical properties caused many difficulties of working and using the wood for application.

Therefore, quality improvement is vital. It is true that many specialty treatments can be applied to wood by either improve its performance or change its properties, and then compressed to improve dimensional stability and increase hardness. A number of studies have been carried out through resin impregnation and compression (Zaidon, 2009; Aik Fei, 2010; Nur Izreen *et al.*, 2011; Rabia'tol Adawiah *et al.*, 2012).

Indeed this area had been widely explore, and capable to enhance the properties of oil palm wood, but there are few things that seems needed to be alter and one can be simplifying in the process and significantly may improve the weakness of the usual method that had been done before. From that, new method had been introduced (Bakar *et al.*, 2014).

The new technique known as Integrated Treatment Process consists of six-step process has been introduced by Bakar, 2014. This method involve six processing step. Debarking-sawing, steaming and compression, drying, resin inclusion, resin semi-curing heating and hot pressing. The key point and the essential parts of this process is that the sawing process of the oil palm trunk is unique without need to be squared and then followed by the compression under cold pressing.

Instead of using the polygon sawing that is not only time consuming but also difficult and required high-skilled operator to conduct, this process uses a newly introduced sawing pattern called "reverse cant sawing". On the other hand, the compression is made to reduce the moisture content and create micro cracks necessary for fastening the drying process (Bakar *et al.*, 2014).

1.3 Justifications of study

This research was carried out to study the performance of oil palm when treated with low molecular weight phenol-formaldehyde (Lmw-PF) using new method, integrated treatment process which is a continuous improvement of previous impregnation and densification method. As this is a new technique, more research needed to be done in many ways which targeted to enhance the physical and mechanical properties of the treated oil palm wood. There are several variables in the each steps of the new process need to be optimized especially the variables in the compression step and resin inclusion step. There are no study have been done in this aspect of where the effect of compression affects towards oil palm wood that varies in shape and thickness.

The treatments are designed to improve the properties of oil palm wood, and in return promote the usage of this wood species. These treatments may minimal the costs because resin inclusion is done by soaking instead impregnating. Furthermore, it is expected that the increasing quality of the material may also offset the cost of processing.

1.4 Objectives of study

The objectives are to

1. Determine the effect of sample location on quality of treated oil palm wood;
2. Determine the effect of initial timber shape (square and waned) on the properties of treated oil palm wood;
3. Determine the effect of sawn timber thickness on the properties of treated oil palm wood;

1.5 Significance of study

This study emphasizes the new method of the oil palm wood quality enhancement. It does simplify the procedure and fasten the processing time of the method introduced before. It may save time, energy and cost, yielding good quality treated oil palm wood. Combined with other environmental aspect, this high quality treated oil palm wood can be a viable alternative for solid wood. The use of oil palm biomass also supports the conservation of forests in Malaysia and the rest of the world. Hopefully, the outcome of this research can be used as future reference by other researcher.

REFERENCES

- A Pizzi and R. Smit (1987). Phenol-Formaldehyde Structures in Relation to Their Adhesion To Wood Cellulose. Wood Adhesives: Chemistry and Technology, Volume 2.
- A. Gardziella, L.A. Pilato and A. Knop, (2000). Phenolic Resins: Chemistry, Applications, Standardization, Safety and Ecology. Springe.
- Abare, A.Y., Bakar E.S, Ashaari Z. (2014). Effect of Steaming and Compression On The Physical – Mechanical Properties Of Compreg OPW Treated With The 6-Step Processing Method, Department Of Forest Production, Faculty Of Forestry, Universiti Putra Malaysia.
- Abdul Khalil, H.P.S., Hashim, R. (2004). *Komposit Panel Berasaskan Sumber Kayu*, Universiti Sains Malaysia Publisher, Penang.
- Abdul Khalil, H. P. S., and Bhat, A. H. (2010). "Oil palm biomass: Fibre cultivation, production and its varied applications," In: Oil Palm: Cultivation, Production and Dietary Components, S. A. Penna (ed.), Nova Science Publisher, Inc., 21-34.
- Akmar, P., and Kennedy, J. (2001). "The potential of oil and sago palm trunk wastes as carbohydrate resources," Wood Science and Technology 35(5), 467-473.
- Alcaide, L. J., Parra, I. S., & Baldovin, F. L. (1990). Characterization of Spanish agricultural residues with a view in obtaining cellulose pulp. Tappi Journal, 73(8), 173–177.
- Amarullah, M., Bakar, E.S., Ashaari, Z., Sahri, M.H., & Febrianto, F. (2010). Reduction of formaldehyde emission from phenol formaldehyde treated oil palm wood through improvement of resin curing state. Journal of Tropical Wood Science and Technology, 8(1), 9-14.
- Amarullah, M. (2010). Formaldehyde Emission and Properties of Phenol Formaldehyde treated Oil Palm Wood, Unpublished M.S. thesis, Universiti Putra Malaysia, Malaysia.
- Arif E.J. 2015. The Benefits of A Jurisdictional Approach to Sustainable Palm Oil Production. Info Sawit. Indonesian Palm Oil Magazine.
- ASTM. D-1666-87. 1999. Standard Method for Conducting Machining Test of Wood and Wood-Base Materials. West Conshohocken: American Standard for Testing and Materials.

- Bakar, E. S., Rachman, O., Hermawan, D., Karlinasari, L., and Rosdiana, N. (1998). "Utilization of oil palm trees as building and furniture materials (1): Physical and chemical properties and durability of oil palm trunk," *Journal of Forest Products* 11(1), 1-12.
- Bakar, E.S., Rachman, O., Darmawan, W., and Hidayat, I. (1999a). "Utilization of oil palm trunk (*Elaeis guineensis* Jacq) as construction materials and furniture (II): Mechanical properties of oil palm wood," *Journal of Forest Products Technology*, Vol. XII (1) 10-20 (in Indonesian).
- Bakar, E. S., Massijaya, Y., Tobing, T. L., and Ma'mur, A. (1999b). "Utilization of oil palm trunk (*Elaeis guineensis* Jacq.) as construction materials and furniture (III): Treatibility properties of oil palm wood with Baselite-CFK and Impralite-BL," *Journal of Forest Products Technology*, Vol. XII (2) 13-20 (in Indonesian).
- Bakar, E. S., Rachman, O., Darmawan, W., and Hidayat, I. (1999c). "Utilization of oil palm trees as building and furniture materials (2): Mechanical properties of oil palm trunk," *Journal of Forest Products Technology* 12(1), 10-20.
- Bakar, E.S. 2000. Utilization of Oil Palm Stem (*Elaeis guineensis* Jacq) as Housing and Furniture Material. Department of Forest Product, Bogor Agricultural University.
- Bakar, E. S., Parida, Md. T., and Shari, M. H. (2005). "Properties enhancement of oil palm lumber through the compreg method," *International Symposium on Wood Science and Technology*, Pacifico Yokohama, Japan, 91-92.
- Bakar, E.S., Tahir P.M., & Sahri, M.H. (2005). Properties enhancement of oil palm wood through the compreg method. *Proceedings International Symposium of Wood Science and Technology*, 2, 91-92.
- Bakar, E.S., Febrianto, F., Wahyudi, I., & Ashaari, Z. (2006). Polygon Sawing: an optimum sawing pattern for oil palm stems. *Journal of Biological Sciences*, 6(4), 744-749.
- Bakar, E.S., Sahri, M.M., Ashaari, Z., & Febrianto, F. (2007). Oil palm trunks - A new alternative material for solid wood products. *Proceedings of IUFRO-All Division 5 Conference: Forest Product and Environment: A Productive Symbiosis*. p.112.
- Bakar, E.S., Sahri, M.H., & H'ng, P.S. (2008). Chapter 12 Anatomical characteristics and utilization of oil palm wood. T. Nobuchi, M.H. Sahri, (Eds.). *The formation of wood in tropical forest tress - A challenge from persepective of functional wood anatomy* (pp.161-178). Penerbit UPM.
- Bakar, E. S., Tahir, P. M., Sahri, M. H., Mohd Noor, M. S., and Zulkifli, F. F. (2013). "Properties of resin impregnated oil palm wood," *Journal of Tropical Agricultural Science*, in press.

- Bakar, E.S., Ashaari, Z., Choo, A.C.Y., & Abare, A. (2014). A new method of producing Compreg Oil Palm Wood. Malaysia
- Boudet, M. (2000). Lignin and lignification: selected issues. *Plant Physiology and Biochemistry*, 38, 81–96.
- Bustos, C.A, Escobar, W.G, Cloutier, A., Fang, C-H., and Carrasco, P.V. (2011) “Densification of wood veneers combined with oil heat treatment. Part 3: Cell wall mechanical properties determined by nanoindentation,” *BioResources* 7(2), 1525-1532.
- Choon, K. K., Killmann, W., Choon, L. S., and Mansor, H. (1991). —Characteristics of the oil palm stem, *Oil Palm Stem Utilization*, K. Shaari, K. C. Khoo, and A. R. M. Ali (eds.), Forest Research Institute Malaysia, Kuala Lumpur, Malaysia, 15-28.
- Chong, Y. W., Bakar, E. S., Zaidon, A., and Sahri, M. H. (2010). “Treatment of oil palm wood with low-molecular weight phenol formaldehyde resin and its planing characteristic,” *Wood Research Journal* 1(1), 7-12.
- Corley, R.H.V., Wood, B.J. & Hardon, J.J. (1976). Future developments in oil palm cultivation. *Oil Palm Research*, Elsevier. Amsterdam.
- Dompok, T.S.B.G. (2014). “Deepening Malaysia’s Palm Oil Advantage” in *Oil Palm*, 1st ed., Malaysia. 288–289.
- Dungani et al. (2013). “Review: Palm impregnation,” A Review on Quality Enhancement of Oil Palm Trunk Waste by Resin Impregnation: Future Materials. *Bio Resources* 8(2).
- Douglas, C. J. (1996). Phenylpropanoid metabolism and lignin biosynthesis: From weeds to trees. *Trends in Plant Science*, 1(6), 171–178.
- Erwinsyah (2008). —Improvement of oil palm trunk properties using bioresin, Ph.D Dissertation, Faculty of Environmental Sciences, Technische Universität Dresden, Germany. <http://www.qucosa.de/fileadmin/data/qucosa/documents/608/1211880694953-3697.pdf>
- Furuno T, Goto T (1978) Structure of the interface between wood and synthetic polymer (XI). The role of polymer in the cell wall on the dimensional stability of wood-polymer composite (WPC). *Mokuzai Gakkaishi* 24(5):287–293.

- Furuno T, Goto T (1979) Structure of the interface between wood and synthetic polymer (XII). Distribution of styrene polymer in the cell wall of wood-polymer composite (WPC) and dimensional stability. *Mokuzai Gakkaishi* 25(7):488–495
- Furuno, T., Imamura, Y., Kajita, H., 2004. The modification of wood by treatment with low molecular weight phenol-formaldehyde resin: a properties enhancement with neutralized phenolic-resin and resin penetration into wood cell walls. *Wood Sci. Technol.* 37, 349–361.
- H. Moll. The economic of oil palm. Economics of crops in developing countries no. 2, Centre of Agricultural Publishing and Documentation (PUDOC), Wageningen, Netherlands, 1987.
- He, L., & Terashima, N. (1990). Formation and structure of lignin in monocotyledons. III. Heterogeneity of sugarcane (*Saccharum officinarum*) lignin with respect to the composition of structural units in different morphological region. *Journal of Wood Chemistry and Technology*, 10, 435–459.
- H'ng, P. S., Wong, L. J., Chin, K. L., Tor, E. S., Tan, S. E., Tey, B. T., & Maminski, M. (2011). Oil palm (*Elaeis guineensis*) trunk as a resource of starch and other sugars. *Journal of Applied Sciences*, 11, 3053–3057.
- Hill, C.A.S. (2006). *Wood Modification: Chemical, Thermal and Other Process*. John Wiley and Sons Ltd., England. 239 pp.
- Husin, M., Zakaria, Z. Z., & Hassan, A. H. (1985). Potentials of oil palm by-products as raw materials for agro-based industries. Proceedings of the national symposium on oil palm by-products for agro-based industries, Kuala Lumpur. *Palm Oil Research Institute Malaysia Bulletin*, 11, 7–15.
- Haynes W.M. (2015). *CRC Handbook of Chemistry and Physics* (96th ed.). Boca Raton, CRC.
- Imamura H, Okamoto H, Goto T, Yasue Y, Yokota T and Yoshimoto T (1983) *Chemistry for wood utilization* (in Japanese). Kyoritsu-Shuppan, Tokyo, pp. 261–262.
- Imamura Y, Kajita H and Higuchi N (1998a) Modification of wood by treatment with low molecular phenol-formaldehyde resin (1). Influence of neutral and alkaline resins (in Japanese). In: Abstracts of the 48th Annual Meeting of the Japan Wood Research Society, Shizuoka, Japan, April 1998.
- Integrated Taxonomic Information System (ITIS) (2012). “*Elaeis guineensis* Jacq.,” ITIS Report TSN 506719, <http://www.itis.gov/servlet/SingleRpt/SingleRpt>.

- Kajita H, Imamura Y (1991) Improvement of physical and biological properties of particleboards by impregnation with phenolic resin. *Wood Sci Technol* 26(1):63–70.
- Knop, W. and Scheib, A. (1979). *Chemistry and Applications of Phenolic Resin-Polymer Properties and Applications -3*. Springer Verlag: Berlin, Germany.
- Kosugi, A., Tanaka, R., Magara, K., Murata, Y., Arai, T., Sulaiman, O., et al. (2010). Ethanol and lactic acid production using sap squeezed from old oil palm trunks felled for replanting. *Journal of Bioscience and Bioengineering*, 4, 4–12.
- Lane, L. (2012). Economic growth, climate change confusion and rent seeking a case of palm oil. *Journal of Palm Oil and the Environment*, 3, 1–8.
- Law, K. N., & Jiang, X. F. (2001). Comparative papermaking properties of oil palm empty fruit bunch. *Tappi Journal*, 84(1), 1–13.
- Lim, S.C, & Khoo, K.C. (1986). Characteristics of oil palm trunk and its potential utilization. *Malaysian Forester* 49(1), 3-23
- Loh, Y.F., Paridah, M.T., Hoong, Y.B., and Yoong, A.C.C. (2011). “Effects of treatment with low molecular weight phenol formaldehyde resin on the surface characteristics of oil palm (*Elaeis guineensis*) stem veneer,” *Journal of Materials and Design*, 32, 2277-2283.
- Mohammad A., Vijay B.T.D. (2008), *Mergers and Value Creation A Case Study of Sime Darby Berhad*. Graduate Study of Business, University of Malaya, 1, 4-5.
- Malaysia Palm Oil Council. (2017). *Economics & industry Development Division, Malaysian Oil Palm Statistics*.
- N. Abdullah and F. Sulaiman. (2013). *The Oil Palm Wastes in Malaysia*. Intech.
- Norimoto, M. and Gril, J. (1993). Structure and properties of chemically treated woods. In: *Recent Research on Wood and Wood-based Materials*, Shiraishi, N., Kajita, H. and Norimoto, M. (eds.). Elsevier, Barking, UK, pp. 135–154.
- Nur Izrean, F. A., Zaidon, A., Robia'tol Adawiah, M. A., Bakar, E. S., Paridah, M. T., Mohd. Hamami, S., and Anwar, U. M. K. (2011). “Enhancing the properties of low density hardwood *Dyera costulata* through impregnation with phenolic resin admixed with formaldehyde scavenger,” *Journal of Applied Sciences* 11(20), 3474-3481
- Nguyen, Q. A., and Tucker, M. P. (2002). “Dilute acid/metal salt hydrolysis of lignocellulosics,” United States Patent, Number 6,423,145.

- Ohmae, K., Minato, K. and Norimoto, M. (2004). The analysis of dimensional changes due to chemical treatment and water soaking for Hinoki wood. *Holzforschung*, 56: 98-102.
- Rabia'tol Adawiah, M.A., Zaidon, A., Nurizreen, F.A., Bakar, E.S., Mohd Hamami, S. and Paridah, M.T. 2012. Addition of urea as formaldehyde scavenger for low molecular weight phenol formaldehyde treated compregwood. *Journal of Tropical Forest Science* 24(3): 265-274.
- Rowell, R.M. and Banks, W.B. (1985). Water repellency and dimensional stability of wood. General Technical Report FPL-50. USDA, Forest Service, Forest Products Laboratory, Madison, WI, USA. 24p.
- Rowell, R. M., and Konkol, P. (1987). "Treatments that enhance physical properties of wood," FPL, General Technical Report FPL-GTR-55, pp.12.
- Rowell, R. M. (2005). "Ch. 14: Chemical modification of wood," *Handbook of Wood Chemistry, Wood Composites*, R. M. Rowell (ed.), CRC Press, Boca Raton, USA, 381-420.
- Ryu, J. Y., Takahashi, M., Imamura, Y., and Sato, T. (1991). "Biological resistance of phenol-resin treated wood," *Mokuzai Gakkaishi* 37(9), 852-858.
- Salmyati, S., Heriyansyah, A., Muhamad, I.I, Supriyanto, Eko. (2016). Effect of palm waste on sloping land to Fresh Fruit Bunch Production in Oil Palm Plantation. *Walailak Journal of Science and Technology (WJST)*.
- Sofina, S.Y. (2012) *Plastics Technology. Tutorial Part 2*, 62.
- Singh, R. P., Ibrahim, M. H., & Esa, N. (2010a). Composting of waste from palm oil mill: A sustainable waste management practice. *Review in Environmental Science and Biotechnology*, 9, 331–344.
- Sitti Fatimah, M. R., Sulaiman, O., Hashim, R., Arai, T., Kosugi, A., Abe, H., et al. (2012). Characterization of parenchyma and vascular bundle of oil palm trunk as function of storage time. *Lignocellulose*, 2, 141–148.
- Stamm, A. J., and Seborg, R. M. (1936). "Resin-treated plywood," *Ind. Eng. Chem.* 31, 897-902.
- Stamm, A.J. (1964). *Wood and Cellulose Science*. Ronald Press, New York, USA.
- Stevenson, Tom (22 December 2006). "Malaysia targets alternative fuels market". *The Daily Telegraph* (London).
- Suhaily et al., (2012). "Review of palm composites," *Bio Resources* 7(3), 4400-4423.
- Sulaiman, O., Hashim, R., Wahab, R., Samsi, H. W., and Mohamed, A. H. (2008). "Evaluation on some finishing properties of oil palm plywood," *Holz Roh Werkst* 66, 5- 10.

- Sulaiman, O., Mohamad, N. H., Hashim, R., Ibrahim, M., & Ibrahim, M. I. H. (2012). Effect of pretreatment using microorganism on production of pulp from oil palm trunk. *International Wood Products Journal*, 2(2), 89–94.
- Szmigielski, M., B. Maniak and W. Piekarski, Evaluation of chosen quality parameters of used frying rape oil as fuel biocomponent, *Int. Agrophys*, 22 (4), 2008, pp.361-364.
- Tabernig, B. and Pippan, R.,. (2002). *Engineering Fracture Mechanics*, vol 69. 899-90.
- Thanate, R., Tanong, C., and Sittipon, K. (2006). “An investigation on the mechanical properties of trunks of palm oil trees for the furniture industry,” *Journal of Oil Palm Research* 114-121.
- Tomimura, Y. (1992). Chemical characteristics and utilization of oil palm trunks. *Japan Agricultural Research Quarterly (JARQ)*, 25, 283–288.
- Winwood Raede, (1872). *The martyrdom of man*. London Trubner & Co., Darwin Library.
- Wolfgang Hesse, (2002). Phenolic Resins" in *Ullmann's Encyclopedia of Industrial Chemistry*.
- World Growth Palm Oil Green Development Campaign: Palm Oil — The Sustainable Oil a Report by World Growth September 2009. Available online at <http://www.worldgrowth.org/assets/files/Palm_Oil.pdf>, (accessed 22 April 2014).
- Yazaki, Y. & Collins, P.J. *Holz als Roh-und Werkstoff* (1994) 52: 307.
- Yew F.K., (2012), CO₂ Removal through Oil Palm Plantations Contributes Significantly to Malaysia's Carbon Sink Status, MPOC.
- Zhong, R., Taylor, J. J., & Ye, Z. H. (1997). Disruption of interfascicular fiber differentiation in an Arabidopsis mutant. *Plant Cell*, 9, 2159–2170.

BIODATA OF STUDENT

The student, Nurul Nabilah binti Hamzah was born in Georgetown, Penang, Malaysia on 24th of October 1987. She completed her primary education at Sekolah Rendah Saint Anne's Convent and secondary education at Sekolah Menengah Kebangsaan Kulim and Sekolah Menengah Kebangsaan Sultan Badlishah, respectively, all located in Kulim, Kedah, Malaysia. In 2005, she excels her higher education at Kedah Matriculation College in the northern region of Malaysia. She received a degree of Bachelor Science (Hons.) in Furniture Technology at Faculty of Applied Science, University of Technology MARA (UiTM), Shah Alam, Selangor, Malaysia on 2009. She constructed a thesis entitled "Physical and Mechanical Properties of Kenaf Reinforced with Polyethylene". In late 2009, she pursued her Master's degree in the field of wood science and technology at Faculty of Forestry, Universiti Putra Malaysia under supervision of Assoc. Prof. Dr. Edi Suhaimi Bakar and Prof. Dr. Zaidon Ashaari.



UNIVERSITI PUTRA MALAYSIA

STATUS CONFIRMATION FOR THESIS / PROJECT REPORT AND COPYRIGHT

ACADEMIC SESSION : Second Semester 2016/2017

TITLE OF THESIS / PROJECT REPORT :

EFFECTS OF SAMPLE LOCATION AND SAWING METHOD ON QUALITY OF OIL PALM WOOD

NAME OF STUDENT: NURUL NABILAH BINTI HAMZAH

I acknowledge that the copyright and other intellectual property in the thesis/project report belonged to Universiti Putra Malaysia and I agree to allow this thesis/project report to be placed at the library under the following terms:

1. This thesis/project report is the property of Universiti Putra Malaysia.
2. The library of Universiti Putra Malaysia has the right to make copies for educational purposes only.
3. The library of Universiti Putra Malaysia is allowed to make copies of this thesis for academic exchange.

I declare that this thesis is classified as :

*Please tick (v)

CONFIDENTIAL

(Contain confidential information under Official Secret Act 1972).

RESTRICTED

(Contains restricted information as specified by the organization/institution where research was done).

OPEN ACCESS

I agree that my thesis/project report to be published as hard copy or online open access.

This thesis is submitted for :

PATENT

Embargo from _____ until _____
(date) (date)

Approved by:

(Signature of Student)
New IC No/ Passport No.:

(Signature of Chairman of Supervisory Committee)
Name:

Date :

Date :

[Note : If the thesis is CONFIDENTIAL or RESTRICTED, please attach with the letter from the organization/institution with period and reasons for confidentially or restricted.]