



UNIVERSITI PUTRA MALAYSIA

***AN EFFICIENT NETWORK MOBILITY MANAGEMENT FOR A 6LoWPAN
MOBILE NETWORK IN HOSPITAL ENVIRONMENTS***

MOHAMMADREZA SAHEBI SHAHAMABADI

FK 2017 124



**AN EFFICIENT NETWORK MOBILITY MANAGEMENT FOR A 6LoWPAN
MOBILE NETWORK IN HOSPITAL ENVIRONMENTS**

By

MOHAMMADREZA SAHEBI SHAHAMABADI

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia In
Fulfillment of the Requirements for the Degree of Doctor of Philosophy**

October 2017

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the degree of Doctor of Philosophy

**AN EFFICIENT NETWORK MOBILITY MANAGEMENT FOR A 6LoWPAN
MOBILE NETWORK IN HOSPITAL ENVIRONMENTS**

By

MOHAMMADREZA SAHEBI SHAHAMABADI

October 2017

Chairman: Professor Borhanuddin b. Mohd Ali, PhD
Faculty: Engineering

In recent times, the hospital wireless sensor network (HWSN) has become one of the most important IPv6 over low-power personal area network (6LoWPAN) applications because the patients are attached with tiny 6LoWPAN sensors. One of the application scenarios is the monitoring of patients' vital signals while the patients are on the move within the hospital premise. Among the different WSN mobility protocols, NEMO is the most common for 6LoWPAN mobile network in buildings equipped with wireless network infrastructure, such as with the case at modern hospitals and clinics. Current network mobility solutions do not perform well in terms of end-to-end delay, packet loss, handover signalling delay and signalling cost in 6LoWPAN area, to keep continuous connectivity for transmitting patients' vital signals. To this date, only a few works on NEMO for 6LoWPAN mobile networks have been reported. The foremost demand of medical application is the need to ensure quality of service (QoS) for data transfer due to its criticalness in medical context. This thesis aims to present an efficient mobility management protocol for HWSNs to reduce patient's data packet loss rate, signalling cost, handover delay, end-to-end delay, and optimize the energy consumption to maintain continued connectivity with the remote care giver.

The effects of three design parameters, namely number of mobile network nodes (MNNs), number of handovers, and MNN packet generation rate in NEMO are evaluated. It is shown that the mobile router (MR) suffers from high energy consumption and traffic congestion which result in a bottleneck. If the MR drains its energy entirely, the connectivity with home network will be lost. Hence, in this thesis, we propose a number of schemes for NEMO based on 6LoWPAN MNNs. The first scheme improves the NEMO handover process on HWSN based on 6LoWPAN called HWSN6 mobility solution. This is extended to MR to offer a fast handover mechanism with low handover

signalling cost, handover delay and packet loss, respectively. The second scheme is a message-scheduling algorithm based on route optimization in tunnelling process between the MNNs and HA to decrease the traffic congestion at MR and packet end-to-end delay. The third scheme considers on the remaining energy of MR to optimize energy consumption to prolong the connectivity between MNNs and HA, this is called selective optimal MR algorithm.

The results are drawn from analytical models and OMNeT++ simulator running on Contiki to perform the 6LoWPAN adaptation layer tasks. An analytical model of the proposed scheme is derived for handover signalling cost, handover signalling delay, and tunnelling cost. Simulation results show that the proposed solution reduces traffic congestion at MR by using the HWSN6 handover solution and the message-scheduling algorithm in the tunnelling process. The number of handover signalling messages is reduced from 6 stages in MIPv6 to 3 stages, this is achieved by exploiting other network elements such as border router (BR). The handover signalling costs and packet loss in the proposed scheme, NEMO-HWSN, are optimized around 13% and 31% respectively and compared to NEMO. Then, by using the proposed message-scheduling algorithm, end-to-end delay in NEMO-HWSN is reduced by approximately 20%. Finally, by using the selective optimal algorithm, the MR energy consumption in NEMO-HWSN is minimized by approximately 15.5%. Our proposed scheme also has a good performance for intra-PAN mobility like hospital environments because it skips the “Binding” and “Challenge” process in intra-PAN mobility. The above results proved that the NEMO-HWSN is more efficient than other schemes in the HWSN environment, with low handover signalling delay, handover signalling cost, packet loss, packet end-to-end delay and energy consumption. Analytical models and simulation have been conducted to show the validation of work to verify that simulation results correspond to reference values (MIPv6, NEMO and HWSN6).

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Doktor Falsafah

PENGURUSAN MOBILITI RANGKAIAN BAGI RANGKAIAN MUDAH ALIH 6LoWPAN DALAM PERSEKITARAN HOSPITAL

Oleh

MOHAMMADREZA SAHEBI SHAHAMABADI

Oktober 2017

Pengerusi: Profesor Borhanuddin b. Mohd Ali, PhD
Faculti: Kejuruteraan

Pada masa mutakhir ini, rangkaian penderia tanpa wayar di hospital (HWSN), yang mana pesakit adalah diliputi dengan penderia IPv6 di atas rangkaian kawasan peribadi bertenaga-rendah (6LoWPAN), telah menjadi salah satu dari aplikasi terpenting 6LoWPAN. Salah satu dari senario aplikasinya adalah bagi pemantauan isyarat penting dari pesakit apabila pesakit sedang bergerak dalam kawasan hospital. Di antara beberapa banyak protokol mobiliti WSN, NEMO adalah paling lazim digunakan untuk rangkaian bergerak 6LoWPAN dalam bangunan yang dilengkapi dengan prasarana rangkaian tanpa wayar, seperti yang terdapat dalam hospital dan klinik yang modern. Penyelesaian bagi mobiliti rangkaian masa kini tidak menunjukkan prestasi yang baik dari segi langkah hujung-ke-hujung, kehilangan paket, kelewatan isyarat penyerahan dan kos pengisyaratan apabila digunakan bersama 6LoWPAN. Sehingga kini, hanya beberapa kajian tentang NEMO bagi rangkaian mudah alih 6LoWPAN telah dilaporkan. Permintaan yang paling utama untuk aplikasi perubatan adalah untuk memastikan kualiti (QoS) untuk penghantaran data oleh kerana runcingnya keadaannya dalam konteks perubatan. Tesis ini membentangkan satu protokol pengurusan mobiliti untuk HWSN untuk mengurangkan kadar kehilangan paket data, langkah penyerahan dan hujung-ke-hujung masing-masing, dan mengoptimumkan penggunaan tenaga untuk mengekalkan penyambungan kepada pemberi penjagaan yang berada pada jarak jauh.

Kesan kepada tiga parameter reka bentuk, iaitu bilangan nod rangkaian bergerak (MNNs), bilangan penyerahan dan kadar penjanaan paket dari MNNs, masing-masing, telah dinilai. Adalah ditunjukkan bahawa penghala mudah alih (MR) mengalami penggunaan tenaga yang tinggi dan kesesakan trafik yang mengakibatkan keadaan terjerut. Jika tenaga MR hapus keseluruhannya, sambungan antara rangkaian mudah alih

dengan rangkaian perumah akan hilang. Oleh itu, di dalam tesis ini, kami mencadangkan beberapa skim untuk NEMO berdasarkan MNN 6LoWPAN. Skim yang pertama memperbaiki proses penyerahan NEMO ke atas HWSN berasaskan 6LoWPAN yang dipanggil sebagai penyelesaian mobiliti HWSN6. Ianya dilanjutkan pada MR untuk menyediakan mekanisma penyerahan yang lebih pantas beserta kos pengisyaratan yang rendah. Skim yang kedua ialah algoritma penjadualan risalah berasaskan pengoptimuman laluan dalam proses penorowangan di antara MNNs dan HA, bagi mengurangkan kesesakan trafik pada MR dan lengah hujung-ke-hujung. Skim yang ketiga mempertimbangkan baki tenaga MR untuk mengoptimumkan penggunaan tenaga rangkaian mudah alih untuk memanjangkan tempoh penyambungan antara MNN dan HA, ini dipanggil sebagai algoritma MR optimum terpilih.

Hasil keputusan adalah dipetik dari model analitik dan simulator OMNet++ yang beroperasi di atas Contiki untuk melaksanakan tugas lapisan adaptasi. Satu model analitik pada skim cadangan ini adalah diterbitkan untuk mendapatkan kos pengisyaratan penyerahan, lengah pengisyaratan penyerahan, dan kos penerowongan. Hasil keputusan simulasi menunjukkan bahawa penyelesaian cadangan ini dapat meringankan kesesakan trafik di MR dengan menggunakan penyelesaian penyerahan HWSN6 dan algoritma penjadualan-risalah dalam proses penerowongan. Bilangan risalah pengisyaratan dapat dikurangkan dari 6 peringkat dalam MIPv6 kepada 3 peringkat, ini dapat dicapai dengan mengeksploitasi unsur-unsur lain rangkaian seperti penghala sempadan (BR). Kos pengisyaratan penyerahan dan kehilangan paket dalam skim cadangan NEMO-HWSN ini, telah dioptimumkan berbanding NEMO dengan kadar 13% and 31%, masing-masing. Kemudian, dengan menggunakan algoritma penjadualan-risalah cadangan ini, lengah hujung-ke-hujung dalam NEMO-HWSN adalah dikurangkan dengan 20%. Akhir sekali, dengan menggunakan algoritma optimum terpilih, penggunaan tenaga MR dalam NEMO-HWSN dapat dikurangkan dengan 15.5% lebihkurang. Skim cadangan kami juga mempunyai prestasi yang baik untuk mobiliti intra-PAN seperti pada persekitaran hospital kerana ia tidak perlu menjalankan proses “Binding” dan “Challenge” dalam mobiliti intra-PAN. Hasil keputusan di atas membuktikan bahawa NEMO-HWSN adalah lebih cekap dari skim-skim lain dalam persekitaran HWSN, dengan pengurangan dalam lengah pengisyaratan penyerahan, kos pengisyaratan penyerahan, kehilangan paket, lengah hujung-ke-hujung dan penggunaan tenaga, masing-masing. Model analisis dan simulasi telah dilakukan untuk menunjukkan validasi kerja ini untuk mengesahkan bahawa hasil keputusan simulasi adalah sepadan dengan nilai rujukan (MIPv6, NEMO and HWSN6).

ACKNOWLEDGEMENT

"In the name of Allah, Most gracious, Most merciful"

First of all, great thanks and praises are due to Allah, the Lord of all that exist. May Allah's peace and blessing be upon his final prophet and messenger, Muhammad, his family and his companions.

I would like to express my sincere gratitude to my supervisor Prof. Dr. Borhanuddin b. Mohd Ali, for his guidance, advice, and encouragement in the completion of this study. His professional review helped me to further improve the thesis.

Special thanks dedicated to my supervisory committee member, Prof. Dr. Nor Kamariah bt. Noordin, Assoc. Prof. Dr. Mohd Fadlee b. A Rasid, and Dr. Pooria Varahram for their motivations and encouragements throughout the years.

Last but not least, I would like to express my deepest gratitude to my beloved wife and daughter, Fatemeh and Darya, for their endless support during my hardest time in completing this research.

Finally, I would like to thank everybody who was important to the successful realization of the thesis, as well as expressing my apology that I could not mention personally one by one.

I certify that a Thesis Examination Committee has met on 6 July 2017 to conduct the final examination of Mohammadreza Sahebishahamabadi on his thesis entitled "An Efficient Network Mobility Management for a 6LoWPAN Mobile Network in Hospital Environments" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998: The Committee recommends that the student be awarded the Doctor of Philosophy.

Members of the Thesis Examination Committee were as follows:

Mohd Hanif bin Yaacob, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Mohamed bin Othman, PhD


Professor
Faculty of Computer Science and Information Technology
Universiti Putra Malaysia
(Internal Examiner)

Aduwati binti Sali, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Nazim Agoulmine, PhD

Professor
University of Évry Val D'Essonne
France
(External Examiner)



NOR AINI AB. SHUKOR, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 30 November 2017

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory Committee were as follows:

Borhanuddin b. Mohd Ali, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Nor Kamariah bt. Noordin, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Mohd Fadlee b. A. Rasid, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Pooria Varahram, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Member)

ROBIAH BINTI YUNUS, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- This thesis is my original work;
- Quotations, illustrations and citations have been duly referenced;
- This thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- Intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- Written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- There is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: _____ Date: _____

Name and Matric No.: Mohammadreza Sahebi Shahamabadi (GS31202)

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: _____

Name of
Chairman of
Supervisory

Committee: Prof. Borhanuddin b. Mohd Ali

Signature: _____

Name of
Member of
Supervisory

Committee: Prof. Nor Kamariah bt. Noordin

Signature: _____

Name of
Member of
Supervisory

Committee: Assoc. Prof. Mohd. Fadlee b. A. Rasid

Signature: _____

Name of
Member of
Supervisory

Committee: Dr. Pooria Varahram

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABLES	xiii
LIST OF FIGURES	xiv
LIST OF ABBREVIATIONS	xvii
CHAPTER	
1 INTRODUCTION	1
1.1 Research Background	1
1.2 Problem Statement and Motivations	3
1.3 Research Aims and Objectives	5
1.4 Research Scope and Limitations of Research	6
1.5 Research Contributions	8
1.6 Thesis Organization	9
2 LITERATURE REVIEW	11
2.1 Introduction	11
2.2 6LoWPAN Design Features	12
2.2.1 6LoWPAN Architectures	13
2.2.2 Node Type Based on Functionalities	15
2.2.3 Limitations of 6LoWPAN Mobile Node	15
2.3 Review of Mobility Management in LoWPAN Area	15
2.3.1 Micro-Mobility and Macro-Mobility Management	16
2.3.2 Host-Based and Network-Based Mobility Protocols	17
2.3.3 Node and Group Mobility Movement Model	18
2.4 Network Mobility Management in 6LoWPAN-based WSN	20
2.4.1 Network Mobility Architecture	21
2.4.2 Network Mobility Process	23
2.4.3 Existing Challenges in NEMO Mobility	24
2.5 Healthcare Monitoring System	25
2.6 HWSN6 Mobility Management Protocol	26
2.6.1 HWSN6 Structure	27
2.6.2 Movement Scenario	28
2.6.3 The Scenario of Messages Exchange in HWSN6 Scheme	29
2.6.4 Scenario 1: Engaging All MNNs for Processing the Handover for Group Movement Independently	33

	2.6.5	Scenario 2: Engaging MR for Processing Handover for Group Movement	33
	2.6.6	Comparison of Applied Handover Process by all MNNs or MR in the Mobile Network	35
	2.7	Comparison of Existing IPv6 Mobility Solutions	36
	2.8	Summary	45
3		METHODOLOGY	46
	3.1	Introduction	46
	3.2	Proposed Scheme (NEMO-HWSN) Model	48
	3.3	Development of Handover Process by a Logical Extension of the HWSN6 Protocol at the MR	53
	3.3.1	Analytical Model of Handover Process Time	55
	3.3.2	The Analytical Model of the NEMO-HWSN Handover Signalling Cost	60
	3.3.3	The Analytical Model of the NEMO-HWSN Handover Delay	64
	3.4	Providing Route Optimization in Tunnelling Process with Message-Scheduling Algorithm	66
	3.4.1	The Message-Scheduling Algorithm	69
	3.4.2	The Analytical Model of Tunnelling Cost	71
	3.5	Improving the Energy Saving of MR by Selective Optimal MR Algorithm	72
	3.5.1	The Selective Optimal MR Algorithm	74
	3.5.2	Summary of Source Code of Selective Optimal MR Algorithm	81
	3.6	Simulation Setup	81
	3.6.1	OMNeT++ Discrete Event Simulator	83
	3.6.2	Simulation of NEMO-HWSN Mobility Management	86
	3.6.3	Simulation Parameters and Platform	88
	3.7	Validation of Work	89
	3.8	Summary	90
4		RESULTS AND DISCUSSIONS	91
	4.1	Introduction	91
	4.2	Analysis of NEMO Mobility Management in 6LoWPAN Area	91
	4.2.1	The Effects of the Number of MNNs, Handovers and Packet Arrival Rate on Messages Cost Ratio at MR	92
	4.2.2	The Effects of Number of MNNs, Handovers and Packet Arrival Rate on Signalling Costs	94
	4.2.3	The Effects of Number of MNNs, Handovers and Packet Arrival Rate on End-to-end Packet Delay	95

4.2.4	The Effects of Number of MNNs, Handovers and Packet Arrival Rate on Packet Loss	98
4.2.5	The Effects of Number of MNNs, Handovers and Packet Arrival Rate on Energy Consumption	99
4.3	The Evaluation of Handover Process in NEMO-HWSN Scheme	104
4.3.1	Handover Signalling Costs in NEMO-HWSN Scheme	105
4.3.2	Packet Loss in NEMO-HWSN Scheme	109
4.3.3	Handover Delay in NEMO-HWSN Scheme	110
4.4	The Evaluation of Route Optimization of Tunnelling Process in NEMO-HWSN Scheme	113
4.4.1	The Evaluation of Traffic Congestion at MR in NEMO-HWSN Mobility Management	113
4.4.2	The Evaluation of End-to-End Packet Delay in NEMO-HWSN Mobility Management	115
4.5	The Evaluation of Energy Saving of MR in NEMO-HWSN Scheme	115
4.6	Results of Validation	121
4.7	Summary	124
5	CONCLUSIONS AND RECOMMENDATIONS FOR FUTURE WORKS	126
5.1	Conclusions	126
5.2	Recommendations for future works	127
	REFERENCES	128
	APPENDIX	140
	BIODATA OF STUDENT	146
	LIST OF PUBLICATIONS	147

LIST OF TABLES

Table		Page
2.1	The comparison of node and network mobility management for the 6LoWPAN mobile network	38
2.2	A comparative summary of IPv6 mobility management protocols	44
3.1	The comparison of mobility management architectures	50
3.2	Biomedical sensor data statistics	51
3.3	The notations of handover control messages	56
3.4	The notations of handover process time	56
3.5	The parameters of handover process	61
3.6	The relationship between remaining energy and feasibility to keep connectivity	74
3.7	Simulation parameters in NEMO-HWSN6	88

LIST OF FIGURES

Figure		Page
1.1	Network mobility (NEMO) scenario	5
1.2	Chart of research	7
2.1	Block diagram of a typical sensor node	11
2.2	6LoWPAN architecture	13
2.3	6LoWPAN protocol stack	14
2.4	Classification criteria of mobility support for 6LoWPAN Networks	16
2.5	Micro-mobility and macro-mobility management	17
2.6	Node and group mobility movement model	19
2.7	NEMO architecture	23
2.8	Hospital network architecture	28
2.9	Movement scenario of mobile node	29
2.10	Messages exchanging scenario for moving to the visited network	31
2.11	Messages exchanging scenario for returning to the base network	32
2.12	Messages exchanging scenario for movement between foreign networks	32
2.13	Scenario 1: When all MNNs run the mobility management	33
2.14	Scenario 2: When only the MR runs the mobility management	34
3.1	Methodology flowchart	47
3.2	Example of a hospital building	50
3.3	Structure of mobile patient node in hospital environments	51
3.4	Comparison of the MIPv6 handover with HWSN6 solution	54
3.5	State diagram for a random walk mobility model	56
3.6	The MIPv6 handover process	57
3.7	The NEMO-HWSN handover process	59
3.8	NEMO-HWSN handover signalling cost model	63
3.9	NEMO-HWSN handover delay model	65
3.10	The energy consumption versus hops length	65
3.11	The summary of message-scheduling algorithm procedures	67
3.12	The example of selective optimal MR algorithm	72
3.13	Data transmission model	75
3.14	The transmission distance for MNNs and MR in (a) NEMO and (b) NEMO-HWSN	76
3.15	The selective optimal MR algorithm procedure	79
3.16	Simulation model of IPv6 host over IEEE 802.15.4 module in INETMANET framework	83
3.17	Simulation model of the network layer of 6LoWPAN host	84
3.18	Simulation model of the network layer with MIPv6 support	85
3.19	Simulation platform of NEMO-HWSN with 5 MNNs	86
4.1	The effect of the number of MNNs on message costs ratio at MR	92

4.2	The effect of data time interval of MNNs on message costs ratio at MR	92
4.3	Messages costs ratio at MR against on numbers of handovers	93
4.4	The signalling costs vs. data time interval of MNNs	94
4.5	The signalling costs against the number of handovers and MNNs respectively in NEMO	94
4.6	The mean end-to-end packet delay against the number of MNNs	95
4.7	The mean end-to-end packet delay for MNNs and MR against data time interval of MNNs	96
4.8	The mean end-to-end packet delay against the number of handovers for MR and MNNs	97
4.9	The packet loss versus the number of MNNs for MNN and MR	98
4.10	The packet loss versus data time interval of MNNs for MNN and MR	98
4.11	The packet loss versus the number of handovers for MNN and MR	99
4.12	The energy consumption of the individual sensor nodes versus the number of MNNs for MNNs and MR	100
4.13	The energy consumption versus data time interval of MNNs for MNNs and MR	101
4.14	The energy consumption versus the number of handovers for MNNs and MR	102
4.15	The NEMO-HWSN signalling costs vs. the number of hops for different MR costs	103
4.16	The NEMO-HWSN signalling costs vs. the number of hops for different FA costs	104
4.17	The NEMO-HWSN signalling costs vs. the number of hops for different HA costs	104
4.18	The NEMO-HWSN signalling costs vs. the number of hops for different MR, FA and HA costs	105
4.19	The comparison of inter-PAN mobility and intra-PAN mobility signalling costs in NEMO-HWSN	106
4.20	The comparison of handover signalling costs in NEMO-HWSN with other mobility protocols	106
4.21	The comparison the packet loss rate for NEMO-HWSN and NEMO	107
4.22	The NEMO-HWSN handover delay vs. number of hops	108
4.23	The comparison of mobility hanover delay of inter-PAN mobility and intra-PAN mobility in NEMO-HWSN	109
4.24	Comparison of NEMO-HWSN and NEMO handover delay vs. wireless link delay	111
4.25	Message cost for NEMO and NEMO-HWSN vs simulation time	112
4.26	Mean end-to-end packet delay for MIPv6, HWSN6, NEMO and NEMO-HWSN vs simulation time	113
4.27	The residual energy percentage of MR and MNNs by applying the selective optimal algorithm in NEMO-HWSN	114

4.28	The residual energy of MR before (MR) and after applying the selective optimal algorithm (MR in (NEMO-HWSN))	115
4.29	The residual energy of MNNs before and after applying the selective optimal algorithm	118
4.30	The comparison of MR and MNNs lifetime in NEMO-HWSN against MR NEMO	119
4.31	The comparison of tunnelling costs for MIPv6 and NEMO-HWSN	120
4.32	The signalling costs vs. the number of MNNs	121
4.33	The signalling costs vs. the number of handovers	121



LIST OF ABBREVIATIONS

IoT	Internet of Things
IPv6	Internet Protocol version 6
6LoWPAN	IPv6 over Low-power Personal Area Network
IETF	Internet Engineering Task Force
IP	Internet Protocol
MN	Mobile Node
PAN	Personal Area Network
MIPv6	Mobile IPv6
WSN	Wireless Sensor Network
LoWPAN	Low-power Personal Area Network
SNs	Sensor Nodes
NEMO	Network Mobility
MR	Mobile Router
MNNs	Mobile Network Nodes
MINT	Mobile Internet Router
HA	Home Agent
HWSN	Hospital Wireless Sensor Network
HWSN6	Hospital Wireless Sensor Networks based on 6LoWPAN
BR	Border Router
FA	Foreign Agent
CN	Corresponding Node
FFDs	Full-Function Devices
BU	Binding Update
DAC	Digital-Analog Converter
ADC	Analog-Digital Converter
AP	Access Point
RFD	Reduced-Function Device
MTU	Maximum Transmission Unit
MAC	Media Access Control
CFD	Coordinator-Function Device
BER	Bit-Error Rate
RSSI	Received Signal Strength Indicator
FMIPv6	Fast Mobile IPv6

HMIPv6	Hierarchical Mobile IPv6
DAD	Duplicate Address Detection
GW	Gateway
MNP	Mobile Network Prefixes
CoA	Care of Address
Home Address	HoA
AR	Access Router
VL	Visitor List
MBT	Mobility Binding Table
LU	Location Update
NP	Network Prefix
ECG	Electrocardiogram
HIS	Hospital Information System
PL-PMIPv6	Packet Lossless Proxy MIPv6
PMIPv6	Proxy mobile IP6
MAP	Mobility Anchor Point
MAG	Mobility Access Gateway
AoA	Angle of Arrival
DLowMob	Distributed LowMoB
MSPs	Mobility Support Points
SPMIPv6	Sensor proxy mobile IPv6
LMA	Local Mobility Anchors
RS	Router Solicitation
RA	Router Advertisement
WBANs	Wireless Body Area Networks
PDA	Personal Digital Assistant
AReq	Associate Request
AREp	Associate Request
RReq	Reassociate Request
RRep	Reassociate Request
NL	Node Left
Ack	Acknowledgment
BReq	Binding Request
BCh	Binding Challenge
BC	Binding Confirm
ChReq	Challenge Request

ChRep
ChF
BAN

Challenge Reply
Challenge Forward
Body Area Networks



CHAPTER 1

INTRODUCTION

1.1 Research Background

The Internet of Things (IoT) has emerged as a new paradigm for virtual things related to Internet connectivity and has caught researchers' attention in recent years Ashton, K. (2009). It is the fact that IoT varies, especially it could be used as a part of the future Internet where there are identities between physical and virtual "things". Arising from the emergence of IoT, Internet protocol version 6 (IPv6) over low-power personal area networks (6LoWPANs), which hitherto has not received a great deal of attention, has recently seen a resurgent of activities in the internet engineering task force (IETF) group (Devarapalli *et al.*, 2005). 6LoWPANs has been defined to enable IPv6 connectivity over the IEEE 802.15.4 for communications with the Internet. It leads to a global connectivity among a large number of tiny IPv6 intelligent devices over large areas, using its large address space. 6LoWPAN nodes are characterized by their low bandwidth, short range, ease of deployment, scarce memory capacity, low power consumption, limited processing capability and other attributes associated with inexpensive hardware. 6LoWPANs also has the disadvantage of limited battery capacity for devices and communication (Oliveira *et al.*, 2011 and Airehrour *et al.*, 2016).

It has been argued that mobility support is one of the most important aspects that need to be addressed for the success of IoT (Gershenfeld *et al.*, 2004 and Montavont *et al.*, 2014). This is because, many of the IoT objects are likely to be mobile and therefore require a mobility management protocol for maintaining internet protocol (IP) mobility. When a 6LoWPAN mobile node (MN) as a part of IoT moves freely, it is important to establish a system of mobility management to maintain continuous network connectivity for information to be exchanged unimpeded with the corresponding node or a server. Current mobility protocols have been constrained by limited energy and power reserves in MNs, which are known characteristics of the 6LoWPAN protocol (Jara *et al.*, 2013b).

Depending on the application requirements, two classes of mobility have been defined, they are respectively node mobility and network (or group) mobility. In node mobility, a node moves within the same personal area network (PAN) or between different PANs and runs the mobility mechanism like Mobile IPv6 (MIPv6) regardless of other nodes. MIPv6, as an example of node mobility, causes traffic congestion, increased complexity, increased power consumption and high handover signalling, when all nodes of a group of nodes run MIPv6 mobility management independently (Ha *et al.*, 2010). In contrast, network mobility has become more common for wireless sensor networks (WSN) (Yick *et al.*, 2008) whereby the mobility is considered for the entire low-power personal area network (LoWPAN) network. In 6LoWPAN, a mobile network includes member nodes and an edge router, and only the edge router changes its attachment point on the Internet while the member nodes remain attached to itself (Shelby and Borman, 2011). The IPv6 mobility protocol is further classified into the host-based and network-based mobility,

respectively. The host-based mobility requires additional protocol stacks and signalling, resulting in an additional burden for battery power and computation resource in the MNs. Hence, the host-based mobility approach is unsuitable for energy-constrained sensor nodes (SNs) like 6LoWPAN. On the other hand, in the network-based mobility schemes, the mobility of 6LoWPAN MN is handled at the network-side and the MNs are not involved with IP mobility signalling, hence it is not necessary to install additional mobility protocol stacks in the MN or additional signalling exchange (Kim, *et al.*, 2008). For example, in network mobility (NEMO) presented in (Devarapalli *et al.*, 2005), a special mobility agent in the network known as a mobile router (MR) is responsible for handover, exchanging mobility-related signalling messages and mobility management on behalf of the mobile network nodes (MNNs). However, the MR is involved with most of the handover management signalling, hence its energy will certainly drain very fast (Kim, *et al.*, 2008). Therefore, it is more sensible that this responsibility is taken by the network components due to their readily available power, such as in well-equipped networking centers. With this arrangement, the load on MNs could be reduced, and therefore its lifetime could be prolonged. The benefits of the MR architecture have been recognized in the 1990s. Hager *et al.*, (1993) presented a mobile internet router (MINT) that describes a router with a sufficient computational power to perform all necessary communication protocol operations and enable a connectivity for MNNs attached to the MR. The MR maintains continuous connectivity between MNNs inside the mobile network and the home network by means of an appropriate mobility management scheme. The mobile network is connected to the Internet via an IP-IP tunnel between the MR and the home agent (HA) when the MR is far away from the home network. Therefore, it is evident that NEMO enables increased manageability, conservation of bandwidth, reduced signalling, and reduced power consumption as compared to MIPv6. However, this comes at the expense of inefficient route and signalling costs (Goswami, *et al.*, 2013).

As one of the many possible applications, healthcare has formed one of the most attractive research fields that leverage on 6LoWPAN based WSNs. In this thesis, the author considers the hospital wireless sensor network (HWSN) as a case study (Khan and Mir, 2014a) to monitor the patient's health, as the application scenario. This kind of network collects continuously, various vital signals from patients such as heart rate, breath rate, blood pressure, blood oxygen saturation, ear thermometer, body temperature and also the current location of the patient (Hoey, *et al.*, 2012). It is important to keep continuous connectivity between mobile patient node and the hospital wireless network by way of a proper mobility management, this will let the system know the exact location of the patients, and this should be done with minimal loss of packets and with low signalling. Jara *et al.*, (2010a) presented a hospital wireless sensor network based on 6LoWPAN (HWSN6) mobility as a network-based protocol because a low messaging load is exerted due to the reduced number of messages necessary to support mobility. By avoiding reconfiguring IP addresses, the number of messages exchanged with the patient nodes are reduced from 12 messages exchanged in MIPv6 to 6 messages exchanged, which results in reduced MN's loading compared to other IPv6 mobility solutions such as MIPv6. Finally, this protocol considers the features of the architecture employed in hospitals when a solution to node mobility has been defined, and other elements of the architecture are exploited including border router (BR) and backbone to support mobility. Therefore, clinical environment is one of the main scenarios where the mobility

for the IoT-based applications exploit these capabilities, in terms of fault tolerance and continuous monitoring of patient's data (Jara *et al.*, 2013b). Thus, the main objective of this thesis is to present an efficient network mobility management for a hospital environment that will enable continuous connectivity between the patient node with its HA for transmitting vital signals. The protocol shall minimize involvement of the patient node, this is done by reducing the interaction of the patient node in the network in the mobility protocol.

1.2 Problem Statement and Motivations

As has been highlighted earlier, the HWSN is a suitable solution for e-Health communication that provides real-time monitoring of medical information for patients. It especially handles low-cost and low-power devices suitable for medical sensors used on mobile patients, this can provide effective support for people suffering from chronic diseases or patients during emergencies (Bui *et al.*, 2012). From the survey of existing mobility solutions, it was concluded that the existing schemes still suffer from the extra signalling cost and packet loss during handover and without continuous connectivity, which is not acceptable when some vital and critical data are being transferred (Khan and Mir, 2014a). Hence, the efficient customization in energy efficient and reliable transmission of network mobility management for health data based on 6LoWPAN network is required to improve the quality of healthcare, potentially save the patient's life.

When a set of 6LoWPAN SNs moves together, NEMO solution is better than host mobility, MIPv6 protocol, running each node independently, because it minimizes complexity and number of handover signalling messages of individual hosts, and power consumption of mobile hosts. NEMO protocol has been developed based on the experiences gained from the MIPv6 standardization, and therefore many of the functionalities are actually extensions of MIPv6 as a host-based mobility, which is not suitable for 6LoWPAN. However, this thesis design parameters such as number of MNNs, number of handovers, and packet generation rate from MNNs for NEMO in 6LoWPAN area are analyzed. Hence, even though NEMO is an excellent approach for managing a mobile network, but there are some shortcomings to manage mobility in 6LoWPAN area.

- The transmission of control information in the handover process of NEMO consumes a large amount of energy and the increasing of handover signalling messages increases handover signalling costs, handover delay, packet loss, and causes traffic congestion (Angadi and Shet, 2013).
- After a successful completion of the binding process, a tunnel is established between the MNNs of the MR and its respective HA to achieve a global connectivity with mobile network (MNN-MR-BR-HA or MNN-MR-HA path). When the MR receives the packets from MNNs, it encapsulates them and sends

them to the HA through the tunnel. When the MR receives a packet from a foreign agent (FA) or HA, it decapsulates it and sends it to the MNNs through the tunnel. This imposes an extra burden on the tunnel (MR-HA path) especially when there is a heavy traffic, hence route optimization is necessary for NEMO.

- There is a heavy traffic at the MR due to network management, data transmission, handover signalling messages and tunnelling process (Petander *et al.*, 2006). Since all traffic goes through the MR in a mobile network, overloading at the MR is critical, as a result the MR depletes its energy very fast and die out soon after, which causes a bottleneck problem and completely disconnects. If the MR fails, the connectivity between the network and MNNs will be severed completely. In basic NEMO, modern and powerful devices like smart phones or BRs with assured energy availability are likely candidates to choose as an MR. However, in the 6LoWPAN mobile network, all devices are characterized with energy constraints not having access to permanent energy resources. Figure 1.1 shows the bottleneck at MR in NEMO protocol that will lead to additional packet delays, or even packet losses. Various works have shown a good agreement with traffic congestion on MR and bottleneck problem (Devarapalli *et al.*, (2005), Mocerri (2006), Bag *et al.*, (2009a), Dinakaran and Balasubramanie (2010), and Mosa *et al.*, (2012)). To this date, there are very few works that has been reported to optimize energy consumptions at the MR by way of handling and optimizing the mobility signalling messages.

Khan and Mir (2014a), from their survey on mobility management, concluded that existing schemes still suffer from extra signalling and packet loss during handover, which is not acceptable when some critical data is being transferred.




Figure 1.1: Network mobility (NEMO) scenario

1.3 Research Aims and Objectives

The aim of this thesis is to obtain an efficient NEMO mobility solution with the following features. (1) Network-based protocol to support 6LoWPAN; (2) Network mobility to support mobile patients; (3) Intra-PAN mobility to support the hospital environments; (4) Support low handover signalling cost, low handover delay, low end-to-end packet delay, low packet loss, and low energy consumption to keep continuous connectivity between MNs and a backend server to exchange the vital signals. Based on the problem statements stated previously, the following specific objectives are identified.

1. To reduce the handover signalling costs and handover delay through a handover process of NEMO mobility by HWSN6 solution. Handover signalling is one of

the major design considerations and performance measure to improve the handover performance like packet loss and keep connectivity.

2. To reduce traffic congestion at MR and end-to-end packet delay by way of a message-scheduling algorithm that is based on tunnelling for NEMO route optimization of packets travelling from MNNs to CN.
3. To improve the energy saving of MR in order to prolong its lifetime through a selective optimal MR algorithm. This is achieved by way of distributing the role of MR among all the MNNs to balance network energy.

By developing an optimized signalling protocol during handover and route optimization during tunnelling process, an efficient mobility management for 6LoWPAN mobile networks can be achieved. It also prolongs the MR lifetime to maintain continued connectivity for mobile networks when exchanging the critical data.

1.4 Research Scope and Limitations of Research

The scope of research work is summarized in figure 1.2 with the bold blue color lines indicating the research path. The aim of this thesis is to develop the NEMO solution by reducing the overload at 6LoWPAN network in smart buildings, particularly a hospital environment, to keep connectivity between mobile network and the Internet. As shown in figure 1.2, this work focuses on three main research issues: minimization of handover signalling to reduce the overhead by consideration on mobility control messages, route optimization in tunnelling process of network mobility, and managing the MR based on battery level. Additionally, the MR as a coordinator in the 6LoWPAN mobile network will be evaluated to improve its residual energy. The performance metrics such as signalling cost, end-to-end packet delay, packet loss, traffic congestion on MR will be investigated. OMNeT++ simulator has been developed to evaluate this network model, linked with Contiki, to process the adaptation layer functionalities. The performance metrics such as traffic congestion at MR, signalling cost, end-to-end packet delay, packet loss and the energy consumption of MR during mobility process, are modeled and simulated using OMNeT++ simulator.




Figure 1.2: Chart of research

However, the following assumptions and limitations are defined for the mobility protocol to manage handover process.

1. A 6LoWPAN node should be reachable by another 6LoWPAN node or a global network node even when it is moving from one attachment point to another,
2. The smart building in this work is clinic, hospital, nursing home, etc. to provide smart control of indoor environmental systems like patients that is served with WSNs. This technology enables doctors and patients to connect remotely and share information through wireless tools,
3. Each domain is a LoWPAN area with a short transmission distance between MNNs for mobile network and BRs,
4. In this scenario a mobile network with attached body sensors are set up to monitor the vital measurement. Using portable monitoring systems based on WSNs makes it possible to get an efficient medical service and provides freedom for patients,
5. All MNNs, especially MR are of type full-function device (FFDs). The FDD type nodes support full functions like managing handover process and capable of operating as a PAN coordinator,
6. Even though security is important for the mobility management in wireless networks to protect the patient's information, it is not considered in this thesis since HWSN6 has already supported it. On the other hand, the other 6LoWPAN research issue such as security concern is out of the scope of this thesis.

1.5 Research Contributions

Hence, the main contributions of this thesis can be summarized as follows:

- **An improved handover process in NEMO, to achieve objective 1:** The NEMO protocol provides basic network mobility functionality on MIPv6 protocol. This contribution results in a higher efficiency and reduces signalling cost compared with host mobility. By way of a logical extension of the HWSN6 operation at the MR, this proposed protocol avoids reconfiguring IP addresses to minimize MR's overload, the handover signalling cost inside the network and handover signalling delay, respectively.

- **A message-scheduling algorithm for tunnelling process, to achieve objective 2:** The route optimization is proposed in the tunnelling process of mobility management. It considers message scheduling from MNNs after binding update (BU) is completed. By way of this solution, efficient data transmission to minimize MR overload can be maintained, and this tends to improve performance metrics like end-to-end packet delay and packet loss.
- **An implementation of the selective optimal MR algorithm to achieve objective 3:** This is an energy solution based on energy-balancing to improve energy saving of MR in NEMO. It searches for an MNN with the largest energy reserves when the MR residual energy drops below the certain threshold to replace it with the new selected MNN.
- **A simulation model to design, test, simulate, and analyze the proposed scheme:** Throughout the simulation, a 6LoWPAN adaptation layer has been developed by using Contiki in OMNeT++ simulator. This contribution is important to provide a 6LoWPAN simulation platform in OMNeT++ for the proposed network mobility protocol and future 6LoWPAN-related works. With this simulator, the behaviors and characteristic of the protocol can be studied without the need to build a real network. Various parameters were set according to the purpose of the simulation to observe the network response.
- **Analytical model:** This work was validated by using the MIPv6 for our proposed scheme. The performance metrics like tunnelling costs is investigated.

1.6 Thesis Organization

This thesis is organized into five chapters as follows:

The first chapter presents the research topic as a background of mobility and highlight the research problem, research motivations, set the objectives, define the scope and limitations, and describes the thesis organization.

The second chapter presents a review of the literature on and around 6LoWPAN. The mobility protocols and architecture are briefly described. Most of the relevant previous works have been critically reviewed and their strengths points and limitations are highlighted.

The third chapter describes the research methodology which explains the proposed scheme in detail for efficient NEMO mobility management to achieve the research objectives and analytical model.

Chapter 4 presents the results and discussions on the evaluation of the mobility protocol against the design parameters, and the results in order to show an efficient mobility management. The performance of the proposed scheme is evaluated and compared with other works in handover signalling cost, handover delay, end-to-end packet delay, packet loss, and energy consumption.

Finally, the last chapter summarizes and highlights the thesis based on the results presented in this thesis. The key points of thesis and contributions of all proposed schemes are summarized. This gives some recommendations for future research in this area.



REFERENCES

- Airehrour, D., Gutierrez, J., and Ray, S. K. (2016). Secure routing for internet of things: A survey. *Journal of Network and Computer Application*, 66: 198-213
- Akyildiz, I. F., and Vuran, M. C. (2010). *Wireless sensor networks*. JohnWiley and Sons Ltd.
- Albarakati, A. J., Qayyum, J., and Fakee, K., A (2014). A Survey on 6LowPAN and its Future Research Challenges. *IJCSCMC*, 3(10),558-570
- Al-Surmi, I., Othman, M., and Mohd Ali, B. (2012). Mobility management for IP-based next generation mobile networks: Review, challenge and perspective. *Journal of Network and Computer Applications*, 35(1): 295–315.
- Angadi, R. V., and Shet, K. C. (2013). QoS Based Handover Technique for Network Based Network Mobility (N-NEMO). *International Journal of Computer Science and Network Security*, 13(7): 34-41
- Ashton, K. (2009). That ‘internet of things’ thing. *RFiD Journal*, 22(7), 97-114.
- Babulal, K. S. (2013). Link Distance Link Cost Link Error Based Energy Efficient Cross Layer Reliable Routing for Wireless Sensor Network. *International Journal of Computer Information Systems and Industrial Management Applications*, 5: 437–444.
- Bag, G., Mukhtar, H., Shams, S. M. S., Kim, K. H., and Yoo, S. (2008a). Inter-PAN Mobility Support for 6LoWPAN. In *2008 Third International Conference on Convergence and Hybrid Information Technology*. Busan, South Korea: 787–792.
- Bag, G., Raza, M. T., Kim, K.-H., and Yoo, S.-W. (2009a). LoWMob: Intra-PAN Mobility Support Schemes for 6LoWPAN. *Sensors* (Basel, Switzerland), 9(7): 5844–5877.
- Bag, G., Raza, M. T., Mukhtar, H., Akbar, A. H., Shams, S. M. S., Kim, K.-H., Yoo, S., and Kim, D. (2008b). Energy-aware and bandwidth-efficient mobility architecture for 6LoWPAN. In *MILCOM 2008 - 2008 IEEE Military Communications Conference*. San Diego, CA, United States, IEEE: 1-7.

- Bag, G., Shams, S. M. S., Akhbar, A. H., M, M. T. R. H., Kim, K., and Yoo, S. (2009b). Network Assisted Mobility Support for 6LoWPAN. In *Consumer Communications and Networking Conference, 2009. 6th IEEE*: 1–5.
- Bhunia, S. S., Roy, S., and Mukherjee, N. (2013). Mobility of IP based Wireless Sensor Nodes in Sensor-Grid infrastructure. *International Journal on Smart Sensing and Intelligent Systems*, 6(5): 2075–2102.
- Bouaziz, M., and Rachedi, A. (2013). A Survey on Mobility and Mobility-Aware MAC Protocols in Wireless Sensor Networks. *IEEE Communications Surveys Tutorials*, 15(1): 88–100.
- Bouaziz, M., and Rachedi, A. (2014). A Survey on Mobility Management Protocols in Wireless Sensor Networks baseb on 6LoWPAN technology. *IEEE Computer Communications*, 74(2016): 3–15.
- Bui, N., Bressan, N., and Zorzi, M. (2012). Interconnection of body area networks to a communications infrastructure: An architectural study. In *European Wireless, 2012. EW. 18th European Wireless Conference*: 1-8.
- Caldeira, J. M. L., Rodrigues, J. J. P., and Lorenz, P. (2013). Intra-Mobility Support Solutions for Healthcare Wireless Sensor Networks–Handover Issues. *IEEE Sensors Journal*, 13(11): 4339-4348.
- Campos, B. da S., Rodrigues, J. J. P. C., Mendes, L. D. P., Nakamura, E. F., Maur', C., and Figueiredo, icio S. (2011). Design and Construction of Wireless Sensor Network Gateway with IPv4 / IPv6 Support. In *Communications (ICC), 2011 IEEE International Conference on. IEEE*: 1–5.
- Chai, R., Zhao, Y. L., Chen, Q. Bin, Dong, T., and Zhou, W. G. (2010). Group mobility in 6LoWPAN-based WSN. In *2010 International Conference on Wireless Communications and Signal Processing*: 1–5.
- Chellani, G., and Kalla, A. (2013). A Review: Study of Handover Performance in Mobile IP. *International Journal of Computer Networks and Communications*, 5(6): 137–151.
- Chen, F., Wang, N., German, R., and Dressler, F. (2008). Performance Evaluation of IEEE 802.15.4 LR-WPAN for Industrial Applications. In *Wireless on Demand Network Systems and Services, Fifth Annual Conference*, IEEE: 89–96.

- Chen, J. (2014). Energy-saving mechanism design for 6LoWPAN wireless sensor network. *Computer Modeling and New Technologies*, 18(12B): 603-609.
- Chen, Y. S., Hsu, C. S., and Lee, H. K. (2014). An enhanced group mobility protocol for 6LoWPAN-based wireless body area networks. *IEEE Sensors Journal*, 14(3): 797-807.
- Choi, J., Ahmed, B., and Gutierrez-Osuna, R. (2012). Development and evaluation of an ambulatory stress monitor based on wearable sensors. *IEEE transactions on information technology in biomedicine*, 16(2): 279-286.
- Chuang, M.-C., and Lee, J.-F. (2011). FH-PMIPv6: A fast handoff scheme in Proxy Mobile IPv6 networks. In *2011 International Conference on Consumer Electronics, Communications and Networks (CECNet)*: 1297-1300.
- Chun, S. M., Kim, H. S., and Park, J. T.(2015). CoAp-based mobility management for the Internet of Things. *Sensors*, 15(7): 16060-16082.
- Culler, D. (2007) Secure, low-power, IP-based connectivity with IEEE 802.15.4 wireless networks. *Industrial Embedded Systems*: 1-4.
- Darwish, A., and Hassanien, A. E. (2011). Wearable and implantable wireless sensor network solutions for healthcare monitoring. In *Sensors, Special Issue on Bioinspired Sensor Systems, MDPI*, 11(6): 5561-5595.
- Devarapalli, V., Wakikawa, R., Petrescu, A., and Thubert, P. (2005). Network Mobility (NEMO) Basic Support Protocol. Internet Engineering Task Force, RFC 3963.
- Diab, A, Mitschele-Thiel, A., Xu, J. (2004) Performance analysis of the mobile ip fast authentication protocol. In *Proceedings of the 7th ACM International Symposium on Modeling, Analysis and Simulation of Wireless and Mobile Systems, MSWiM '04, ACM*, New York, NY, USA: 297-300.
- Dinakaran, M., and Balasubramanie, P. (2010). A Route Optimization Technique for LFN-CN in NEMO. *Journal of Computing*, 2(5): 70-77.
- Ding, J., Balasingham, I., and Bouvry, P. (2011). Management Challenges for Emerging Wireless Networks. *Emerging Wireless Networks: Concepts, Techniques and Applications*: 3-34.

- Ee, G. K., Ng, C. K., Noordin, N. K., and Ali, B. M. (2010). A Review of 6LoWPAN Routing Protocols. In *Proceedings of the Asia-Pacific Advanced Network*, 30: 71–81.
- Ergen, S. C., and Varaiya, P. (2005). On multi-hop routing for energy efficiency. *IEEE Communications Letters*, 9(10): 880-881.
- Fletcher, R. R., Tam, S., Omojola, O., Redemske, R., and Kwan, J. (2011, August). Wearable sensor platform and mobile application for use in cognitive behavioral therapy for drug addiction and PTSD. In *2011 Annual International Conference of the IEEE Engineering in Medicine and Biology Society*: 1802-1805.
- Forster, A., Puccinelli, D., and Giordano, S. (2011). Sensor node lifetime: An experimental study. In *2011 IEEE International Conference on Pervasive Computing and Communications Workshops (PERCOM Workshops)*: 202–207.
- Fotouhi, H., Alves, M., Koubaa, A., and Baccour, N. (2010). On a reliable handoff procedure for supporting mobility in wireless sensor networks. In *the 9th international workshop on real-time networks (RTN 2010) in conjunction with the 22nd euromicro international conference on real-timesystems (ECRTS 2010)*, Brussels, Belgium: 6–9.
- George, L. K., Blazer, D. G., Hughes, D. C., and Fowler, N. (1989). Social support and the outcome of major depression. *The British Journal of Psychiatry*, 154(4): 478-485.
- Gershenfeld, N., Krikorian, R., and Cohen, D. (2004). The Internet of things. *Scientific American*, 291(4): 76–81.
- Ghasemzadeh, H., Jafari, R., and Prabhakaran, B. (2010). A body sensor network with electromyogram and inertial sensors: multimodal interpretation of muscular activities. *IEEE transactions on information technology in biomedicine*, 14(2): 198-206.
- Goswami, S., Das, C. B., and Joardar, S. (2013). A Survey on various Route Optimization Techniques for Internet Applications in Network Mobility (NEMO). *International Journal of Wireless Communication*, 5(12): 441-452
- Gundavelli, S., Leung, K., Devarapalli, V., Chowdhury, K., Patil, B. (August 2008). Proxy mobile ipv6. Internet Engineering Task Force, RFC 5213.

- Ha, M., Kim, D., Kim, S. H., and Hong, S. (2010). Inter-MARIO: A Fast and Seamless Mobility Protocol to Support Inter-Pan Handover in 6LoWPAN. In *2010 IEEE Global Telecommunications Conference GLOBECOM 2010*. New York, USA: 1-6.
- Han, D., Chung, J. M., and Garcia, R. C. (2012). Energy efficient wireless sensor networks based on 6LoWPAN and virtual MIMO technology. In *Circuits and Systems (MWSCAS), 2012 IEEE 55th International Midwest Symposium on*. Boise, ID, USA: 849-852.
- Haenggi, M. (2004). Twelve reasons not to route over many short hops. In Conference, 2004. VTC2004-Fall. 2004 IEEE 60th: pp. 3130–3134.
- Hager, R., Klemets, A., Maguire, G. Q., Smith, M. T., and Reichert, F. (1993). MINT - A Mobile Internet Router. In *Vehicular Technology Conference*: 18–21.
- Halapeti, P., and Patil, S. (2014). Healthcare Monitoring System Using Wireless Sensor Networks. *International Journal of Advanced Research in Computer Science and Technology (IJARCST 2014)*, 2(2): 443–446.
- Himabindu, G. B., Vedhagrani, A. M., Raj, K. S. R. (2014). Performance Evaluation of mobility management using mobile IPv4 and mobile IPv6 protocols. *International Journal of Computer Science and Technologies*, 5(5):6286-6289.
- Hoey, T. K., Sinniah, G. R., Khoshdelniat, R., Abdullah, A., and Subramaniam, S. (2012). Mobility management schemes and mobility issues in low power Wireless Sensor Network. In *Telecommunication Technologies (ISTT), 2012 International Symposium on*, IEEE: 65-70.
- Hu, J. Y., Chou, C. F., Sha, M. S., Chang, C., and Lai, C. Y. (2007, December). On the design of micro-mobility for mobile network. In *International Conference on Embedded and Ubiquitous Computing*, Springer Berlin Heidelberg: 401-412.
- Hui, J. W., and Culler, D. E. (2008). Extending IP to Low-Power, Wireless Personal Area Networks. *Internet Computing, IEEE*, 12(4): 37–45.
- Hui, J., W. and Culler, D. E. (2009). 6LoWPAN: *Incorporating IEEE 802.15.4 into the IP architecture*: 1–17.
- Hui, J. W., and Culler, D. E. (2010). IPv6 in Low-Power Wireless Networks. *Proceedings of the IEEE*, 98(11): 1865–1878.

Hwang, S. M., Kim, K. J., Islam, M. M., Huh, E. N., Huang, W., Foo, V., and Biswas, J. (2010, June). Multi-modal sensing smart spaces embedded with WSN based image camera. In *Proceedings of the 3rd International Conference on Pervasive Technologies Related to Assistive Environments*, ACM, No.63.

IEEE Computer Society. (2007). IEEE Standard for Part 15.4 : Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (WPANs), IEEE Standard 802.15.4.

INET Framework. (2015). Retrieved from <http://www.inet.omnetpp.org>

INETMANET Framework. (2015). Retrieved from <https://github.com/aarizaq/inetmanet-2.0>

Islam, M. M., Hassan, M. M., and Huh, E. N. (2010, December). Sensor proxy mobile IPv6 (SPMIPv6)-a framework of mobility supported IP-WSN. In *Computer and Information Technology (ICCIT), 2010 13th International Conference, IEEE*:295-299.

Islam, M. M., and Huh, E.-N. (2011). Sensor proxy mobile IPv6 (SPMIPv6)--a novel scheme for mobility supported IP-WSNs. *Sensors 2011* (Basel, Switzerland), 11(2): 1865–87.

Jabir, A. J., Subramaniam, S. K., Ahmad, Z. Z., and Hamid, N. A. W. A. (2012). A cluster-based proxy mobile IPv6 for IP-WSNs. *EURASIP Journal on Wireless Communications and Networking*, 2012(1): 1–17.

Jara, A. J., Fernandez, D., Lopez, P., Zamora, M. A., and Skarmeta, A. F. (2013a). Lightweight mobile IPv6: A mobility protocol for enabling transparent IPv6 mobility in the internet of things. In *2013 IEEE Global Communications Conference (GLOBECOM)*: 2791-2797.

Jara, A. J., Ladid, L., and and Skarmeta, A. F. G. (2013b). The Internet of Everything through IPv6: An Analysis of Challenges, Solutions and Opportunities. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications*, 4(3): 97-118

Jara, A. J., Silva, R. M., Silva, J. S., Zamora, M. a., and Skarmeta, A. F. G. (2011). Mobile IP-Based Protocol for Wireless Personal Area Networks in Critical Environments. *Wireless Personal Communications*, 61(4): 711–737.

- Jara, A. J., Zamora, M. a., and Skarmeta, A. F. G. (2009). HWSN6: Hospital Wireless Sensor Networks Based on 6LoWPAN Technology: Mobility and Fault Tolerance Management. In *International Conference on Computational Science and Engineering*. Vancouver, BC, Canada: 879-884.
- Jara, A. J., Zamora, M. A., and Skarmeta, A. F. G. (2010a). An Initial Approach to Support Mobility in Hospital Wireless Sensor Networks based on 6LoWPAN (HWSN6). *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications*, 1(2/3): 107–122
- Jara, A. J., Zamora, M. A., and Skarmeta, A. F. G. (2010b). Intra-mobility for Hospital Wireless Sensor Networks based on 6LoWPAN. In *2010 Sixth International Conference on Wireless and Mobile Communications*: 389–394.
- Jebaseeli Samuelraj, A., and Jayapal, S. (2015). Efficient Mobility Management Signalling in Network Mobility Supported PMIPV6. *The Scientific World Journal*, 2015.
- Johnson, D., and Perkins, C. (2004). Mobility Support in IPv6. RFC 3775.
- Johnson, D., Perkins, C., and Arkko, J. (2011). Mobility Support in IPv6. RFC 6275.
- Khan, R. A., and Mir, A. H. (2014a). A Study of Network Based Mobility Management Schemes, 6LoWPAN Mobility. Open Issues and Proposed Solutions. *arXiv Preprint arXiv:1408.2632*, 1–45
- Khan, R., and Mir, A. (2014b). Sensor fast proxy mobile IPv6 (SFPMPv6)-A framework for mobility supported IP-WSN for improving QoS and building IoT. In *Communications and Signal Processing (ICCSP), 2014 International Conference on. IEEE*: 1593–1598.
- Kim, J., Haw, R., Cho, E. J., Hong, C. S., and Lee, S. (2012). A 6LoWPAN sensor node mobility scheme based on proxy mobile IPv6. *IEEE Transactions on Mobile Computing*, 11(12): 2060-2072.
- Kim, J. H., Hong, C. S., and Okamura, K. (2007). A Routing Scheme for Supporting Network-Mobility of Sensor Network Based on 6LoWPAN. *APNOMS 2007, Springer-Verlag Berlin Heidelberg, LNCS4773*: 155–164.

- Kim, J. H., Hong, C. S., and Shon, T. (2008). A Lightweight NEMO Protocol to Support 6LoWPAN. *ERTI Journal*, 30(5): 685–695
- Kirsche, M., and Hartwig, J. (2013). Poster Abstract: A 6LoWPAN Model for OMNeT++. In *Proceedings of the Sixth International Conference on Simulation Tools and Techniques*. 3–6.
- Kirsche, M., and Schnurbusch, M. (2014). A New IEEE 802.15.4 Simulation Model for OMNeT++ / INET. arXiv:1409.1177v2. Networking and Internet Architecture.
- Kong, K., Song, M., Park, K., and HWANG, C.-S. (2006). A Comparative Analysis on the Signalling Load of Mobile IPv6 and Hierarchical Mobile IPv6 : Analytical Approach. *IEICE TRANS. INF. and SYST.*, E89-D(1): 139–149.
- Koodli, R. (2005). Fast handovers for mobile IPv6. In RFC 4068.
- Kumar, V., and Tiwari, S. (2012). Routing in IPv6 over Low-Power Wireless Personal Area Networks (6LoWPAN): A Survey. *Journal of Computer Networks and Communications*, 2012: 1–10.
- Lee, H. B., Han, Y. H., and Min, S. G. (2010). Network mobility support scheme on PMIPv6 networks. *International Journal of Computer Networks and Communications (IJCNC)*, 2(5): 206-213.
- Li, J., and Mohapatra, P. (2007). Analytical modeling and mitigation techniques for the energy hole problem in sensor networks. *Pervasive and Mobile Computing*, 3(3): 233-254.
- Lin, H., and Labiod, H. (2007, July). Hybrid handover optimization for multiple mobile routers-based multihomed NEMO networks. In *IEEE International Conference on Pervasive Services*:136-144.
- Leung, K., Dommety, G., Narayanan, V., and Petrescu, A. (2008). Network mobility (NEMO) extensions for Mobile IPv4. In RFC 5177.
- Lmberis, A., and Dittmar, A. (2007). Advanced wearable health systems and applications-Research and development efforts in the European Union. *IEEE Engineering in Medicine and Biology Magazine*, 26(3): 29-33.

- Mehmood, W., Hassan, A., Tabish, R., Touati, F., Mnaouer, A. B., and Gaabab, B. (2014). Performance evaluation of 6LoWPAN based networks for ubiquitous health monitoring system. In *Proceedings of the International Conference on Wireless Networks (ICWN)*.
- Mekkaoui, K., and Rahmoun, A. (2011). Short-hops vs. Long-hops - Energy efficiency analysis in Wireless Sensor Networks. In *CIIA*.
- MiXiM Modeling Framework. (2015). Retrieved from <http://mixim.sourceforge.net/>
- Moceri, P. (2006). Enabling Network Mobility : A Survey of NEMO. In Washington University Engineering in St. Louis: 3–6.
- Montavont, J., Roth, D., and Noël, T. (2014). Mobile IPv6 in Internet of Things: Analysis, experimentations and optimizations. *Ad Hoc Networks*, 14: 15–25.
- Mosa, A. A., Abdalla, A. H., and Saeed, R. A. (2012). Evaluation of MANEMO route optimization schemes. *Journal of Network and Computer Applications*, 35(5): 1454–1472.
- Neves, P. A. C. S., Stachyra, M., and Rodrigues, J. (2008). Application of wireless sensor networks to healthcare promotion. *Journal of Communications Software and Systems*, 181-190.
- Nikolidakis, S., Kandris, D., Vergados, D., and Douligeris, C. (2013). Energy Efficient Routing in Wireless Sensor Networks Through Balanced Clustering. *Algorithms 2013*, 6(1): 29–42.
- Oliveira, L. M. L., Sousa, A. F. De, and Rodrigues, J. J. P. C. (2011). Routing and mobility approaches in IPv6 over LoWPAN mesh networks. *International Journal of Communication Systems*, 11(24): 1445–1466.
- OMNeT++ Simulator. (2015). Retrieved from <http://www.omnetpp.org>
- Osterlind, F., Dunkels, A., Eriksson, J., Finne, N., and Voigt, T. (2006). Cross-level sensor network simulation with cooja. In *Local Computer Networks, Proceedings 2006 31st IEEE Conference*: 641–648.
- Pantazis, N. A., and Vergados, D. D. (2007). A survey on power control issues in wireless sensor networks. *IEEE Communications Surveys and Tutorials*, 9(4): 86-107.

- Pantelopoulos, A., and Bourbakis, N. G. (2010). A survey on wearable sensor-based systems for health monitoring and prognosis. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 40(1):1-12.
- Perera, E., Sivaraman, V., and Seneviratne, A. (2004). Survey on Network Mobility Support. *ACM SIGMOBILE Mobile Computing and Communications Review*, 8(2): 7–19.
- Perkins, C. (2002). Ip mobility support for ipv4. Internet Engineering Task Force, RFC 3344.
- Petander, H., Perera, E., Kun-Chan, L., and Seneviratne, A. (2006). Measuring and Improving the Performance of Network Mobility Management in IPv6 Networks. *IEEE Journal on Selected Areas in Communications*, 24(9): 1–11.
- Riegel, M., Xie, Q., Tuexen, M. (2007). Mobile sctp, draft-riegeltuexen-mobile-sctp-09.tx, Internet-Draft, 2007.
- Rodriguez-Sanchez, M. C., Borromeo, S., and Hernández-Tamames, J. A. (2011). Wireless sensor networks for conservation and monitoring cultural assets. *IEEE Sensors Journal*, 11(6): 1382-1389.
- Saha, D., Mukherjee, A., Misra, I. S., and Chakraborty, M. (2004). Mobility Support in IP: A Survey of Related Protocols. *IEEE Network*, 18(6): 34–40.
- Shahriar, A. Z. M., Atiquzzaman, M., Member, S., and Ivancic, W. (2010). Route Optimization in Network Mobility: Solutions, directions, comparison, and future research directions. *Communications Surveys and Tutorials, IEEE 2010*, 12(1): 24–38.
- Shelby, Z., and Borman, C. (2009). 6LoWPAN: the wireless embedded internet. John Wiley and Sons, Ltd.
- Shelby, Z., and Borman, C. (2011). The wireless embedded Internet. John Wiley and Sons, Ltd.
- Shen, X., Kato, N., and Lin, X. (2010). Wireless technologies for e-healthcare. *IEEE Wireless Communications*, 17(1): 10-11.

- Shu, L., Niu, J., Hara, T., Hauswirth, M., and Nishio, S. (2011). Integrating weather information with body sensor networks for health monitoring. In *Proceedings of the 6th International Conference on Body Area Networks*, Beijing, China, November 7-8, 2011: 130-131
- Shin, M., and Kim, H. (2009). L3 Mobility Support in Large-scale IP-based Sensor Networks (6LoWPAN). *Advanced Communication Technology*, 2009. IEEE, 2: 941-945.
- Silva, R., Sa Silva, J., and Boavida, F. (2014). Mobility in wireless sensor networks - Survey and proposal. *Computer Communications*, 52: 1-20.
- Singh, D., Tiwary, U. S., Lee, H., and Chung, W. (2009). Global Healthcare Monitoring System using 6lowpan Networks. In *ICACT 2009*: 113-117.
- Sinniah, G. R., Suryady, Z., Sarwar, U., and Hoey, T. K. (2013). Node Mobility Scheme for IP and Non-IP Wireless Personal Area Network Nodes using 6LoWPAN. In *SENSORCOMM 2013: The Seventh International Conference on Sensor Technologies and Applications*: 83-89.
- Soliman, H., Castelluccia, C., Malki, K. El, and Bellier, L. (2005). Hierarchical MIPv6 Mobility Management. In RFC 4140.
- Teo, K. H., Subramaniam, Sh., and Sinniah, G. R. (2015). Node Mobility Support Between Multi-hop 6LoWPAN Networks Based on Proxy Mobile IPv6. *Wireless Personal Communications journal*, 85(3): 959-986.
- Udugama, A., Iqbal, M. U., Toseef, U., Goerg, C., Fan, C., and Schlaeger, M. (2009, April). Evaluation of a network based mobility management protocol: PMIPv6. In *Vehicular Technology Conference, 2009. VTC Spring 2009*. IEEE 69th: 1-5.
- Wang, J., Yang, X., Zheng, Y., Zhang, J., and Kim, J. (2012). An Energy-Efficient Multi-hop Hierarchical Routing Protocol for Wireless Sensor Networks. *International Journal of Future Generation Communication and Networking*, 5(4): 89-98.
- Wang, X., and Qian, H. (2012a). Constructing a 6LoWPAN Wireless Sensor Network Based on a Cluster Tree. *IEEE Transactions on Vehicular Technology*, 61(3): 1398-1405.

- Wang, X., Zhong, S., and Zhou, R. (2012b). A mobility support scheme for 6LoWPAN. *Computer Communications*, 35(3): 392–404.
- Wang, X., Le, D., and Cheng, H. (2015). Mobility Management for 6LoWPAN Wireless Sensor Networks in Critical Environments. *International Journal of Wireless Information Networks*. 22(1):41–52
- Wang, X., and Cheng, H. (2016). Research on seamless mobility handover for 6LoWPAN wireless sensor networks. *Telecommunication Systems*, 61(1): 141–157.
- Xue, F., Li, Y., Bao, S., Yin, C., and Cao, C. (2012). Healthcare Delivery with IP-Based Sensor Networks. In *Biomedical and Health Informatics (BHI), IEEE-EMBS International Conference*. 25, China: 792–794.
- Yi, D., and Yang, H. (2016). HEER—A delay-aware and energy-efficient routing protocol for wireless sensor networks. *Computer Networks*, 104(2016): 155–173.
- Yick, J., Mukherjee, B., and Ghosal, D. (2008). Wireless sensor network survey. *Computer Networks*, 52(12): 2292–2330.
- Yin, B., Shi, H., and Shang, Y. (2005). A two-level strategy for topology control in wireless sensor networks. In *Proceedings of the 11th International Conference on Parallel and Distributed Systems - Workshops (ICPADS05), IEEE Computer Society*. Washington, DC, USA: 358–362
- Yousaf, F. Zarrar and Bauer, Christian and Wietfeld, C. (2008). An Accurate and Extensible Mobile IPv6 (xMIPv6) Simulation Model for OMNeT++. In *Proceedings of the 1st international conference on Simulation tools and techniques for communications, networks and systems and workshops. ICST (Institute for Computer Sciences, Social-Informatics and Telecommunications Engineering)*, Marseille.
- Zinonos, Z., and Vassiliou, V. (2010). Inter-mobility support in controlled 6LoWPAN networks. In *2010 IEEE Globecom Workshops*: 1718–1723.

LIST OF PUBLICATIONS

- Mohammadreza Sahebi Shahamabadi, Borhanuddin B. M. Ali, Nor Kamariah bt. Noordin, Mohd Fadlee b. A Rased, Pooria Varahram, Antonio J. Jara. (2014). A NEMO-HWSN Solution to Support 6LoWPAN NETWORK Mobility in Hospital Wireless Sensor Network. *Computer Science and Information System Journal*, 11(3): 943-960, (ISI, IF: 0.64, Q3).
- Mohammadreza Sahebi Shahamabadi, Borhanuddin B. M. Ali, Nor Kamariah Binti Noordin, Mohd Fadlee b. A Rased, Antonio J. Jara.(2017). The Analysis of NEMO for 6LoWPAN Mobile Networks in Hospital Environments. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications (JoWUA)*. (Accepted).
- Mohammadreza Sahebi Shahamabadi, Borhanuddin B. M. Ali, Nor Kamariah Noordin, Mohd Fadlee b. A Rased, Antonio J. Jara. (2016). The Challenges of NEMO in 6LoWPAN Smart Building Area. *2016 International Conference on Identification, Information and Knowledge in the Internet of Things (IIKI 2016). 20-21 October 2016 in Beijing, China*. [Indexed by IEEE].
- Mohammadreza Sahebi Shahamabadi, Borhanuddin Bin Mohd Ali, Pooria Varahram, Mahda Noura. (2013). On Power Consumption in IPv6 Over Low Power Wireless Personal Area Network (6LoWPAN). *The First International Conference on Green Computing, Technology and Innovation (ICGCTI2013), Malaysia*: pp. 21-28,
- Mohammadreza Sahebi Shahamabadi, Borhanuddin Bin Mohd Ali, Pooria Varahram, Antonio J. Jara. (2013). A Network Mobility Solution Based on 6LoWPAN Hospital Wireless Sensor Network (NEMO-HWSN). *2013 Seventh International Conference on Innovative Mobile and Internet Services in Ubiquitous Computing (IMIS-2013). Taichung, Taiwan*: pp. 433-438 [Indexed by IEEE].



UNIVERSITI PUTRA MALAYSIA

STATUS CONFIRMATION FOR THESIS / PROJECT REPORT AND COPYRIGHT

ACADEMIC SESSION : _____

TITLE OF THESIS / PROJECT REPORT :

AN EFFICIENT NETWORK MOBILITY MANAGEMENT FOR A 6LoWPAN MOBILE NETWORK IN HOSPITAL ENVIRONMENTS

NAME OF STUDENT: MOHAMMADREZA SAHEBI SHAHAMABADI

I acknowledge that the copyright and other intellectual property in the thesis/project report belonged to Universiti Putra Malaysia and I agree to allow this thesis/project report to be placed at the library under the following terms:

1. This thesis/project report is the property of Universiti Putra Malaysia.
2. The library of Universiti Putra Malaysia has the right to make copies for educational purposes only.
3. The library of Universiti Putra Malaysia is allowed to make copies of this thesis for academic exchange.

I declare that this thesis is classified as :

*Please tick (v)

CONFIDENTIAL

(Contain confidential information under Official Secret Act 1972).

RESTRICTED

(Contains restricted information as specified by the organization/institution where research was done).

OPEN ACCESS

I agree that my thesis/project report to be published as hard copy or online open access.

This thesis is submitted for :

PATENT

Embargo from _____ until _____
(date) (date)

Approved by:

(Signature of Student)
New IC No/ Passport No.:

Date :

(Signature of Chairman of Supervisory Committee)
Name:

Date :

[Note : If the thesis is **CONFIDENTIAL** or **RESTRICTED**, please attach with the letter from the organization/institution with period and reasons for confidentially or restricted.]