



UNIVERSITI PUTRA MALAYSIA

***EFFICIENT NODE COOPERATION STIMULATION MECHANISM IN
WIRELESS MULTIHOP NETWORKS***

NORMALIA BINTI SAMIAN

FSKTM 2018 13



**EFFICIENT NODE COOPERATION STIMULATION MECHANISM IN
WIRELESS MULTIHOP NETWORKS**

By

NORMALIA BINTI SAMIAN

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of Doctor of Philosophy**

December 2017

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial uses of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright ©Universiti Putra Malaysia



DEDICATIONS

*I dedicate this thesis to my beloved **children** with the hope that all of you will hold stronger endurance and perseverance in order to accomplish greater success than what your mother has achieved...*



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirements for the degree of Doctor of Philosophy

EFFICIENT NODE COOPERATION STIMULATION MECHANISM IN WIRELESS MULTIHOP NETWORKS

By

NORMALIA BINTI SAMIAN

December 2017

Chairman : Zuriati Ahmad Zukarnain, PhD
Faculty : Computer Science and Information Technology

In an autonomous environment of wireless multihop networks, like wireless ad hoc and sensor networks, nodes need to cooperate with one another to relay information effectively across the network. However, due to limited resources especially energy, nodes may be compelled to adopt selfish behaviour by not participating in forwarding packets for other nodes. Most, if not all, existing works on cooperation stimulation approaches assumed that this behaviour can be detected but do not explicitly describe how selfishness is actually quantified which leads to inaccurate behaviour judgment. This scenario may be worsened by false accusation issues induced by group of colluding nodes which might cheat in evaluating node behaviour during global/second-hand observation process, for their own communication gains in the network. In addition, cooperation of nodes is hampered by the lack of efficient scheme that is able to stimulate node cooperation effectively to achieve optimum communication rate in the network.

This thesis proposes a mechanism named Compare and Measure Selfishness Detection (CMSD) to evaluate node behaviour more accurately and promptly by adopting quantification elements such as correlation co-efficient tool that are able to classify node into several selfishness/cooperativeness and fairness types. Based on simulation results, CMSD mechanism is able to provide more accurate and prompt behaviour information and increase network performance in term of low false positive and high packet delivery ratio.

Moving further, this study proposes a mechanism that can avoid false recommendation and illegitimate node collusion during global observation. The mechanism is called Trust Features-based Evidence (TFE) which is developed based on significant and unique trust features to ensure that the reported information is of actual behaviour of an observed

node. Assisted by an efficient cross-checking algorithm on several cheating and colluding cases, TFE mechanism is able to reduce the number of cheating nodes over time and the rate of illegitimate collusion as proven in the simulation results.

Ultimately, a hybrid cooperation stimulation scheme named Recharge-As-Reward (RAR) and Credit-As-Reward (CAR) which functions as an explicit reward (i.e. in the form of token/flag) for cooperative nodes has been proposed in this study. Combining good features in reputation-based and credit-based mechanisms, this hybrid scheme is able to reduce the message/communication overheads suffered by many of existing hybrid schemes by reducing the reliance on a central agent. Performance evaluations demonstrate that the proposed mechanisms are able to reduce the number of dropped packets, increase nodes' forwarding ratio and reduce message and communication overhead.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Doktor Falsafah

MEKANISMA RANGSANGAN KERJASAMA NOD YANG EFEKTIF DALAM RANGKAIAN TANPA WAYAR BERBILANG HOP

Oleh

NORMALIA BINTI SAMIAN

Disember 2017

Pengerusi : Zuriati Ahmad Zukarnain, PhD
Fakulti : Sains Komputer dan Teknologi Maklumat

Dalam persekitaran rangkaian multihop tanpa wayar berautonomi seperti rangkaian ad hoc tanpa wayar dan rangkaian sensor, nod perlu bekerjasama antara satu sama lain untuk menghantar data secara berkesan ke seluruh rangkaian. Walau bagaimanapun, disebabkan sumber yang terhad terutamanya tenaga, nod bermungkinan untuk mementingkan diri sendiri dengan tidak membantu menghantar paket untuk nod lain. Kebanyakan, jika tidak semua, mekanisme cadangan sedia ada mengandaikan bahawa bahawa sikap mementingkan diri dapat dikesan, tetapi tidak menjelaskan dengan nyata bagaimana sikap tersebut diukur secara kuantitatif yang mengakibatkan penilaian menjadi tidak tepat. Senario ini boleh diburukkan lagi oleh isu tuduhan palsu oleh nod-nod yang bersubahat yang mungkin menipu dalam menilai tingkah laku nod yang dinilai semasa proses pemerhatian global/tidak langsung demi kemaslahatan komunikasi mereka sendiri di dalam rangkaian. Di samping itu, kerjasama daripada nod terjejas akibat kekurangan skim yang efektif untuk merangsang kerjasama nod dengan berkesan untuk mencapai kadar optimum komunikasi di dalam rangkaian.

Tesis ini mencadangkan satu mekanisme yang dipanggil Banding dan Ukur Pengesanan Mementingkan Diri (CMSD) untuk menilai tingkah laku nod dengan lebih tepat dan segera menggunakan elemen kuantifikasi seperti kaedah korelasi koefisien yang dapat mengklasifikasikan nod kepada beberapa kategori sikap mementingkan diri/kerjasama dan keadilan. Berdasarkan keputusan simulasi, mekanisme CMSD dapat memberikan maklumat tentang sikap nod dengan lebih tepat dan cepat, serta meningkatkan prestasi rangkaian dari segi kadar rendah positif palsu dan kadar penghantaran paket yang tinggi.

Seterusnya, tesis ini mencadangkan satu mekanisme yang boleh mengelakkan rekomendasi palsu dan persubahatan nod yang tidak sah semasa pemerhatian global. Mekanisma ini dikenali sebagai Bukti Berasaskan Ciri-ciri Percaya (TFE) yang dibangunkan berdasarkan ciri-ciri percaya yang signifikan dan unik bagi memastikan bahawa maklumat yang dilaporkan adalah kelakuan sebenar nod yang diperhatikan. Dibantu oleh algoritma silang-semak yang efisien terhadap beberapa kes penipuan dan persubahatan, mekanisme TFE dapat mengurangkan jumlah penipuan nod dan kadar persubahatan yang tidak sah seperti terbukti dalam keputusan simulasi.

Kemuncaknya, sebuah skim rangsangan kerjasama hibrid bernama Mengecas Sebagai Ganjaran (RAR) dan Kredit Sebagai Ganjaran (CAR) yang berfungsi sebagai ganjaran nyata (dalam bentuk token/bendera) untuk nod yang bekerjasama telah dicadangkan dalam kajian ini. Menggabungkan ciri-ciri yang baik dalam mekanisme berasaskan reputasi dan berasaskan kredit, skim hibrid ini bertujuan untuk mengurangkan overhead mesej dan komunikasi yang dialami oleh kebanyakan skim hibrid sedia ada dengan mengurangkan pergantungan terhadap ejen sentral. Penilaian prestasi menunjukkan bahawa mekanisme yang dicadangkan dapat mengurangkan jumlah paket tercicir, meningkatkan kadar penghantaran nod dan mengurangkan overhead mesej dan komunikasi.

ACKNOWLEDGEMENTS

Alhamdulillah... Praise be to Allah S.W.T for giving me the guidance and strength to complete my Ph.D thesis throughout the roller-coaster journey.

First of all, I would like to express my appreciation to my UPM supervisors, Assoc. Prof. Dr. Zuriati Ahmad Zukarnain, Dr. Azizol Abdullah and Assoc. Prof. Dr. Zurina Mohd Hanapi for their precious support and encouragement throughout the course of this research study till I found light at the end of the tunnel. Against all odds, to my external supervisor from VUW, Prof. Dr. Winston K. G. Seah, I thank you more than words can say for your endless commitment that inspires me to become a better researcher. I look forward to working with you in future and having much more interesting challenges ahead.

I am in debt with my wonderful parents; Samian Sawiyo and Masnah Jamin, and my siblings; Hariz, Haizad and Atiqah, who have always been supporting and sacrificing for me in all possible angles. Wonderful thanks to my family in-law in Sabah who have been so supportive and understanding despite of the long distance we are apart. Not to forget to all my close friends who have always been the best listeners and support me in struggling with my battle. Thank you dear friends, you know who you are.

A special appreciation goes to my husband, Muhammad Daniel Hafiz Abdullah who has been going through many hurdles and challenges together with me in this journey to complete our PhD studies. Finally, both of us have reached the finishing line (I made it first though ヽ_(ツ)_/).

Ultimately, my appreciation goes to my lovely and cheeky children, Nur Qystina and Adam Uqayl. Both of you are the main reasons why your parents are still standing strong.

~ NS ~

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABLES	xiv
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xv
 CHAPTER	
1 INTRODUCTION	1
1.1 Introduction	1
1.2 Background and Motivation	2
1.3 Problem Statement	4
1.4 Research Objectives	5
1.5 Research Scopes	6
1.6 Research Contributions	7
1.7 Structure of Thesis	9
 2 LITERATURE REVIEW	11
2.1 Introduction	11
2.2 State of the Art of Wireless Multihop Networks	13
2.2.1 Full Cooperation	13
2.2.2 Partial/Zero Cooperation	15
2.3 Cooperation Stimulation Mechanisms in Wireless Multihop Networks	15
2.3.1 Incentive-based Mechanism	15
2.3.1.1 Credit Payment Scheme	16
2.3.1.2 Reputation Scheme	19
2.3.1.3 Hybrid Scheme	24
2.3.2 Punishment-based Mechanism	26
2.4 Using Game Theory to Model and Analyze Cooperation Stimulation Mechanisms	27
2.5 Structure and Components of Cooperation Stimulation Mechanisms	31
2.5.1 Monitoring Mechanism	31
2.5.1.1 Passive Acknowledgment	32
2.5.1.2 Active Acknowledgment	33
2.5.1.3 Specification-based Approach	36
2.5.1.4 Game Theory of Perfect/Imperfect Public/Private Monitoring	36

2.5.2	Node Behaviour Judgment	40
2.5.2.1	Local vs. Global Information	40
2.5.2.2	Monitored Behaviour	41
2.5.3	Information Broadcast	41
2.5.4	Comparative Analysis	42
2.6	Highlighted Issues	48
2.6.1	False Judgment	48
2.6.2	Node Collusion	50
2.6.3	Accuracy	50
2.6.4	Scalability	51
2.6.5	Security	51
2.6.6	Application	51
2.7	Summary	52
3	RESEARCH METHODOLOGY	53
3.1	Introduction	53
3.2	Methodology Framework	53
3.3	First Phase – Research Problem Formulation	54
3.3.1	Literature Survey	55
3.3.2	Identification of Unaddressed Issues	55
3.4	Second Phase – Design and Development	56
3.4.1	Development of Existing Scheme for Benchmarking	56
3.4.2	Design of Proposed Mechanisms and Algorithms	57
3.5	Third Phase – Implementation and Analysis	58
3.5.1	Implementation on Routing Protocol	58
3.5.2	Simulation-based Experiment	59
3.5.2.1	Overall OMNeT++ Framework	60
3.5.2.2	Validation of Results	61
3.5.3	Network Topology	62
3.5.4	Performance Metrics	63
3.5.4.1	Selfishness and Fairness Metrics	63
3.5.4.2	3.5.4.2 Accuracy and Promptness	64
3.5.4.3	False Positive, False Negative and True Detection	64
3.5.4.4	Sustainable Level toward Selfishness	64
3.5.5	Network Performance:	65
3.6	Summary	65
4	COMPARE AND MEASURE SELFISHNESS DETECTION (CMSD) MECHANISM FOR PROMPT AND ACCURATE NODE BEHAVIOUR EVALUATION	66
4.1	Introduction	66
4.2	Quantification of a Node's Effort in Packet Forwarding	67
4.2.1	Single Set of Actions (SSA) Technique	67
4.2.2	Quantifiable Metrics Based on E-Model	68
4.3	Compare and Measure Selfishness Detection (CMSD) Mechanism	69
4.3.1	Framework of CMSD Mechanism	70
4.3.2	Collection of Behaviour Information	72

4.3.3	Measuring Selfishness and Fairness	75
4.3.3.1	Rate of data packets forwarded by a relay node	76
4.3.3.2	Correlation coefficient of rate of data packets transmitted	77
4.3.3.3	The Proposed Selfishness and Fairness Metrics	78
4.4	CMSD vs. SSA (Quantifiable Metrics vs. Finite Form)	79
4.4.1	Behavioural Information Dissemination	79
4.4.2	Matrix of Judgment	82
4.5	Performance Evaluation	83
4.5.1	Analysis of CMSD in Classifying Node Behaviour Types	84
4.5.1.1	Amount of Traffic Introduced Has No Variations	85
4.5.1.2	New traffic Introduced Creates Randomness	87
4.5.1.3	Incomplete Information and Random Rate of Traffic	88
4.5.2	Analysis of CMSD in Providing Promptness and Accuracy	90
4.5.2.1	Evaluation on Time Taken to Perform Quantification	90
4.5.2.2	The Promptness of CMSD	93
4.5.2.3	The Accuracy of CMSD (Matrix of Judgment)	94
4.5.3	Analysis of CMSD Compared to SSA on ICARUS Scheme	98
4.5.3.1	False Positive Evaluation	99
4.5.3.2	Packet Delivery Ratio	101
4.6	Summary	102
5	TRUST FEATURES-BASED EVIDENCE (TFE) SCHEME TO MITIGATE FALSE RECOMMENDATION AND NODE COLLUSION	103
5.1	Introduction	103
5.2	Framework of The Trust Features-based Evidence (TFE) Scheme	105
5.3	The Proposed Recommendation Policy	107
5.4	Trust Features Formulation	107
5.4.1	Assessment of Recommender Node, IDV and Its Shared Information	108
5.4.2	Assessment of Recommended Node, IDR	111
5.5	Cheating and Node Collusion Detection	111
5.6	Performance Evaluation	115
5.6.1	Simulation Settings	115
5.6.2	Trust Values Assignment	116
5.6.3	Detection Accuracy	117
5.6.4	5.6.4 Network Performance	121
5.7	Summary	123
6	RECHARGE-AS-REWARD (RAR) AND CREDIT-AS-REWARD (CAR) MECHANISMS TO INCENTIVIZE COOPERATIVE NODES	125
6.1	Introduction	125

6.2	Communication Model	126
6.3	Node Behaviour Model	127
6.4	Selfishness Detection	127
6.5	The RAR and CAR Mechanisms	128
6.5.1	General Architecture	128
6.5.2	Recharge as Reward (RAR)	129
6.5.3	Credit as Reward (CAR)	131
6.5.4	Paying Node with RAR/CAR to Stimulate Cooperation	133
6.6	Performance Evaluation	134
6.6.1	Analysis of RAR Mechanism in Helping Node under Stress	135
6.6.2	Analysis of RAR Mechanism in Reducing Dropped Packets	136
6.6.3	Analysis of RAR and CAR in Sustaining Node's Lifetime	137
6.6.4	RAR/CAR Mechanisms Compared with ICARUS	140
6.6.4.1	Cooperation Stimulation	140
6.6.4.2	Overhead Analysis	141
6.7	Summary	142
7	CONCLUSION AND FUTURE WORKS	144
7.1	Conclusion	144
7.2	Future Works	146
	REFERENCES	147
	APPENDIX	159
	BIODATA OF STUDENT	160
	LIST OF PUBLICATIONS	161

LIST OF TABLES

Table		Page
2.1	Game theoretical approaches	28
2.2	Local Observation vs. Global Observation	40
2.3	Comparative Analysis	43
4.1	Cooperativeness level	79
4.2	Selfishness and fairness metrics	79
4.3	Classical Weightage Schemes VS CMSD Mechanism	82
4.4	Fairness Substitution Metrics	83
4.5	Simulation Parameters	84
5.1	Ideal Reports	112
5.2	Case Description	114
5.3	Sample Case	114
5.4	Simulation Parameters	115

LIST OF FIGURES

Figure	Page
1.1 Structure and Components of Cooperation Stimulation Mechanism	3
2.1 State of The Art of Wireless Multihop Networks	12
2.2 Classification of Cooperation Stimulation Components	16
2.3 The Circulating Problem of False Judgment based on SSA	49
3.1 Methodology Framework	54
3.2 Overall OMNeT++ Framework	61
3.3 Simulation Validation Comparison	62
3.4 Network Topology	63
4.1 SSA Operation	68
4.2 General Framework of CMSD	70
4.3 CMSD Operation	71
4.4 CMSD Operation (<i>zoomed in</i>)	72
4.5 Two Flows Scenario Where Source Nodes are Within the Same Wireless Transmission Range (<i>scenario one</i>)	73
4.6 Two Flows Scenario Where Source Nodes Are Not within the Same Wireless Transmission Range (<i>scenario two</i>)	74
4.7 Various potential epochs of CMSD's timing diagram	75
4.8 Behavioural Information Dissemination in Finite Form Based on SSA	80
4.9 Behavioural information dissemination in quantifiable metrics based on CMSD	81
4.10 Fairly Cooperative Node	85

4.11	Unfairly Cooperative Node	86
4.12	Fairly Uncooperative Node (Fairly Selfish Node)	87
4.13	Unfairly Cooperative Node (Random Send Rate)	88
4.14	Unfairly Cooperative Node (Incomplete Information)	89
4.15	CMSD versus SSA for Fairly Cooperative Node	91
4.16	CMSD versus SSA for Unfairly Cooperative Node	92
4.17	CMSD versus SSA for Unfairly Cooperative Node (Contrary Bias)	92
4.18	CMSD versus SSA for Fairly Selfish Node	93
4.19	Effect of Collecting Behavioural History by SSA (case in Figure 4.16)	94
4.20	12 Nodes Topology	95
4.21	Matrix of Judgment Based on SSA	96
4.22	Matrix of Judgment Based on CMSD	97
4.23	False Positive Rate	100
4.24	Packet Delivery Ratio	101
5.1	Framework of Trust Features-based Evidence Scheme	105
5.2	Packet Format	107
5.3	Recommendation Validation	111
5.4	Cheating and Node Collusion Detection	113
5.5	Trust Value Assignment	117
5.6	False Positive Rate	118
5.7	False Negative Rate	119
5.8	True Detection Rate	120

5.9	Detection Rate of Cases	121
5.10	Packet Delivery Ratio	122
5.11	Average Detection Delay	123
6.1	Communication Model	126
6.2	Architecture of RAR and CAR	129
6.3	RAR Mechanism	130
6.4	CAR Mechanism	132
6.5	20-node Network Topology (similarly, but more random for 50-node)	134
6.6	Number of Detected Selfish Nodes in the Network	136
6.7	Number of Dropped Packets in AODV with RAR	137
6.8	Collection of RAR / CAR / VCAR with Selfish Nodes	139
6.9	Number of Online Nodes	140
6.10	Packet Forwarding Ratio	141
6.11	Message/Communication Overhead	142

LIST OF ABBREVIATIONS

ACK	Acknowledgment
AODV	Ad hoc On-Demand Distance Vector
CA	Central Agent
CAR	Credit-As-Reward
CC	Cooperative Communication
CCS	Credit Clearance Service
CMSD	Compare and Measure Selfishness Detection
CPS	Credit Payment Scheme
CRP	Cooperative Routing Protocol
DP	Dynamic Programming
DSR	Dynamic Source Routing
FSC	Feasible Solution Construction
FSM	Finite State Machine
HS	Hybrid Scheme
ID	Identity
IETF	Internet Engineering Task Force
IoT	Internet of Things
LRI	Local Routing Instance
MAC	Medium Access Control
MANET	Mobile Ad hoc Network
NE	Nash Equilibrium
ORA	Optimal Relay Assignment
OSI	Open Systems Interconnection
PDR	Packet Delivery Ratio
PPM	Packet Purse Model
PTM	Packet Trade Model
RAR	Recharge-As-Reward
RREP	Route Reply
RREQ	Route Request
RRER	Route Error

RS	Reputation Scheme
SC	Settlement Centre
SSA	Single Set of Action
SDN	Software Defined Networking
TFE	Trust Features-based Evidence
TFT	Tit-for-Tat
TTP	Trusted Third Party
VANET	Vehicular Ad hoc Network
VoIP	Voice over IP
WBTFT	Worst Behavior Tit-for-Tat
WMN	Wireless Mesh Network
WSN	Wireless Sensor Network

CHAPTER 1

INTRODUCTION

1.1 Introduction

Wireless multihop networks consist of autonomous nodes that perform network tasks in a self-organizing manner. The networks which fall under infrastructure-less category includes several class of networks such as wireless sensor network (WSN) (Yick *et al.*, 2008) , mobile ad hoc network (MANET) (Macker & Corson, 1998), wireless mesh network (WMN) (Akyildiz & Wang, 2005), and vehicular ad hoc network (Sharef *et al.*, 2014) (VANET). As they are infrastructure-less, there is no central controller or wired backbone to handle the communication process. Therefore, the nodes in these networks have to act as routers and hosts simultaneously and utilize hop-by-hop packet transmission. Consequently, with these processes occurring in the network, high frequency of communication among peer nodes is expected. Examples of applications utilizing wireless multihop networks for data transmission exist in military battlefield, catastrophe recovery, event monitoring sites, vehicular ad hoc technology system, health monitoring services and many other civilian applications.

As applications based on wireless multihop networks have evolved rapidly, much attention has been given to address issues that may affect the performance of such networks. These include issues related to resource constraint, security, cooperation and connectivity where the main concern is to ensure that data can be efficiently transmitted across the networks to reach intended recipient. In the case where packets that need to be transmitted are between nodes within direct wireless transmission range, a successful rate of data transmission is assured if connectivity is good. However, when the source and destination nodes are beyond direct wireless transmission range of each other, the source node has to rely on relay nodes or intermediaries to help forward the packets towards intended destination node.

When dealing with relay nodes in wireless multihop networks, the issue of uncooperative forwarding behaviour will most likely occur because each node has different motivations and intentions. The intentions are very subjective and may result in good, selfish or malicious behaviours. Ideally, if each node shows a good behaviour by cooperatively relaying packets from other nodes, an optimum network performance can be achieved. However, such assumption is not valid in the real environment of wireless multihop networks where nodes are autonomous and most importantly, have resource constraints. With these characteristics, nodes are compelled to preserve their own energy to sustain in the network, which is why cooperative relaying is difficult to achieve.

This behaviour is known as selfishness and can exist in any node, affecting topology design and network operations like routing and packet forwarding. The level of selfishness can be very abstract, making it difficult to measure and quantify because unlike a node with malicious intent, selfishness may be shown intermittently depending on the network scenarios that it needs to handle. For example, if a node is handling heavy forwarding loads due to its location being the closest to a particular hectic destination, it may decide to favour certain requesting nodes or drop any incoming packets that arrive after certain forwarding periods to avoid excessive energy depletion. From the energy conservation principle, such behaviour is reasonable for a node's own benefits but if it is done excessively and unfairly, the final effect towards the network may be the same as those by malicious nodes.

In contrast to malicious nodes which intentionally plan to disrupt network services through harmful attacks, selfish nodes do not mean to harm the network. However, the effect of selfishness may eventually cause network disruption if all nodes decide to be self-centered by not forwarding packets for other nodes. Although selfishness can be classified as a type of malicious behaviour, it may not be effectively overcome with security approaches. Generally, security approaches are often implemented using cryptographic-based mechanism in order to thwart bad nodes from the network such as in (Zhong & Wu, 2010). Although this kind of security mechanism may work well in reducing selfishness, it has high computational overheads and is not a suitable countermeasure for selfish nodes, which are not as malignant as malicious nodes. Hence, cooperation mechanisms have been introduced to solve the problem of selfishness by detecting nodes that show uncooperative behaviour and provide a means to discourage selfishness (i.e. stimulate cooperativeness) using either incentive-based or punishment-based mechanisms. Hence, the main goal of this research is to investigate and identify voids and gaps in existing cooperation approaches for wireless multihop networks and proposes new mechanisms/schemes to solve the identified issues/problems pertaining to node selfishness.

1.2 Background and Motivation

Node selfishness issue has become one of major focus research problems in wireless multihop networks which have been widely addressed with the proposal of cooperation stimulation mechanisms/schemes in many relevant existing works. Nonetheless, there are several challenges in developing an efficient cooperation stimulation mechanism/scheme. This can be viewed from general structure and components of cooperation stimulation schemes that are still requiring efficiency enhancement. In general, cooperation stimulation scheme consists of five major components as has been summarized in Figure 1.1. Detailed explanation about this structure is discussed in Chapter 2 (cf. Section 2.5).




Figure 1.1 : Structure and Components of Cooperation Stimulation Mechanism

Starting from the most basic element which is on the detection and evaluation of node behaviour, choosing the suitable (if not optimal) monitoring mechanism for accurate behaviour detection can be investigated and improved in several different angles. This element itself has already opened up tremendous amount of research study especially on determining accurate node behaviour using several monitoring tools in order to detect selfish node correctly prior to enforcing subsequent actions. Several monitoring mechanisms that are based on four major techniques as shown in Figure 2.2 (cf. Section 2.3) have been proposed. Nonetheless, the proposed approaches impose some similar weaknesses such as inaccuracy of behaviour information, delay in collecting sufficient information, and false judgment which open up rooms for improvement.

The study can be further expanded throughout upper layers' components of cooperation stimulation mechanisms' structure specifically on the utilization of the node behaviour information obtained towards achieving the final effect i.e. optimal node cooperation. However, having multiple layers also means that there are multiple issues may arouse. These have been discussed in many existing works such as and among other popular issues which remain open research problems to be addressed are on node collusion in falsely praise/accuse other nodes, flooding overhead during information sharing with neighbourhood nodes, inefficient punishment mechanisms, high communication and storage overhead for assessing node behaviour.

The aforementioned issues have become major motivations to be investigated and addressed in this research whereby details of literature survey related to this research field are discussed in Chapter 2.

1.3 Problem Statement

In cooperation stimulation mechanism research, the key challenge in designing an efficient scheme is the ability to answer as to whether or not the proposed scheme is able to stimulate node cooperation effectively by reducing (if not fully thwarting) selfish behaviour and thus, improve network performance. By means of effective scheme, this does not come without imposing trade-offs in implementing the scheme such as high communication and message overheads, undetected selfish nodes, and inaccurate node behaviour judgment, etc. In this thesis, based on rigorous study on the cooperation mechanism elements in Figure 1.1, three major problems in cooperation stimulation mechanisms been identified as follows:

1. Inaccurate measurement of behaviour information based on local observation

Detecting node behaviour accurately during local observation is crucial as having wrong evaluation on a particular node behaviour will most likely impose negative consequences towards the observed node itself and the network performance as a whole. Hence, it is very important for any observer node to perform an accurate first-hand/local observation process prior to sharing the information so that false judgment can be reduced (if not totally avoided). However, there is a lack of accurate and prompt measurement on node behaviour during local observation in existing works whereby selfishness is assumed detected, but did not explicitly describe how selfishness is actually measured. Hence, there is a need to provide a quantification method that is able to measure a node's behaviour more accurately in a quicker manner.

2. Node collusion in falsely accusing/praising node during global observation

The behaviour information obtained from first-hand/local observation may be shared with other nodes upon requested. The process of getting other nodes' opinions about a particular node's behaviour is known as a second-hand/global observation, which forms a global report to rate the reputation level of a particular node via voting system that is formed by group of nodes in proximity. This is where information might be tampered with false accusation by a group of colluding nodes which might simply lie to manipulate the network for their own benefits. In many existing works such issue is handled by relying on a central agent to aggregate behaviour information from as many other nodes as possible. Although this approach helps in reducing false accusation, but, the communication overhead is high and still susceptible to large number of colluding lying nodes. Having said that, such schemes are actually lacking of efficient distributive methods to assure that the information shared is genuine before being counted as a vote. Thus, the authenticity of the nodes and their corresponding shared information need to be validated by an efficient mechanism to ensure that the shared information is hard to be falsified.

3. Inefficient scheme to stimulate node cooperation in wireless multihop networks

A cooperation stimulation scheme can be generally classified as reputation-based, credit-based or hybrid-based (combination of reputation and credit) scheme. As depicted in Table 2.3 (cf. Section 2.5.4), each type of scheme possesses pros and cons criteria that need to be carefully considered during the design process. For reputation scheme, the voting system component motivates node to be persistent in cooperative mode as its behaviour is continuously being assessed by neighbouring nodes. Nonetheless, it comes with several drawbacks such as susceptibility to large numbers of cheaters that leads to false accusation, the possible need of long behavioural assessment to ensure up-to-date information and high communication overhead. Credit-based scheme was introduced to overcome the overhead imposed by reputation scheme during behaviour observation and assessment which could take long time. By having virtual credit as remuneration for being cooperative and loss of credit as an implicit punishment for being selfish, the highly resources consumption to perform behaviour observation and evaluation can be avoided. However, issues like undetected selfish node, communication bottleneck when dealing with central agent and unfairness of credit distribution do occur in credit-based scheme and remain open research problems to be addressed. As a result, hybrid of reputation-based and credit-based schemes has been introduced whereby the good aspects of both schemes are combined into creating a more efficient scheme. But, it also comes with dis-advantageous especially on the tendency to have very high communication and processing overhead due to the hybrid features, which have become the focus issues to be addressed in this thesis.

Overall, the research presented in this thesis will help answer the following main research questions:

1. How to quantify a node's effort in forwarding packet for other nodes in order to accurately determine its level of cooperativeness or selfishness?
2. How to assure the authenticity of node behaviour information that is shared across the network such that cheating actions can be reduced?
3. How to develop an efficient scheme that is able to stimulate node cooperation effectively so that optimum communication rate in wireless multihop network can be achieved at reasonable communication/message overheads?

1.4 Research Objectives

The main goal of this research is to develop an efficient scheme that is able to stimulate cooperation among nodes in wireless multihop networks so that optimal communication rate can be achieved. Efficiency-wise, the proposed scheme should be able to identify node behaviour more accurately and promptly, broadcast the behaviour information genuinely at a reduced cheating rate to avoid false judgment, punish selfish node more efficiently such that eventually every node realizes that being cooperative is the best way to sustain in the network and ultimately, successfully stimulate node cooperation to

improve network performance. In order to achieve the main goal, the following objectives have been identified:

- 1) To devise a mechanism that is able to quantify and classify node behaviour accurately and promptly during first-hand/local observation process using suitable measurement method and statistical tool to increase packet delivery ratio and thus, improving network performance.
- 2) To design a mechanism that can avoid node collusion during second-hand/global observation using relevant trust features such that the authenticity of the broadcast behaviour information can be assured and cheating rate can be reduced to decrease and increase packet forwarding ratio of selfish nodes and cooperative nodes respectively.
- 3) To develop an effective hybrid cooperation stimulation scheme combining good features in reputation-based and credit-based mechanisms by proposing an alternative explicit reward other than just rewarding using reputation level for the earlier and reducing node reliance on central agent to manage credit transactions for the latter, to reduce message/communication overhead and increase forwarding ratio of nodes.

1.5 Research Scopes

The scopes of this research are as follows:

1. The network considered is ad hoc networks in which nodes require multi-hop transmissions to send and forward packets for each other.
2. This research focused on network layer whereby selfish behaviour of a node in forwarding packets for other nodes has been investigated.
3. Only nodes with selfish behaviour are considered in this research, whereas, nodes with malicious intent aiming to purposely attack the network are out of the scope.
4. All proposed schemes in this research are built onto the Ad hoc On-Demand Distance Vector (AODV) routing protocol. AODV is an on-demand (reactive) routing protocol which finds a route only when needed and requires a node to only have information of its neighbours. The ability of our schemes to work with such limited network information make them more scalable, and can be extended to other routing protocols such as Dynamic Source Routing (DSR) that provide more information, albeit, incurring overheads. On other node, a reactive protocol has been chosen over proactive routing protocol such as Optimized Link State Routing (OLSR) and Destination Sequence Distance Vector (DSDV) due to the unnecessary of constant propagation of routing information in the network which can lead to high routing traffic overheads.

1.6 Research Contributions

The main contributions of this thesis are as follows:

1. Accurate and prompt measurement of node forwarding behaviour

Current approaches on evaluating node behaviour based on local observation rely mainly on single set of action (SSA) approach. SSA is a condition of when a node observes another node's forwarding effort towards its own requests while at the same time disregarding that node's effort towards other nodes' requests. This scenario leads to inaccurate judgment and would require conducting another round of observations or acquiring global observation reports from other nodes to verify the behaviour information, which inducing delay. The research in this thesis addresses the issues with the proposal of a quantification mechanism that is based on correlation coefficient that could measure levels of forwarding effort (cooperativeness or selfishness) and fairness imposed by a relay node based on their speed of packet forwarding for more than one node at the same time. The proposed quantification method which is named Compare and Measure Selfishness Detection (CMSD) is aiming to provide (1) a metrics to quantify selfishness based on nodes' effort to forward data packets for corresponding requesting nodes; (2) application of the (selfishness) metrics to evaluate a node's fairness in forwarding packets for different requestors; and (3) a more accurate and prompt classification of different types of selfish/cooperative behaviour. Based on simulation results, the implementation of CMSD mechanism has able to provide more accurate and prompt behaviour information and increase the network performance in term of low false positive and high packet delivery ratio.

2. A filtering mechanism to reduce false recommendation and avoid node collusion

In evaluating a node's cooperativeness/selfishness behaviour, global reports from other nodes in MANET may be required to strengthen the judgment made using local observation. However, it cannot be assumed that a node is always honest in sharing the behaviour information. A group of nodes might collude to falsely accuse/praise a particular node to gain communication benefits at the cost of other nodes' resources. This paper proposes a filtering mechanism named Trust Features-based Evidence (TFE) by formulating evidence that is based on trust features to reduce the number of liar nodes and thus, ensuring the authenticity of the shared information. Assisted by an efficient punishment element, TFE mechanism is able to reduce the number of cheating nodes over time and the rate of illegitimate collusion, by having detected cheaters aware that the only way to survive in the network is by presenting genuine information.

3. A new type of reward mechanism for reputation scheme

In reputation scheme, assigning good reputation level alone does not provide strong motivation either for node to remain cooperative or to stimulate selfish node to become cooperative. Thus, in this research, an explicit reward other than just providing reputation level incentive for nodes has been proposed to strengthen motivation for nodes to cooperate. The proposed reward is known as Recharge-As-Reward (RAR) and works by giving a cooperative node a recharge session which is represented in the form of token/flag every time a node has reached a particular forwarding threshold value. This would allow cooperative nodes to recuperate without being labelled as selfish, thus avoiding unnecessary punishment. Significant achievement of proposing this type of instant reward mechanism is that nodes can maintain longer operational lifetime in the network without having to wait for too long for their rewards to be verified and approved, which may degrade motivation to cooperate.

4. A hybrid cooperation scheme with less message/communication overheads

Hybrid of reputation-based and credit-based schemes has been proposed to improve the efficiency in mitigating selfishness by adopting the pros sides of both schemes. However, implementing hybrid scheme is commonly at the cost of high communication/message overhead mainly due to (1) wide-broadcast of packets to collect and evaluate reputation level of a node, and (2) high traffic due to node-to-node and node-to-central agent (CA) communications. This thesis addresses the overhead issues in hybrid scheme with the proposal of a Credit-As-Reward (CAR) mechanism that is combined with RAR mechanism to create the hybrid feature. From the credit-based element, significant difference in our proposed scheme compared to other existing hybrid schemes is that nodes are stimulated to being less reliant to the CA although its usage to process credit transaction is retained, which also signifies that credit provision is not a mandatory reward for cooperative nodes. This is done with the help of RAR mechanism whereby if the amount of RAR flags collected is enough to sustain nodes lifetime in the network, credit transaction is not necessary be done. This is also apply for the case of when credit processing fails to complete due to factors like observer node is reluctant to submit report on other nodes' forwarding information to the CA, which has mostly been neglected in existing schemes. The idea is that, nodes need not rely on credit reward only as RAR works as an alternative to reduce reliance on CA, thus reducing communication/message overheads. Through a comparison with another hybrid scheme, it has been shown that the proposed hybrid scheme in this research is able to detect selfish nodes and reward cooperative nodes more efficiently while reducing reliance on a central agent to reduce message/communication overhead.

1.7 Structure of Thesis

The outcome of this research is documented and organized into a thesis of seven chapters as follows:

Chapter 1 overviews the main motivation in conducting research in cooperation stimulation for wireless multihop networks and generally guides readers on what to anticipate from this thesis. This is done by discussing the research problems identified through rigorous literature survey which derives the objectives to address the issues within specified scopes of research. Summary of all proposed contributions is also discussed at the end of this chapter.

Chapter 2 discusses the literature survey that has been done for this research by reviewing existing related works on selfishness mitigation cum cooperativeness stimulation in wireless multihop networks. Based on the rigorous survey which includes performing comparative analysis, issues and problems related to cooperation in wireless multihop network are highlighted and potential gaps that need to be fulfilled are identified.

Chapter 3 describes the research methodology applied for this research which is illustrated in a general framework. The methodology framework explains the overall steps that involved in this research based on several phases which were carried out consecutively but may be repeated when necessary. There are three main phases which have involved in this research; namely analysis, theoretical design and validation. Discussions on the simulation tool used and the routing protocol chosen as platform to simulate all proposed contributions are also done in this chapter.

Chapter 4 introduces a new mechanism to quantify a node's forwarding effort during local observation named Compare and Measure Selfishness Detection (CMSD) scheme. The discussion covers the steps that have involved in the quantification method's design and its applications to classify a node's behaviour based on its forwarding effort. This chapter also discusses the efficiency of CMSD to work under several network scenarios and its strength in improving network performance.

Chapter 5 presents a filtering mechanism to prevent illegitimate node collusion and cheating behaviour during global/indirect observation whereby information about particular node behaviour is shared across the network upon requested by certain nodes. The proposed mechanism named Trust Features-based Evidence (TFE) is developed based on significant and unique trust features which are effective to thwart cheating behaviour of nodes to ensure that the reported information is of actual behaviour of an observed node.

Chapter 6 presents the final contribution for this thesis which is the development of a hybrid cooperation scheme which consists of a combination of reputation-based and credit-based schemes. The explanation is mainly divided into two parts whereby the first part focuses on proposed enhancement for reputation scheme using RAR scheme, and the second part discusses on CAR scheme which is an enhancement of credit-based scheme.

Chapter 7 concludes this thesis by highlighting all contributions and discussing some potential future works.



REFERENCES

- Abolhasan, M., Lipman, J., Ni, W., & Hagelstein, B. (2015). Software-defined wireless networking: centralized, distributed, or hybrid? *IEEE Network*, 29(4), 32–38.
- Ahmed, A., Bakar, K. A., Channa, M. I., Haseeb, K., & Khan, A. W. (2016). A trust aware routing protocol for energy constrained wireless sensor network. *Telecommunication Systems*, 61(1), 123–140.
- Akkarajitsakul, K., Hossain, E., Niyato, D., & Kim, D. I. (2011). Game Theoretic Approaches for Multiple Access in Wireless Networks: A Survey. *IEEE Communications Surveys & Tutorials*, 13(3), 372–395.
- Akyildiz, I. F., & Wang, X. (2005). A survey on wireless mesh networks. *IEEE Communications Magazine*, 43(9), 23–30.
- Anderegg, L., & Eidenbenz, S. (2003, 14–19 September). *Adhoc-VCG: A Truthful and Cost-efficient Routing Protocol for Mobile Adhoc Networks with Selfish Agents*. Paper presented at the Proceedings of The 9th International Conference on Mobile Computing and Networking (MobiCom), San Diego, CA.
- Aoyagi, M. (2002). Collusion in Dynamic Bertrand Oligopoly with Correlated Private Signals and Communication. *Journal of Economic Theory*, 102(1), 229–248.
- Arboit, G., Crepeau, C., Davis, C. R., & Maheswaran, M. (2008). A Localized Certificate Revocation Scheme for Mobile Ad Hoc Networks. *Ad Hoc Networks*, 6(1), 17–31.
- Awerbuch, B., Holmer, D., Nita-Rotaru, C., & Rubens, H. (2012, 28September). *An On-demand Secure Routing Protocol Resilient to Byzantine Failures*. Paper presented at the Proceedings of the ACM Workshop on Wireless Security (WiSE), Atlanta, GA, USA.
- Balakrishnan, K., Deng, J., & Varshney, P. K. (2005, 13–17 March). *TWOACK: Preventing Selfishness in Mobile Ad Hoc Networks*. Paper presented at the Proceedings of the IEEE Wireless Communications and Networking Conference (WCNC), New Orleans, LA, USA.
- Bansal, S., & Baker, M. (2003). Observation-based Cooperation Enforcement in Ad Hoc Networks *Technical Reportcs NI/0307012*. Stanford, California, USA: Computer Science Department, Stanford University.
- Bhaskar, V., & Eric, V. D. (2002). Moral Hazard and Private Monitoring. *Journal of Economic Theory*, 102(1), 16–39.

- Buchegger, S., & Boudec, J.-Y. L. (2002, 9-11 June). *Performance Analysis of the CONFIDANT Protocol*. Paper presented at the Proceedings of the 3rd ACM International Symposium on Mobile Ad hoc Networking and Computing (MOBIHOC), Lausanne, Switzerland.
- Buchegger, S., & LeBoudec, J.-Y. (2003, 3-5 March). *The Effect of Rumor Spreading in Reputation Systems for Mobile Ad Hoc Networks*. Paper presented at the Proceedings of the Workshop on Modeling and Optimization in Mobile, Ad hoc and Wireless Networks (WiOpt), INRIA Sophia-Antipolis, France.
- Buttayan, L., & Hubaux, J.-P. (2000). *Enforcing Service Availability in Mobile Adhoc WANS*. Paper presented at the Proceedings of the 1st IEEE/ACM Workshop on Mobile and Adhoc Networking and Computing (MobiHOC), Boston, MA.
- Buttayan, L., & Hubaux, J.-P. (2001). Nuglets: A Virtual Currency to Stimulate Cooperation in Self-organized Mobile Ad hoc Networks *Technical Report DSC/2001/001*. Lausanne, Switzerland.: Swiss Federal Institute of Technology.
- Buttayan, L., & Hubaux, J.-P. (2002). Stimulating Cooperation in Self-organizing Mobile Ad Hoc Networks. *Mobile Networks and Applications*, 8(15), 579-592.
- Charilas, D. E., Georgilakis, K. D., & Panagopoulos, A. D. (2012). ICARUS: hybrid incentive mechanism for cooperation stimulation in ad hoc networks. *Ad Hoc Networks*, 10(6), 976-989. doi: 10.1016/j.adhoc.2011.12.010
- Charilas, D. E., & Panagopoulos, A. D. (2010). A Survey on Game Theory Applications in Wireless Networks. *Computer Networks*, 54(18), 3421-3430.
- Chen, I.-R., Bao, F., & Guo, J. (2016a). Trust-Based Service Management for Social Internet of Things Systems. *IEEE Transaction on Dependable and Secure Computing*, 13(6), 684-696.
- Chen, I.-R., Guo, J., & Bao, F. (2016b). Trust Management for SOA-Based IoT and Its Application to Service Composition. *IEEE Transaction On Services Computing*, 9(3), 482-495.
- Cheng, L., Cao, J., Chen, C., Chen, H., Ma, J., & Siebert, J. I. (2010, 28 June - 2 July). *Cooperative Contention-Based Forwarding for Wireless Sensor Networks*. Paper presented at the Proceedings of the 6th International Wireless Communications and Mobile Computing Conference (IWCMC), Caen, France.
- Cho, J.-H., Swami, A., & Chen, I.-R. (2012). Modeling and Analysis of Trust Management with Trust Chain Optimization in Mobile Ad Hoc Networks. *Journal of Network and Computer Applications*, 35(3), 1001-1012.

- Cho, J. H., Swami, A., & Chen, I. R. (Fourth Quarter 2011). A Survey on Trust Management for Mobile Ad Hoc Networks. *IEEE Communications Surveys & Tutorials*, 13(4), 562-583.
- Chong, Z.-K., Tan, S.-W., Goi, B.-M., & Ng, B. C.-K. (2012). Outwitting Smart Selfish Nodes in Wireless Mesh Networks. *International Journal of Communication Systems*, 1163-1175. doi: 10.1002/dac.1388
- Cole, R. G., & Rosenbluth, J. H. (2001). Voice over IP Performance Monitoring. *ACM SIGCOMM Computer Communication Review*, 31(2), 9-24.
- Compte, O. (1998). Communication in Repeated Games with Imperfect Private Monitoring. *Econometrica*, 66(3), 597-626.
- Compte, O. (2002). On Failing to Cooperate when Monitoring is Private. *Journal of Economic Theory*, 102(1), 151-188.
- Conti, M., Gregori, E., & Maselli, G. (2003, 23-25 September). *Towards Reliable Forwarding for Ad Hoc Networks*. Paper presented at the Proceedings of The Personal Wireless Communications (PWC), Venice, Italy.
- Dewan, P., Dasgupta, P., & Bhattacharya, A. (2004, 7-9 July). *On using Reputations in Ad Hoc Networks to Counter Malicious Nodes*. Paper presented at the Proceedings of the 10th International Conference on Parallel and Distributed Systems (ICPADS), Newport Beach, CA, USA.
- E-Model. (Dec. 1998). The E-model: A Computational Model for Use in Transmission Planning *ITU-T Recommendation G.107*.
- Eidenbenz, S., Resta, G., & Santi, P. (2005, 3-8 April). *COMMIT: A Sender-centric, Truthful and Energy-efficient Routing Protocol for Ad Hoc Networks with Selfish Nodes*. Paper presented at the Proceedings of 19th IEEE International, Parallel and Distributed Processing Symposium (IPDPS), Denver, Colorado, USA.
- Eissa, T., Razak, S. A., Khokhar, R., & Samian, N. (2011). Trust-Based Routing Mechanism in MANET: Design and Implementation. *Mobile Networks and Applications*, 18(5), 666-677. doi: 10.1007/s11036-011-0328-0
- Felegyhazi, M., Hubaux, J. P., & Buttyan, L. (2006). Nash Equilibria of Packet Forwarding Strategies in Wireless Ad Hoc Networks. *IEEE Transactions on Mobile Computing*, 5(5), 463-476.
- Ferraz, L. H. G., Velloso, P. B., & Duarte, O. C. M. B. (2014). An Accurate and Precise Malicious Node Exclusion Mechanism for Ad Hoc Networks. *Ad Hoc Networks*, 19, 142-155.

- Fudenberg, D., & Tirole, J. (1991). *Game Theory*. Cambridge, MA: MIT Press.
- Govindan, K., & Mohapatra, P. (Second Quarter 2012). Trust Computations and Trust Dynamics in Mobile Adhoc Networks: A Survey. *IEEE Communications Surveys & Tutorials*, 14(2), 279-298.
- Green, E. J., & Porter, R. H. (1984). Noncooperative Collusion under Imperfect Price Competition. *Econometrica*, 52(1), 87-100.
- Guo, J., Liu, H., Dong, J., & Yang, X. (2007). HEAD: A Hybrid Mechanism to Enforce Node Cooperation in Mobile Ad Hoc Networks. *Tsinghua Science and Technology*, 12(1), 202-207.
- Han, Z., Ji, Z., & Liu, K. J. R. (2008). A Cartel Maintenance Framework to Enforce Cooperation in Wireless Networks with Selfish Users. *IEEE Transaction on Wireless Communications*, 7(5), 1889-1899.
- He, Q., Wu, D., & Khosla, P. (2004, 21-25 March). *SORI: A Secure and Objective Reputation-based Incentive Scheme for Ad-hoc Networks*. Paper presented at the Proceedings of IEEE Wireless Communications and Networking Conference (WCNC), New Orleans, LA, USA.
- Herhold, P., Zimmermann, E., & Fettweis, G. (2005). Cooperative multi-hop transmission in wireless networks. *Computer Networks*, 49(3), 299-324. doi: 10.1016/j.comnet.2005.05.009
- Hernandez-Orallo, E., Serrat, M. D., Cano, J., Calafate, C. T., & Manzoni, P. (2012). Improving Selfish Node Detection in MANETs using a Collaborative Watchdog. *IEEE Communications Letters*, 16(5), 642-645. doi: 10.1109/lcomm.2012.030912.112482
- Hotelling, H. (1953). New Light on the Correlation Coefficient and its Transforms. *Journal of the Royal Statistical Society. Series B (Methodological)*, 15(2), 193-232.
- Hu, J., & Burmester, M. (2006, 10-12 March). *LARS: A Locally Aware Reputation System for Mobile Ad Hoc Networks*. Paper presented at the Proceedings of the 44th Annual Southeast Regional Conference, Melbourne, Florida, USA.
- Huang, L., Li, L., Liu, L., Zhang, H., & Tang, L. (2007). *Stimulating Cooperation in Route Discovery of Ad Hoc Networks*. Paper presented at the Proceedings of the 3rd ACM Workshop on QoS and Security for Wireless and Mobile Networks, Chania, Crete Island, Greece.

- IEEE. (1997). IEEE Standard for Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications *IEEE Std P802.11*.
- Jakobsson, M., Buttyan, L., & Hubaux, J.-P. (2003, 27-30 January). *A Micro-payment Scheme Encouraging Collaboration in Multi-hop Cellular Networks*. Paper presented at the Proceedings of The 7th International Financial Cryptography Conference, Gosier, Guadeloupe.
- Janzadeh, H., Fayazbakhsh, K., Dehghan, M., & Fallah, M. S. (2009). A secure credit-based cooperation stimulating mechanism for MANETs using hash chains. *Future Generation of Computer Systems*, 25(8), 926-934. doi: 10.1016/j.future.2008.12.002
- Jaramillo, J. J., & Srikant, R. (2007). *DARWIN: Distributed and Adaptive Reputation Mechanism for Wireless Ad-hoc Networks*. Paper presented at the Proceedings of the 13th Annual ACM International Conference on Mobile Computing and Networking (MobiCom), Montreal, Canada.
- Just, M., Kranakis, E., & Wan, T. (2003, 8-10 October). *Resisting Malicious Packet Dropping in Wireless Ad Hoc Networks*. Paper presented at the Proceedings of the International Conference on Ad Hoc, Mobile, and Wireless Networks (ADHOC-NOW), Montreal, Canada.
- Kandori, M. (2002). Introduction to Repeated Games with Private Monitoring. *Journal of Economic Theory*, 102(1), 1-15.
- Kandori, M. (2003). Randomization, Communication, and Efficiency in Repeated Games with Imperfect Public Monitoring. *Econometrica*, 71(1), 345-353.
- Kandori, M., & Matsushima, H. (1998). Private Observation, Communication and Collusion. *Econometrica*, 66(3), 627-652.
- Karygiannis, A., Antonakakis, E., & Apostolopoulos, A. (2006, 29 June). *Detecting Critical Nodes for MANET Intrusion Detection Systems*. Paper presented at the Proceedings of Second International Workshop on Security, Privacy and Trust in Pervasive and Ubiquitous Computing (SecPerU), Lyon, France.
- Khandani, A. E., Abounadi, J., Modiano, E., & Lizhong, Z. (2007). Cooperative Routing in Static Wireless Networks. *IEEE Transactions on Communications*, 55(11), 2185-2192.
- Kleinrock, L. (1975). *Queueing Systems* (Vol. Volume 1): Wiley-Interscience.

- Lee, J. F., Liao, W., & Chen, M. C. (2008). An Incentive-based Fairness Mechanism for Multi-hop Wireless Backhaul Networks with Selfish Nodes. *IEEE Transactions on Wireless Communications*, 7(2), 697-704.
- Lei, H., & Liu, L. (2008). Extended Watchdog Mechanism for Wireless Sensor Networks. *Journal of Information and Computing Science*, 3(1), 39-48.
- Li, H., & Singhal, M. (2007). Trust Management in Distributed Systems. *Computers*, 40(2), 45-53.
- Liang, G., Agarwal, R., & Vaidya, N. (2010, 15-19 March). *When Watchdog Meets Coding*. Paper presented at the Proceedings of the 29th IEEE International Conference on Information Communications (INFOCOM), San Diego, CA, USA.
- Lin, H.-C., Sun, M.-K., Huang, H.-W., C.-Y.H., T., & Lin, H.-T. (2012, 26-28 September). *A Specification-based Intrusion Detection Model for Wireless Ad Hoc Networks*. Paper presented at the Proceedings of the 3rd International Conference on Innovations in Bio-inspired Computing and Applications (IBICA), Kaohsiung City, Taiwan.
- Lin, Y., Song, J.-H., & Wong, V. (2009). Cooperative Protocols Design for Wireless Ad-Hoc Networks with Multi-hop Routing. *Mobile Networks and Applications*, 14(2), 143-153. doi: 10.1007/s11036-008-0132-7
- Liu, K., Deng, J., Varshney, P. K., & Balakrishnan, K. (2007). An Acknowledgment-based Approach for the Detection of Routing Misbehavior in MANETs. *IEEE Transaction on Mobile Computing*, 6(5), 536-550.
- Liu, Z., Joy, A. W., & Thompson, R. A. (2004, 26-28 May). *A dynamic trust model for mobile ad hoc networks*. Paper presented at the Proceedings of the 10th IEEE International Workshop on Future Trends of Distributed Computing Systems (FTDCS), Sushou, China.
- MacKenzie, A. B., & DaSilva, L. A. (2006). Game Theory for Wireless Engineers
- Macker, J. P., & Corson, M. S. (1998). Mobile Ad Hoc Networking and the IETF. *ACM SIGMOBILE Mobile Computing and Communications Review*, 2(1), 9-14.
- Mahmoud, M. E., & Shen, X. (2010, 15-19 March). *Stimulating cooperation in multi-hop wireless networks using cheating detection system*. Paper presented at the Proceedings of the 29th IEEE International Conference on Information Communications (INFOCOM), San Diego, California, USA.

- Mahmoud, M. M. E. A., & Shen, X. S. (2011). An Integrated Stimulation and Punishment Mechanism for Thwarting Packet Drop in Multihop Wireless Networks. *IEEE Transaction on Vehicular Technology*, 60(8), 3947–3962.
- Mahmoud, M. M. E. A., & Shen, X. S. (2012). FESCIM: Fair, Efficient, and Secure Cooperation Incentive Mechanism for Hybrid Ad Hoc Networks. *IEEE Transaction on Mobile Computing*, 11(5), 753–766.
- Mahmoud, M. M. E. A., & Shen, X. S. (2013). A Secure Payment Scheme with Low Communication and Processing Overhead for Multihop Wireless Networks. *IEEE Transaction on Parallel and Distributed Systems*, 24(2), 209–224.
- Mailath, G. J., Matthews, S. A., & Sekiguchi, T. (2002b). Private Strategies in Finitely Repeated Games with Imperfect Public Monitoring. *Contributions in Theoretical Economics*, 2(1), 1–2.
- Mailath, G. J., Obara, I., & Sekiguchi, T. (2002a). The Maximum Efficient Equilibrium Payoff in the Repeated Prisoners Dilemma. *Games and Economic Behaviour*, 40(1), 99–122.
- Markopoulou, A. P., Tobagi, F. A., & Karam, M. J. (2003). Assessing the Quality of Voice Communications over Internet Backbones. *IEEE/ACM Transactions on Networking*, 11(5), 747–760.
- Marti, S., Giuli, T. J., Lai, K., & Baker, M. (2000). *Mitigating Routing Misbehavior in Mobile Ad Hoc Networks*. Paper presented at the Proceedings of the 6th Annual International Conference on Mobile Computing and Networking, Boston, Massachusetts, USA.
- Mayer, R. C., Davis, J. H., & Schoorman, F. D. (1995). An Integrative Model of Organizational Trust. *Academy of Management Executive*, 20(3).
- Michiardi, P., & Molva, R. (2002, 26–27 September). *CORE: A Collaborative Reputation Mechanism to Enforce Node Cooperation in Mobile Ad Hoc Networks*. Paper presented at the Proceedings of 6th Joint Working Conference on Communications and Multimedia Security, Netherlands.
- Milan, F., Jaramillo, J. J., & Srikant, R. (2006, 14th October). *Achieving Cooperation in Multihop Wireless Networks of Selfish Nodes*. Paper presented at the Proceedings of the Workshop on Game theory for Communications and Networks (GameNets), Pisa, Italy.
- Minoli, D., Sohrawy, K., & Occhiogrosso, B. (2017). IoT Considerations, Requirements, and Architectures for Smart Buildings - Energy Optimization and Next-Generation Building Management Systems. *IEEE Internet of Things Journal*, 4(1), 269–283.

- Myerson, R. B. (1991). *Game Theory: Analysis of Conflict*: Harvard University Press.
- Ng, S.-K., & Seah, W. K. G. (2010). Game-Theoretic Approach for Improving Cooperation in Wireless Multihop Networks. *IEEE Transactions on Systems, Man, and Cybernetics, Part B: Cybernetics*, 40(3), 559-574.
- Niu, B., Zhao, H. V., & Hai, J. (2011). A Cooperation Stimulation Strategy in Wireless Multicast Networks. *IEEE Transactions on Signal Processing*, 59(5), 2355-2369.
- OMNeT++ Discrete Event Simulator. (2001-2015) OpenSim Ltd. Retrieved 25 October, 2016
- Orset, J.-M., Alcalde, B., & Cavalli, A. (2005, 4–7 October). *An EFSM-based Intrusion Detection System for Ad Hoc Networks*. Paper presented at the Proceedings of the 3rd Automated Technology for Verification and Analysis (ATVA), Taipei, Taiwan.
- Perkins, C. E., & Belding-Royer, E. M. (2003). Ad hoc on Demand Distance Vector (AODV) Routing *IETF Internet-Draft, RFC 3561*.
- Prandoni, P., & Vetterli, M. (2008). *Signal Processing for Communications*: EPFL Press.
- Rebahi, Y., Mujica, -. V. V. E., & Sisalem, D. (2005, 27–30 June). *A Reputation-based Trust Mechanism for Ad hoc Networks*. Paper presented at the Proceedings of the 10th IEEE Symposium on Computers and communications (ISCC), Cartagena, Spain.
- Refaei, M. T., Rong, Y., A., D. L., & Choi, H.-A. (2007, 24–28 June). *Detecting Node Misbehavior in Ad Hoc Networks*. Paper presented at the Proceedings of the IEEE International Conference on Communications (ICC), Glasgow, Scotland.
- Refaei, M. T., Srivastava, V., DaSilva, L., & Eltoweissy, M. (2005). *A Reputation-based Mechanism for Isolating Selfish Nodes in Ad Hoc Networks*. Paper presented at the Proceedings of the The Second Annual International Conference on Mobile and Ubiquitous Systems: Networking and Services.
- Salem, N. B., Buttyan, L., Hubaux, J.-P., & Jakobsson, M. (2006). Node Cooperation in Hybrid Ad Hoc Networks. *IEEE Transaction on Mobile Computing*, 5(4), 365–376.
- Shabut, A. M., Dahal, K. P., Bista, S. K., & Awan, I. U. (2015). Recommendation Based Trust Model with an Effective Defence Scheme for MANETs. *IEEE Transactions on Mobile Computing*, 14(10), 2101-2115.

- Sharef, B. T., Alsaqour, R. A., & Ismail, M. (2014). Vehicular communication ad hoc routing protocols: A survey. *Journal of Network and Computer Applications*, 40, 363-396.
- Sharma, S., Yi, S., Hou, Y. T., & Kompella, S. (2011). An Optimal Algorithm for Relay Node Assignment in Cooperative Ad Hoc Networks. *IEEE/ACM Transactions on Networking*, 19(3), 879-892.
- Sharma, S., Yi, S., Hou, Y. T., Sherali, H. D., & Kompella, S. (2010, 15-19 March). *Cooperative Communications in Multi-hop Wireless Networks: Joint Flow Routing and Relay Node Assignment*. Paper presented at the The 29th IEEE Conference on Computer Communications (INFOCOM), San Diego, CA.
- Shen, H., & Li, Z. (2008, 17–20 June). *ARM: An Account-based Hierarchical Reputation Management System for Wireless Ad Hoc Networks*. Paper presented at the Proceedings of 28th International Conference on Distributed Computing Systems Workshops (ICDCS), Beijing, China.
- Sorin, S. (1986). On Repeated Games with Complete Information. *Mathematics of Operations Research*, 11(1), 147–160.
- Srivastava, V., & Dasilva, L. A. (2006, 11-15 June 2006). *Equilibria for Node Participation in Ad Hoc Networks - An Imperfect Monitoring Approach*. Paper presented at the IEEE International Conference on Communications (ICC), Istanbul, Turkey.
- Srivastava, V., Neel, J., Mackenzie, A. B., Menon, R., Dasilva, L. A., Hicks, J. E., . . . Gilles, R. P. (2005). Using Game Theory to Analyze Wireless Ad Hoc Networks. *IEEE Communications Surveys & Tutorials*, 7(4), 46-56.
- Sun, Y., Guo, Y., Ge, Y., Lu, S., Zhou, J., & Dutkiewicz, E. (2013). Improving the Transmission Efficiency by Considering Non-cooperation in Ad Hoc Networks. *The Computer Journal*, 56(8), 1034–1042.
- Tipler, P. A. (1995). *Physics For Scientists and Engineers* (3rd ed.): Worth Publishers.
- Toledo, A. L., & Wang, X. (2007). IEEE Journal on Selected Areas in Communications. *Robust Detection of Selfish Misbehavior in Wireless Networks*, 25(6), 1124–1134.
- Tseng, C.-Y., Balasubramanyam, P., Ko, C., Limprasittiporn, R., Rowe, J., & Levitt, K. (2003, 27-30 October). *A Specification-based Intrusion Detection System for AODV*. Paper presented at the Proceedings of the 1st ACM workshop on Security of Ad Hoc and Sensor Networks, Fairfax, Virginia.

- Varga, A., & Hornig, A. R. (2008, 3-7 March). *An Overview of the OMNeT++ Simulation Environment*. Paper presented at the Proceedings of the 1st International Conference on Simulation Tools and Techniques for Communications, Networks and Systems & Workshops, Marseille, France.
- Velloso, P. B., Laufer, R. P., Cunha, D. D. O. O., Duarte, O. C. M. B., & Pujolle, G. (2010). Trust Management in Mobile Ad Hoc Networks Using a Scalable Maturity-based Model. *IEEE Transactions on Network and Service Management*, 7(3), 172-185.
- Walker, J. Q. (2002). Assessing VoIP Call Quality Using the E-model. Retrieved from
- Wang, B., Soltani, S., Shapiro, J. K., & Tan, P.-N. (2005). *Local Detection of Selfish Routing Behavior in Ad Hoc Networks*. Paper presented at the Proceedings of the 8th International Symposium on Parallel Architectures, Algorithms and Networks (ISPAN), Las Vegas, Nevada, USA.
- Wang, X., Cai, Y., & Li, Z. (2014). A Novel Hybrid Incentive Mechanism for Node Cooperation in Mobile Cyber-physical Systems. *International Journal of Parallel Emergent and Distributed Systems*, 29(3), 316–336.
- Wang, Y., & Singhal, M. (2005, 22-24 August). *A Light-weight Solution for Selfish Nodes Problem Considering Battery Status in Wireless Ad-hoc Networks*. Paper presented at the Proceedings of IEEE International Conference on Wireless and Mobile Computing, Networking and Communications (WiMob), Montreal, QC, Canada.
- Weyland, A., Staub, T., & Braun, T. (2006). Comparison of Motivation-based Cooperation Mechanisms for Hybrid Wireless Networks. *Computer Communications*, 29(13-14), 2661–2670.
- Xu, C., Feng, J., Zhou, Z., Wu, J., & Perera, C. (2017). Cross-Layer Optimization for Cooperative Content Distribution in Multihop Device-to-Device Networks. *IEEE Internet of Things Journal*(99), 1-10. doi: 10.1109/JIOT.2017.2741718
- Yaqoob, I., Ahmed, E., Hashem, I. A. T., Ahmed, A. I. A., Gani, A., Imran, M., & Guizani, M. (2017). Internet of Things Architecture - Recent Advances, Taxonomy, Requirements, and Open Challenges. *IEEE Wireless Communications*, 24(3), 10-16.
- Ye, X., & Li, J. (2009, 18–20 December). *An FSM-based Automatic Detection in AODV for Ad Hoc Network*. Paper presented at the Proceedings of the International Symposium on Computer Network and Multimedia Technology (CNMT), Wuhan, China.

- Yick, J., Mukherjee, B., & Ghosal, D. (2008). Wireless sensor network survey. *Computer Networks*, 52(12), 2292-2330.
- Yokoyama, S., Nakane, Y., Takahashi, O., & Miyamoto, E. (2006, 10-12 May). *Evaluation of the Impact of Selfish Nodes in Ad Hoc Networks and Detection and Countermeasure Methods*. Paper presented at the Proceedings of 7th International Conference on Mobile Data Management (MDM), Nara, Japan.
- Yu, H., Liu, S., Kot, A. C., Miao, C., & Leung, C. (2011, 25-28 Sept). *Dynamic witness selection for trustworthy distributed cooperative sensing in cognitive radio networks*. Paper presented at the IEEE 13th International Conference on Communication Technology (ICCT), Jinan, China.
- Yu, M., Zhou, M., & Su, W. (2009). A Secure Routing Protocol against Byzantine Attacks for Manets in Adversarial Environments. *IEEE Transactions on Vehicular Technology*, 58(1), 449-460.
- Zhang, C., Zhu, X., Song, Y., & Fang, Y. (2010, 15-19 March). *A Formal Study of Trust-based Routing in Wireless Ad Hoc Networks*. Paper presented at the Proceedings of the 29th IEEE International Conference on Information Communications (INFOCOM), San Diego, CA, USA.
- Zhang, G., Yang, K., Liu, P., & Feng, X. (2013). Stimulating Cooperation in Self-organizing Mobile Ad Hoc Networks Incentive Mechanism for Multiuser Cooperative Relaying in Wireless Ad Hoc Networks: A Resource-exchange Based Approach. *Wireless Personal Communications*, 73(3), 697-715.
- Zhang, J., & Zhang, Q. (2008, 15-17 April). *Cooperative Routing in Multi-source Multi-destination Multi-hop Wireless Networks*. Paper presented at the Proceedings of the 27th IEEE International Conference on Information Communications (INFOCOM), Phoenix, USA.
- Zhang, Z., Shi, J., Chen, H.-H., Guizani, M., & Qiu, P. (2008). A Cooperation Strategy Based on Nash Bargaining Solution in Cooperative Relay Networks. *IEEE Transactions on Vehicular Technology*, 57(4), 2570-2577.
- Zhong, S., & Wu, F. (2010). A Collusion-Resistant Routing Scheme for Noncooperative Wireless Ad Hoc Networks. *IEEE/ACM Transactions on Networking*, 18(2), 582-595.
- Zhong, S., Yang, Y. R., & Chen, J. (2003, 1-3 April). *Sprite: A Simple, Cheat Proof, Credit-based System for Mobile Adhoc Networks*. Paper presented at the Proceedings of The 22nd IEEE International Conference on Information Communications (INFOCOM), San Francisco, USA.

Zouridaki, C., Mark, B. L., Hejmo, M., & Thomas, R. K. (2005). *A Quantitative Trust Establishment Framework for Reliable Data Packet Delivery in MANETs*. Paper presented at the Proceedings of the 3rd ACM Workshop on Security of Ad hoc and Sensor Networks, Alexandria, VA, USA.

