



**UNIVERSITI PUTRA MALAYSIA**

***HEXAGONAL GRID-BASED DYNAMIC ROUTING ADJUSTMENT FOR  
OPTIMISING NETWORK LIFETIME IN WIRELESS SENSOR NETWORK***

**ZAID FAWAZ JARALLAH**

**FSKTM 2018 17**



**HEXAGONAL GRID-BASED DYNAMIC ROUTING ADJUSTMENT FOR  
OPTIMISING NETWORK LIFETIME IN WIRELESS SENSOR NETWORK**

By

**ZAID FAWAZ JARALLAH**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,  
In Fulfilment for the Degree of Master of Science**

**November 2017**

## COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise states. Use may be made of material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



## DEDICATION

**This thesis is dedicated to my beloved *parents***

For their endless love, encouragement and unconditional support in all my life

And

**Especially to my beloved wife, Sarah**

Anything good that has come to my life has been because of your example

And

**My lovely Children (*Wisam and Tamarah*)**

Love you always and forever

And

**My Dear Sister (Luma) and her husband (Azher)**

I will always be grateful to you



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in Fulfilment  
of the requirement for the degree of Master of Science

**HEXAGONAL GRID-BASED DYNAMIC ROUTING ADJUSTMENT FOR  
OPTIMISING NETWORK LIFETIME IN WIRELESS SENSOR NETWORK**

By

**ZAID FAWAZ JARALLAH**

**November 2017**

**Chairman : Abdullah Muhammed, PhD**  
**Faculty : Computer Science and Information Technology**

Over past few years we have seen a growing interest in the prospect use of wireless sensor networks (WSNs) in enormous domain of applications and it became an interesting research area. The formation of WSNs, which consist of small battery with limited power, make it has a huge shortage of energy.

Many researchers proposed various techniques to solve this problem, aiming to prolong the network lifetime. In the scientific literatures, some of the researchers proposed routing protocols to pass the data through the network. These include the division of sensing area into grids or cells as clusters, each cluster select one node as Cluster-Head (CH). CHs task inside the network is to connect with each other in order to receive the data from MNs and send it to S. The other suggested technique assumed that the sink has to be routable and moves around the network and collect data from MNs directly. By doing so, the mobile sink can reduce the energy depletion of the nodes subsequently, will enhance the network lifetime. The major issues while utilising this technique is how to detect the sink while moving and this is still a challenge. This research try to solve the problem that occur while utilizing the clustering technique, which are the CHs that close to the S node will deplete the energy faster than others, as well as, during the sink mobility technique, solving the detection of the mobile sink location process.

However, a new protocol has proposed called Hexagonal Grid based Dynamic Routes Adjustment (HGDR) which divides the network cells into hexagonal clusters and used the mobile sink technique inside the network area in order to prolong the network lifetime. The proposed technique tries to reconstruct a data packet path that detects the mobile sink with less energy consumption, as well as improving the network lifetime.

The experimental result that gained via Ns2 simulator demonstrate that the proposed approach produce better quality solutions in terms of network reconstruction cost, number of hops, nodes residual energy and network lifetime when compared with the benchmark approach.



Abstrak tesis ini dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**PELARASAN PENGHALAAN DINAMIK BERASASKAN GRID  
HEKSAGONAL(HGDRA) UNTUK MENGOPTIMUMKAN JANGKA  
HAYAT RANGKAIAN DALAM RANGKAIAN PENGESAN WAYARLES**

Oleh

**ZAID FAWAZ JARALLAH**

**November 2017**

**Pengerusi : Abdullah Muhammed, PhD**  
**Fakulti : Sains Komputer dan Teknologi Maklumat**

Sejak beberapa tahun kebelakangan ini kita telah melihat minat yang semakin meningkat dalam penggunaan prospek rangkaian sensor tanpa wayar (WSNs) dalam domain besar aplikasi dan ia menjadi kawasan penyelidikan yang menarik. Pembentukan WSNs, yang terdiri daripada bateri kecil dengan kuasa terhad, menjadikan ia mempunyai kekurangan besar tenaga. Ramai penyelidik mencadangkan pelbagai teknik untuk menyelesaikan masalah ini, yang bertujuan untuk memanjangkan jangka hayat rangkaian. Dalam kesusasteraan saintifik, beberapa penyelidik mencadangkan protokol routing untuk lulus data melalui rangkaian. Ini termasuk pembahagian kawasan ke dalam grid atau sel-sel sebagai kelompok penderiaan, setiap kelompok pilih satu nod sebagai Kluster-Kepala (CH). CHS tugas di dalam rangkaian ini adalah untuk menyambung antara satu sama lain untuk menerima data dari MNS dan hantar ke S. Teknik disyorkan lain diandaikan bahawa sinki telah menjadi routable dan bergerak di sekitar rangkaian dan mengumpulkan data dari MNS langsung. Dengan berbuat demikian, sinki mudah alih boleh mengurangkan kekurangan tenaga nod seterusnya, akan meningkatkan jangka hayat rangkaian. Isu-isu utama semasa menggunakan teknik ini adalah bagaimana untuk mengesan sink sambil bergerak dan ini masih satu cabaran. Kajian ini cuba untuk menyelesaikan masalah yang berlaku semasa menggunakan teknik pengelompokan, yang adalah CHS yang menutup kepada nod S akan dapat mengurangkan tenaga yang lebih cepat daripada yang lain, dan juga, semasa teknik sink mobiliti, menyelesaikan pengesanan sink mudah alih proses lokasi. Walau bagaimanapun, protokol baru telah dicadangkan dipanggil hexagon Grid berasaskan Laluan Dynamic Pelarasan (HGDRA) yang membahagikan sel-sel rangkaian ke dalam kelompok heksagon dan menggunakan teknik sinki mudah alih di dalam kawasan rangkaian untuk memanjangkan jangka hayat rangkaian. teknik yang dicadangkan cuba untuk membina semula jalan paket data yang mengesan sink mudah alih dengan penggunaan tenaga yang kurang, serta

memperbaiki hidup rangkaian. Hasil eksperimen yang mendapat melalui NS2 simulator menunjukkan bahawa pendekatan yang dicadangkan menghasilkan penyelesaian yang lebih berkualiti dari segi kos rangkaian pembinaan semula, bilangan hop, nod tenaga sisa dan jangka hayat rangkaian jika dibandingkan dengan pendekatan penanda aras. teknik yang dicadangkan cuba untuk membina semula jalan paket data yang mengesan sink mudah alih dengan penggunaan tenaga yang kurang, serta memperbaiki hidup rangkaian. Hasil eksperimen yang mendapat melalui NS2 simulator menunjukkan bahawa pendekatan yang dicadangkan menghasilkan penyelesaian yang lebih berkualiti dari segi kos rangkaian pembinaan semula, bilangan hop, nod tenaga sisa dan jangka hayat rangkaian jika dibandingkan dengan pendekatan penanda aras. teknik yang dicadangkan cuba untuk membina semula jalan paket data yang mengesan sink mudah alih dengan penggunaan tenaga yang kurang, serta memperbaiki hidup rangkaian. Hasil eksperimen yang mendapat melalui NS2 simulator menunjukkan bahawa pendekatan yang dicadangkan menghasilkan penyelesaian yang lebih berkualiti dari segi kos rangkaian pembinaan semula, bilangan hop, nod tenaga sisa dan jangka hayat rangkaian jika dibandingkan dengan pendekatan penanda aras.





## ACKNOWLEDGEMENTS

First and foremost, great thanks, glories and praises devoted to God (Allah), the Supreme Ruler of the universe who created us, for giving us ability to think and power to perform our duties.

Profound and sincere gratitude is extended to my supervisor Dr. Abdullah Muhammed for his great advice, encouragement, valuable guidance, and foresight throughout the years. This thesis would have never been completed without his assistance. He has helped me in providing all facilities required to do this work. It is my pleasure also to thank the active members of my supervisory committee, Dr Azizol Abdullah, Assoc. Prof Zurina Mohd Hanapi, for their suggestions, assistance and support during my research.

I would like also to express my deepest appreciation and thanks to Iraqi Government represented by Ministry of Higher Education and Scientific Research, Scholarship and Cultural Relations Directorate, Iraqi Embassy and Cultural Attaché in Kuala Lumpur, for the opportunity to given in pursuing the Master degree at Universiti Putra Malaysia.

Last but not least, I acknowledgment my family (my parents, my wife, my children, and my brothers) and my friends for their support, help and encouragement.

I certify that a Thesis Examination Committee has met on 10 November 2017 to conduct the final examination of Zaid Fawaz Jarallah Al Hadawa on his thesis entitled "Hexagonal Grid-Based Dynamic Routing Adjustment for Optimising Network Lifetime in Wireless Sensor Network" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

**Rohaya binti Latip, PhD**


Associate Professor  
Faculty of Computer Science and Information Technology  
Universiti Putra Malaysia  
(Chairman)

**Amir Rizaan bin Abdul Rahiman, PhD**

Senior Lecturer  
Faculty of Computer Science and Information Technology  
Universiti Putra Malaysia  
(Internal Examiner)

**Rafidah binti Md Noor, PhD**

Associate Professor  
University of Malaya  
Malaysia  
(External Examiner)



---

**NOR AINI AB. SHUKOR, PhD**

Professor and Deputy Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date: 29 January 2018

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

**Abdullah Muhammed PhD**

Senior Lecturer  
Faculty of Computer Science and Information Technology  
Universiti Putra Malaysia  
(Chairman)

**Azizol Abdullah PhD**

Senior Lecturer  
Faculty of Computer Science and Information Technology  
Universiti Putra Malaysia  
(Member)

**Zurina Mohd Hanapi, PhD**

Associate Professor  
Faculty of Computer Science and Information Technology  
Universiti Putra Malaysia  
(Member)

---

**ROBIAH BINTI YUNUS, PhD**

Professor and Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date:

## Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Name and Matric No.: Zaid Fawaz Jarallah ,GS40591

## Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: \_\_\_\_\_  
Name of Chairman  
of Supervisory  
Committee: Abdullah Muhammed, PhD

Signature: \_\_\_\_\_  
Name of Member  
of Supervisory  
Committee: Azizol Abdullah, PhD

Signature: \_\_\_\_\_  
Name of Member  
of Supervisory  
Committee: Associate Professor Dr. Zurina Mohd Hanapi

## TABLE OF CONTENTS

	<b>Page</b>
<b>ABSTRACT</b>	i
<b>ABSTRAK</b>	iii
<b>ACKNOWLEDGEMENTS</b>	v
<b>APPROVAL</b>	vi
<b>DECLARATION</b>	viii
<b>LIST OF TABLES</b>	xii
<b>LIST OF FIGURES</b>	xiii
<b>LIST OF ABBREVIATIONS</b>	xv
<b>CHAPTER</b>	
<b>1 INTRODUCTION</b>	<b>1</b>
1.1 Research Background	1
1.1.1 Clustering Routing Protocols	2
1.2 Problem Statement	3
1.3 Research Questions	3
1.4 Research Objectives	4
1.5 Research Scope	4
1.6 Research Contributions	4
1.7 Organisation of the Thesis	5
<b>2 LITERATURE REVIEW</b>	<b>6</b>
2.1 Introduction	6
2.2 WSNs Applications	6
2.3 Clustering Protocols in WSNs	8
2.4 Sink Mobility Pattern and Data Collection	10
2.4.1 Advantages of Sink Mobility	10
2.4.2 Clustering Technique with Sink Mobility	11
2.5 Virtual Backbone-Based Approach	14
2.5.1 Honeycomb Form Protocols	14
2.5.2 Different Geometric Form Protocols	18
2.6 Summary	24
<b>3 RESEARCH METHODOLOGY</b>	<b>25</b>
3.1 Research Methodology	25
3.1.1 Problem Overview	26
3.1.2 Solution Techniques	26
3.1.3 Model Implementation	28
3.1.4 Performance Evaluation Metrics	31
3.2 Summary	31

<b>4</b>	<b>MOBILE SINK WITH READJUSTMENT ROUTE FOR WSNS</b>	<b>32</b>
4.1	Introduction	32
4.2	Sink hexagonal movement	32
4.3	HGDRA Protocol	34
4.3.1	The Network Characteristic	35
4.3.2	HGDRA Network Model	35
4.3.2.1	Hexagonal grid structure	36
4.3.2.2	Route Reconstruction Process	37
4.3.2.3	Mobile sink adjustment on hexagonal clusters	39
4.4	HGDRA-S Protocol	40
4.4.1	HGDRA-S Network Model	40
4.4.2	Smart Sink Technique in HGDRA-S	40
4.5	Summary	42
<b>5</b>	<b>RESULTS AND DISCUSSIONS</b>	<b>43</b>
5.1	Introduction	43
5.2	Performance Evaluation of Three Scenarios Sink Movement	43
5.2.1	Network Residual Energy	43
5.2.2	Network throughput	45
5.2.3	Number of Collisions Occurrences	46
5.2.4	Network Lifetime	48
5.3	Performance Evaluation of HGDRA	49
5.3.1	Area Construction Energy Consumption	49
5.3.2	Per-Round Route Reconstruction Cost	50
5.3.3	Network convergence time	51
5.3.4	Average Number of Hops	53
5.3.5	The Network Lifetime	54
5.3.6	Summary	55
5.4	Performance Evaluation of HGDRA-S	55
5.4.1	Area Construction Energy Consumption	55
5.4.2	Per-Round Routes Reconstruction Cost	56
5.4.3	Network Convergence Time	57
5.4.4	Average Number of Hops	58
5.4.5	The Network Lifetime	60
5.4.6	Conclusion	61
5.5	Summary	61
<b>6</b>	<b>CONCLUSION AND FUTURE WORK</b>	<b>62</b>
	<b>REFERENCES</b>	<b>63</b>
	<b>BIODATA OF STUDENT</b>	<b>69</b>
	<b>PUBLICATION</b>	<b>70</b>

## LIST OF TABLES

Table		Page
2.1	Protocols in WSNs	22
3.1	The Network Initialisation Phases	28
4.1	The Sink Movement Scenarios Network Parameters	34
4.2	The HGDRA Network Simulation Parameter	36
5.1	The Percentages Of Residual Energy Comparison Among Three Techniques	44
5.2	The Network Throughput Percentages for Three Techniques by bit per second (bps)	46
5.3	The Percentages Comparison For Collision Occurrences of The Three Scenarios	47
5.4	The Percentages Comparison of Network Lifetime	48
5.5	Area Construction Energy Consumption Percentages Comparison For VGDRA With HGDRA	49
5.6	Per-Round Route Reconstruction Percentages For VGDRA And HGDRA	51
5.7	The Network Convergence Time Percentages Comparison for VGDRA and HGDRA	52
5.8	The Number of Hops Comparison Percentages For VGDRA With HGDRA	53
5.9	The Network Lifetime Improvement Percentage Comparison For VGDRA With HGDRA	54
5.10	The Area Construction Energy Consumption Percentages Comparison By 100% For VGDRA With HGDRA-S	56
5.11	Per-Round Route Reconstruction Percentages Comparison for HGDRA and HGDRA-S	57
5.12	The Network Convergence Time Enhancement Comparison By 100% Percentages For VGDRA With HGDRA-S	58
5.13	The Number Of Hops Percentages Comparison For VGDRA With HGDRA-S	59
5.14	The Network Lifetime Improvement Percentage Comparison For VGDRA With HGDRA-S	60



## LIST OF FIGURES

Figure		Page
2.1	MMSR Mobility Trajectory	14
2.2	The Six Stop Position of Hexagonal Cluster (Marta & Cardei, 2009)	15
2.3	The 12 Stop Position of Hexagonal Cluster (Marta & Cardei, 2009)	16
2.4	The Border Cells and Extant Formation of HexDD	17
2.5	Virtual Backbone for VGDRA Scheme	20
2.6	Literature Review Map	21
3.1	Research Methodology Framework	25
3.2	Illustrate the HGDR A Two Movement Techniques Selections	26
3.3	The Trace Files Structure for The Ns-2 Simulation	29
3.4	Ns2 commands to start the simulation	30
3.5	NAM File Simulation Starting for Hexagonal Movement	30
4.1	(a),(b),(c) Illustrate The Sink Movement Scenarios Over WSN	33
4.2	The Differences between the Two Protocols In The Factor of Number of Neighbours	34
4.3	(a), (b) Comparing Virtual Backbone for the Two Protocols	36
4.4	Algorithm 1 Path Detection and Data Collection of HGDR A Pseudo Code	38
4.5	Sink Movement Inside The WSN Cells	39
4.6	Smart Sink Readjustment Move Inside WSN	41
4.7	The Pseudo Code of Smart Sink Detection in HGDR A	42
5.1	The Network Residual Energy Comparison for The Three Scenarios	45
5.2	The Network Throughput Comparison for the Three Scenarios	46
5.3	The Collision Occurrences Comparison For The Three Scenarios	47
5.4	The Network Lifetime Energy Comparison for the Three Scenarios	48
5.5	The Area Construction Energy Consumption of VGDRA and HGDR A	50
5.6	Per-Round Route Reconstruction Cost Comparison of VGDRA and HGDR A	51
5.7	The Network Convergence Time Comparison for VGDRA And HGDR A	52
5.8	Comparison for Number of Hops for VGDRA and HGDR A Protocols	53

5.9	Comparing the Network Lifetime in Term of Rounds for VGDRA and HGDRA	55
5.10	Comparing For Area Construction Energy Consumption between VGDRA And HGDRA-S Protocols	56
5.11	The Comparison between VGDRA and HGDRA-S For Per-Round Route Reconstruction Cost	57
5.12	The Network Convergence Time Line Graph Comparison between VGDRA and HGDRA-S	58
5.13	Comparison for Number of Hops for VGDRA and HGDRA-S Protocols	59
5.14	Comparing the Network Lifetime in Term of Rounds for VGDRA and HGDRA-S	61



## LIST OF ABBREVIATIONS

AP	Access point
BS	Base Station
BVI	Backbone-based Virtual Infrastructure
CDS	Connected Domination Set-based backbone
CH	Cluster Head
DDB	Dynamic Directed Backbone
DN	Dominating Nodes
DWEHC	Distributed Weight-Based Energy-Efficient Hierarchical Clustering
EASR	Energy-Aware Sink Relocation
GMR	Geographic Multicast Routing
GPS	Global Positioning System
HCDD	Hierarchical Cluster-based Data Dissemination
HEED	Hybrid Energy-Efficient Distributed clustering
HexDD	Hexagonal Tiling-Based Data Dissemination
HGDRA	Hexagonal Grid-based Dynamic Routes Adjustment
HGDRA-S	Hexagonal Grid-based Dynamic Route Adjustment with Smart sink
HRPM	Hierarchical Rendezvous Point Multicasting
HTTDD	Hexagonal Two-Tier Data Dissemination
LEACH	Low Energy Adaptive Clustering Hierarchy
LEGOS	Low Energy self-Organisation Scheme
MCP	Maximum Capacity Protocol
MEME	Micro Electro Mechanical System
MMSR	Multiple Mobile Sink-based Routing
MN	Member Node
Ns2	Networks Simulator 2
RP	Rendezvous Point
S	Sink
SN	Sensor Node
TEEN	Threshold-sensitive Energy-Efficient sensor Network protocol
TTDD	Two-Tier Data Dissemination

VCCSR

Virtual Circle Combined Straight Routing

VGDR

Virtual Grid based Dynamic Routes Adjustment

WSN

Wireless Sensor Network



# CHAPTER 1

## INTRODUCTION

### 1.1 Research Background

Rapid evolution of Micro Electro Mechanical System (MEMS) technologies accelerates Wireless Sensor Networks (WSN) development, and it becomes growingly attractive for abundant application system in many fields, such as military exploration, security surveillance, disaster warning system, medical health, habitat monitoring, industrial automation, etc WSNs managed to create a relation between the human communities, physical world, and the computing world (Liu, 2012a).

WSN is a type of network that consists on number of nodes that connect with each other without a physical medium. The nodes are tiny size and containing a small battery with limited energy, and unplugged with power resources. The components of single sensor node in general: a controller module, memory module, communication module, sensing module, power supply module (Bal & Rath, 2014). Furthermore, in some types of networks it could contain a Global Positioning System (GPS) (Patwari et al., 2005).

WSN system architecture contains a base station or sink located in a specific place inside or around the network, this sink node does receive the data that collected by other nodes. The nodes inside the network works as data mining after exploring the area and give a pre-warning signals to the base station, then after collecting data they send it to the base station or the sink.

The data packet flow through the network using hop-by-hop communication, which makes the data flowing more effective in aspect of energy consumption. The sensor nodes in WSNs are highly restricted in terms of transmission energy, processing capacity storage, battery life-time and thus require careful energy managed (Singh et al., 2010a). Network lifetime is the most important factor in WSN, and the energy consumption remains the main critical issue that effect the network lifetime in general (Y. Wang, 2008).

The main goal of initiating a new technique is to prolong the sensor network life-time by presenting a protocol that will help the network consuming more energy for each single node in order to prolong the whole network life-time. The clustering technique has been applied on sensor network in many adjustment protocols to solve the fast energy depletion issues. A wide description on clustering technique are as follow (Kumarawadu et al., 2008).

### 1.1.1 Clustering Routing Protocols

Clustering routing protocols have many advantages such as scalability, energy consumption, and robustness.

- I. High scalability: the sensor nodes separated around the clusters and it has different level of functions. The function of CHs is data forwarding and network management, and MNs function is to sense events and collect information within their signal range. The clustering topology is able to localise the routing setups inside the clusters and decrease the routing table size for each single sensor node. This type of network is easier to manage thus more scalable for responding in the environment.
- II. Data aggregation: the processing of data gathering from many nodes to remove the redundant transmission and comprise data to the BS, the effective technique for saving energy in the WSNs. The most common data propagation technique is the clustering data aggregation. Each CH collects and forwards the compressed data to BS, and generally transmitted the data by using multi-hopping to other CHs with a tree structure which considered a high energy saving technique.
- III. Energy consumption: Data aggregation in clustering routing protocols helps increasing data transmission and saving more energy. Moreover, clusters with intra-cluster data transmission help in reducing the number of nodes in performing long distance communication tasks. Thus providing more energy saving for the entire network.
- IV. Robustness: In clustering routing protocols, it's easy for the network to control and respond to the network changes such as nodes numbers, nodes mobility and nodes failures. With the clustering protocol, these parameters can be controlled by a single cluster, thus the whole network more stable and robust and easy to manage.
- V. Avoid collisions/latency: In WSNs, when it's divided into clusters, data transmission will be performed only on CHs outside the cluster. This mode of data transmission out of cluster is helping to avoid collisions between nodes. Accordingly, the latency will be decreased. The data transmission performed hop-by-hop flooding in flat routing protocols reducing the number of hops between source nodes and BS, and latency will be decreased accordingly.
- VI. Network lifetime: the network lifetime is unavoidable factor in WSNs, because of low nodes energy supply, and with functions of sensing, processing data and bandwidth transmission. Apparently, it is essential to minimise the energy consumption for intra cluster communication via CHs which will be higher data resources than other nodes. Besides, nodes that are near to the most of nodes in the clusters should be apt to be selected as CHs. Additionally, energy-aware idea aiming to select routes that are expected to prolong the network lifetime in intra cluster communication, and the nodes with higher energy should be involved in these routes (Liu, 2012a; Y. Wang, 2008).

## 1.2 Problem Statement

In the WSNs, the most critical problem in the networks function is how to maintain the network lifetime. Utilising the clustering technique provide more energy fairness to the CHs by receiving the data flow for all other MNs and send it to the sink. Clustering technique help the sensor network avoiding energy hole problems (Thanigaivelu & Murugan, 2012).

The CHs will be suffered from the same energy problem, precisely, for CHs that close to the static sink will deplete their energy faster than others. Therefore, a new technique suggested that using the mobile sink in different patterns will help the CHs energy fairness, furthermore, enhance the whole network lifetime (Marta & Cardei, 2009).

Despite the enormous advantages of sink mobility, it caused difficulties in data collection during mobile sink tracking process. In order to maintain tracking the mobile sink in such networks, it has to take in consideration the route reconstruction mechanism that can ease the sink position detection process. In this research, the base work protocol will be Virtual Grid based Dynamic Routes Adjustment (VGDRA). The VGDRA protocol used a clustering technique for peripheral square shape network with mobile sink routing around the network perimeter (Khan et al., 2015a). There are some lacking in the scheme; firstly, CHs that had only four neighbouring clusters can communicate with, while there could be more than that number if we divided the network in a different shape, secondly, some of clusters that far from sink node in some of its position will have to send the data flow all over the network passing through large number of clusters in order to reach the sink and that will exhaust the whole network. The previous issue encourages us to suggest changing the sink movement path by letting it to go cross the network in orderly way to communicate with CHs by being closer to them, as well as, decreasing the data flow inside the network.

## 1.3 Research Questions

In line with the problem statements the following research questions are:

1. What is the best mechanism for improving the efficiency of the WSNs lifetime?
2. How an integrated routing protocol can conserve more energy and enhance the network energy depletion when utilising the clustering technique in WSNs?

## 1.4 Research Objectives

The main points of objectives for this research are as follows:

1. To improve the functionality of the mobile sink data collection mechanism by finding an ideal sink trajectory movement in WSN.
2. To propose a Hexagonal Grid-based Dynamic Route Adjustment (HGDRA) protocol that incorporate with smart sink technique to increase the number of data packets and the number of hops in order to improve the network lifetime.

## 1.5 Research Scope

Our research is scoping the energy dissipation that caused by data packet transmission for the nodes that are close to the base station (sink) in the WSNs. For the mobile sink cluster-heads that are close to the sink node, as well. We tried to solve the problem of the cluster-heads energy consumption, which are close to the sink, by improving the sink movement, as well as, enhancing the grid dividing technique for the sensor network.

## 1.6 Research Contributions

- The major contribution of this research is producing a clustering WSN approach that provides a better lifetime for all nodes inside the network. In order to achieve the main goal, a three movement scenarios for the mobile sink has been examined; hexagonal movement, peripheral movement and random movement. These scenarios have been compared and the result shows the hexagonal movement is outperforming the other two scenarios in terms of network lifetime.
- The best scenario has been used in our new proposed protocol called Hexagonal Grid-based Dynamic Routes Adjustment (HGDRA) that works in a new sink movement pattern which provides an ideal mechanism of sensor network data collection. The proposed protocol compared to a base work protocol Virtual Grid-based Dynamic Route Adjustment (VGDR) using the same parameters and our proposed protocol outperforms the base work protocol with a magnificent percentage in all aspects.
- Another protocol has been proposed that uses a new technique called Hexagonal Grid-based Dynamic Route Adjustment with Smart sink (HGDRA-S), which used a new technique to detect the most active clusters in the network and move the sink near it, this protocol has been compared to the other two protocols (VGDR) and (HGDRA) and the results demonstrate that the proposed protocol outperforms the other two with a good percentage.



## 1.7 Organisation of the Thesis

This thesis is generally divided into 6 chapters; the first chapter is the introduction of the research study that explains the research background. Next the problem statement, the questions of the research, the objectives of the research, the research contribution of this study, the scope of the research, and lastly, the organisation of the thesis, are depicted.

Chapter 2 of the study looks into the related works of the study, the related applications that utilises the WSNs, and the related clustering protocols that been implemented in order to solve the same issue that we refer to, and lastly, the approach of virtual backbone and the related protocols that used it.

In Chapter 3, the methodology of the research has been presented in steps, and each step has been illustrated clearly for our research and we give an explanation for each part of it in details.

In Chapter 4, we illustrate our proposed protocols in details and we explain the mechanism for each one of them and we explain the tools that we used to present the proposed protocols.

In Chapter 5, we demonstrate the result that we obtained from our experimental and we analyse the performance metrics for each protocol.

In Chapter 6, we discuss the conclusion of the research and the future work that could be done for the research method.

## REFERENCES

- Abbasi, A. A., & Younis, M. (2007). A survey on clustering algorithms for wireless sensor networks. *Computer Communications*, 30(14–15), 2826–2841.
- Akkaya, K., & Younis, M. (2005). A survey on routing protocols for wireless sensor networks. *Ad Hoc Networks*, 3(3), 325–349.
- Arboleda, L. M. C. A. L. M. C., & Nasser, N. N. N. (2006). Comparison of Clustering Algorithms and Protocols for Wireless Sensor Networks. *2006 Canadian Conference on Electrical and Computer Engineering*, 1787–1792.
- Baggio, A. (2005). Wireless sensor networks in precision agriculture. *Workshop on Real-World Wireless Sensor Networks*, 107–108.
- Bal, R. S., & Rath, A. K. (2014). Clustering Structure and Deployment of Node in Wireless Sensor Network. *International Journal of Information Technology and Computer Science*, 6(10), 70–76.
- Basagni, S., Carosi, A., Melachrinoudis, E., Petrioli, C., & Wang, Z. M. (2008). Controlled sink mobility for prolonging wireless sensor networks lifetime. *Wireless Networks*, 14(6), 831–858.
- Cano, C., Bellalta, B., Sfairopoulou, A., & Barcelo, J. (2009). A Low Power Listening with Wake up after Transmissions MAC Protocol for WSNs. *IEEE COMMUNICATIONS LETTERS*, 13(4), 221.
- Chang-ri, L., Yun, Z., Xin-hua, Z., & Zi-bo, Z. (2010). A Clustering Algorithm Based on Cell Combination for Wireless Sensor Networks. *2010 Second International Workshop on Education Technology and Computer Science*, 2, 74–77.
- Chatzigiannakis, I., Kinalis, A., & Nikolettseas, S. (2006). Sink mobility protocols for data collection in wireless sensor networks. *International Workshop on Mobility Management and Wireless Access*, 52–59.
- Chen, T. S., Tsai, H. W., Chang, Y. H., & Chen, T. C. (2013a). Geographic convergecast using mobile sink in wireless sensor networks. *Computer Communications*, 36(4), 445–458.
- Ding, P., Holliday, J., & Celik, A. (2005). Distributed Energy-Efficient Hierarchical Clustering for Wireless Sensor Networks. *IEEE International Conference on Distributed Computing in Sensor Systems*, 322–339.
- Erman, A., Dilo, A., & Havinga, P. (2012). A virtual infrastructure based on honeycomb tessellation for data dissemination in multi-sink mobile wireless sensor networks. *EURASIP Journal on Wireless Communications and Networking*, 2012(1), 17.

- Erman, A. T., & Havinga, P. (2010). Data dissemination of emergency messages in mobile multi-sink wireless sensor networks. *9th IFIP Annual Mediterranean Ad Hoc Networking Workshop, MED-HOC-NET 2010*.
- Fall, K., & Varadhan, K. (2010). *The ns manual (formerly ns Notes and Documentation)1. The VINT project, 2005 - cs.sunyit.edu*.
- Giani, A., Roosta, T., & Sastry, S. (2008). Integrity checker for wireless sensor networks in health care applications. *2008 Second International Conference on Pervasive Computing Technologies for Healthcare*, 135–138.
- Guha, S., & Khuller, S. (1998). Approximation algorithms for connected dominating sets. *Algorithmica*, 20(4), 374–387.
- Hamida, E., & Chelius, G. (2008a). Strategies for data dissemination to mobile sinks in wireless sensor networks. *IEEE Wireless Communications*, 15, 31–37.
- Hamida, E. Ben, & Chelius, G. (2008b). Strategies for Data Dissemination to Mobile Sinks in Wireless Sensor Networks. *IEEE Communications Magazine*, 15(6), 31–37.
- Han, G., Jiang, J., Shu, L., Niu, J., & Chao, H.-C. (2014). Management and applications of trust in Wireless Sensor Networks: A survey. *Journal of Computer and System Sciences*, 80(3), 602–617.
- Heinzelman, W. R., Chandrakasan, A., & Balakrishnan, H. (2000). Energy-efficient communication protocol for wireless microsensor networks. *Proceedings of the 33rd Annual Hawaii International Conference on System Sciences*, 0(c), 3005–3014.
- Huang, S.-C. H. S.-C., & Jan, R.-H. J. R.-H. (2004). Energy-aware, load balanced routing schemes for sensor networks. *Proceedings. Tenth International Conference on Parallel and Distributed Systems, 2004. ICPADS 2004*.
- Jiang, L., Huang, J., Kamthe, A., Liu, T., & Freeman, I. (2009). SenSearch : GPS and Witness Assisted Tracking. *Ad-Hoc, Mobile and Wireless Networks*, 255–269.
- Keskin, M. E., Altinel, I. K., Aras, N., & Ersoy, C. (2014). Wireless sensor network lifetime maximization by optimal sensor deployment, activity scheduling, data routing and sink mobility. *Ad Hoc Networks*, 17, 18–36.
- Khan, A. W., & Abdullah, A. H. (2015). VGDR : A Virtual Grid-Based Dynamic Routes Adjustment Scheme for Mobile Sink-Based Wireless Sensor Networks. *IEEE SENSORS JOURNAL*, 15(1), 526–534.
- Koutsonikolas, D., Das, S. M., Hu, Y. C., & Stojmenovic, I. (2010). Hierarchical geographic multicast routing for wireless sensor networks. *Wireless Networks*, 16(2), 449–466.

- Kumar, D., Aseri, T. C., & Patel, R. B. (2009). EEHC: Energy efficient heterogeneous clustered scheme for wireless sensor networks. *Computer Communications*, 32(4), 662–667.
- Kumarawadu, P., Dechene, D. J., Luccini, M., & Sauer, A. (2008). Algorithms for Node Clustering in Wireless Sensor Networks: A Survey. *2008 4th International Conference on Information and Automation for Sustainability*, 295–300.
- Lai, L., Zhang, L., & Wu, X. (2009). Personalized home medical testing technology and equipment. *FBIE 2009 - 2009 International Conference on Future BioMedical Information Engineering*, (October 2007), 401–405.
- Li, M., & Liu, Y. (2009). Underground coal mine monitoring with wireless sensor networks. *ACM Transactions on Sensor Networks*, 5(2), 1–29.
- Liaqat, M., Javaid, N., Akbar, M., Khan, Z. a., Ali, L., Hafizah, S., & Ghani, A. (2014). HEX Clustering Protocol for Routing in Wireless Sensor Network. *2014 IEEE 28th International Conference on Advanced Information Networking and Applications*, 549–554.
- Lin, C., Chou, P., & Chou, C.-F. (2006). HCDD: Hierarchical Cluster-based Data Dissemination in Wireless Sensor Networks with Mobile Sink. *International Conference on Wireless Communications and Mobile Computing*, 1189–1194.
- Lin, C. R., & Gerla, M. (1997). Adaptive Clustering for Mobile Wireless Networks. *Journal on Selected Areas in Communication*, 15(7), 1265–1275.
- Liu, X. (2012a). *A Survey on Clustering Routing Protocols in Wireless Sensor Networks*. *Sensors* (Vol. 12).
- Lu, J. L., & Valois, F. (2007). On the data dissemination in WSNs. *3rd IEEE International Conference on Wireless and Mobile Computing, Networking and Communications, WiMob 2007*, (WiMob).
- Luo, J., & Hubaux, J.-P. (2010). Joint Sink Mobility and Routing to Increase the Lifetime of Wireless Sensor Networks: The Case of Constrained Mobility. *IEEE/ACM Transactions on Networking*, 18(3), 871–884.
- Mahmoud, A. K., Khedr, M. E., & Shaaban, S. (2012). hexagonal two tier data dissemination for large scale wireless sensor networks. *2012 Japan-Egypt Conference on Electronics, Communications and Computers (JEC-ECC)*, 150–156.
- Mainwaring, A., Culler, D., Polastre, J., Szewczyk, R., & Anderson, J. (2002). Wireless Sensor Networks for Habitat Monitoring. *International Workshop on Wireless Sensor Networks and Applications*, 88–97.

- Manjeshwar, A., & Agrawal, D. P. (2002). APTEEN: A hybrid protocol for efficient routing and comprehensive information retrieval in wireless sensor networks. *International Parallel and Distributed Processing Symposium, 0(C)*, 195–202.
- Manjeshwar, a, & Agrawal, D. (2001). TEEN: a routing protocol for enhanced efficiency in wireless sensor networks. *Parallel and Distributed Processing ...*, (JANUARY 2014).
- Marta, M., & Cardei, M. (2009). Improved sensor network lifetime with multiple mobile sinks. *Pervasive and Mobile Computing*, 5(5), 542–555.
- Miller, K., & Sankaranarayanan, S. (2009). Monitoring Patient Health using Policy based Agents in Wireless Body Sensor Mesh Networks. *2009 World Congress on Nature & Biologically Inspired Computing (Nabic 2009)*, 502–507.
- Nayak, A., & Stojmenovic, I. (2009). Algorithms and Protocols for Scalable Coordination and Data Communication. In A. Nayak & I. Stojmenovic (Eds.), *Wireless Sensor and Actuator Networks* (pp. 33–35). A JOHN WILEY & SONS, INC., PUBLICATION.
- Oh, S., Lee, E., Park, S., Jung, J., & Kim, S.-H. (2010a). Communication Scheme to Support Sink Mobility in Multi-hop Clustered Wireless Sensor Networks. *International Conference on Advanced Information Networking and Applications*, 866–872.
- Onur, E. (2007). Deployment Quality Measures in Surveillance Wireless Sensor Networks. *IEEE Network*, (3), 48–53.
- Patwari, N., Ash, J. N., Kyperountas, S., H, A. O., Moses, R. L., & Correal, N. S. (2005). Locating the Nodes. *Ieee Signal Processing Magazine*, (July), 54–69.
- Schindelhauer, C. (2006). Mobility in Wireless Networks. *SOFSEM: International Conference on Current Trends in Theory and Practice of Computer Science*, 100–116.
- Sharma, N., & Nayyar, A. (2014). A Comprehensive Review of Cluster Based Energy Efficient Routing Protocols for. *International Journal of Application or Innovation in Engineering & Management (IJAIEM)*, 3(1), 441–453.
- Singh, S. K., Singh, M. P., & Singh, D. K. (2010a). Energy-efficient Homogeneous Clustering Algorithm for Wireless Sensor Network. *International Journal of Wireless & Mobile Networks (IJWMN)*, 2(3), 49–61.
- SUDHA, M. N., VALARMATHI, M. L., RAJSEKAR, G., MATHEW, M. K., DINESHRAJ, N., & RAJBARATH, S. (2009). Minimization of Collision in Energy Constrained Wireless Sensor Network. *Wireless Sensor Network*, 1(4), 350–357.
- Sun, M., Liu, Q., & Jiang, M. (2008). An implementation of remote lighting control system based on zigbee technology and soc solution. *ICALIP 2008 - 2008*

*International Conference on Audio, Language and Image Processing, Proceedings*, 629–632.

- Szewczyk, B. R., Osterweil, E., Polastre, J., Hamilton, M., Mainwaring, A., & Estrin, D. (2006). Geography-informed Energy Conservation for Ad Hoc Routing. *Communications of the ACM*, 47(6), 34–40.
- Szewczyk, R., Polastre, J., Mainwaring, A., & Culler, D. (2004). Lessons from a Sensor Network Expedition. *Wireless Sensor Networks*, 307–322.
- Taheri, H., Neamatollahi, P., Younis, O. M., Naghibzadeh, S., & Yaghmaee, M. H. (2012). An energy-aware distributed clustering protocol in wireless sensor networks using fuzzy logic. *Ad Hoc Networks*, 10(7), 1469–1481.
- Thanigaivelu, K., & Murugan, K. (2012). Grid - based Clustering with Predefined Path Mobility for Mobile Sink Data Collection to Extend Network Lifetime in Wireless Sensor Networks. *IETE Technical Review*, 133–148.
- Tillapart, P., Thammarojsakul, S., Thumthawatworn, T., & Santiprabhob, P. (2005). An Approach to Hybrid Clustering and Routing in Wireless Sensor Networks. *2005 IEEE Aerospace Conference*, 1–8.
- Wang, C.-F., Shih, J.-D., Pan, B.-H., & Wu, T.-Y. (2014). A Network Lifetime Enhancement Method for Sink Relocation and Its Analysis in Wireless Sensor Networks. *IEEE Sensors Journal*, 14(6), 1932–1943.
- Wang, D., Xu, L., Peng, J., & Robila, S. (2009). Subdividing hexagon-clustered wireless sensor networks for power-efficiency. *Proceedings - 2009 WRI International Conference on Communications and Mobile Computing, CMC 2009*, 2, 454–458.
- Wang, J., Zuo, L., Shen, J., Li, B., & Lee, S. (2014). Multiple mobile sink-based routing algorithm for data dissemination in wireless sensor networks. *CONCURRENCY AND COMPUTATION: PRACTICE AND EXPERIENCE*, 27(10), 2656–2667.
- Wang, Y. (2008). Topology Control for Wireless Sensor Networks. *Wireless Sensor Networks and Applications*, 113–147.
- Winkler, M., Tuchs, K., Hughes, K., & Barclay, G. (2008). Theoretical and practical aspects of military wireless sensor networks. *Journal of Telecommunications and Information Technology*, 2, 37–45.
- Xie, G., & Pan, F. (2016). Cluster-Based Routing for the Mobile Sink in Wireless Sensor Networks with Obstacles. *IEEE Access*, 4, 2019–2028.
- Ye, F., Luo, H., Cheng, J., Lu, S., & Zhang, L. (2002). A Two-Tier Data Dissemination Model for Large-scale Wireless Sensor Networks \* Categories and Subject Descriptors. *International Conference on Mobile Computing and Networking*, 148--159.

Younis, O., & Fahmy, S. (2004a). HEED: a hybrid, energy-efficient, distributed clustering approach for ad hoc sensor networks. *IEEE Transactions on Mobile Computing*, 3(4), 366–379.

Zhang, H., & Arora, A. (2003). GS3: Scalable self-configuration and self-healing in wireless sensor networks. *Computer Networks*, 43(4), 459–480.



© COPYRIGHT UPM