



UNIVERSITI PUTRA MALAYSIA

***DEVELOPMENT OF ON-FARM STRUCTURES AND WATER DELIVERY
MANAGEMENT MODEL FOR IMPROVED RICE IRRIGATION
PRACTICES, TANJUNG KARANG, MALAYSIA***

MOHD YAZID BIN ABDULLAH

FK 2016 19



**DEVELOPMENT OF ON-FARM STRUCTURES AND WATER DELIVERY
MANAGEMENT MODEL FOR IMPROVED RICE IRRIGATION PRACTICES,
TANJUNG KARANG, MALAYSIA**

By

MOHD YAZID BIN ABDULLAH

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in
Fulfillment of the Requirements for the Degree of Doctor of Philosophy**

April 2016

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of and material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



DEDICATION

This work is dedicated to my beloved parents, wife, children and siblings.



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the Degree of Doctor of Philosophy.

**DEVELOPMENT OF ON-FARM STRUCTURES AND WATER DELIVERY
MANAGEMENT MODEL FOR IMPROVED RICE IRRIGATION PRACTICES,
TANJUNG KARANG, MALAYSIA**

By

MOHD YAZID BIN ABDULLAH

April 2016

Chairman : Professor Mohd Amin Mohd Soom; PhD, P.Eng.
Faculty : Engineering

This pilot project study was conducted in Tanjung Karang Rice Irrigation Scheme, Selangor. The problems of the tertiary canal and on-farm water management in the scheme are related to the design of the tertiary canal; structures employed and water delivery management system for different modes of irrigation requirement. Other problems were related to the design and distribution of the existing structures along the tertiary canal and length of concrete canal measured up to seven kilometer serving up to 230 paddy lots caused the difficulties in delivering water timely, equitably and adequately to the whole canal length for different water delivery modes. As to overcome these problems, this study proposed development of three new on-farm structures and water delivery management models. Three structures in the tertiary irrigation canal and on-farm levels which were developed and evaluated in this study are: (1) flexible field offtake and automated float type flow control valve structure; (2) tertiary canal water level regulator or check structure and (3) field drainage outlet control structure. This water delivery management model was developed for four modes of irrigation supply for rice irrigation requirements, namely presaturation, second flooding, supplementary and termination of irrigation supply. The developed structures were tested in the laboratory and at the pilot project site for performance in terms of suitability and functionality in water delivery to obtain their accuracy, sensitivity and flexibility in different water delivery modes. The on-site evaluation were conducted to evaluate their performance in water delivery for different delivery modes, effectiveness in improving farm related activities in rice production and overall crop planting duration. The tests of these structures showed encouraging results for their respective functions in improving water delivery management in tertiary canal and on farm rice irrigation system. The most outstanding result of the laboratory tests was the stable and close to linear nature of flow through the flexible field offtake, for flow rate up to 10 liter/sec and maximum delivering capacity of up to 22 liter/sec. The results indicated its suitability to function as a flow measurement and flow control structures to provide a stable and accurate water delivery for supplementary irrigation and meet the flexibility of faster delivery for presaturation and second flooding other irrigation practices for rice cultivation.

Sensitivity analysis of the offtake indicated that there was about 175 mm allowable water level fluctuation that provide flexibility and advantage to deal with the possible different in gate submergence in the canal operation or other reasons. Improved presaturation water delivery with the utilization of the newly developed flexible field offtake was based on the fact that faster water delivery in a shorter duration has reduced the amount of water required for presaturation. Through the utilization of the developed delivery management model for supplementary irrigation, the advantages of minimizing perturbation in tertiary canal flow, reducing farmers' task in managing on farm irrigation practice, harvesting and capturing rainfall in paddy fields as well as controlling the run off flow from irrigation and rainfall to the drainage system could all be realized. It was successfully proven that the developed model with the support of efficient farm machinery service provider and responsive farmers result in shorter presaturation duration, saving a significant amount of water, and also shortened the overall duration of seasonal rice production significantly.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk Ijazah Doktor Falsafah

**PEMBANGUNAN STRUKTUR-STRUKTUR PERINGKAT LADANG DAN
MODEL PENGURUSAN PENYAMPAIAN AIR BAGI PENAMBAHBAIKAN
AMALAN PENGAIRAN PADI, TANJUNG KARANG, MALAYSIA**

Oleh

MOHD YAZID BIN ABDULLAH

April 2016

Pengerusi : Profesor Mohd Amin Mohd Soom; PhD, P.Eng.
Fakulti : Kejuruteraan

Kajian projek perintis ini telah dilaksanakan di Skim Pengairan Padi Tanjung Karang, Selangor. Masaalah utama bagi sistem tersier dan ladang di skim ini adalah berkaitan dengan rekabentuk taliair tersier, struktur-struktur yang digunakan dan sistem pengurusan penyampaian air bagi memenuhi keperluan pengairan air untuk tanaman padi yang berubah. Masaalah lain adalah berkaitan dengan rekabentuk dan taburan struktur-struktur sepanjang taliair, panjang taliair tersier yang mencapai tujuh kilometer panjang dengan bilangan lot padi mencapai 230 lot menimbulkan kerumitan untuk menyampaikan air mengikut jadual, saksama dan mencukupi ke seluruh kawasan mengikut bentuk penyampaian yang berbeza berdasarkan keperluan air bagi amalan penanaman padi masa kini. Untuk menyelesaikan masaalah tersebut, kajian ini mencadangkan pembangunan tiga struktur baru dan pembangunan model pengurusan penyampaian air. Tiga jenis struktur peringkat tersier dan ladang yang telah dibangunkan dan dinilai dalam kajian ini: (i) Offtake sawah fleksibel beserta sistem injap kawalan aliran automatik jenis pelampung; (ii) struktur kawalan paras air jenis rata dan (iii) struktur kawalan saliran keluar air sawah. Model-model ini telah dibangunkan bagi empat bentuk pembekalan air pratepuan (presaturation), banjirair kedua, bekalan pencukupan semasa pertumbuhan padi dan penamatan bekalan dan kawalan saliran sebelum penuaian padi. Penilaian terhadap model dengan struktur yang telah diubahsuai kemudiannya dilakukan di tapak projek perintis bagi menilai prestasi penyampaian air untuk keperluan bekalan air yang berlainan, dalam meningkatkan keberkesanan aktiviti berkaitan pengeluaran padi serta tempoh keseluruhan bagi pengeluaran padi semusim. Pengujian-pengujian tersebut telah memperlihatkan keputusan yang memberangsangkan mengikut fungsi masing-masing dalam meningkatkan mutu penyampaian air. Keputusan yang paling terserlah dari pengujian di makmal hidrolik adalah kadar aliran menghampiri linear bagi aliran melalui flexible field offtake bagi kadar aliran sehingga 10 liter sesaat dan kapasiti penyampaian maksima 22 liter sesaat. Keputusan ini dan pengiraan sensitiviti yang dibuat menunjukkan bahawa struktur ini sesuai untuk berfungsi sebagai struktur pengukuran kadar alir dan kawalan air bagi penyampaian air bagi tujuan bekalan air untuk bekalan pencukupan. Pengujian sensitiviti mendapati terdapat 175 mm ruang perubahan turun naik paras air untuk

mengealkan kesesuaian struktur ini yang boleh memberikan fleksibiliti dan mengatasi kemungkinan perbezaan paras penenggelaman pintu air semasa pengoperasian taliair diakibatkan oleh perubahan paras air dalam taliair tersier, jarak relatif dari pengatur paras air, pemendapan taliair atau sebab-sebab lain. Oleh itu, penambahbaikan bekalan air pratepuan dengan menggunakan flexible field offtake dibuat berdasarkan fakta bahawa penyampaian air yang cepat dalam tempoh yang pendek telah mengurangkan jumlah air yang diperlukan untuk bekalan pratepuan. Saranan untuk mengamalkan pembekalan air untuk bekalan pencukupan melalui penyampaian secara berterusan mengikut keperluan harian telah membolehkan kelebihan meminimalkan pertubasi paras air dalam taliair tersier, mengurangkan tugas petani dalam menguruskan praktis pengairan peringkat ladang, penuaian dan penakungan air hujan dan pengawalan aliran keluar air hujan dan air pengairan dapat direalisasikan. Keputusan ujian juga telah mengesahkan bahawa model yang dibangunkan dengan disokong oleh pembekalan jentera pertanian yang cekap serta petani yang responsif; telah berjaya memendekkan tempoh pratepuan, menjimatkan air dengan banyak, justeru memendekkan tempoh keseluruhan pengeluaran padi dengan signifikan.

ACKNOWLEDGEMENTS

Praise be to Allah Almighty, the Cherisher and Sustainer of the Universe. May the peace and blessings of Allah Almighty be upon Muhammad, the Seal of the Prophets. First and foremost, the student would like to express his sincere gratitude and indebtedness to his supervisor, Prof. Ir. Dr. Mohd Amin Mohd Soom, for his unreserved support, persistent guidance, sincere advice and encouragement all the way towards the completion of this study. The student is also grateful and thankful to his supervisory committee members, Professor Ir. Dr Lee Teang Shui and Associate Professor Dr. Abdul Rashid bin Mohamed Shariff for their constructive advice, fruitful suggestions and useful guidance. The student is very grateful and sincerely appreciate all the members of the teaching staff especially Dr. Aimrun Wayayok and Dr. Md. Rowshon Kamal for their advice. The student must acknowledge Mr. Muhammad Maina and Mr. Sobri Hj Merais for the data collection support and the regular and continuous discussion and exchange of ideas to broaden the understanding on the issues of the study. Thanks to the support from Directors and Deputy Directors of Irrigation and Agricultural Drainage, Ministry of Agriculture and Agro-based Industry, Malaysia, Dato' Azahari, Tuan Hj Syed Abdul Hamid Syed Shuib, Tuan Hj Abdul Halim bin Abdul Jalil and Puan Hajjah Zalilah binti Selamat and Tuan Ir Hj Ahmad Jamaluddin Shaaban, Director General of NAHRIM and all NAHRIM staffs.

Acknowledgement is also extended to the staff of IADA Barat Laut Selangor and Sawah Sempadan field staff. Special thanks to Mr. Zulkifli Sulaiman and Block CJO Water User Group for his continuous and dedicated efforts and support to bring farmers' cooperation that enabled the study to be successfully conducted. Thanks to Mr. Hafifi and all his staff from Afftech Corporation for their support in data collection for this study. The student never forget the dedication of his mother and father and the difficulties they went through to ensure the success of their children's search of knowledge. May Allah bless all of them forever.

The student would like to express a special gratitude and acknowledgement to his beloved wife, sons, daughters, brothers and sisters for their strong support.

I certify that a Thesis Examination Committee has met on 15 April 2016 to conduct the final examination of Mohd Yazid bin Abdullah on his thesis entitled "Development of On-Farm Structures and Water Delivery Management Model for Improved Rice Irrigation Practices, Tanjung Karang, Malaysia" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Doctor of Philosophy.

Members of the Thesis Examination Committee were as follows:

Biswajeet Pradhan, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Thamer Ahmad Mohammad Ali, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Abdul Halim bin Ghazali, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Rameshwar S. Kanwar, PhD

Professor
Iowa State University
United States
(External Examiner)



ZULKARNAIN ZAINAL, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 26 July 2016

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory Committee were as follows:

Mohd Amin Mohd Soom, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Lee Teang Sui, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Abdul Rashid Mohd Shariff, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

BUJANG BIN KIM HUAT, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software

Signature: _____

Date: _____

Name and Matric No.: Mohd Yazid Bin Abdullah, GS 19512

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) were adhered to.

Signature: _____

Name of Chairman
of Supervisory
Committee:

Professor
Dr. Mohd Amin Mohd Soom

Signature: _____

Name of Member
of Supervisory
Committee:

Professor
Dr. Lee Teang Sui

Signature: _____

Name of Member
of Supervisory
Committee:

Associate Professor
Dr. Abdul Rashid Mohd Shariff

TABLE OF CONTENTS

		Page
	ABSTRACT	i
	ABSTRAK	iii
	ACKNOWLEDGEMENTS	v
	APPROVAL	vi
	DECLARATION	viii
	LIST OF TABLES	xiv
	LIST OF FIGURES	xvi
	LIST OF ABBREVIATIONS	xxi
	CHAPTER	
1	INTRODUCTION	1
	1.1 Background	1
	1.2 Importance of the Study	3
	1.3 Statement of Problem	5
	1.4 Research Questions	7
	1.5 Aims and Objectives	7
	1.6 Scopes and Limitations	8
	1.7 Thesis Organization	9
2	LITERATURE REVIEW	10
	2.1 Introduction	10
	2.2 Rice Production and Irrigation Schemes in Malaysia	10
	2.2.1 Development of Irrigation Schemes in Malaysia	11
	2.3 Tanjung Karang Rice Irrigation Scheme	12
	2.3.1 Introduction to the Scheme Area	12
	2.3.2 Previous Studies in the Scheme	12
	2.3.3 Existing Structures and Their Constrains	14
	2.4 Water Delivery and System Performance	22
	2.4.1 Water Delivery Performance Indicators	24
	2.5 MASSCOTE Approach, RAPs and Performance of Irrigation Scheme	26
	2.5.1 RAP External Indicators	26
	2.5.2 RAP Internal Indicators	27
	2.5.3 Irrigation Management Constraints in the Study Area	29
	2.6 Irrigation Canal Water Control System	30
	2.6.1 Flow Control and Measurement at Delivery Points	31
	2.6.2 Hydraulics Behavior of Diversion Structures	32
	2.6.3 Canal Water Delivery and Irrigation Scheduling	37
	2.6.4 Sensitivity Indicators for Canal Irrigation Water Control	37
	2.6.5 Structure Sensitivity in Irrigation System Management	38
	2.6.6 Conveyance and Delivery-Oriented Sensitivities	40
	2.6.7 Automation for Irrigation Canal Water Control	41

2.6.8	Automatic Control Performance of Irrigation Systems	42
2.7	Modeling of Irrigation Systems	43
2.8	Control Structures in Open Channel Irrigation System	44
2.8.1	Adjustment of Irrigation Structures	44
2.8.2	Type of Control: Upstream and Downstream	45
2.8.3	Defining the Controlled Water Variable	45
2.8.4	Organizing the Operation of Irrigation Structures	45
2.8.5	Operation of Single Structure: Offtake	46
2.8.6	Operation of Single Structure: Regulator	46
2.9	Best Practices in Irrigation Management	47
2.10	Latest Publication on Irrigation Practices on Water Delivery in Other Parts of the World	48
2.11	Summary	50
3	DESIGN AND LABORATORY EVALUATION OF FLEXIBLE FIELD OFFTAKE STRUCTURES AT TERTIARY CANAL	52
3.1	Introduction	52
3.1.1	Objectives	52
3.2	Structure Component, Configuration and Design Consideration	53
3.2.1	Flexible Field Offtake Structure	53
3.2.2	Float Type Automated Flow Control Structure	62
3.2.3	Flat Gate Regulator Structure	66
3.2.4	Field Drainage Outlet Control Structure	67
3.3	Methodology and Data Collection for Laboratory Evaluation of Flexible Field Offtake	70
3.3.1	Material and Method	70
3.3.2	Data Collection	71
3.4	Results and Discussions	77
3.5	Summary	108
4	FIELD PERFORMANCE EVALUATION OF THE ON FARM STRUCTURES	110
4.1	Introduction	110
4.1.1	Structures Tested in This Study	111
4.1.2	Research Questions	112
4.1.3	Objectives of the Study	112
4.2	Methodology and Data Collection	113
4.2.1	Methodology and Data Collection for Field Testing for the Flat Gate Regulator and Flexible Field Offtake in Tertiary Canal	113
4.2.2	Methodology and Data Collection for Field Testing for Flexible Field Offtake and Automated Float Type Flow Control Structure	123
4.3	Results and Discussions	125
4.3.1	Field Testing for the Flat Gate Regulator and Flexible Field Offtake in Tertiary Canal	125

4.3.2	Result and Discussions on Field Testing for Flexible Field Offtake and Automated Float Type Flow Control Structure	137
4.3.3	Comparison of the Functionality of Flexible Field Offtake with Continuous and Automated Flow Control Structure Delivery for Various Parameters	145
4.3.4	Suggestions on Field Application of the Developed Structures	148
4.4	Summary	151
5	DEVELOPMENT AND PERFORMANCE EVALUATION OF WATER DELIVERY MANAGEMENT MODEL	154
5.1	Introduction	154
5.1.1	Research Questions	155
5.1.2	General and Specific Objectives	155
5.2	Development of Improved Water Delivery Management Models	156
5.2.1	Water Delivery Management Model Design Considerations	156
5.2.2	Development of Operational Management for Presaturation	157
5.2.3	Development of Operational Management for Second Flooding	159
5.2.4	Development of Water Delivery Management for Crop Growing Stage	161
5.2.5	Drainage Prior to Harvesting	163
5.3	Methodology and Data Collection	164
5.3.1	Methodology and Data Collection for Evaluation of Water Delivery Development Model for Presaturation and Second Flooding	164
5.3.2	Methodology and Data Collection for Evaluation of Water Deliver Development Model for Supplementary Irrigation	166
5.3.3	Methodology and Data Collection for Evaluation of the Effectiveness of Water Delivery Management Model	173
5.4	Results and Discussions	178
5.4.1	Evaluation of Water Delivery Development Model for Presaturation and Second Flooding	178
5.4.2	Evaluation Performance of Water Delivery Management Model for Supplementary Irrigation Supply	181
5.4.3	Evaluation of the Effectiveness Water Delivery Management Model for Farm Activities and Overall Planting Duration	184
5.5	Summary	188
6	CONCLUSION AND RECOMMENDATIONS	190
6.1	Conclusions	190
6.2	Recommendations for Future Research	192

REFERENCES	193
APPENDICES	198
BIODATA OF STUDENT	223
LIST OF PUBLICATIONS	224



LIST OF TABLES

Table	Page
2.1 Several salient features of Tanjung Karang Irrigation Scheme	12
2.2 RAP's external Indicators of Main Irrigation Schemes in Malaysia	27
2.3 RAP's internal indicators of different canal levels for Tanjung Karang Rice Irrigation Scheme (TKRIS)	28
2.4 RAP's Water Delivery Service performance indicators for Tanjung Karang Rice Irrigation Scheme in 2009	29
3.1 Presaturation water requirement in depth of water for different presaturation duration and water delivery rate in liter/sec/ha for TKRIS	55
3.2 Second flooding water requirement in depth of water for different duration and water delivery rate in liter/sec/ha for TKRIS	55
3.3 Daily supplementary irrigation water requirement in depth of water for and water delivery rate in liter/sec/ha for TKRIS	56
3.4 Water delivery requirement for different modes of water delivery for different paddy lot sizes for TKRIS	57
3.5 Estimation of the coefficient of discharge (Cd) for the flexible field offtake	101
3.6 Water delivery flow rate for different pipe arrangements for head difference of 350 mm with gate openings of 125 mm and 150 mm	102
4.1 Regulator Sensitivity for different discharges and heads for regulator at CH 439m of TASS 7	136
4.2 Regulator Sensitivity for different discharges and heads for regulator at CH 982m of TASS 7	136
4.3 Comparisons of the performance and functionality of flexible field offtake and field offtake with automated flow control valve	146
5.1 Depth of water required to achieve pre-saturation requirement for different durations in Tanjung Karang Rice Irrigation Scheme	157
5.2 Presaturation water requirement lot no. 2, 3 and 4 for Season 2 /2012	158
5.3 Discharge observed along TASS 7 (1 -28 July 2013)	167
5.4 Discharge observed along TASS 8 (1 -28 July 2013)	168

5.5	Daily water delivery to each block for TASS 7 (1-28 July 2013)	169
5.6	Daily water delivery to each block for TASS 8 (1-28 July 2013)	170
5.7	Daily water delivery for TASS 7 during supplementary supply	171
5.8	Daily water delivery for TASS 8 during supplementary supply	171
5.9	Daily water delivery for TASS 9 during supplementary supply	172
5.10	Daily water delivery for TASS 10 during supplementary supply	172
5.11	Progress of weekly field activities in TASS 7	174
5.12	Progress of weekly field activities in TASS 8	175
5.13	Expected progress of harvesting for Block C, J, O and Overall of TASS 7	176
5.14	Expected progress of harvesting for Block C, J, O and Overall of TASS 8	177

LIST OF FIGURES

Figure		Page
2.1	Salient Features in Tanjung Karang Rice Irrigation Scheme	13
2.2	Existing Concrete Conduit Canal	16
2.3	Existing Field Offtake Pipe	17
2.4	Existing Siphon Pipes	19
2.5	Existing Check Structures	20
2.6	Existing Field Drainage Outlet Control Structures	21
2.7	Overshoot Gate	32
2.8	Schematic Diagram of Water Behavior in Overshoot Gates	33
2.9	Undershoot Gate Behavior of Water under Free Flow	33
2.10	Undershoot Gate Behavior of Water under Submerged Flow	34
2.11	Orifice Gate under Free Fall Condition	36
2.12	Orifice Gate under Submerged Flow Condition	36
3.1	Design Drawings of Flexible Field Offtake	61
3.2	Photos of Developed Flexible Gate and its Installation at the Pilot Project Site	62
3.3	Component Arrangement of Automated Float Type Flow Control Valve	65
3.4	Site Installation for Automated Float Type Flow Control Valve	65
3.5	Design Drawings of Flat Gate Regulator	66
3.6	Site Installation of Flat Gate Regulator	67
3.7	Plan View and Cross Section Drawing of the Overall System Of The Adjustable Field Drainage Outlet Control Structure	69
3.8	Site Installation of the Adjustable Field Drainage Outlet Control Structure	70
3.9 (a)	Plan View of the Experimental Setup for Calibration of Offtake Gate	72

3.9 (b)	Sectional Elevation View of Pipe and Measuring Channel	73
3.10 (a)	Photos of the Laboratory Experimental Setup Showing Testing Channel and Stilling Tank	74
3.10 (b)	Photos of the Laboratory Experimental Setup Showing Suction Pipes and Water Source	75
3.10 (c)	Photos of the Laboratory Experimental Setup Showing Testing Channel and Installation of Offtake	75
3.10 (d)	Photos of the Experimental Setup Showing the Location of Three Sensors of ISCO Flow Meter	76
3.11	Relationship of the Discharge and Head for Different Opening for 1.0 m Pipe With Elbow	81
3.12	Relationship of the Discharge and Head for Different Opening for 1.0 m Pipe Without Elbow	82
3.13	Relationship of the Discharge and Head from Gate Bottom for Different Gate Opening for 3.0 m Pipe with Elbow	83
3.14	Relationship of Flow Rate and Head Difference for Different Gate Opening for 6.0 m Pipe with Elbow	84
3.15	Relationship of Flow Rate and Head Difference for Various Gates Opening for 1.0 m Pipe with Elbow	86
3.16	Relationship of Flow Rate and Head Difference for Various Gates Opening for 1.0 m Pipe without Elbow	87
3.17	Relationship of Flow Rate and Head Difference for Various Gates Opening for 3.0 m Pipe with Elbow	88
3.18	Relationship of Flow Rate and Head Difference for Various Gates Opening for 6.0 m Pipe with Elbow	89
3.19	Relationship of Flow Rate and Gate Opening (70 mm and Less) for Various Head Difference for 1.0 m Pipe with Elbow	90
3.20	Relationship of Flow Rate and Gate Opening (70 mm and Less) for Various Head Difference for 1.0 m Pipe without Elbow	91
3.21	Relationship of Flow Rate and Gate Opening (70 mm and Less) for Variou Head Difference for 3.0 m Pipe with Elbow	92
3.22	Relationship of Flow Rate and Gate Opening (70 mm and Less) for Various Head Difference for 6.0 m Pipe with Elbow	93

3.23	Relation of Sofftake to Head Difference for Various Gate Opening for 1.0 m Pipe Length with Elbow	96
3.24	Relation of Sofftake to Head Difference for Various Gate Opening for 1.0 m Pipe Length without Elbow	97
3.25	Relation of Sofftake to Head Difference for Various Gate Opening for 3.0 m Pipe Length with Elbow	98
3.26	Relation of Sofftake to Head Difference for Various Gate Opening for 6.0 m Pipe Length with Elbow	99
3.27 (a)	Flexible Field Offtake with Stick Gauge to Measure Head Difference	103
3.27 (b)	Flexible Field Offtake with Developed 2 mm Steps Wise Gate Opening	103
3.28	Flow Rate vs. Gate Openings Chart of Flexible Field Offtake with 1.0 meter Pipe Length with Elbow	104
3.29	Flow Rate vs. Gate Openings Chart of Flexible Field Offtake with 1.0 meter Pipe Length without Elbow	105
3.30	Flow Rate vs. Gate Openings Chart of Flexible Field Offtake with 3.0 meter Pipe Length with Elbow	106
3.31	Flow Rate vs. Gate Openings Chart of Flexible Field Offtake with 6.0 meter Pipe Length with Elbow	107
4.1	Travelling Path of the Beam and Dimensional Specification of the Microflex-C Sensor in (mm)	114
4.2	Water Level Sensor	115
4.3	Water Level Sensors, Lysimeter and Telemetry Station at TASS 7	115
4.4	PCM 4 Portable Measurement System Employed to Measure Flow Rate in the Tertiary Canal	116
4.5	Sawah Sempadan Compartment in Tanjung Karang Rice Irrigation Scheme Showing Block C, J, O and Location of the Experimental Site	117
4.6	Arrangement of the Gate Regulator Structures, Sensors, Telemetry Station and Lysimeter Installation at TASS 7	118
4.7	Tertiary Canal Conduit TAAS 7 Profile and Allowable Maximum and Minimum Water Level from CH 00 to CH 1000m	119

4.8	Photos of Tertiary Canal TASS 7, Structures and Equipment Installed for the Field Offtakes and Flat Gate Regulator Tests	120
4.9	Photos of Structures and Equipment Installed for the Field Tests For The Performance of Flexible Field Offtake and Flat Gate Regulator Structure	121
4.10	Lysimeters and Measuring Instruments Installation at TASS 7 for Water Level Monitoring For Field Offtake Performance Tests	123
4.11	Structures and Measuring Instruments Installation at TASS 7 for Testing Automated Float Type Control Structures	124
4.12	Tertiary Canal Profile and Allowable Maximum and Minimum Water Level For TASS 7	127
4.13	Water Level in the Tertiary Canal TASS 7 for Various Flow Rate For CH 00 to CH 439	129
4.14	Water Level in the Tertiary Canal TASS 7 for Various Flow Rates For CH 00 To 982	130
4.15	Water Level in Tertiary Canal TASS 7 from CH 00 to CH 439m for Various Flow Rate with Flat Gate Regulator Spilling of 3.887m Located at CH 430	133
4.16	Water Level in Tertiary Canal TASS 7 from CH 00 To CH 982m for Various Flow Rate with Flat Gate Regulator Spilling of 3.77m Located at CH 982	134
4.17	Field Water Depth of Lot No. 3117 with Continuous Delivery through Field Offtake from 1st to 20th September 2013	140
4.18	Field Water Depth of Lot No. 3137 with Continuous Delivery through Field Offtake from 1st to 20th September 2013	141
4.19	Field Water Depth of Lot No. 3125 with Delivery through Field Offtake with Automated Flow Control Valve from 1st to 20th September 2013	143
4.20	Field Water Depth of Lot No. 3121 with Delivery through Field Offtake with Automated Flow Control Valve from 1st to 20th September 2013	144
5.1	Flow Rate against Gate Opening Of Various Head Difference Chart for 1m Pipe with Elbow	160
5.2	Flow Rate against Opening of Various Head Difference Chart for 1m Pipe with Elbow (Gate Opening of 2mm Step-Wise for Gate Opening of 70mm and Below)	162

5.3	Tertiary Canals (TASS 7, TASS 8, TASS 9 and TASS 10), Irrigation Blocks and Location of Flow Rate Measurement Stations	165
5.4	Water Delivery to the Tertiary Canal TASS 7 and the Blocks	179
5.5	Water Delivery to the Tertiary Canal TASS 8 and the Blocks	180
5.6	Supplementary Irrigation for the Tertiary Canals TASS 7 for 6th, 10th and 17th of September 2013	182
5.7	Supplementary Irrigation for the Tertiary Canal TASS 8 for 6th, 10th and 17th Of September 2013	182
5.8	Supplementary Irrigation for the Tertiary Canals TASS 9 for 6th, 10th and 17th of September 2013	183
5.9	Supplementary Irrigation for the Tertiary Canals TASS 10 for 6th, 10th and 17th Of September 2013	183
5.10	Progress of Field Activities at TASS 7 for Block C, J, O and Overall for First 4 Weeks after Starting of Irrigation Supply	185
5.11	Progress of Field Activities in TASS 8 for Block C, J, O and Overall for First 4 Weeks after Starting of Irrigation Supply	185
5.12	Expected Progress of Harvesting for Block C, J, O and TASS 7	187
5.13	Expected Progress of Harvesting for Block C, J, O and TASS 8	187

LIST OF ABBREVIATIONS

BPSP	Bahagian Pengairan & Saliran Pertanian (Irrigation and Agricultural Drainage Division, MOA)
DID	Department of Irrigation and Drainage
DOA	Department of Agriculture
DR	Drainage Requirement
ET	Evapotranspiration
ET _c	The crop evapotranspiration is the evapotranspiration from a disease-free, well-fertilized and under optimal soil-water and agronomic conditions growing crop ($ET_c = ET_o * K_c$).
ET _o	Reference crop evapotranspiration (or reference evapotranspiration is defined as the evapotranspiration rate (for example mm day ⁻¹) from a reference surface which is hypothetically a well-watered grass crop with specific characteristics.
ET _c	The crop coefficient (K_c) is an experimentally determined coefficient relating ET_c to ET_o ($ET_c = ET_o * K_c$)
ETP	Economic Transformation Program
FSL	Full Supply Level
FAO	Food and Agriculture Organization
IADA	Integrated Agricultural Development Area
JICA	Japan International Cooperation Agency
MASSCOTE	Mapping System and Services for Canal Operation Techniques
MOA	Ministry of Agriculture and Agro-base Industry, Malaysia
RAP	Rapid Appraisal Procedure
SWC	Soil water content
SWT	Soil water tension
TASS	Taliair Sawah Sempadan (Tertiary Canal in Sawah Sempadan Compartment)

CHAPTER ONE

INTRODUCTION

1.1 Background

Water is a scarce resource all over the world and irrigation consumes more than 70% of the fresh water resources, hence management of the agricultural water resources has become an important issue. As water resources are stretched between competing demands, irrigation efficiency must be increased at all levels of irrigation system (Guera et al., 1998). A key component of improving irrigation efficiency is the accurate measurement and control of water flow rate as well as water level control in the main canal, secondary canal, and tertiary canal. Increasing irrigation efficiency through water conservation, management of field for high water productivity, management of non-point source pollutants, rainwater harvesting and storing all would require efficient management at the tertiary canal and on-farm level. The water losses in irrigation channels are large, but it is recognized that these losses can be substantially reduced by employing improved and efficient modern control systems.

A major part of the 250 million hectares irrigated land worldwide is served by surface canal systems where 142 million hectares is cultivated with rice (UN, 2007). In surface canal systems, performance is generally low and improvements are critically needed to improve water resource management, service to irrigated agriculture and cost-effectiveness of infrastructure management for efficient irrigation water schedule.

Allocation, distribution and control of water is the core process of water management in irrigation system. It is the process by which the available water is divided and equitably distributed to the smaller command units or irrigation blocks within the system, which in turn is distributed further down to the individual water user (farmers) who will control and direct to the crop root zones in particular fields. Chambers (1980) stated that 'who gets what, where and when', is the point as far as irrigation is concerned. Surrounding this issues, human actions and interactions take place resulting in the re-design, re-construction, and re-shaping of the physical and organizational arrangements (Pradhan, 1996). The process of water control in canal irrigation and on-farm using modern technology therefore becomes the main thrust of this study.

Canal irrigation has been traditionally practised in Malaysia for many decades. However the development of modern canal irrigation systems that can ensure flexibility is yet to be adopted. The increasing investment by the government in the development of modern canal irrigation systems, especially after realization of the need to manage water as a scarce resources. Despite this effort, however, there is a general contention that most of the government-built modern canal irrigation systems do not function optimally and therefore more water is being wasted daily. The reason for this is not clear since there are almost no scientific studies into what actually happens in these systems as regards to their design and water allocation and distribution. Hence there is a need to examine and explore

irrigation water allocation and distribution, the technical design and the operational features of the existing tertiary canals with the aim to innovate some of its facilities. It should be possible to develop appropriate methods for improving water control in public canal irrigation systems.

Irrigation water scheduling at farm level constitutes the most critical part in on-farm water management, a plan and most suitable situations, a decision on when, how long and with what flow rate, expressed in absolute value or as a sharing proportion, water should be delivered at the off-take gate to meet crop water requirement. It would be nice if every farm could be supplied with enough irrigation water from the canal. The farmers would then be in a position to fully master their irrigation schedules and to best manage irrigation for their crops and gain from farming business, an indicator to the on-farm constraints which could be constraints from economics and/or the environment.

Current issues of food shortage and significant increase of food prices pose a challenge to many countries including Malaysia, to increase food production. In order to meet future food demand, increase farmers' income and the contribution to Gross National Income (GNI), The Government of Malaysia, through the Economic Transformation Program (ETP), plan to construct new and upgrading the existing infrastructures including the tertiary canals to facilitate the economic growth in rice production. The main constraints to increase rice production include limited land and water resources, competition for available water resources with the other sectors, low efficiency in irrigation water use, poor management of the irrigation systems, non-availability of appropriate infrastructure for modern irrigation management and environmental degradation.

The success of any irrigation project in meeting water requirements depends to a large extent on the proper functioning of its water conveyance and distribution system. Proper functioning is essentially identified with proper operation of the system so that equitable and reliable apportionment of water among users and the conveyance of water with minimum losses are ensured. While operation of an irrigation system is dependent on good organizational and institutional backing, its effectiveness is basically dependent on a well-planned, designed, constructed and maintained network from the source of the water supply down to farmers' fields.

Optimum irrigation management and control has different meanings to different stakeholders. Levine (1980) pointed out that 'what is optimum from an irrigation system point of view is not necessarily optimum from the farmers' point of view; these optima must be reasonably close for efficient use of the resources available to both irrigation system and farmers alike.

Supply system flexibility is the main factor in modern irrigation structures to increase water productivity and increase crop yield. Flexibility means ability to adjust the frequency, rate and duration of flow to suit crop water requirement, requirement of land preparation and need to serve recommended field activities and agricultural practices to

optimize water, input or labor. The practices are required to increase yield (quality and quantity) or to reduce production costs.

Bhumiyan et al. (1998) recognized the excessive amount of water often used for land soaking and providing required standing water for land preparation during presaturation supply in rice cultivation. Reducing the period of land preparation would lead to substantial saving in water including water lost because of evaporation, seepage and percolation and surface run off. Then, reducing the presaturation duration will definitely reduce the water application, increase irrigation efficiency and consequently reduce the overall rice planting duration. The time needed for distributing water in the field can be shortened significantly by using more field channels instead of the plot-to-plot method. In the case of water delivery is conveyed through the tertiary canal, the delivery period can be reduced through the delivery of larger amount of water to each lot. Changing the presaturation duration requires the flexibility in the canal system to change flows through offtakes.

To have a flexible system, the offtakes should be able to control flows, have the size larger than normal rates and able to measure flows. The tertiary canal also should be large enough to convey the required discharge for the system to be flexible. The question is in order to have a flexible system for rice cultivation, what is the flow rate to be provided for individual paddy lot, as compared to the continuous flow normally practiced in Malaysia, or in other parts of the world. In irrigation districts, water management is becoming more challenging as irrigators realize that crop yields can be maximized if sufficient amounts of water can be delivered at the proper time. As irrigation districts try to be more responsive to water users, they are finding that water losses are increasing and the canal systems are becoming harder to manage (Stringam et al., 2003).

1.2 Importance of Study

This pilot project study was conducted in Tanjung Karang Rice Irrigation Scheme, Selangor. Previous studies on the performance of irrigation schemes in Malaysia and other parts of the world indicated that water delivery service quality at tertiary canal and on farm levels operated by farmers and paid employees is comparatively low as compared to the main and secondary canal levels.

It has been acknowledged today worldwide that the demands for fresh water resources is on the rise and are stretched between competing demands; irrigation efficiency needs to be increased especially at farm level. Tertiary canal and on farm level are the most critical part of the irrigation system as these levels take up most of efforts and money spent for water management and loss most of water that is lost from the whole scheme.

A key component of improving irrigation efficiency is accurate control of off-take gates for water flow into the farm area. The off-take gate function is for getting the right amount

of water into the farm. There is a lack of accurate information and lack of precision in the setting of these structures. In non-automated off-take systems, management requires the mobilization of human resources to set and check structures (Renault & Hemakumara, 1999). Many researchers have delved into the gate control system and have made remarkable achievements worthy of mentioning here related to this research.

Field off-take is an important structure in tertiary canal provided as the turn-out structure from tertiary or quaternary level canal to the field. This structure plays important roles in providing the required water to the farm to suit crop water requirement and controlling the flow rate of water into the field. There are many complaints by many parties on the availability of simple flow measuring devices to measure flow rate in the case of small scale surface irrigation systems (Gopalakrishnan, 2009).

For an efficient water distribution, distant-downstream control, i.e. use the upstream gate to control the downstream water-level of each pool, is paramount (Li and Schutter, 2010). Results obtained from the previous studies showed that the off-take discharge deviations as a results of the errors in cross-regulator settings are significant consequently a new sensitivity indicator can be defined for those off-takes that are influenced by the cross regulators (Shahrokhnia & Javan, 2008). This sensitivity not only defines better indicator but also prove that cross-regulator settings are prone to errors. Ghazali et al. (2006) undertook a study with the ultimate aim of evaluating the performance of an automated CHO off-take structure in terms of discharge, orifice gate and turnout gate openings and operational time requirements.

Measurement and control of flows are another important aspect of water management in tertiary canal. Measurement of flows is required to ensure exact amount of water is supplied to every lot according to the demand of the lot based on predetermined rate as agreed or planned. Knowing the rate of flow, the duration and frequency can be easily manipulated accordingly to manage supply and demand. The opening of the intake gate can then be operated to suit the various planned or unplanned requirement to save water. The uncertainty may occur due to changes in flow of the river, pumps operation, rainfall, spill, flood control in paddy fields, etc. Hence, flow control and measurement of the field intake are very important for on-farm water management.

Through the Economic Transformation Program (ETP), the Malaysian government has launched a massive campaign to transform rice production so as to become a commercial business for farmers, to increase rice production as well as farmers' income while ensuring environmental sustainability. One of the important aspects in rice production is the ability of the existing irrigation system to provide required water supply to the paddy fields. For this purpose the tertiary canal and on farm structures and water delivery and management system obviously play very important role in providing water supply to the paddy fields.

1.3 Statement of Problem

The problems encountered in the scheme with regard to existing tertiary canal and field infrastructure are related to original design of structures inclusive of concrete conduit canals, field offtakes, check structures and field drainage outlet control structures to meet new water delivery requirement for different modes of irrigation supply as demanded by farmers.

The conveyance capacity of the concrete conduit is not large enough to meet faster presaturation for direct seeding practices that require faster presaturation period and farmers' demand for presaturation for individual paddy lot of less than three days. If presaturation is made simultaneously, the whole tertiary canal, the canals need to be reconstructed and enlarge to meet the requirement.

Reconstruction and enlargement of the existing canal will require a heavy investment cost from the government. Other problems of the existing tertiary concrete conduit canals are related to the settlement of canal stump that caused the uneven level of the conduit and the leaking of the conduit. Long tertiary canal up to seven kilometre covering number paddy lots up to 230 lots caused the difficulty in delivering water timely, equitably and adequately to the whole canal length for different modes delivery.

The existing field offtake pipe is made of uncontrolled 50 mm diameter steel pipes to each farm lot. This field offtake pipe gives different discharge due to the available head fluctuations and various discrepancies. On top of that, settlement of canal stump caused the other discrepancy to field offtake delivery rate. As the flow capacity of the offtake pipes is insufficient to meet peak presaturation water requirement, the use of siphon was later suggested and practiced by the farmers. The problems are related to the utilization of plastic siphons for field off-take, without proper flow control and accurate flow measurement. Indiscriminate use of siphon caused the over taping of water by farmers resulting in inequitable, inadequate and unreliable of water delivery to the individual farmers, especially to tail end users.

The existing check structures have failed to function appropriately to control water level in the tertiary canal. Tertiary canal system must ensure certain water level in the canal for the offtake gate to deliver the required amount into the field. The distance between checks is too far to provide the required water level in the canal. As the distance between checks is too far, the provision of slot was suggested to suitably control water level along the canal. The field drainage outlet control structure is made of concrete box opening with groove provided to insert wooden drop board to control water level in the paddy field. The problem with this structure is the leakage through the drop board and the step-wise control height depending on the width of the drop board, making it difficult to obtain precise water level as desired.

With regards to water delivery management for different irrigation requirement, several problems with the current land preparation practices require the presaturation for each individual lot to complete within 2 or 3 days. During the second flooding, a large amount of water is required in a short time, while during crop growth stages, smaller water delivery is required continuously or intermittently to meet crop consumption and water losses in paddy field. Hence, the field offtake certain degree of flexibility in it to deliver the required flow rate for different water delivery modes in rice irrigation supply and to function at different hydraulic conditions in tertiary canal.

Presently, in order to make best use of the present conduit, rotational irrigation was introduced together with the use of siphon to replace the existing field offtake pipe to meet peak presaturation water requirement caused over tapping of water by farmers, fluctuation of water level in the conduit canal and run off flow of water from the drainage system. These problems caused waste of water, effect the water use efficiency, pollution of drainage system due to the flow of chemicals and water delivery service quality in term of reliability, adequacy and equity to the individual farmers.

Water level in the tertiary canal is also depending on the distance of the offtake upstream of the water level control structures as the structures function as a weir. The longer the canal, the more the number of off-takes, then more effort is required to properly manage the water flows and ensure in particular that the tail-enders is receiving a fair share. Provision of good flow control and measurement for off-takes and water level control structures of the tertiary canal will reduce the demand for canal operation related to perturbations.

Water level control in the paddy fields is important to provide uniform water depth in the paddy field, to capture and store water in the fields and to prevent run off flow of water and chemicals from the field to the drainage system. Current practice of controlling standing water depth in the paddy fields by the height control of drainage outlet caused low water use efficiency due to continuous flow of water. The problem with the tertiary canal supply is that the current structure is unable to provide the required flow control and precise flow measurement to meet field requirement accurately. Intermittent irrigation requires regular adjustment to open and close the field offtake by farmers and caused frequent water level fluctuation in tertiary canal water level.

As to overcome these problems, this study proposed development of three new on-farm structures and water delivery management model. Three structures in the tertiary irrigation canal and on-farm levels which were developed and evaluated in this study are: (1) field offtake to deliver water from tertiary canal to paddy fields; (2) tertiary canal water level regulator or check structure and (3) field drainage outlet control structure. Automated float type flow control valve structure is the attachment to the field offtake to provide automated water delivery control of the field offtake. Water delivery management model was developed for four modes of irrigation supply, viz. presaturation, second flooding, crop growth stage water delivery, and the termination of irrigation.

1.4 Research Questions

This research seeks to address the issue of improving water delivery management for tertiary canal and on farm for commercial rice production in canal irrigation system operated by individual farmers. The study has addressed these questions:

- a. What is the most suitable water control management in tertiary canal and the paddy field and how to achieve it?
- b. How to set, control and maintain the water level in the tertiary canal for different flow rates and different field requirements?
- c. What are the physical and operational improvements required to the tertiary canal offtake to improve water delivery?
- d. How to manage and operate tertiary canal offtake to control and measure flow rate for different flow rates to meet different rice water requirements and fluctuations of water level in the main and secondary canal?
- e. How to manage tertiary canal water management and irrigation scheduling to deliver water to the paddy field for different stages of irrigation supply for rice cultivation?
- f. What flexible water management model can ensure equitable water distribution in on-farm irrigation water management?
- g. What is the suitable flow measurement flow control equipment for water delivery from tertiary canal to the field?
- h. What are the structures required to improve water management and water delivery for tertiary canal and on farm for modern commercial rice cultivation?

1.5 Aims and Objectives

The aim of the study was to develop on-farm structures and water delivery management model to improve rice irrigation practices.

The specific objectives are as follows;

- i. To design and evaluate laboratory performance of the flexible field offtake structure and float type automated flow control structure
- ii. To evaluate field performance of the developed on farm structures in tertiary canal.
- iii. To develop a new water delivery management model for rice tertiary irrigation canal utilizing the developed structures and evaluate the performance of the new model and structures in the pilot study area.

1.6 Scopes and Limitations

The Scopes of the study covered the following activities:

- i. Laboratory testing in NAHRIM Hydraulics and Instrumentation Laboratory covered the calibration of 150 mm diameter orifice type field offtake for different water level, pipe length and pipe end and the functionality of automated float control flow valve system.
- ii. Field applications of field offtake were conducted at lot no 3117 and 3137 in TASS 7 for 20 days duration from 1st September to 20th September 2013 during supplementary irrigation supply.
- iii. Field applications of field offtake with automated float type flow control valve were conducted at lot no. 3121 and 3125 in Taliar Sawah Sempadan no 7 (TASS 7) for 20 days duration from 1st September to 20th September 2013 during supplementary irrigation supply.
- iv. Field water delivery management for presaturation, second flooding and crop growth stage for the first 28 days of water delivery from 1st July to 28th July 2013 (Second Season 2013) for TASS 7 and TASS 8 Pilot Project Area.
- v. Field water delivery monitoring for crop growth stage from week 10th to week 13th (Third month (September 2013) TASS 7 and TASS 8 of the Pilot Project Area, and TASS 9 and TASS 10 outside the Pilot Project Area for comparison.
- vi. Tertiary canal flow calibration for the functionality and operational management procedures for flat gate regulator, flexible field offtake and tertiary canal offtake in first 1000 meter of the TASS 7 tertiary canal.
- vii. Water level in the canal was observed by the use of electronic sensor. Flow rate was measured using PCM 4 flow rate and water depth measurement.
- viii. Water level in canals referred to an assumed datum, properly surveyed by private surveyors.

Due to the financial, time and other resources constraints, there are several limitations associated with this study as described below:

- i. As the tertiary canal levels and sizes in the scheme may differ from one another, the calibration made and the results obtained during the field testing may not be similar for other tertiary canals. Every tertiary needs to be assessed separately.
- ii. Due to time and resources limitation, the data were only observed for the Second Season 2013 and during the limited time of the season, not throughout the whole season.

- iii. Several data observed were based on the real time reading from the telemetry system. There was the possibility of the gate setting being disturbed by the land owner, although they were advised not to do so.

1.7 Thesis Organization

This thesis comprises of six chapters through which the reports of the study are compiled. Chapter one gives a broad background of the study and highlights (i) the importance of the study, (ii) the statement of problem, (iii) the research questions, (iv) Aim and objectives, and (v) the scope and limitations of the study (iv) thesis organization.

Chapter two explore the literature related to this study to determine what has been done so far in this problem area. The review unfold the problems that lead to this study, though there were not too many literature in this area until recently but the arguments are worthy of further study.

Chapter three discusses the design and fabrication of tertiary canal offtakes and on-farm structures. The design and fabrication of the offtake flexi-gate are described and evaluation of the structure is reported.

Chapter four is concerned with the testing for field applicability of the developed structures at the tertiary canal, Taliar Sawah Sempadan Number 7 (TASS 7), Sawah Sempadan Compartment, and Tanjung Karang irrigation scheme. The technique used and results obtained are described.

Chapter five deals with the development of water delivery management model followed with evaluation of its performance for field application in the pilot project. The technique used and results obtained are described in detail.

Chapter six provides the conclusions and recommendations for the future research related to this study.

REFERENCES

- AHT Group A.G. (2008). Irrigation Planning, Design and Water Distribution (Vol. 3, p. 611).
- Bos, M.G. (1989) Discharge Measurement Structures, Publication 20, Third revised edition, International Institute for Land Reclamation(IILR), Wageningen.(p.41-47, p. 50-52, p.271-273).
- Brandes, D. and Barlow, W.T. (2012). New Method for Modeling Thin-Walled Orifice Flow under Partially Submerged Conditions. *J. Irrig. Drain Eng.*, 138(October), 924–928. doi:10.1061/(ASCE)IR.1943-4774.
- Burt, C.M. and Stuart S. (1990). Modern Water control and management Practices in Irrigation: Impact on performance. Development (p. 244). Rome, Italy.
- Carlos, A.S., Toepfer. (2007). Instrumentation, Model Identification and Control of an Experimental Irrigation Canal.
- Cernusak, L. , Winter, K., Aranda, J., Turner, B.L., and Marshall, J.D. (2007). Transpiration efficiency of a tropical pioneer tree (*Ficus insipida*) in relation to soil fertility. *Journal of experimental botany*, 58(13), 3549–66. doi:10.1093/jxb/erm201.
- Daniel J. Howes, D. J. and Burt, C. M. (2015). Accuracy of Round Meter Gates for On - Farm Deliveries. *Journal of Irrigation and Drainage Engineering*, 10.1061/(ASCE)IR.1943-4774.0000930, 04015033.
- DID Malaysia. (2009). DID Manual Volume 5. Drainage and Irrigation Department DID), Malaysia. Chapter 16, p.18-19).
- DOA Malaysia (2014). Perangkaan Padi Malaysia 2013. Department of Agriculture (DOA) Malaysia.
- Donelan, M., Neils M., kimmo K.K., Ioannis K. Tsanis, M. (1999). Apparatus for Atmospheric Surface Layer Measurements over Waves. *Journal of Atmospheric and Oceanic Technology*, 16, 1172–1182.
- FAO (1985). Irrigation Water Management: Introduction to irrigation. Italy, Rome: Food and Agriculture Organization of United Nation.
- FAO, (2007). Modernizing irrigation management: the MASSCOTE approach. FAO Irrigation and Drainage Paper 63. Food and Agriculture Organization of United Nation, Rome.
- Gates, B.T.K., Alshaikh, A.A., Ahmed, S.I., Molden, D.J. (1992). Optimal irrigation delivery system design under uncertainty. *J. Irrig. Drain Eng.*, 118(3), 433–449.

- Gates, T.K. and Ahmed, S.I. (1995). Sensitivity of predicted irrigation-delivery performance to hydraulic and hydrologic uncertainty. *Agricultural Water Management*, 27(3-4), 267–282. doi:10.1016/0378-3774(95)01153-A.
- Ghazali, H. (2006). Field Performance Evaluation Of An Automated Constant Head Orifice Off-Take Structure At The Sungai Muda Irrigation Scheme In Malaysia. *The Journal of the Agricultural Engineering Society of Sri Lanka*, 9(1).
- Guera, L.C., Bhuiyan S.I., Tuong T.P., and Barker, R. (1998). Producing More Rice with Less Water from Irrigated Systems. System-Wide Initiative on Water Management (SWIM) Paper no 5, International Water Management Institute (IWMI), Colombo. (p. 20).
- ICID (2011). *Irrigation & Drainage in the World – A Global Review*. International Commission on Irrigation and Drainage, New Delhi.
- Javan, M. and Fiuzat, A.A. (2002). Quantifying Management of Irrigation and Drainage Systems. *J. Irrig. Drain Eng.*, 128(February), 19–25.
- JICA. (1987). Feasibility Study on Tanjung Karang Irrigation Development Project.(p. Final Report). Japan International Cooperation Agency, Japan.
- JICA (1998). JICA (Japan International Cooperation Agency) The study on modernization of irrigation water management system in the Granary area of peninsular Malaysia (p. Final Report). Japan.
- Keller, J.R.W., Hill, M.J. and Mickelson, A.S. (1984). Review of Irrigation facilities Operation and Maintenance (p. 91). Jordan.
- Kim, J.S. (2005). Delivery Management Water Requirement for Irrigation Ditches Associated with Large-Sized Paddy Plots in Korea. *Paddy Water Environ* (2005) 3: 57-62
- Koech, R., Smith, R. and Gillies, M. (2010). Automation and Control in Surface Irrigation Systems : Current Status and Expected Future Trends. In Southern Region Engineering Conference (p. 1–7). Toowoomba, Australia.
- Korkmaz, N., Avci, M., Unal, H.B., Asik, S. and Gunduz, M. (2009). Evaluation of the Water Delivery Performance of the Menemen Left Bank Irrigation System Using Variables Measured On-Site. *Journal of Irrigation and Drainage Engineering*, 135, 633–642.
- Kulkarni, S.A. (2004). Benchmarking of Irrigation and Drainage Projects. ICID Report. New Delhi. (p. 25).
- Laura, S. and Miguel A.R. (2010). Distributed Control of Irrigation Canals. Hierchical and Distributed Model Predictive Control for rrigation Canal (HD-MPC) project. (p. 46).

- Levido L. (2014). Improve Water-Efficient Irrigation: Prospects and Difficulties of Innovative Practices. *Agricultural Water Management* 146 (2014) 84 -94.
- Lenton, R. (1984). A note on Monitoring productivity and Equity in Irrigation System. *Int. J. Water Resources Development*, 51–65.
- Li, M., Guo, P. and Singh, V.P. (2016). An efficient irrigation water allocation model under uncertainty. *Agricultural Systems* 144 (2016) 46-57
- Lozano, D., Arranja, C., Rijo, M. and Mateos, L. (2010). Simulation of automatic control of an irrigation canal, 97, 91–100. doi:10.1016/j.agwat.2009.08.016
- Luo, Y.F., Khan, S., Cui, Y.L., Feng, Y.H. and Li, Y.L. (2003). Modeling The Water Balance For Aerobic Rice : A System Dynamics Approach. *Water*, 1860–1866.
- Maghsoudi A. (2013). Sustainability of Agricultural Water Management Associations in Iran (Case study of Khuzestan Province). *European Journal of Experimental Biology*, 2013: 3(1), 545–550.
- Mattamana, B.A., Varghese, S. and Paul, K. (2013). Irrigation System Assessment- Farmer 's and Manager 's view. *International Journal of Engineering Science and Innovative Technology (IJESIT)*, 2(2), 148–159.
- MOA Malaysia. (1999). Third National Agricultural Policy (1998-2010). Ministry of Agriculture and Agro-based Industry (MOA Malaysia). (Vol. 3, p. 104)
- Mohsen, A.A, Kitamura, Y and Shimizu, K. (2013). Assessment of Irrigation Practices at Tertiary Canalleve in an Improved System - A Case Study of Wasat Area, the Nile Delta. *Paddy Water Environ* (2013) 11:445-454.
- Molden, B.D.J. and Gates, T.K. (1991). Performance Measures for Evaluation of Irrigation Water Delivery Systems. *Journal of Irrigation and Drainage Engineering*, 116(6), 804–823.
- Mutambara, S., Darkoh, M.B.K. and Atlhopheng J.R. (2016). A Comparative Review of Water Management Sustainability Challenges in Smallholder Irrigation Schemes in Africa and Asia *Agricultural Water Management* 171 (2016) 63-72.
- Negenborn, R.R., Overloop, P., Van, Keviczky, T. and Schutter de, B. (2009). Distributed Model Predictive Control of Irrigation Canals. *Networks and Heterogeneous Media*, vol., 4(2), 23.
- Oad, R. and Levine, G. (1985). Distribution of Water in Indonesian Irrigation Systems. *Transactions of the American Society of Agricultural Engineers*, 28(4), 1166–1172.
- Odhiambo, L.O. and Murty, V.V.N. (1996). Modeling Water Balance Components in Relation to Field Layout in Lowland Paddy Fields: Model application. *Agricultural Water Management*, 30(2), 185–199. doi:10.1016/0378-3774(95)01214-1

- Pradhan, T.M.S. (1996). Gated or Ungated : Water Control in Government-built Irrigation Systems (p. 290). Sch Service Centrum, Wageningen.
- Romero, R., J.L. Muriel, I. García, D.M. and de la Pena. (2012). Research on Automatic Irrigation Control : State of The Art and Recent Results. *Agricultural Water Management*, 114, 59–66. doi:10.1016/j.agwat.2012.06.026
- Raine, S.R. (1999). Research, Development and Extension in Irrigation and Water Use Efficiency. University of Southern Queensland, Toowoomba, Queensland.
- Rampano, B. (2009). Water Control Structures : Design Suitability for Natural Resource Management on Coastal Floodplains (p. 60). Port Stephens.: NSW Department of Industry and Investment.
- Renault, D. (2000). Aggregated Hydraulic Sensitivity Indicators for Irrigation System Behavior. *Agricultural Water Management*, 43(2), 151–171. doi:10.1016/S0378-3774(99)00059-1
- Renault D. and H.M. Hemakumara. (1999). Irrigation OffTake Sensitivity. *Journal Of Irrigation And Drainage Engineering*, (June), 131–136.
- Rowshon, M.K., Amin, M.S.M., Lee, T.S., and Shariff, A.R.M. (2009). GIS-integrated Rice Irrigation Management System for a River-fed Scheme. *Water Resources Management*. 23 (14): 2841-2866.
- Santhi, C. and Pundarikanthan, N.V. (2000). A New Planning Model for Canal Scheduling of Rotational Irrigation. *Agricultural Water Management*, 43(3), 327–343. doi:10.1016/S0378-3774(99)00065-7
- Schutter, Y.L. and De B. (2010). Offtake Feed forward Compensator Design for An Irrigation Channel with Distributed Control * Offtake Feedforward Compensator Design for an Irrigation Channel with Distributed Control. In *Proceedings of the 2010 American Control Conference*, Baltimore, Maryland, pp. 3747–3752, June–July 2010. (Vol. 19, pp. 3747–3752).
- Seckler, D. and Sampath R.S. (1988). An Index for Measuring the Performance of Irrigation Management Systems with An Application. *Water Resources Bull*, 24(4), 855–860.
- Shahrokhnia, M.A. and Javan, M. (2008). Influence of Cross-Regulator Settings on the Offtake Discharge in a Modern Irrigation Network. *Irrigation Science*, 27(2), 165–173. doi:10.1007/s00271-008-0133-0
- SMHB.(1996). Detailed Study on Water Resources Availability in North West Selangor Integrated Agricultural Development Project (IADP). SMHB/SMEC, K. Lumpur.
- Soulis, K.X. and Dercas, N. (2012). Field Calibration of Weirs Using Partial Volumetric Flow Measurements. *J. Irrig. Drain Eng.*, 138(May), 481–484. doi:10.1061/(ASCE)IR.1943-4774.0000424.

- Stringam, B.L., Sauer, B.W. and Pugh, C. (2003). Accurate Water Delivery Using A Simplified Automated Farm Turnout. *Irrigation and Drainage*, 52(4), 355–361. doi:10.1002/ird.102
- Unal, H.B.B., Asik, S., Avci, M., Yasar, S. and Akkuzu, E. (2004). Performance of Water Delivery System at Tertiary Canal Level : A Case Study of The Menemen Left Bank Irrigation System, Gediz Basin, Turkey. *Agricultural Water Management*, 65(3), 155–171. doi:10.1016/j.agwat.2003.10.002
- United Nations. (2007). *Irrigation in the World and Saskatchewan*. United Nation (UN). (pp. 5–37).
- Zhu, H., Krause, R.C., Derksen, R.D., Brazee, R. and Zondag, N.R.F. (2004). Real-Time Measurement of Drainage From Pot-In-Pot Container Nurseries. *American Society of Agricultural Engineers*, 47(6), 1973–1980.
- Zelege, A.D, Bart, S., and Laszlo, H.(2015). Water Delivery Performance at Metahara Large Scale Irrigation Scheme, Ethiopia. *Journal of Irrigation and Drainage*, 64: 479-490 (2015)
- Zwart, S.J. and Bastiaanssen, W.G. (2004). Review of Measured Crop Water Productivity Values for Irrigated Wheat, Rice, Cotton and Maize. *Agricultural Water Management*, 69(2), 115–133. doi:10.1016/j.agwat.2004.04.007.