



UNIVERSITI PUTRA MALAYSIA

***INTERACTION BETWEEN TWO CRACKS IN CIRCULAR POSITIONS IN
PLANE ELASTICITY***

RAHIMAH BINTI ABDUL RAFAR

FS 2017 69



**INTERACTION BETWEEN TWO CRACKS IN CIRCULAR POSITIONS IN
PLANE ELASTICITY**

By

RAHIMAH BINTI ABDUL RAFAR

**Thesis Submitted to the School of Graduate Studies, Universiti Putra
Malaysia, in Fulfillment of the Requirements for the Master of Science**

February 2017

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



DEDICATIONS

*To all of my love;
Mak & Along*



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the degree of Master of Science

INTERACTION BETWEEN TWO CRACKS IN CIRCULAR POSITIONS IN PLANE ELASTICITY

By

RAHIMAH BINTI ABDUL RAFAR

February 2017

Chairman: Nik Mohd Asri bin Nik Long, PhD
Faculty: Science

In this thesis, the interaction between two cracks in circular positions in plane elasticity is formulated into a system of hypersingular integral equations by using the complex variable function method. The center of the cracks are placed at the edge of a circle with radius R . The first crack is fixed on the x -axis while the second crack is located on the boundary of a circle with the varying angle, θ . By using the curved length coordinate method, the cracks are mapped into a straight line which require less collocation points, hence give faster convergence. With the help of particular quadrature rules, the unknown coefficients are solved numerically from the resulting system of hypersingular integral equations. The obtained unknown coefficients are then used for determining the stress intensity factor (SIF).

Three different domains for the problems of two cracks in circular positions will be considered which is the varying angle of positions of the second crack, the length ratio of the second to the first crack, and the length ratio of the first crack to the radius of a circle. The results for the tested problem presented here agree with the previous reported results.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Sarjana Sains

INTERAKSI ANTARA DUA REKAHAN PADA KEDUDUKAN MEMBULAT DALAM SATAH KEKENYALAN

Oleh

RAHIMAH BINTI ABDUL RAFAR

Februari 2017

Pengerusi: Nik Mohd Asri bin Nik Long, PhD
Fakulti: Sains

Dalam tesis ini, interaksi antara dua rekahan pada kedudukan membulat dalam satah kekenyalan dirumuskan kepada sistem persamaan kamiran hipersingular dengan menggunakan kaedah fungsi pembolehubah kompleks. Pusat rekahan diletakkan di atas sempadan bulatan yang mempunyai jejari R . Rekahan pertama berada tetap pada paksi- x manakala rekahan kedua diletakkan di atas sempadan bulatan dengan sudut θ yang berbeza. Dengan menggunakan kaedah koordinat panjang lengkung, rekahan dipetakan pada satu garis lurus yang hanya memerlukan titik kolokasi yang sedikit, dengan itu memberi penumpuan yang lebih cepat. Pekali yang tidak diketahui diselesaikan dengan menggunakan kaedah kuadratur tertentu bagi menyelesaikan persamaan kamiran hipersingular secara berangka. Pekali yang terhasil digunakan untuk mengira faktor keamatan tekanan.

Tiga domain yang berbeza bagi masalah dua rekahan pada kedudukan membulat dipertimbangkan iaitu sudut kedudukan rekahan, nisbah panjang antara rekahan pertama dan rekahan kedua, dan nisbah panjang antara rekahan pertama dan jejari bulatan. Hasil untuk masalah yang diuji mempunyai persetujuan yang bagus dengan keputusan lepas.

ACKNOWLEDGEMENTS

Alhamdulillah.

All praises belong to the almighty ALLAH for His blessings and mercy that enable me to learn, understand and complete this thesis.

A very special thanks to my beloved mother, Ruziah binti Mansor, and my brother for their love, support, understanding and encouragements.

I am sincerely grateful to my supervisor, Assoc. Prof. Dr. Nik Mohd Asri bin Nik Long, for giving me the opportunity to work under his supervision. He has been very generous and patient to contribute his valuable time to the numerous discussion sessions. He has taught me a lot of things and I came to know so many things not only in my study but also in my daily life. I highly appreciated his advice, assistance and commitment which help me to prepare and complete this thesis. Thanks a lot Dr. Nik.

I want to thank my supervisory committee Associate Professor Dr. Norazak bin Senu for his helpful guidance. This thesis will not be possible without the contribution from him. I would also like to thank all my seniors in this field for their help and support.

My thanks and appreciation also go to the School of Graduate Studies (SGS) for providing me UPM scholarship (Graduate Research Fellowship) and also to Ministry of Higher Education for giving me scholarship (MyMaster) throughout my studies. Also, I take this opportunity to express gratitude to all staff of the Department of Mathematics for their help and support.

I would also like to give my biggest appreciation to all my friends, Noly, Nisah, Najwa, and Mimi, and also to my cousin, Sabrina, for their love, support, understanding, advice and encouragements. Words cannot express how grateful I am. Thank you all

I certify that a Thesis Examination Committee has met on 6 February 2017 to conduct the final examination of Rahimah bt Abdul Rafar on her thesis entitled "Interaction between Two Cracks in Circular Positions in Plane Elasticity" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

Siti Hasana binti Sapar, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Chairman)

Leong Wah June, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Internal Examiner)

Ahmad Izani Md. Ismail, PhD

Associate Professor
Universiti Sains Malaysia
Malaysia
(External Examiner)



NOR AINI AB. SHUKOR, PhD
Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 2 June 2017

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Nik Mohd Asri bin Nik Long, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Chairperson)

Norazak bin Senu, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Member)

ROBIAH BINTI YUNUS, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: _____ Date: _____

Name and Matric No: Rahimah binti Abdul Rafar, GS38863

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: _____

Name of

Chairman of

Supervisory

Committee: Nik Mohd Asri bin Nik Long

Signature: _____

Name of

Member of

Supervisory

Committee: Norazak bin Senu

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENTS	iii
APPROVAL	iv
DECLARATION	vi
LIST OF TABLES	x
LIST OF FIGURES	xi
LIST OF ABBREVIATIONS	xiii
CHAPTER	
1 INTRODUCTION	1
1.1 Introduction	1
1.2 Motivation	3
1.3 Research questions	3
1.4 Objectives	3
1.5 Outline of thesis	4
2 LITERATURE REVIEW	5
2.1 Literature review	5
3 METHODOLOGY	9
3.1 Complex variable function method	9
3.2 Hypersingular integral equations	12
3.3 Superposition principle	13
4 TWO STRAIGHT CRACKS PROBLEM IN CIRCULAR POSITIONS	17
4.1 Introduction	17
4.2 Formulation of the problem	17
4.3 Curved length coordinates method	20
4.4 Quadrature rule	21
4.5 Stress intensity factor	22
4.6 Numerical examples	25
4.7 Conclusion	30
5 MULTIPLE INCLINED OR CURVED CRACKS PROBLEM IN CIRCULAR POSITIONS	31
5.1 Introduction	31

5.2	Formulation of the problem	31
5.3	Curved length coordinate methods	32
5.4	Quadrature rules	33
5.5	Stress intensity factor	34
5.6	Numerical examples	35
5.6.1	Example 1: Two Inclined Cracks	36
5.6.2	Example 2: Two Curved Cracks	43
5.6.3	Example 3: Curved and Inclined Cracks	47
5.7	Conclusion	51
6	CURVED OR INCLINED CRACK WITH STRAIGHT CRACK PROBLEMS IN CIRCULAR POSITIONS	52
6.1	Introduction	52
6.2	The first crack is a curved or inclined crack and the second crack is a straight crack.	52
6.2.1	Formulation of the problem	52
6.2.2	Curved length coordinate methods	55
6.2.3	Quadrature rules	56
6.2.4	Stress intensity factor	56
6.2.5	Numerical examples	58
6.2.6	Conclusion	67
6.3	The first crack is a straight crack and the second crack is a curved crack.	68
6.3.1	Formulation of the problem	68
6.3.2	Curved Length Coordinate Methods	71
6.3.3	Quadrature Rules	72
6.3.4	Stress intensity factor	72
6.3.5	Numerical example	74
6.3.6	Conclusion	77
7	CONCLUSION AND FUTURE WORK	78
7.1	Work Done	78
7.2	Future Work	78
	REFERENCES	79
	BIODATA OF STUDENT	82
	LIST OF PUBLICATIONS	84

LIST OF TABLES

Table	Page
1.1 The classification of the integral equations.	2
4.1 $K_1/p\sqrt{\pi a}$ for two equal straight cracks (Figure 4.3) under mode I remote stress p .	26
5.1 A comparison of the nondimensional SIFs for two inclined cracks in an infinite plate with the previous numerical computation.	36
5.2 Nondimensional SIFs for the problem shown in Figure 5.9.	43
6.1 A comparison of nondimensional SIFs for the crack problem shown in Figure 6.2.	58

LIST OF FIGURES

Figure	Page
3.1 A smooth curve L in an infinite plate.	10
3.2 The superposition principle for the solution of two inclined cracks problem.	14
4.1 A straight crack L in an infinite plate.	18
4.2 Two straight cracks placed in a circular position in plane elasticity.	18
4.3 Two equal straight cracks in an infinite plate.	25
4.4 Nondimensional SIF for two straight cracks when θ is changing.	27
4.5 Nondimensional SIF for two straight cracks when b/a changing.	28
4.6 Nondimensional SIF for two straight cracks when a/R changing.	29
5.1 Two inclined cracks placed in a circular position in plane elasticity.	32
5.2 Two equal inclined cracks in an infinite plate.	36
5.3 Nondimensional SIF for two inclined crack with $\alpha_1 = \alpha_2 = 20^\circ$ when θ is changing.	37
5.4 Nondimensional SIF for two inclined crack with $\alpha_1 = \alpha_2 = 60^\circ$ when θ is changing.	38
5.5 Nondimensional SIF for two inclined cracks for $\alpha_1 = \alpha_2 = 20^\circ$ as b/a changing.	39
5.6 Nondimensional SIF for two inclined cracks for $\alpha_1 = \alpha_2 = 60^\circ$ as b/a changing.	40
5.7 Nondimensional SIF for two inclined cracks with $\alpha_1 = \alpha_2 = 20^\circ$ and $b/a = 1.0$ as a/R changing.	41
5.8 Nondimensional SIF for two inclined cracks with $\alpha_1 = \alpha_2 = 60^\circ$ and $b/a = 1.0$ as a/R changing.	42
5.9 Two curved cracks in an infinite plate.	43
5.10 Two curved cracks placed in a circular position in plane elasticity.	44

5.11	Nondimensional SIF for two curved cracks as θ varies.	44
5.12	Nondimensional SIF for two curved cracks when R_2/R_1 changing.	45
5.13	Nondimensional SIF for two curved cracks when R_1/R changing and $R_2/R_1 = 1.0$.	46
5.14	Curved and inclined cracks placed in a circular position in plane elasticity.	47
5.15	Nondimensional SIF for $\alpha = 20^\circ$ as the angle θ changing.	48
5.16	Nondimensional SIF for $\alpha = 30^\circ$ when b/R_1 changing.	49
5.17	Nondimensional SIF for $\alpha = 30^\circ$ and $b/R_1 = 1.0$ when R_1/R changing.	50
6.1	Inclined and straight cracks placed in a circular position in plane elasticity.	52
6.2	Inclined and straight cracks.	58
6.3	Nondimensional SIF for $\alpha = 20^\circ$ when the angle θ varied.	59
6.4	Nondimensional SIF for $\alpha = 60^\circ$ when the angle θ varied.	60
6.5	Nondimensional SIF for $\alpha = 20^\circ$ when b/a changing.	61
6.6	Nondimensional for $\alpha = 60^\circ$ when b/a changing.	62
6.7	Nondimensional SIF for $\alpha = 20^\circ$ when a/R changing.	63
6.8	Curved and straight cracks placed in a circular position in plane elasticity.	64
6.9	Nondimensional SIF for various θ .	65
6.10	Nondimensional SIF for b/R_1 changing.	66
6.11	Nondimensional SIF for R_1/R changing.	68
6.12	Straight and curved cracks placed in a circular position in plane elasticity.	69
6.13	Nondimensional SIF for various θ .	74
6.14	Nondimensional SIF for R_2/a changing.	75
6.15	Nondimensional SIF for $R_2/a = 1.0$ and a/R changing.	76

LIST OF ABBREVIATIONS

SIF	Stress Intensity Factor
WS	Weakly Singular
S1	Singular type 1
S2	Singular type 2
HS	Hypersingular
COD	Crack Opening Displacement
DISD	Derivative In a Specific Direction
SIE	Singular Integral Equation



CHAPTER 1

INTRODUCTION

1.1 Introduction

The existence of flaws or cracks in a structure usually reduces the structure fatigue and static strength because the stresses and strains are highly magnified at the crack tip. To ensure the stress values are never close to the maximum received stress, large concentrations of stress are avoided and some reasonable securities are taken. However, the imperfections of material that caused at the production process or the material usage are inevitable, and hence must be taken into consideration.

Brittle fracture is the study that concerned the failure of a structure made from a normally ductile material at a load below that required to cause common yielding, and without obvious plastic deformation (Rolfe and Barsom, 1977). This study has led to the development of fracture mechanics. Fracture mechanics is the field that deals with the study of the cracks propagation in materials. The study uses analytical solid mechanics methods in order to calculate the force that apply on a crack and to characterize the resistance of materials to fracture.

Predicting the fatigue life of cracked components is one of the most important tasks in engineering of fracture mechanics. Based on the theories of elasticity, the stress and strain are applied to the materials in order to predict the mechanical failure of bodies. The parameters analyzed from linear elastic fracture mechanics can be used to determine the stress and strain magnification at the crack tip. This parameter known as the stress intensity factor (SIF), combines applied stress levels, geometry and crack size in a systematic manner and may be evaluated from the elastic stress analysis of cracked structures.

Many investigators gave their full attention in evaluating the SIFs in order to solve the crack problems. For instance, the regularization of the singular integral equation in a crack problem is an important study in the theory of integral equations and in the solid mechanics. In the past few years, the hypersingular integral equation was also used to solve the crack problems, involving the multiple crack problems. The multiple crack problems become an important topic in fracture mechanics since there exists the interaction among the cracks. Generally, the difficulty in the solution technique for this problem must be expected because of the interactions between the cracks.

An infinite plate crack problems, including the multiple cracks problem can be formulated into the integral equations. For the problems that involve a dislocation dis-

tribution or a dislocation doublet along a crack path, the integral equation may be generally expressed as

$$\int_L K(t, t_0) f(t) dt + \dots = p(t_0) \text{ (or } p(t_0) + c), \quad (t_0 \in L), \quad (1.1.1)$$

where L represents the crack configuration, $f(t)$ denotes the unknown function, $K(t, t_0)$ denotes the kernel, and $p(t_0)$ denotes the right hand term in the equation.

There are two possibilities for the choices of right hand term, one is the traction along the crack and second is the resultant force along the crack. The property of the kernel $K(t, t_0)$ depends on the choice of the functions $f(t)$ and $p(t_0)$. Table 1.1 lists the possibilities of the functions $f(t)$ and $p(t_0)$, and the property of $K(t, t_0)$.

Table 1.1: The classification of the integral equations.

Type	$f(t)$	$p(t_0)$	Property of $K(t, t_0)$
WS	Dislocations	Resultant forces	Weakly singular
S1	Dislocations	Tractions	Cauchy singular
S2	Displacement jump (COD)	Resultant forces	Cauchy singular
HS	Displacement jump (COD)	Tractions	Hypersingular

In weakly singular (WS) integral equations, the unknown function is the dislocation distribution, and the right hand term is the resultant force (Cheung and Chen, 1987). This integral equation is named weakly singular because the kernel is a logarithmic function, that has the weaker singularity for integration. This type of integral equation has not received a widespread concern for solving the multiple crack problems. Even though, the straightforward solution of this integral equation is unknown, but it can be solved numerically with the boundary element method.

In the first kind of Cauchy singular integral equations (S1), the unknown function is the dislocation distribution, and the right hand term is traction applied on the crack face. This integral equation is named S1 because the integral belongs to Cauchy principal value integral. For second kind Cauchy singular integral equations (S2), the unknown function is the crack opening displacement (COD) function, and the right hand term is the resultant force on the crack face. This type of integration is also a Cauchy principle value integral.

For hypersingular (HS) integral equations, the unknown function is the COD, and the right hand term is the traction applied on the crack face. This integral equation is names HS because the equation has a hypersingular kernel. The advantage for using this type of integral equation is that one can get the COD function directly from the solution. In general, the integration rule for the hypersingular integral along a curve crack is quite complicated.

1.2 Motivation

In fracture mechanics, there are several situations which involve complicated arrangement and configuration of cracks that can actually be solved by using suitable method of analysis. On the other hand, the presence of a crack will affect the stability and safety of a component and reduce the life of a components or structures significantly. The stresses in the vicinity of the crack tips governing the failure of cracked components. The singular stress contribution is defined by the stress intensity factor (SIF) which determined the stability and safety of the component. To this end, efficient and accurate approaches are required for evaluating the SIFs. Thus, the focus of this research is to investigate the interaction between two cracks in circular positions in plane elasticity. The hypersingular integral equation are used to solve this problem.

1.3 Research questions

In this thesis, we investigate two cracks problems lie on the boundary of a virtual circle in plane elasticity. The research questions of these problems are:

1. how the mathematical model for the interaction between two cracks in circular positions can be built?
2. how the hypersingular integral equations can be formulated for the above mentioned problems?
3. how the obtained hypersingular integral equations be solved to find the stress intensity factor (SIF) at the cracks tips?
4. how the two cracks behave as the distance between both cracks are close together or far apart?

1.4 Objectives

Based on the identified problem, the objectives of this investigation are to:

1. Formulate the mathematical model for the interaction between two cracks in circular positions.
2. Obtain the hypersingular integral equations for the above mentioned problems.

3. Solve the obtained hypersingular integral equations for the stress intensity factor (SIF) at the cracks tips.
4. Investigate the behavior of the cracks tips with respect to their positions and length.

1.5 Outline of thesis

The thesis covers seven chapters. Chapter 1 gives a brief introduction on the research subject. Chapter 2 is dedicated for literature review. Chapter 3 focuses on the methodology for solving the multiple crack problems. Chapter 4 studies the interaction between two straight cracks problem in circular positions in plane elasticity. Chapter 5 discusses the curved crack and inclined crack problems in circular positions. Chapter 6 studies the interaction between curved or inclined crack with straight crack in circular position. Chapter 7 contains the summary of the study and the suggestion for the future research.

REFERENCES

- Aridi, M. R., Nik Long, N. M. A., and Eshkuvatov, Z. K. (2014). Mode stresses for the interaction between straight and curved cracks problem in plane elasticity. *Journal of Applied Mathematics and Physics*, 2:225–234.
- Aridi, M. R., Nik Long, N. M. A., and Eshkuvatov, Z. K. (2016). Stress intensity factor for the interaction between a straight crack and a curved crack in plane elasticity. *Acta Mechanica Solida Sinica*, 29(4):1–9.
- Banichuk, N. V. (1970). Determination of the form of a curvilinear crack by small parameter technique. *Izv. An SSR, MIT* 7, 2.
- Chen, Y. Z. (1993a). New fredholm integral equation for multiple crack problem in plane elasticity and antiplane elasticity. *International Journal of Fracture*, 64:63–77.
- Chen, Y. Z. (1993b). Numerical solution of a curved crack problem by using hypersingular integral equation approach. *Engineering Fracture Mechanics*, 46(2):275–283.
- Chen, Y. Z. (1995). Hypersingular integral equation approach for the multiple crack problem in an infinite plate. *Acta Mechanica*, 108:121–131.
- Chen, Y. Z. (2003). A numerical solution technique of hypersingular integral equation for curved cracks. *Communication in Numerical Methods in Engineering*, 19:645–655.
- Chen, Y. Z. (2004a). Singular integral equation method for the solution of multiple curved crack problems. *International Journal of Solids and Structures*, 41:3505–3519.
- Chen, Y. Z. (2004b). Solution of integral equation in curve crack problem by using curve length coordinate. *Engineering Analysis with Boundary Elements*, 28:989–994.
- Chen, Y. Z., Gross, D., and Huang, Y. J. (1991). Numerical solution of the curved crack problem by means of polynomial approximation of the dislocation distribution. *Engineering Fracture Mechanics*, 39:791–797.
- Chen, Y. Z. and Hasebe, N. (1992). An alternative fredholm integral equation approach for multiple crack problem and multiple rigid line problem in plane elasticity. *Engineering Fracture Mechanics*, 43:257–268.
- Chen, Y. Z. and Hasebe, N. (1997). Fredholm integral equation for the multiple circular arc crack problem in plane elasticity. *Archive of Applied Mechanics*, 67:433–446.
- Chen, Y. Z., Hasebe, N., and Lee, K. Y. (2003). *Multiple crack problems in elasticity*. WIT Press, Southampton.

- Chen, Y. Z. and Lin, X. Y. (2010). Numerical solution of singular integral equation for multiple curved branch-cracks. *Structural Engineering and Mechanics*, 34:85–95.
- Cheung, Y. K. and Chen, Y. Z. (1987). New integral equation for plane elasticity crack problems. *Theoretical and Applied Fracture Mechanics*, 7:177–184.
- Chudnovsky, A., Dolgopolsky, A., and Kachanov, M. (1987a). Elastic interaction of a crack with a microcrack array-i. formulation of the problem and general form of the solution. *International Journal of Solids and Structures*, 23(1):1–10.
- Chudnovsky, A., Dolgopolsky, A., and Kachanov, M. (1987b). Elastic interaction of a crack with a microcrack array-ii. elastic solution for two crack configurations (piecewise constant and linear approximations). *International Journal of Solids and Structures*, 23(1):11–21.
- Cotterel, B. and Rice, J. R. (1980). Slightly curved or kinked cracks. *International Journal of Fracture*, 6:155–169.
- Denda, M. and Dong, Y. F. (1997). Complex variable approach to the bem for multiple crack problems. *Computer Methods in Applied Mechanics and Engineering*, 141:247–264.
- Erdogan, F. (1962). On the stress distribution in plates with collinear cuts under arbitrary loads. Proc. 4th U.S. Nat. Congr. Appl. Mech., pages 547–553.
- Eshkuvatov, Z. K., Zulkarnain, F. S., Nik Long, N. M. A., and Muminov, Z. (2016). Modified homotopy perturbation method for solving hypersingular integral equations of the first kind. *SpringerPlus*, 5(1):1473.
- Goldstein, R. V. and Salganik, R. L. (1970). Plane problem of curvilinear cracks in an elastic solid. *Izv. An SSR, MIT* 7, 3:69–82.
- Hadnard, J. (1923). *Lectures on Cauchy's problem in linear differential equation*. University Press: Yale.
- Hasan, S. (2015). Dugdale model for three unequal collinear straight cracks with coalesced yield zones: A complex variable approach. *International Journal of Pure and Applied Mathematics*, 105(2):311–323.
- Helsing, J. (2011). A fast and stable solver for singular integral equations on piecewise smooth curved. *SIAM Journal on Scientific Computing*, 33:153–174.
- Helsing, J. and Peters, G. (1999). Integral equation methods and numerical solutions of crack and inclusion problems in planar elastostatics. *SIAM Journal on Applied Mathematics*, 59:965–982.
- Kachanov, M. (1985). A simple technique of stress analysis in elastic solids with many cracks. *International Journal of Fracture*, 28:R11–R19.
- Kachanov, M. (1987). Elastic solids with many cracks: A simple method of analysis. *International Journal of Solids and Structures*, 23(1):23–43.

- Kaya, A. C. and Erdogan, F. (1987). On the solutions of integral equations with strongly singular kernels. *Quarterly of Applied Mathematics*, 45:105–122.
- Lam, K. Y. and Phua, S. P. (1991). Multiple crack interaction and its effect on stress intensity factor. *Engineering Fracture Mechanics*, 40(3):585–592.
- Leonel, E. D. and Venturini, W. S. (2011). Multiple random crack propagation using a boundary element formulation. *Engineering Fracture Mechanics*, 78:1077–1090.
- Li, Y. P., Tham, L. G., Wang, Y. H., and Tsui, Y. (2003). A modified kachanov method for analysis of solids with multiple cracks. *Engineering Fracture Mechanics*, 70:1115–1129.
- Linkov, A. M. and Mogilevskaya, S. G. (1986). Finite-part integrals in problems of three-dimensional cracks. *Journal of Applied Mathematics and Mechanics*, 50:652–658.
- Mayrhofer, K. and Fischer, F. D. (1992). Derivation of a new analytical solution for a general two-dimensional finite-part integral applicable in fracture mechanics. *International Journal for Numerical Methods in Engineering*, 33:1027–1047.
- Moes, N., Dolbow, J., and Belytschko, T. (1999). A finite element method for crack growth without remeshing. *International Journal for Numerical Methods in Engineering*, 46:131–150.
- Muskhelishvili, N. I. (1957). *Some basic problems of the mathematical theory of elasticity*. Noordhoff International Publishing, Leyden.
- Nik Long, N. M. A., Aridi, M. R., and Eshkuvatov, Z. K. (2015). Mode stresses for the interaction between an inclined crack and a curved crack in plane elasticity. *Mathematical Problem in Engineering*.
- Nik Long, N. M. A. and Eshkuvatov, Z. K. (2009). Hypersingular integral equation for multiple curved cracks problem in plane elasticity. *International Journal of Solids and Structures*, 46:2611–2617.
- Oliveira, H. L. and Leonel, E. D. (2013). Dual bem formulation applied to analysis of multiple crack propagation. *Materials Science and Engineering*, 560:99–106.
- Panasyuk, V. V., Savruk, M. P., and Datsyshyn, A. P. (1977). A general method of solution of two-dimensional problems in the theory of cracks. *Engineering Fracture Mechanics*, 9:481–497.
- Rice, J. R. (1972). Some remarks on elastic crack-tip stress fields. *International Journal of Solids and Structures*, 8:751–758.
- Rolfe, S. T. and Barsom, J. M. (1977). *Fracture and fatigue control in structures: applications of fracture mechanics*. ASTM International.
- Vitek, V. (1977). Plane strain stress intensity factors for branched cracks. *International Journal of Fracture*, 13(4):481–501.

Wang, X., Ang, W., and Fan, H. (2015). Hypersingular integral and integro-differential micromechanical models for an imperfect interface between a thin orthotropic layer and an orthotropic half-space under inplane elastostatic deformations. *Engineering Analysis with Boundary Elements*, 52:32–43.

Zhang, X., Gunzburger, M., and Ju, L. (2016). Nodal-type collocation methods for hypersingular integral equations and nonlocal diffusion problems. 299:401–420.

