



**UNIVERSITI PUTRA MALAYSIA**

***CHARACTERIZATION OF OPTICAL PARAMETERS IN SEEDED AND  
SEEDLESS WATERMELON USING LASER-INDUCED  
BACKSCATTERING  
IMAGING***

**MAIMUNAH BINTI MOHD ALI**

**FK 2017 31**



**CHARACTERIZATION OF OPTICAL PARAMETERS IN SEEDED AND  
SEEDLESS WATERMELON USING LASER-INDUCED BACKSCATTERING  
IMAGING**

By

**MAIMUNAH BINTI MOHD ALI**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in  
Fulfilment of the Requirements for the Degree of Master of Science**

**April 2017**

## **COPYRIGHT**

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

## **CHARACTERIZATION OF OPTICAL PARAMETERS IN SEEDED AND SEEDLESS WATERMELON USING LASER-INDUCED BACKSCATTERING IMAGING**

By

**MAIMUNAH BINTI MOHD ALI**

**April 2017**

**Chairman : Norhashila binti Hashim, PhD**  
**Faculty : Engineering**

Monitoring of watermelon fruit quality is essential in order to regulate proper postharvest handling and yield production. Problems arise in forecasting the quality parameters of watermelon during storage as the shelf-life of the fruit is only lasts for three weeks. The non-climacteric nature of the fruit is also related to high perishability which does not undergo a continuous process to ripen after being harvested. In the present study, laser-induced backscattering imaging was used to determine the firmness, soluble solids content (SSC), pH, moisture content (MC), and colour changes of watermelons in seven interval days starting from storage day 0 after harvesting (day 0, day 4, day 8, day 12, day 15, day 18, and day 21). Two types of watermelon cultivars were used in this study; seeded watermelon (Black Beauty) and seedless watermelon (Red Seedless). The backscattered images of the fruit surface were obtained at six different locations using laser diodes emitting at 658 nm wavelength. The backscattered images were analysed and the feature information was extracted based on the backscattering image parameters which are minor length, major length, perimeter, maximum intensity, minimum intensity, and mean intensity. The standard reference methods were carried out after the image acquisition process in order to determine the quality parameter measurements.

The multivariate analysis was used to optimise the classification between seeded and seedless watermelons, as well as the regression models between backscattering data and quality parameters, were also discussed. Principal component analysis (PCA) was used to classify the seeded and seedless watermelons into two different classes according to the physicochemical changes. Partial least squares (PLS) regression with full cross-validation method was used to establish the regression models between the backscattering data and quality parameters. The firmness values obtained were 5.07 to 3.24 kg/cm<sup>2</sup> and 4.78 to 3.03 kg/cm<sup>2</sup>, whereas the SSC values achieved 9.06 to 5.66 Brix and 8.52 to 6.41 Brix for the seeded and seedless watermelons, respectively. The pH values were 5.27 to 7.10 pH and 5.60 to 6.42 pH while the moisture content values

revealed 95.46 to 82.79 % w.b. and 94.53 to 86.43 % w.b. for the seeded and seedless watermelons, respectively. For colour parameters, the  $L^*$  values ranged from 24.08 to 51.06, whereas the  $b^*$  values ranged from 11.52 to 36.84. The chroma and hue values were also increased from 12.41 to 38.95 and  $104.55^\circ$  to  $111.60^\circ$ , respectively. The  $a^*$  value reduced significantly ( $P < 0.05$ ) from -4.32 to -13.06 for both seeded and seedless watermelons. For seedless watermelon, the colour prediction ( $L^*$ ,  $a^*$ ,  $b^*$ , chroma, and hue) gave the highest coefficient of determination ( $R^2$ ) with all of them above 0.90. Meanwhile, the firmness prediction gave the highest  $R^2$  of 0.92 for seeded watermelon. On the whole, it is concluded that the application of laser-induced backscattering imaging is a promising technique for assessing quality parameters of watermelons during storage. The proposed approach has significant potential as a well-controlled system for developing automated sorting and grading system in the future.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

## **PENCIRIAN PARAMETER OPTIK DALAM TEMBIKAI BERBIJI DAN TIDAK BERBIJI MENGGUNAKAN PENGIMEJAN LASER PEMBALIKKAN**

Oleh

**MAIMUNAH BINTI MOHD ALI**

**April 2017**

**Pengerusi : Norhashila binti Hashim, PhD**  
**Fakulti : Kejuruteraan**

Pemantauan kualiti buah tembikai adalah penting dalam usaha untuk mengawal pengendalian lepas tuai yang betul dan hasil pengeluaran buah. Masalah timbul dalam meramal parameter kualiti tembikai semasa dalam simpanan kerana kitaran buah ini hanya bertahan selama tiga minggu. Sifat bukan klimakterik buah ini juga berkaitan dengan kadar mudah rosak yang tidak menjalani proses berterusan untuk masak sepenuhnya selepas dituai. Dalam kajian ini, pengimejan laser pembalikan telah digunakan untuk menentukan ketegasan, kandungan pepejal larut (SSC), pH, kandungan kelembapan (MC), dan perubahan warna tembikai dalam tempoh tujuh hari interval bermula dari hari 0 selepas penuaian (0, 4, 8, 12, 15, 18, 21). Dua jenis tembikai telah digunakan dalam kajian ini; tembikai berbiji (Black Beauty) dan tembikai tidak berbiji (Red Seedless). Imej-imej yang dibalikkan di permukaan buah pada enam lokasi berbeza daripada tembikai berbiji dan tidak berbiji menggunakan diod laser yang dipancarkan pada gelombang 658 nm. Imej-imej yang dibalikkan telah dianalisis dan maklumat ciri diekstrak berdasarkan parameter imej pembalikan iaitu panjang kecil, panjang utama, perimeter, intensiti maksimum, intensiti minimum, dan purata intensiti. Kaedah rujukan standard telah dijalankan selepas proses pengambilan imej untuk menentukan ukuran kualiti parameter.

Analisis multivariat digunakan untuk mengoptimumkan klasifikasi antara tembikai berbiji dan tidak berbiji, serta model regresi antara data pembalikan dan parameter kualiti, juga telah dibincangkan. Analisis komponen utama (PCA) telah digunakan untuk mengelaskan tembikai berbiji dan tidak berbiji kepada dua kelas yang berbeza mengikut sifat-sifat perubahan kualiti. Regresi separa kuasa dua terkecil (PLS) dengan kaedah pengesahan silang penuh telah digunakan untuk mewujudkan model regresi antara data pembalikan dan parameter kualiti. Nilai ketegasan diperoleh adalah 5.07-3.24 kg/cm<sup>2</sup> dan 4.78-3.03 kg/cm<sup>2</sup>, manakala nilai SSC adalah 9.06-5.66 Brix dan 8.52-6.41 Brix untuk tembikai berbiji dan tidak berbiji. Nilai pH adalah 5.27-7.10 pH dan 5.60-6.42 pH, manakala nilai kandungan kelembapan adalah 95.46-82.79% w.b. dan 94.53-86.43% w.b. untuk tembikai berbiji dan tidak berbiji. Untuk parameter warna, nilai L\* diperoleh di antara 24.08 hingga 51.06, manakala nilai b\* adalah di antara

11.52 hingga 36.84. Nilai kroma dan hue juga meningkat daripada 12.41 hingga 38.95 dan 104.55° hingga 111.60°. Nilai  $a^*$  berkurang dengan ketara ( $P < 0.05$ ) daripada -4.32 hingga -13.06 untuk tembikai berbiji dan tidak berbiji. Untuk tembikai tidak berbiji, ramalan warna ( $L^*$ ,  $a^*$ ,  $b^*$ , kroma, dan hue) memberikan pekali tertinggi penentuan ( $R^2$ ) dengan nilai 0.90. Sementara itu, ramalan ketegasan memberikan nilai tertinggi  $R^2$  sebanyak 0.92 untuk tembikai berbiji. Secara keseluruhannya, penggunaan pengimejan laser pembalikan adalah teknik yang berkesan untuk menilai parameter kualiti tembikai semasa penyimpanan. Pendekatan yang dicadangkan mempunyai potensi yang besar sebagai satu aplikasi yang terkawal untuk membangunkan system automatik pengasingan dan penggredan buah pada masa hadapan.



## ACKNOWLEDGEMENTS

First of all, I would like to take this opportunity to express my profound gratitude and deep regards to my supervisor, Dr. Norhashila Hashim for her exemplary guidance, monitoring and constant encouragement throughout the course of this research work. The blessing, help and guidance given by her from time to time shall carry me a long way in the journey of life upon which I am about to embark.

I also take this opportunity to express a deep sense of gratitude to Assoc. Prof. Dr. Siti Khairunniza Bejo and Assoc. Prof. Dr. Rosnah Shamsudin for their co-supervision, valuable information and guidance, which helped me in completing this task through the various stages. I am indebted to the staff members of the Department of Biological and Agricultural Engineering, for the valuable information provided by them in their respective fields. I am grateful for their cooperation during the period of my assignment

Lastly, I would like to thank my parents, Mr. Mohd Ali Abu Seman and Mrs. Mariam@Mary Abdullah, grandpa Mr. Abu Seman Sirat, grandma Mrs. Saerah@Imbo Abdullah, family, and fellow friends for their constant encouragement without which this thesis would not have been possible.



I certify that a Thesis Examination Committee has met on 4 April 2017 to conduct the final examination of Maimunah binti Mohd Ali on her thesis entitled "Characterization of Optical Parameters in Seeded and Seedless Watermelon using Laser-Induced Backscattering Imaging" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

**Muhammad Razif bin Mahadi @ Othman, PhD**

Senior Lecturer  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**Samsuzana binti Abd Aziz, PhD**

Senior Lecturer  
Faculty of Engineering  
Universiti Putra Malaysia  
(Internal Examiner)

**Ibni Hajar bin Haji Rukunudin, PhD**

Professor Ir.  
Universiti Malaysia Perlis  
Malaysia  
(External Examiner)



---

**NOR AINI AB. SHUKOR, PhD**  
Professor and Deputy Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date: 2 June 2017

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

**Norhashila binti Hashim, PhD**

Senior Lecturer  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**Siti Khairunniza binti Bejo, PhD**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**Rosnah binti Shamsudin, PhD**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

---

**ROBIAH BINTI YUNUS, PhD**

Professor and Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date:

## Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Name and Matric No.: Maimunah binti Mohd Ali (GS42752)

### **Declaration by Members of Supervisory Committee**

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: \_\_\_\_\_  
Name of Chairman of  
Supervisory  
Committee: \_\_\_\_\_

Signature: \_\_\_\_\_  
Name of Member of  
Supervisory  
Committee: \_\_\_\_\_

Signature: \_\_\_\_\_  
Name of Member of  
Supervisory  
Committee: \_\_\_\_\_

## TABLE OF CONTENTS

	<b>Page</b>
<b>ABSTRACT</b>	i
<b>ABSTRAK</b>	iii
<b>ACKNOWLEDGEMENTS</b>	v
<b>APPROVAL</b>	vi
<b>DECLARATION</b>	viii
<b>LIST OF TABLES</b>	xiii
<b>LIST OF FIGURES</b>	xv
<b>LIST OF ABBREVIATIONS</b>	xvii
 <b>CHAPTER</b>	
 <b>1 INTRODUCTION</b>	 <b>1</b>
1.1 Background Study	1
1.2 Problem Statements	3
1.3 Importance of Study	4
1.4 Objectives	4
1.5 Scope and Limitations	5
1.6 Thesis Overview	5
 <b>2 LITERATURE REVIEW</b>	 <b>6</b>
2.1 Cultivation of Watermelon	6
2.1.1 Seeded watermelon	8
2.1.2 Seedless watermelon	8
2.2 Postharvest Handling	9
2.3 Quality Evaluation of Watermelon	11
2.3.1 Colour Assessment	11
2.3.2 Texture Assessment	12
2.3.3 Size Assessment	13
2.3.4 Shape Assessment	14
2.3.5 Defect Assessment	15
2.3.6 Sweetness Assessment	16
2.4 Non-destructive Applications for Quality Evaluation of Watermelon	16
2.4.1 Acoustic Impulse Response	17
2.4.2 Laser Doppler Vibrometry	18
2.4.3 Near-infrared Spectroscopy	19
2.4.4 Machine Vision System	20
2.5 Optical Parameters	21
2.5.1 Wavelength	21

2.5.2	Refractive Index	22
2.5.3	Dispersion of Light	23
2.5.4	Effects of Surface Curvature	23
2.6	Laser-induced Backscattering Imaging System	23
2.6.1	Incident Light Beam	26
2.6.2	Principle of Laser Light Backscattering Imaging	26
2.6.3	Components of Laser-induced Backscattering Imaging Systems	28
2.7	Summary	29
<b>3</b>	<b>MATERIALS AND METHODS</b>	<b>30</b>
3.1	Preparation of Data Collection	30
3.2	Image Acquisition using LLBI System	33
3.3	Dimensional Measurements	35
3.4	Determination of Physicochemical Properties	36
3.4.1	Firmness Measurement	36
3.4.2	Colour Measurement	37
3.4.3	Moisture Content Measurement	38
3.4.4	Soluble Solids Content Measurement	39
3.4.5	pH measurement	39
3.5	Determination of Backscattering Image Parameters	40
3.6	Data Analysis	42
3.6.1	Descriptive Statistics	42
3.6.2	Two-way Analysis of Variance (ANOVA)	43
3.6.3	Principal Component Analysis (PCA)	43
3.6.2	Multivariate Pattern Recognition Algorithms	44
3.6.5	Partial Least Squares (PLS)	45
3.7	Summary	46
<b>4</b>	<b>RESULTS AND DISCUSSIONS</b>	<b>47</b>
4.1	Dimensional Measurements of Samples	47
4.2	Changes of Physicochemical Properties during Storage	48
4.2.1	Firmness	49
4.2.2	SSC	50
4.2.3	pH	51
4.2.4	Moisture Content	52
4.2.5	Colour Evaluation	52
4.3	Interaction between Storage and Watermelon Cultivar	54
4.4	Correlation between Physicochemical Properties	55
4.5	Backscattering Parameters	56

4.6	Classification of Seeded and Seedless Watermelons using Backscattering Imaging	62
4.6.1	Classification of Watermelon Based on Cultivars	62
4.6.2	Classification of Watermelons Based on Storage Day	64
4.7	Prediction of Physicochemical Properties using Backscattering Imaging	68
4.7.1	Firmness Prediction	72
4.7.2	SSC Prediction	72
4.7.3	pH Prediction	73
4.7.4	Moisture Content Prediction	73
4.7.5	Prediction of Colour Properties using Backscattering Parameters	74
4.8	Summary	76
<b>5</b>	<b>CONCLUSION AND RECOMMENDATIONS</b>	<b>77</b>
5.1	Conclusions	77
5.2	Recommendations for Future Work	78
	<b>REFERENCES</b>	<b>80</b>
	<b>APPENDICES</b>	<b>92</b>
	<b>BIODATA OF STUDENT</b>	<b>98</b>
	<b>LIST OF PUBLICATIONS</b>	<b>99</b>

## LIST OF TABLES

Table	Page
2.1 The maturity level of watermelon	10
2.2 Grade classification of watermelon	13
2.3 Size classification of watermelon	13
2.4 The overview of the application of LLBI system of agricultural produce	25
3.1 Cultivars and properties of watermelons	30
3.2 The setting measurements of laser-induced backscattering imaging system	33
4.1 The dimensional measurements of seeded and seedless watermelons	47
4.2 Statistical characteristics of seeded and seedless watermelons	48
4.3 Regression equations with their corresponding correlation coefficient (r) for the physicochemical properties	49
4.4 The changes of firmness values of watermelons at different storage days after harvesting	50
4.5 The changes of SSC values of watermelons at different storage days after harvesting	51
4.6 The changes of pH values of watermelons at different storage days after harvesting	51
4.7 The changes of moisture content (MC) values of watermelons at different storage days after harvesting	52
4.8 F-values (ANOVA) of physicochemical properties of watermelons	55
4.9 Pearson correlation coefficients for physicochemical properties of watermelons	56
4.10 Descriptive statistics of backscattering parameters of seeded and seedless watermelons at different storage days	57
4.11 Backscattering images of seeded and seedless watermelons at different storage days (representative of one sample image)	59



4.12	ANOVA of backscattering parameters in watermelons	61
4.13	The average classification accuracies of seeded and seedless watermelons at different storage day using multivariate pattern recognition algorithms	66
4.14	The classification accuracies of seeded and seedless watermelons at different storage day based on the backscattering parameters	67
4.15	Statistical details of the samples used in calibration and prediction set for physicochemical properties of seeded and seedless watermelons	70
4.16	Calibration and prediction models based on the backscattering parameters of seeded and seedless watermelons	71

## LIST OF FIGURES

Figure	Page
2.1 The watermelons are harvested during dry and sunny conditions	7
2.2 The schematic illustration of the acoustic impulse response	17
2.3 Spectra measurements of watermelon. (a) excitation vibration signal, (b) laser Doppler vibrometry experimental set-up	19
2.4 Schematic diagram of infrared spectroscopy using watermelon fruits	20
2.5 Image acquisition system of a watermelon using machine vision	21
2.6 The electromagnetic spectrum of light	22
2.7 A typical laser backscattered image using LLBI system	24
2.8 Distribution of incident light in fruits	27
2.9 A schematic diagram of LLBI system	29
3.1 The flow chart of sampling grouping of seeded and seedless watermelons	31
3.2 Procedure for data collection	32
3.3 The experimental set-up used for laser-induced backscattering imaging system	33
3.4 Lightproof frame covered with black cloth	34
3.5 The incident point location	34
3.6 Dimensional measurements of watermelon	35
3.7 The watermelon samples of Black Beauty and Red Seedless used for each interval storage day	36
3.8 The firmness measurement using penetrometer	37
3.9 The colour measurement using a handheld colorimeter	37
3.10 The procedure for the measurement of moisture content: (a) watermelon cube samples, (b) mass measurement before oven-dried, (c) samples were oven-dried at for 24h at 105 °C, (d) mass measurement after oven-dried	38

3.11	SSC measurement using a refractometer	39
3.12	The pH measurement using a pH meter	40
3.13	The procedure of image processing analysis	41
3.14	Image segmentation processes: (a) original image, (b) Gaussian filter smoothing, (c) segmented image after morphological operations, (d) Sobel edge detection	42
4.1	Changes in colour parameter values of seeds and seedless watermelons during storage. (a) L* value, (b) a* value, (c) b* value, (d) Chroma value, (e) Hue value. Each storage day represents by N=10 for both seeded and seedless watermelons. The corresponding values represent the mean of three replications and their standard error bars. Different letters indicate statistical difference by the Tukey test ( $p < 0.05$ )	54
4.2	PCA score plot of seeded and seedless watermelons from backscattering parameters measurement (■ Seeded; ● Seedless)	62
4.3	Average classification accuracies using the multivariate classification model	64
4.4	PCA score plot of (a) seeded and (b) seedless watermelons stored at seven storage days. Fresh samples evaluated initially on: (■ day 0; ● day 4; ▲ day 8; ◆ day 12; ▼ day 15; * day 18; † day 21)	65

## LIST OF ABBREVIATIONS

a*	Greenness
ANOVA	Analysis of variance
b*	Yellowness
C	Chroma
CCD	Charge-coupled device
CMOS	Complementary metal-oxide-semiconductor
CV	Cross validation
GL	Gaussian-Lorentzian
h	Hue angle
HSI	Hue-saturation-intensity
kNN	k-nearest neighbours
L*	Lightness
LDA	Linear discriminant analysis
LDV	Laser Doppler vibrometry
LLBI	Laser light backscattering imaging
MC	Moisture content
MLR	Multiple linear regression
NIR	Near infrared
PC	Principal component
PCA	Principal component analysis
PLS	Partial least squares
PLS-DA	Partial least squares discriminant analysis
QDA	Quadratic discriminant analysis
r	Correlation coefficient
R <sup>2</sup>	Coefficient of determination
RGB	Red-green-blue
RMSEC	Root mean square of calibration
RMSEP	Root mean square of prediction
ROI	Region of interest
SEP	Standard error of prediction
SSC	Soluble solids content

TSS	Total soluble solids
VIS/NIR	Visible/near-infrared
$\mu_a$	Absorption coefficient
$\mu_s$	Scattering coefficient
$\mu'_s$	Reduced scattering coefficient



## CHAPTER 1

### INTRODUCTION

#### 1.1 Background Study

Watermelon (*Citrullus lanatus*) is an edible and beneficial fruit which is available all year round. The fruit is the world's second most produced fruit with approximately 109.28 million metric tonnes in global production in 2013 (FAO, 2015). The fruit belongs to the family of *Cucurbitacea* and well-known for its sweet and juicy flesh. Moreover, the fruit is also denoted as a pepo; a special type of berry that has a thick rind and deep flesh inside it (Ajuru & Okoli, 2013). The pepo is also developed from the inferior fruit which is distinctive for every crop in the *Cucurbitaceae* family. Normally, the colour of watermelon flesh of most commercial cultivars is red or yellow. Meanwhile, the watermelon rind colour varies from light to dark green with yellow spots, stripes, or marbles. As an added value, the entire fruit is edible and frequently being eaten raw or consumed as fruit juice, stir-fried, salad, and pickled watermelon.

Apart from that, watermelon differs in terms of shape and size from circular to oblong. The fruit has high water content and another source of vitamins and minerals such as carbohydrates, calcium, phosphorus, and ascorbic acid (Tlili et al., 2011). Other than that, watermelon is also proven to be one of lycopene and citrulline sources (Perkins-Veazie & Collins, 2004; Rimando & Perkins-Veazie, 2005). Citrulline is a non-essential amino acid whereas lycopene is a type of carotenoid that gives the distinct property of red colour (Liu et al., 2010). In addition, watermelon is a non-climacteric fruit which does not undergo a continuous process to ripen after being harvested (Wechter et al., 2008).

Watermelon consists of numerous cultivars, including seeded, seedless, and disorder-resistant cultivars. At the moment, the watermelon seeds are mostly imported from Taiwan or Japan. The seeded cultivars which are Black Beauty, Sugar Baby, New Dragon, Empire No. 1, and Cina Dragon are grown in Malaysia. On the other hand, seedless cultivars such as Fengshan No. 1, Red Seedless, Gold Rush 1663, and Felicity Orchid Sweet which are the combination of F1 hybrids are imported from Taiwan and Japan. The seedless cultivars have characteristics of short-term maturity phase, high yield, as well as better-quality compared to the seeded cultivars (Nunes, 2009).

The evaluation of internal and external qualities in the past has been difficult and time-consuming due to the subjective form of assessment and the use of destructive measurements. Most aspects of the evaluation have always been based on the visual appearance and inspection of the fruit which could lead to inaccuracies in the results. Further, assessment by manual sorting depends very much on human labour and time management which is liable to subjectivity (Hashim et al., 2014). For watermelon, the conventional technique for choosing a good-quality fruit is usually done by thumping

the skin of the fruit in order to check its sound, as it is used to detect a hollow heart defect in the fruit. The other technique is searching for yellow spots on the surface which is not practical when dealing with a huge number of fruits, especially during the harvesting season. Thus, since the demand for good-quality fruit is increasing, an automated system using non-destructive techniques is desirable.

The advanced technology in non-destructive and fibre optics applications has been developed rapidly in the agricultural sector to fill in the requirement for high yield production. In recent years, non-destructive techniques have been used for monitoring quality changes externally and internally of various crops and agricultural produce. The most recommended techniques are generally based on the food properties including optical, vibration, sound, and electrical properties. These assessments are very much related to the relationship of physicochemical properties and the features of the non-destructive method. For instance, non-destructive applications have been tested on watermelon using acoustic impulse response (Armstrong et al., 1997; Diezma-Iglesias et al., 2004; Mao et al., 2016), laser Doppler vibrometry (Abbaszadeh et al., 2011; Abbaszadeh et al., 2014; Taniwaki et al., 2009), image-based methods (Abdul Rahman et al., 2009; Koc, 2007; Syazwan et al., 2012), infrared spectroscopy (Jie et al., 2014; Lohumi et al., 2013; Yao et al., 2013), and dielectric spectroscopy (Nelson et al., 2007a; 2007b). Nevertheless, the techniques involving vibration property are sensitive to the noise of surrounding and mechanical vibration (Tian et al., 2007). Saito et al. (1996) have investigated the application of nuclear magnetic resonance imaging (MRI) in detecting soluble solids content of watermelon. However, the equipment used in MRI is quite expensive and more complex since this technique is not dependent on the difference between internal flesh and external surface of the fruit. Therefore, effective non-destructive techniques are needed to increase the commercial value of agricultural produce.

Light backscattering imaging is one of the novel methods which has recently arisen as an alternative to machine vision by combining imaging and spectroscopic approaches for quality control and safety assessment of crops and agricultural produce (Mollazade et al., 2012). The technique of light backscattering imaging is categorised into three categories based on the usage of the light source and imaging unit: laser light backscattering imaging (LLBI), hyperspectral backscattering imaging, and multispectral backscattering imaging (Adebayo et al., 2016; Mollazade et al., 2012). In addition, the application of LLBI has been used for monitoring fruit quality such as firmness, soluble solids content (SSC), pH, moisture content, colour, total acidity, and maturity level.

Results indicated promising and reliable potential on its application for in-line determination of moisture content changes during drying process of bell peppers (Romano et al., 2012), optimisation and control process equipped with sensors for in-line system in various food processing (Udomkun et al., 2014), as well as detection of water content values to obtain chilling injury in bananas (Hashim et al., 2015). The method offers a non-destructive and low-cost assessment along with advanced processing analysis for predicting quality parameters of various agricultural produce. The fundamental research studies have also proven promising results demonstrating the



versatility and simplicity of the LLBI as an innovative approach for quality assessment of food quality of agricultural produce.

## 1.2 Problem Statements

Nowadays, consumers are demanding for fresh food and agricultural produce which has longer shelf-life. The postharvest handling and storage of the agricultural produce vary in terms of the physiological state as well as the harvest time (Tirkey et al., 2014). There has been a limitation due to the effect of storage on quality parameters of the agricultural produce. The effect of storage is also associated with the loss of nutrition, chemical, and microbiological changes, deterioration of food quality, and detection of defects (Falah et al., 2015). Therefore, optimal storage condition is important to preserve the quality of the fruit and minimise postharvest losses.

Since the current assessment in sorting and grading watermelons involves manual labour, there has been a strong call for the application of automatic and non-destructive devices. The application of manual assessment in sorting and grading processes may lead to non-uniform results as the size-based sorting system may varied in terms of fruit density (Omid et al., 2010). Apart from that, manual sorting also causes slight damage in fruit product such as bruising and mechanical injuries, due to the deterioration of the external defects. Another important factor in manual sorting is the impracticality of the process which is subjected to the subjective assessment according to the surface appearance, texture, and thumping sound (Sun et al., 2010). Besides, the manual sorting is quite labourious which depends very much on the competency of manpower and human skills. Hence, the effective non-destructive approach is needed to replace the application of conventional methods which apparently are not so practical in the modern days.

Watermelon production depends on the various conditions and postharvest handling. The shelf life of seedless watermelon is expected to be longer than seeded watermelon since the seeds produce hormones that generate deterioration. The seedless watermelons have a soft texture and become overripe later than seeded watermelons. Besides, seedless watermelons have immature small seeds and should be free of hard seeds. The selection of seeded and seedless watermelons must have adequate yield and suitable with the production demand according to the market acceptability. Thus, the development of laser-induced backscattering imaging delivers a novel method to classify between the seeded and seedless watermelons. Apart from that, the potential use of backscattering imaging system evaluates the sensing and classification abilities as an indicator for developing automated machine system.

Choosing a suitable watermelon variety is one of the most important decisions by a watermelon producer. The backscattering imaging system classifies the watermelon according to the type of cultivars (seeded vs seedless) and storage day (after harvest). Unlike other agricultural produce, the variation of watermelons in terms of shapes and sizes presents challenges for non-destructive applications during storage. The ability of the system to classify between the storage day is necessary to obtain information on the



condition and quality attributes of the fruit. Accurate analysis based on the classification of the fruit also provides minimal postharvest losses and maintains good fruit quality. The future of classifying watermelons based on the type of cultivars and storage days in possible automated systems might be useful with the progression on multivariate pattern recognition algorithms and suitable device detectors.

The non-destructive methods are recommended due to its rapid process, objective measurements and reliable results (Wu & Sun, 2013). The ability of non-destructive techniques in terms of fast data processing and handling contributes to the high anticipation of good food products for the consumers. A lot of studies have been conducted on the application of LLBI in various crops and conditions such as kiwifruits (Baranyai & Zude, 2009), bananas (Dénes et al., 2013; Hashim et al., 2014, 2013, 2012), apples (Baranyai et al., 2009; Lafuente et al., 2013; Qing et al., 2007, 2008), papayas (Udomkun et al., 2014), citrus fruits (Lorente et al., 2013; Lorente et al., 2015; Lorente et al., 2014), and bell pepper (Romano et al., 2012). Nonetheless, the facts and information on the feasibility of this technique are still inadequate for evaluating quality changes of tropical fruits such as watermelon. Hence, the potential of light scattering in quantifying the quality of seeded and seedless watermelon is investigated.

### **1.3 Importance of Study**

The cultivation of watermelon in Malaysia has been massively developed especially in the East Coast Region for domestic use and export. According to the Food and Agriculture Organization Corporate Statistical Database (FAOSTAT), Malaysia has produced 227 thousand tonnes production of watermelon in 2013. In the agricultural society, much research effort has been put into developing a seedless strain as well as seeded watermelon. Hence, there has been an increased concern in the application of non-invasive computer-aided image processing methods to evaluate fruit properties, chemical constituents, and qualities of both cultivars. Laser-induced light backscattering imaging offers computationally inexpensive technology that might change the production scenarios in fruit industries. Besides that, information about the interaction between seeded and seedless properties and the quality changes during storage could be a baseline study to the development of optimal storage condition not only to watermelon but also to other agricultural produce. The laser backscattering approach has been evaluated on a limited and small scope of agricultural produce. Hence, it is advisable that the effectiveness of laser backscattering approach is investigated over a vast range of agricultural produce for the new database.

### **1.4 Objectives**

The goal of this research is to determine the quality changes of seeded and seedless watermelons during storage non-destructively by means of backscattering imaging. The specific objectives are:

- i) To establish the changes of physicochemical properties in seeded and seedless watermelons during storage.

- ii) To evaluate the interaction between backscattering parameters and physicochemical properties of watermelons.
- iii) To develop a prediction model of quality deterioration during storage using LLBI system.
- iv) To classify the watermelons based on the type of cultivars and storage days.

## **1.5 Scope and Limitations**

The present study aims at exploring the potential use of backscattering imaging for monitoring quality parameters of watermelons. This study was conducted to determine the seeded and seedless properties of watermelon non-destructively by means of backscattering imaging. The samples only cover one variety from each type of the fruit which is Black Beauty (seeded) and Red Seedless (seedless) cultivars of watermelon. Besides, this investigation focuses on one type of LBI which is LLBI using a solid-state laser diode emitting light at 658 nm. The backscattering image is obtained in the two-dimensional (2D) image with the dimension measured in pixel (1392 x 1040 pixels).

## **1.6 Thesis Overview**

The thesis is organised as follows. Chapter 1 describes the background study driving this work. This chapter also outlines the research objectives, scope, and limitation as well as the importance of the study. Chapter 2 provides a literature review of cultivation and quality evaluation of watermelons. This chapter also describes the postharvest handling of the fruit, application, and future prospect of laser-induced backscattering system. Chapter 3 explains the experimental set-up for image acquisition process using backscattering imaging system as well as the procedure of physicochemical and optical properties measurements. Image processing and data analysis are also discussed in this chapter. Chapter 4 discusses the results and findings obtained for each research objective. Chapter 5 summarises the conclusions and achievements of this research, alongside recommendations for future studies.

## REFERENCES

- Abbaszadeh, R., Rajabipour, A., Ahmadi, H., Delshad, M., & Mahjoob, M. (2011). Assessment of watermelon quality using vibration spectra. *Innovative Computing Technology*, 241, 21–29.
- Abbaszadeh, R., Rajabipour, A., Delshad, M., Mahjub, M. J., & Ahmadi, H. (2011). Prediction of watermelon consumer acceptability based on vibration response spectrum. *World Academy of Science, Engineering and Technology*, 5(6), 549–552.
- Abbaszadeh, R., Rajabipour, A., Sadrnia, H., Mahjoob, M. J., Delshad, M., & Ahmadi, H. (2014). Application of modal analysis to the watermelon through finite element modeling for use in ripeness assessment. *Journal of Food Engineering*, 127, 80–84.
- Abbaszadeh, R., Rajabipour, A., Ying, Y., Delshad, M., Mahjoob, M. J., & Ahmadi, H. (2015). Nondestructive determination of watermelon flesh firmness by frequency response. *LWT - Food Science and Technology*, 60(1), 637–640.
- Abdul Rahman, F. Y., Mohd Shah Baki, S. R., Mohd Yassin, A. I., Md Tahir, N., & Wan Ishak, W. I. (2009). Monitoring of watermelon ripeness based on fuzzy logic. In *2009 WRI World Congress on Computer Science and Information Engineering, CSIE 2009* (Vol. 6, pp. 67–70).
- Abu Bakar, B. H., Ishak, A. J., Shamsuddin, R., & Wan Hassan, W. Z. (2013). Ripeness level classification for pineapple using RGB and HSI colour maps. *Journal of Theoretical and Applied Information Technology*, 57(3), 587–593.
- Adebayo, S. E., Hashim, N., Abdan, K., & Hanafi, M. (2016). Application and potential of backscattering imaging techniques in agricultural and food processing – A review. *Journal of Food Engineering*, 169, 155–164.
- Ajuru, M. G., & Okoli, B. E. (2013). The morphological characterization of the melon species in the family Cucurbitaceae Juss., and their utilization in Nigeria. *International Journal of Modern Botany*, 3(2), 15–19.
- Al Ohali, Y. (2011). Computer vision based date fruit grading system: Design and implementation. *Journal of King Saud University - Computer and Information Sciences*, 23(1), 29–36.
- Albert, S. (2013). Vegetable Crop Soil pH Tolerances. Retrieved March 9, 2016, from <http://www.harvesttotable.com/2013/12/vegetable-crop-soil-ph-tolerances/>
- Altuntaş, E., & Yıldız, M. (2007). Effect of moisture content on some physical and mechanical properties of faba bean (*Vicia faba* L.) grains. *Journal of Food Engineering*, 78(1), 174–183.

- Amin, M. N., Hossain, M. A., & Roy, K. C. (2004). Effects of moisture content on some physical properties of lentil seeds. *Journal of Food Engineering*, 65(1), 83–87.
- Antonucci, F., Pallottino, F., Paglia, G., Palma, A., D'Aquino, S., & Menesatti, P. (2011). Non-destructive estimation of mandarin maturity status through portable vis-nir spectrophotometer. *Food and Bioprocess Technology*, 4(5), 809–813.
- Ariana, D. P., & Lu, R. (2010). Evaluation of internal defect and surface color of whole pickles using hyperspectral imaging. *Journal of Food Engineering*, 96(4), 583–590.
- Armstrong, P. R., Stone, M. L., & Brusewitz, G. H. (1997). Nondestructive acoustic and compression measurements of watermelon for internal damage detection. *Applied Engineering in Agriculture*, 13(5), 641–645.
- Armstrong, W. P. (2001). Plant Hybrids. <http://waynesword.palomar.edu/hybrids1.htm>. Retrieved 9 March 2016.
- Baranyai, L. (2011). *Estimation of Optical Properties in Postharvest and Processing Technology*. (Prof. Shaul Mordechai, Ed.), *Applications of Monte Carlo Method in Science and Engineering*. InTech.
- Baranyai, L., Regen, C., & Zude, M. (2009). Monitoring optical properties of apple tissue during cool storage. In *Proceedings of CIGR Workshop on Image Analyses in Agriculture* (Vol. 69, pp. 112–119).
- Baranyai, L., & Zude, M. (2009). Analysis of laser light propagation in kiwifruit using backscattering imaging and Monte Carlo simulation. *Computers and Electronics in Agriculture*, 69(1), 33–39.
- Bejo, S. K., & Kamaruddin, S. (2014). Determination of Chokanan mango sweetness (*Mangifera indica*) using non-destructive image processing technique. *Australian Journal of Crop Science*, 8(4), 475–480.
- Bertone, E., Venturello, a., Leardi, R., & Geobaldo, F. (2012). Prediction of the optimum harvest time of “Scarlet” apples using DR-UV-Vis and NIR spectroscopy. *Postharvest Biology and Technology*, 69, 15–23.
- Biolatto, A., Salitto, V., Cantet, R. J. C., & Pensel, N. A. (2005). Influence of different postharvest treatments on nutritional quality of grapefruits. *LWT - Food Science and Technology*, 38(2), 131–134.
- Bonazzi, C., & Dumoulin, E. (2011). *Quality Changes in Food Materials as Influenced by Drying Processes*. (E. Tsotsas & A. S. Mujumdar, Eds.) (First Edit, Vol. 3). Wiley-VCH Verlag GmbH & Co. KGaA.
- Both, A. J., Benjamin, L., Franklin, J., Holroyd, G., Incoll, L. D., Lefsrud, M. G., & Pitkin, G. (2015). Guidelines for measuring and reporting environmental parameters for experiments in greenhouses. *Plant Methods*, 11(43), 1–18.

- Carvalho, C. P., & Betancour, J. A. (2015). Quality characterization of Andean blackberry fruits (*Rubus glaucus* Benth.) in different maturity stages in Antioquia. *Agronomía Colombiana*, 33(1), 74–83.
- Costa, C., Menesatti, P., Paglia, G., Pallottino, F., Aguzzi, J., Rimatori, V., Reforgiato Recupero, G. (2009). Quantitative evaluation of Tarocco sweet orange fruit shape using optoelectronic elliptic Fourier based analysis. *Postharvest Biology and Technology*, 54(1), 38–47.
- Cubero, S., Aleixos, N., Moltó, E., Gómez-Sanchis, J., & Blasco, J. (2011). Advances in Machine Vision Applications for Automatic Inspection and Quality Evaluation of Fruits and Vegetables. *Food and Bioprocess Technology*, 4(4), 487–504.
- Dénes, D. L., Parrag, V., Felföldi, J., & Baranyai, L. (2013). Influence of parameters of drying on laser induced diffuse reflectance of banana discs. *Journal of Food Physics*, 26, 11–16.
- Diezma-Iglesias, B., Ruiz-Altisent, M., & Barreiro, P. (2004). Detection of internal quality in seedless watermelon by acoustic impulse response. *Biosystems Engineering*, 88(2), 221–230.
- Diezma-Iglesias, B., Ruiz-Altisent, M., & Jancsó, P. (2005). Vibrational analysis of seedless watermelons: use in the detection of internal hollows. *Spanish Journal of Agricultural Research*, 3(1), 52–60.
- DOA. (2010). *Panduan menanam tembikai (Tanaman Jangka Pendek dan Sederhana)*. [http://pertanianmjg.perak.gov.my/bahasa/panduan\\_tembeikai.htm](http://pertanianmjg.perak.gov.my/bahasa/panduan_tembeikai.htm). Retrieved 3 March 2015.
- Eicher, D. J. (2013). *COMETS!: Visitors from Deep Space* (pp. 168-173). Cambridge, UK: Cambridge University Press.
- El-Ramady, H. R., Domokos-Szabolcsy, É., Abdalla, N. A., Taha, H. S., & Fári, M. (2015). Postharvest Management of Fruits and Vegetables Storage. *Sustainable Agriculture Reviews*, 15, 65–152.
- Elwakil, W. M., & Mossler, M. A. (2010). *Florida Crop/Pest Management Profiles : Watermelon*. <https://edis.ifas.ufl.edu/pi031>. Retrieved 4 May 2016.
- Esehaghbeygi, A., Ardforoushan, M., Monajemi, S. A. H., & Masoumi, A. A. (2010). Digital image processing for quality ranking of saffron peach. *International Agrophysics*, 24(2), 115–120.
- Fadilah, N., Mohamad-Saleh, J., Halim, Z. A., Ibrahim, H., & Ali, S. S. S. (2012). Intelligent color vision system for ripeness classification of oil palm fresh fruit bunch. *Sensors*, 12(10), 14179–14195.
- Falah, M. A. F., Nadine, M. D., & Suryandono, A. (2015). Effects of Storage Conditions on Quality and Shelf-life of Fresh-cut Melon (*Cucumis Melo* L.) and Papaya (*Carica Papaya* L.). *Procedia Food Science*, 3, 313–322.



- Feng, M., Ghafoor, K., Seo, B., Yang, K., & Park, J. (2013). Effects of ultraviolet-C treatment in Teflon-coil on microbial populations and physico-chemical characteristics of watermelon juice. *Innovative Food Science and Emerging Technologies*, 19, 133–139.
- FAO. (2015). *Global production of vegetables in 2013, by type (in million metric tons)*. <https://www.statista.com/statistics/264065/global-production-of-vegetables-by-type/>. Retrieved 17 May 2016.
- García-Ramos, F. J., Valero, C., Homer, I., Ortiz-Cañavate, J., & Ruiz-Altisent, M. (2005). Non-destructive fruit firmness sensors: a review. *Spanish Journal of Agricultural Research*, 3(1), 61–73.
- Gómez, A. H., Wang, J., & Pereira, A. G. (2005). Impulse response of pear fruit and its relation to Magness-Taylor firmness during storage. *Postharvest Biology and Technology*, 35(2), 209–215.
- González-Centeno, M. R., Knoerzer, K., Sabarez, H., Simal, S., Rosselló, C., & Femenia, A. (2014). Effect of acoustic frequency and power density on the aqueous ultrasonic-assisted extraction of grape pomace (*Vitis vinifera* L.) – A response surface approach. *Ultrasonics Sonochemistry*, 21(6), 2176–2184.
- Hashim, N., Janius, R. B., Abdul, R., Osman, A., Shitan, M., & Zude, M. (2014). Changes of backscattering parameters during chilling injury in bananas. *Journal of Engineering Science and Technology*, 9(3), 314–325.
- Hashim, N., Janius, R. B., Baranyai, L., Rahman, R. A., Osman, A., & Zude, M. (2012). Kinetic Model for Colour Changes in Bananas During the Appearance of Chilling Injury Symptoms. *Food and Bioprocess Technology*, 5(8), 2952–2963.
- Hashim, N., Janius, R. B., Rahman, R. A., & Osman, A. (2013). Application of Computer Vision in the Detection of Chilling Injury in Bananas. *Pertanika J. Sci. & Technol.*, 21(1), 111–118.
- Hashim, N., Janius, R. B., & Zude, M. (2015). Effect of Water Content on Backscattering Parameters. *Australian Journal of Basic and Applied Sciences*, 9(7), 265–268.
- Hashim, N., Pflanz, M., Regen, C., Janius, R. B., Abdul Rahman, R., Osman, A., Zude, M. (2013). An approach for monitoring the chilling injury appearance in bananas by means of backscattering imaging. *Journal of Food Engineering*, 116(1), 28–36.
- Ibarra-Garza, I. P., Ramos-Parra, P. A., Hernández-Brenes, C., & Jacobo-Velázquez, D. A. (2015). Effects of postharvest ripening on the nutraceutical and physicochemical properties of mango (*Mangifera indica* L. cv Keitt). *Postharvest Biology and Technology*, 103, 45–54.
- Ignat, T., Schmilovitch, Z., Fefoldi, J., Steiner, B., & Alkalai-Tuvia, S. (2012). Non-destructive measurement of ascorbic acid content in bell peppers by VIS-NIR and

SWIR spectrometry. *Postharvest Biology and Technology*, 74, 91–99.

Jaiswal, P., Jha, S. N., & Bharadwaj, R. (2012). Non-destructive prediction of quality of intact banana using spectroscopy. *Scientia Horticulturae*, 135, 14–22.

Jha, S. N., & Matsuoka, T. (2000). Non-destructive techniques for quality evaluation of intact fruits and vegetables. *Food Science and Technology Research*, 6(4), 248–251.

Jha, S. N., Rai, D. R., & Shrama, R. (2012). Physico-chemical quality parameters and overall quality index of apple during storage. *Journal of Food Science and Technology*, 49(5), 594–600.

Jie, D., Xie, L., Fu, X., Rao, X., & Ying, Y. (2013). Variable selection for partial least squares analysis of soluble solids content in watermelon using near-infrared diffuse transmission technique. *Journal of Food Engineering*, 118(4), 387–392.

Jie, D., Xie, L., Rao, X., & Ying, Y. (2014). Using visible and near infrared diffuse transmittance technique to predict soluble solids content of watermelon in an on-line detection system. *Postharvest Biology and Technology*, 90, 1–6.

Joseph, G. (2005). *Fundamentals of Remote Sensing* (pp. 88-90 ). India: Universities Press.

Khojastehnazhand, M., Omid, M., & Tabatabaefar, A. (2010). Development of a lemon sorting system based on color and size. *African Journal of Plant Science*, 4(4), 122–127.

Koc, A. B. (2007). Determination of watermelon volume using ellipsoid approximation and image processing. *Postharvest Biology and Technology*, 45(3), 366–371.

Koocheki, A., Razavi, S. M. A., Milani, E., Moghadam, T. M., Abedini, M., Alamediyan, S., & Izadkhah, S. (2007). Physical properties of watermelon seed as a function of moisture content and variety. *International Agrophysics*, 21, 349–359.

Kyriacou, M. C., & Soteriou, G. (2015). Quality and postharvest performance of watermelon fruit in response to grafting on interspecific cucurbit rootstocks. *Journal of Food Quality*, 38, 21–29.

Lafuente, V., Val, J., Urzola, C., & Negueruela, I. (2013). Determination of quality parameters in apple “Smoother Golden Delicious” using backscattering laser imaging. In *8th Iberoamerican Optics Meeting and 11th Latin American Meeting on Optics, Lasers, and Applications* (Vol. 8785, pp. 1–6).

Li, J., Chen, L., Huang, W., Wang, Q., Zhang, B., Tian, X., Li, B. (2016). Multispectral detection of skin defects of bi-colored peaches based on vis–NIR hyperspectral imaging. *Postharvest Biology and Technology*, 112, 121–133.

Liaghat, S., Mansor, S., Ehsani, R., Shafri, H. Z. M., Meon, S., & Sankaran, S. (2014).

- Mid-infrared spectroscopy for early detection of basal stem rot disease in oil palm. *Computers and Electronics in Agriculture*, 101, 48–54.
- Liew, C. Y., & Lau, C. Y. (2012). Determination of quality parameters in Cavendish banana during ripening by NIR spectroscopy. *International Food Research Journal*, 19(2), 751–758.
- Liming, X., & Yanchao, Z. (2010). Automated strawberry grading system based on image processing. *Computers and Electronics in Agriculture*, 71(SUPPL. 1), 32–39.
- Liu, S., Jiang, L., & Li, Y. (2011). Research of aqueous enzymatic extraction of watermelon seed oil of ultrasonic pretreatment assisted. In *Procedia Engineering* (Vol. 15, pp. 4949–4955).
- Liu, W., Zhao, S., Cheng, Z., Wan, X., Yan, Z., & King, S. R. (2010). Lycopene and citrulline contents in watermelon (*Citrullus lanatus*) fruit with different ploidy and changes during fruit development. *Acta Horticulturae*, 871, 543–550.
- Liu, Y., Sun, X., Zhang, H., & Aiguo, O. (2010). Nondestructive measurement of internal quality of Nanfeng mandarin fruit by charge coupled device near infrared spectroscopy. *Computers and Electronics in Agriculture*, 71S, 5–9.
- Lohumi, S., Mo, C., Kang, J., Hong, S., & Cho, B. (2013). Nondestructive evaluation for the viability of watermelon (*Citrullus lanatus*) seeds using fourier transform near infrared spectroscopy. *Journal of Biosystems Engineering*, 38(4), 312–317.
- Lorente, D., Juste, F., & Blasco, J. (2014). Detection of decay in citrus fruit using absorption and scattering properties. *Proceedings International Conference of Agricultural Engineering, Zurich*, 6–10.
- Lorente, D., Zude, M., Idler, C., Gómez-Sanchis, J., & Blasco, J. (2015). Laser-light backscattering imaging for early decay detection in citrus fruit using both a statistical and a physical model. *Journal of Food Engineering*, 154, 76–85.
- Lorente, D., Zude, M., Regen, C., Palou, L., Gómez-Sanchis, J., & Blasco, J. (2013). Early decay detection in citrus fruit using laser-light backscattering imaging. *Postharvest Biology and Technology*, 86, 424–430.
- Louw, E. D., & Theron, K. I. (2010). Robust prediction models for quality parameters in Japanese plums (*Prunus salicina* L.) using NIR spectroscopy. *Postharvest Biology and Technology*, 58(3), 176–184.
- Lu, R. (2004). Multispectral imaging for predicting firmness and soluble solids content of apple fruit. *Postharvest Biology and Technology*, 31(2), 147–157.
- Lu, R., & Ariana, D. P. (2013). Detection of fruit fly infestation in pickling cucumbers using a hyperspectral reflectance/transmittance imaging system. *Postharvest Biology and Technology*, 81, 44–50.



- Lysiak, G. (2012). The base colour of fruit as an indicator of optimum harvest date for two apple cultivars (*Malus domestica* Borkh.). *Folia Horticulturae*, 24(1), 81–89.
- Magwaza, L. S., & Opara, U. L. (2015). Analytical methods for determination of sugars and sweetness of horticultural products—A review. *Scientia Horticulturae*, 184, 179–192.
- Manickavasagan, A., Al-Mezeini, N. K., & Al-Shekaili, H. N. (2014). RGB color imaging technique for grading of dates. *Scientia Horticulturae*, 175, 87–94.
- Mao, J., Yu, Y., Rao, X., & Wang, J. (2016). Firmness prediction and modeling by optimizing acoustic device for watermelons. *Journal of Food Engineering*, 168, 1–6.
- Mavi, K. (2010). The relationship between seed coat color and seed quality in watermelon Crimson sweet. *Horticultural Science*, 37(2), 62–69.
- McGregor, B. M. (1989). *Tropical Products Transport Handbook*. United States Department of Agriculture, Agriculture Handbook No. 668. p. 148.
- Moghim, A., Aghkhani, M. H., Sazgarnia, A., & Sarmad, M. (2010). Vis/NIR spectroscopy and chemometrics for the prediction of soluble solids content and acidity (pH) of kiwifruit. *Biosystems Engineering*, 106(3), 295–302.
- Mollazade, K., Omid, M., Akhlaghian Tab, F., Kalaj, Y. R., Mohtasebi, S. S., & Zude, M. (2013). Analysis of texture-based features for predicting mechanical properties of horticultural products by laser light backscattering imaging. *Computers and Electronics in Agriculture*, 98, 34–45.
- Mollazade, K., Omid, M., Tab, F. A., & Mohtasebi, S. S. (2012). Principles and Applications of Light Backscattering Imaging in Quality Evaluation of Agro-food Products: A Review. *Food and Bioprocess Technology*, 5(5), 1465–1485.
- Mynewshub. (2015). Penanam Tembikai Di Setiu Mengeluh Harga Tembikai Jatuh. <http://www.mynewshub.cc/terkini/penanam-tembikai-di-setiu-mengeluh-harga-tembikai-jatuh>. Retrieved 2 March 2016.
- NARI. (2003). *Watermelon: Postharvest Care and Market Preparation*. Technical Bulletin No. 2. [http://pdf.usaid.gov/pdf\\_docs/Pnacy822.pdf](http://pdf.usaid.gov/pdf_docs/Pnacy822.pdf). Retrieved 23 August 2015.
- Nasaruddin, A. S., Mohd Shah Baki, S. R., & Md. Tahir, N. (2011). Watermelon maturity level based on rind colour as categorization features. In *2011 IEEE Colloquium on Humanities, Science and Engineering, CHUSER 2011* (pp. 545–550).
- Nawi, N. M., Jensen, T., & Chen, G. (2013). Application of spectroscopic method to predict sugar content of sugarcane internodes, 41(2), 211–220.
- Nelson, S. O., Guo, W. C., Trabelsi, S., & Kays, S. J. (2007a). Sensing quality of

- watermelons through dielectric permittivity. In *IEEE Antennas and Propagation Society, AP-S International Symposium (Digest)* (Vol. 712100, pp. 285–288).
- Nelson, S. O., Guo, W., Trabelsi, S., & Kays, S. J. (2007b). Dielectric spectroscopy of watermelons for quality sensing. *Measurement Science and Technology*, 18(7), 1887–1892.
- Nishizu, T., Ikeda, Y., Torikata, Y., Manmoto, S., Umehara, T., & Mizukami, T. (2001). Automatic, Continuous Food Volume Measurement with a Helmholtz Resonator. *Agricultural Engineering International: The CIGR Journal of Scientific Research and Development*, 3, 1–10.
- Noh, J., Kim, J. M., Sheikh, S., Lee, S. G., Lim, J. H., Seong, M. H., & Jung, G. T. (2013). Effect of heat treatment around the fruit set region on growth and yield of watermelon [*Citrullus lanatus* (Thunb.) Matsum. and Nakai]. *Physiology and Molecular Biology of Plants*, 19(4), 509–514.
- Nunes, M. C. do N. (2009). *Color Atlas of Postharvest Quality of Fruits and Vegetables* (pp. 208–210). New Jersey: John Wiley & Sons.
- Omid, M., Khojastehnazhand, M., & Tabatabaefar, A. (2010). Estimating volume and mass of citrus fruits by image processing technique. *Journal of Food Engineering*, 100, 315–321.
- Oyeleke, G. O., Olagunju, E. O., & Ojo, A. (2012). Functional and Physicochemical Properties of Watermelon (*Citrullus Lanatus*) Seed and Seed-Oil. *IOSR Journal of Applied Chemistry*, 2(2), 29–31.
- Pathare, P. B., Opara, U. L., & Al-Said, F. A. J. (2013). Colour measurement and analysis in fresh and processed foods: a review. *Food and Bioprocess Technology*, 6(1), 36–60.
- Peng, Y., & Lu, R. (2006). Improving apple fruit firmness predictions by effective correction of multispectral scattering images. *Postharvest Biology and Technology*, 41(3), 266–274.
- Peng, Y., & Lu, R. (2008). Analysis of spatially resolved hyperspectral scattering images for assessing apple fruit firmness and soluble solids content. *Postharvest Biology and Technology*, 48(1), 52–62.
- Perkins-Veazie, P., Beaulieu, J. C., & Siddiq, M. (2012). Watermelon, Cantaloupe and Honeydew. In *Tropical and Subtropical Fruits* (pp. 549–568). Oxford, UK: Wiley-Blackwell.
- Perkins-Veazie, P., & Collins, J. K. (2004). Flesh quality and lycopene stability of fresh-cut watermelon. *Postharvest Biology and Technology*, 31(2), 159–166.
- Pholpho, T., Pathaveerat, S., & Sirisomboon, P. (2011). Classification of longan fruit bruising using visible spectroscopy. *Journal of Food Engineering*, 104(1), 169–172.

- Piazza, L., & Giovenzana, V. (2015). Instrumental acoustic-mechanical measures of crispness in apples. *Food Research International*, 69, 209–215.
- Prahl, S. A., van Gemert, M. J. C., & Welch, A. J. (1993). Determining the optical properties of turbid media by using the adding-doubling method. *Applied Optics*, 32(4), 559–568.
- Pua, E. C., & Davey, M. R. (2007). *Transgenic Crops V* (pp. 131-132). Berlin, Germany: Springer Science & Business Media.
- Qing, Z., Ji, B., & Zude, M. (2007). Predicting soluble solid content and firmness in apple fruit by means of laser light backscattering image analysis. *Journal of Food Engineering*, 82(1), 58–67.
- Qing, Z., Ji, B., & Zude, M. (2008). Non-destructive analyses of apple quality parameters by means of laser-induced light backscattering imaging. *Postharvest Biology and Technology*, 48(2), 215–222.
- Quek, S. Y., Chok, N. K., & Swedlund, P. (2007). The physicochemical properties of spray-dried watermelon powders. *Chemical Engineering and Processing: Process Intensification*, 46(5), 386–392.
- Rahman, M. M., Moniruzzaman, M., Ahmad, M. R., Sarker, B. C., & Khurshid Alam, M. (2014). Maturity stages affect the postharvest quality and shelf-life of fruits of strawberry genotypes growing in subtropical regions. *Journal of the Saudi Society of Agricultural Sciences*, 15(1), 28–37.
- Rimando, A. M., & Perkins-Veazie, P. M. (2005). Determination of citrulline in watermelon rind. *Journal of Chromatography A*, 1078, 196–200.
- Romano, G., Argyropoulos, D., Nagle, M., Khan, M. T., & Müller, J. (2012). Combination of digital images and laser light to predict moisture content and color of bell pepper. *Journal of Food Engineering*, 109(3), 438-448.
- Romano, G., Baranyai, L., Gottschalk, K., & Zude, M. (2008). An approach for monitoring the moisture content changes of drying banana slices with laser light backscattering imaging. *Food and Bioprocess Technology*, 1(4), 410–414.
- Romano, G., Nagle, M., Argyropoulos, D., & Müller, J. (2011). Laser light backscattering to monitor moisture content, soluble solid content and hardness of apple tissue during drying. *Journal of Food Engineering*, 104(4), 657–662.
- Rushing, J. W., Keinath, A. P., & Cook, W. P. (1999). Postharvest Development and Transmission of Watermelon Fruit Blotch. *HortTechnology*, 9(2), 217–219.
- Saito, K., Miki, T., Hayashi, S., Kajikawa, H., Shimada, M., Kawate, Y., Suzuki, M. (1996). Application of magnetic resonance imaging to non-destructive void detection in watermelon. *Cryogenics*, 36(12), 1027–1031.
- Saldaña, E., Quevedo, R., Siche, R., Lujan, M., & Quevedo, R. (2013). Review :

- computer vision applied to the inspection and quality control of fruits and vegetables. *Brazilian Journal of Food Technology, Campinas*, 16(4), 254–272.
- Salomon, D. (2012). *Data Compression: The Complete Reference* (pp. 277-278). Berlin, Germany: Springer.
- Sankaran, S., Mishra, A., Maja, J. M., & Ehsani, R. (2011). Visible-near infrared spectroscopy for detection of Huanglongbing in citrus orchards. *Computers and Electronics in Agriculture*, 77(2), 127–134.
- Shah Rizam, M. S. B., Annuar, M. Z. M., Yassin, I. M., Hassan, H. A., & Zabidi, A. (2010). Non-destructive classification of watermelon ripeness using Mel-frequency cepstrum coefficients and multilayer perceptrons. In *Proceedings of the International Joint Conference on Neural Networks* (pp. 1–6).
- Shamsudin, R., Daud, W. R. W., Takriff, M. S., & Hassan, O. (2007). Physicochemical Properties of the Josapine Variety of Pineapple Fruit. *International Journal of Food Engineering*, 3(5), 1–12.
- Shamsudin, R., Ling, C. S., Ling, C. N., Muda, N., & Hassan, O. (2009). Chemical compositions of the jackfruit juice (*Artocarpus*) cultivar J33 during storage. *Journal of Applied Sciences*, 9(17), 3202-3204.
- Stajanko, D., Rakun, J., & Blanke, M. (2009). Modelling apple fruit yield using image analysis for fruit colour, shape and texture. *European Journal of Horticultural Science*, 74(6), 260–267.
- Sun, T., Huang, K., Xu, H., & Ying, Y. (2010). Research advances in nondestructive determination of internal quality in watermelon/melon: A review. *Journal of Food Engineering*, 100(4), 569–577.
- Syazwan, N. A., Rizam, M. S. B. S., & Nooritawati, M. T. (2012). Categorization Of Watermelon Maturity Level Based On Rind Features. In *Procedia Engineering* (Vol. 41, pp. 1398–1404).
- Taghizadeh, M., Gowen, A. a., & O'Donnell, C. P. (2011). Comparison of hyperspectral imaging with conventional RGB imaging for quality evaluation of *Agaricus bisporus* mushrooms. *Biosystems Engineering*, 108(2), 191–194.
- Takizawa, K., Nakano, K., Ohashi, S., Yoshizawa, H., Wang, J., & Sasaki, Y. (2014). Development of nondestructive technique for detecting internal defects in Japanese radishes. *Journal of Food Engineering*, 126, 43–47.
- Taniwaki, M., Hanada, T., & Sakurai, N. (2009). Postharvest quality evaluation of “Fuyu” and “Taishuu” persimmons using a nondestructive vibrational method and an acoustic vibration technique. *Postharvest Biology and Technology*, 51, 80–85.
- Taniwaki, M., & Sakurai, N. (2008). Texture measurement of cabbages using an acoustical vibration method. *Postharvest Biology and Technology*, 50, 176–181.

- Taniwaki, M., Takahashi, M., & Sakurai, N. (2009). Determination of optimum ripeness for edibility of postharvest melons using nondestructive vibration. *Food Research International*, 42(1), 137–141. 007
- Thybo, A. K., Jespersen, S. N., Lærke, P. E., & Stødtkilde-Jørgensen, H. J. (2004). Nondestructive detection of internal bruise and spraing disease symptoms in potatoes using magnetic resonance imaging. *Magnetic Resonance Imaging*, 22(9), 1311–1317.
- Tian, H.-Q., Ying, Y.-B., Lu, H.-S., Fu, X.-P., & Yu, H.-Y. (2007). Measurement of soluble solids content in watermelon by Vis/NIR diffuse transmittance technique. *Journal of Zhejiang University SCIENCE B*, 8(2), 105–110.
- Tilley, R. J. D. (2010). *Colour and the Optical Properties of Materials: An Exploration of the Relationship Between Light, the Optical Properties of Materials and Colour, 2nd Edition - Richard J. D. Tilley*. Chichester: Wiley.
- Tirkey, B., Pal, U. S., Bal, L. M., Sahoo, N. R., Bakhara, C. K., & Panda, M. K. (2014). Evaluation of physico-chemical changes of fresh-cut unripe papaya during storage. *Food Packaging and Shelf Life*, 1(2), 190–197.
- Tlili, I., Hdider, C., Lenucci, M. S., Riadh, I., Jebari, H., & Dalessandro, G. (2011). Bioactive compounds and antioxidant activities of different watermelon (*Citrullus lanatus* (Thunb.) Mansfeld) cultivars as affected by fruit sampling area. *Journal of Food Composition and Analysis*, 24(3), 307–314.
- Udomkun, P., Nagle, M., Mahayothee, B., & Müller, J. (2014). Laser-based imaging system for non-invasive monitoring of quality changes of papaya during drying. *Food Control*, 42, 225–233.
- Unay, D., & Similar. (2006). *Multispectral Image Processing and Pattern Recognition Techniques for Quality Inspection of Apple Fruits* (pp. 21-24). Presses univ. de Louvain.
- Valente, M., Leardi, R., Self, G., Luciano, G., & Pain, J. P. (2009). Multivariate calibration of mango firmness using vis/NIR spectroscopy and acoustic impulse method. *Journal of Food Engineering*, 94(1), 7–13.
- Vesali, F., Gharibkhani, M., Komarizadeh, M. H., Branch, A., & Club, Y. R. (2011). An approach to estimate moisture content of apple with image processing method. *Australian Journal of Crop Science*, 5(2), 111–115.
- Wani, A. A., Sogi, D. S., Singh, P., & Shivhare, U. S. (2011). Characterization and functional properties of watermelon (*Citrullus lanatus*) seed protein isolates and salt assisted protein concentrates. *Food Science and Biotechnology*, 20(4), 877–887.
- Wechter, W. P., Levi, A., Harris, K. R., Davis, A. R., Fei, Z., Katzir, N., Trebitsh, T. (2008). Gene expression in developing watermelon fruit. *BMC Genomics*, 9, 275–287.



- Wehner, T. C. (1996). *Watermelon Crop Information Breeding Methods*. <http://cuke.hort.ncsu.edu/cucurbit/wmelon/wmhndbk/wmbreeding.html>. Retrieved 23 August 2015.
- Perkins-Veazie, P., Beaulieu, J. C., & Siddiq, M. (2012). Watermelon, Cantaloupe and Honeydew. In *Tropical and Subtropical Fruits* (pp. 549–568). Oxford, UK: Wiley-Blackwell.
- Wen, Z., Shen, L., Jing, H., & Fang, K. (2010). Color and shape grading of citrus fruit based on machine vision with fractal dimension. In *2010 3rd International Congress on Image and Signal Processing* (pp. 898–903).
- Wu, D., & Sun, D. W. (2013). Colour measurements by computer vision for food quality control - A review. *Trends in Food Science and Technology*, 29(1), 5–20.
- Wu, L., He, J., Liu, G., Wang, S., & He, X. (2016). Detection of common defects on jujube using Vis-NIR and NIR hyperspectral imaging. *Postharvest Biology and Technology*, 112, 134–142.
- Yao, Y., Chen, H., Xie, L., & Rao, X. (2013). Assessing the temperature influence on the soluble solids content of watermelon juice as measured by visible and near-infrared spectroscopy and chemometrics. *Journal of Food Engineering*, 119(1), 22–27.
- Yau, E. W., Rosnah, S., Noraziah, M., Chin, N. L., & Osman, H. (2010). Physico-chemical compositions of the red seedless watermelons (*Citrullus Lanatus*). *International Food Research Journal*, 17(2), 327–334.
- Zhang, B., Huang, W., Li, J., Zhao, C., Fan, S., Wu, J., & Liu, C. (2014). Principles, developments and applications of computer vision for external quality inspection of fruits and vegetables: A review. *Food Research International*, 62, 326–343.
- Zhang, W., Cui, D., & Ying, Y. (2014). Nondestructive measurement of pear texture by acoustic vibration method. *Postharvest Biology and Technology*, 96, 99–105.
- Zhao, Y., Wang, D., & Qian, D. (2009). Machine Vision Based Image Analysis for the Estimation of Pear External Quality. In *2009 Second International Conference on Intelligent Computation Technology and Automation* (pp. 629–632).
- Zheng, C., Sun, D.-W., & Zheng, L. (2006). Recent developments and applications of image features for food quality evaluation and inspection – A review. *Trends in Food Science & Technology*, 17(12), 642–655.
- Zou, X., & Zhao, J. (2015). *Nondestructive Measurement in Food and Agro-products* (pp. 14–16). Berlin, Germany: Springer.