UNIVERSITI PUTRA MALAYSIA

DEVELOPMENT OF GIS-BASED SEBAL MODEL FOR ESTIMATION OF EVAPOTRANSPIRATION IN IRAQ

HUSSEIN SABAH JABER

FK 2017 54

DEVELOPMENT OF GIS-BASED SEBAL MODEL FOR ESTIMATION OF EVAPOTRANSPIRATION IN IRAQ

By

HUSSEIN SABAH JABER

Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, In Fulfillment of the Requirements for the Degree of Doctor of Philosophy

April 2017

DEDICATION

This dissertation is dedicated to my father, who taught me the meaning of life, patience, and who provided unconditional support with my studies all the way since I entered this life. It is also dedicated to my mother, who has always given me courage to pursue my dreams.

I dedicate this work and give special thanks to my main supervisor Prof. Dato .Dr. Shattri Mansor .This dissertation is dedicated to my wife and my brothers, who have supported me during this research.

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in Fulfillment of the requirement for the degree of Doctor of Philosophy

DEVELOPMENT OF GIS-BASED SEBAL MODEL FOR ESTIMATION OF EVAPOTRANSPIRATION IN IRAQ.

By

HUSSEIN SABAH JABER

April 2017

Chairman : Prof. Dato' Shattri Mansor, PhD
Faculty : Engineering

A change in weather parameters and climate will result in a significant change in evapotranspiration. Iraq suffers from problems such as reduction in water availability and unpredictable climate change that would affect irrigated agriculture and evapotranspiration. Therefore, estimation of evapotranspiration and standardized measurement are important because evapotranspiration (ET) is the means for exploiting irrigation and irrigation is considered as the backbone of the peasant society.

Most of the studies in Iraq depend on traditional methods to estimate evapotranspiration. These conventional methods are not practical for large areas because it is difficult and costly. Therefore, this research aims to use remote sensing (satellite imagery data) and GIS as modern technologies to estimate evapotranspiration.

In this research, the proposed model has been developed based on equations of SEBAL by using GIS to make a simplified model for estimation of evapotranspiration automatically that leads to a reduction in cost and time and saves effort. Subsequently, the proposed GIS-based SEBAL model was evaluated with field data by using regression coefficient. The area surrounding the Al-Hindiyah barrage has been selected as a study area because it is one of the most significant water resources in the middle part of Iraq. A series of Landsat OLI (Operational Land Imager) satellite images and climate data of the study area have been collected to determine actual evapotranspiration using the GIS-based model. In addition, actual evapotranspiration has been used to assess irrigation performance based on several indicators and to analyze water balance depending on the curve number method in GIS for the study area, respectively.

The results indicate that the proposed GIS-based SEBAL model for estimation of actual evapotranspiration has reasonable agreement with the field data based on the values of coefficient of variance(CoV) equal to (0.75%, 2.2%, 0.68% and% 2.27%) indicates that the predicted results of the SEBAL model have high accuracy and consistency. The mean value of the SEBAL model was close to 1.0 (0.99, 0.98, 0.99 and 1.01), which indicated a good correlation between the measured and estimated Et. Therefore, the SEBAL model efficiently estimated the Et.

In addition, the results of irrigation performance were poor depending on comparison values of irrigation performance indicator results with recommended values of these indicators. Moreover, the results showed a close agreement between rainfall and runoff based on the value of the CoV values between Q observed/ Q proposed less than Q observed/ Q calculated indicates that the proposed model results have high accuracy and consistency than existing model. Therefore, the proposed model efficiently estimated the runoff.

Furthermore, the change of water content (ΔS) for the total study area was observed to have positive values that indicated that there was a percolation of groundwater in the crop root zone that can be used when water was insufficient.

This study concludes that the development of the GIS-based SEBAL model for calculating actual evapotranspiration provides an efficient and cost-effective means for estimation of evapotranspiration and it was verified that SEBAL will perform better if it is supported with field data. In addition, there should be a consensus between the period when water is provided from the source and the period when it is needed to increase the irrigation performance. This study provides the possibility of simulating the runoff either on a daily, monthly, seasonal or an annual scale for each rainfall. It can be useful for estimating runoff at places where observed runoff records are not available.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Doktor Falsafah

PEMBANGUNAN MODEL SEBAL BERASASKAN-GIS UNTUK ANGGARAN PENYEJATPELUHAN DI IRAQ

Oleh

HUSSEIN SABAH JABER

April 2017

Pengerusi : Profesor Dato Shattri Mansor,PhD
Fakulti : Kejuruteraan

Perubahan parameter cuaca dan iklim akan menyebabkan perubahan penyejatpeluhan yang ketara. Iraq mengalami masalah seperti pengurangan ketersediaan air dan perubahan iklim yang tidak menentu yang akan menjejas pertanian pengairan dan penyejatpeluhan. Oleh itu, anggaran penyejatpeluhan dan pengukuran yang seragam adalah penting kerana penyejatpeluhan (ET) adalah cara untuk mengeksploitasi pengairan dan pengairan dianggap sebagai tulang belakang kepada masyarakat petani.

Kebanyakan kajian di Iraq bergantung kepada kaedah tradisional untuk menganggarkan penyejatpeluhan. Kaedah konvensional tidak praktikal untuk kawasan yang besar kerana ia sukar dan mahal. Oleh itu, kajian ini bertujuan untuk menggunakan penderiaan jarak jauh (data imej satelit) dan GIS sebagai teknologi moden untukmenganggarkan penyejatpeluhan.

Dalam kajian ini, cadangan reka bentuk SEBAL telah dibangunkan dengan menggunakan GIS untuk membuat suatu model mudah untuk menganggarkan penyejatpeluhan yang membawa kepada pengurangan dalam kos dan masa dan menjimatkan usaha. Kemudiannya, model SEBAL berasaskan-GIS yang dicadangkan telah dinilai dengan data lapangan dengan menggunakan pekali regresi. Kawasan di sekitar empangan rendah Al-Hindiyah telah dipilih sebagai kawasan kajian kerana ia adalah salah satu sumber air yang paling penting di bahagian tengah Iraq. Satu siri imej satelit Landsat OLI (Operational Land Imager) dan data iklim kawasan kajian telah dikumpulkan untuk menentukan penyejatpeluhan sebenar menggunakan model berasaskan-GIS. Di samping itu, penyejatpeluhan sebenar telah digunakan untukmenilai prestasi pengairan berdasarkan beberapa petunjuk dan untuk menganalisis keseimbangan air bergantung pada kaedah keluk angka dalam GIS untuk kawasan kajian, masing-masing.

Keputusan menunjukkan bahawa model SEBAL berasaskan-GIS yang dicadangkan untuk anggaran penyejatpeluhan sebenar mempunyai persetujuan yang berpatutan dengan data lapangan berdasarkan (CoV) ialah antara (0.75%, 2.2%, 0.68% and% 2.27%). Tambahan lagi, hasil prestasi pengairan adalah tidak baik bergantung kepada nilai perbandingan petunjuk prestasi pengairan dengan nilai-nilai petunjuk yang disyorkan. Selain itu, keputusan menunjukkan persetujuan rapat antara hujan dan air larian berdasarkan nilai Cov=0.10 yang diperolehi. Tambahan pula, ΔS bagi keseluruhan kawasan kajian telah diperhatikan sebagai mempunyai nilai-nilai positif yang menunjukkan bahawa terdapat penelusan air bawah tanah di zon akar tanaman yang boleh digunakan apabila air tidak mencukupi.

Kajian ini menyimpulkan bahawa pembangunan model SEBAL berasaskan- GIS untuk mengira penyejatpeluhan sebenar menyediakan cara yang cekap dan kos-efektif untuk anggaran penyejatpeluhan dan ia telah mengesahkan bahawa SEBAL akan berprestasi lebih baik jika ia disokong dengan data lapangan. Di samping itu, perlu ada konsensus di antara tempoh apabila air disediakan dari sumber dan tempoh apabila ia diperlukan untuk meningkatkan prestasi pengairan. Kajian ini menyediakan kemungkinan simulasi air larian sama ada pada skala harian, bulanan, bermusim atau tahunan bagi setiap kali hujan. Ia mungkin menjadi berguna untuk menganggarkan air larian di tempat-tempat di mana rekod air larian yang diperhatikan tidak

ACKNOWLEDGEMENTS

First of all praise is due "Allah" for giving me the strength to complete this work.

I would like to express my sincere gratitude to my supervisor Prof .Dato. Dr .Shattri Mansor for his parental kindness, helpful advices, valuable suggestions, and encouragement throughout my study in general and my research in particular.

I would like also to express my sincere gratitude and deep thanks to my co-supervisor Asst. Prof. Dr. Biswajeet Pardhan and Asst. Prof. Dr. Noordin Ahmad for their valuable time dedication to help and provide scientific guidance for me and valuable suggestions also for their unlimited support to complete my thesis.

I would like to express my thanks to the university of Baghdad and university putra Malaysia (UPM) for their help me during the time of study and for their generosity to provide the data for this study.

Finally, I would like to offer my deep thanks and gratitude to my family and friends for their care, unlimited support, and encouragement to me without whom I couldn't complete my study.

I certify that a Thesis Examination Committee has met on 26 April 2017 to conduct the final examination of Hussein Sabah Jaber on his thesis entitled "Development of GIS-Based Sebal Model for Estimation of Evapotranspiration in Iraq" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Doctor of Philosophy.

Members of the Thesis Examination Committee were as follows:

Hussain bin Hamid, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Helmi Zulhaidi bin Mohd Shafri, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Abdul Halim bin Ghazali, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Nitin Kumar Tripathi, PhD
Professor
Asian Institute of Technology
Thailand
(External Examiner)

NOR AINI AB. SHUKOR, PhD
Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 8 August 2017

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree Doctor of Philosophy. The members of the Supervisory Committee were as follows:

Dato' Shattri Mansor, PhD
Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Biswajeet Pradhan, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

Noordin Ahmad, PhD
Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

ROBIAH BINTI YUNUS, PhD
Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice- Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: _____ Date: _____

Name and Matric No: Hussein Sabah Jaber, GS 39885

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) were adhered to.

Signature: _____

Name of Chairman of Supervisory Committee: Dato'Professor Dr.Shattri Mansor

Dato' Dr. Shattri Mansor
Professor
Department of Civil Engineering
Faculty of Engineering
Universiti Putra Malaysia

Signature: _____

Name of Member of Supervisory Committee: Assoc.Prof. Dr. Biswajeet Pradhan

Assoc. Prof. Dr. Biswajeet Pradhan
Dept. of Civil Engineering
Faculty of Engineering
Universiti Putra Malaysia
43400 Serdang, Selangor

Signature: _____

Name of Member of Supervisory Committee: Dr. Noordin Ahmad

Dr Noordin Ahmad
Jabatan Kejuruteraan Awam
Fakulti Kejuruteraan
Universiti Putra Malaysia

TABLE OF CONTENTS

LIST OF TABLES

LIST OF FIGURES

.

LIST OF ABBREVIATIONS

AVHRR	Advanced Very High Resolution Radiometer
ANNs	Artificial Neural Networks
ANFIS	Adaptive Neuro-Fuzzy Inference System
CN	Curve Number
CWD	Crop water deficit
DF	Depleted fraction
ET	Evapotranspiration
ETM+	Enhanced Thematic Mapper Plus
EBEC	Energy-budget eddy covariance
FAO	Food Agricultural Organization
FAR	Field application ratio
FFBP	Feed Forward Back Propagation
GIS	Geographic Information Systems
GEP	Gene Expression Programming
LAI	Leaf Area Index
LULC	Land Use Land Cover
LC	Land Cover
LISS-III	Linear Imaging and Self Scanning–III
MODIS	Moderate Resolution Imaging Spectroradiometer
MAE	mean absolute errors
MRE	mean relative errors
MBE	Mean Bias Errors
METRIC	Mapping Evapotranspiration with high Resolution and Internalized Calibration
MLR	Multi Linear Regression
NDVI	Normalized Difference Vegetation Index
NOAA	National Oceanic Atmospheric Administration.
NSE	Nash–Sutcliffe efficiency
NDWI	Normalized Difference Water Index
OLI	Operational Land Imager
PF	Penman –FAO
PM	Penman Monteith
RMSE	Root mean square error

RS	Remote sensing
RIS	Relative Irrigation supply
RET	Relative evapotranspiration
RHmean	Relative Humidity average
RWS	Relative water supply
SEBAL	Surface Energy Balance Algorithm for Land
SEBS	Soil Energy Balance System
SEBI	Surface energy balance index
S-SEBI	Simplified surface energy balance index
SVAT	Soil vegetation atmosphere transfer
TSEB	Two-source energy balance
SDISTA	Semi-distributed time area
SWAT	Soil and Water Analysis Tool
SDISTA	Semi-distributed time area
SWAT	Soil and Water Analysis Tool
WDVI	Weighted Difference Vegetation Index
WUE	Water Use Efficiency
ETp	the evapotranspiration's potential in mm
Pe	the value of (effective) precipitation in mm
Vc	volume of supplied water used for irrigation
Pg	gross precipitation in mm
ETc	Crop Evapotranspiration
Kc	Crop Coefficient
Rn	Net Radiation
R	correlation coefficient
R^2	Coefficient of Determination
Rs ↓ and Rs ↑	Incoming and reflected shortwave radiations
RL ↓ and RL ↑	Incoming and outgoing long wave radiations
Gsc	The solar constant equal to 1,367 W m^{-2}
θ	Solar inclination angle in radians
de-s	the relative distance between Earth and Sun in astronomical units
τ_{sw}	One-way atmospheric transitivity
Ɛs	Surface emissivity
Ts	Surface temperature

ρ	Air density (kg/m3)
Cp	air specific heat (1004 J/kg/K)
dT (K)	the temperature difference (T1– T2) between two heights (z1and z2)
rah	The aerodynamic resistance to heat transport (s/m).
k	constant value (von Karman)
ux	wind's speed measured in m/s at a particular height
z_{om}	The momentum roughness length (m).
u*	the friction velocity
λET	an instantaneous value for the time of the satellite overpass (W/m2)
ETinst	the instantaneous ET (mm/hr)
λ	The amount of heat absorbed for a kilogram of water that evaporates (J/kg)
ETrF	reference ET Fraction
ETr-24	the cumulative 24-hour ETr for the day of the image
F	Actual Retention (mm)
S	Retention (mm).
Q	Runoff Depth (mm).
P	Total Rainfall (mm)
I	Initial Abstraction (mm).
ΔS	The change in the amount of water stored in the surface layer (root zone (mm month $^{-1}$).
Ts	Surface Temperature
ea	Actual vapor pressure (kPa).
es	Saturation vapor pressure (kPa).
G	Soil heat flux (MJ m-2 d-1).
H	Soil heat flux (MJ m-2 d-1).
Rn	Net radiation at the crop surface (MJ m-2 d-1)
Rs	Solar radiation (MJ m-2 d-1)
Tmean	Average air temperature (ºC)
U2	Wind speed measured at 2 m height (m s-1)
Z	Altitude of the location (m).
ETa	Actual Evapotranspiration.
ep	overall consumed ratio

CHAPTER 1

INTRODUCTION

1.1 Background

Evapotranspiration (ET) is one of the major components in the hydrological cycle (Telis & Koutsogiannis, 2007). Hence, estimation of this parameter and standardized measurement related to ET possesses high degree of importance. ET varies by location, climate, crop type, soil type, and moisture availability. Evapotranspiration increases with increasing radiation, decreasing humidity, increasing temperature, and increasing wind speed. The increase in evapotranspiration should be of necessary concern to permit studies to estimate the increases and integrate in water management strategies. It is vital to put forth the effort to know the impact of climate change on evapotranspiration and use the information for developing adaptations in water resources management (Allen et al. 2005).

Remote sensing-based surface energy flux modeling is good for mapping spatially distributed ET for large area application, where conventional measurement are not practical. Various models are available and these models have some limitations and are mostly applied to agricultural areas mainly for quantifying crop evapotranspiration for irrigation management. Remote sensing offers data valuable to estimate surface energy fluxes in the thermal infrared portion of the spectrum (Bastiaanssen et al., 2001; Bos et al., 2005).

The mean for exploiting irrigation is evapotranspiration (ET).Irrigation is considered as the backbone of the peasant society. This society constitutes the largest percentage of the world population. It is estimated that around 70 percent of global water usage is demanded for irrigation, which in turn contributes to approximately 30 to 40 percent of the world's food production (Bastiaanssen et al., 2000).Hence, the assessment of irrigation performance and analysis of water balance require the usage of effective tools. These tools enable the decision makers to study large area and at the same time analyses large number of variables related to irrigation performance and water balance. Remote sensing and GIS techniques are considered as efficient techniques that can be used for achieving such works. (Molden et al., 1998).

1.2 Problem Statement

Currently, in some countries such as Iraq, that faces challenges such as reduction in water availability and unpredictable climate change where a change in weather parameters and climate will result in a significant change in evapotranspiration. The worst-case state for water supply is decreasing rainfall, increasing temperatures, and increasing evapotranspiration that Iraq suffer from it. Therefore, estimation of evapotransipration and standardized measurement are challenging.

Most of the studies in Iraq depend on traditional methods to estimate evapotranspiration **.** Measurement of evapotranspiration based on traditional methods and climate data is difficult and costly particularly on large area .Therefore, the current study aims to use remote sensing (satellite imagery data) and GIS as modern technologies to calculate evapotranspiration. Based on the best knowledge of the author of this thesis, there is no studies have been carried out to estimate of evapotranspiration parameters via remote sensing and GIS techniques in Iraq. Remote sensing techniques can be used to gather data over an entire areas, while traditional field data collecting depended on sample areas. Combination remote sensing data with field data can be an extremely active tool to study the performance of large irrigated areas and to develop spatiotemporal data**.** Therefore, using GIS and remote sensing techniques for estimating of evapotranspiration have many advantages, these include reduction in cost, time, efforts and providing an integrated assessment approach for irrigation. Studies focused on estimating of evapotranspiration are very significant because these studies help in irrigation management practices. In current study, Geographic Information Systems (GIS) -based Surface Energy Balance Algorithm for Land (SEBAL) model has been developed and used to estimate of evapotranspiration as the first time in Iraq.

The SEBAL model has been developed by using GIS to make a simple model for estimation of evapotranspiration that leads to minimize the cost and time. In addition, estimation of evapotranspiration from the SEBAL model is the most crucial part in this research for irrigation performance and water balance analysis. SEBAL can be applied and implemented for solving evapotranspiration and irrigation problems.

1.3 Objectives

The overall objective of this study is to develop a GIS-based SEBAL model for estimation of evapotranspiration in Iraq. Specifically, the objectives of this research are summarized as follows:

1- To develop a geospatial Surface Energy Balance Algorithm for Land (SEBAL) based on Geographic Information Systems (GIS) for evapotranspiration modelling.
2- To evaluate the hybrid GIS- SEBAL model for estimation of evapotranspiration.
3- To assess irrigation performance analysis of the study area (Al-Hindiyah Barrage, Babil city, Iraq) based on SEBAL model and several indicators.
4- To build rainfall-runoff model for analyzing of the water balance for the study area.

1.4 Thesis Outline

Chapter one presents an introduction to the research conducted which contains research background, problem statement, research objectives and the overall organization of this thesis.

Chapter two highlights the general literature review of the research. In this chapter, information about the research objectives is described.

Chapter three focuses on the research methodology as well as the materials used in the study.

Chapter four discusses the results obtained from the research objectives that are divided into four sections. The first section presents the production of evapotransipration parameters maps in GIS. The second section contains the discussion and evaluation of the SEBAL results using field data. The third section presents the assessment of irrigation performance for the study area. The final section contains the modeling of rainfall-runoff and analyzing of water balance for the study area.

Chapter five presents the conclusions obtained from this research. Discussion on future works is also presented.

REFERENCES

Acharya, S., Pandey, A., & Chaube, U. (2014). Use of geographic information systems in irrigation management: a review. Journal of Indian Water Resources Society, 34(2).

Abtew, W., & Melesse, A. (2013). Evaporation and Evapotranspiration: Measurements and Estimations, DOI 10.1007/978-94-007-4737-1 5, Springer Science+ Business Media Dordrecht.

Abtew W, Sculley S (1991) .Evapotranspiration estimation method for south Florida (The Everglades Agricultural Area). Paper presented at the 51st annual meeting of the Soil and Crop Science Society of Florida, Orlando.

Ahmad, M.D., Turral, H., & Nazeer, A. (2009). Diagnosing irrigation performance and water productivity through satellite remote sensing and secondary data in a large irrigation system of Pakistan. Agricultural water management, 96(4), 551-564.

Ahmad, M.D., Biggs, T., Turral, H., &Scott, C.A., 2006. Application of SEBAL approach and MODIS time-series to map vegetation water use patterns in the data scarce Krishna river basin of India. IWA Journal of Water Science and Technology 53 (10), 83–90.

Al Zayed, I. S., Elagib, N. A., Ribbe, L., & Heinrich, J. (2015). Spatio-temporal performance of large-scale Gezira Irrigation Scheme, Sudan. Agricultural Systems, 133, 131-142.

Alexandridis, T., Panagopoulos, A., Galanis, G., Alexiou, I., Cherif, I., Chemin, Y., & Zalidis, G. (2014). Combining remotely sensed surface energy fluxes and GIS analysis of groundwater parameters for irrigation system assessment. Irrigation Science, 32(2), 127-140.

Ali, M. (2011). GIS in Irrigation and Water Management Practices of Irrigation & On-farm Water Management: Volume 2 (pp. 423-432): Springer.

Allen, R. G., Tasumi, M., & Trezza, R. (2007). Satellite-based energy balance for mapping evapotranspiration with internalized calibration (METRIC)—Model. Journal of irrigation and drainage engineering, 133(4), 380-394.

Allen, R.G.,Pereira, L.S., Raes, D.,& Smith, M.(1998). Crop Evapotranspiration—Guidelines for Computing Crop Water Requirements; FAO Irrigation and Drainage Paper 56; Food and Agriculture Organization of the United Nations: Rome, Italy,

Awan, U. K., Tischbein, B., Conrad, C., Martius, C., & Hafeez, M. (2011). Remote sensing and hydrological measurements for irrigation performance assessments in a water user association in the lower Amu Darya River Basin. Water resources management, 25(10), 2467-2485.

Bashir, M., Tanakamaru, H., & Tada, A. (2011). Remote Sensing for Assessing Water Management and Irrigation Performance in the Arid Environment of

the Gezira Scheme, Sudan. Journal of Environmental Science and Engineering, 5(3).

Bandara, K.M.P.S., 2006. Assessing irrigation performance by using remote sensing. Doctoral thesis, Wageningen University, Wageningen, The Netherlands. p. 156.

Bastiaanssen, W.G.M., Menenti, M., Feddes, R.A., & Holtslag, A.A.M.,(1998a). A remote sensing surface energy balance algorithm for land (SEBAL). Part 1. Formulation. Journal of Hydrology 212–213, 198–212.

Bastiaanssen, W.G.M., Pelgrum, H., Wang, J., Ma, Y., Moreno, J.F., Roerink, G.J., & van der Wal, T., (1998b). A remote sensing surface energy balance algorithm for land (SEBAL). Part 2. Validation. Journal of Hydrology 213–229.

Bastiaanssen, W.G.M., Ahmad, M.D., & Chemin, Y., (2002). Satellite surveillance of evaporative depletion across the Indus. Water Resources Research 38 (12), 1–9 1273.

Bastiaanssen, W.G.M., Brito, R.A.L., Bos, M.G., Souza, R.A., Cavalcanti, E.B., &Bakker, M.M., (2001). Low cost satellite data for monthly irrigation performance monitoring: benchmarks from Nilo Coelho, Brazil. Irrigation and Drainage Systems 15, 53–79.

Bastiaanssen, W., Noordman, E., Pelgrum, H., Davids, G., Thoreson, B., & Allen, R. (2005). SEBAL model with remotely sensed data to improve water-resources management under actual field conditions. Journal of irrigation and drainage engineering.

Bastiaanssen, W.G.M., Molden, D.J., & Makin, I.W., (2000). Remote sensing for irrigated agriculture: examples from research and possible applications. Agricultural Water Management 46, 137–155.

Bhattarai, N., Dougherty, M., Marzen, L. J., & Kalin, L. (2012). Validation of evaporation estimates from a modified surface energy balance algorithm for land (SEBAL) model in the south-eastern United States. Remote Sensing Letters, 3(6), 511-519.

Boegh, E., Poulsen, R., Butts, M., Abrahamsen, P., Dellwik, E., Hansen, S., & Pilegaard, K. (2009). Remote sensing based evapotranspiration and runoff modeling of agricultural, forest and urban flux sites in Denmark: From field to macro-scale. Journal of Hydrology, 377(3), 300-316.

Bos, M.G., (1997). Performance indicators for irrigation and drainage. Irrigation and Drainage Systems 11, 119–137.

Bosman, H.H., (1990). Methods to convert American Class A-Pan and Symon's Tank evaporation to that of a representative environment. Water SA, 16, 227-236.

Bos, M.G., Nugteren, J., (1990). On irrigation efficiencies. International Institute for Land Reclamation and Improvement (ILRI), ILRI Publication 19, Wageningen, the Netherlands, p. 138.

Bos, M.G., Burton, M.A., &Molden, D.J., (2005). Irrigation and Drainage Performance Assessment: Practical Guidelines. CABI Publishing, Trowbridge, US, p. 155.

Bos, M.G., Wolters, W., Drovandi, A., & Morabito, J.A., (1991). The Viejo Retamo secondary canal performance evaluation case study: Mendoza, Argentina. Irrigation and Drainage Systems 5, 77–88.

Buyukcangaz, H., & Korukcu, A. (2007). Integrated approach for water resources and irrigation management in Turkey. Water international, 32(S1), 710-719.

Cammalleri, C., Anderson, M., Ciraolo, G., Durso, G., Kustas, W., La Loggia, G., & Minacapilli, M. (2012). Applications of a remote sensing-based two-source energy balance algorithm for mapping surface fluxes without in situ air temperature observations. Remote Sensing of Environment, 124, 502-515.

Campbell,JB.,&Wynne,RH.,(2011).Intorduction to remote sensing.Fifth edition,Guilford press.NewYork.

Conrad, C., Dech, S., Hafeez, M., Lamers, J., & Tischbein, B. (2013). Remote sensing and hydrological measurement based irrigation performance assessments in the upper Amu Darya Delta, Central Asia. Physics and Chemistry of the Earth, Parts A/B/C, 61, 52-62.

Chen, J., Shi, H., Sivakumar, B., & Peart, M. R. (2016). Population, water, food, energy and dams. Renewable and Sustainable Energy Reviews, 56, 18-28.

Diamond, M. G., & Melesse, A. M. (2016). Water resources assessment and geographic information system (GIS)-based stormwater runoff estimates for artificial recharge of freshwater aquifers in New Providence, Bahamas. InLandscape Dynamics, Soils and Hydrological Processes in Varied Climates(pp. 411-434). Springer International Publishing.

Dixon,B., & Uddameri,V.(2016).GIS and geocomputation for water resourcescience and engineering. John Wiley & Sons, Ltd.

DeWinnaar, G., Jewitt, G., & Horan, M. (2007). A GIS-based approach for identifying potential runoff harvesting sites in the Thukela River basin, South Africa. Physics and Chemistry of the Earth, Parts A/B/C, 32(15), 1058-1067.

Deshmukh, D. S., Chaube, U. C., Hailu, A. E., Gudeta, D. A., & Kassa, M. T. (2013). Estimation and comparision of curve numbers based on dynamic land use land cover change, observed rainfall-runoff data and land slope. Journal of Hydrology, 492, 89-101.

Filimonova, M. & Trubetskova M. (2005). Calculation of evaporation from the Caspian Sea surface. Nijmegen, Netherlands.

Gad, M. A. (2013). A useful automated rainfall-runoff model for engineering applications in semi-arid regions. Computers & Geosciences, 52, 443-452.

Ghahroodi, E. M., Noory, H., & Liaghat, A. (2015). Performance evaluation study and hydrologic and productive analysis of irrigation systems at the Qazvin irrigation network (Iran). Agricultural water management, 148, 189-195.

Gibson, L., Jarmain, C., Su, Z., & Eckardt, F. (2013). Estimating evapotranspiration using remote sensing and the Surface Energy Balance System-A South African perspective. Water Sa, 39(4), 00-00.

Gitika, T., & Ranjan, S. (2014). Estimation of Surface Runoff using NRCS Curve number procedure in Buriganga Watershed, Assam, India-A Geospatial Approach. International research journal of earth sciences, 2 (5), 1, 7.

Gökbulak, F., Şengönül, K., Serengil, Y., Yurtseven, İ., Özhan, S., Cigizoglu, H. K., & Uygur, B. (2015). Comparison of Rainfall-Runoff Relationship Modeling using Different Methods in a Forested Watershed. Water resources management, 29(12), 4229-4239.

González-Dugo, M., Escuin, S., Cano, F., Cifuentes, V., Padilla, F., Tirado, J., & Mateos, L. (2013). Monitoring evapotranspiration of irrigated crops using crop coefficients derived from time series of satellite images. II. Application on basin scale. Agricultural water management, 125, 92-104.

Guermazi, E., Bouaziz, M., & Zairi, M. (2016). Water irrigation management using remote sensing techniques: a case study in Central Tunisia. Environmental Earth Sciences, 75(3), 1-14.

Ines, A. V., Honda, K., Gupta, A. D., Droogers, P., & Clemente, R. S. (2006). Combining remote sensing-simulation modeling and genetic algorithm optimization to explore water management options in irrigated agriculture. Agricultural water management, 83(3), 221-232.

Isaev, V., & Mikhailova, M. (2009). The hydrography, evolution, and hydrological regime of the mouth area of the Shatt al-Arab River. Water resources, 36(4), 380-395.

Jain, M. K., Kothyari, U. C., & Raju, K. G. R. (2004). A GIS based distributed rainfall–runoff model. Journal of Hydrology, 299(1), 107-135.

Jiang, Y., Liu, C., Li, X., Liu, L., & Wang, H. (2015). Rainfall-runoff modeling, parameter estimation and sensitivity analysis in a semiarid catchment. Environmental Modelling & Software, 67, 72-88.

Kadhum,H.M.,(2014). Evaluation of irrigation network of Al-Hussainiyah irrigation project using geomatics techniques.Msc thesis,University of Technology.Iraq

Karatas, B. S., Akkuzu, E., Unal, H. B., Asik, S., & Avci, M. (2009). Using satellite remote sensing to assess irrigation performance in Water User Associations in the Lower Gediz Basin, Turkey. Agricultural water management, 96(6), 982-990.

Kato, T., Kuroda, H., & Yoshida, K. (2013). GIS analysis of conjunctive water resource use in Nganjuk district, east Java, Indonesia. Paddy and Water Environment, 11(1-4), 193-205.

Kharrou, M. H., Le Page, M., Chehbouni, A., Simonneaux, V., Er-Raki, S., Jarlan, L., & Chehbouni, G. (2013). Assessment of equity and adequacy of water delivery in irrigation systems using remote sensing-based indicators in semi-arid region, Morocco. Water resources management, 27(13), 4697-4714.

King, D. A., Bachelet, D. M., Symstad, A. J., Ferschweiler, K., & Hobbins, M. (2015). Estimation of potential evapotranspiration from extraterrestrial radiation, air temperature and humidity to assess future climate change effects on the vegetation of the Northern Great Plains, USA. Ecological Modelling, 297, 86-97.

Kirpich, P. Z., Haman, D. Z., & Styles, S. W. (1999). Problems of irrigation in developing countries. Journal of irrigation and drainage engineering, 125(1), 1-6.

Kisi, O., Shiri, J., & Tombul, M. (2013). Modeling rainfall-runoff process using soft computing techniques. Computers & Geosciences, 51, 108-117.

Kumar, K. A., Reddy, M., Devi, M. U., Narender, N., & Neelima, T. (2014). Irrigation performance assessment of left bank canal, Nagarjuna Sagar Project, India During Rabi Using Remote Sensing and GIS. Agrotechnol, 3(122), 2.

Kumar,P.S.,(2004).Diagnosing irrigation water resourecs with multi-sensor remote sensing and GIS techniques.Msc thesis.Enschede,Netherlands.

Lecina, S., Neale, C., Merkley, G., & Dos Santos, C. (2011). Irrigation evaluation based on performance analysis and water accounting at the Bear River Irrigation Project (USA). Agricultural water management, 98(9), 1349-1363.

Liou, Y. A., & Kar, S. (2014) Evapotranspiration Estimation with Remote Sensing and Various Surface Energy Balance Algorithms. A Review. Energies, 7, 2821-2849.

Lian, J., & Huang, M. (2015). Evapotranspiration Estimation for an Oasis Area in the Heihe River Basin Using Landsat-8 Images and the METRIC Model. Water resources management, 29(14), 5157-5170.

Long, D., & Singh, V. P. (2012). A modified surface energy balance algorithm for land (M-SEBAL) based on a trapezoidal framework. Water Resources Research, 48(2).

Long, D., Singh, V. P., & Li, Z. L. (2011). How sensitive is SEBAL to changes in input variables, domain size and satellite sensor? Journal of Geophysical Research: Atmospheres, 116(D21).

Ma, W., Hafeez, M., Ishikawa, H., & Ma, Y. (2013). Evaluation of SEBS for estimation of actual evapotranspiration using ASTER satellite data for irrigation areas of Australia. Theoretical and applied climatology, 112(3-4), 609-616.

Mahmoud, S. H. (2014). Investigation of rainfall–runoff modeling for Egypt by using remote sensing and GIS integration. Catena, 120, 111-121.

Masoud, M.(2015).Rainfall-runoff modeling of ungauged Wadis in arid environments (case study Wadi Rabigh—Saudi Arabia). Arabian Journal of Geosciences, 8(5), 2587-2606.

Mekonnen, M.G., & Bastiaanssen, W.G.M., (2000). A new simple method to determine crop coefficients for water allocation planning from satellites; results from Kenya. Irrigation and Drainage Systems 14 (3), 237–256.

Melesse, A. M., & Shih, S. (2002). Spatially distributed storm runoff depth estimation using Landsat images and GIS. Computers and Electronics in Agriculture, 37(1), 173-183.

Merchán, D., Causapé, J., Abrahão, R., & García-Garizábal, I. (2015). Assessment of a newly implemented irrigated area (Lerma Basin, Spain) over a 10-year period. I: Water balances and irrigation performance. Agricultural water management, 158, 277-287.

Molden, D.J. (1997). Accounting for water use and productivity, SWIM paper 1, International Water Management Institute (IWMI), Colombo, Sri Lanka, p. 16.

Molden, D., Sakthivadivel, R., Perry, C., & De Fraiture, C., (1998), Indicators for comparing performance of irrigated agriculture systems, Research Report 20, International Irrigation Management Institute, Colombo, Sri Lanka.

Ministry of Transportation, Babil Meteorological Station, (2014), Unpublished climatic data, Babil, Iraq.

Ministry of Agriculture and Irrigation, State Organization for Land Reclamation and Engineering Consulting Bureau at University of Technology, (1990). The economic feasibility study of Al-Hussainiyah irrigation project in Karbala Province, Technical report, Baghdad, Iraq,

Nagarajan, R., & Suresh, M. (2002). Performance assessment of water resource project using remote sensing and a Geographical Information System-a case study. International Journal of Remote Sensing, 23(20), 4475-4485.

Napoli, M., Cecchi, S., Orlandini, S., & Zanchi, C. A. (2014). Determining potential rainwater harvesting sites using a continuous runoff potential accounting procedure and GIS techniques in central Italy. Agricultural water management, 141, 55-65.

Nouri, H., Beecham, S., Kazemi, F., Hassanli, A. M., & Anderson, S. (2013). Remote sensing techniques for predicting evapotranspiration from mixed vegetated surfaces. Hydrology and Earth System Sciences Discussions, 10(3), 3897-3925.

Paiva, C. M., Franca, G. B., Liu, W. T. H., & Rotunno Filho, O. C. (2011). A comparison of experimental energy balance components data and SEBAL model results in Dourados, Brazil. International Journal of Remote Sensing, 32(6), 1731-1745.

Papadavid, G., Hadjimitsis, D. G., Toulios, L., & Michaelides, S. (2013). A modified SEBAL modeling approach for estimating crop evapotranspiration in semi-arid conditions. Water resources management, 27(9), 3493-3506.

Paul, G., Gowda, P. H., Prasad, P. V., Howell, T. A., Aiken, R. M., & Neale, C. M. (2014). Investigating the influence of roughness length for heat transport (z oh) on the performance of SEBAL in semi-arid irrigated and dryland agricultural systems. Journal of Hydrology, 509, 231-244.

Priestley, C.H., &Taylor, R.J., (1972). On the assessment of surface heat flux and evaporation using large scale parameters. Monthly Weather Review 100, 81–92.

Rahimi, S., Gholami Sefidkouhi, M. A., Raeini-Sarjaz, M., & Valipour, M. (2015). Estimation of actual evapotranspiration by using MODIS images (a case study: Tajan catchment). Archives of Agronomy and Soil Science, 61(5), 695-709.

Perry, C.J., (1996). Quantification and measurement of a minimum set of indicators of the performance of irrigation systems. International Irrigation Management Institute, Colombo, Sri Lanka

Roerink, G.J., Bastiaanssen, W.G.M., Chambouleyron, J., & Menenti, M. (1997). Relating crop water consumption to irrigation water supply by remote sensing. Water Resources Management 11 (6), 445–465.

Rao, K. D., Rao, V. V., & Dadhwal, V. K. (2014). Improvement to the Thornthwaite method to study the runoff at a basin scale using temporal remote sensing data. Water resources management, 28(6), 1567-1578.

Ray, S., Dadhwal, V., & Navalgund, R. (2002). Performance evaluation of an irrigation command area using remote sensing: a case study of Mahi command, Gujarat, India. Agricultural water management, 56(2), 81-91.

Sajikumar, N., & Remya, R. (2015). Impact of land cover and land use change on runoff characteristics. Journal of environmental management, 161, 460-468.

Santos, C., Lorite, I., Allen, R., & Tasumi, M. (2012). Aerodynamic parameterization of the satellite-based energy balance (METRIC) model for ET estimation in rainfed olive orchards of Andalusia, Spain. Water resources management, 26(11), 3267-3283.

Santos, C., Lorite, I. J., Tasumi, M., Allen, R., & Fereres, E. (2010). Performance assessment of an irrigation scheme using indicators determined with remote sensing techniques. Irrigation Science, 28(6), 461-477.

Savige, C. L., French, A. N., Western, A. W., Walker, J. P., Abuzar, M., Hacker, J. M., & Kalma, J. D. (2006). Remote sensing estimates of actual evapotranspiration in an irrigation district. Australian Journal of Water Resources, 10(2), 207-212.

Schipper, P. (2005).Determination of the actual evapotranspiration on a regional scale for a closed watershed in Argentina. MSc Thesis. Delft University of Technology. Water Resources of Rio Dulce in Santiago del Estero. Delft. p. 77.

Shiklomanov, I. A. (2000). Appraisal and assessment of world water resources. Water international, 25(1), 11-32.

Singh, R. K., Liu, S., Tieszen, L. L., Suyker, A. E., & Verma, S. B. (2012). Estimating seasonal evapotranspiration from temporal satellite images. Irrigation Science, 30(4), 303-313.

Smith,G.N.(1986).Probability and statistics in civil engineering.Collins London.

Smith, M., (1992). CROPWAT a computer program for irrigation planning and management, FAO Irrigation and Drainage Paper 46. Rome. p.126.

Steele, D. D., Thoreson, B. P., Hopkins, D. G., Clark, B. A., Tuscherer, S. R., & Gautam, R. (2015). Spatial mapping of evapotranspiration over Devils Lake basin with SEBAL: application to flood mitigation via irrigation of agricultural crops. Irrigation Science, 33(1), 15-29.

Taguas, E., Gómez, J., Denisi, P., & Mateos, L. (2015). Modelling the Rainfall-Runoff Relationships in a Large Olive Orchard Catchment in Southern Spain. Water resources management, 29(7), 2361-2375.

Tasumi, M. (2003). Progress in operational estimation of regional evapotranspiration using satellite imagery.

Tayfur,G.,Brocca, L. (2015). Fuzzy Logic for Rainfall-Runoff Modelling Considering Soil Moisture. Water resources management, 29(10), 3519-3533.

Telis, A., Koutsogiannis, D. (2007). Estimation of evapotranspiration in Greece. PhD Thesis, University of Athens.

Tempfli,K.,Kerle,N.,Gerrit,C.,&Janssen,L.(2009).Principlesof remote sensing.Fourth edition,ITC,The Netherlands.

Tibor, G. J., Grigg, N. S., Helweg, O. J., Plusquellec, H., Burt, C. M., Merriam, J. L., & Kirpich, P. Z. (2000). Problems of Irrigation in Developing Countries. Journal of irrigation and drainage engineering, 126(3), 195-202.

Tuya, S., Batjargal, Z., Kajiwara, K., & Honda, Y. (2005). Satellite-derived estimates of evapotranspiration in the arid and semi–arid region of Mongolia. International journal of environmental studies, 62(5), 517-526.

USDA, (2004). Estimation of direct runoff from storm rainfall. National Engineering Hand- book p. 79.

USDA, (2004). Hydrologic Soil-Cover Complexes National Engineering Hand- book p. 14.

Usman, M., Liedl, R., & Awan, U. (2015). Spatio-temporal estimation of consumptive water use for assessment of irrigation system performance and management of water resources in irrigated Indus Basin, Pakistan. Journal of Hydrology, 525, 26-41.

Van Dijk, A., & Renzullo, L. J. (2011). Water resource monitoring systems and the role of satellite observations. Hydrology and Earth System Sciences, 15(1), 39-55.

Yang, G., Guo, P., Huo, L., & Ren, C. (2015). Optimization of the irrigation water resources for Shijin irrigation district in north China. Agricultural Water Management, 158, 82-98.

Zhang, X. c., Wu, J. w., Wu, H.y., & Li, Y. (2011). Simplified SEBAL method for estimating vast areal evapotranspiration with MODIS data. Water Science and Engineering, 4(1), 24-35.

Zhang, X., Berhane, T., & Seielstad, G. (2008). Comparision of Landsat and MODIS Estimates of Heat Fluxes: Effect of Surface Heterogeniety. Paper presented at the Geoscience and Remote Sensing Symposium, 2008. IGARSS 2008. IEEE International.

Zhang, X., & Wu, H. (2011). Sensitivity analysis of the sunshine duration parameters in SEBAL model for estimating winter wheat evapotranspiration. Paper presented at the Geoscience and Remote Sensing Symposium (IGARSS), IEEE International.

Zwart, S. J., & Leclert, L. M. (2010). A remote sensing-based irrigation performance assessment: a case study of the Office du Niger in Mali. Irrigation science, 28(5), 371-385.