



**UNIVERSITI PUTRA MALAYSIA**

***EVALUATIONS OF OIL PALM FRESH FRUIT BUNCHES MATURITY  
DEGREE USING MULTIBAND SPECTROMETER***

**ADILIJANG TUERXUN**

**FK 2017 66**



**EVALUATIONS OF OIL PALM FRESH FRUIT BUNCHES MATURITY  
DEGREE USING MULTIBAND SPECTROMETER**

**By**

**ADILJIANG TUERXUN**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in  
Fulfillment of the Requirements for the Degree of Master of Science**

**May 2017**

## **COPYRIGHT**

All materials contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia.



Abstract of thesis presented to the Senate of University of Putra Malaysia in fulfillment of the requirement for the degree of Master of Science

## **EVALUATIONS OF OIL PALM FRESH FRUIT BUNCHES MATURITY DEGREE USING MULTIBAND SPECTROMETER**

By

**ADILIJANG TUERXUN**

**May 2017**

**Chairman : Abdul Rashid bin Mohammed Shariff, PhD, CEng**  
**Faculty : Engineering**

The demand for high accuracy in grading system of the ripeness and maturity level of the Oil Palm Fresh Fruits Bunch (FFB) is one of the important impending factor facing the oil milling industry globally. This limitation directly affects the Oil Palm Extraction Rate (OER), the quantity, and quality of products produced annually, thereby reducing the profitability margin of the milling industry. However, numerous studies targeted at investigating several improved techniques of grading, and classification of the current oil palm maturity classification in order to enhance the oil palm yield in terms of quality, and quantity annually have been carried out. In view of the needed improvement in OER, there is need to test a novel data mining, and knowledge discovery approach within collected spectrometer data from the oil palm FFB, using WEKA software for classification, and prediction of the oil palm FFB ripeness, to enhance the current manual human grader system. In this research, several machine learning algorithms housed in WEKA data mining tool were proposed for the building of a classifier models, as compared with other earlier manual, and statistical analytical method which require high computational knowledge in coding, time consumption, and prior to human or computational error. This novel approach is tested on the 106-labelled sampled of oil palm FFB of four ripeness categories of unripe, under ripe, ripe, and over ripe by human grader, with reference to the stipulated standard of the Oil Palm Grading Manual (OPGM) of Malaysia. The reflectance data of different wavelength bands incidence from 8 LED modules upon the oil palm FFB, were extracted by 4 different sensors of a spectrometer in laboratory experiment, for onward detailed analysis with machine learning algorithms in WEKA data mining tool. The result illustrated that just one sensor features (sensor 4) are significantly enough to build a good, accurate classifier model that can predict, and classify the oil palm FFB ripeness, rather than the proposed 4 bands sensors with 32 feature attributes. Hence, reducing cost for other sensors, improving the analysis time for the classifier model building, and enhancing the productivity of the system at large. Furthermore, the Lazy-IBK algorithm have been validated to produce the best classifier model, with the machine learning algorithm performance of 65.26%, recall of 65.3%, and 65.4% F-measured as compared to other evaluated machine learning

classifier algorithms proposed within the WEKA data mining algorithm. The ROC curve area indicated an average weighted value of 77.4% for the area under the curve as indicated, which is a measure applied for the accuracy of the applied algorithm. In conclusion, the simple machine learning algorithm model evaluation is developed to classify the oil palm maturity degrees, in order to validate the human grader assessments to enhance the productivity of the oil milling industries.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

## **MENILAI KEMATANGAN BUAH SAWIT SEGAR DENGAN MENGUNAKAN PELBAGAI JALUR PENGESAN SPEKTROMETER**

Oleh

**ADILIJANG TUERXUN**

**Mei 2017**

**Pengerusi : Abdul Rashid bin Mohammed Shariff, PhD, CEng**  
**Fakulti : Kejuruteraan**

Tuntutan tinggi di atas ketepatan sistem pengredan aras keranuman dan kematangan Buah Sawit Segar (FFB) adalah salah satu faktor pasti yang dihadapi oleh Industri Pengilangan Minyak di seluruh dunia. Kekangan ini menjejaskan secara langsung Kadar Pengestran Sawit (OER), kuantiti dan kualiti produk yang dihasilkan setiap tahun, dan seterusnya mengurangkan garis keuntungan industri pengilangan. Namun demikian, banyak kajian yang menyasarkan pengkajian ke atas beberapa teknik pengredan dan klasifikasi kematangan sawit yang diperbaiki untuk meningkatkan lagi hasil sawit dari sudut kualiti dan kuantitinya saban tahun. Tambahan lagi, oleh kerana kurangnya panduan jelas tentang algoritma atau teknik mana yang paling sesuai dengan klasifikasi keranuman sawit segar untuk menggantikan pengred manusia manual semasa. Dalam kajian ini, beberapa algoritma pembelajaran mesin dalam alat perlombongan data dicadangkan dalam membina model pengklasifikasi, yang diuji ke atas 106 sampel berlabel FFB sawit mengikut empat kategori keranuman- tidak ranum, kurang ranum, ranum dan terlebih ranum oleh pengred manusia, dengan merujuk kepada piawaian terancang Manual Pengredan Sawit (OPGM) Malaysia. Data pantulan insiden band jarak gelombang yang berbeza-beza dari modul-modul 8 LED ke atas FFB sawit, diestrik oleh 4 pengesan spektrometer berlainan dalam satu eksperimen makmal terbuka, untuk analisis terperinci dengan algoritma pembelajaran mesin dalam alat perlombongan data WEKA. Keputusan menunjukkan bahawa satu ciri pengesan (pengesan 4) memadai untuk membina satu model pengklasifikasi yang baik dan tepat serta boleh meramal, dan mengelaskan keranuman FFB sawit, daripada 4 pengesan yang dicadangkan dengan 32 ciri. Oleh itu, dengan mengurangkan kos untuk pengesan lain, memperbaiki masa analisis untuk membangunkan model pengklasifikasi dan meningkatkan lagi produktiviti sistem secara keseluruhannya. Tambahan lagi, algoritma Lazy-IBK telah disahkan untuk menghasilkan model pengklasifikasi terbaik, dengan prestasi algoritma 65.26%, perolehan kembali 65.3%, dan 65.4% sukatan F berbanding dengan algoritma cadangan iaitu algoritma pengklasifikasi pembelajaran mesin yang dinilai. Kawasan lengkung ROC menampilkan nilai berat purata 77.4% untuk kawasan di bawah lengkung seperti yang ditunjukkan, iaitu satu pengukuran yang diaplikasi untuk ketepatan dan

generalisasi algoritma yang digunakan. Kesimpulannya, satu penilaian model algoritma pembelajaran mesin mudah dibangun untuk mengklasifikasi keranuman sawit dengan tepat, untuk mengesahkan penilaian pengged manusia untuk menambahbaiki OER, mengoptima prestasi dan meningkatkan produktiviti industri pengilangan minyak.



## ACKNOWLEDGEMENTS

My sincere appreciation to my supervisor, Associate Professor Gs Sr. Dr. Abdul Rashid bin Mohammed Shariff, PhD, CEng, the chairman of my supervisory committee, for giving me this opportunity to embark on this project and guiding me throughout this excitingly challenging task. I would like to also thank other members of my supervisory committee: Associate Professor Rimfiel b. Janius, Associate Professor Zulkifly Abbas, Dr Ghafour Amouzad Mahdiraji for their supports and advices during the period of my study. I appreciate their knowledge, collaborations and recommendations in making this project a dream come true.

I am also grateful to the Geographical Information System Research Centre (GISRC), FELDA Agricultural Services Sdn. Bhd. and Department of Biological and Agricultural Engineering, Faculty of Engineering University of Putra Malaysia, for their contribution in facilitating smoothly for the completion of this project alongside with other co-researchers in the Centre. Last but not least, my deepest appreciations to my family, friends, especially my lovely parents who supported me in many terms. I could not have done this research work without their patients and supports.



This thesis was submitted to the Senate of Universiti of Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

**Abdul Rashid bin Mohammed Shariff, PhD, CEng**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**Rimfiel b. Janius, PhD**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**Zulkifly Abbas, PhD**

Associate Professor  
Faculty of Science  
Universiti Putra Malaysia  
(Member)

**Ghafour Amouzad Mahdiraji, PhD**

Lecturer  
School of Engineering  
Taylor's University  
(Member)

---

**ROBIAH BINTI YUNUS, PhD**

Professor and Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date:

## Declaration by Members of Supervisory Committee

This is to confirm that:

- The research conducted and the writing of the thesis was under our supervision;
- Supervision responsibilities as stated in the University of Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012 – 2013) are adhered to.

Signature: \_\_\_\_\_  
Name of  
Chairman of  
Supervisory  
Committee: Assoc. Prof. Dr. Abdul Rashid bin Mohamed Shariff

Signature: \_\_\_\_\_  
Name of  
Member of  
Supervisory  
Committee: Assoc. Prof. Dr. Rimfiel b. Janius

Signature: \_\_\_\_\_  
Name of  
Member of  
Supervisory  
Committee: Assoc. Prof. Dr. Zulkifly Abbas

Signature: \_\_\_\_\_  
Name of  
Member of  
Supervisory  
Committee: Dr. Ghafour Amouzad Mahdiraji

## TABLE OF CONTENTS

	<b>ABSTRACT</b>	<b>Page</b>
	<b>ABSTRAK</b>	i
	<b>ACKNOWLEDGEMENTS</b>	iii
	<b>APPROVAL</b>	v
	<b>DECLARATION</b>	vi
	<b>LIST OF TABLES</b>	viii
	<b>LIST OF FIGURES</b>	xii
	<b>LIST OF ABBREVIATIONS</b>	xiii
	<b>LIST OF ABBREVIATIONS</b>	xiv
 <b>CHAPTER</b>		
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Background of Study	1
	1.2 Problem Statement	2
	1.3 Research Objectives	2
	1.4 Scope of Research	3
	1.5 Research Contribution	3
	1.6 Thesis Layout	3
	1.7 Summary	4
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>5</b>
	2.1 Overview	5
	2.2 World Oil Palm Production	5
	2.3 Conventional Oil Palm FFB Ripeness Grading System	6
	2.4 Research Trend Base on Reviewed Literatures	7
	2.5 WEKA Data Mining Software	10
	2.6 Summary	11
<b>3</b>	<b>METHODOLOGY AND PROCEDURES</b>	<b>12</b>
	3.1 Overview	12
	3.2 Research Workflow	12
	3.3 Samples Collection and Preparation	14
	3.4 Laboratory Experimental Setup and OPRiD Spectrometer	14
	3.5 Data Collections and Pre-Processing	17
	3.5.1 Data pre-processing	18
	3.5.2 Experimental Research Limitation	20
	3.6 Significant Band Selection	20
	3.7 WEKA Data Mining Classification of the Oil Palm FFB	21
	3.7.1 Data Collection and Preparation	21
	3.7.2 Data Cleansing	21
	3.7.3 Converting collected data to CSV or ARRF Format	22
	3.7.4 Loading of data in WEKA	22
	3.7.5 Attribute Selection	24
	3.7.6 Classifier Model Building	25
	3.7.7 Model Generalisation	26
	3.8 Summary	26

<b>4</b>	<b>RESULT AND DISCUSSIONS</b>	<b>28</b>
4.1	Overview	28
4.2	Box Plot Result and Discussion	28
4.3	Machine Learning Classification Result	36
4.4	Classifier Models Result Analysis	39
4.4.1	Built Models from Selected Attribute	39
4.4.2	Built Models from All 32 Attributes	39
4.5	Built Classifier Model Result Summary	40
4.6	Built Classifier Model Validation	42
<b>5</b>	<b>CONCLUSION</b>	<b>46</b>
5.1	Overview	46
5.2	Contribution to Knowledge	46
5.3	Limitation and Recommendation for Future Research	46
	<b>REFERENCES</b>	<b>47</b>
	<b>APPENDICES</b>	<b>51</b>
	<b>BIODATA OF STUDENT</b>	<b>57</b>
	<b>LIST OF PUBLICATIONS</b>	<b>58</b>

## LIST OF TABLES

Table	Page
3.1 Spectrometer sensors sensitivities	16
3.2 LED characteristics of the sensor	17
3.3 Grading standard used by MPOB	19
3.4 Samples of raw measured data by the four sensors	20
3.5 Combined experimental data from sensors reading	27
4.1 Box plot mean values	35
4.2 Percentage contributions of sensors for feature selection algorithm	37
4.3 Wrapper method of significant feature selection with different classification algorithm	38
4.4 Classifier model result from all selected attribute	40
4.5 Confusion matrix result of the built model	41
4.6 Classifier evaluation result summary from all built models	43
4.7 Comparative analysis result from significant attribute selection	44

## LIST OF FIGURES

Figure	Page
2.1 World production of palm oil versus other vegetable oils	6
3.1 Flowchart of obtaining the analytical results	13
3.2 Spectrometer System layout	15
3.3 OPRID system layout	15
3.4 Laboratory experimental Setup	18
3.5 WEKA explorer interface outlook	22
3.6 Preprocessing operation after data loading	23
3.7 Attribute selection result for Lazy IBK algorithm	24
3.8 Lazy IBK model building using 32 attributes	25
4.1 AbmerS2 vs Class	31
4.2 RedS2 vs Class	32
4.3 DRedS2 vs Class	32
4.4 FRedS2 vs Class	33
4.5 UVS4 vs Class	33
4.6 GreenS4 vs Class	34
4.7 RedS4 vs Class	34
4.8 FRedS4 vs Class	35
4.9 Sensors contribution to feature selection	37
4.10 Oil palm FFB ripeness predictive model summary	41

## LIST OF ABBREVIATIONS

ANN	artificial neural network
ARFF	attribute related file format
CSV	comma separated value
FFB	fresh fruit bunches
GANN	genetic algorithm neural network
GDI	graphic device interface
HSI	hue saturation and intensity
LED	light emitting diode
MAE	mean absolute error
MPOB	Malaysian palm oil board
NIR	near infra-red
NOL	neutral oil
NIR	near-infra red
OER	oil extraction rate
OPRiD	oil palm ripeness detector
RGB	red, green and blue
RMSE	root mean squared error
RSM	response surface methodology
ROC	receiver operating characteristic
SVM	support vector machine
UPM	Universiti Putra Malaysia
MPOC	Malaysian Palm Oil Council
WEKA	Waikato Software
UVS1	ultra violet from sensor 1
BlueS1	blue from sensor 1
GreenS1	green from sensor 1
AmberS1	amber from sensor 1
RedS1	red from sensor 1
DRedS1	deep red from sensor 1
FRedS1	far red from sensor 1
IRedS1	infra-red from sensor 1

UVS2	ultra violet from sensor 2
BlueS2	blue from sensor 2
GreenS2	green from sensor 2
AmberS2	amber from sensor 2
RedS2	red from sensor 2
DRedS2	deep red from sensor 2
FRedS2	far red from sensor 2
IRedS2	infra-red from sensor 2
UVS3	ultra violet from sensor 3
BlueS3	blue from sensor 3
GreenS3	green from sensor 3
AmberS3	amber from sensor 3
RedS3	red from sensor 3
DRedS3	deep red from sensor 3
FRedS3	far red from sensor 3
IRedS3	infra-red from sensor 3
UVS4	ultra violet from sensor 4
BlueS4	blue from sensor 4
GreenS4	green from sensor 4
AmberS4	amber from sensor 4
RedS4	red from sensor 4
DRedS4	deep red from sensor 4
FRedS4	far red from sensor 4
IRedS4	infra-red from sensor 4



# CHAPTER 1

## INTRODUCTION

### 1.1 Background of Study

Oil palm fruit is mostly grown in the tropical parts of South Eastern Asia, South Africa and South America as a major export product. This provides a major source of vital food for several millions of people and an essentially import diet for human healthy living (World Oil, 2016). Medically, the oil has good resistance to oxidation and enhances exposure to high temperatures, thereby enhancing it uses as a frying agent. The palm oil structure encourages its addition to other frying oils in large proportions, and also has good economic values as may be needed as an export product (Jamil, Mohamed, & Abdullah, 2009). Moreover, the oil palm industry in Malaysia is highly regulated, and one major problem faced by industry is in the accurate grading system of the fresh oil palm fruits based on its ripeness, which helps in the determination of the quality and quantity of the palm oil that could be extracted from the Fresh Fruit Bunches (FFB). The quest for increase in the Oil Extraction Rate (OER) in Malaysia have been an important research areas, which is necessitated as a result of limited land resources availability, since oil palm is one of the major agricultural export product that covers approximately over 5 million hectares of land within the country (Ismail et al., 2009). The maturity rate of the oil palm FFB determines the quality and quantity of OER that could be achieved annually, thereby contributing to per capital GDP of the country economy growth annually. Furthermore, a ripe oil palm FFB produces a high and qualitative OER, while an under ripe FFB will produced less OER, while overripe FFB has lesser oil quality as the case maybe.

The FFB maturity and ripeness dictates the product marketability and increase in the demand of the product based on its good quality, result from correct ripeness prediction. The FFB ripeness is generally categorised into four basic classes as: ripe, under ripe, unripe and overripe (Abdullah et al., 2001). There are several ranges of colour exhibited by the fruits from yellow at the base, reddish orange, dark purple to at the black at the apex and red. Most tender FFB contain 50 to 100 red-violet ripe fruits per bunch, since the ratio FFB pigment like the carotenoids and chlorophylls determines the colour of the FFB. Hence, fruits with higher proportion of chlorophyll, gradually decreases as the FFB matures, while a high content of carotenoids increase as oil palm fruits mature (Jamil et al., 2009). Therefore, the FFB colours changes that is due to these mentioned factors from biochemical reactions can relates to the fruit maturity.

This thesis presents a data mining approach for accurate classification of the oil palm FFB into under-ripe, ripe, and over-ripe categories, in order to address the above stated problems and limitations. This research was done at an oil palm plantation in peninsular Malaysia.

## **1.2 Problem Statement**

The oil palm sector faces many problems, one major challenges being the accurate grading system of the oil palm FFB based on maturity. The accurate prediction of the oil palm FFB maturity helps in the determination of the oil palm extraction rate (OER) from the FFB. (Yeow et al., 2010). The quest for increase in the OER has also called for a more robust and reliable means of FFB maturity grading in Malaysia, which has triggered several researches in this area, and also motivated this research work for the application of an intelligent data mining, and knowledge discovery approach based on available spectrometer data without human intervention for the oil palm FFB ripeness prediction with lesser time, and rigor. Furthermore, the accuracy of the human grader as currently adopted in the Malaysia oil palm industries cannot be ascertained during grading, labeling and harvesting of the oil palm FFB. It is also considered to be time consuming, strenuous and also subjected to human error of judgments which may also compromised the final grading result (Hudzari, 2012) (Hazir et al., 2012).

This thesis presents a data mining and knowledge discovery approach for the extraction of hidden useful knowledge from the spectrometer extracted data, for accurate classification of oil palm FFB maturity in a laboratory experimental setup, for the building of a classifier model that can accurately predict the oil palm FFB maturity levels. This validates the performance of the conventional human grader assessments system of the maturity determination of the oil palm FFB into unripe, under-ripe, ripe and over-ripe categories. This research was done at an oil palm plantation in peninsular Malaysia.

## **1.3 Research Objectives**

In order to achieve an effective performance evaluation and applicability of spectrometry data for the accurate maturity level determination of the oil palm FFB ripeness classification, so as to addresses the above stated problems, the following objectives are set out to be achieved:

1. To determine the most significant spectrum bands from the built model for the oil palm FFB ripeness classification model building.
2. To determine the best classier model for effective generalization of the built model for future prediction of the oil palm FFB maturity level.
3. To validate the performance evaluation of the built mode against conventional human grader assessment in the oil palm industries.

#### **1.4 Scope of Research**

In this research work, the scope is limited to these areas based on the gap discovered from the reviewed literatures:

- i. Only matured freshly harvested 106 samples of nigrescens oil palm FFB were used for this research work.
- ii. The harvesting skills of the human grader is not considered in this study
- iii. The data extraction from the OPRiD spectrometer sensor application for the reflectance reading of the 8 band LED module light.
- iv. Only visible light, infra-red and ultra violet in the wavelength range of 10 – 1000000 nm are considered as dictated by the equipment used.
- v. 106 oil palms FFB samples with four maturity classes of unripe (31), under-ripe (25), ripe (24) and over-ripe (26) were considered in this research work, as compared to the conventional six known classes.
- vi. The distance between the spectrometer and the samples to the measured are fixed and not adjustable as seen in some other models of spectrometer.
- vii. The research experiment was conducted in the laboratory on already labeled oil palm FFB harvested and labeled by human grader manually.

#### **1.5 Research Contribution**

This research work achieves the following contributions to knowledge in this field of study:

- i. Building of an intelligent model that could generalized in the classification of the oil palm FFB as compared to the conventional manual grading system.
- ii. Determination of an accurate spectrometer band frequency, appropriate for the effective classification of the oil palm FFB ripeness, thereby saving time and energy applied in the application of all extracted wavelength band from the spectrometer sensors.
- iii. Determination an improved OER classifier model that will improve the productivity of the oil palm industries in term of cost optimization and profit maximization.

#### **1.6 Thesis Layout**

Chapter 1 (Introduction), entails the background of study to this research work, necessary insight on the oil palm extraction rate improvements, problems statement, research hypothesis and objectives to be achieve.

Chapter 2 (Literature Review) discusses reviews on the previous proposed techniques as applied in both classical and modern oil palm FFB grading system as proposed in the literatures. Other applied nature inspired optimization algorithm application was also considered in solving the stated problems. However, recent proposed AI approaches in

recent researches in this area were studied and compared with the earlier conventional known methods to determine its merits and weakness.

Chapter 3 (Methodology and Procedures) discusses the elaborate steps in achieving the set research objectives that is hypothesized. The equipment experimental setup in the laboratory for features extractions from the oil palm FFB, alongside with relevant data extraction and recording for onward application in data mining tool of WEKA software. The entire sequence of procedures in achieving the set objectives was fully explained in this chapter.

Chapter 4 (Results and Discussions) presents all obtained results and discussions on the outcome of all findings, validations and testing. Results comparison is also detailed.

Chapter 5 (Conclusion) the derive conclusion on the research work, discussion on the research contributions and recommend with some potential future researches improvement.

## **1.7 Summary**

This chapter introduces the basic concepts and guidelines of this research work with illustrations on basic known fact based on the pending challenges faced in oil palm industries, with respect to accurate maturity grading of oil palm FFB ripeness determination and its impacts on the OER. A proposed data mining and knowledge discovery approach is proposed to address the pending identified research gap problems, through building of an intelligent classifier model that could generalized and enhanced accurate classification of the oil palm FFB ripeness. The next chapter will illustrate several literatures reviewed on recent research works in this area, while the merits and challenges of earlier applied method will also be mention accordingly. The research gap will be discovered to enhance the newly proposed techniques and its merit with future research area for improvement also mention.

## REFERENCES

- Abdullah, M. Z., Guan, L. C., Lim, K. C., & Karim, A. A. (2004). The applications of computer vision system and tomographic radar imaging for assessing physical properties of food. *Journal of Food Engineering*, 61(1 SPEC.), 125–135.
- Abdullah, M. Z., Guan, L. C., & Mohd Azemi, B. M. N. (2001). Stepwise Discriminant Analysis for Colour Grading of Oil Palm Using Machine Vision System. *Food and Bioproducts Processing*, 79(4), 223–231.
- Alfatni, M. S. M., Shariff, A. R. M., Abdullah, M. Z., Marhaban, M. H., Shafie, S. B., BAmiruddin, M. D., & Saaed, O. M. B. (2014). Oil palm fresh fruit bunch ripeness classification based on rule- based expert system of ROI image processing technique results. *IOP Conference Series: Earth and Environmental Science*, 20, 12018.
- Alfatni, M., Shariff, A., & Shafri, H. (2008). Oil palm fruit bunch grading system using red, green and blue digital number. *Journal of Applied science*. 8(8), 1444 - 1452
- Arakeri, M. P., & Lakshmana. (2016). Computer Vision Based Fruit Grading System for Quality Evaluation of Tomato in Agriculture industry. *Procedia Computer Science*, 79, 426–433.
- Bensaeed, O. M., Shariff, A. M., Mahmud, A. B., Shafri, H., & Alfatni, M. (2014). Oil palm fruit grading using a hyperspectral device and machine learning algorithm. *IOP Conference Series: Earth and Environmental Science*, 20(1), 12017.
- Dharma. Silalahi, D., Reaño, C. E., Lansigan, F. P., Panopio, R. G., & Bantayan, N. C. (2016). Using Genetic Algorithm Neural Network on Near Infrared Spectral Data for Ripeness Grading of Oil Palm (*Elaeis guineensis* Jacq.) Fresh Fruit. *Information Processing in Agriculture*, 3, 252–261.
- Fadilah, N., & Mohamad-Saleh, J. (2014). Color feature extraction of oil palm fresh fruit bunch image for ripeness classification. *13th International Conference on Applied Computer and Applied Computational Science (ACACOS'14)*, 51–55.
- Fadilah, N., Mohamad-Saleh, J., Halim, Z. A., Ibrahim, H., & Ali, S. S. S. (2012). Intelligent color vision system for ripeness classification of oil palm fresh fruit bunch. *Sensors*, 12(10), 14179–14195.
- Fadilah, N., Saleh, J. M., Ibrahim, H., & Halim, Z. A. (2012). Oil palm fresh fruit bunch ripeness classification using artificial neural network. *2012 4th International Conference on Intelligent and Advanced Systems (ICIAS2012)*, 1, 18–21.

- Giovenzana, V., Beghi, R., Civelli, R., & Guidetti, R. (2015). Optical techniques for rapid quality monitoring along minimally processed fruit and vegetable chain. *Trends in Food Science and Technology*, 46(2), 331–338.
- Harun, N. H., Misron, N., Sidek, R. M., Aris, I., Ahmad, D., Wakiwaka, H., & Tashiro, K. (2013). Investigations on a novel inductive concept frequency technique for the grading of oil palm fresh fruit bunches. *Sensors (Switzerland)*, 13(2), 2254–2266.
- Hazir, M. H. M., Shariff, A. R. M., & Amiruddin, M. D. (2012a). Determination of oil palm fresh fruit bunch ripeness—Based on flavonoids and anthocyanin content. *Industrial Crops and Products*, 36(1), 466–475.
- Hazir, M. H. M., Shariff, A. R. M., & Amiruddin, M. D. (2012b). Determination of oil palm fresh fruit bunch ripeness—Based on flavonoids and.pdf. *Industrial Crops and Products*, 36, 466–475.
- Hazir, M. H. M., Shariff, A. R. M., Amiruddin, M. D., Ramli, A. R., & Iqbal Saripan, M. (2012). Oil palm bunch ripeness classification using fluorescence technique. *Journal of Food Engineering*, 113(4), 534–540.
- Hudzari Razali, M. (2012). A Novel Technology in Malaysian Agriculture. *Advances in Computing*, 2(2), 1–8. <https://doi.org/10.5923/j.ac.20120202.01>
- Ian H. Witten, Eibe Frank, & Hall, M. A. (2011). *Data Mining Practical Machine Learning Tools and Techniques*. Vasa.
- Ismail, W. I. W., & Razali, M. H. (2010). Outdoor Colour Recognition System for Oil Palm Fresh Fruit Bunches (Ffb). *International Journal of Machine Intelligence*, 2(1), 1–10.
- Ismail, W. I. W., Razali, M. H., Ramli, A. R., Sulaiman, M. N., & Harun, M. H. B. (2009). Development of Imaging Application for Oil Palm Fruit Maturity Prediction. *Engineering E-Transaction*, 4(2), 56–63.
- Jamil, N., Mohamed, A., & Abdullah, S. (2009). Automated grading of palm oil Fresh Fruit Bunches (FFB) using neuro-fuzzy technique. *SoCPaR 2009 - Soft Computing and Pattern Recognition*, (1), 245–249.
- Khan, M., & Quadri, S. M. K. (2012). Evaluating Various Learning Techniques for Efficiency, (2), 326–331.
- Kumar, V., & Rathee, N. (2011). Knowledge discovery from database Using an integration of clustering and classification. *International Journal of Advanced Computer Science and Applications*, 2(3), 29–33.
- Makky, M. (2016). A Portable Low-cost Non-destructive Ripeness Inspection for Oil Palm FFB. *Agriculture and Agricultural Science Procedia*, 9, 230–240. <https://doi.org/10.1016/j.aaspro.2016.02.139>



- Makky, M., & Soni, P. (2014). In situ quality assessment of intact oil palm fresh fruit bunches using rapid portable non-contact and non-destructive approach. *Journal of Food Engineering*, 120(1), 248–259.
- Makky, M., Soni, P., & Salokhe, V. M. (2014a). Automatic Non-destructive Quality Inspection System for Oil Palm Fruits. *International Agrophysics*, 28(3), 319–329.
- Makky, M., Soni, P., & Salokhe, V. M. (2014b). Automatic Non-destructive Quality Inspection System for Oil Palm Fruits. *International Agrophysics*. <https://doi.org/10.2478/intag-2014-0022>
- May, Z., & Amaran, M. H. (2011). Automated Oil Palm Fruit Grading System using Artificial Intelligence. *International Journal of Video and Image Processing and Network Security IJVIPNS-IJENS*, 11(June), 30–35.
- Mikut, R., & Reischl, M. (2011). Data mining tools. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, 1(5), 431–443.
- Nureize, A., & Watada, J. (2010). A fuzzy regression approach to a hierarchical evaluation model for oil palm fruit grading. *Fuzzy Optimization and Decision Making*, 9(1), 105–122.
- Preethi, N., & Goswami, D. (2015). A Review on Role of Data Mining Techniques in Enhancing Educational Data to Analyze Student 's Performance. *International Journal of Computer Science and Information Technology Research ISSN*, 3(1), 123–129.
- Rungpichayapichet, P., Mahayothee, B., Nagle, M., Khuwijitjaru, P., & Müller, J. (2016). Robust NIRS models for non-destructive prediction of postharvest fruit ripeness and quality in mango. *Postharvest Biology and Technology*, 111, 31–40.
- Saeed, O. M. Ben, Sankaran, S., Shariff, A. R. M., Shafri, H. Z. M., Ehsani, R., Alfatni, M. S., & Hazir, M. H. M. (2012). Classification of oil palm fresh fruit bunches based on their maturity using portable four-band sensor system. *Computers and Electronics in Agriculture*, 82, 55–60.
- Sampaio, K. A., Ceriani, R., Silva, S. M., Taham, T., & Meirelles, A. J. A. (2011). Steam deacidification of palm oil. *Food and Bioproducts Processing*, 89(4), 383–390.
- Shabdin, M. K., Shariff, A. R. M., Johari, M. N. A., Saat, N. K., & Abbas, Z. (2016). A study on the oil palm fresh fruit bunch (FFB) ripeness detection by using Hue, Saturation and Intensity (HSI) approach. *IOP Conference Series: Earth and Environmental Science*, 37, 12039.
- Talebi, S., & Sayficar, A. A. (2014). Using Educational Data Mining ( EDM ) to Prediction and Classify Students. *International Journal Of Engineering And Computer Science*, 3(12), 9395–9398.

Taparugssanagorn, A., Siwamogsatham, S., & Pomalaza-Ráez, C. (2015). A non-destructive oil palm ripeness recognition system using relative entropy. *Computers and Electronics in Agriculture*, 118, 340–349.

World oil. (2016). OIL WORLD Database. *World Oil*, (3).

Yeow, Y. K., Abbas, Z., & Khalid, K. (2010). Application of Microwave Moisture Sensor for Determination of Oil Palm Fruit Ripeness, 10(1), 7–14.

Zhang, C., Guo, C., Liu, F., Kong, W., He, Y., & Lou, B. (2016). Hyperspectral imaging analysis for ripeness evaluation of strawberry with support vector machine. *Journal of Food Engineering*, 179, 11–18.

Zhu, Q., He, C., Lu, R., Mendoza, F., & Cen, H. (2015). Ripeness evaluation of “Sun Bright” tomato using optical absorption and scattering properties. *Postharvest Biology and Technology*, 103, 27–34.