

# **UNIVERSITI PUTRA MALAYSIA**

# MODELING INFILTRATION CAPACITY OF PERMEABLE CHANNELS UNDER STATIC AND DYNAMIC HYDRAULIC CONDITIONS

AHMED MOHAMMED SAMI AL-JANABI

FK 2018 132



## MODELING INFILTRATION CAPACITY OF PERMEABLE CHANNELS UNDER STATIC AND DYNAMIC HYDRAULIC CONDITIONS



AHMED MOHAMMED SAMI AL-JANABI

Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in Fulfillment of the Requirements for the Degree of Doctor of Philosophy

July 2018

## COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs, and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



## **DEDICATION**

То

My parents

My parents-in-law

My lovely family, wife and children

&

Everybody who support my journey to obtain

Degree of Doctor of Philosophy

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the degree of Doctor of Philosophy

### **MODELING INFILTRATION CAPACITY OF PERMEABLE CHANNELS** UNDER STATIC AND DYNAMIC HYDRAULIC CONDITIONS

By

### AHMED MOHAMMED SAMI AL-JANABI

**July 2018** 

Chairman Faculty :

: Associate Professor Abdul Halim Bin Ghazali, PhD Engineering

Increasing infiltration rate of stormwater is important for improving the control of stormwater quantity to foster sustainable urban stormwater management. In the design of stormwater channels, the effect of infiltration on the channel flow and the effects of hydraulic parameters such as water level, channel cross section, flow velocity, and vegetation, on the infiltration capacity of channels are usually ignored. The present study aimed to examine the effects of hydraulic parameters on the infiltration capacity of permeable channels through laboratory investigation on channel models under static and dynamic hydraulic conditions. The study also aimed to develop empirical models for the variations of infiltration capacity with flow hydraulic parameters, in order to improve the design of permeable stormwater channels. Different channel models were constructed for each of the above condition, and different sets of hydraulic and channel boundary conditions were used to characterise the channel flow considering the effect of infiltration and to develop empirical models for predicting infiltration capacity for permeable channels. The effect of channel cross section on the flow reduction by seepage and infiltration processes were first examined under static or standing water condition, with various initial water levels, channel base widths and side slopes. Regression analysis was used to develop an equation for predicting the rate of unsteady seepage over time, and the equation was used to examine several cases of different flow cross-sectional areas and channel dimensions, and subsequently, to determine the section that produced highest infiltration and seepage under the unsaturated soil condition. Moreover, five existing infiltration models, namely, the Kostiakov, Horton, Modified Kostiakov, Philip, and Soil Conservation Service (SCS) models were evaluated, and then they were modified by incorporating the cross-sectional flow area parameters (depth y, side slope m, and bottom width b) into them. Under the dynamic or flowing water condition, the mass-balance method was used for the estimation of infiltration rate, and the experimental tests employed five inflow rates ( $Q_{in} = 5.5, 7.5, 9.5, 11.5, 13.5 \text{ l/s}$ ), with three downstream check dam



heights ( $h_w = 10, 15, 20$  cm). In addition, two other sets of experiments were conducted to investigate the effects of grass cover and subsurface water on infiltration rate. The findings were used to quantify and compare the different cases in terms of the infiltration rate and cumulative infiltration, and then to develop predictive equations that include the effect of hydraulic parameters for estimating the infiltration rate in permeable channels. The results indicated that the infiltration and seepage rates increase with increasing initial water level irrespective of the base width and side slope. Moreover, an increase in the side slope increases both the infiltration and seepage rates, with the effect becoming more significant as the initial water level increases, while the effect of varying the base width is insignificant. It has also been found that increasing the wetted perimeter or top width of a channel enhances the infiltration rate if this is achieved by varying the side slope, and not by increasing the base width. In the evaluation of the five infiltration models, a comparison using the coefficients of determination  $R^2$  obtained before and after the parameters were added into the models reveals that the difference between the observed and predicted values using the modified models was significantly reduced, and  $R^2$  increased sharply from 0.14, 0.158, 0.164, 0.146 and 0.162 for the Kostiakov, Horton, Modified Kostiakov, Philip, and SCS models, respectively, to 0.732, 0.621, 0.735, 0.718 and 0.609. Two predictive equations were developed finally using the nonlinear regression analysis after introducing the four hydraulic parameters (y, m, b and v) into the Kostiakov and Modified Kostiakov models, which were chosen to be improved because they have been shown to give better performance than the other models during the previous analysis. The latter model with the new parameters was used for the analysis of a channel section to determine the best conditions to obtain the highest infiltration rates for given flow rates and then to plot graphs of the variation of cumulative infiltration F over time for a grassed channel with different check dam heights and inflow rates. Cumulative infiltration quantity after 90 min for two cases of channels, with and without check dams, were compared and the results reveal that the percentage of total infiltrated water volume increased from 8% to 14% when using check dams with 20cm height and 10-m spacing compared to the channel without the check dams. Modeling the variations of infiltration capacity with hydraulic parameters in permeable channels using the models developed in this study therefore promises better stormwater management and provides a valuable decision support tool for designing the permeable channels.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Doktor Falsafah

### PEMODELAN KEUPAYAAN PENYUSUPAN SALURAN TELAP DI DALAM KEADAAN HIDRAULIK STATIK DAN DINAMIK

Oleh

### AHMED MOHAMMED SAMI AL-JANABI

Julai 2018

### Pengerusi : Profesor Madya Abdul Halim Bin Ghazali, PhD Fakulti : Kejuruteraan

Meningkatkan kadar penyusupan air larian hujan adalah penting untuk menambah baik kawalan kuantiti air larian hujan bagi memupuk pengurusan air larian hujan bandar yang lestari. Dalam mereka bentuk saluran air hujan, kesan penyusupan ke atas aliran saluran dan kesan parameter hidraulik, iaitu paras air, keratan rentas saluran, halaju aliran dan tumbuh-tumbuhan dalam saluran, ke atas keupayaan penyusupan biasanya diabaikan. Kajian ini bertujuan untuk menilai kesan parameter hidraulik ke atas kapasiti penyusupan saluran telap melalui penyiasatan makmal ke atas model saluran di dalam keadaan hidraulik statik dan dinamik. Kajian ini juga bertujuan untuk membangunkan model empirikal untuk meramalkan variasi kapasiti penyusupan dengan parameter hidraulik, bagi meningkatkan reka bentuk saluran air hujan yang telap. Model saluran yang berlainan dibina bagi setiap keadaan di atas, dan keadaan hidraulik dan sempadan saluran yang berlainan digunakan untuk mencirikan aliran dalam saluran dengan mengambil kira kesan penyusupan serta untuk membangunkan model empirikal bagi menjangka keupayaan penyusupan bagi saluran telap. Kesan keratan rentas saluran ke atas pengurangan aliran melalui proses resapan dan penyusupan mula-mula dikaji di dalam keadaan statik atau air bertakung, dengan pelbagai aras air awal, lebar dasar saluran dan cerun sisi. Analisis regresi digunakan untuk membina satu persamaan bagi meramalkan kadar resapan tak mantap melawan masa, dan persamaan itu digunakan untuk meneliti beberapa kes saluran dengan luas keratan-rentas aliran dan dimensi saluran yang berbeza, dan seterusnya menentukan keratan yang menghasilkan kadar penyusupan dan resapan tertinggi di dalam keadaan tanah tak tepu. Selain itu, lima model penyusupan sedia Modified Kostiakov, Philip, ada. iaitu model Kostiakov, Horton, dan Soil Conservation Service (SCS) telah dinilai. dan kemudian model tersebut telah diubahsuai dengan memasukkan parameter luas aliran keratan rentas (kedalaman y, cerun sisi m, dan lebar dasar b) ke dalamnya. Di dalam keadaan dinamik atau air mengalir, kaedah imbangan-jisim telah digunakan untuk



menganggarkan kadar penyusupan, dan ujian telah dilakukan menggunakan lima kadar aliran masuk (Q<sub>masuk</sub> = 5.5, 7.5, 9.5, 11.5, 13.5 l/s), dengan tiga ketinggian empangan penyekat hiliran ( $h_w = 10$ , 15, dan 20 cm). Di samping itu, dua set eksperimen lain telah dijalankan untuk menyiasat kesan kewujudan rumput dan air bawah permukaan ke atas kadar penyusupan. Hasil yang diperolehi digunakan untuk mengira dan membandingkan saluran telap yang berlainan, dari segi kadar penyusupan dan penyusupan kumulatif, dan kemudian untuk membangunkan persamaan ramalan yang merangkumi kesan parameter hidraulik untuk menganggarkan kadar penyusupan di dalam saluran telap. Keputusan menunjukkan bahawa kadar penyusupan dan kadar resapan meningkat dengan peningkatan aras air awal tanpa mengira lebar dasar dan cerun sisi. Selain itu, peningkatan cerun sisi meningkatkan kedua-dua kadar penyusupan dan resapan, dengan kesannya menjadi lebih signifikan apabila aras air awal meningkat, manakala kesan perbezaan lebar dasar adalah tidak signifikan. Didapati juga bahawa peningkatan perimeter basah atau lebar atas saluran dapat meningkatkan kadar resapan sekiranya ia dicapai dengan mengubah cerun sisi, dan bukan dengan menambahkan lebar dasar. Di dalam penilaian lima model penyusupan, perbandingan menggunakan koefisien penentuan  $R^2$  yang diambil sebelum dan selepas parameter ditambah ke dalam model itu menunjukkan bahawa perbezaan di antara nilai yang dicerapkan dan nilai yang diramalkan menggunakan model yang diubahsuai telah dikurangkan dengan ketara, dan  $R^2$ meningkat dengan mendadak daripada 0.14, 0.158, 0.164, 0.146 dan 0.162 masingmasing bagi model Kostiakov, Horton, Modified Kostiakov, Philip, dan SCS, kepada 0.732, 0.621, 0.735, 0.718 dan 0.609. Akhir sekali, dua persamaan ramalan telah dibangunkan menggunakan analisis regresi tak linear dengan memperkenalkan empat parameter hidraulik  $(v, m, b \, dan \, v)$  ke dalam model Kostiakov dan Modified Kostiakov. Dua model ini telah dipilih untuk diperbaiki kerana kedua-dua model itu telah menunjukkan prestasi yang lebih baik daripada model lain semasa terdahulu. Model kedua dengan parameter baru digunakan untuk analisis menganalisis satu seksyen saluran untuk menentukan keadaan terbaik untuk memperolehi kadar penyusupan tertinggi bagi kadar aliran tertentu dan kemudian memplot graf variasi penyusupan kumulatif F dengan masa untuk saluran berumput dengan ketinggian empangan sekatan dan kadar aliran masuk yang berbeza. Kuantiti penyusupan kumulatif selepas 90 minit untuk dua kes saluran, dengan dan tanpa empangan sekatan, telah dibandingkan dan hasilnya menunjukkan bahawa peratusan isi padu air penyusupan meningkat daripada 8% ke 14% apabila jumlah menggunakan empangan sekatan dengan ketinggian 20-cm dan jarak 10-m berbanding saluran tanpa empangan sekatan. Oleh itu, pemodelan variasi kapasiti penyusupan dengan parameter hidraulik dalam saluran telap menggunakan model yang dibangunkan di dalam kajian ini menjanjikan pengurusan air larian hujan yang lebih baik dan mengemukakan suatu alat sokongan keputusan yang berharga dalam mereka bentuk saluran telap.

#### ACKNOWLEDGEMENTS

First and Foremost, all praise is devoted to the Almighty ALLAH (SWT), the Lord of the worlds, for giving me the strength and determination to undertake this research study, and complete it to appear in its current form.

Profound and sincere gratitude is expressed to my supervisor Associate Professor Dr. Abdul Halim Ghazali for his invaluable support and guidance throughout all of the experiments and the thesis stages, which have significantly contributed to the success of this research.

I would like also to express my sincere appreciation and gratitude to my co-supervisor Dr. Badronnisa Binti Yusuf, the leader of this study project, which is funded by the Ministry of Science, Technology & Innovation (MOSTI), Malaysia through its science fund project (No. UPM0008770). I would like also to express my sincere appreciation and gratitude to Professor Dr. Thamer Ahmad Mohammad, my supervisory committee member, for his constructive comments and suggestions, which enriched this research.

The great assistance provided to the author during the experimental work by the technicians of the Hydraulic Laboratory of Universiti Putra Malaysia is appreciated. Not forgetting either to thank my friends and my workmates, who supported me during the period of the study.

Last but not least, my heartfelt thanks to all my family, without their support and encouragement this study would not have been possible.

This thesis was submitted to the Senate of the Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory Committee were as follows:

#### Abdul Halim Ghazali, PhD

Associate Professor Faculty of Engineering Universiti Putra Malaysia (Chairman)

### **Badronnisa Binti Yusuf, PhD** Senior Lecturer Faculty of Engineering Universiti Putra Malaysia

(Member)

### Thamer Ahmad Mohammad Ali, PhD Professor Faculty of Engineering Universiti Putra Malaysia (Member)

### **ROBIAH BINTI YUNUS, PhD** Professor and Dean School of Graduate Studies Universiti Putra Malaysia

Date:

### **Declaration by graduate student**

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software

Signature:	Date:

Name and Matric No: Ahmed MohammedSami Ali Al-Janabi, GS37471

## **Declaration by Members of Supervisory Committee**

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) were adhered to.

Signature: Name of Chairman	
Committee:	Associate Professor Dr. Abdul Halim Ghazali
Signature:	
Name of Member	
of Supervisory	
Committee:	Dr. Badronnisa Binti Yusuf
Signature:	
Name of Member of Supervisory	
Committee:	Professor Dr. Thamer Ahmad Mohammad Ali

### **TABLE OF CONTENTS**

ABSTRACT

ABS ACI APP DEC LIS <sup>7</sup> LIS <sup>7</sup>	<i>STRAK</i> KNOWL PROVAL CLARAT I OF TA I OF FIG I OF AE	EDGEMENTS TION ABLES GURES BBREVIATIONS	iii v vi viii xiii xv xxi
CHA	APTER		
1	INTR	ODUCTION	1
	1.1	Background	1
	1.2	Problem Statement	3
	1.3	Research Objectives	4
	1.4	Significance of the Study	4
	1.5	Scope and Limitations	5
	1.6	Thesis Layout	7
2	LITE	RATURE REVIEW	8
-	2.1	Introduction	8
	2.2	Flow Characteristics in Permeable Open Channels	8
	2.3	Infiltration and Unsaturated Seepage	15
	2.4	Effect of Channel Section on Infiltration and Seepage Rates	18
		2.4.1 Seepage Rate versus Channel Cross Section	18
		2.4.2 Infiltration Rate versus Channel Cross Section	23
	2.5	Design of a Grassed Stormwater Channel Cross Section	25
	2.6	Modelling Flow with Infiltration in Permeable Channels	31
	2.7	Infiltration Models	33
		2.7.1 Kostiakov Model	34
		2.7.2 Horton Model	34
		2.7.3 Modified Kostiakov Model	35
		2.7.4 Philip Model	35
		2.7.5 SCS Model	35
	2.8	Measuring Flow and Infiltration in Permeable Channels	35
		2.8.1 Flow Rate Measurement Methods	36
		2.8.2 Measuring Infiltration Rate in permeable Channels	38
	2.9	Summary of the Literature Review	39

i

3	MATERIALS AND METHODS			41
	3.1	Introd	uction	41
	3.2	Phase	1 : Material and Methods for Experiments under Static	
		Condi	tions	44
		3.2.1	Experimental Setup	44
		3 2 2	Channel Material	47
		323	Experimental Method	48
		324	Rate of Seenage	49
		3.2.4	Evaluation of Existing Infiltration Models	50
	2 2	Dhasa	2 : Material and Matheda for Experiments under Dynamic	50
	5.5	Canali	2. Material and Methods for Experiments under Dynamic	50
				50
		3.3.1	Experimental Setup	51
		3.3.2	Channel Material	54
		3.3.3	Experimental Method	56
4	RESU	<b>JLTS A</b>	ND DISCUSSION	62
	4.1	Introd	uction	62
	4.2	Phase	1 : Results and Discussion for Experiments under Static	
		Condi	tion	62
		4.2.1	Effect of Boundary Conditions of Channel Models on	
			Infiltration Rate	63
		4.2.2	Seepage as a Function of Time	65
		4.2.3	Effect of Water Level on Seepage Rate	67
		4.2.4	Effect of Base Width on Seepage Rate	68
		4.2.5	Effect of Side Slope on Seepage Rate	69
		4.2.6	Modeling of Unsteady Seepage Rate	71
		427	Sections for Enhancing Seenage in Permeable Channels	75
		428	Effect of the Channel Section on the Infiltration Rate	79
		429	Evaluation of Existing Infiltration Models	81
		4.2.10	Modeling the Infiltration Pate for Permeable Stormwater	01
		7.2.10	Channels	87
		1 2 11	Comparison of the Infiltration Models	0/
	12	T.2.11	2 · Regults and Discussion for Experiments under	24
	4.5	Dumon	2. Results and Discussion for Experiments under	05
			The Variations of Flow Characteristics	95
		4.3.1	Variations of Flow Danths and Valasities under	95
		4.3.2	Variations of Flow Depins and velocities under	0.0
		4 2 2	Different Channel Conditions	98
		4.3.3	Variations of Infiltration Rates under Different Channel	100
		1.2.4	Conditions	102
		4.3.4	Effect of the Grass Cover on Infiltration Rate	108
		4.3.5	Effect of Check Dam Height on Infiltration Rate	109
		4.3.6	Effect of Subsurface Water on Infiltration Rate	110
	4.4	Model	ing the Infiltration Rate for Grassed Channels	112
	4.5	Sectio	ns for Enhancing Infiltration in Grassed Stormwater	
		Chann	els	119
	4.6	Exam	ble of Modeling Flow with Infiltration in a Permeable	
		Chann	el	129

5	SUM	IMARY, CONCLUSIONS AND RECOMMENDATIONS	138
	5.1	Summary	138
	5.2	Conclusions	139
	5.3	Contribution of the Study	141
	5.4	Recommendation for Future Studies	141

REFERENCES APPENDICES BIODATA OF STUDENT LIST OF PUBLICATIONS

C



## LIST OF TABLES

Table		Page
2.1	Retardance Class for Vegetative Covers	13
2.2	The Values of Constant <i>K</i> for Equation 2.23 as suggested by Wanielista and Yousef (1993)	27
2.3	Calculations of required channel length for complete infiltration of inflow using Equation 2.22 and Equation 2.23	29
3.1	Properties of the soil samples	47
3.2	Details of the laboratory experiments under static condition	48
3.3	Details of laboratory experiments under dynamic conditions	59
4.1	Values of constants $C_a$ and $C_b$ for different initial water levels, base widths, and side slopes	71
4.2	Standard error of constants estimate	73
4.3	Flow-area-based calculated initial water levels	75
4.4	Cumulative seepage volumes after 2 and 4 h	77
4.5	Dimensional details for design cases 4 and 6	78
4.6	Infiltration model parameters for sandy loam soil	81
4.7	Kostiakov's parameters for sandy loam soil based on observation	84
4.8	Initial and final constant infiltration rates	84
4.9	Infiltration model parameters for sandy loam soil using observed data	85
4.10	Standard error of constants estimate for Equation 4.5	87
4.11	Standard error of constants estimate for Equation (4.6)	89
4.12	Standard error of constants estimate for Equation 4.7	90
4.13	Standard error of constants estimate for Equation 4.8	92
4.14	Standard error of constants estimate for Equation 4.9	93
4.15	Details of flow velocities and water depths	99

4.16	The hydraulic residence time $HRT$ (min) with different cases	102
4.17	Standard error of constants estimate for Equation 4.12	113
4.18	Standard error of constants estimate for Equation 4.14	115
4.19	The equivalent water depths, top widths, flow areas, wetted perimeters, hydraulic radiuses, and velocities for different combinations of the side slope and base width	121
4.20	The total volume of inflow, outflow, standing water, and infiltration for the two cases	135



# LIST OF FIGURES

Figur	e	Page
1.1	Types of permeable channels used for stormwater management	2
1.2	The Four Groups of Sustainable Urban Drainage (Stahre, 2008)	3
2.1	Velocity distribution in a trapezoidal channel section (Akan, 2010)	10
2.2	Approximate normal depth chart for grassed channels	14
2.3	Variation of the seepage loss with the bed width for different side slopes "(Swamee et al., 2000), © ASCE"	20
2.4	Seepage from a trapezoidal channel underlain by a drainage layer (Chahar, 2007)	21
2.5	Canal seepage geometry for different boundary conditions	22
2.6	Water depth and ponding depth in channel and land surface respectively	24
2.7	Flow measurement methods in open channels	36
3.1	The summary of experimental work under static and dynamic conditions	43
3.2	Half-trapezoidal channel models with different base widths and side slopes	45
3.3	Comparison of the infiltration rates from the columns with and without atmospheric boundary conditions	46
3.4	Soil textures based on USDA Textural Triangle (USDA, 1971)	48
3.5	Plan view of the channel model inside the concrete flume	51
3.6	Channel model inside concrete flume	52
3.7	Channel downstream check dam	53
3.8	Inflow tank at the upstream of the channel	53
3.9	Outflow tank at the downstream of the channel	54
3.10	The channel with topsoil and grass	55

3.11	Comparison of the infiltration rates from the columns with and without atmospheric boundary conditions	56
3.12	Inflow pipe with electronic flow meter	57
3.13	The channel model at operation	57
3.14	The movable current meter	58
3.15	The gate after channel downstream to control water level in the concrete flume	61
4.1	Time variations of the infiltration rates from columns with natural soil with and without atmospheric boundary conditions	63
4.2	Time variations of the infiltration rates from columns with top-soil with and without atmospheric boundary conditions	64
4.3	The value of variations between infiltration rates over time	65
4.4	Variation of the seepage rate with time for sandy loam soil for different initial water levels $(y)$ , base widths $(b)$ , and side slopes $(m)$	66
4.5	Variation of the seepage rate with time for loamy sand soil for different initial water levels $(y)$ , base widths $(b)$ , and side slopes $(m)$	67
4.6	Seepage rates for sandy loam soil for base widths of 1, 0.5, and 0.2 m for different initial water levels $(y)$	68
4.7	Seepage rates for loamy sand soil for base widths of 1, 0.5, and 0.2 m for different initial water levels $(y)$	69
4.8	Seepage rates for sandy loam soil for side slopes of 2, 3, and 4 for different initial water levels $(y)$	70
4.9	Seepage rates for loamy sand soil for side slopes of 2, 3, and 4 for different initial water levels $(y)$	70
4.10	Variations of $C_1$ and $C_2$ with the initial water level, base width, and side slope	72
4.11	Comparison between the $q_s$ values obtained using Equation 4.3 and $q_s$ values from Equation 4.1 using observed $C_a$ and $C_b$ values for different initial water levels (y), base widths (b), and side slopes (m)	74
4.12	Unsteady seepage discharge rate and cumulative seepage volume per unit length (CSV) for different side slopes and base widths	76
4.13	Cumulative seepage volumes after 4 h for case 4 and case 6	77

4.14	Variation of the infiltration rate over time for different initial water depths $(y)$ , base widths $(b)$ , and side slopes $(m)$ for the fine sandy loam soil	80
4.15	Comparison of the observed infiltration rates with those obtained from the infiltration models using parameter values from the literature	83
4.16	Observed infiltration rates data and the power equation for it for $m = 2$ , $b = 0.2$ m, $y = 0.45$ m	84
4.17	Comparison of the observed infiltration rates with those obtained using the infiltration models with predictive parameter values	86
4.18	Comparison of the observed infiltration rates with those predicted using Equation 4.5	88
4.19	Comparison of the observed infiltration rates with those predicted using Equation 4.6	89
4.20	Comparison of the observed infiltration rates with those predicted using Equation 4.7	91
4.21	Comparison of the observed infiltration rates with those predicted using Equation 4.8	93
4.22	Comparison of the observed infiltration rates with the infiltration rates predicted using Equation 4.9	94
4.23	Relations between normal depth $y_n$ , critical depth $y_c$ , and Froude number $F_r$ with inflow rates used in experiments	96
4.24	Water surface profiles at the three flow stages	97
4.25	Typical flow hydrographs during the experiments	97
4.26	Comparison between the measured and calculated mean velocity	100
4.27	Relation between inflow rates and time to peak $t_p$ (min) for grassed channels with different check dam height $h_w$ of 10, 15 and 20 cm	100
4.28	Relation between inflow rates and time to downstream $t_d$ (min) for grassed channels with different check dam height $h_w$ of 10, 15 and 20 cm	101
4.29	Variations of water depth at peak flow with inflow rate for the grassed channel with different check dam heights $h_w$	101
4.30	Flow hydrographs and the variation of the infiltration rate over time for a bare channel with check dam height $h_w = 10$ cm for different inflow rates	103

4.31	Flow hydrographs and the variation of the infiltration rate over time for a grassed channel with check dam height $h_w = 10$ cm for different inflow rates	104
4.32	Flow hydrographs and the variation of the infiltration rate over time for a grassed channel with check dam height $h_w = 15$ cm for different inflow rates	105
4.33	Flow hydrographs and the variation of the infiltration rate over time for a grassed channel with check dam height $h_w = 20$ cm for different inflow rates	106
4.34	Flow hydrographs and the variation of the infiltration rate over time for a grassed channel with subsurface water and check dam height $h_w$ = 15 cm for different inflow rates	107
4.35	Variation of cumulative infiltration $F$ over time for different inflow rates for channel with and without grass cover	108
4.36	Cumulative infiltration F after 2 h for bare and grassed channels with check dam height $h_w$ of 10 cm for different inflow rates	109
4.37	Variation of cumulative infiltration $F$ over time for a grassed channel with check dam height $h_w$ of 10, 15 and 20 cm respectively for different inflow rates	109
4.38	Cumulative infiltration $F$ after 2 h for a grassed channel with check dam height $h_w$ of 10, 15 and 20 cm for different inflow rates	110
4.39	Variation of cumulative infiltration <i>F</i> over time for different inflow rates for channel with and without subsurface water	111
4.40	Cumulative infiltration $F$ after 2 h for a grassed channel with and without subsurface water, with check dam height $h_w$ of 15 for different inflow rates	111
4.41	Comparison of the variation of cumulative infiltration $F$ over time obtained using Equation 4.12 and the variation of $F$ over time obtained from observed infiltration rates	114
4.42	Comparison of the variation of cumulative infiltration $F$ over time obtained using Equation 4.14 and the variation of $F$ over time obtained from observed infiltration rates	116
4.43	Cumulative infiltration $F$ after 2 h for a grassed channel with check dam height $h_w$ of 10, 15 and 20 cm using infiltration rates values from observed and predictive data (Equation 4.12)	118

4.44	Cumulative infiltration $F$ after 2 h for a grassed channel with check dam height $h_w$ of 10, 15 and 20 cm using infiltration rates values from observed and predictive data (Equation 4.14)	118
4.45	Infiltration rates and cumulative infiltration for a channel with base width of $b = 0.5$ m with different side slopes	122
4.46	Infiltration rates and cumulative infiltration for a channel with base width of $b = 1$ m with different side slopes	122
4.47	Infiltration rates and cumulative infiltration for a channel with base width of $b = 1.5$ m with different side slopes	123
4.48	Infiltration rates and cumulative infiltration for a channel with base width of $b = 2$ m with different side slopes	123
4.49	Infiltration rates and cumulative infiltration for a channel with base width of $b = 2.5$ m with different side slopes	124
4.50	Infiltration rates and cumulative infiltration for a channel with base width of $b = 3$ m with different side slopes	124
4.51	Infiltration rates and cumulative infiltration for a channel with side slope $m = 2$ with different base widths	125
4.52	Infiltration rates and cumulative infiltration for a channel with side slope $m = 2.5$ with different base widths	126
4.53	Infiltration rates and cumulative infiltration for a channel with side slope $m = 3$ with different base widths	126
4.54	Infiltration rates and cumulative infiltration for a channel with side slope $m = 3.5$ with different base widths	127
4.55	Infiltration rates and cumulative infiltration for a channel with side slope $m = 4$ with different base widths	127
4.56	Variation of the final constant infiltration rate $f_c$ with the base width for different side slopes	128
4.57	Variation of cumulative infiltration $F$ after 2 h with the base width for different side slopes	129
4.58	Cross section and side view of the channel with check dams	130
4.59	Cross section and side view of the channel without check dams	130
4.60	Flow hydrograph and the variation of the infiltration rate over time for the channel with check dams at the 5 sections	133

4.61	Flow hydrograph and the variation of the infiltration rate over time for the channel without check dams at the 5 sections	133
4.62	Variations of water depth along sections over time for channel with check dams of 20-cm height	134
4.63	Variations of water depth along sections over time for channel without check dams	134
4.64	Variations of cumulative infiltration over time at the 5 sections for the channels with and without check dams	135
4.65	Percentage of infiltrated water volume after 90 min through the channel with check dams	136
4.66	Percentage of infiltrated water volume after 90 min through the channel without check dams	136
4.67	Percentage of infiltrated water volume through the channel with check dams with including the standing water	137

G

# LIST OF ABBREVIATIONS

α	Dimensionless parameter in Figure 2.2
α	Coefficient representing the rate of reduction in hydraulic conductivity $k$ or water content $\theta$ as the pressure head $\psi$ becomes more negative, (Equation (2.16))
A	Channel cross-sectional area (L <sup>2</sup> )
Ad	Drainage area (L <sup>2</sup> )
$A_{ m md}$	Cross-sectional area at mid-point of channel length (L <sup>2</sup> )
$A_1$ and $A_2$	Channel cross-sectional area at different sections (L <sup>2</sup> )
$\frac{\Delta A}{\Delta t}$	The decrease of the cross-sectional flow area with respect to time $(L^2/t)$ .
b	Channel base width (L)
С	Runoff coefficient, (Equation (2.19))
С	Constant = $1,300 (\sec^2/\text{ft}^2), (\text{Equation } (2.25))$
Ca	Constant rate of infiltration (L/t), for Equation (2.30)
$C_{\rm a}$ and $C_{\rm b}$	Constants for Equation (4.1)
C <sub>n</sub>	Dimensionless retardance factor depending on the type and the maturity of the grass as shown in Table 2.1
C <sub>1</sub> , C <sub>2</sub> C <sub>3</sub> , C <sub>4</sub> and C <sub>5</sub>	Constants for Equation (4.2)
C <sub>1</sub> , C <sub>2</sub> C <sub>3</sub> and C <sub>4</sub>	Constant of hydraulic parametes for Equations (4.11) and (4.13)
CSV	Cumulative seepage volume per unit length (L <sup>3</sup> )
$d_{ m q}$	Depth of flow at $Q_q(L)$
D	Hydraulic depth (L), $D = A/T$
f	Infiltration rate (L/t)
$f_0$	Initial infiltration capacity (L/t)

 $\bigcirc$ 

	fc	Final infiltration capacity (L/t)
	$f_{\rm p}$	Infiltration capacity (L/t)
	F	Cumulative infiltration (L/t)
	$F_{ m hp}$	Function of hydraulic parameters
	$F_r$	Frode number (dimensionless)
	$F_s$	Seepage function (dimensionless), for Equation (2.17)
	g	Gravitational acceleration (L/t <sup>2</sup> )
	$h_1$ and $h_2$	The heights above a reference level of water in a manometer terminated above and below the soil layer respectively, in Dracy's Law (Equation (2.14))
	$h_{ m w}$	Downstream check dam heights (L)
	HRT	Hydraulic residence time (t)
	Ι	Rainfall intensity (L/t)
	k	Constant representing the rate of decrease in $f_p$ (Equation (2.28))
	k	Soil permeability
	<i>k</i> <sub>u</sub>	Unsaturated hydraulic conductivity
	$k_s$	Saturated hydraulic conductivity
	K	Function of the side slope $m$ , which decreases with increasing side slope (Table 2.2).
	$K_{\rm k}$ , and $\alpha$	Empirical constants (non-dimensional) for Kostiakov, modified Kostiakov and SCS models (Equations (2.27), (2.29)and (2.31))
	Kv	Unit conversion factor For Equation (2.12), $K_v = 3.28 \text{ m}^{-1}=1.0 \text{ ft}^{-1}$
	$L_{\rm d}$	Thickness of the soil in Dracy's Law (Equation (2.14))
	L	Length of the channel (L)
	т	Channel side slope (H:V)
	п	Manning's roughness coefficient
	Р	Channel wetted perimeter (L)

	$\overline{P}$	The average wetted parameter (L), $\overline{P} = (P_1 + P_2) / 2$
	$P_1$ and $P_2$	The wetted parameter $P$ values at the beginning and end of a time interval respectively
	q	Darcy's water flow which is the volume of water crossing a unite area in unit time
	$q_{ m L}$	Lateral inflow or outflow
	$q_{ m s}$	Seepage discharge per unit length of a channel $(L^2/t.L)$
	Q	Flow rate (discharge)
	$Q_{ m f}$	Peak infiltration flow rate $(L^3/t)$
	$Q_{ m in}$	Inflow rate directed to a channel $(L^3/t)$
	$Q_{\mathrm{out}}$	Outflow rate from a channel $(L^3/t)$
	$Q_{ m p}$	Peak runoff rate (L <sup>3</sup> /t)
	$Q_{q}$	Discharge at water quality flow (L <sup>3</sup> /t)
	R	Hydraulic radius (L) = A/P
	$R^2$	Coefficient of determination
	S	Sorptivity of the soil (Lt <sup>-1/2</sup> )
	$S_0$	Longitudinal channel bottom slope (L/L).
	$\frac{\Delta S}{\Delta t}$	Change in channel storage over the time intervals $(L^3/t)$ .
	SCS	Soil Conservation Service infiltration model
	t	Time
	tp	Time to peak flow
	t <sub>d</sub>	Time to downstream
	Т	Channel top width (L)
	V	Mean velocity (L/t)
	V	Cross-sectional average velocity (L/t)
	$V_{\rm m}$	Volume of water

$V_{q}$	velocity at $Q_q$ (L/t)
$V_1$ and $V_2$	Mean velocity at different channel sections (L/t)
x	Displacement in the main flow direction (L)
У	Water depth (L)
$y_c$	Critical flow depth (L)
Уn	Normal flow depth (L)
Ур	Flow depth at peak flow (L)
Z	Elevation head (L)
θ	Soil volumetric water content
$\theta_r$	Residual volumetric water content
$\theta_s$	Saturated volumetric water content
ρ	Water density
ψ	Pore-water pressure head

C

### **CHAPTER 1**

#### **INTRODUCTION**

### 1.1 Background

Modern urban development typically creates impervious areas, which reduce the infiltration of rainwater and increase the volume of runoff. When combined with urbanization, climate change influences the hydrologic variables in urban areas, thereby increasing the frequency and magnitude of urban flooding, and negatively impacting both humans and the environment (Zhou, 2014).

The philosophy of urban stormwater management has therefore shifted away from narrow traditional approaches, i.e., 'rapid discharge' or 'collecting and conveying stormwater away from urban areas as quickly as possible', to new sustainable approaches that leverage more natural methods (Villarreal, 2005). For example, source control uses storage and infiltration methods that allow rainfall events to be conveyed and infiltrated along the surface rather than in underground pipes (Miguez et al., 2012). Reducing the volume of runoff by infiltration through permeable surfaces at the source lessens the effort needed to control the remaining runoff at the downstream basin (Ferguson, 1994). Moreover, sustainable approaches consider other important aspects in urban water management, such as reducing the volume of runoff, water quality, recreational value, protection of the environment, and multiple water uses (Zhou, 2014).

Perceiving these environmental and economic benefits therefore have resulted in the growing interest in infiltration to be a sustainable alternative approach or at least with conjunction with the conventional drainage practices. Several different terms are used to describe these new approaches in different parts of the world, albeit with minor differences in concept and practice. Some well-known terms include low impact development (LID), sustainable urban drainage systems (SUDS), water sensitive urban design (WSUD), and best management practices (BMPs). Numerous studies of the differences and applications of these approaches have been conducted (e.g., Fletcher et al., 2014; Zhou, 2014; Miguez et al., 2012; Shutes and Raggatt, 2010).

Permeable channels are commonly used for sustainable urban drainage and management of stormwater quantity. The term "Permeable channels" may refer to unlined earthen channels, or channels with flexible lining which may consist of grass, rip-rap, or gabions (DSD, 2013), as shown in Figure 1.1. Lining should be provided to channel bottom and side slopes when flow velocity exceeds 1 to 2 m/s (Chow, 1959), and hence unlined earthen channels are not preferred for stormwater practices because of the concern of soil erosion at high flow velocity.

The use of grass, where practical, is the most preferred lining type for stormwater channels, because of the low cost of grass lining that is much less than other lining types, in addition to grass ability to stabilize the channel bed and sides, prevent soil erosion, consolidate the soil mass, and provide water quality benefits (CCSMDM, 2014). However, some conditions may prevent the use of grass lining such as the high flow velocities, standing water or continuous flowing, excessive shade, lack of maintenance and inadequate topsoil (CCSMDM, 2014).



a) Rip-Rap channel

b) Gabions channel



c) Grassed channel



Permeable stormwater channels can be categorized under the slow transport group of sustainable urban drainage (Figure 1.2) as they link several on-site control systems, delay rapid runoff, and reduce the volume of runoff by their infiltration function (Stahre, 2008). Permeable channels are also used to enhance the quality of stormwater through infiltration, sedimentation, and filtration (Boogaard et al., 2014).

Infiltration capacity of permeable channels may be influenced by many factors that may make the infiltration rate through permeable channel differ from other infiltration devices. Therefore, the ability to accurately quantify infiltration rates is very important in the design of permeable stormwater channels, because it enables the capability of the channels to be assessed to determine if they can perform the required functions.



Figure 1.2 : The Four Groups of Sustainable Urban Drainage (Stahre, 2008)

### 1.2 Problem Statement

The use of permeable stormwater channels introduces the concern about the effects of infiltration on the hydraulics behavior of flow in such channels, as well as the effect of hydraulics parameters such as water level, base width, side slope, velocity, and vegetation, on infiltration rate. However, design methods in most cases, are simplified and based on experience and empirical design criteria gained from existing stormwater channels (Grinden, 2014).

Manning's equation is usually used in the design of a channel cross section at a required discharge, and then the design is usually checked either versus the maximum allowable velocity for erosion protection and for water quality (e.g. DID, 2012; DPLG, 2010) or versus the minimum allowable hydraulic residence time for water quality design (e.g. Caltrans, 2012; WEF, 2012). However, even when the infiltration rate is taken into consideration, the variation of infiltration rate with several factors such as



the water depth, flow velocity and channel cross section as well as the variation of infiltration capacity with time are usually ignored (e.g. St. Johns River, 2010; Wanielista and Yousef, 1993).

Disregarding the infiltration effect on flow in design procedures of permeable stormwater channels often results in overdesign them for a given flow rate and channels become bigger than required (Grinden, 2014).

Thus, it is essential to investigate the factors affecting the infiltration process through the beds and sides of permeable channels and then to relate the infiltration rate with the channel flow to improve the design of permeable stormwater channels as an infiltration device.

### 1.3 Research Objectives

The study aims to investigate factors affecting infiltration process and flow reduction in permeable open channels under static and dynamic hydraulic conditions, and subsequently to develop empirical models for the variations of infiltration capacity with flow hydraulic parameters, in order to improve the design of permeable stormwater channels.

The specific objectives of the study are:

- 1. To examine the effect of the channel cross section on seepage and infiltration rates in permeable channels under static condition.
- 2. To evaluate the performance of five existing infiltration models for estimating the infiltration rate in permeable open channels under static condition.
- 3. To examine the effect of flow hydraulic parameters on infiltration capacity of permeable stormwater channels under dynamic condition.
- 4. To develop empirical models for predicting the infiltration capacity for permeable stormwater channels with considering various channel flow characteristics.

#### **1.4** Significance of the Study

This study provides more insight on the effect of the hydraulic parameters on the flow with infiltration in permeable channels. To improve the efficiency of a permeable stormwater channel, the channel section that, within the design criteria, maximizes infiltration and seepage through the channel bed and side slope should be chosen. A good understanding of how infiltration rates are affected by flow hydraulic conditions helps to choose the optimal channel cross section and height of check dams that allow the maximum possible infiltration rate. Although some studies show how the infiltration rate is affected by the ponding depth of the water and surface slope, they were limited to overland flow and the effect of the channel cross section on the infiltration rate has largely been ignored. While the ponding depth and slope may not be significant infiltration factors in some hydrologic models, the water level and side slope in a channel may prove important when seeking to maximize the infiltration rate in a particular channel with a given flow rate. Modeling the variations of infiltration rate with flow hydraulic parameters in permeable channels promises best stormwater management and provide a valuable decision support tool in designing permeable channels. Moreover, the application of the findings of this study to the design of a stormwater channel promises to reduce the length of the channel and occupied land, thereby decrease the construction and maintenance costs.

### **1.5** Scope and Limitations

The scope of this research is to investigate experimentally the effects of flow hydraulics parameters, which are water level, base width, side slope, and velocity on infiltration rate in a permeable channel and their effectiveness in flow reduction.

For better understanding the characteristics of flow with infiltration in permeable open channels, flow hydraulics parameters were studied using different sets of hydraulic and soil conditions, and the study involved the determination of infiltration rate through permeable channels in two flow conditions, namely, static and dynamic, and hence different physical channel models were developed in the laboratory for each condition.

Under the static condition, the ponding method was used for the infiltration and seepage tests under unsaturated soil conditions. Physical channel models were used to investigate the effects of the channel section on the infiltration and seepage rates in a permeable channel, and determine the section that maximizes water reduction by infiltration and seepage under the unsaturated soil condition. The experimental tests includes four initial water depths (y = 0.15, 0.25, 0.35, and 0.45 m), three base widths (b = 1, 0.5, and 0.2 m), and three side slopes (m = 2, 3, and 4). The physical channel models were also used to evaluate the performance of five infiltration models, namely, the Kostiakov, Horton, Modified Kostiakov, Philip, and Soil Conservation Service (SCS), for estimating the infiltration rate in permeable stormwater channels versus the measured values.

Under the dynamic condition, the mass-balance method was used for infiltration rate estimation, and the experimental tests includes five inflow rates ( $Q_{in} = 0.0055, 0.0075, 0.0095, 0.0115, 0.0135 \text{ m}^3/\text{s}$ ), with three downstream check dam heights ( $h_w = 10, 15, and 20 \text{ cm}$ ). In addition, two other sets of experiments were conducted to investigate the effects of grass cover and subsurface water on infiltration rate. The results were used to quantify and compare the different cases in terms of the infiltration rate and cumulative infiltration for better surface water reduction. All comparisons focused on

the hydraulic considerations of channel design rather than economic analysis of different alternatives.

There are many factors that may influence the infiltration capacity of permeable channels, however, it is difficult to consider all these factors. In this study, the flow hydraulics parameters which are the water level, channel section, and flow velocity were taken into account in the investigation, while the other factors were considered as fixed parameters.

Soil used to form the permeable layer in the test channels was natural soil collected from the farm of the Universiti Putra Malaysia, which was homogeneous and isotropic, and represented only one type of soil. Hence, the analysis and development of predictive equations throughout this study are applicable for this type of soil, and further investigations should be conducted to confirm their suitability for other types. Moreover, only one texture of top-soil and one type of grass, which known as Cow grass, were used for the channel under the dynamic phase of the study.

The rate of seepage through the natural unsaturated soil is significantly influenced by the infiltration rate from the surface to the top soil when water stands, that is the water is not flowing in a channel. Therefore, seepage was studied under the static condition only, while it was considered insignificant and thus ignored under the dynamic condition.

The model scales were limited according to the space available for the permeable channel fabrication in the hydraulic laboratory at the Faculty of Engineering, Universiti Putra Malaysia. Experiments were limited to the laboratory temperature, and the filed capacity of soil saturation.

Channel model for dynamic condition was placed inside an existed concrete flume which has a length of 16 m after the flow inlet, width of 1.5 m and height of 1.2 m. The reason of placing the model inside the concrete flume was to use its facilities such as pumping and draining water, measuring inflow and outflow, supporting water level measurement tools, and placing the movable current meter.

The study considered only one longitudinal slope of a channel, and did not cover the effect of longitudinal slope variations on infiltration capacity of channels. Moreover, initial water level of flow was reached very fast comparing to the case of rainfall on permeable stormwater channels, and water for dynamic condition was re-circulated during the experiment by collecting both conveyed and infiltrated water at the end of channel and pumping it to the overhead tank and re-circulating again.

The analysis throughout the study was based on statistical approach using IBM SPSS Statistics software (version 21). Moreover, SPSS software was used for developing predictive equations and fitting their parameters because of that the mathematical basis of all available software does not consider the variations of infiltration rate with the hydraulic parameters in stormwater channels. While numerical analysis is highly relevant in this work, it was not used due to time limitation.

### 1.6 Thesis Layout

This thesis is composed of five chapters. Chapter One presents an overview of the use of permeable channels for sustainable stormwater management and their functions, the problems accompanying such channels, and the objectives of the study, together with the significance, scope and limitations of the current research.

Relevant literature is reviewed in Chapter Two. This Chapter reviews the characteristics of flow in open channels and the variables governing the flow in permeable stormwater channels. The Chapter also reviews extensively the previous studies on the effect of channel cross section on seepage and infiltration rates in different conditions and practices. Moreover, this Chapter reviews the design procedures of permeable stormwater channels, the methods for estimating infiltration rate through permeable channels, and summarises the formulas of five infiltration models, namely, the Kostiakov, Horton, Modified Kostiakov, Philip, and Soil Conservation Service (SCS). Finally, a summary of the literature review and the research gaps related to flow with infiltration in a permeable channel is presented in this chapter.

Experimental setup, channel material, experimental method, and data collection for the two hydraulic conditions, namely, static and dynamic conditions, are described in the third Chapter. Moreover, Chapter Three also comprises a description of the two separate laboratory pre-tests that conducted to examine how the placement of soil on an open to the atmosphere boundary condition may affect the infiltration and seepage rates, and how the results would differ if the experiments were performed in a native channel.

Chapter Four presents the results of the experiments from the two phases. Discussion in Chapter Four was based on the comparisons among different cases and their effect on the flow with infiltration in permeable channels under static and dynamic hydraulic conditions using graphs, tables and empirical equations. An example of modelling flow with infiltration with two cases in a grassed channel was detailed at the end of Chapter Four.

Finally, Chapter Five presents a summary and conclusions of the study, as well as suggestions for some future studies.

#### REFERENCES

- Ab.Ghani, A., Zakaria, N.A., Chang, C.K., Ainan. A., (2008), "Sustainable Urban Drainage System (SUDS) – Malaysian Experiences.", 11th International Conference on Urban Drainage, Edinburgh, Scotland, UK, 1-10.
- Abood, M.M., Yusuf, B., Mohammed, T.A., Ghazali, A.H., 2006. "Manning Roughness Coefficient for Grass-Lined Channel," *Suranaree J. Sci. Technol.*, Vol. 13(4), pp. 317-330
- Adarsh, S., (2012). "Design of minimum seepage loss irrigation canal sections using probabilistic search." *Int. J. Optim. Civ. Eng.*, 2(1),15–28.
- AgriLife (Agriculture and Life Extension, Texas A&M University), (2017), "Measuring Seepage Losses from Canals Using the Ponding Test Method" Texas A&M University, B-6218, 1-19.
- Ahmed, N.A, Ab.Ghani, A., Zakaria, N.A., Azamathullah, H.M., (2011), "Hydraulic characteristic for flow in swales.", 3rd International Conference on Managing Rivers in the 21st Century: Sustainable solutions for Global Crisis of Flooding, Pollution and Water Scarcity, 6-9 Dec, 2011, Penang, Malaysia.
- Akan A. O. (2010), Open Channel Hydraulics, Elsevirer Ltd., UK.
- Akan, A. O. and Hager, W. W. (2001). "Design aid for grass-lined channels." J. *Hydraul. Eng.*, ASCE, 127(3), 236–237.
- Ala-aho, P., Soulsby, C., Wang, H., Tetzlaff, D., (2017), "Integrated surfacesubsurface model to investigate the role of groundwater in headwater catchment runoff generation: A minimalist approach to parameterisation.", J. Hydrolo., 547, 664-677.
- Al-Azawi, S.A. (1985). "Experimental evaluation of infiltration models." J. Hydrol., 24(2), 77–88.
- Araghi, F.P., Mirlatifi, S.M., Ghorbani D.S., Mahdian M.H., (2010), "Evaluation some infiltration models under different soil texture classes and land uses.", *Iran J. Irrig. Drain.*, 2, 193-205.
- Argyrokastritis, I., and Kerkides, P. (2003). "A note to the variable sorptivity infiltration equation." *Water Resour. Manage.*, 17, 133–145.
- Bell, F.G., (2016), *Fundamentals of Engineering Geology*, revised edition, Elsevier, UK.
- Boogaard, F.C., Lucke T., Sommer H., Beer J., Giesen N.C., and Ven F.H.M. (2014). "Lessons learned from over two decades of global swale use." *13th Int. Conf. on Urban Drainage*, Sarawak, Malaysia.

- Bouwer H., (1982). "Design Considerations for Earth Linings for Seepage Control." Ground Water, 20: 531–537. doi:10.1111/j.1745-6584.1982.tb01366.x
- Brady, N.C., and Weil, R.R. (1999). *The Nature and Properties of Soils*, Prentice Hall, Inc., Upper Saddle River, NJ.
- Caltrans (California Department of Transportation), (2012), Caltrans Storm Water Quality Handbook: Biofiltration Swale, Design Guidance, California, USA
- Carleton, G.B., (2010). "Simulation of groundwater mounding beneath hypothetical stormwater infiltration basins.", U.S. Geological Survey Scientific Investigations Report 2010-5102, p. 64.
- CCSMDM (Columbia County Stormwater Management Design Manual), (2014), *Open Channel Design*, Columbia County, Georgia, USA.
- Chahar, B.R., (2007). "Analysis of Seepage from Polygon Channels." J. Hydr. Eng., ASCE, 133(4), 451–460.
- Chahar, B.R., Graillot, D., and Gaur, S., (2012). "Storm-water management through infiltration trenches." *J. Irrig. Drain. Eng.*, ASCE, 138 (3), 274–281.
- Chahinian, N., Moussa, R., Voltz, M., Andrieux, P. (2005). "Models to simulate flood events at the field scale." *J. Hydrol.*, 306, 191–214.
- Chen, L., and Young, M. (2006). "Green-Ampt infiltration model for sloping surfaces.", *Water Resour. Res.*, 42, W07420, 1–9 doi:10.1029/2005WR004468.
- Chen, Y. H., and Cotton, G. K., (1988) "Design of Roadside Channels with Flexible Linings." *Hydraulic Engineering Circular* No. 15, Publication No. FHWA-IP-87-7, US Department of Transportation, Federal Highway Administration, McLean, VA.
- Chou, V.T. (1964). Handbook of Applied Hydrology: A Compendium of Water Reservoir Technology, McGraw Hill Book Company, New York.
- Chow, V.T., (1959). *Open Channel Hydraulics*, McGraw-Hill Book Company, New York.
- Chow, V.T., Maidment, D.R., and Mays, L.W., (1988). *Applied Hydrology*. McGraw-Hill, New York.
- Clemmens, A. J., and Bautista, E. (2009). 'Toward physically based estimation of surface irrigation infiltration.' *J. Irrig. Drain. Eng.*, 135(5), 588-596.
- Clemmens, A.J. (1983). "Infiltration equations for border irrigation models." P266-274. In: Advances in infiltration. *Proc. Nat. Conf. on Advances in Infiltration*. Dec. 12–13, 1983. Chicago, Ill. ASAE Pub. 11–83. St. Joseph, Mo.

- CWP (Center for Watershed Protection). 1996. *Design of Stormwater Filtering Systems.* Prepared for the Chesapeake Research Consortium, Solomons, MD, and USEPA Region V, Chicago, IL, by the Center for Watershed Protection, Ellicott City, MD.
- De Ploey, J., Savat, J., and Moeyersons, J., (1976), "The differential impact of some soil loss factors on flow, runoff creep and rainwash", *Earth Surf. Processes Landforms*, 1, 151-161.
- Deng, B., Wang, J., (2017), "Saturated-unsaturated groundwater modeling using 3D Richards equation with a coordinate transform of nonorthogonal grids." Applied Mathematical Modelling, 50, 39-52.
- DEP (The Derwent Estuary Program), (2012), Water Sensitive Urban Design Procedures for Stormwater Management in Tasmania, Chap. 7 Swales and buffers. Tasmania, Australia.
- DID (Department of Irrigation and Drainage). (2012). Urban Stormwater Management Manual for Malaysia, 2nd Ed., Kuala Lumpur, Malaysia.
- Djorovic, M., (1980), *Slope effect on runoff and erosion*, in Assessment of Erosion, edited by M. De Boodt and D. Gabriels, pp. 215-225, John Wiley, Hoboken, N. J.
- DPLG (Department of Planning and Local Government), (2010), *Water Sensitive* Urban Design Technical Manual for the Greater Adelaide Region, Government of South Australia, Adelaide.
- DSD (Drainage Services Department), (2013), *Stormwater Drainage manual*, 4<sup>th</sup> Edition, Government of the Hong Kong.
- Elhanafy, H., and Copeland, G. (2007). "The effect of water stage on the infiltration rate for initially dry channels." Strathclyde University, UK.
- Everett, S.R., and Dutt, G.R. (1985). "Length and slope effects on runoff from sodium dispersed, compacted earth microcatchments." *Soil Sci. Soc. Am. J.*, 49, 734–738.

Ferguson, B. K. (1994). Stormwater Infiltration, LEWIS Publishers, CRC press, Inc.

- Fletcher, J.E. (1949). "Some properties of water solutions that influence infiltration." *Trans. Am. Geophys. Union*, 30, 548–554.
- Fletcher, T., Shuster, W., Hunt, W., Ashley, R., Butler, D., Arthur, S., Trowsdale, S., Barraud, S., Davies, A.S., Krajewski, J.L., Mikkelsen, P.S., Rivard, G., Uhl, M., Dagenais D., and Viklander, M. (2014). "SUDS, LID, BMPs, WSUD and more The evolution and application of terminology surrounding urban drainage." *Urban Water J.*, 1–18.

- Fox, D. M., Bryan, R.B., and Price, A.G., (1997), "The influence od slope angle on final infiltration rate for interrill conditions", *Geoderma*, 80, 181-194.
- Ghazaw, Y., (2011). "Design and analysis of a canal section for minimum water loss." *Alexandria Eng. J.*, 50(4), 337–344.
- Govers, G., (1991), "A field study on topographical and topsoil effects on runoff generation", *Catena*, 18, 91-111.
- Goya N. (2012), Stormwater Source Control Design Guidelines, Fanal report, Vancouver, Canada.
- Green, H.W., and Ampt, G.A. (1911). "Studies on Soil Physics." J. Agr. Sci., 4(1), 1–24.
- Grinden A., (2014), "Numerical Modeling of Combined Hydraulics and Infiltration in Grassed Swales.", M.Sc. thesis, Norwegian University of Science and Technology, Norway.
- Grosh, J. L., and Jarrett, A. R., (1994), "Interrill erosion and runoff on very steep slope", *Trans.* ASAE, 37(4), 1127-113.
- Haggard, B.E., Moore Jr., P.A., and Brye., K.R. (2005)." Effect of Slope on Runoff from a Small Variable-Slope Box." *JEH*, 13, paper 25.
- Harvey E. J. and David C. F., (1988), *Basic Hydraulic Principles Of Open-Channel Flow*, U.S. Geological Survey, report 88-707.
- Henderson, F. M., (1966), "Open Channel Flow," MacMillan Company, New York, USA.
- Hillel, D. (1998). Environmental Soil Physics. Academic Press, San Diego, CA.
- Holtan, H.N. (1961). "A concept for infiltration estimates in watershed engineering." USDA, Agricultural Research Service Publication 41–51.
- Horton, R. E. (1933). "The role of infiltration in the hydrologic cycle". *Trans. Am. Geophys. Union.* 14th Ann. Mtg: 446–460.
- Horton, R.E. (1940). "An approach towards a physical interpretation of infiltration capacity." *Soil Sci. Soci. of America*, 5, 399–417.
- Hoyos, E.M., and Cavalcante, A.L. (2015). "Sensitivity analysis of one-dimensional infiltration models." *EJGE*, 20 (10), 4313–4324.
- Hsu, S.M., MASCE, P.E., Ni, C.F., and Hung, P.F. (2002), "Assessment of three infiltration formulas based on model fitting on Richards equation." *J. Hydrol. Eng.*, 7(5), 373–379.

- Huat, B.B., Ali, F.H., and Low, T.H. (2006). "Water infiltration characteristics of unsaturated soil slope and its effect on suction and stability." *Geotech. Geol. Eng.*, 24, 1293–1306.
- Igbadun, H.E., Othman, M.K. and Ajayi, A.S. (2016). "Performance of selected water infiltration models in sandy clay loam soil in Samaru Zaria." *GJRE*, 16(4), 8–14.
- Israelsen, O.W., West, F.L., (1922), "Bulletin No. 183-Water holding capacity of irrigated soils", UAES Bulletin Paper 149, Utah Agricultural Experiment Station, Logan, UT.
- James A., Hatfield K., and Graham W. (2000) *Review of Integrated Surface Water/Ground Water Computer Models*, University of Florida, US.
- Keller-Bliesner Engineering, (1992). "Critique of the Conservation Program's Lateral Canal Lining Verification Plans and Procedures." Imperial Irrigation District, South Logan, USA.
- Kostiakov, A.V., (1932). "On the dynamics of the coefficient of water percolation in soils and on the necessity for studying it from a dynamics point of view for purposes of amelioration." In: Fauser, O., editor, Transactions of the Sixth Commission of International Society of Soil Science, Part A. Leiden: Martinius Nijhoff Publishers; p. 15–21.
- Kresic, N., (2006). *Hydrogeology and Groundwater Modeling*, 2nd Ed., CRC Press, USA.
- Lai, R., (1976), "Soil erosion of Alfisols in western Nigeria: Effects of slope, crop rotation and residue management.", *Geoderma*, 16, 363-375.
- Lewis, M.R., and Powers, W.L., (1938). "A study of factors affecting infiltration." *Soil Sci. Soc. Am. Proc.*, 3, 334–339.
- Liu, H., Lei, T.W., Zhao, J., Yuan, CP., Fan, YT., Qu, LQ., (2011), "Effects of rainfall intensity and antecedent soil water content on soil infiltrability under rainfall conditions using the run off-on-out method." J. Hydrol., 396 (1–2), 24–32.
- Mays L. W., 2011, Water Resources Engineering, 2nd Ed., John Wiley & Sons, Inc.
- Mbagwu, J.S., (1993). "Testing the goodness of fit of selected infiltration models on soils with different land use histories." *International Centre for Theoretical Physics*. Trieste, Italy.
- McCuen, R.H. (2005). *Hydrologic Analysis and Design*, 3rd Ed. Pearson Prentice Hall, USA.
- Mein, R.G., and Larson, C.L. (1973). "Modeling infiltration during a steady rain." *Water Resour. Res.*, 9, 384–395.

- Mezencev, V.J. (1948). "Theory of formation of the surface runoff." *Meteorologiae Hidrologia* 3, 33–40.
- Miguez, M.G., Veról, A.P., and Carneiro, P.R. (2012). Sustainable Drainage Systems: An Integrated Approach, Combining Hydraulic Engineering Design, Urban Land Control and River Revitalization Aspects, Drainage Systems, Prof. Muhammad Salik Javaid (Ed.), ISBN: 978-953-51-0243-4, InTech.
- Mirzaee, S., Zolfaghari, A.A., Gorji, M., Dyck, M., Dashtaki, S.G. (2013). "Evaluation of infiltration models with different numbers of fitting parameters in different soil texture classes." *Arch. Agron. Soil Sci.*, DOI: 10.1080/03650340.2013.823477.
- Mishra, S.K., Chaudhary, A., Shrestha, R.K., Pandey A., and Lal, M. (2014). "Experimental Verification of the Effect of Slope and Land Use on SCS Runoff Curve Number." *Water Resour. Manage.* 28, 3407–3416.
- Mishra, S.K., Tyagi, J.V., and Singh, V.P. (2003). "Comparison of Infiltration Models." *Hydrol. Process.* 17, 2629–2652.
- Morita, M., and Yen, B., (2002) "Modeling of conjunctive two-dimensional surfacethree-dimensional subsurface flows." J. Hydraul. Eng. 128(2):184–200.
- MSDEPQ (Ministry of Sustainable Development, Environment and Parks of Quebec), (2007), Sampling Guide for Environmental Analysis: Booklet 7 – Flow Measurement Methods in Open Channels, Center of Expertise in Environmental Analysis of Quebec, p 223.
- Mustafa, N., Ahmed, N. A., and Razi, M. A., (2015), "Variations of Roughness Coefficients with Flow Depth of Grassed Swale.", *Soft Soil Engineering International Conference 2015 (SEIC2015)*, IOP Conf. Series: Materials Science and Engineering 136 (2016) 012082 doi:10.1088/1757-899X/136/1/012082
- Mustaffa, N., Ahmad, N.A., Razi M.A., (2017), "Evaluation on Flow Discharge of Grassed Swale in Lowland Area.", MATEC Web of Conferences 103, 04017, DOI: 10.1051/matecconf/20171030
- Pal, D., Galelli, S., Tang, H., and Ran, Q., (2018), "Toward improved design of check dam systems: a case study in the Loess Plateau, China." J. Hydrolo., 559, 762-773
- Paramananthan, S., and Zauyah, S. (1986). "Soil landscapes in Peninsular Malaysia." *Geol. Soc. Malaysia*, Bulletin 19, pp. 565–583.
- Parr, J.F., and Bertrand, A.R. (1960). "Water infiltration into soils." *Adv. Agron.*, 12, 311–358.

- Philip, J.R. (1957a). "The theory of infiltration. 1. The infiltration equation and its solution." *Soil Sci.*, 83, 345–357.
- Philip, J.R. (1957b). "The theory of infiltration: 4. Sorptivity and algebraic infiltration equations." *Soil Sci.*, 84, 257–264.
- Philip, J.R. (1958). "The theory of infiltration. 6. Effect of water depth over soil." *Soil Sci.*, 85, 278–286.
- Poesen, J., (1984), The influence of slope angle on infiltration rate and Hortonian overland flow volume, Z. Geomorphol., 49, 117-131.
- Rawls, W.J., Ahuja, L.R., Brakensiek, D.L., and Shirmohammadi, A., (1993), *Infiltration and soil water movement*, Handbook of hydrology, McGraw Hill, Inc. NY, p. 5.1-5.51.
- Rawls, W.J., Brakensiek, D.L., and Miller, N. (1983). "Green-Ampt infiltration parameters from soils data." *J. Hydraul. Eng.*, 109(1), 62-70.
- Richards, L.A. (1931). "Capillary conduction of liquids through porous medium." *Physics*, 1(5), 318–333.
- Ruggenthaler, R., Meißl, G., Geitner, C., Leitinger, G., Endstrasser, N., and Schöberl, F., (2016), "Investigating the impact of initial soil moisture conditions on total infiltration by using an adapted double-ring infiltrometer." *Hydrol. Sci. J.*, 61:7, 1263-1279.
- Saha, B., (2015). "A critical study of water loss in canals and its reduction measures." Int. J. Eng. Res. Appl. 5 (3) (Part 4), 53–56.
- Sarki, A., Memon, S.Q., and leghari, M., (2008). "Comparison of different methods for computing seepage losses in an earthen watercourse.", *Agric. Trop. Subtrop.* 41(4), 197–205.
- Saxton, K.E. and Rawls, W.J., (2006), "Soil Water Characteristics Estimates by Texture and Organic Matter for Hydrologic Solutions." *Soil Sci. Soci. Am. J.*, 70, 1569-1578.
- Schmid, B.H. (1989). "On overland flow modeling: Can rainfall excess be treated as independent of flow depth?" *J. Hydrol.*, 107, 1–8.
- Shamsuddin, J., and Darus, A. (1979). "Mineralogy and genesis of soils in Universiti Pertanian Malaysia, Serdang, Selangor." *Pertanika*, 2(2), 141–148.
- Sharma, K., Pareek, O., and Singh, H., (1986), "Microcatchment water harvesting for raising Jujube orchards in an arid climate.", *Trans.* ASEA, 29(1), 112-118.
- Shuster, W.D., and Pappas, E., (2011), "Laboratory Simulation of Urban Runoff and Estimation of Runoff Hydrographs with Experimental Curve Numbers Implemented in USEPA SWMM.", J. Irrig. Drain. Eng., 137(6), 343-351.

- Shutes, B., and Raggatt, L. (2010). "Development of generic Best Management Practice (BMP) Principles for the management of stormwater as part of an integrated urban water resource management strategy." Urban Pollution Res. Centre, Dept. of Natural Sciences, Middlesex Univ., UK.
- Singh, V.P., and Yu, F.X. (1990). "Derivation of infiltration equation using systems approach." J. Irrig. Drain. Eng., 116(6), 837–857.
- Smith, R. E., and Woolhiser, D. A. (1971), "Mathematical simulation of infiltrating watersheds." *Hydrology*, 47, Colorado State Univ., Fort Collins, Colo.
- Smith, R.E. (1972). "The infiltration envelope: results from a theoretical infiltrometer." J. Hydrol., 17, 1–21.
- Sparks T. (2008), *Integrated Surface Water Groundwater Modeling*, A PhD thesis submitted to Cardiff university, UK.
- Srivastava R, Yeh TCJ. (1991), Analytical solutions for one-dimension, transient infiltration toward the water table inhomogeneous and layered soils. *Water Resources Research*. 27(5):753–762.
- St. Johns River, (2010). Regulation of Stormwater Management System. St. Johns River Water Management District, Palatka, Florida, USA.
- Stahre, P. (2008). *Blue-Green Fingerprints in the city of Malmo, Sweden*, VA SYD, Sweden.
- Swamee, P.K., Mishra, G.C., Chahar, B.R., (2000). "Design of minimum seepage loss canal sections." J. Irrig. Drain. Eng., ASCE, 126 (1), 28–32.
- Temple, D. M., Robinson K. M., Ahring, R. M., and Davis, A. G. (1987). Stability Design of Grass- lined Open Channels. Agricultural Handbook, 667. USDA: Washington, D.C.
- Turner, E.R. (2006). Comparison of infiltration equations and their field validation with rainfall simulation. M.S. thesis, Univ. of Maryland, USA.
- Uchdadiya, K.D., Patel, J.N., (2014). "Seepage losses through unlined and lined canals." Int. J. Adv. Appl. Math. Mech. 2 (2), 88–91.
- USDA (United States Department of Agriculture), (1999), Soil Taxonomy A Basic System of Soil Classification for Making and Interpreting Soil Survey. USDA Handbook No. 436. Wash. D.C.
- USDA-NRCS (US Department of Agriculture, Natural Resources and Conservation Service) (1974). *National engineering handbook. Section 15, Chapter 4: Border Irrigation.* Washington (DC): National Technical Information Service.

- Villarreal, E.L. (2005). *Beneficial Use of Stormwater Opportunities for urban renewal and water conservation*. Ph.D. thesis, Lund Institute of Technology, Lund Univ., Sweden.
- Wallach, R., Grigorin, G., Rivlin, J. (1997). "The errors in surface runoff prediction by neglecting the relationship between infiltration rate and overland flow depth," *J. Hydrol.*, 200, 243–259.
- Wanielista, M.P., and Yousef, Y.A., (1993). *Stormwater Management*. John Wiley & Sons, Inc., USA.
- Wanielista, M.P., Yousef, Y.A., and Avellaneda, E., (1988). Alternatives for the Treatment of Groundwater Contaminants: Infiltration Capacity of Roadside Swales. Technical report, University of Central Florida, Department of Civil Engineering and Environmental Sciences, USA.
- Warrick, A.W., Zerihun, D., Sanchez, C.A., and Furman, A. (2005). "Infiltration under Variable Ponding Depths of Water." *J. Irrig. Drain. Eng.*, 131(4), 358–363.
- WDNR (Wisconsin Department of Natural Resources), (2017), Vegetated Swale, Conservation Practice Standard, (1005), 1-16.
- WEF (Water Environment federation), (2012), *Design of Urban Stormwater Controls*, Virginia, USA.
- Weill, S., Mouche, E., Patin, J., (2009), "A generalized Richards equation for surface/subsurface flow modelling." J. Hydrolo., 366(4), 9-20.
- Whitaker, S., (1986), "Flow in porous media I: A theoretical derivation of Darcy's law.", *Transport in Porous Media* (1) 3-25.
- Wohling T. Singh R., and Schmitz G., (2004), "Physically Based Modeling of Interacting Surface–Subsurface Flow During Furrow Irrigation Advance.", J. Irri. Drain. Eng., ASCE
- Woolhiser, D.A., Smith, R.E., Giraldez, J.-V., 1996. "Effects of spatial variability of saturated hydraulic conductivity on Hortonian overland flow." *Water Resour. Res.* 32 (3), 671-678.
- WSUD (Water Sensitive Urban Design). (2004). *Technical Guidelines for Western Sydney*. Section 5. Sydney. Australia
- Wu, F., Shen, H. W., and Chou, Y. (1999). "Variations of Roughness Coefficients for Unsubmerged and Submerged Vegetation." J. Hydraul. Eng. 125(9), 239-245.

- Yousef, Y. A., Wanielista, M. P., and Harper, H. H. (1985). "Removal of highway contaminants by roadside swales." *Transp. Res. Rec.* 1017: Surface Drainage and Highway Runoff Pollutants, Transportation Re-search Board, National Research Council, Washington, D.C., 62–68
- Yu, S. L., Kuo, J. T., Fassman, E. A., and Pan, H. (2001). "Field Test of Grassed Swale Performance in Removing Runoff Pollutant." J. Water Res. Planning and Management, May/June 2001, 186-171.
- Yusof, M.F, Zakaria, N.A., Ab.Ghani, A., Abdllah, R., Kiat, C.C., (2005), "Infiltration study for urban soil: Case studies-butterworth and engineering campus, University Sains Malaysia.", XXXI IAHR Congress: Water Engineering for the Future - Choiceand Challenges, 11-16 September, Seoul, Korea, pp. 1154-1162.
- Zakaria, N.A., Ab.Ghani, A., Abdllah, R., Sidek, L.M., Ainan. A., (2005), "Bio-Ecological Drainage System (BIOECODS) For Water Quantity And Quality Control.", International Journal River Basin Management, IAHR & INBO, 1(3), pp. 237-251.
- Zerihun D., Furman A. Warrick W., and Sanchez C., (2005), "Coupled Surface-Subsurface Flow Model for Improved Basin Irrigation Management.", *J. Irri. Drain. Eng.*, ASCE.
- Zhang, G., Qian, Y., Wang, Z., and Zhao, B., (2014), "Analysis of Rainfall Infiltration Law in Unsaturated Soil Slope.", *The Scientific World Journal*, Article ID 567250.
- Zhao, N., Yu, F., Li, C., Zhang, L., Liu, J., Mu, W., and Wang, H., (2014), "Soil Moisture Dynamics and Effects on Runoff Generation at Small Hillslope Scale." *J. Hydrolo. Eng.*, 20(7 0):05014024.
- Zhiguo H., Weiming W., Yongping Y., and Sam S., (2007), "Simulation of Rainfall-Runoff in the Deep Hollow Lake Watershed Using an Integrated Surface-Subsurface Flow Model.", World Environment and Water Resources Congress, ASCE.
- Zhou, Q. (2014). "A Review of Sustainable Urban Drainage Systems Considering the Climate Change and Urbanization Impacts." *Water*, 6, 976–992.