



UNIVERSITI PUTRA MALAYSIA

***OPTIMIZATION OF THE JAKIM HALAL LOGO PLACEMENT ON QR
CODE
USING ENHANCED GENETIC ALGORITHM***

FUAAD BIN ROHANI

FK 2018 147



**OPTIMIZATION OF THE JAKIM HALAL LOGO PLACEMENT ON QR CODE
USING ENHANCED GENETIC ALGORITHM**

By

FUAAD BIN ROHANI

**Thesis Submitted to the School of Graduate Studies, Universiti
Putra Malaysia, in Fulfilment of the Requirements for the Degree of
Master of Science**

May 2018

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia





Specially dedicated to
My parents, my wife and my children

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in
fulfilment of the requirement for the degree of Master of Science

OPTIMIZATION OF THE JAKIM HALAL LOGO PLACEMENT ON QR CODE USING ENHANCED GENETIC ALGORITHM

By

FUAAD BIN ROHANI

May 2018

Chair : Syamsiah Binti Mashohor, PhD
Faculty : Engineering

A logo placed on Quick Response (QR) code provides additional aesthetic value and visual information to the user. Visual quality of the embedded logo is an important criterion besides success in QR code readability. Unfortunately, most work placed a logo on QR code with low embedded data capacity. Therefore, Jabatan Kemajuan Islam Malaysia (JAKIM) halal premises information is used to represent high data capacity. The thesis proposed a method to place a logo on top of the QR code, embedded with high data capacity, using Genetic Algorithm (GA) search technique to find appropriate size and location so the QR code can be decoded by various QR code decoders. Pad codewords modification technique is used to minimize the error introduced by the logo while three QR code decoders are used to achieve high probability of decode feasibility. A fitness function has been formulated to determine the appropriate size and location of the logo. A total of 3949 samples retrieved from JAKIM public access database was segregated into six groups based on the amount of information that could be embedded in the QR code, wherein 10% of the items from each group were used as samples for data generation. From the experiments, logo size about 69 to 76 pixels which covered about 5.39% to 7.16% of the QR code area can be used for all items in the respective group without decoding failure compared to 2% currently used in JAKIM Halal tag. The module pixel error in the QR code is found to be less than 4.25%. The logo placement system had successfully avoided error correction modules and control patterns, simultaneously, the placement location of the logo is maintained within the QR code area. The proposed work has been compared to GA-based technique, module modification technique and Simulated Annealing technique related to QR code readability, embedded logo visual quality and high embedded data capacity. As a conclusion, the system can successfully find a set of logo size and location on a QR code embedded with high data capacity that does not affect the QR code readability and can be decoded by various decoders with 100% accuracy.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Master Sains

PENGOPTIMUMAN PELETAKAN LOGO HALAL JAKIM DI ATAS KOD QR MENGUNAKAN ALGORITMA GENETIK DITINGKATKAN

Oleh

FUAAD BIN ROHANI

Mei 2018

Pengerusi : Syamsiah Binti Mashohor, PhD
Fakulti : Kejuruteraan

Logo yang diletakkan pada kod QR memberikan nilai tambah estetik dan maklumat visual kepada pengguna. Kualiti visual logo yang dibenam di dalam kod QR adalah kriteria yang penting selain kejayaan kebolehbacaan kod QR. Malangnya, kebanyakan kerja hanya meletakkan logo pada kod QR yang mempunyai kapasiti data tertanam yang rendah. Oleh itu, maklumat premis halal Jabatan Kemajuan Islam Malaysia (JAKIM) digunakan untuk mewakili kapasiti data yang tinggi. Tesis ini mencadangkan kaedah untuk meletakkan logo di atas kod QR, yang tertanam dengan data berkapasiti tinggi, menggunakan teknik carian Algoritma Genetik (GA) untuk mencari saiz dan lokasi yang sesuai supaya kod QR dapat dinyahkod oleh pelbagai penyahkod kod QR. Teknik pengubahan ruang pad digunakan untuk mengurangkan ralat yang dijana oleh logo manakala tiga jenis penyahkodan kod QR digunakan untuk mendapatkan kebarangkalian kejayaan nyahkod yang tinggi. Fungsi kesesuaian telah dirumus untuk penentuan saiz dan lokasi peletakan logo yang sesuai. Sejumlah 3949 sampel yang diambil dari pangkalan data awam JAKIM telah diasingkan ke dalam enam kumpulan berdasarkan jumlah maklumat yang boleh dimasukkan ke dalam kod QR, dimana 10% daripada item dari setiap kumpulan digunakan sebagai sampel untuk penjaan data. Daripada eksperimen, saiz logo sekitar 69 hingga 76 piksel yang meliputi di antara 5.39% hingga 7.16% daripada kawasan kod QR boleh digunakan untuk semua sampel dalam kumpulan masing-masing tanpa kegagalan nyahkod berbanding dengan 2% yang digunakan pada tag Halal JAKIM. Ralat piksel modul di dalam kod QR didapati kurang daripada 4.25%. Sistem peletakan logo ini telah berjaya mengelakkan modul pembetulan ralat dan corak kawalan, pada masa yang sama, lokasi letakan logo dikekalkan di dalam kawasan kod QR. Kerja yang dicadangkan telah dibandingkan dengan teknik berasaskan GA, teknik pengubahsuaian modul dan teknik *Simulated Annealing* berkaitan dengan kebolehbacaan kod QR, kualiti visual logo terbenam dan data terbenam berkapasiti tinggi. Sebagai kesimpulan, sistem yang dicadangkan berjaya

menemui set saiz dan lokasi logo pada kod QR yang tertanam dengan kapasiti data yang tinggi yang tidak menjejaskan kebolehbacaan kod QR dan boleh dinyahkod oleh berbagai jenis penyahkodan dengan ketepatan 100%.



ACKNOWLEDGEMENTS

Alhamdulillahilahi rabbil 'alamin, praise belong to Allah, the Lord of the Worlds.

I would like to express my deepest gratitude to my supervisor Dr. Syamsiah bt. Mashohor, who has always given productive advice and understanding. Without her supervision and constant help this thesis would not have been possible. I would also like to express my appreciation to my committee member Associate Professor Dr. Abd Rahman bin Ramli who also has given support and fruitful advice.

I would like to thank En. Jamali Bin Janib from the Dean Office, Faculty of Engineering, En. Mohd. Hafizul Amin bin Mohd. Supian and En. Firdaus from iDEC Faculty of Engineering for giving me permission to use one of the engineering computer labs to run the projects for two weeks. Without them, it would not be possible to finish this thesis.

I would also like to thank Puan Messiah Sadar, Puan Tuan Zawinah Raja Hamat, the staff from SGS and the staff in the Deputy Dean of Graduate Studies Division (TDS) Faculty of Engineering for the support given to me through my candidature.

I would like to thank my parents and my family who are very understanding, supportive and encouraging.

Last but not least I would like to thank the open source community for their excellent contributions to the open source software such as Linux, LibreOffice, AForge.Net, ZXing.Net, and everyone that has helped me in one way or another, directly or indirectly.

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Syamsiah Binti Mashohor, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Abd Rahman Bin Ramli, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

ROBIAH BINTI YUNUS, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: _____ Date: _____

Name and Matric No.: _____ Fuaad Bin Rohani (GS35749) _____

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: _____

Name of Chairman
of Supervisory
Committee:

Dr. Syamsiah Binti Mashohor

Signature: _____

Name of Member of
Supervisory
Committee:

Assoc. Prof. Dr. Abd Rahman Bin Ramli

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENTS	iv
APPROVAL	v
DECLARATION	vii
LIST OF TABLES	xii
LIST OF FIGURES	xiii
LIST OF ABBREVIATIONS	xvi
 CHAPTER	
 1 INTRODUCTION	 1
1.1 Background	1
1.2 Problem Statement	2
1.3 Research Aim	3
1.4 Research Objectives	3
1.5 Scope of the Study	4
1.6 Contribution of Thesis	4
1.7 Outline of Thesis	4
 2 LITERATURE REVIEW	 6
2.1 Introduction to QR code	6
2.2 QR code requirement for logo placement	7
2.3 QR code with illustration	9
2.4 Object placement optimization techniques	12
2.4.1 GA-based placement technique	14
2.4.2 Logo positioning search for QR code using GA	14
2.4.3 Redundant codewords modification for QR code	15
2.5 GA Parameters	15
2.5.1 Chromosomes representation	17
2.5.2 Selection	19
2.5.3 Crossover	20
2.5.4 Mutation	21
2.5.5 Fitness function	22
2.6 Performance metrics of logo placement on QR code	24
2.6.1 QR code readability	24
2.6.2 Logo visual quality	24
2.6.3 Module error	24
2.6.4 Data accuracy	25

	2.6.5	Processing time	25
	2.7	Summary	25
3		METHODOLOGY	28
	3.1	Introduction	28
	3.2	High data capacity dataset	29
	3.3	QR code version identification	30
	3.3.1	QR code generator layout design	31
	3.3.2	Logo size and readability determination	34
	3.4	GA-based generator design	35
	3.4.1	Chromosomes	35
	3.4.2	Fitness function	36
	3.4.3	GA-based QR code with logo generator	43
	3.4.4	Population and generation	46
	3.4.5	Mutation and crossover probability	48
	3.4.6	QR code encoder/decoder modification	49
	3.5	Evaluation of GA-based QR code generator	51
	3.6	Comparison with related works	55
	3.7	Summary	57
4		RESULTS AND DISCUSSION	58
	4.1	Introduction	58
	4.2	QR code version identification	58
	4.2.1	Readability	58
	4.2.2	Rate of logo size to QR code size	60
	4.2.3	Module pixel error	60
	4.2.4	Data accuracy	62
	4.2.5	Processing time	63
	4.3	Results on GA-based QR code generator	63
	4.3.1	Population and generation	64
	4.3.2	Crossover and mutation	64
	4.3.3	Performance Graph	66
	4.4	Evaluation of GA-based QR code generator	67
	4.4.1	Selective sampling	67
	4.4.2	Rate of logo size to QR code size	68
	4.4.3	Module pixel error	69
	4.4.4	Placement candidate for each group	70
	4.4.5	Evaluation of candidate to all	72

	items in the dataset	
4.4.6	Effect of Error Correction level selection	79
4.5	Comparison with related works	80
4.5.1	Comparison with GA-based technique	80
4.5.2	Comparison with modules modification technique	82
4.5.3	Comparison with Simulated Annealing technique	83
4.6	Summary	84
5	CONCLUSION AND FUTURE WORKS	86
5.1	Conclusion	86
5.2	Future Works	87
REFERENCES		89
BIODATA OF STUDENT		98
LIST OF PUBLICATIONS		99

LIST OF TABLES

Table	Page
2.1 Error Correction level	7
2.2 Level M module size and capacity for each QR version	8
2.3 Methods to embed illustration on top of QR code	10
2.4 Nature Inspired Algorithms	13
2.5 Comparison between several logo embedding techniques	26
3.1 Settings to determine the effect of overlapped logo on QR code	35
3.2 Q(x) function description	38
3.3 Settings for population and generation test	48
3.4 Settings for mutation and crossover effect test	49
3.5 Data samples group by version with 10% selection	51
3.6 Data selection group by character length	53
3.7 Settings for QR code generator evaluation	54
3.8 Character length, QR code version and image use for comparison	57
4.1 Number of other error found using ZXing decoder	62
4.2 Logo size, fitness value and error for each group	68
4.3 Items undecodable by ZXing, ZBar and qrcode	72
4.4 Undecodable QR code embedded data by ZXing, ZBar or qrcode	74
4.5 Placement candidate that can be decoded by all three decoders	76
4.6 Logo area and pixel error comparison between sample and all pass	77

LIST OF FIGURES

Table	Page
2.1 QR code structure	6
2.2 GA implementation	17
2.3 Chromosome presentation	18
2.4 Elitism selection	20
2.5 One-point crossover operator	21
2.6 Mutation operator	22
3.1 Work flow of the proposed framework	29
3.2 Number of data items group by length	30
3.3 JAKIM Halal logo	31
3.4 Logo layout search	32
3.5 Overall flow chart of QR code generator	33
3.6 Chromosomes representation	36
3.7 Overlapped pad codewords	39
3.8 Similar data codewords pixels and binarized logo pixels	40
3.9 Out of Range logo pixels	41
3.10 Overlapped error correction codewords	42
3.11 Overlapped control patterns	43
3.12 GA-based generator flow	44
3.13 GA logo placement search flow	45
3.14 Decoder verification process	46
3.15 Generation and population check flow	47
3.16 QR code encode function flow	50
3.17 Check all downloaded premises data using	55

	sample candidate	
3.18	Images used for comparison	56
4.1	Logo size and placement iteration	59
4.2	Rate of logo size to QR code size	60
4.3	QR code module pixel error	61
4.4	Processing time comparison between module size	63
4.5	Trend line for various population	64
4.6	Comparison between mutation probability	65
4.7	Crossover probability for mutation probability $P_m = 0.3$	65
4.8	Performance graph generation = 200 population = 50	66
4.9	QR code area occupied by logo	69
4.10	QR code pixel error for all groups	69
4.11	Location of logo placement candidate for each group	71
4.12	Each group decoding success using placement candidate	73
4.13	Each group decoding success after eliminate undecodable data	75
4.14	Best logo size with maximum area and minimum pixel error	78
4.15	Effect of error correction level selection	79
4.16	Comparison of proposed work with current GA-based technique	80
4.17	Logo size without alignment pattern calculation	81
4.18	Logo location affected by low quality decoder	82
4.19	Comparison with modules modification technique	83



LIST OF ABBREVIATIONS

QR	Quick Response
2D	Two-dimensional
JAKIM	Jabatan Kemajuan Islam Malaysia
RFID	Radio-frequency identification
NFC	Near-field communication
SA	Simulated Annealing Optimization
GA	Genetic Algorithm
EC	Error correction
ECC	Error Correction Codewords
DE	Differential Evolution
ABC	Artificial Bee Colony
CSS	Charge Search Systematic
PSO	Particle Swarm Optimization
ES	Evolution Strategies
XOR	Exclusive-OR
RGB	Red, Green, Blue

CHAPTER 1

INTRODUCTION

1.1 Background

Quick Response (QR) code is a two-dimensional (2D) barcode originally utilized by the automobile industry in Japan for their production management system (Denso wave, 2000). Increasing awareness and adoption of the QR code, especially in the marketing field, has increased the trend of smartphone users to scan the QR code (Tiwari, 2016). Currently, the use of QR code ranges from food traceability (Ramundo, Taisch, & Terzi, 2016) to document authentication (Tkachenko et al., 2016).

QR code with company's logo can attract more user to scan it compared to plain QR code (Čović & Šimon, 2016). Unfortunately, embedding logo on QR code introduce error to the QR code modules making it difficult to scan (Wang et al., 2015). The embedded logo is preferred to be as large as possible, but must not degrade the readability of the QR code (Lay et al., 2016). High embedded data capacity can degrade the visual quality of the embedded logo (Y.-H. Lin, Chang, & Wu, 2013) because of the limited modules that can be changed freely.

In recent years, Jabatan Kemajuan Islam Malaysia (JAKIM) has introduced a passive QR code known as JAKIM Halal tag (JAKIM, 2012) placed at JAKIM certified halal premises that can be scanned offline using a QR code decoder. Unfortunately, the QR code symbol only can be scanned by i-nigma (<http://www.i-nigma.com>) QR code decoder which prevented consumer from using a standard QR code decoder. This limitation may not attract its usage as ease of use and reliability are important to the customers (Abd Rahman et al., 2016).

The JAKIM Halal logo has significant contribution to the confidence level of customers (Rezai, Mohamed, & Shamsudin, 2012) and purchase intention (Aziz & Chok, 2013) when they are about to acquire halal product or service. In Malaysia, JAKIM has been given the task of managing halal certifications, making regulations and monitoring the halal industry for any breach of halal certificates and logo. The JAKIM Halal logo is the easiest way for halal consumers to determine halal compliance of JAKIM halal certified premises. Nevertheless, some customers are less confident in the halal logo due to the failure of the authority to adequately enforce law and take action on the misuse of halal logo (Rezai et al., 2012). Unfortunately, halal logo fraud cases appeared such as use of halal logo other than JAKIM Halal logo (Bernama, 2016a, 2016b) and using an unauthorized JAKIM Halal logo (Mohd Amin,

2016) so that the company involved can make profit by confusing halal consumers.

In preventing of such fraud activity from widespread, JAKIM introduced halal portal (JAKIM, 2011) that can be accessed by the public to verify the status of halal products or services. Meanwhile, to strengthen and simplify the verification process of halal products and services, researchers and industries have developed systems using technology such as Radio Frequency Identification (RFID) (Anir, Nizam, & Masliyana, 2008b, 2008a), Near Field Communication (NFC) (Sawari, Ghazali, & Yap, 2015) and QR code (JAKIM, 2012; Sinar Harian, 2012). QR code also being used in other applications (Husny et al., 2014) such as a watermarking image to authenticate halal logo and certificates (Yahaya, Hassan, & Kahmi, 2012).

As JAKIM Halal logo is an important element for consumers to recognize JAKIM halal certified premises (Abu Bakar, Rosslee, & Saidin, 2014), the inclusion of JAKIM Halal logo on top of the QR code provides a visual meaning that the QR code is from JAKIM. The consumers should not be constraint to use only one brand of QR code decoder so that many consumers can get benefit from the application. This problem motivates this project to find the appropriate placement of logo on QR code embedded with high data capacity that can be decoded by various QR code decoders.

1.2 Problem Statement

Several techniques have been developed to superimpose logo on top of QR code without sacrificing the QR code readability such as searching for appropriate placement areas (Ono, Morinaga, & Nakayama, 2008b; Wakahara & Yamamoto, 2011), modification of QR code redundant modules (Wakahara, Yamamoto, & Ochi, 2010), selection of parity bits modules (Fujita, Kuribayashi, & Morii, 2011) and modification of module color intensity (Garateguy et al., 2014). These techniques have their own advantages regarding logo visual quality. Unfortunately, high data capacity usage of the QR code can degrade the visual quality of the embedded logo (Y.-H. Lin et al., 2013).

Premises' address usually has a long stream of characters and when embedded in a QR code requires high data capacity storage. Therefore, the first question is what is the length of premises' address to be used and how it affects the QR code parameters such as version and size. Long information required higher QR code version which makes the size larger compared to shorter information. Therefore, as each premise has different information, the generated QR code is unique to each premise. In order to simulate high data capacity, premises' address is downloaded from JAKIM public database (<http://www.halal.gov.my/ehalal>) and analyzed to find the distribution of the information length. JAKIM Halal tag is also investigated to find other parameters such as error correction (EC) level and QR code version used.

Placing a logo on top of the QR code introduces noise that prevents the QR

code from being decoded correctly by the QR code decoders available in the market. Y.-H. Lin et al. (2013) used Simulated Annealing Optimization (SA) to find optimal codewords that can minimize the visual distortion of the embedded logo. The technique also required the QR code version number to be increased in order to create more redundant codewords as used by Wakahara et al. (2010) and Fujita et al. (2011). Unfortunately, the logo distortion gets worst when 20% of the QR code data are occupied. Ono et al. (2008b) has formulated a Genetic Algorithm (GA) fitness function to search for appropriate logo placement on QR code that can be decoded successfully by various QR code decoders. This technique uses highest QR code EC level to compensate with the error introduced when a logo is placed on the QR code. Even though data capacity does not affect the logo appearance, there are possibilities of decoding failure by one of QR code decoder used.

The next question is how can the QR code with a logo on top of it can be designed in such a way that various QR code decoders can be used to scan the QR code. As data capacity does not affect the logo visual distortion for the GA technique, this technique can be improved by reformulate the fitness function so that various QR code decoders able to decode the resultant QR code. There are a lot of QR code decoders in the market and each of them have their own advantages and disadvantages. Some decoders have the ability to decode the QR code whenever certain requirement for QR code detection is missing but other decoders may not have the same capability. Therefore, it is essential for important pattern to be retained so that various QR code decoders can be used to scan the QR code with logo on it.

The last question is the possibility of the resultant sample placement candidate to be used by other premises information with different length. The sampling resultant candidate needs to be evaluated against all downloaded premises data to determine the readability of the QR code. A comparison with current implementation needs to be done related to logo size, QR code readability and embedded data capacity.

1.3 Research Aim

This thesis proposed to find appropriate placement of moderate logo size on top of QR code embedded with high data capacity that can be decoded by various QR code decoders.

1.4 Research Objectives

The objectives identified are as follow:

1. To determine the QR code version which is suitable for high data capacity with logo placement.
2. To design an optimal placement of logo using GA on QR code

considering readability, data capacity and visual quality.

3. To evaluate the GA-based logo placement method on QR code with various logos and compare with other logo placement methods.

1.5 Scope of the Study

The embedded information used in the experiments was obtained from JAKIM Halal directory (JAKIM, 2007) on 30 Jan 2014 to 9 Feb 2014 to simulate high data capacity. The data has been formatted to follow the format of JAKIM Halal tag as close as possible.

Mode optimization is not done in generating the QR code due to the limitation of the encoder capability. EC level M is used, same as JAKIM Halal tag. Module size of three pixels is used due to the decoding capability of ZBar and qrcode decoder. Three decoders are used to simulate various decoders.

1.6 Contribution of Thesis

In this thesis, GA-based logo placement technique is improved by reformulate the GA fitness function. The probability of decoding success depends on decoding result of the three QR code decoders. All three QR code decoders must be able to decode the QR code so that the logo placement location can be calculated. Pad codewords, error correction codewords (ECC) and control patterns calculation are added to the logo placement quality function.

1.7 Outline of Thesis

Chapter Two starts with a brief introduction of the QR code standard followed by requirements of logo placement on QR code. QR code with illustration is introduced, followed by optimization techniques used to place logo on QR code. Next, GA parameters and performance metrics regarding logo placement on QR code are given.

Chapter Three presents the methodology and steps involved in implementing the proposed idea. High data capacity dataset distribution is presented, followed by identification of QR code version suitable for pad codewords modification technique. Afterward GA-based QR code generator design is explained, including chromosome representation, fitness function formulation and parameters setting. A method to evaluate GA-based QR code generator to produce placement candidate is described, followed by evaluating the solution to the whole premises dataset. Lastly, method to benchmark the proposed work with current implementation is depicted.

Chapter Four discusses the experimental results and discussion on finding

appropriate placement of logo on top of QR code embedded with premises information. The chapter starts by discussing the selection of appropriate QR code version to be used for pad modification technique followed by parameter tuning and evaluation of the GA-based QR code generator on the premises dataset. Lastly, comparison of related work with the proposed work is considered.

Chapter Five presents the conclusion, limitation of the proposed work and possible future enhancements and usability.



REFERENCES

- Abd Rahman, A., Hanafiah, M. H., Abdul, M., & Ruslee, A. A. (2016). Assessing consumers' willingness to use tagging technology in tracing halal status. *International Journal of Islamic Marketing and Branding*, 1(3), 272–284.
- Abu Bakar, E., Rosslee, N. N., & Saidin, A. Z. (2014). Consumers' perceptions towards mobile halal application system. *IEEE 2014 The 5th International Conference on Information and Communication Technology for The Muslim World (ICT4M)*, 1–5.
- Ahmad, A.-R. (2014). A new hierarchical placement algorithm for two-dimensional rectangular layout design. *International Journal of Operations and Quantitative Management*, 20, 101–120.
- Alajmi, A., & Wright, J. (2014). Selecting the most efficient Genetic Algorithm sets in solving unconstrained building optimization problem. *International Journal of Sustainable Built Environment*, 3, 18–26.
- Anir, N. A., Nizam, M. N. M. H., & Masliyan, A. (2008a). RFID tag for halal food tracking in Malaysia: Users perceptions and opportunities. *Proceedings of the 7th WSEAS International Conference on Telecommunications and Informatics*, 87–92.
- Anir, N. A., Nizam, M. N. M. H., & Masliyan, A. (2008b). The users perceptions and opportunities in Malaysia in introducing RFID system for halal food tracking. *WSEAS Transactions on Information Science and Applications*, 5(5), 843–852.
- Aziz, Y. A., & Chok, N. V. (2013). The role of halal awareness, halal certification, and marketing components in determining halal purchase intention among non-muslims in Malaysia: A structural equation modeling approach. *Journal of International Food & Agribusiness Marketing*, 25(1), 1–23.
- Baharav, Z., & Kakarala, R. (2013). Visually significant QR codes: Image blending and statistical analysis. *2013 IEEE International Conference on Multimedia and Expo (ICME)*, 1–6.
- Bernama. (2016a). Restoran Persiaran Gurney kantoi guna logo halal tak sah. Retrieved July 18, 2017, from www.themalaymailonline.com/projekmmo/berita/article/restoran-persiaran-gurney-kantoi-guna-logo-halal-tak-sah
- Bernama. (2016b). Syarikat penjagaan rambut guna logo halal tidak sah. Retrieved July 18, 2017, from www.sinarharian.com.my/semasa/syarikat-penjagaan-rambut-guna

- Brown, J. (2009). ZBar barcode reader version 0.10. Retrieved July 19, 2017, from <http://zbar.sourceforge.net/download.html>
- Can, U., & Alatas, B. (2015). Physics based metaheuristic algorithms for global optimization. *American Journal of Information Science and Computer Engineering*, 1(3), 94–106.
- Chu, H.-K., Chang, C.-S., Lee, R.-R., & Mitra, N. J. (2013). Halftone QR codes. *ACM Transactions on Graphics (TOG)*, 32(6), 217.
- Čović, Z., & Šimon, J. (2016). Usage of QR codes in promotion on social networks. *2016 International Conference on Smart Systems and Technologies (SST)*, 123–127.
- Črepinšek, M., Liu, S.-H., & Mernik, M. (2013). Exploration and exploitation in evolutionary algorithms: A survey. *ACM Computing Surveys (CSUR)*, 45(3), 35.
- Deb, K., & Deb, D. (2014). Analysing mutation schemes for real-parameter genetic algorithms. *International Journal of Artificial Intelligence and Soft Computing*, 4(1), 1–28.
- Denso wave. (2000). QRcode. Retrieved July 29, 2017, from www.qrcode.com/en/index.html
- Drira, A., Pierreval, H., & Hajri-Gabouj, S. (2007). Facility layout problems: A survey. *Annual Reviews in Control*, 31(2), 255–267.
- El-Serafy, A., El-Sayed, G., Salama, C., & Wahba, A. (2015). Enhanced Genetic Algorithm for MC/DC test data generation. *IEEE 2015 International Symposium on Innovations in Intelligent Systems and Applications (INISTA)*, 1–8.
- Fan, J. (2012). Photo layout with a fast evaluation method and Genetic Algorithm. *Proceedings of the 2012 IEEE International Conference on Multimedia and Expo Workshops (ICMEW)*, 308–313.
- Fang, C., Zhang, C., & Chang, E.-C. (2014). An optimization model for aesthetic two-dimensional barcodes. *International Conference on Multimedia Modeling*, 278–290.
- Festa, P. (2014). A brief introduction to exact, approximation, and heuristic algorithm for solving hard combinatorial optimization problems. *2014 16th International Conference on Transparent Optical Networks (ICTON)*, 1–20.
- Flores, J. J., Martínez, J., & Calderón, F. (2016). Evolutionary computation

- solutions to the circle packing problem. *Soft Computing*, 20, 1521–1535.
- Frijters, J. (2012). IKVM.NET Java VM for .NET. Retrieved July 19, 2017, from <https://sourceforge.net/projects/ikvm/>
- Fujita, K., Kuribayashi, M., & Morii, M. (2011). Expansion of image displayable area in design QR code and its applications. *Forum on Information Technology 2011(FIT2011)*, 10, 517–520.
- Garateguy, G. J., Arce, G. R., Lau, D. L., & Villarreal, O. P. (2014). QR images: Optimized image embedding in QR codes. *IEEE Transactions on Image Processing*, 23(7), 2842–2853.
- Geigel, J., & Loui, A. (2003). Using Genetic Algorithms for album page layouts. *IEEE MultiMedia*, 10(4), 16–27.
- Harada, S., Morinaga, K., & Hirakawa, M. (2005). Development of an interactive business card creation support system using Genetic Algorithm. *Proceedings of the 2005 International Conference on Active Media Technology, 2005. (AMT 2005)*, 85–88.
- Hasda, R. K., Bhattacharjya, R. K., & Bennis, F. (2016). Modified Genetic Algorithms for solving facility layout problems. *International Journal on Interactive Design and Manufacturing (IJIDeM)*, 11(3), 713–725.
- Haupt, R. L. (2000). Optimum population size and mutation rate for a simple real Genetic Algorithm that optimizes array factors. *IEEE Antennas and Propagation Society International Symposium. Transmitting Waves of Progress to the Next Millennium.*, 2, 1034–1037.
- Husny, Z. J. M., Tan, M. I. I., Ibrahim, I. S., & Rozan, M. Z. A. (2014). Assessment on the utilization of current halal certification technologies by halal industry players in Malaysia. *Proceedings of The World Congress on Engineering and Computer Science 2014 (WCECS 2014)*, 2, 1004–1009.
- Hussain, K., Mohd Salleh, M. N., Cheng, S., & Shi, Y. (2018). Metaheuristic research: A comprehensive survey. *Artificial Intelligence Review*, 1–43.
- International Organization for Standardization. (2006). *Information technology — Automatic identification and data capture techniques — QR Code 2005 bar code symbology specification* (No. ISO/IEC 18004: 2006(E)).
- Ishibashi, K., & Miyata, K. (2013). Grid layout generator using interactive evolutionary computation. *2013 International Conference on Biometrics and Kansei Engineering*, 1–6.
- Jacobson, L., & Kanber, B. (2015). *Genetic Algorithms in Java Basics*.

Berkeley, CA: Apress.

- Jahn, M. (2013). ZXing.Net 0.12.0.0 barcode reader. Retrieved July 19, 2017, from <https://zxingnet.codeplex.com/releases/view/106588>
- JAKIM. (2007). JAKIM eHalal direktori. Retrieved February 9, 2014, from <http://www.halal.gov.my/ehalal>
- JAKIM. (2011). Semua negeri disasar guna E-Halal tahun depan. Retrieved March 16, 2013, from <http://www.halal.gov.my/v3/index.php/ms/media/berita/249-sistem-e-halal>
- JAKIM. (2012). Konvensyen badan pensijilan halal luar negara kali ke-4 pada 13-14 September 2012. Retrieved December 17, 2013, from <http://www.halal.gov.my/v3/index.php/ms/media/berita/281-konvensyen-badan-pensijilan-halal-luar-negara-kali-ke-4-pada-13-14-september-2012>
- Jensen, J. F., McEvoy, P., & McCaig, B. (2011). ZBar-sharp .Net/Mono bindings for ZBar version 0.10. Retrieved July 19, 2017, from <https://github.com/jonasfj/zbar-sharp>
- Karafotias, G., Hoogendoorn, M., & Eiben, A. E. (2015). Parameter control in evolutionary algorithms: Trends and challenges. *IEEE Transactions on Evolutionary Computation*, 19(2), 167–187.
- Kato, H., & Tan, K. T. (2005). 2D barcodes for mobile phones. *2005 2nd International Conference on Mobile Technology, Applications and Systems*, 1–8.
- Kato, H., & Tan, K. T. (2007a). First read rate analysis of 2D barcodes for camera phone applications as a ubiquitous computing tool. *2007 IEEE Region 10 Conference TENCN 2007*, 1–4.
- Kato, H., & Tan, K. T. (2007b). Pervasive 2D barcodes for camera phone applications. *IEEE Pervasive Computing*, 6(4), 76–85.
- Kato, H., Tan, K. T., & Chai, D. (2008). Development of a novel finder pattern for effective color 2D barcode detection. *IEEE 2008 International Symposium on Parallel and Distributed Processing with Applications*, 1006–1013.
- Kato, H., Tan, K. T., & Chai, D. (2009). Novel colour selection scheme for 2D barcode. *IEEE 2009 International Symposium on Intelligent Signal Processing and Communication Systems (ISPACS)*, 529–532.
- Kirillov, A. (2009). AForge.NET Framework-2.2.4. Retrieved July 17, 2017, from <https://code.google.com/archive/p/aforge/downloads>

- Kuribayashi, M., & Morii, M. (2017). Aesthetic QR code based on modified systematic encoding function. *IEICE Transactions on Information and Systems*, 100, 42–51.
- Lay, K.-T., Chen, Y.-J., Hsueh, H.-C., & Karungaru, S. G. (2016). Visually comprehensible QR codes via embedding of big logos. *2016 IEEE International Conference on Signal and Image Processing (ICSIP)*, 225–230.
- Li, L., Qiu, J., Lu, J., & Chang, C.-C. (2016). An aesthetic QR code solution based on error correction mechanism. *Journal of System and Software*, 116, 85–94.
- Lim, Z. Y., Ponnambalam, S. ., & Izui, K. (2017). Multi-objective hybrid algorithms for layout optimization in multi-robot cellular manufacturing systems. *Knowledge-Based System*, 120, 87–98.
- Lim, Z. Y., Ponnambalam, S. G., & Izui, K. (2016). Nature inspired algorithms to optimize robot workcell layouts. *Applied Soft Computing*, 49, 570–589.
- Lin, S.-S., Hu, M.-C., Lee, C.-H., & Lee, T.-Y. (2015). Efficient QR code beautification with high quality visual content. *IEEE Transactions on Multimedia*, 17(9), 1515–1524.
- Lin, Y.-H., Chang, Y.-P., & Wu, J.-L. (2013). Appearance-based QR code beautifier. *IEEE Transactions on Multimedia*, 15(8), 2198–2207.
- Lin, Y.-S., Luo, S.-J., & Chen, B.-Y. (2013). Artistic QR code embellishment. *Computer Graphics Forum*, 32(7), 137–146.
- Majumdar, A., & Ghosh, D. (2015). Genetic Algorithm parameter optimization using Taguchi robust design for multi-response optimization of experimental and historical data. *International Journal of Computer Applications*, 127(5), 26–32.
- Masui, T. (1992). Graphic object layout with interactive Genetic Algorithms. *IEEE 1992 Workshop on Visual Languages*, 74–80.
- Mills, K. L., Filliben, J. J., & Haines, A. L. (2015). Determining relative importance and effective settings for Genetic Algorithm control parameters. *Evolutionary Computation*, 23(2), 309–342.
- Mohd Amin, K. A. (2016). Restoran pamer logo halal diragui diberi amaran. Retrieved July 18, 2017, from www.sinarharian.com.my/mobile/edisi/perak/restoran-pamer-logo-halal-diragui-diberi-amaran-1.480944
- Negnevitsky, M. (2011). *Artificial intelligence: A guide to intelligent systems* (Third). Essex: Pearson.

- Oda, T., Barolli, A., Spaho, E., Barolli, L., Xhafa, F., & Iwashige, J. (2012). Genetic Algorithms for node placement in WMNs: Effect of changes in population size and number of generations. *2012 Seventh International Conference on Broadband, Wireless Computing, Communication and Applications (BWCCA)*, 356–361.
- O'Donovan, P., Agarwala, A., & Hertzmann, A. (2014). Learning layouts for single-page graphic designs. *IEEE Transactions on Visualization and Computer Graphics*, 20(8), 1200–1213.
- Ono, S., Morinaga, K., & Nakayama, S. (2008a). Barcode design by evolutionary computation. *Artificial Life and Robotics*, 13(1), 238–241.
- Ono, S., Morinaga, K., & Nakayama, S. (2008b). Two-dimensional barcode decoration based on Real-Coded Genetic Algorithm. *2008 IEEE Congress on Evolutionary Computation (CEC 2008)*, 1068–1073.
- Ono, S., Morinaga, K., & Nakayama, S. (2009). Animated two-dimensional barcode generation using optimization algorithms-redesign of formulation, operator, and quality evaluation. *Journal of Advanced Computational Intelligence and Intelligent Informatics*, 13(3), 245–254.
- Ono, S., & Nakayama, S. (2010a). A system for decorating QR code with facial image based on Interactive Evolutionary Computation and Case-Based Reasoning. *2010 Second World Congress on Nature and Biologically Inspired Computing (NaBIC)*, 401–406.
- Ono, S., & Nakayama, S. (2010b). Fusion of interactive and non-interactive evolutionary computation for two-dimensional barcode decoration. *IEEE Congress on Evolutionary Computation (CEC)*, 1–8.
- Ono, S., Sakimoto, K., & Nakayama, S. (2012). A generation alternation model for user–system cooperative evolutionary computation. *Artificial Life and Robotics*, 17(2), 251–256.
- Pandey, H. M., Chaudhary, A., & Mehrotra, D. (2014). A comparative review of approaches to prevent premature convergence in GA. *Applied Soft Computing*, 24, 1047–1077.
- Patel, G., & Panchal, G. (2017). Quick response codes decodability improvements using error correction levels. *2017 International Conference on Intelligent Sustainable Systems (ICISS)*, 231–234.
- Qiao, S., Fang, X., Sheng, B., Wu, W., & Wu, E. (2015). Structure-aware QR code abstraction. *Visual Computer*, 31, 1123–1133.
- Ramundo, L., Taisch, M., & Terzi, S. (2016). State of the art of technology in the food sector value chain towards the IoT. *2016 IEEE 2nd International Forum on Research and Technologies for Society and*

- Rexhepi, A., Maxhuni, A., & Dika, A. (2013). Analysis of the impact of parameters values on the Genetic Algorithm for TSP. *International Journal of Computer Science Issues*, 10(1), 158–164.
- Rezai, G., Mohamed, Z., & Shamsudin, M. N. (2012). Assessment of consumers' confidence on halal labelled manufactured food in Malaysia. *Pertanika J. Soc. Sci. & Hum.*, 20(1), 33–42.
- Rothlauf, F. (2006). *Representations for Genetic and Evolutionary Algorithms* (Second). Heidelberg: Springer.
- Samretwit, D., & Wakahara, T. (2011). Measurement of reading characteristics of multiplexed image in QR code. *2011 Third International Conference on Intelligent Networking and Collaborative Systems (INCoS)*, 552–557.
- Sastry, K., Goldberg, D. E., & Kendall, G. (2014). Genetic Algorithms. In E. K. Burke & G. Kendall (Eds.), *Search Methodologies: Introductory Tutorials in Optimization and Decision Support Techniques* (pp. 93–117). New York: Springer.
- Sawari, S. S. M., Ghazali, M. A., & Yap, S. M. A. B. (2015). Near Field Communications (NFC) as halal detection application. *Mediterranean Journal of Social Sciences*, 6(5), 547–552.
- Schnecke, V., & Vornberger, O. (1997). Hybrid Genetic Algorithms for constrained placement problems. *IEEE Transactions On Evolutionary Computation*, 1(4), 266–277.
- Shen, H., Cunderlik, J., & Hunter, C. (2016). Automating a hydraulic transient model to enable efficient sensitivity analysis and calibration. *Journal of Water Management Modeling*, 25, 1–9.
- Sinar Harian. (2012). Jakim bangunkan sistem “MyHalalTrace” untuk semak produk halal. Retrieved July 19, 2017, from <http://www.sinarharian.com.my/jakim-bangunkan-sistem-myhalaltrace-untuk-semak-produk-halal-1.85098>
- Sindhuja, P., Ramamoorthy, P., & Kumar, M. S. (2018). A brief survey on nature inspired algorithms: Clever algorithm for optimization. *Asian Journal of Computer Science and Technology*, 7(1), 27–32.
- Sivanandam, S. N., & Deepa, S. N. (2008). *Introduction to Genetic Algorithms*. Heidelberg: Springer.
- Skawattananon, C., & Vongpradhip, S. (2013). An improved method to embed larger image in QR code. *2013 10th International Joint Conference on*

- Smit, S. K., & Eiben, A. E. (2009). Comparing parameter tuning methods for evolutionary algorithms. *2009 IEEE Congress on Evolutionary Computation (CEC 2009)*, 399–406.
- Tan, K. T., Chai, D., Kato, H., & Ong, S. K. (2012). Designing a color barcode for mobile applications. *IEEE Pervasive Computing*, 11(2), 50–55.
- Tiwari, S. (2016). An introduction to QR code technology. *2016 International Conference on Information Technology (ICIT)*, 39–44.
- Tkachenko, I., Puech, W., Destruel, C., Strauss, O., Gaudin, J.-M., & Guichard, C. (2016). Two-level QR code for private message sharing and document authentication. *IEEE Transactions on Information Forensics and Security*, 11(3), 571–583.
- Tkachenko, I., Puech, W., Strauss, O., Gaudin, J.-M., Destruel, C., & Guichard, C. (2014). Improving the module recognition rate of high density QR codes (Version 40) by using centrality bias. *2014 4th International Conference on Image Processing Theory, Tools and Applications (IPTA)*, 1–6.
- Tkachenko, I., William Puech, Strauss, O., Gaudin, J.-M., Destruel, C., & Guichard, C. (2016). Centrality bias measure for high density QR code module recognition. *Signal Processing: Image Communication*, 41, 46–60.
- Valvo, E. L. (2017). Meta-heuristic algorithms for nesting problem of rectangular pieces. *17th International Conference on Sheet Metal (SHEMET17)*, 183, 291 – 296.
- Wakahara, T., Samretwit, D., Maki, T., & Yamamoto, N. (2013). Design and characteristics of two-dimensional color code editor with dotted images. In J. Park, L. Barolli, F. Xhafa, & H.-Y. Jeong (Eds.), *Information Technology Convergence* (Vol. 253, pp. 323–332). Dordrecht: Springer.
- Wakahara, T., & Yamamoto, N. (2011). Image processing of 2-dimensional barcode. *IEEE 2011 14th International Conference on Network-Based Information Systems (NBIS)*, 484–490.
- Wakahara, T., Yamamoto, N., & Ochi, H. (2010). Image processing of dotted picture in the QR code of cellular phone. *2010 IEEE International Conference on P2P, Parallel, Grid, Cloud and Internet Computing (3PGCIC)*, 454–458.
- Wang, S., Yang, T., Li, J., Bowei, Y., & Zhang, Y. (2015). Does a QR code must be black and white? *International Conference on Orange*

Technologies (ICOT), 161–164.

Xu, M., Li, Q., Niu, J., Liu, X., Xu, W., Lv, P., & Zhou, B. (2018). ART-UP: A novel method for generating scanning-robust aesthetic QR codes. *ArXiv Preprint ArXiv:1803.02280*.

Xu, M., Su, H., Li, Y., Li, X., Liao, J., Niu, J., ... Zhou, B. (2018). Stylize aesthetic QR code. *ArXiv Preprint ArXiv:1803.01146*.

Yahaya, C. K. H. C. K., Hassan, H., & Kahmi, M. I. B. M. (2012). Investigation on perceptual and robustness of LSB digital watermarking scheme on halal logo authentication. *IEEE 2012 International Conference on System Engineering and Technology (ICSET)*, 1–6.

Yanbe, Y. (2007). Open source QR code library project. Retrieved July 19, 2017, from <https://osdn.net/projects/qrcode/>

Yang, X.-S., Deb, S., Fong, S., He, X., & Zhao, Y.-X. (2016). From swarm intelligence to metaheuristics: Nature-inspired optimization algorithms. *Computer*, 49(9), 52–59.