



**UNIVERSITI PUTRA MALAYSIA**

**STRUCTURAL BEHAVIOUR OF PRECAST CONCRETE SANDWICH  
PANEL WITH HIGH THERMAL EFFICIENCY**

**SANI MOHAMMED BIDA**

**FK 2019 71**



**STRUCTURAL BEHAVIOUR OF PRECAST CONCRETE SANDWICH  
PANEL WITH HIGH THERMAL EFFICIENCY**

By

**SANI MOHAMMED BIDA**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia, in  
Fulfilment of the Requirements for the Degree of Doctor of Philosophy**

**October 2018**

## **COPYRIGHT**

All materials contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



## **DEDICATION**

This thesis is dedicated to my precious mum and wife for their supports,  
encouragement and prayers.



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Doctor of Philosophy

## **STRUCTURAL BEHAVIOUR OF PRECAST CONCRETE SANDWICH PANEL WITH HIGH THERMAL EFFICIENCY**

By

**SANI MOHAMMED BIDA**

**October 2018**

**Chairman: Assoc. Prof. Farah Nora Aznieta Binti Abd.Aziz, PhD**  
**Faculty: Engineering**

Malaysian Government has targeted the year 2020 for full implementation for energy efficiency in buildings known as Green Building. In line with this perspective, this research aims to develop a thermally efficient and structurally acceptable precast concrete sandwich panels (PCSP) for structural applications. In order to achieve the aims, four objectives are outlined to determine the thermal and structural performance of staggered shear connectors. The staggered shear connector is a method used to avoid thermal bridges between layers. In this research, PCSP is designed with staggered shear connection spaced at 200, 300 and 400 mm on each concrete layers. While the control panel is designed with a direct shear connection at 200 mm. Four panels of 500mm x 500mm and 150mm thick are subjected to Hot Box Test to determine the thermal performance. While for structural performance, four (4) number of a full-scale panel of size 2500mm x 1650mm x 150mm are subjected to flexural test and another four (4) of 3000mm x 1650mm x 150mm size for axial load tests. These experimental results are validated by numerical analysis using the finite element method (FEM). In addition, an empirical equation of axial load capacity of the reinforced concrete wall was modified to determine the PCSP capacity. The hot box test result shows that thermal efficiency of the PCSP with staggered shear connectors increases with increase in spacing. The PCSP with 400 mm staggered shear connectors indicate the best thermal efficiency with a thermal resistance (R-value) of 2.48 m<sup>2</sup>K/W. The R-value is higher than the maximum value recorded in the literature. The thermal performance was verified by FEA which shows less than 5% error coupled with a precise prediction of isothermal flux lines behaviour. The structural performance of PCSP under flexural loading showed that all PCSP with staggered shear connector achieved full compositeness with no debonding failure observed. The PCSP panel with a staggered shear connector at 300mm is capable of sustaining the axial capacity for five (5) storey load. However, beyond 300 mm staggered shear connector, the PCSP failed due to bucking. The experimental results were verified by FEA with about 4% and 15% error for the flexural and axial loadings, respectively. The empirical equation of axial load capacity of the reinforced concrete wall has overestimated the ultimate load capacity of PCSP. Therefore, the equation is subjected to statistical analysis using particle swarm optimization technique (PSO) by taking into

consideration the effect of insulation and shear connection in PCSP. The modified equation has successfully predicted load capacity of PCSP with high accuracy. The result was achieved with objective function (MAE) at swarm 30 with minimum iteration and  $CoV$  value of 10%. In conclusion, the PCSP with 300mm staggered shear connectors has met the energy efficiency requirement for sustainable buildings i.e. thermally efficient with excellent structural performance in both axial and flexural behaviour. These results proved that better thermal resistant and structural performance of PCSP can be achieved using conventional steel and concrete materials using staggered thermal path approach. Hopefully, the output of this research will help designers; both architects and engineers to choose PCSP wall to provide better thermal resistance and load bearing structural panels toward green and sustainable buildings.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Doktor Falsafah

## **KELAKUAN STRUKTUR PANEL APIT KONKRIT PRATUANG BERKECEKAPAN HABA TINGGI**

Oleh

**SANI MOHAMMED BIDA**

**Oktober 2018**

**Pengerusi: Prof. Madya Farah Nora Aznieta Binti Abd.Aziz, PhD**  
**Fakulti: Kejuruteraan**

Kerajaan Malaysia mensasarkan tahun 2020 untuk melaksanakan sepenuhnya kecekapan tenaga di bangunan yang dikenali sebagai Bangunan Hijau. Sejalan dengan perspektif ini, kajian ini bertujuan untuk membangunkan panel apit konkrit pratuang (PCSP) yang berkecekapan haba dan strukturnya diterima untuk aplikasi struktur. Bagi mencapai matlamat penyelidikan ini, empat objektif dinyatakan untuk mengenalpasti kemampuan haba dan struktur bagi sambungan ricih berperingkat panel. Metod sambungan ricih berperingkat ini adalah untuk mengelakkan jambatan haba antara lapisan. Dalam kajian ini, PCSP direka dengan sambungan ricih berperingkat pada jarak 200, 300 dan 400 mm pada setiap lapisan. Manakala, panel kawalan direka dengan sambungan ricih langsung pada jarak 200 mm. Empat panel bersaiz 500mm x 500mm dan ketebalan 150mm dikenakan ujian kotak panas untuk mengenalpasti kemampuan habanya. Manakala untuk kemampuan struktur, empat (4) jumlah panel berskala penuh bersaiz 2500mm x 1650mm x 150mm dikenakan ujian lenturan dan empat (4) lagi panel persaiz 300mm x 1650mm x 150mm dikenakan ujian paksi. Keputusan ujian ini telah divarifikasi oleh analisis berangka yang menggunakan perisian metod elemen terhad (FEM). Tambahan pula, persamaan empirikal bagi kapasiti beban paksi bagi dinding konkrit bertetulang diubahsuai untuk mendapatkan kapasiti PCSP. Keputusan ujian kotak panas mendapati kecekapan haba bagi PCSP dengan sambungan ricih bertingkat bertambah dengan pertambahan jarak sambungan ricih tersebut. Panel PCSP dengan sambungan ricih jarak 400 mm mencapai kecekapan haba terbaik dengan rintangan haba (nilai R) (sebanyak 2.48 m<sup>2</sup>K/W). Nilai R ini jauh lebih tinggi daripada yang direkodkan dalam kajian terdahulu. Prestasi termal ini telah diverifikasi menggunakan perisian FEA dengan ralat kurang daripada 5% dan meramalkan kelakuan lilitan fluks isoterma dengan tepat. Perlakuan struktur PCSP di bawah beban lenturan menunjukkan bahawa semua PCSP dengan sambungan ricih bertingkat mencapai kapasiti komposit penuh dengan tiada kegagalan sambungan permukaan yang diperhatikan. Panel PCSP dengan sambungan ricih bertingkat 300 mm menunjukkan kapasiti paksi mampu mencapai beban bangunan lima (5) tingkat, namun, bagi PCSP bersambungan lebih dari 300mm, kegagalan lenturan dikenalpasti. Keputusan hasil ujikaji atau eksperimen divarifikasi oleh FEA dengan ralat lebih kurang 4% dan 15% untuk beban lenturan dan paksi. Persamaan empirikal bagi

kapasiti beban paksi bagi dinding konkrit bertetulang telah melebihi anggar kapasiti muktamad PCSP. Oleh itu, persamaan empirikal tersebut telah dikenakan analisis statistik menggunakan teknik pengoptimuman swarm partikel (PSO) dengan mengambilkira kesan lapisan insulasi dan sambungan ricih. Persamaan yang telah diubahsuai telah berjaya menganggarkan kapasiti muktamad beban PCSP dengan ketepatan yang tinggi. Hasilnya dicapai dengan fungsi objektif (MAE) pada kumpulan 30 dengan pengulangan minimum dan nilai CoV 10%. Sebagai kesimpulan, PCSP dengan sambungan ricih 300mm telah berjaya memenuhi keperluan kecekapan tenaga untuk bangunan lestari i.e. kecekapan haba, dengan pencapaian struktur yang cemerlang didalam perlakuan paksi dan lenturan. Keputusan ini membuktikan ketahanan haba dan pencapaian struktur yang lebih baik mampu dicapai oleh PCSP yang menggunakan tetulang dan konkrit konvensional dengan pendekatan jambatan haba bertingkat. Mudah-mudahan, hasil kajian ini akan membantu pereka bentuk seni bina dan jurutera untuk memilih PCSP sebagai dinding yang memberikan ketahanan haba dan struktur penanggung beban yang lebih baik ke arah bangunan hijau dan lestari.



## ACKNOWLEDGEMENTS

Special Thanks to Almighty Allah the most gracious, the most merciful who have given me the strength and life to carry out this research. I would like to thank my humble supervisor Assoc. Prof. Farah Nora Aznieta Binti Abd.Aziz who has always worked relentlessly by sparing ample time for me in an effort to guide, support and sourced for fund toward the successful completion of this research experience. I must not forget to thank my co-supervisors Prof. Mohd Saleh Jaafar, Assoc. Prof. Farzad Hejazi and Dr. Nabilah Abu Bakar for their contributions toward the successful completion of this research.

My sincere gratitude goes to my dear mother for her special prayers and moral support that has encouraged me to start the program despite constraints. Special thanks also goes to my beloved wife for her encouragement, patience and prayers throughout my study period. Indeed, this success would not have been without your efforts and prayers.

Thank you all.

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Doctor of Philosophy. The members of the Supervisory Committee were as follows:

**Farah Nora Aznieta Binti Abd.Aziz, PhD**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**Mohd Saleh Jaafar, PhD**

Professor, Dato. Ir  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**Farzad Hejazi, PhD**

Associate Professor  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**Nabilah Abu Bakar, PhD**

Senior Lecturer  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

---

**ROBIAH BINTI YUNUS, PhD**

Professor and Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date:

## Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of the thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form ) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: \_\_\_\_\_



Date: \_\_\_\_\_

Name and Matric No.: Sani Mohammed Bida (GS45203)

## Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhere to.

Signature: \_\_\_\_\_

Name of Chairman  
of Supervisory  
Committee:

Associate Professor Dr Farah Nora Aznieta Binti Abd.Aziz

Signature: \_\_\_\_\_

Name of Member  
of Supervisory  
Committee:

Professor Dato Dr Ir Mohd Saleh Jaafar

Signature: \_\_\_\_\_

Name of Member  
of Supervisory  
Committee:

Associate Professor Dr Farzad Hejazi

Signature: \_\_\_\_\_

Name of Member  
of Supervisory  
Committee:

Dr Nabilah Abu Bakar

## TABLE OF CONTENTS

	<b>Page</b>
<b>ABSTRACT</b>	i
<b>ABSTRAK</b>	iii
<b>ACKNOWLEDGEMENTS</b>	v
<b>APPROVAL</b>	vi
<b>DECLARATION</b>	viii
<b>LIST OF TABLES</b>	xv
<b>LIST OF FIGURES</b>	xvi
<b>LIST OF ABBREVIATIONS</b>	xxi
<b>CHAPTER</b>	
<b>1 INTRODUCTION</b>	<b>1</b>
1.1 Background	1
1.1.1 Precast Concrete Sandwich Panel	3
1.2 Problem Statement	5
1.3 Objectives	7
1.4 Scope and Limitation	7
1.5 Layout of Thesis	8
<b>2 LITERATURE REVIEW</b>	<b>10</b>
2.1 Introduction	10
2.2 Precast Concrete Sandwich Panel	10
2.3 Components of Precast Concrete Sandwich Panel	13
2.3.1 Wythes	14
2.3.2 Shear Connectors	14
2.3.3 Reinforcement Bar/BRC Wire	19
2.3.4 Insulation	20
2.4 Structural Capacity of Precast Concrete Sandwich Panels (PCSPS)	20
2.4.1 Flexural Loading	20
2.4.2 Axial Loading	21
2.5 Putra Block	24
2.6 Thermal (Heat) Transfer	25
2.6.1 Thermal Performance	26
2.6.2 Types of Thermal Insulation Materials	27
2.6.3 Insulation Position and Thickness	29
2.6.4 Thermal Test Methods	31
2.6.5 Thermal Efficiency of Wythes Materials in PCSP	32
2.6.6 Thermal Efficiency of Shear Connection Materials	33
2.7 Alternative Design Approach to PCSP	34
2.8 Finite Element Analysis (FEA)	36
2.9 Optimization Techniques	37
2.9.1 Particle Swarm Optimization	37
2.9.2 Overview of PSO Method	38
2.9.3 Convergence Criteria	39
2.10 Summary of Review	40

<b>3</b>	<b>THERMAL PROPERTIES OF PRECAST CONCRETE SANDWICH PANELS</b>	<b>42</b>
3.1	Introduction	42
3.2	Materials	43
3.2.1	Concrete and mortar	43
3.2.2	Insulation	44
3.2.3	Steel Reinforcement and BRC Wire Mesh	45
3.2.4	Material for Putra Block	45
3.3	Specimen Description	46
3.3.1	PCSP Specimen	46
3.3.2	Putra Block Description	47
3.4	PCSP Specimen Preparation	48
3.4.1	Formwork Preparation and Reinforcement Works	48
3.4.2	Concrete Preparation	49
3.4.3	Panel Assembling	50
3.5	Instrumentation	51
3.6	Hot Box Test Setup	52
3.7	FEA Modelling	55
3.7.1	Material and Geometry	55
3.7.2	Modelling and Boundary Conditions	56
3.7.3	Governing Equations	56
3.8	Experimental Results	57
3.8.1	Environmental temperature	57
3.8.2	Surface Temperatures	58
3.8.3	Heat flux	64
3.9	Average Experimental Results	67
3.9.1	Average Surface Temperatures	67
3.9.2	Average Heat Flux	69
3.9.3	Thermal Resistance	70
3.10	Numerical Analysis Results and Discussion	71
3.10.1	Verification of Thermal Analysis Results	73
3.11	Discussions/ Summary	75
<b>4</b>	<b>STRUCTURAL INVESTIGATION METHODOLOGY</b>	<b>77</b>
4.1	Introduction	77
4.2	Specimen Design	78
4.3	Materials	80
4.4	Specimen Details	81
4.5	Specimen Preparation	85
4.5.1	Formwork Preparation and Reinforcement Works	85
4.5.2	Concrete Works	87
4.5.3	Panel Assembling	87
4.5.4	Handling Procedure	89
4.6	Flexural Test Setup	89
4.6.1	Instrumentations	90
4.6.2	Crack Patterns	90
4.7	Axial Test Setup	91
4.7.1	Instrumentations	91
4.7.2	Crack Patterns	92

4.8	Finite Element Analysis	92
4.8.1	Constitutive Model	93
4.8.2	Material Properties	95
4.8.3	Panel Discretization	96
4.8.4	Surface Interaction and Boundary Conditions	99
4.8.5	Mesh control	100
4.9	Summary	102
<b>5</b>	<b>STRUCTURAL INVESTIGATION: EXPERIMENTAL RESULTS AND DISCUSSION</b>	<b>103</b>
5.1	Introduction	103
5.2	Flexural Results	103
5.2.1	Load–Deflection Response	103
5.2.2	Span-Deflection Profile	104
5.2.3	Concrete Surface Strain	105
5.2.4	Shear Connector Strain	107
5.2.5	Steel Reinforcement/BRC Wire Strain	111
5.2.6	Crack Pattern	113
5.3	Axial Loading Results	115
5.3.1	Load–Deflection Profile	115
5.3.2	Panels Height vs Lateral Deflection Profile	118
5.3.3	Concrete Surface Strain	120
5.3.4	Strain in Steel Reinforcement Bars/BRC Wire	122
5.3.5	Strain in Steel Shear Connectors	124
5.3.6	Crack Patterns	126
5.4	Discussion for Structural Behavior	130
5.5	Summary	131
<b>6</b>	<b>FINITE ELEMENT ANALYSIS (FEA) RESULTS</b>	<b>132</b>
6.1	Introduction	132
6.2	FEA Results and Discussion for Panels under Flexural Loading	132
6.3	Crack Pattern for the FEA Models	136
6.4	FEA Results and Discussion for Panels under Axial Loading	139
6.5	Crack Pattern in the FEA Models	143
6.6	Discussions	146
6.6.1	Flexural Loading	146
6.6.2	Axial Loading	146
6.7	Summary	147
<b>7</b>	<b>EMPIRICAL EQUATION</b>	<b>149</b>
7.1	Introduction	149
7.2	Load Capacity of Solid Panel	149
7.3	Proposed Model using PSO Algorithm	151
7.3.1	Steps for implementing PSO Algorithm	152
7.3.2	Objective function	153
7.3.3	Optimization data	154
7.4	Proposed load capacity Equation using PSO Algorithm	158
7.4.1	Validation of the proposed load capacity model	159

7.5	Discussion	164
7.6	Summary	164
<b>8</b>	<b>CONCLUSIONS AND RECOMMENDATIONS</b>	<b>166</b>
8.1	Introduction	166
8.2	Conclusions	166
8.3	Recommendations	168
	<b>REFERENCES</b>	<b>169</b>
	<b>APPENDICES</b>	<b>178</b>
	<b>BIODATA OF STUDENT</b>	<b>203</b>
	<b>LIST OF PUBLICATIONS</b>	<b>204</b>





## LIST OF TABLES

<b>Table</b>		<b>Page</b>
1.1	Countries with their green/sustainable building indicator programs	3
2.1	Response of different shear connector types	15
2.2	Properties of materials used in PCSP	16
2.3	Properties of thermal insulation materials	29
2.4	Convergence criteria in PSO algorithm	40
3.1	Mix proportion	44
3.2	Specimen tested for thermal performance	46
3.3	Details of the Putra Blocks	47
3.4	Material properties used in FEA model	56
3.5	Temperature differences between hot	69
3.6	Thermal properties of specimens	71
3.7	Numerical and experimental surface temperature results for all specimen	75
4.1	Theoretical estimated level of composite action	79
4.2	Compressive strength of concrete cubes	81
4.3	Yield strength of steel reinforcements	81
4.4	Specimen description	82
4.5	Material properties	95
5.1	Experimental load-deflection results for panels under flexural loading	104
5.2	Experimental results for PCSP under flexural loading	113
5.3	Experimental results for PCSP under axial loading	116
5.4	Differential lateral displacement between the opposite LVDT	120
6.1	Verification results for panels under	136
6.2	Verification results for Panels under Axial	143
7.1	Predicted load capacity of proposed panel using ACI-318 equation	151
7.2	Parameters used in the PSO algorithm	156
7.3	Range of values for parameters used in the database	158

7.4	Result of the proposed model based on the objective functions	161
7.5	Summary of results of the proposed model	163
7.6	Results from the modelled equation	164



## LIST OF FIGURES

Figure		Page
1.1	Section through Precast Concrete Sandwich Panel	4
2.1	Section through Precast Concrete Sandwich Panel	11
2.2	Strain diagram for different PCSP system	12
2.3	Some precast concrete sandwich panels available in the market	13
2.4	Different shapes and types of shear connectors	15
2.5	Mode of deformation of shear connection embedded in concrete stud for (a) un-deformed section (b) deformed- fully effective stud (c) deformed- no stud	18
2.6	Insulation materials (a) polystyrene (b) Foam (c) plastic	20
2.7	PCSWP failure at the (a) top (b) bottom and crack at the top of the panel	23
2.8	Crushing at the top of the panel	24
2.9	Physical features of Putra Block	25
2.10	Classification of insulation materials	28
2.11	Location of insulation layer for (a) control (b) towards inside (c) middle and (d) outside the wall	31
2.12	Super-insulated timber wall panel with staggered connection	35
2.13	Three wythes wall panel	35
2.14	Ultimate flexural load versus vertical deflection	37
2.15	Particle swarm optimization approach	38
3.1	Methodology for thermal analysis investigation	43
3.2	Thickness of wythes and insulation used for the panels	44
3.3	Formwork showing reinforcement used in the specimen panels	45
3.4	Description of the proposed PCSP	47
3.5	Layout of Putra Block assembly for thermal test	48
3.6	Formwork preparation and steel works for specimen sized panels	49

3.7	Concrete (a) casting operation, (b) levelled top surface after 24 hours of casting and (c) panels ready for assembling.	50
3.8	PCSP assembling process (a) installation of insulation material, (b) Sample clamped together during assembling, (c) installation of longitudinal rebar and (d) assembled panels.	51
3.9	Instrumentation in the (a) hot side and (b) cold side of the Hotbox experimental.	52
3.10	Accessories used in the Hotbox experiment	52
3.11	Hotbox experimental setup	53
3.12	A plan and section through the Hotbox apparatus.	54
3.13	3D- model of specimen in Comsol Multiphysics	55
3.14	Average climatic and hot air temperature profile in the Hotbox from all experiments.	57
3.15	Hot Surface temperature of Panels (a) P0, (b) P2, (c) P3 and (d) P4	59
3.16	Hot Surface temperature of the blocks (a) Putra Block and (b) Putra FC	60
3.17	Cold Surface temperature of the PCSP (a) P0, (b) P2, (c) P3 and (d) P4	62
3.18	Cold Surface temperature of the blocks (a) Putra Block, and (b) Putra FC	63
3.19	Results of the 2 Heat flux sensors attached to the hot face of the PCSP (a) P0, (b) P2, (c) P3 and (d) P4	65
3.20	Results of the 2 Heat flux sensors attached to the hot face of the blocks (a) Putra Block and (b) Putra FC	66
3.21	Average Hot surface temperatures of PCSP and Putra Block.	67
3.22	Average Cold surface temperature of the proposed PCSPs and Putra Blocks.	68
2.33	Average Heat flux through the proposed panels and Blocks.	70
3.24	Temperature gradient of the specimen (a) control (P0), (b) P2 (c) P3 and (d) P4	72
3.25	Isothermal flux through the column stud (shear connection) for (a) control (P0_N), (b) P2_N (c) P3_N and (d) P4_N, respectively.	73

3.26	Numerical and experimental surface temperature results for control P0, (a) hot and (b) cold surfaces	74
3.27	Numerical and experimental surface temperature results for control P2, (a) hot and (b) cold surfaces	74
3.28	Numerical and experimental surface temperature results for control P3, (a) hot and (b) cold surfaces	75
3.29	Numerical and experimental surface temperature results for P4, (a) hot and (b) cold surfaces	75
4.1	Flow chart for the methodology of research	77
4.2	Proposed precast concrete sandwich panel P2, P3 and P4	83
4.3	Proposed control panel (P0)	84
4.4	Specimen preparation (a) Formwork, (b) BRC reinforcement, (c) guide rail, (d) Shear connectors, (e) handle installation and (f) location of handles	86
4.5	Concrete works (a) compaction method, (b) finishing, (c) ready for curing and (d) ready for assembling	87
4.6	Panel assembling process (a) insulation, (b) layers assembling, (c) erection in (d) placement of longitudinal shear bar (e) levelling the top grout area	89
4.7	Displacement transducers (LVDT) and strain gauge positions on panels under flexural load.	90
4.8	Displacement transducers (LVDT) and strain gauge positions on panels under axial loading.	92
4.9	Stress-strain relationships of concrete used in FEA model (Hanoon et al., 2017)	94
4.10	Panel discretization in FEA (a) one wythe, (b) wythe assembled with column studs (c) side view of assembled panel	97
4.11	Reinforcement (a) BRC merged with shear connectors for one wythe and (b) side view for rebar embedded in completed panel	98
4.12	Contact interaction (a) between layer surfaces and boundary condition for (b) flexural and (c) axial loadings	100
4.13	Meshed specimen for (a) flexural and (b) axial loadings	101
5.1	Load-deflection profile at Mid-span of panels P0F, P2F, P3F and P4F	104

5.2	Deflection profile of the proposed panels under flexural loading	105
5.3	Concrete surface strain results for panels (a) P0F, (b) P2F, (c) P3F and (d) P4F, under flexural loading	106
5.4	Shear connector strain results for panels (a) P0F, (b) P2F, (c) P3F and (d) P4F, respectively	108
5.5	Top and bottom shear connector strain results for panels (a) P0F, (b) P2F, (c) P3F and (d) P4F, respectively	110
5.6	Top and bottom BRC reinforcement strain results for panels (a) P0F, (b) P2F, (c) P3F and (d) P4F, respectively	112
5.7	Crack transition in the proposed PCSP under flexural loading.	114
5.8	Crack at the bottom sides of all the proposed PCSP	114
5.9	Crack at the top side of the proposed PCSP (P3F and P4F).	115
5.10	Load vs lateral deflection at the top, middle and bottom of SPCSSP under axial loading	117
5.11	Panel height vs lateral deflection profile	119
5.12	load vs strain profiles on concrete surface of PCSP under axial loading	121
5.13	Load vs strain curves for BRC located at top, middle and bottom of one side of PCSP under axial loading	123
5.14	Load vs shear connector strain at the top sides of the PCSP	125
5.15	Panel WP0 after failure	127
5.16	Panel WP2 after failure	128
5.17	Panel WP3 after failure	129
5.18	Panel P4 after failure	130
6.1	Load-deflection verification between FEA and the experimental results for control panel (P0F).	133
6.2	Load-deflection verification between FEA and the experimental results for panel (P2).	134
6.3	Load-deflection verification between FEA and the experimental results for panel P3F.	135
6.4	Load-deflection verification between FEA and the experimental results for panel P4.	136

6.5	Strain distribution and crack pattern in panel P0F	137
6.6	Strain distribution and crack pattern in panel P2	138
6.7	Strain distribution and crack pattern in panel P3	138
6.8	Strain distribution and crack pattern in panel P4	139
6.9	Load-deflection verification between FEA and the experimental results for panel WP0 under axial loading.	140
6.10	Load-deflection verification between FEA and the experimental results for panel WP4 under axial loading.	141
6.11	Load-deflection verification between FEA and the experimental results for panel WP3 under axial loading.	142
6.12	Load-deflection verification between FEA and the experimental results for panel P4 under axial loading.	143
6.13	The 3-dimensional model of the proposed (a) control panel, (b) WP4, (c) WP3 and (d) WP4 PCSP	145
7.1	Implementation of the PSO algorithm in MATLAB	153
7.2	The result of the three (3) objective function (a) Mean Absolute Error (MAE), (b) Mean Absolute Percentage Error (MAPE) and (c) Root Mean Square Error (RMSE) at different swarm sizes 10-40.	160

## LIST OF ABBREVIATIONS

q	Heat flux (W/m <sup>2</sup> )
R	Thermal resistance (m <sup>2</sup> K/W)
t	Thickness of panel
T	average temperature (K)
U	thermal transmittance (W/m <sup>2</sup> /K)
DOE	Department of Energy
EPBD	Directive on Energy Performance of Buildings
EU	European Union
Exp	Experimental
FEA	Finite Element Analysis
FRP	Fibre Reinforced Polymer
GBI	Green Building Index
HB	HotBox test
HRC	Housing Research Centre
PCSP	Precast concrete sandwich panel
P0	Control panel
P2	Panel with 200 mm connector spacing
P3	Panel with 300 mm connector spacing
P4	Panel with 400 mm connector spacing
TC	Cold surface
TH	Hot surface
T1_Num	Hot sample surface Numerical
T2_Num	Cold sample surface Numerical
T1_Exp	Hot sample surface Experimental
T2_Exp	Cold sample surface Experimental
US	United State
nZEB	near Zero energy buildings



# CHAPTER 1

## INTRODUCTION

### 1.1 Background

Innovative technology is required in the construction industry in order to provide more sustainable buildings that are practicable in the field. Therefore, precast component are more preferable to conventional building construction, which can shortened construction period without sacrificing quality of the product. In addition, the offsite or factory manufactured components has reduced the cost of production due to it shorten construction time and less labour.

In Malaysia, precast system is also known as Industrialised Building Systems (IBS) that is implemented in two stages, namely: (1) productions of modular parts in a yard/factory located near the site or transported and, (2) assemble for erection at the construction sites at in-situ position. IBS received greater attention after the Second World War particularly in the war-devastated countries due to rapid population growth, but its development and acceptance especially in Asia is still low. Beside Europe and USA, conventional construction technique is still predominant in most countries in Asia including Malaysia (Thanoon et al., 2003; Mydin et al., 2014). Survey conducted by Construction Industry Development Board (CIDB) Malaysia revealed that the adoption level of IBS in Malaysia stands at about 15% after over 40 years of initiation (Nawi et al., 2011). Hence, it is necessary for researchers in Malaysia to continue doing research on IBS development, compatibility and practicality to the local environment.

Apart from IBS, the need to produce sustainable buildings is growing. Sustainable building, also refer to as green building is a design philosophy that emphasizes on increasing efficiency in the use of resources such as energy, water, and materials in buildings. It reduces possible negative impacts on human life and the environment during it intended lifecycle through design, construction, operation and maintenance (Chua and Oh, 2011). Therefore, the most important sustainability feature in this research is the ability to use less energy during the intended design lifecycle of buildings. In tropical countries, most buildings use air-conditioners to control the temperature while, in Polar Regions, heaters are used that is subsequently becoming unsustainable.

Recently, global interest in energy conservation due to sustainability issues has called for a renewed demand for energy efficiency in building components. Because, substantial amount of thermal (heat) transfer through convection or radiation from external surrounding of the building into the inner part, thus, requiring power for cooling or heating (Demirboğa, 2003). In America, a significant share of energy consumption comes from housing with about 50-70% coming from heating and cooling or air-conditioning (Al-Homoud, 2005). In Europe, buildings account for about 30% of energy use which could be more in arid and semi-arid region of the word. In China, heating or cooling energy requirement in buildings account for about 15% of the total energy and

is increasing by the day (Jiang and Wu, 2010; Zeng et al., 2011). Generally, buildings account for about 25–40% of total energy consumption which is mostly due to space heating or air-conditioning (Široký et al., 2011; Zeng et al., 2011; Robinson et al., 2017). So, this has become a challenging phenomenon with far-reaching consequences on the environment.

Therefore, in an effort to conserve the energy, various governments' agencies have been working vigorously toward zero energy buildings (ZEBs) which is becoming part of energy policy in several countries; in the Europe, EU Directive on Energy Performance of Buildings (EPBD) was set to the year 2020 in which all new buildings are expected to comply with “nearly zero energy buildings” (Sartori et al., 2012). In the United States, US Department of Energy (DOE) unveiled its strategic master plan toward “marketable zero energy homes in the year 2020 and commercial zero energy buildings in 2025”, while in Malaysia, the government introduced Green Building Index (GBI) in 2009 whose target is to achieve 100 green rated factories and more in buildings by the year 2020 (Chua and Oh, 2011). Similar policies have been enacted in many countries as shown in Table 1.1.

Therefore, to achieve this targets, a more practical and sustainable approach through minimization of thermal (heat) transfer between outside and inner parts of buildings such as the provision of insulation layer between the building components refer to as precast concrete sandwich panel (PCSP) could be a way out. This is consistent with the report by Gervásio et al. (2010), who highlighted that material and energy efficiency are the two main factors contributing to the building's sustainability. Therefore, optimization of energy use such as in heating and cooling during building's service period by introducing an insulation material into the building is one way of improving the energy efficiency in buildings.


**Table 1.1: Countries with their green/sustainable building indicator programs**

Country	Green Building Program	Year of Initiation	Achievement to date
Australia	Green Star	2003	1900 Green rated projects
Brazil	Aqua/ LEED Brasil	2010	1,308 registered projects
Canada	LEED Canada/Green Globes	2000	2576
China	GBAS	2006	-
Finland	PromisE	1998	-
France	HQE	1996	16000
Germany	DGNB	2007	2800 certificates
Hong Kong	HKBEAM	2009	Over 1000
India	Indian Green Building Council (IGBC)	2007	Over 4794 buildings
Indonesia	Indonesian Green building Council (Greenship)	2009	-
Italy	Protocollo Itaca	2000	-
Japan	CASBEE	2004	500 Over buildings
Korea	KGBC	2000	1786
Malaysia	Green Building Index (GBI)	2008	Over 300 projects
Mexico	LEED Mexico	2000	Over 94000
Netherlands	BREEAM Netherlands	-	-
New Zealand	Green Star NZ	2005	153 buildings
Portugal	Lider A	2005	-
Singapore	Green Mark	2005	Over 360 projects
South Africa	Green Star SA	2007	-
United States	Build it Green/LEED/IGCC/	1993	-
United Kingdom	BREEAM	1990	-
United Arab Emirate	Estidama	2009	-
Jordan	EDAMA	2009	-
Czech Republic	SBToolCZ	2005	-

### 1.1.1 Precast Concrete Sandwich Panel

Generally, sandwich refers to the combination of different material together either in layers or as a matrix to form a composite. This approach can be implemented on various

materials and systems depending on its intended application. Precast concrete sandwich panels (PCSP) are composite system that consists of two or more layers of concrete called wythes which are separated by layer of insulation as shown in Figure 1.1. The wythes are connected to each other to form an assembly system through steel connectors, concrete webs or a combination of both (Einea et al., 1991; Benayoune et al., 2006).



**Figure 1.1: Section through Precast Concrete Sandwich Panel (Hamed, 2016)**

The existing PCSPs are designed with continuous shear connection, which causes thermal bridges across the layers (wythes) as shown in Figure 1.1. The thermal bridge significantly reduces the thermal performance of PCSP system. Therefore, most research interest in PCSP have been focused on the use of alternative material such as fibre reinforced polymers (FRP) other than conventional steel as shear connectors to reduce the effect of thermal bridge. Some of the FRP materials used as shear connectors are carbon fibre reinforced polymers (CFRP) (Cho et al., 2010; Bunn, 2011; Frankl et al., 2011; Hodicky et al., 2014), Basalt fibre reinforced polymers (BFRP), Glass fibre reinforced polymers (GFRP) (Maximos et al., 2007; Pantelides et al., 2008; Seo et al., 2013; Woltman et al., 2013; Corradi et al., 2014; Choi et al., 2015; Kazem et al., 2015; Kim and You, 2015; Kang and Kim, 2016). However, these materials are expensive and will increase the cost of PCSP, coupled with structural effects such as high bond slip and high brittleness failure when used.

The continuous shear connection are still in use and most of the previous works reported are on the structural performance of the panel alone. The influence of certain parameters such as slenderness ratio and aspect ratio on structural performance have been established (Bush and Stine, 1994; Benayoune et al., 2006; Benayoune et al., 2007; Benayoune et al., 2008; Gara et al., 2012; Carbonari et al., 2013). However, more research works are needed in the area of shear connection design which affect both the thermal and the structural performance of PCSP system.

Besides changing the shear connector materials, effort has been made to improve the thermal performance of PCSP by replacing the concrete wythes with foamed concrete due to its low thermal conductivity (Mohamad et al., 2011; Mohamad and Hassan, 2013; Amran et al., 2016a; Amran et al., 2018). Foamed concrete is defined as a light cellular concrete produced from mixture of foaming agent in mortar which contains randomly distributed air voids and have a density range of 400–1850 kg/m<sup>3</sup> (Amran et al., 2015). This material result in a lightweight panels, but, is associated with structural effects such as crushing, sudden failure and high porosity which absorbs water and reduce the thermal performance, that shows limited application particularly in weather exposed condition.

## 1.2 Problem Statement

In an effort to conserve the energy, various governments' agencies have been working tirelessly toward a more sustainable and energy efficient buildings (Wells et al., 2018). Currently, energy efficiency in buildings has formed part of legislation as policy in many countries including Malaysia (Zuo and Zhao, 2014). In particular, the Malaysian government has targeted the year 2020 as a dateline for any new building or buildings undergoing major repairs to satisfy energy performance requirement before approval (Chua and Oh, 2011). However, despite this target, most building construction in Malaysia are still predominantly conventional masonry walls and solid concrete panels. This building technology exhibit high thermal transmittance and conductivity (Soares et al., 2013).

In Malaysia a few agencies discussed on this issue, the Malaysian Government Green Building Index (GBI) master plan, which is given the responsibility to assess, certify, license and approve buildings that are deemed thermally efficient highlighted the needs of using green material and thermal efficient designs for buildings (GBI, 2018). Apart from that, the Malaysian Green Building Confederation has reported that after over 50 years of rapid industrialization with an annual growth of between 5% to 9%, most of the successes recorded are unsustainable, in another word, it require holistic sustainable approach especially in terms of thermal performance (MGBC, 2018). Furthermore, MS1525 (2014) was enacted to ensure energy sustainability in the building sector but did not mentioned on the thermal efficiency of sandwich panel.

According to Gervásio et al. (2010), the most sustainable way to develop thermally efficient building system is through the use of insulation material known as precast concrete sandwich panels (PCSP). These panels are more thermally efficient and are used as non-load bearing placed as partition walls (Losch et al., 2011). While, most building components used in Malaysia construction industry are slabs, beams and columns which are thermally inefficient (Mydin et al., 2014).

Development of load-bearing PCSP requires high level of shear connection which in turn reduce thermal performance (Benedetti et al., 2018). In Malaysia, load-bearing PCSP application mainly focuses on single and double storey buildings (Badir et al., 2002). However, the limited space in city centres and the need for urbanisation has called for high rise and structural buildings. Therefore, if structural building made of PCSP can be

developed, the dreamed GBI master plan would easily be achieved. Therefore, the main component of PCSP that ensure load bearing capacity and composite action is the shear connectors and a concrete section that connect the two wythes together.

The most predominant shear connectors use in the existing PCSP are shear steel truss, double truss, bend up bars, hooks, pins and continuous truss shear connection (Naito et al., 2011). These connectors are continuously connected from layer or wythe to another through the insulation which causes thermal bridges and subsequently reduces the thermal performance of the panel (Tomlinson and Fam, 2015). Besides, according to Amran et al. (2015), when 0.08% of direct steel pin shear connection is used, thermal reduction of about 77% is observed. Hence, the need to avoid the effect of thermal bridges due to the shear connectors is necessary in PCSP in order to improve its thermal efficiency.

The other approach is the staggered thermal path reported by Zarr et al. (1987) who used timber PCSP and successfully increase the thermal efficiency of the panel. This concept was then repeated on three layered PCSP without shear connectors by (Lee and Pessiki, 2006) and reported better thermal efficiency than the conventional PCSP. Unfortunately, it is non-load bearing and un-economical due to excessive thickness and the production method is un-practicable.

Despite the type of shear connectors, its material will also influence the thermal and strength behaviour of PCSP. As mentioned earlier, many researches had been carried out using FRP material due to its lower thermal conductivity behaviour. This approach is considered to reduce the effect of thermal bridges. Significant improvements were recorded in terms of strength, but bond slip and brittle failure between the shear connectors and concrete were observed. This can be improved by providing thicker concrete wythes sections to enable sufficient embedment length of the shear connectors. However, the panel becomes heavier and leads to uneconomical section. Apart from that, FRP shear connectors failed in sandwich panels at strength far below its tensile capacity and in brittle mode making it less practical (Hodicky et al., 2014).

Another approach to improving the thermal performance of the PCSP is by replacing the concrete wythes with Foamed and/or Aerated concretes. Even though, the thermal properties are improved, a significant reduction in strength parameters coupled with the sudden crushing of the specimen has been recorded (Mohamad and Muhammad, 2011; Amran et al., 2016b). Moreover, this material absorbs much more water than the conventional concrete that contributes to its high thermal performance. According to Steiger and Hurd (1978), when a unit weight of concrete increase by 1% due to water absorption, the thermal conductivity increases by 5%, making porous materials like foamed concrete exhibit higher values of thermal conductivity.

Many investigations on PCSP under flexural tests, shear tests and tests under combined shear and flexure abound in the literature (Huanzhi et al., 2017). However, investigations on PCSP under axial load are limited due to the high capacity equipment required and the cost of building full-scale panels (Benayoune et al., 2007). Based on these works of

literature, it is obvious that most of the existing PCSP are excellent in thermal efficiency when it is made for the non-load-bearing panel. But, when it is designed as load-bearing PCSP, the thermal efficiency need to be compensated in order to allow the strength of the PCSP to reached its load-bearing performance. Thus, this research is to study the load-bearing PCSP that will not compensate the thermal efficiency of the wall. Hence, the following research questions are highlighted:

1. Is the staggered thermal path method suitable for load-bearing PCSP?
2. If the thermal path method works, what is the appropriate spacing between the shear connectors that fulfilled the energy performance requirement as well as the structural performance?
3. What are the axial and flexural capacity of the load-bearing PCSP with different spacing of the connectors?
4. Is there any established equation to estimate the axial load capacity of PCSP?

### **1.3 Objectives**

Based on the above-mentioned research questions, the aim of this research is to develop a thermally efficient load-bearing PCSP that satisfy both thermal and structural performances. To achieve this, the work tasks consists of four main objectives:

1. Three different shear connector spacing will be studied using staggered thermal path methods to determine the optimum thermal performance of PCSP and the results will then be verified using Finite Element Analysis (FEA) method.
2. To determine the structural performance of the proposed PCSP with staggered shear connectors when subjected to flexural and axial loads.
3. To verify the structural behaviour of the PCSP using Finite Element Analysis (FEA) method when subjected to flexural and axial loads.
4. To propose an empirical equation for axially loaded PCSP.

### **1.4 Scope and Limitation**

This research covers experimental work, finite element modelling and empirical equation modelling on precast concrete sandwich panels. The experimental work involves thermal performance test, flexural test and axial load test. Each of the tests consists of four (4) PCSP. For the thermal test, the specimen size is 500 mm x 500 mm x 150 mm, while, for the flexural test is 2500 mm x 1650 mm x 150 mm and 3000 x 1650 x 150 mm for the axial test. All the specimens are made from 40 MPa concrete strength and minimum reinforcements are provided. The shear connector studs are cast with mortar of 40 MPa. Three different staggered shear connector spacing is studied; 200mm, 300, and 400mm.

The scope of the thermal test covers PCSPs with staggered shear connectors and Foamed Putra Blocks and Mortar Putra Block for comparison purposes. The test specimen is limited to small-scale to accommodate the test set-up. The results are verified by Finite element Analysis (FEA) using COMSOL Multi-physics, a software to develop 3D-

models for the thermal performance verification. In the numerical modelling, insulation of the boundary conditions was ensured using the default full-insulation settings of the software. While for the structural tests, specimens are different in size to accommodate the size limitation of the test frame. The numerical analysis using Abaqus CAE was used to validate the experimental results of both flexural and axial tests.

Since the theoretical equation regarding axial load capacity is scarce in literature, the existing equation for solid wall panel according to ACI 318-M (2011) is statistically modified using particle swarm optimization (PSO) method. This is done to incorporate the appropriate parameters to improve the equation for use in PCSP. The statistical analysis was carried out with the aid of MATLAB software using data obtained from experimental, FEA and literature. The PSO analysis takes into account two main parameters that influence the behaviour of the PCSP namely an insulation material and shear connection. The proposed equation is limited to estimation of axial load capacity for PCSP only.

## **1.5 Layout of Thesis**

This section presents the layout of thesis and the content of each chapter.

Chapter one presents the background to the need for the new/modification of the existing precast concrete sandwich panels. The objectives, problem statement, scope and limitation of the research work are also presented.

Chapter two present the literature review on general precast concrete panels from the conventional precast normal weight walls to the current state of the art sandwich systems and the need to further modify the current systems toward sustainable and thermally efficient structural system.

Chapter three discusses in detail the experimental and FEA results obtained on the thermal (heat transfer) analysis of the proposed sandwich panels. The investigation include; material, methodology, experimental and FEA analysis and verification of the results.

Chapter four present the methodology used to carry out the experimental and FEA on the structural performance of the proposed PCSPs. The procedure employed and design approach used. Standard test methods adopted during the experiments are also presented. The methodology include experimental and numerical analysis used for the structural tests.

Chapter five presents the experimental results of the proposed panels under structural test (flexural and axial loadings). Also, failure patterns and load capacity of the panels are discussed in details.



Chapter six presents the FEA results of the proposed panels under structural test (flexural and axial loadings). Also, failure patterns and load capacity of the panels are discussed in details.

Chapter seven presents the analytical equation developed for the structural capacity of the panels under axial loading. The analytical equation is developed using Particle swarm Optimization Approach with the aid of MatLab software.

Chapter eight presents the discussion, conclusions and recommendations based on the results achieved. Recommendation for further investigation or action are proposed for continuous sustainable development.



## REFERENCES

- Abang Ali, A., & Abdul Kadir, M. (1987). Strength properties and structural performance of interlocking hollow block walls. *Jurnal Institut Jurutera Malaysia*, 25-35.
- Abdelrahman, M., Said, S., Ahmad, A., Inam, M., & Abul-Hamayel, H. (1990). Thermal conductivity of some major building materials in Saudi Arabia. *Journal of Thermal Insulation*, 13(4), 294-300.
- Abdou, A. A., & Budaiwi, I. M. (2005). Comparison of thermal conductivity measurements of building insulation materials under various operating temperatures. *Journal of Building Physics*, 29(2), 171-184.
- ACI 318-M. (2011). *Building Code Requirements for Structural Concrete (ACI 318-11M) and Commentary*.
- Al-Abidi, A. A., Mat, S. B., Sopian, K., Sulaiman, M., & Mohammed, A. T. (2013). CFD applications for latent heat thermal energy storage: a review. *Renewable and Sustainable Energy Reviews*, 20, 353-363.
- Al-Ajlan, S. A. (2006). Measurements of thermal properties of insulation materials by using transient plane source technique. *Applied thermal engineering*, 26(17-18), 2184-2191.
- Al-Hammad, A.-M., Abdelrahman, M., Grondzik, W., & Hawari, A. (1994). A comparison between actual and published K-values for Saudi insulation materials. *Journal of Thermal Insulation and Building Envelopes*, 17(4), 378-385.
- Al-Homoud, M. S. (2005). Performance characteristics and practical applications of common building thermal insulation materials. *Building and environment*, 40(3), 353-366.
- Al-Rubaye, S., Sorensen, T., Olsen, J., & Maguire, M. (2018). Evaluating elastic behavior for partially composite precast concrete sandwich wall panels Date Published: September-October 2018.
- Al-Sanea, S. A., & Zedan, M. (2011). Improving thermal performance of building walls by optimizing insulation layer distribution and thickness for same thermal mass. *Applied Energy*, 88(9), 3113-3124.
- Amran, Y. M., Ali, A. A., Rashid, R. S., Hejazi, F., & Safiee, N. A. (2016a). Structural behavior of axially loaded precast foamed concrete sandwich panels. *Construction and Building materials*, 107, 307-320.
- Amran, Y. M., Farzadnia, N., & Ali, A. A. (2015). Properties and applications of foamed concrete; a review. *Construction and Building materials*, 101, 990-1005.
- Amran, Y. M., Rashid, R. S., Hejazi, F., Ali, A. A., Safiee, N. A., & Bida, S. M. (2018). Structural Performance of Precast Foamed Concrete Sandwich Panel Subjected to Axial Load. *KSCE Journal of Civil Engineering*, 22(4), 1179-1192.
- Amran, Y. M., Rashid, R. S., Hejazi, F., Safiee, N. A., & Ali, A. A. (2016b). Structural behavior of laterally loaded precast foamed concrete sandwich panel. *International Journal of Civil, Environmental, Structural, Construction and Architectural Engineering*, 10(3).
- Ascione, L., & Feo, L. (2000). Modeling of composite/concrete interface of RC beams strengthened with composite laminates. *Composites Part B: Engineering*, 31(6-7), 535-540.
- Asdrubali, F., & Baldinelli, G. (2011). Thermal transmittance measurements with the hot box method: Calibration, experimental procedures, and uncertainty analyses of three different approaches. *Energy and buildings*, 43(7), 1618-1626.

- ASHRAE Handbook. (1997). American society of heating, refrigerating and air-conditioning engineers. *Inc.: Atlanta, GA, USA.*
- ASTM C518. (2004). Standard test method for steady-state thermal transmission properties by means of the heat flow meter apparatus *ASTM C.*
- ASTM C1155/C1046. (2013). Standard Practice for Determining Thermal Resistance of Building Envelope Components from the In-Situ Data. *ASTM C.*
- ASTM C1363. (2011). Standard test method for thermal performance of building materials and envelope assemblies by means of a hot box apparatus. *ASTM C, 1363.*
- Badir, Y. F., Kadir, M. A., & Hashim, A. H. (2002). Industrialized building systems construction in Malaysia. *Journal of architectural engineering, 8(1), 19-23.*
- Bai, Q. (2010). Analysis of particle swarm optimization algorithm. *Computer and information science, 3(1), 180.*
- Bazant, Z. P., & Becq-Giraudon, E. (2002). Statistical prediction of fracture parameters of concrete and implications for choice of testing standard. *Cement and concrete research, 32(4), 529-556.*
- Benayoune, A., Aziz, A., Trikha, D., & Abdullah, A. (2001). Behaviour of precast reinforced concrete sandwich panels with continuous shear truss connectors. *J Inst Eng (Malaysia), 62(3), 59-66.*
- Benayoune, A., Samad, A., Aziz, A., Trikha, D., Ali, A., Abdullah, A., & Monayem Akhand, A. (2004). Precast reinforced concrete sandwich panel as an industrialised building system.
- Benayoune, A., Samad, A. A., Ali, A. A., & Trikha, D. (2007). Response of pre-cast reinforced composite sandwich panels to axial loading. *Construction and Building materials, 21(3), 677-685.*
- Benayoune, A., Samad, A. A., Trikha, D., Ali, A. A., & Ellinna, S. (2008). Flexural behaviour of pre-cast concrete sandwich composite panel—experimental and theoretical investigations. *Construction and Building materials, 22(4), 580-592.*
- Benayoune, A., Samad, A. A., Trikha, D., Ali, A. A., & Ashrabov, A. (2006). Structural behaviour of eccentrically loaded precast sandwich panels. *Construction and Building materials, 20(9), 713-724.*
- Benedetti, M., Gervasio, P., Luscietti, D., Pilotelli, M., & Lezzi, A. M. (2018). Point Thermal Transmittance of Rib Intersections in Concrete Sandwich Wall Panels. *Heat Transfer Engineering, 1-10.*
- Blum, C., & Li, X. (2008). Swarm intelligence in optimization. *Swarm Intelligence. Natural Computing Series, 43-85.*
- Bolattürk, A. (2006). Determination of optimum insulation thickness for building walls with respect to various fuels and climate zones in Turkey. *Applied thermal engineering, 26(11-12), 1301-1309.*
- BS EN 206-1. (2000). Eurocode2: Concrete—Part. 1: Specification, Performance, Production and Conformity. *BS-EN-206-1.*
- BS EN 12390-5. (2009). 12390-5. Testing hardened concrete—Part 5: Flexural strength of test specimens. *British Standards Institution-BSI and CEN European Committee for Standardization.*
- BS EN 12664. (2001). BS EN 12664: 2001: Thermal performance of building materials and products—determination of thermal resistance by means of guarded hot plate and heat flow meter methods—dry and moist products of medium and low thermal resistance: BSI Milton Keynes, UK.

- BS EN 12939. 12939: 2001 Thermal performance of building materials and products. *Determination of thermal resistance by means of guarded hot plate and heat flow meter methods. Thick products of high and medium thermal resistance.*
- Bunn, W. (2011). CFRP Grid/Rigid Foam Shear Transfer Mechanism for Precast, Prestressed Concrete Sandwich Wall Panels.
- Bush Jr, T. D., & Wu, Z. (1998). Flexural analysis of prestressed concrete sandwich panels with truss connectors. *PCI journal*, 43(5).
- Bush, T. D., & Stine, G. L. (1994). Flexural behavior of composite precast concrete sandwich panels with continuous truss connectors. *PCI journal*, 39(2).
- Carbonari, G., Cavalaro, S., Cansario, M., & Aguado, A. (2013). Experimental and analytical study about the compressive behavior of eps sandwich panels. *Materiales de Construcción*, 63(311), 393-402.
- Chinneck, J. W. (2006). Practical optimization: a gentle introduction. *Systems and Computer Engineering*, Carleton University, Ottawa. <http://www.sce.carleton.ca/faculty/chinneck/po.html>.
- Cho, K., Park, S. Y., Kim, S. T., Cho, J.-R., & Kim, B.-S. (2010). Shear connection system and performance evaluation of FRP-concrete composite deck. *KSCE Journal of Civil Engineering*, 14(6), 855-865.
- Choi, G.-S., Kang, J.-S., Jeong, Y.-S., Lee, S.-E., & Sohn, J.-Y. (2007). An experimental study on thermal properties of composite insulation. *Thermochimica Acta*, 455(1-2), 75-79.
- Choi, K.-B., Choi, W.-C., Feo, L., Jang, S.-J., & Yun, H.-D. (2015). In-plane shear behavior of insulated precast concrete sandwich panels reinforced with corrugated GFRP shear connectors. *Composites Part B: Engineering*, 79, 419-429.
- Chua, S. C., & Oh, T. H. (2011). Green progress and prospect in Malaysia. *Renewable and Sustainable Energy Reviews*, 15(6), 2850-2861.
- Corradi, M., Borri, A., Castori, G., & Sisti, R. (2014). Shear strengthening of wall panels through jacketing with cement mortar reinforced by GFRP grids. *Composites Part B: Engineering*, 64, 33-42.
- Cox, L., & van Dijk, S. (2002). Foam concrete: a different kind of mix. *Concrete*, 36(2).
- Dally, J. W., & Riley, W. F. (1965). Experimental stress analysis.
- Darwin, D., Manning, D., Hognestad, E., Beeby, A., Rice, P., & Ghowrwal, A. (1985). Debate: Crack width, cover, and corrosion. *Concrete International*, 7(5), 20-35.
- Davies, M. (1997). Wall transient heat flow using time-domain analysis. *Building and environment*, 32(5), 427-446.
- Demirboğa, R. (2003). Influence of mineral admixtures on thermal conductivity and compressive strength of mortar. *Energy and buildings*, 35(2), 189-192.
- Doğan, E., & Saka, M. P. (2012). Optimum design of unbraced steel frames to LRFD-AISC using particle swarm optimization. *Advances in Engineering Software*, 46(1), 27-34.
- Eberhart, R., & Kennedy, J. (1995). *A new optimizer using particle swarm theory*. Paper presented at the Micro Machine and Human Science, 1995. MHS'95., Proceedings of the Sixth International Symposium on.
- Einea, A., Salmon, D., Fogarasi, G., Culp, T., & Tadros, M. (1991). State of-the-art of precast sandwich panel system. *PCI journal*, 36(6), 90-101.
- Einea, A., Salmon, D. C., Tadros, M. K., & Culp, T. (1994). A new structurally and thermally efficient precast sandwich panel system. *PCI journal*, 39(4).
- Ekici, B. B., Gulten, A. A., & Aksoy, U. T. (2012). A study on the optimum insulation thicknesses of various types of external walls with respect to different materials, fuels and climate zones in Turkey. *Applied Energy*, 92, 211-217.

- EN 1992-1-1. (1992). *Eurocode2: Design of concrete structures-Part 1-1: design of building and civil engineering structures in plain, reinforced and pre-stressed concrete*. Retrieved from
- Fiber, C., & Enable, C. (2007). New carbon fiber reinforcement advances sandwich wall panels. *Structure*, 61.
- Frankl, B. A., Lucier, G. W., Hassan, T. K., & Rizkalla, S. H. (2011). Behavior of precast, prestressed concrete sandwich wall panels reinforced with CFRP shear grid. *PCI journal*, 56(2), 42-54.
- Gara, F., Ragni, L., Roia, D., & Dezi, L. (2012). Experimental tests and numerical modelling of wall sandwich panels. *Engineering Structures*, 37, 193-204.
- GBI. (2018). *new.greenbuildingindex.org*.
- Gerlich, V., Sulovská, K., & Zálešák, M. (2013). COMSOL Multiphysics validation as simulation software for heat transfer calculation in buildings: Building simulation software validation. *Measurement*, 46(6), 2003-2012.
- Gervásio, H., Santos, P., da Silva, L. S., & Lopes, A. (2010). Influence of thermal insulation on the energy balance for cold-formed buildings. *Advanced Steel Construction*, 6(2), 742-766.
- Haavi, T., Jelle, B. P., & Gustavsen, A. (2012). Vacuum insulation panels in wood frame wall constructions with different stud profiles. *Journal of Building Physics*, 36(2), 212-226.
- Hacker, J. N., De Saulles, T. P., Minson, A. J., & Holmes, M. J. (2008). Embodied and operational carbon dioxide emissions from housing: A case study on the effects of thermal mass and climate change. *Energy and buildings*, 40(3), 375-384.
- Hamed, E. (2016). Modeling, Analysis, and Behavior of Load-Carrying Precast Concrete Sandwich Panels. *Journal of Structural Engineering*, 142(7), 04016036.
- Hanoon, A. N., Jaafar, M., Hejazi, F., & Aziz, F. N. A. (2017). Strut-and-tie model for externally bonded CFRP-strengthened reinforced concrete deep beams based on particle swarm optimization algorithm: CFRP debonding and rupture. *Construction and Building materials*, 147, 428-447.
- Hata, R. M., Hassan, R., Idayu, H., & Arshad, F. (2016). The thermal conductivity of selected tropical timber species using hot box method. *Jurnal Teknologi*, 78(5-4), 7-12.
- Henin, E., Morcou, G., & Tadros, M. K. (2013). Precast/prestressed concrete sandwich panels for thermally efficient floor/roof applications. *Practice Periodical on Structural Design and Construction*, 19(3), 04014013.
- Hodicky, K., Sopal, G., Rizkalla, S., Hulin, T., & Stang, H. (2014). Experimental and numerical investigation of the FRP shear mechanism for concrete sandwich panels. *Journal of Composites for Construction*, 19(5), 04014083.
- Huang, J.-Q., & Dai, J.-G. (2018). Direct Shear Tests of Glass Fiber Reinforced Polymer Connectors for Use in Precast Concrete Sandwich Panels. *Composite Structures*.
- Huanzhi, J., Zhengxing, G., & Jiabin, L. (2017). Composite behavior of sandwich panels with W-shaped SGFRP connectors. *KSCE Journal of Civil Engineering*, 1-11.
- ISO 8301. (1991). 8301, Thermal insulation—Determination of steady-state thermal resistance and properties—Heat flow meter apparatus. *International Organization for Standardization*.
- ISO 9869-1. (2014). Thermal insulation, Building elements, In-situ measurement of thermal resistance and thermal transmittance-Part 1: Heat flow meter method. *International Organization for Standardization*.

- Jelle, B. P. (2011). Traditional, state-of-the-art and future thermal building insulation materials and solutions—Properties, requirements and possibilities. *Energy and buildings*, 43(10), 2549-2563.
- Jiang, Y., & Wu, X. (2010). Annual report on China building energy efficiency. *China Architecture & Building Press, Beijing (2010)(in Chinese)*.
- Jones, M., & McCarthy, A. (2005). Preliminary views on the potential of foamed concrete as a structural material. *Magazine of concrete research*, 57(1), 21-31.
- Jones, M., & McCarthy, A. (2006). Heat of hydration in foamed concrete: Effect of mix constituents and plastic density. *Cement and concrete research*, 36(6), 1032-1041.
- Joseph, J. D. R., Prabakar, J., & Alagusundaramoorthy, P. (2017). Precast concrete sandwich one-way slabs under flexural loading. *Engineering Structures*, 138, 447-457.
- Joseph, J. D. R., Prabakar, J., & Alagusundaramoorthy, P. (2019). Flexural Behavior of Concrete Sandwich Panels Under Punching Load and Four-Point Bending—Experimental and Analytical Study *Recent Advances in Structural Engineering, Volume 2* (pp. 771-781): Springer.
- Kang, W.-H., & Kim, J. (2016). Reliability-based flexural design models for concrete sandwich wall panels with continuous GFRP shear connectors. *Composites Part B: Engineering*, 89, 340-351.
- Kazem, H., Bunn, W. G., Seliem, H. M., Rizkalla, S. H., & Gleich, H. (2015). Durability and long term behavior of FRP/foam shear transfer mechanism for concrete sandwich panels. *Construction and Building materials*, 98, 722-734.
- Kearsley, E., & Wainwright, P. (2001a). The effect of high fly ash content on the compressive strength of foamed concrete. *Cement and concrete research*, 31(1), 105-112.
- Kearsley, E., & Wainwright, P. (2001b). Porosity and permeability of foamed concrete. *Cement and concrete research*, 31(5), 805-812.
- Kearsley, E. P. (1999). *The effect of high volumes of ungraded fly ash on the properties of foamed concrete*. University of Leeds.
- Kennedy, J. (2006). Swarm intelligence, handbook of nature-inspired and innovative computing. A. Zomaya, ed, 187-219.
- Kennedy, J. (2010). Particle swarm optimization Encyclopedia of Machine Learning (pp. 760-766): Springer.
- Kim, J., & You, Y.-C. (2015). Composite behavior of a novel insulated concrete sandwich wall panel reinforced with GFRP shear grids: Effects of insulation types. *Materials*, 8(3), 899-913.
- Kim, Y. J., & Allard, A. (2014). Thermal response of precast concrete sandwich walls with various steel connectors for architectural buildings in cold regions. *Energy and buildings*, 80, 137-148.
- Kochhar, G. S., & Manohar, K. (1995). *Effect of moisture on thermal conductivity of fibers biological insulating materials*. Paper presented at the Thermal Performance of the Exterior Envelopes of Building VI. ASHRAE/DOE Conference.
- Kontoleon, K., Theodosiou, T. G., & Tsikaloudaki, K. (2013). The influence of concrete density and conductivity on walls' thermal inertia parameters under a variety of masonry and insulation placements. *Applied Energy*, 112, 325-337.
- Kossecka, E., & Kosny, J. (2002). Influence of insulation configuration on heating and cooling loads in a continuously used building. *Energy and buildings*, 34(4), 321-331.

- Kossecka, E., & Kosny, J. (2008). Hot-Box Testing of Building Envelope Assemblies— A Simplified Procedure for Estimation of Minimum Time of the Test. *Journal of Testing and Evaluation*, 36(3), 242-249.
- Kripanarayanan, K. (1977). *Interesting aspects of the empirical wall design equation*. Paper presented at the Journal Proceedings.
- Kulkarni, R. V., & Venayagamoorthy, G. K. (2011). Particle swarm optimization in wireless-sensor networks: A brief survey. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 41(2), 262-267.
- Lameiras, R., Barros, J., Valente, I. B., & Azenha, M. (2013). Development of sandwich panels combining fibre reinforced concrete layers and fibre reinforced polymer connectors. Part I: Conception and pull-out tests. *Composite Structures*, 105, 446-459.
- Larson, D., & Benner, S. (1985). *Field and laboratory studies of the thermal resistance of moist building insulation systems*. Paper presented at the Thermal Performance of the Exterior Envelopes of Building III, ASHRAE/DOE/BTECC Conference.
- Lavanya, D., & Udgata, S. K. (2011). *Swarm intelligence based localization in wireless sensor networks*. Paper presented at the International Workshop on Multi-disciplinary Trends in Artificial Intelligence.
- Lee, B.-J., & Pessiki, S. (2004). Analytical investigation of thermal performance of precast concrete three-wythe sandwich wall panels. *PCI journal*, 49(4).
- Lee, B.-J., & Pessiki, S. (2006). Thermal Behavior of Precast Prestressed Concrete Three-Wythe Sandwich Wall Panels *Building Integration Solutions* (pp. 1-15).
- Lee, B.-J., & Pessiki, S. (2008). Experimental evaluation of precast, prestressed concrete, three-wythe sandwich wall panels. *PCI journal*, 53(2).
- Li, Z., Kulkarni, S., & Shah, S. (1993). New test method for obtaining softening response of unnotched concrete specimen under uniaxial tension. *Experimental Mechanics*, 33(3), 181-188.
- Losch, E. D., Hynes, P. W., Andrews Jr, R., Browning, R., Cardone, P., Devalapura, R., Donahey, R., Freedman, S., Gleich, H. A., & Goettsche, G. (2011). State of the art of precast/prestressed concrete sandwich wall panels. *PCI journal*, 56(2), 131-176.
- Maximos, H. N., Pong, W. A., Tadros, M. K., & Martin, L. (2007). Behavior and design of composite precast prestressed concrete sandwich panels with NU-tie. *Final Report*.
- MGBC. (2018). [www.mgbc.org.my](http://www.mgbc.org.my).
- Mirasa, A. K., Zakaria, F., & Fathi, M. S. (1999). *The Effect of Grout on Mortarless Interlocking Block Masonry*: Universiti Teknologi Malaysia.
- Mo, S., Zeng, J., & Xie, L. (2012). Extended particle-swarm optimization algorithm. *Control Theory & Applications*, 29(6), 811-816.
- Mohamad, N., & Hassan, N. (2013). *The structural performance of precast lightweight foam concrete sandwich panel with single and double shear truss connectors subjected to axial load*. Paper presented at the Advanced Materials Research.
- Mohamad, N., & Muhammad, H. M. (2011). *Testing of precast lightweight foamed concrete sandwich panel with single and double symmetrical shear truss connectors under eccentric loading*. Paper presented at the Advanced Materials Research.
- Mohamad, N., Omar, W., & Abdullah, R. (2011). *Precast Lightweight Foamed Concrete Sandwich Panel (PLFP) tested under axial load: preliminary results*. Paper presented at the Advanced Materials Research.

- Mohd Zahari, N., Abdul Rahman, I., Zaidi, A., & Mujahid, A. (2009). Foamed concrete: potential application in thermal insulation.
- Moy, S. (2013). Advanced fiber-reinforced polymer (FRP) composites for civil engineering applications *Developments in Fiber-Reinforced Polymer (FRP) Composites for Civil Engineering* (pp. 177-204): Elsevier.
- MS1525. (2014). *Code of Practice on Energy Efficiency and Use of Renewable Energy for Non—Residential Building (First Revision)*, Department of Standard Malaysia. Paper presented at the ICS.
- Mydin, M. O., Sani, N. M., & Taib, M. (2014). *Industrialised building system in Malaysia: A review*. Paper presented at the MATEC Web Of Conferences.
- Naito, C., Hoemann, J., Beacraft, M., & Bewick, B. (2011). Performance and characterization of shear ties for use in insulated precast concrete sandwich wall panels. *Journal of Structural Engineering*, 138(1), 52-61.
- Najm, A. M. (2001). *Structural behaviour of load-bearing interlocking hollow block masonry*. Universiti Putra Malaysia.
- Nambiar, E. K., & Ramamurthy, K. (2006a). Influence of filler type on the properties of foam concrete. *Cement and concrete composites*, 28(5), 475-480.
- Nambiar, E. K., & Ramamurthy, K. (2006b). Models relating mixture composition to the density and strength of foam concrete using response surface methodology. *Cement and concrete composites*, 28(9), 752-760.
- Nawi, M., Lee, A., & Nor, K. (2011). Barriers to implementation of the industrialised building system (IBS) in Malaysia. *The Built & Human Environment Review*, 4(2), 34-37.
- Neville, A. M. (1995). *Properties of concrete* (Vol. 4): Longman London.
- Nooraini, M. Z., Ismail, A. R., Mujahid, A., & Zahidi, A. (2010). Foamed concrete: potential application in thermal insulation.
- Nussbaumer, T., Wakili, K. G., & Tanner, C. (2006). Experimental and numerical investigation of the thermal performance of a protected vacuum-insulation system applied to a concrete wall. *Applied Energy*, 83(8), 841-855.
- Ozel, M. (2011). Thermal performance and optimum insulation thickness of building walls with different structure materials. *Applied thermal engineering*, 31(17-18), 3854-3863.
- Ozel, M., & Pihtili, K. (2007). Optimum location and distribution of insulation layers on building walls with various orientations. *Building and environment*, 42(8), 3051-3059.
- Pantelides, C. P., Surapaneni, R., & Reaveley, L. D. (2008). Structural performance of hybrid GFRP/steel concrete sandwich panels. *Journal of Composites for Construction*, 12(5), 570-576.
- Papadopoulos, A. M. (2005). State of the art in thermal insulation materials and aims for future developments. *Energy and buildings*, 37(1), 77-86.
- PCI Handbook. (2007). *PCI design handbook: precast and prestressed concrete: MNL-120*. 6th ed. Chicago, IL: PCI.
- Peng, C., & Wu, Z. (2008). In situ measuring and evaluating the thermal resistance of building construction. *Energy and buildings*, 40(11), 2076-2082.
- Pessiki, S., & Mlynarczyk, A. (2003). Experimental evaluation of the composite behavior of precast concrete sandwich wall panels. *PCI journal*, 48(2), 54-71.
- Pillai, S. U., & Parthasarathy, C. (1977). Ultimate strength and design of concrete walls. *Building and environment*, 12(1), 25-29.
- Qi, J., Wang, J., & Ma, Z. J. (2018). Flexural response of high-strength steel-ultra-high-performance fiber reinforced concrete beams based on a mesoscale constitutive model: Experiment and theory. *Structural Concrete*, 19(3), 719-734.



- Rahim, N. H. A., Mohamad, N., Samad, A. A. A., Goh, W., & Jamaluddin, N. (2017). *Flexural Behaviour of Precast Aerated Concrete Panel (PACP) with Added Fibrous Material: An Overview*. Paper presented at the MATEC Web of Conferences.
- Rardin, R. (1998). *Optimization in Operations Research* Prentice-Hall. *New Jersey*.
- Robinson, A., Lesage, F., Reilly, A., McGranaghan, G., Byrne, G., O'Hegarty, R., & Kinnane, O. (2017). A new transient method for determining thermal properties of wall sections. *Energy and buildings*, 142, 139-146.
- Royon, L., Karim, L., & Bontemps, A. (2013). Thermal energy storage and release of a new component with PCM for integration in floors for thermal management of buildings. *Energy and buildings*, 63, 29-35.
- Sabir, B., Wild, S., & O'farrell, M. (1998). A water sorptivity test for mortar and concrete. *Materials and Structures*, 31(8), 568.
- Salmon, D. C., & Einea, A. (1995). Partially composite sandwich panel deflections. *Journal of Structural Engineering*, 121(4), 778-783.
- Salmon, D. C., Einea, A., Tadros, M. K., & Culp, T. D. (1997). Full scale testing of precast concrete sandwich panels. *ACI Structural Journal*, 94, 239-247.
- Sartori, I., Napolitano, A., & Voss, K. (2012). Net zero energy buildings: A consistent definition framework. *Energy and buildings*, 48, 220-232.
- Seeber, K., Andrews Jr, R., JACQUES, F. J., BATY, J. R., KOURAJIAN, P., CAMPBELL, P. S., LONG, R. T., FORCE, G., OEHRLEIN, M., & FRANCIES, S. (1997). State-of-the-art of precast/prestressed sandwich wall panels. *PCI Committee Report*, 42(2), 33.
- Seo, D.-W., Park, K.-T., You, Y.-J., & Kim, H.-Y. (2013). Enhancement in elastic modulus of GFRP bars by material hybridization. *Engineering*, 5(11), 865.
- Sharaf, T., Shawkat, W., & Fam, A. (2010). Structural performance of sandwich wall panels with different foam core densities in one-way bending. *Journal of Composite Materials*, 44(19), 2249-2263.
- Shi, Y., & Eberhart, R. (1998). *A modified particle swarm optimizer*. Paper presented at the Evolutionary Computation Proceedings, 1998. IEEE World Congress on Computational Intelligence., The 1998 IEEE International Conference on.
- Sinha, B., Gerstle, K. H., & Tulin, L. G. (1964). *Stress-strain relations for concrete under cyclic loading*. Paper presented at the Journal Proceedings.
- Široký, J., Oldewurtel, F., Cigler, J., & Privara, S. (2011). Experimental analysis of model predictive control for an energy efficient building heating system. *Applied Energy*, 88(9), 3079-3087.
- Smith, G. N. (1986). *Probability and statistics in civil engineering*. Collins Professional and Technical Books, 244.
- Soares, N., Costa, J. J., Gaspar, A. R., & Santos, P. (2013). Review of passive PCM latent heat thermal energy storage systems towards buildings' energy efficiency. *Energy and buildings*, 59, 82-103.
- Steiger, R., & Hurd, M. (1978). Lightweight insulating concrete for floors and roof decks. *Concrete Construction*, 23(7), 411-422.
- Straube, J. F. (2002). Moisture in buildings. *ASHRAE journal*, 44(1), 15.
- Sujivorakul, C., Muhummud, T., & Kong, S. (2017). Steel fibre reinforced concrete sandwich panel using a foam core: flexural investigation and prediction. *Journal of Thailand Concrete Association*, 5(1), 24-34.
- Thanoon, W., Peng, L. W., Kadir, M. R. A., Jaafar, M. S., & Salit, M. S. (2003). *The Experiences of Malaysia and other countries in industrialised building system*. Paper presented at the Proceeding of International Conference on Industrialised Building Systems, Sep.

- Tomlinson, D., & Fam, A. (2014). Experimental investigation of precast concrete insulated sandwich panels with glass fiber-reinforced polymer shear connectors. *ACI Structural Journal*, 111(3), 595.
- Tomlinson, D., & Fam, A. (2015). Flexural behavior of precast concrete sandwich wall panels with basalt FRP and steel reinforcement. *PCI journal*.
- Tomlinson, D. G., Teixeira, N., & Fam, A. (2016). New shear connector design for insulated concrete sandwich panels using basalt fiber-reinforced polymer bars. *Journal of Composites for Construction*, 20(4), 04016003.
- Tsilingiris, P. (2006). Parametric space distribution effects of wall heat capacity and thermal resistance on the dynamic thermal behavior of walls and structures. *Energy and buildings*, 38(10), 1200-1211.
- Ucar, A., & Balo, F. (2009). Effect of fuel type on the optimum thickness of selected insulation materials for the four different climatic regions of Turkey. *Applied Energy*, 86(5), 730-736.
- Van Schijndel, A., Schellen, H., & De Wit, M. (2009). Improved HVAC operation to preserve a church organ. *Building and environment*, 44(1), 156-168.
- Vilanova, I., Baena, M., Torres, L., & Barris, C. (2015). Experimental study of bond-slip of GFRP bars in concrete under sustained loads. *Composites Part B: Engineering*, 74, 42-52.
- Wells, L., Rismanchi, B., & Aye, L. (2018). A review of Net Zero Energy Buildings with reflections on the Australian context. *Energy and buildings*, 158, 616-628.
- Woltman, G., Tomlinson, D., & Fam, A. (2013). Investigation of various GFRP shear connectors for insulated precast concrete sandwich wall panels. *Journal of Composites for Construction*, 17(5), 711-721.
- Yu, J., Yang, C., Tian, L., & Liao, D. (2009). A study on optimum insulation thicknesses of external walls in hot summer and cold winter zone of China. *Applied Energy*, 86(11), 2520-2529.
- Zarr, R., Burch, D., Faison, T., & Arnold, C. (1987). Thermal Resistance Measurements of Well-Insulated and Superinsulated Residential Walls Using a Calibrated Hot Box. *Journal of Thermal Insulation*, 10(3), 197-218.
- Zeng, R., Wang, X., Di, H., Jiang, F., & Zhang, Y. (2011). New concepts and approach for developing energy efficient buildings: Ideal specific heat for building internal thermal mass. *Energy and buildings*, 43(5), 1081-1090.
- Zhai, X., Wang, Y., & Wang, X. (2018). Thermal performance of precast concrete sandwich walls with a novel hybrid connector. *Energy and buildings*, 166, 109-121.
- Zuo, J., & Zhao, Z.-Y. (2014). Green building research—current status and future agenda: A review. *Renewable and Sustainable Energy Reviews*, 30, 271-281.

## BIODATA OF STUDENT

Sani Mohammed Bida was born on the 25 December, 1979 in Bida Local Government of Niger State, Nigeria. He obtained his Bachelor's Degree in Civil Engineering (B. Eng) in 2005 from Bayero University Kano, Nigeria. He further obtained Master of Science in Structural Engineering from Universiti Putra Malaysia (UPM) in 2014. Thereafter, he began to pursue his Doctor of Philosophy (PhD) in Structural Engineering in 2015. The author commenced his career as an engineer in the Ministry of Infrastructural Development, Niger State from 2007-2009 before he left for Federal Polytechnic Bida as Lecturer III. He has engaged in many activities professionally outside his work environment as Non-Governmental Organization (NGO). During this period, freelance structural designs are provided for communities as a social responsibility under the NGO.



## LIST OF PUBLICATIONS

- Bida, S. M., Aziz, F., Jaafar, M. S., Hejazi, F., & Nabilah, A. B. (2017). Efficient Structural Sandwich Wall Panels Devoid of Thermal Bridges. **Published**; Global Civil Engineering Conference (GCEC, 2017) (Vol. volume 9, pp. 59-67): Springer.
- Abdul Aziz, Farah, Sani Mohammed Bida, Abu Bakar Nabila, Mohd Saleh Jaafar and Farzad Hejazi(2018). Thermal Resistance of Two Layers Precast Concrete Sandwich Panels. **Published**; International Journal of Engineering and Technology, Vol 10, No 4, August. pp 320-324, DOI: 10.7763/IJET.2018.V10.1077
- Bida, S. M., Aziz, F. N. A. A., Jaafar, M. S., Hejazi, F., & Nabilah, A. B. (2018). Flexural behavior of super-insulated precast concrete two-layers sandwich panels. **Under Review**; Composite Structures.
- Bida, S. M., Aziz, F. N. A. A., Jaafar, M. S., Hejazi, F., & Nabilah, A. B. (2018). Axial behavior of super-insulated precast concrete sandwich panels. **Under Review**; Engineering Structures.



**UNIVERSITI PUTRA MALAYSIA**

**STATUS CONFIRMATION FOR THESIS / PROJECT REPORT AND COPYRIGHT**

**ACADEMIC SESSION :** \_\_\_\_\_

**TITLE OF THESIS / PROJECT REPORT :**

STRUCTURAL BEHAVIOUR OF PRECAST CONCRETE SANDWICH PANEL WITH  
HIGH THERMAL EFFICIENCY

**NAME OF STUDENT:** SANI MOHAMMED BIDA

I acknowledge that the copyright and other intellectual property in the thesis/project report belonged to Universiti Putra Malaysia and I agree to allow this thesis/project report to be placed at the library under the following terms:

1. This thesis/project report is the property of Universiti Putra Malaysia.
2. The library of Universiti Putra Malaysia has the right to make copies for educational purposes only.
3. The library of Universiti Putra Malaysia is allowed to make copies of this thesis for academic exchange.

I declare that this thesis is classified as :

\*Please tick (✓)

**CONFIDENTIAL**

(Contain confidential information under Official Secret Act 1972).

**RESTRICTED**

(Contains restricted information as specified by the organization/institution where research was done).

**OPEN ACCESS**

I agree that my thesis/project report to be published as hard copy or online open access.

This thesis is submitted for :

**PATENT**

Embargo from \_\_\_\_\_ until \_\_\_\_\_  
(date) (date)

(Signature of Student)  
New IC No/ Passport No.:

Date :

**Approved by:**

\_\_\_\_\_  
(Signature of Chairman of Supervisory Committee)  
Name:

Date :

[Note : If the thesis is CONFIDENTIAL or RESTRICTED, please attach with the letter from the organization/institution with period and reasons for confidentially or restricted. ]