



UNIVERSITI PUTRA MALAYSIA

**SHEAR AND COMPRESSION BEHAVIOUR OF CRUSHED MUDROCKS
IN MALAYSIA**

ILI SYAZWANI BINTI CHE MOHD ROSLEY

FK 2019 106



SHEAR AND COMPRESSION BEHAVIOUR OF CRUSHED MUDROCKS IN MALAYSIA

By

ILI SYAZWANI BINTI CHE MOHD ROSLEY

**Thesis Submitted to the School of Graduate Studies, Universiti Putra
Malaysia, in Fulfilment of the Requirements for the Degree of Master of
Science**

March 2019

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in
fulfilment of the requirement for the degree of Master of Science

SHEAR AND COMPRESSION BEHAVIOUR OF CRUSHED MUDROCKS IN MALAYSIA

By

ILI SYAZWANI BINTI CHE MOHD ROSLEY

March 2019

Chairman : Haslinda Binti Nahazanan, PhD
Faculty : Engineering

Mudrocks is a type of rock that tends to deteriorate upon exposure to water. Studies have found mudrocks to be in low to medium durability in which its shear strength and compressibility were easily influenced by its resistance towards wetting and drying. However, in Malaysia, it is difficult to avoid mudrocks from exposure to water due to the tropical climate. When mudrocks were encountered on construction sites, they were often been excavated however, it is not a sustainable solution. Thus research on shear and compression behaviour of crushed mudrocks with detailed explanations on morphological changes that relate with mineralogical and chemical composition is required before suitable stabilisation or any advance solutions on working out crushed mudrocks as geotechnical material could be carried out. Hence this research implied direct shear tests, XRD, XRF and VPSEM to evaluate the shear and compression behaviour of crushed mudrocks in Malaysia. This study was conducted onto mudrocks in Malaysia from Putrajaya, Semanggol (Perak) and Durian Tunggal (Melaka). The materials were named as CM1, CM2, and CM3 respectively. These crushed mudrocks predominantly contained of swelling clays where CM1 contained 38.2%, CM2 contained 35.1% and CM3 contained 58% of swelling clays respectively. Three types of slaking tests were carried out; jar slake test, slake durability test, and slaking immersion test. Based on the results, CM2 was the most durable, followed by CM1 and lastly CM3. This pattern of sequence agrees with swelling clay minerals contents but went inversely with total mica contents in which CM2 has the highest with 34.7%, followed by CM1 with 29.4% and lastly CM3 with 25%. Shear and compression behaviour of crushed mudrocks were investigated at various compaction degree, various initial moisture content, and various terms of immersion in which the tests were accompanied with staged-loading process using direct shear box test. Higher compaction degrees caused crushed mudrocks to exhibit highest peak shear strength in

which decrease of subsequent 5% compaction degrees had caused 11% to 12% peak shear strength reduction and 2% compression to take place. Due to increment of initial moisture content from natural to optimum, peak shear strength of crushed mudrocks increased by 4.4% to 6.9% with reduced brittleness and about 0.6% to 1.2% compression took place since early loading stage. Upon immersions, direct shear tests revealed that all crushed mudrocks failed in brittle deformation when without immersion. Short term immersion had intensified crushed mudrocks brittle behaviour with peak shear strength reduction of 15% for CM1 and CM2, and 42% for CM3. Long term immersion, on the other hand had caused only 3% strength reduction with fully plastic straining behaviour after failure. In addition, short term immersion caused immediate compression of about 3% to crushed mudrocks while long term immersion caused CM1 and CM2 to show progressively reduced compression, and CM3 to show progressive compression along staged-loading process. VPSEM images shown that vigorous micro activities that took place during short term immersion had led to strength reduction and high compressibility of mudrocks while long term immersion had enabled prolonged micro-activities hence resulted into higher peak shear strength than that of recorded by short term immersion. As a result, micro flaws; micro holes, micro fracture and micro cracks were seen from VPSEM images of mudrocks after short term immersion. The micro flaws had caused mudrocks to experience strength reduction and high compression. However the micro flaws were seen resealed after long term immersion as prolonged micro activities had promoted healing to the flaws. Interestingly, these micro activities were able to occur due to presence of swelling clay minerals which seem to have increased aggregate's ability to absorb water and to weave with each other. This study hence found that mudrocks are not only sensitive to moisture changes but to sudden moisture changes as pictured through short term immersion while pre-wetting effect through long term immersion had reduced mudrocks sensitivity towards moisture changes throughout staged-loading.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia
sebagai memenuhi keperluan untuk ijazah Master Sains

TINGKAHLAKU RICIH DAN MAMPATAN MUDROCKS TERHANCUR DI MALAYSIA

Oleh

ILI SYAZWANI BINTI CHE MOHD ROSLEY

Mac 2019

Pengerusi : Haslinda Nahazanan, PhD
Fakulti : Kejuruteraan

Mudrocks adalah sejenis batuan yang mudah merosot apabila terdedah kepada lembapan. Kajian telah banyak mendapati bahawa *mudrocks* berada dalam kelas ketahanan rendah ke sederhana di mana kekuatan ricih dan kemampatannya mudah dipengaruhi oleh daya rintangan *mudrocks* terhadap pembasahan dan pengeringan. Di Malaysia, ianya amat sukar untuk menghalang *mudrocks* daripada pendedahan kepada air oleh kerana cuaca tropikal di Malaysia iaitu panas dan hujan sepanjang tahun. Oleh itu, *mudrocks* digali dan dibuang dari tapak pembangunan. Namun, ini bukanlah suatu penyelesaian lestari. Maka kajian tentang tingkahlaku ricih dan mampatan *mudrocks* terhancur yang disokongi oleh penerangan perubahan morfologi bersertakan pengetahuan kandungan mineral dan kimia adalah diperlukan. Ini adalah bagi membolehkan kajian tentang kaedah penstabilan bersesuaian untuk dijalankan ke atas *mudrocks* dan seterusnya boleh melestarikan *mudrocks*. Kajian ini menggunakan ujian ricih terus, pembiasan x-ray (XRD), pendafluor x-ray (XRF) dan ujian pengesanan imbasan mikroskop pelbagai tekanan (VPSEM) untuk menilai tingkahlaku ricih dan mampatan *mudrocks* terhancur di Malaysia. *Mudrocks* yang dikaji diambil dari Putrajaya, Semanggol (Perak) dan Durian Tunggal, Melaka yang dilabel sebagai CM1, CM2, dan CM3. Sampel-sampel *mudrocks* ini masing-masing mengandungi mineral tanahliat membengkak sebanyak 38.2%, 35.1%, dan 58%. *Mudrocks* ini diuji ketahanannya melalui tiga jenis ujian kehancuran iaitu ujian kehancuran balang, ujian kehancuran dan ketahanan, dan ujian rendaman kehancuran. Menurut keputusan yang diperolehi, CM2 menunjukkan ketahanan paling tinggi, diikuti oleh CM1 dan CM3. Turutan ini dilihat selari dengan kandungan mineral tanahliat membengkak yang diperolehi melalui XRD tetapi terbalik dengan kandungan mica di mana CM2 mempunyai kandungan jumlah mica tertinggi dengan 34.7%, diikuti dengan CM1 sebanyak 29.4%, dan CM3 sebanyak 25%. Tingkahlaku ricih dan

mampatan pula dikaji pada darjah padatan yang berbeza, kandungan lembapan awalan berbeza, dan penggal rendaman berbeza. Didapati bahawa darjah padatan yang lebih tinggi mempamerkan kekuatan ricih puncak yang lebih tinggi dan penurunan 5% darjah padatan menyebabkan penurunan kekuatan ricih puncak sebanyak 11% ke 12% dan 2% mampatan direkodkan. Apabila kandungan lembapan awalan meningkat daripada asli ke optimum, kekuatan ricih puncak meningkat sebanyak 4.4% ke 6.9% manakala mampatan menungkat sebanyak 0.6% ke 1.2% di peringkat awal bebanan. Ujian ricih rendaman pendek menyebabkan kerapuhan *mudrocks* makin jelas dengan penurunan nilai kekuatan ricih puncak sebanyak 15% bagi CM1 dan CM2, dan 42% bagi CM3. Manakala selepas ujian ricih rendaman panjang pula, kerapuhan tersebut hilang dan menyebabkan penurunan nilai kekuatan ricih puncak sebanyak 3% sahaja. Malahan, selepas gagal, tingkahlaku terikan penuh plastic dapat diperhatikan. Ujian ricih rendaman pendek juga telah menyebabkan kenaikan nilai mampatan serta merta sebanyak 3% sebaik sahaja rendaman bermula ujian ricih rendaman panjang pula member kesan yang berbeza; CM1 dan CM2 telah menunjukkan penurunan mampatan secara beransur manakala CM3 menunjukkan mampatan sekata sepanjang proses bebanan berperingkat itu. Imej imbasan VPSEM menunjukkan bahawa ujian ricih rendaman pendek menyebabkan aktiviti mikro berlaku dengan cepat dan banyak pada masa rendaman yang pendek. Ia telah menyebabkan kekuatan ricih berkurang dan *mudrocks* mudah menerima mampatan manakala selepas ujian ricih rendaman panjang, aktiviti mikro dapat berlaku dalam masa yang lebih lama sambil dibebani oleh beban-beban berikutnya. Berdasarkan pemerhatian, cela mikro yang terlihat pada *mudrocks* selepas rendaman pendek telah ditutupi setelah rendaman panjang. Menariknya, aktiviti mikro ini boleh terjadi kerana kehadiran mineral tanahliat membengkak di mana kehadiran mineral-mineral ini telah meningkatkan kebolehan *mudrocks* dalam menyerap air lalu membolehkan jalinan antara agregat. Jadi melalui kajian ini, *mudrocks* didapati bukan sensitif kepada perubahan lembapan tetapi ianya sensitif terhadap perubahan lembapan secara mengejut yang digambarkan melalui ujian ricih rendaman pendek. Sebagai inferens, ujian ricih rendaman panjang telah membuktikan sensitiviti *mudrocks* terhadap perubahan lembapan berkurang apabila direndam dan dibebani secara berperingkat.

ACKNOWLEDGEMENTS

In the name of Allah, the Most Gracious and the most Merciful.

Alhamdulillah, all praise to Allah SWT because of His blessing, I could complete this research study. In this occasion, I would like to thank everyone involved directly and indirectly throughout the study's completion.

First of all, I would like to express my appreciation and gratitude to my supervisor, Dr. Haslinda Binti Nahazanan, for her time, support, guidance and invaluable opinions with a continuous stream of suggestions, feedback, and encouragement that have guided me throughout the whole period of this research. I especially would like to thank her for always being accessible. All her sacrifices and understanding will not be forgotten.

Thank you also to Dr. Zainuddin Md. Yusoff for his co-supervision and help in completing this research. I would like to express my gratitude to MOHE for funding of the research through the FRGS project (Grant No. 5524614) for financial support.

I would like to thank the faculty and staffs in the Department of Civil Engineering for their continuous support and cooperation during the session of project implementation, especially the assistant engineer of Geotechnical Engineering lab, En. Mohd Razali (Tok) who have aided technical works throughout the study and all members of GEGE unit for creating a very supportive environment

My sincere warm hearted gratitude goes to my mother and eldest brother, Pn. Adzmah Mahmud and En. Mohd Adzman Rosley for have been giving me full encouragement and sacrifices. The gratitude nonetheless goes to all my other siblings for their endless love, understanding, patience, support, prayers and encouragement. Without them, none of my accomplishments would have been possible. To them, I dedicate this thesis.

Finally, I would like to thank my best friends, Siti Nurliyana and Syafina Auni for their continuous motivation, love, and support that have always keeping me from failing. This also goes to my companion friends Nur Izzati Md Saleh, Hazimah Madzaki, Falil Nisa Abdul Jalil, Tuan Norizan and Syahin Mohamad Saleh for the friendship and help in completing this research and for creating a very pleasant environment through this journey.

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Haslinda binti Nahazanan, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Zainuddin bin Md Yusoff, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Member)

ROBIAH BINTI YUNUS, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any other institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: _____ Date: _____

Name and Matric No.: Ili Syazwani binti Che Mohd Rosley, GS43794

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: _____

Name of
Chairman of
Supervisory
Committee:

Dr. Haslinda binti Nahazanan

Signature: _____

Name of
Member of
Supervisory
Committee:

Dr. Zainuddin bin Md Yusoff

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABLES	xiii
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xvii
 CHAPTER	
1 INTRODUCTION	1
1.1 Research background	1
1.2 Problem statements	3
1.3 Aim and objectives	4
1.4 Scope of work	4
1.5 Limitations of study	5
 2 LITERATURE REVIEW	6
2.1 Mudrocks	6
2.1.1 Introduction	6
2.1.2 Physical properties of mudrocks	7
2.1.3 Mineralogy and chemical composition of mudrocks	8
2.1.4 General problems of mudrocks	9
2.1.5 Studies on crushed mudrocks	12
2.2 Durability and slaking behaviour of mudrocks	13
2.3 Mudrocks shear behaviour	17
2.4 Geotechnical assessment	19
2.4.1 Atterberg limit	19
2.4.2 Moisture content	20
2.4.3 Specific gravity	20
2.4.4 Compaction	21
2.4.5 Direct shear	21
2.5 Mineralogical, Chemical And Morphological Analyses	22
2.5.1 X-Ray diffraction (XRD)	22
2.5.2 X-ray fluorescence (XRF) analysis	23
2.5.3 Scanning electron microscopy (SEM) imaging	24
2.6 Summary on Findings of Crushed Mudrocks	26

3	METHODOLOGY	27
3.1	Introduction	27
3.2	Material collection	29
3.2.1	Mudrocks from Putrajaya	31
3.2.2	Mudrocks from Semanggol, Perak	31
3.2.3	Mudrocks from Durian Tunggal, Melaka	32
3.3	Material preparations for crushed mudrocks	32
3.3.1	Various compaction degrees	33
3.3.2	Various initial moisture contents	34
3.3.3	Various terms of immersion	34
3.3.4	Mudrocks classification based on lithology	35
3.4	Geotechnical assessment	36
3.4.1	Sieve analysis test	36
3.4.2	Atterberg limit test	36
3.4.3	Moisture content	37
3.4.4	Specific gravity	37
3.4.5	Compaction test	37
3.4.6	California bearing ratio (CBR) test	38
3.5	Slaking tests	38
3.5.1	Jar slake test	38
3.5.2	Slake durability test	39
3.5.3	Slaking immersion test	40
3.6	Shear and compression behaviour analysis – direct shear test	41
3.7	Mineralogical, chemical and morphological analyses	42
3.7.1	X-ray diffraction (XRD) analysis	42
3.7.2	X-ray fluorescence (XRF) spectrometry	43
3.7.3	Variable pressure scanning electron microscopy (VPSEM)	43
3.8	Summary	44
4	RESULTS AND DISCUSSIONS	45
4.1	Introduction	45
4.2	Geotechnical assessments	45
4.2.1	Atterberg limit test	45
4.2.2	Moisture content	47
4.2.3	Specific gravity, G_s	48
4.2.4	Compaction Test	50
4.2.5	California Bearing Ratio (CBR) Test	52
4.3	Slaking behaviour of mudrocks	52
4.3.1	Jar slake test	52
4.3.2	Slake durability test	54
4.3.3	Slaking immersion test	55
4.4	Shear behaviour of crushed mudrocks	58
4.4.1	Shear strength of mudrocks due to different compaction degrees	59
4.4.2	Shear strength of mudrocks due to different initial moisture contents	62

4.4.3	Shear strength of mudrocks at different terms of immersion	65
4.4.4	Shear strength parameters of mudrocks due to different terms of immersion	68
4.5	Compression behaviour of crushed mudrocks	69
4.5.1	Compressive settlement of mudrocks due to different compaction degrees	69
4.5.2	Compressive settlement of mudrocks due to change of moisture content	71
4.5.3	Compressive settlement of crushed mudrocks due to immersion	73
4.6	Influence of mineralogical and chemical content on crushed mudrocks	75
4.6.1	Influence of mineral and chemical composition on durability of mudrocks	76
4.6.2	Influence of mineral and chemical composition on shear behaviour of mudrocks	77
4.6.3	Influence of mineral composition on compressive behaviour of mudrocks	78
4.7	Morphological changes of crushed mudrocks	78
4.7.1	Various initial moisture content	78
4.7.2	Sudden aggregate-water interaction on microstructural activity of mudrocks	80
4.7.3	Preliminary additional moisture effect on micro flaws healing of mudrocks	82
4.8	Summary	85
5	CONCLUSIONS AND RECOMMENDATIONS	86
5.1	Summary	86
5.2	Conclusions	87
5.3	Recommendations	88
	REFERENCES	89
	APPENDICES	102
	BIODATA OF STUDENT	108
	LIST OF PUBLICATIONS	109

LIST OF TABLES

Table	Page
2.1 Geological classification of mudrocks	7
2.2 Class of durability made through observation during jar slake test by Santi and Higgins (1998)	16
2.3 Class of durability modified from Santi and Higgins (1998) by Sadisun <i>et al.</i> , 2005	16
2.4 Characteristic with different plasticity indices (Sowers, 1979)	20
2.5 Summary on findings from research of crushed mudrocks	26
3.1 Testing program for crushed mudrocks with respect to compaction degrees	34
3.2 Testing program for crushed mudrocks with respect to initial moisture content	34
3.3 Testing program for crushed mudrocks with respect to terms of immersion	35
3.4 Classification and naming of materials based on structure and percent clay –sized particle	35
3.5 Legends for classification of observation during slaking immersion test	41
3.6 Summary of Chapter 3	44
4.1 Atterberg limits and swelling clay mineral content of crushed mudrocks	45
4.2 Comparison of liquid limit and plasticity index of crushed mudrocks by other researches	46
4.3 A classification of plasticity index in qualitative manner by Burmister (1949)	47
4.4 Comparison of natural moisture content of crushed mudrocks in this study and other researches	48
4.5 Specific gravity, G_s of crushed mudrocks in this study and other researches	49
4.6 Specific gravity of some common minerals (Das, 2010) and their percent content in crushed mudrocks	49

4.7	Variations of γ_{dmax} and w_{opt} shown by CM1, CM2 and CM3	50
4.8	CBR values of crushed mudrocks with respect to unsoaked and soaked condition	52
4.9	Classification index of mudrocks from observation made at each time interval and the samples' condition at end of each tests	53
4.10	I_{d1} and I_{d2} of all four sets of each mudrocks samples	54
4.11	Summary of slake durability index, I_d and their percentage difference	55
4.12	Characteristics of slaking and disintegration based on observations made onto CM1, CM2 and CM3	56
4.13	Variation of shear strength parameters of mudrocks with different terms of immersion	69
4.14	Variations of mineral compositions of CM1, CM2 and CM3	76
4.15	Chemical compositions of CM1, CM2 and CM3	76
4.16	VPSEM images of crushed mudrocks at natural and optimum moisture content where (a) and (b) are CM1, (c) and (d) are CM2, (e) and (f) are CM3	79
4.17	VPSEM images of crushed mudrocks after short term immersion where (a) is CM1, (b) is CM2 and (c) is CM3	81
4.18	VPSEM images of crushed mudrocks after long term immersion where (a) is CM1, (c) is CM2 and (c) is CM3	83

LIST OF FIGURES

Figure	Page
2.1 Photo of road depression occurred at Kundasang adopted from Liew and Gue (2001)	11
2.2 A schematic diagram of electron beaming concept for ESEM adopted from (Donald, 2003)	24
2.3 (a) SEM image of dry mudrocks with less dense structure, (b) SEM image of saturated mudrocks with denser structure adopted from Pejon and Zuquette, 2002	25
3.1 Flowchart of research study	28
3.2 Crushed mudrocks sampling sites with exact location of (a) Semanggol, (b) Putrajaya, and (c) Durian Tunggal	30
3.3 Mudrocks samples collected from Putrajaya	31
3.4 Mudrocks samples collected from Semanggol	32
3.5 Mudrocks samples from Melaka	32
3.6 : Controlled particle size distribution of crushed mudrocks from all sampling sites	33
3.7 The classification made by Santi (1998)	39
3.8 Sample preparation for XRD test	42
3.9 Bruker Discover D8 XRD equipment	43
3.10 VPSEM equipment used in research study	44
4.1 A plasticity chart proposed by Casagrande (1932)	47
4.2 Compaction curve and 0%,5%,10% void lines of (a) CM1, (b) CM2, and (c) CM3	51
4.3 Plot of discussion for shear behavior of crushed mudrocks	59
4.4 Shear stress-shear displacement relation of (a) CM1, (b) CM2 and (c) CM3 at natural moisture content with 90%, 95% and 100% compaction degree	60
4.5 Shear stress-shear displacement relation of (a) CM1, (b) CM2 and (c) CM3 with 100% compaction degree at natural and optimum moisture content	63

4.6	Void ratio-shear displacement relation of CM3 with 100% compaction at natural and optimum moisture content	65
4.7	Shear stress-shear displacement of (a) CM1, (b) CM2 and (c) CM3 with 100% compaction degree at optimum moisture content subjected to without immersion, short term immersion and long term immersion	66
4.8	Shear stress-shear displacement relation of CM3 + 1.0% coir fibers with different terms of immersion	68
4.9	Development of compressive strain over time of (a) CM1, (b) CM2 and (c) CM3 at natural moisture content due to 90%, 95% and 100% compaction degree, without immersion.	70
4.10	Development of compressive strain with time of (a) CM1, (b) CM2 and (c) CM3 with 100% compaction degree with respect to natural moisture content and optimum moisture content	72
4.11	Development of compressive strain of (a) CM1, (b) CM2 and (c) CM3 with 100% compaction degree at optimum moisture content with respect to without immersion, short term immersion and long term immersion	74
4.12	VPSEM image of CM3 + 1.0% coir fibres after short term immersion direct shear test	82
4.13	VPSEM image of CM3 + 1.0% coir fibres after subjected to long term immersion direct shear test	84

LIST OF ABBREVIATIONS

AASHTO	American Association of State Highway and Transportation Officials
ASTM	American Society for Testing and materials
BS	British Standard
C	Cohesion
CBR	Claifornia bearing ratio
Cc	Coefficient of curvature
Cu	Coefficient of uniformity
CM	Crushed mudrocks
E	Void ratio
EDX	Energy dispersive x-ray
ED-XRF	Energy dispersal x-ray fluorescence
EPMA	Electron microprobe analysis
ESEM	Environmental scanning electron microscopy
FESEM	Field emission scanning electron microscopy
I _d	Slake durability index
OM	Optical microscopy
PI	Plasticity index
SEM	Scanning electron microscopy
USCS	Unified Soil Classification system
VPSEM	Variable pressure scanning electron microscopy
W	Moisture content
WD-XRF	Wavelength dispersal x-ray fluorescence
w _L	Liquid limit
w _{nat}	Natural moisture content
w _{opt}	Optimum moisture content
w _p	Plastic limit
XRD	X-ray diffraction
XRF	X-ray fluorescence
γ _{dmax}	Maximum dry density
Δ	Shear displacement
E	Compressive settelement (strain)
σ'	Shear strength
Φ	Friction angle

CHAPTER 1

INTRODUCTION

1.1 Research background

Mudrocks are sedimentary rocks that are very sensitive to changes in moisture content. It has a great tendency to slake when contacted with water. Mudrocks are also often categorized as problematic rocks by researchers (Yagiz 2001; Bell and Survey 2005; Adewuyi and Festus 2015) and has given rise to numerous construction problems. Mudrocks, including all the subgroups it hold; siltstone, claystone, mudstone, and shale are enlisted as problematic geo-material due to low durability and its high clay mineral content. Due to that, mudrocks have been remarked by researchers as a type of rock that has a great tendency to deteriorate when in contact with water (Olivier and Yagiz, 2001; Yoshida *et. al.*, 2002).

Aforetime, Franklin and Chandra (1972) reported that in India, mudrocks were instantaneously rejected the second it is found in construction area, even as subgrade material. Upon acceptance, many construction problems that occurred including slope failure, embankment failure, and road settlements were found to have been related to mudrocks' behaviour (Sharma, 2013). Also, Putra and Kikumoto (2016) stated that mudrocks often deposited as waste disposal due to mudrocks behaviour when exposed to water. The term 'behaviour' connotes the high clay mineral content which had been regarded as key factor that influenced mudrocks water absorption (Na *et al.*, 2014) and hence water been described as a harmful role for mudstone's stability (Jiang *et al.*, 2014). Relatively, Koralegedara and Maynard (2017) found that in absence of swelling clay minerals, correlation between mudrocks mineralogy and its durability did not exist.

A threefold classification of mudrocks proposed siltstone comprising less than 25% clay fraction, claystone containing more than 40% clay fraction and mudstone restricted to the intermediate materials. The mudstone category can also refer to those rocks which would be difficult in the field to classify as either siltstones or claystones.

Classification of mudrocks depends on the grain size of the minerals making up the rock and whether or not the rock is fissile or non-fissile. Fissile or laminations are parallel layers less than 1 cm thick. Such laminations can be seen as differences in grain size of the clasts in different laminate, due to changes in current velocity of the depositing medium, or could be due to changes in the organic content and oxidation conditions at the site of deposition of the different layers. They often represent anisotropic over a

range of length scales, which Horne (2012) claimed that at the microscopic level mudrocks often possess aligned clay platelets and low-aspect ratio horizontal pores.

Mudrocks are most abundant of all sedimentary rocks, constituting about 45% to 55% of stratigraphic sequences (Hajdarwish *et al.*, 2006), thus they are often encountered in engineering construction. Mudrocks are widely found in various areas of construction such as, subgrade, base, aggregate and foundation (Aghamelu and Okogbue, 2011; Adewuyi and Festus, 2015; Maduka *et al.*, 2016; Tuffour *et al.*, 2016; Hartono *et al.*, 2018). For instance, tertiary sedimentary soft rock namely mudstone, have been undertaken in many construction sites and is the most often encountered geologic material. According to Shima and Imagawa (1980), mudstone was also reported to have caused poor performance of highway embankment in Japan which required drastic measures due to an excessive pavement cracks, rutting, and longitudinal roughness. In addition, massive landslides occurred in central Hokkaido, Japan and Shiaolin, Taiwan were also related with mudrocks abundance in the area (Tsou *et al.*, 2011; Yoneda *et al.*, 2014). Also, Sakai and Nakano (2018) found that slaking progression of mudstone in embankment near Makinohara service area had caused failure. These failures were reported as the effect of mudrocks-water interaction whether it was triggered by earthquake or weathering.

Based on the problems stated, it is clear that mudrocks when expose to water will cause slaking and consequently result into reduction of mechanical strength. This study is aiming to evaluate the shear and compression behaviour of mudrocks in Malaysia when in different contact with water. There are numerous of past researches that have explained the shear and compression behaviour of mudrocks (Petley, 1999; Nygård and Gutierrez, 2002; Yoshida *et al.*, 2004; Hajdarwish and Shakoor, 2006; Nahazanan *et al.*, 2013; Li and Wong, 2015; Liu *et al.*, 2016). However, the explanations available are only in physical prospective whereby the analysis and description of the behaviour were based wholly on results obtained from physical testings. There are also a number of researchers that have studied mudrocks through microstructural investigation (Blatt and Schultz, 1976; Lashkaripour and Ghafoori, 2002; Hildenbrand and Urai, 2003; Jiang *et al.*, 2014; Nooraiepour *et al.*, 2017), however, the findings were mainly concerning the mineralogical alteration and mudrocks sensitivity towards moisture but not to what happen to mudrocks during the failure. The discussion and explanation on microstructural changes and the corresponding mechanism prior to its shear and compression behaviour is somehow lacking. This is because the studies that have been conducted on studying mudrocks shear and compression behaviour were mainly on degree of settlement that may be caused due to swelling behaviour of mudrocks and its brittle-ductile transition (Nygård *et al.*, 2006; Amann *et al.*, 2012; Farid, 2016; Yin *et al.*, 2016). This study is hence point to describe shear and compression behaviour of mudrocks based on microstructural viewpoint

observed through VPSEM images, mineralogical analysis from XRD analysis and chemical composition obtained from XRF analysis. The microstructural testing were carried out and analysed to infer the problem of mudrocks governed by results of physical testing carried out beforehand.

1.2 Problem statements

Mudrocks including mudstone, shale, siltstone and claystone which comprised of mud-sized particles are one of major geological features of Malaysia occurring widely in Sabah and some parts of Peninsular Malaysia. In Sabah, series of landslides occurred at Kampung Mesilou, Kundasang were reportedly triggered by Kinabalu earthquake and followed by heavy rainfall (Rahim *et al.*, 2017). Also due to heavy rainfall, a landslide at forest reserve in Bukit Nanas, Kuala Lumpur occurred and it is found that the area was underlain by Kenny Hill Formation rock which comprised of sandstone, siltstone, and shale (Osman *et al.*, 2014).

Meanwhile in other countries, mudrocks has been widely used in construction such as highway embankment, as subgrade material, base course, aggregate and fill material around the world (Yoshida *et al.*, 2002; Aghamelu and Okogbue, 2011). In UK and US for instance, crushed mudrocks were heavily used to backfill opencast coal mine (Nahazanan *et al.*, 2013). Most of the times an area of mudrocks were crossed by road schemes, embankments and engineered slope due to its abundance in Japan (Yoshida *et al.*, 2002; Kimura *et al.*, 2010; Putra and Kikumoto, 2016; Nakano and Sakai, 2017). The main problem in utilizing mudrocks as the construction material is that they tend to deteriorate when in contact with water. According to Wang *et al.*(2015), the self-sealing property of mudrocks has led to their volume variation upon wetting. Mudrocks is a moisture sensitive materials that can change from a brittle crushable nature when dry to a ductile clay material when subjected to inundation (Nahazanan *et al.*, 2013). The deterioration or softening with time after construction had resulted into shear strength reduction and high compressibility (Putra and Kikumoto, 2016; Sharma *et al.*, 2017) which had caused settlement of fill, slope instability, damages to road pavement and foundations. In spite of its poor engineering behaviour, mudrocks is extensively used because often there are no other sources of suitable and economical construction material available (Bryson *et al.*, 2012). Studies on shear and compression behaviour of crushed mudrocks had been done on several countries by researchers (Kimura *et al.*, 2010; Aghamelu and Okogbue 2011; Nahazanan *et al.*, 2013; Sakai and Nakano 2018) however, studies on crushed mudrocks in Malaysia is lacking. The understanding on shear and compression behaviour of crushed mudrocks in Malaysia is important as Malaysia is a tropical country with tropical climate which exposed the crushed mudrocks to very dry season and heavy raining season. The exposure then increase crushed mudrocks susceptibility to fail in performing as industrial application such as subgrade or backfill material.

Hence to understand the mechanism of the softening, disintegration and deterioration of mudrocks which took place during the failure due to shear and compression from morphological prospective is of a vital importance in order to understand the root problem upon the failure. Through the understanding, further study and measurements that should be taken in overcoming the microscopic problem could be conducted in future with the advancing technologies.

1.3 Aim and objectives

The overall aim of this research is to investigate the shear and compression behaviour of crushed mudrocks in Malaysia as civil engineering construction materials. The following measures were carried out to achieve the aim:

- i. To study shear and compression behaviour of crushed mudrocks with various compaction degrees.
- ii. To study shear and compression behaviour of crushed mudrocks with various initial moisture contents.
- iii. To study shear and compression behaviour of crushed mudrocks with various terms of immersion.

1.4 Scope of work

This research is conducted to investigate the microstructural changes occurred during which the mudrocks failed when dry and when subjected to different term of submersion. The materials of mudrocks were collected from Putrajaya, Melaka (Durian Tunggal) and Perak (Semanggol).

The study focuses on the geotechnical and geological properties of samples including clay content, clay mineralogy, moisture content, specific gravity, liquid limit, plastic limit and plasticity index. The samples obtained from the sites were crushed into aggregate form and were made sure to be well graded before been tested to further tests. The Proctor Compaction Test was performed to determine the relationship between dry density and optimum moisture content of crushed sample. All samples from the sampling sites were compacted to three different compaction degrees (90%, 95%, and 100%). All procedures of laboratory tests were carried out by following a standard from BS 1377 (1990). Crushed samples were then made ready to be tested with direct shear test.

Despite the standard direct-shear test, a staged compression-immersion-direct shear test was implied in this research from which not only its compressive behaviour but also shear strength change during staged loading and due to immersion can be evaluated. Each sample was tested under five

different values of normal stresses by applying the loadings of 50 kPa, 100 kPa, 150 kPa, 300 kPa and 600 kPa. The five loadings were applied stage by stage, after settlement increment caused by each loading became negligible. Immersion was done onto samples to illustrate both short term immersion and long term immersion condition. Short term immersion is when the sample been immersed during the last stage (at 600 kPa loading) of the staged-loading process whilst long term immersion is when the sample been immersed since the second stage (at 100kPa loading) of staged-loading process. Detailed procedure is as described in Chapter 3.

Properties of mudrocks, such as durability, compressive strength, and shear strength were obtained and evaluated from the physical testing. Meanwhile, the mineralogical content, chemical composition, and morphological changes of the samples were analyzed and evaluated from XRD, XRF, and VPSEM.

1.5 Limitations of study

The crushed mudrocks used in this study were collected from Putrajaya, Semanggol (Perak), and Durian Tunggal (Melaka) in which the crushed mudrocks from the first two sampling sites were classified as mudstones while the other one was classified as claystone. The sampling works were limited to certain season (taken during April to May). This is to ensure the homogeneity of samples condition (not too dry and not too wet). Samples' crushing were conducted outdoor (due to lab's rule), was made sure to be conducted during right season too to reduce moisture escape. Moreover, due to limitation of the apparatus, it is recommendable that modification of the drum mesh is made as suggested by Heidari *et al.*(2015)

REFERENCES

- Abd Rahim, I., Lee, K.Y., and Mohd Salleh, N. (2017). Kampung Mesilou landslide: The controlling factors. *Geological Behavior (GBR)*, 1(1): 19–21. <https://doi.org/10.26480/gbr.01.2017.19.21>
- Abdullah, N. T. (2009). Mesozoic stratigraphy. In *Geology in Peninsular Malaysia*, eds. C. S. Hutchison and D. N. K. Tan, pp. 87. Petaling Jaya: The Geological Society of Malaysia.
- Adewuyi, O. I., and Festus, F. O. (2015). Suitability of Ugbo-Odogu and Gariki Shale, Southeastern Nigeria as Construction Materials, *International Journal of Pure and Applied Sciences and Technology*, 26(1): 1–13.
- Aghamelu, O. P., and Okogbue, C. O. (2011). Geotechnical Assessment of Road Failures in the Abakaliki Area, Southeastern Nigeria. *International Journal of Civil and Environmental Engineering*, 11(April): 12–24.
- Ahmed, J., Ghazali, M. A., Mukhlisin, M., Alias, M. N., and Taha, M. R. (2011). Effectiveness of horizontal drains in improving slope stability: A case study of landslide event in Putra Jaya Precinct 9, Malaysia. *Unsaturated Soils: Theory and Practice*, (January): 753–758.
- Al-Rawas, A. A., Guba, I., and McGown, A. (1998). Geological and engineering characteristics of expansive soils and rocks in northern Oman. *Engineering Geology*, 50(3–4): 267–281.
- Al-Rawas, A., Cheema, T., and Al-Aghbari, M. (2000). Geological and Engineering Classification Systems of Mudrocks. *Science and Technology*, (Special Review): 137–155.
- Alatas, I. M., Kamaruddin, S. A., Nazir, R., and Irsyam, M. (2016). Effect Of Weathering On Disintegration. *Jurnal Teknologi*, 78(7–3): 93–99.
- Amann, F., Kaiser, P., and Button, E. A. (2012). Experimental study of brittle behavior of clay shale in rapid triaxial compression. *Rock Mechanics and Rock Engineering*, 45(1): 21–33.
- Aplin, A. C., Hansen, S., and Yang, Y. (1995). Assessment of B, the compression coefficient of mudstones and its relationship with detailed lithology. *Marine and Petroleum Geology*, 12(8): 955–963.
- Avsar, E., Ulusay, R., and Sonmez, H. (2009). Assessments of swelling anisotropy of Ankara clay. *Engineering Geology*, 105(1–2): 24–31.
- Aziz, M., Towhata, I., Yamada, S., Qureshi, M. U., and Kawano, K. (2010). Water-induced granular decomposition and its effects on geotechnical

properties of crushed soft rocks. *Natural Hazards and Earth System Science*, 10(6): 1229–1238.

Bahar, R., Benazzoug, M., and Kenai, S. (2004). Performance of compacted cement-stabilised soil. *Cement and Concrete Composites*, 26(7): 811–820.

Ban, H., Lee, H., Bae, K., and Cho, W. (2015). Engineering Properties of Uncemented Mudrock. *Journal of the Korean Geo-Environmental Society*, 16(12): 53–58.

Bell, F. G., and Survey, B. G. (2005). Problematic Rocks. In F. G. Bell (Ed.), *Engineering Geology* (p. 2005). Elsevier Ltd.

Blatt, H., & Schultz, D. J. (1976). Size distribution of quartz in mudrocks. *Sedimentology*, 23(6): 857–866.

Braithwaite, C. J. R., and Heath, R. A. (2015). Alice, aggregates and tax: muddy waters. *Quarterly Journal of Engineering Geology and Hydrogeology*, 48: 244–247.

Brattli, B., and Broch, E. (1995). Stability problems in water tunnels caused by expandable minerals. Swelling pressure measurements and mineralogical analysis. *Engineering Geology*, 39(3–4): 151–169.

Broderick, G. P., and Daniel, D. E. (1990). Stabilizing Compacted Clay Against Chemical Attck. *Journal of Geotechnical Engineering*, 116(10): 1549–1567.

Bryson, L. S., Gomez-gutierrez, I. C., and Hopkins, T. C. (2012). Development of a new durability index for compacted shale. *Engineering Geology*, 139–140: 66–75.

Burmister, D. M. (1949). Principles and techniques of soil identification. In *Soils*, pp. 402–433). New York.

Casey, B., Germaine, J. T., Flemings, P. B., and Fahy, B. P. (2016). In-situ stress state and strength in mudrocks. *American Geophysical Union*, 121(8): 5611-5623.

Cheema, T., Al-Harthy, A., Al-Aghbari, M., and Al-Aufi, M. (2004). Proceedings from Geo Jordan Conference 2004, Irbid, Jordan.

Chu, L., and Yin, J. (2006). Comparison of Interface Shear Strength of Soil Nails Measured by Both Direct Shear Box Tests. *Journal of Geotechnical and Geoenvironmental Engineering*, 131(9): 1097–1107.

Chuan, S., Jun, T., Wang, J., Feng, Z., You, Q., and Tan, M. (2019). Effects of Wet – Dry Cycle on the Shear Strength of a Sandstone – Mudstone Particle Mixture. *International Journal of Civil Engineering*

- Clegg, W. (2015). *X-ray Crystallography*. Oxford, United Kingdom: Oxford University Press.
- Corominas, J., Martinez-Bofill, J., and Soler, A. (2015). A textural classification of argillaceous rocks and their durability. *Landslides*, 12: 669–687.
- Cox, S. (2018, October 5). Retired BC Hydro engineer calls for independent safety review of Site C dam. *The Narwhal Canada*.
- Cripps, J. C., and Czerewko, M. A. (2017). The influence of diagenetic and mineralogical factors on the breakdown and geotechnical properties of mudrocks. *Geomechanical and Petrophysical Properties of Mudrocks*, 454.
- Das, B. M. (2010). *Principles of Geotechnical Engineering Seventh Edition* Stamford, USA: Cengage Learning.
- Desbois, G., Höhne, N., Urai, J., Bésuelle, P., and Viggiani, G. (2017). Deformation in cemented mudrock (Callovo-Oxfordian Clay) by microcracking, granular flow and phyllosilicate plasticity: Insights from triaxial deformation, broad ion beam polishing and scanning electron microscopy. *Solid Earth*, 8(2): 291–305.
- Dick, J. C., and Shakoor, A. (1992). Lithological controls of mudrock durability. *Quarterly Journal of Engineering Geology and Hydrogeology*, 25(1): 31–46.
- Donald, A. M. (2003, August). The use of environmental scanning electron microscopy for imaging wet and insulating materials. *Nature Publishing Group*, 511–516.
- El-Shamy, A. M., Shehata, M. F., and Ismail, A. I. M. (2015). Effect of moisture contents of bentonitic clay on the corrosion behavior of steel pipelines. *Applied Clay Science*, 114: 461–466.
- Erguler, Z. A., and Shakoor, A. (2009). Relative contribution of various climatic processes in disintegration of clay-bearing rocks. *Engineering Geology*, 108(1–2): 36–42.
- Erguler, Z. A., and Ulusay, R. (2009). Assessment of physical disintegration characteristics of clay-bearing rocks: Disintegration index test and a new durability classification chart. *Engineering Geology*, 105(1–2): 11–19.
- Farid, A. T. M. (2016). Swelling Characteristics of Wadi Al Dawasir Mudrocks and Impact on Light Structures. Proceedings from ASCE: *Fourth Geo-China International Conference*, Shandong, China.

- Fityus, S. (2015). Weathering and Degradation of Shales and Mudrocks. Proceedings from ISRM: *13th ISRM International Congress of Rock Mechanics*. Montreal, Canada.
- Franklin, J. A., and Chandra, R. (1972). The slake-durability test. *International Journal of Rock Mechanics and Mining Sciences*, 9(3): 325–328.
- Gasparrini, M., Sassi, W., and Gale, J. F. W. (2014). Natural sealed fractures in mudrocks: A case study tied to burial history from the Barnett Shale, Fort Worth Basin, Texas, USA. *Marine and Petroleum Geology*, 55: 122–141.
- Gautam, T. P. (2012). *An Investigation of Disintegration Behavior of Mudrocks Based on Laboratory and Field Tests*. (Electronic Thesis or Dissertation). Retrieved from <https://etd.ohiolink.edu>
- Gautam, T. P., and Shakoor, A. (2013). Slaking behavior of clay-bearing rocks during a one-year exposure to natural climatic conditions. *Engineering Geology*, 166: 17–25.
- Gautam, T. P., and Shakoor, A. (2015). An Experimental Study for Evaluating the Disintegration Behavior of Clay-Bearing Rocks under Field Conditions. *Engineering Geology for Society and Territory*, 5: 1285–1288.
- Gonzalez, I. J., and Scherer, G. W. (2004). Effect of swelling inhibitors on the swelling and stress relaxation of clay bearing stones. *Environmental Geology*, 46: 364–377.
- Grainger, P. (1984). The classification of mudrocks for engineering purposes. *Quarterly Journal of Engineering Geology*, 17: 381–387.
- Gue, S. S., and Tan, Y. C. (2002). Prevention of failures related to geotechnical works on soft ground. Proceedings from *Malaysian Geotechnical Conference*, Malaysia.
- Guiltinan, E. J., Espinoza, D. N., Cockrell, L. P., and Cardenas, M. B. (2018). Advances in Water Resources Textural and compositional controls on mudrock breakthrough pressure and permeability. *Advances in Water Resources*, 121: 162–172.
- Gullà, G., Mandaglio, M. C., and Moraci, N. (2006). Effect of weathering on the compressibility and shear strength of a natural clay. *Canadian Geotechnical Journal*, 43(6): 618–625.
- Hajdarwish, A., and Shakoor, A. (2006). Predicting the shear strength parameters of mudrocks. *International Association for Engineering Geology and the Environment*, (607): 1–9.

- Hajdarwish, A., Shakoor, A., and Wells, N. A. (2013). Investigating statistical relationships among clay mineralogy , index engineering properties , and shear strength parameters of mudrocks. *Engineering Geology*, 159: 45–58.
- Hartono, E., Prabandiyani, S., Wardani, R., and Muntohar, A. S. (2018). The effect of cement stabilization on the strength of the Bawen ' s siltstone. Proceedings from EDP Sciences: *MATEC Web of Conferences*.
- Hawkins, A. B., and Pinches, G. M. (1992). Engineering description of mudrocks. *Quarterly Journal of Engineering Geology*, 25: 17–30.
- Heidari, M., Rafiei, B., Mohebbi, Y., and Torabi-Kaveh, M. (2015). Assessing the Behavior of Clay-Bearing Rocks Using Static and Dynamic Slaking Indices. *Geotechnical and Geological Engineering*, 33(4): 1017–1030.
- Hildenbrand, A., and Urai, J. L. (2003). Investigation of the morphology of pore space in mudstones-first results. *Marine and Petroleum Geology*, 20(10): 1185–1200.
- Hopkins, T. C., and Deen, R. C. (1983). Identification of Shales. *Kentucky Transportation Research Program*. Kentucky: University of Kentucky.
- Horpibulsuk, S., Miura, N., and Bergado, D. T. (2004). Undrained Shear Behavior of Cement Admixed Clay at High Water Content. *Journal of Geotechnical and Geoenvironmental Engineering*, 130(10): 1096–1105.
- Horpibulsuk, S., Udomchai, A., Joongklang, A., Mavong, N., Nikompakdi, P., and Arulrajah, A. (2016). Pullout mechanism of the bearing reinforcement embedded in claystone soil of Mae Moh mine. Proceedings from Japanese Geotechnical Society Special Publication: *The 15th Asian Regional Conference on Soil Mechanics and Geotechnical Engineering*.
- Hosterman, J. W., and Loferski, P. J., *Sample preparation for x-ray diffraction analysis and clay mineralogy of Devonian Shale from the Appalachian basin*. United States Department of Energy. Morgantown. 1981.
- Huggett, J. M., and Uwins, P. J. R. (1994). Observations of water-clay reactions in water-sensitive sandstone and mudrocks using an environmental scanning electron microscope. *Journal of Petroleum Science and Engineering*, 10: 211–222.
- Hupp, B. N., and Donovan, J. J. (2018). Quantitative mineralogy for facies definition in the Marcellus Shale (Appalachian Basin, USA) using XRD-XRF integration. *Sedimentary Geology*, 371: 16–31.

- Hussein, A. N. (2004). Failure Investigation of a Fill Slope in Putrajaya , Malaysia. Proceedings from Missouri University of Science and Technology: *Fifth International Conference on Case Histories in Geotechnical Engineering*. New York.
- Hutchison, C. S., and Tan, D. N. K. (2009). *Geology of Peninsular Malaysia*. Kuala Lumpur: Geological Society of Malaysia.
- Javadpour, F. (2009). Javedpour- Nanopores and Apparent Permeability of Gas Flow in Mudrocks, Shales and Siltstone. *Journal of Canadian Petroleum Technology*, 48: 16–21.
- Jenkins, R. (1999). X-Ray Fluorescence Spectrometry. *International Centre for Diffraction Data*. Pennsylvania.
- Jiang, Q., Cui, J., Feng, X., and Jiang, Y. (2014). Application of computerized tomographic scanning to the study of water-induced weakening of mudstone. *Bulletin of Engineering Geology and the Environment*, 73(4): 1293–1301.
- Johnston, I. W., and Chiu, H. K. (1984). Strength of weathered Melbourne mudstone. *Journal of Geotechnical Engineering*, 110(7): 875–898.
- Kimura, S., Gibo, S., Nakamura, S., Sasaki, K., and Zhou, Y. (2010). Shear strength in first-time activation and reactivation of Shimajiri-mudstone landslide: An example of Asato landslide, Okinawa, Japan. *Journal of the Japan Landslide Society*, 47(3): 138–146.
- Kong, L., Zeng, Z., Bai, W., and Wang, M. (2017). Engineering geological properties of weathered swelling mudstones and their effects on the landslides occurrence in the Yanji section of the Jilin-Hunchun high-speed railway. *Buletin of Engineering Geology and Environment*.
- Koralegedara, N. H., & Maynard, J. B. (2017). Chemical , mineralogical and textural properties of the Kope Formation mudstones : How they affect its durability, *Engineering Geology*, 228: 312–322.
- Kowalik-klimczak, A., Bednarska, A., and Gradkowski, M. (2016). Scanning Electron Microscopy (SEM) in the Analysis of the Structure of Polymeric Nanaofiltration membranes. *Problemy Eksploatacji – Maintenance Problems*, 1: 119–128.
- Lashkaripour, G. R., and Ghafoori, M. (2002). Mineralogical controls of mudrock durability. Proceedings from *9th Congress of the International Association for Engineering Geology and the Environment*. Durban, South Africa.
- Latifi, N., Marto, A., Safuan, A., Jacky, A. R., and Jia, L. (2015). Strength and Physico-chemical Characteristics of Fly Ash–Bottom Ash Mixture, *Arabian Journal for Science and Engineering*.

- Leśniak, G. (2011). An application of microscopic analyses in shale gas rock description. Krakow: Oil and Gas Institute.
- Li, B., and Wong, R. C. . (2015). Quantifying structural states of soft mudrocks. *Journal of Geophysical Research: Solid Earth*, 1–24.
- Liew, S. S., and Gue, S. S. (2001). Massive Creep Movements of Post-Glacial Deposits in Kundasang Areas. Proceedings from GSM-IEM Forum : *Engineering Geology & Geotechnics of Slopes*. Kuala Lumpur, Malaysia.
- Liu, W., Chen, W., Lin, G., Wang, J., Sun, G., and Zhong, X. (2018). Shear Strength of Slip Surface in Loess-Mudstone Interface Landslide Wei. Proceedingd from *Proceedings of GeoShanghai 2018 International Conference: Fundamentals of Soil Behaviours* (Vol. 1, pp. 531–539). Shanghai: Springer Singapore.
- Liu, X., Zhang, C., Yuan, S., Fityus, S., William, S., and Olivier, S. (2016). Effect of High Temperature on Mineralogy , Microstructure , Shear Stiffness and Tensile Strength of Two Australian Mudstones. *Rock Mechanics and Rock Engineering*, 49(9): 3513–3524.
- Loggerenberg, D. E. Van, Laver, P. N., Myburgh, J. G., and Botha, C. J. (2018). Diagnostic Value of Energy Dispersive Hand-Held X-ray Fluorescence Spectrometry in Determining Trace Element Concentrations in Ovine Liver. *Biological Trace Element Research*, 1–4.
- Loucks, R. G., Reed, R. M., Ruppel, S. C., and Hammes, U. (2012). Spectrum of pore types and networks in mudrocks and a descriptive classification for matrix-related mudrock pores. *AAPG Bulletin*, 96(6): 1071–1098.
- Maduka, R. I., Ayogu, N. O., Ayogu, C. N., & Gbakurun, G. A. (2016). Role of smectite-rich shales in frequent foundation failures in southeast Nigeria, (6): 1215–1233.
- Manasseh, J., & Olufemi, A. (2008). Effect of lime on some geotechnical properties of Igumale shale. *Electronic Journal of Geotechnical Engineering*. Retrieved from <http://ejge.com/2008/Ppr0696/Ppr0696>.
- Marques, E. A. G., Pedes, E., and Vargas, D. O. A. (2005). A study of the durability of some shales , mudrocks and siltstones from Brazil, 321–348.
- Mathieu, C. (1998). Effects of Electron-Beam / Gas Interactions on X-Ray Microanalysis in the Variable Pressure SEM, 300: 295–296.
- Mohamad, N. O., Razali, C. E., Hadi, A. A. A., Som, P. P., Eng, B. C., Rusli, M. B., and Mohamad, F. R. (2016). Challenges in Construction over

- Mollins, L. H., Stewart, D. I., and Cousens, T. W. (1996). Predicting the properties of bentonite-sand mixtures. *Clay Minerals*, 31(2): 243–252.
- Mondol, N. H., Bjørlykke, K., Jahren, J., and Høeg, K. (2007). Experimental mechanical compaction of clay mineral aggregates-Changes in physical properties of mudstones during burial. *Marine and Petroleum Geology*, 24(5): 289–311.
- Moon, V. G., and Beattie, A. G. (1995). Textural and microstructural influences on the durability of Waikato Coal Measures mudrocks. *Quarterly Journal of Engineering Geology*, 28: 303–312.
- Mote, V., Purushotham, Y., and Dole, B. (2012). Williamson-Hall analysis in estimation of lattice strain in nanometer-sized ZnO particles. *Journal of Theoretical and Applied Physics*, 6(1): 6.
- Na, Z., Longbiao, L., Dongwen, H., Manchao, H., and Yilei, L. (2014). Geomechanical and water vapor absorption characteristics of clay-bearing soft rocks at great depth. *International Journal of Mining Science and Technology*, 24: 811–818.
- Nahazanan, H., Clarke, S., Asadi, A., Md.Yusoff, Z., and Huat, B. K. (2013). Effect of inundation on shear strength characteristics of mudstone backfill. *Engineering Geology*, 158: 48–56.
- Nakano, M., and Sakai, T. (2017). Interpretation of slaking of a mudstone embankment using soil skeleton structure model concept and reproduction of embankment failure by seismic analysis. Proceedings from *The 15th Asian Regional Conference on Soil Mechanics and Geotechnical Engineering*.
- Nakano, R. (1970). On weathering and change of properties of Tertiary sedimentary rocks (mudstone) related to landslide. *Rock Mechanics in Japan*, 1: 71–73.
- Ng, S. M., Ismail, M. A. M., and Abustan, I. (2014). Probabilistic Back Analysis of a Cut Slope: A Case Study of Slope Failure Event in Precinct 9, Putrajaya, Malaysia. Proceedings from *Landslide Science for a Safer Geoenvironment*. Springer..
- Nooraiepour, M., Haque, N., and Hellevang, H. (2017). Experimental mechanical compaction of reconstituted shale and mudstone aggregates : Investigation of petrophysical and acoustic properties of SW Barents Sea cap rock sequences. *Marine and Petroleum Geology*, 80: 265–292.

- Nygård, R., and Gutierrez, M. (2002). Undrained Shear Behaviour of Some UK Mudrocks Explained by Petrology. *Journal of Canadian Petroleum Technology*, 41(12), 37–46.
- Nygård, R., Gutierrez, M., Bratli, R. K., and Høeg, K. (2006). Brittle-ductile transition, shear failure and leakage in shales and mudrocks. *Marine and Petroleum Geology*, 23(2): 201–212.
- Odoma, A. N., Obaje, N. G., Omada, J. I., Idakwo, S. O., and Erbacher, J. (2015). Mineralogical, chemical composition and distribution of rare earth elements in clay-rich sediments from Southeastern Nigeria. *Journal of African Earth Sciences*, 102: 50–60.
- Olgaard, D. L., Urai, J., Dell'Angelo, L. N., Nuesch, R., and Ingram, G. (1997). The influence of swelling clays on the deformation of mudrocks. *International Journal of Rock Mechanics and Mining Sciences & Geomechanic*, 34(3–4): 364.
- Olivier, H. J. (1979). A New Engineering-Geological Rock Durability Classification. *Engineering Geology*, 14: 255–279.
- Osman, K., Kasim, N., and Yusof, M. A. M. (2014). Landslide Investigation : A Case Study of the Landslide in Bukit Nanas Kuala Lumpur , Malaysia. Proceedings from *World Landslide Forum 3*.
- Pejon, O. J., and Zuquette, L. V. (2002). Analysis of cyclic swelling of mudrocks. *Engineering Geology*, 67(1–2): 97–108.
- Petley, D. N. (1999). Failure envelopes of mudrocks at high confining pressures. *Muds and Mudstones: Physical and Fluid Flow Properties*, 158(May 2007): 61–71.
- Phan, V. T. (2017). Improvement in Engineering Properties of Mudstone in Southwestern Taiwan Through Compaction and a Cement Additive. *Geotechnical and Geological Engineering*.
- Prodan, M. V., and Arbanas, C. (2016). Weathering Influence on Properties of Siltstones from Istria , Croatia. *Advances in Materials Science and Engineering*, 2016: 1–15.
- Putra, A. D., and Kikumoto, M. (2016). Slaking of Mudstone and its Mechanical Consequences in 1D compression condition. Proceedings from *50th U.S. Rock Mechanics/Geomechanics Symposium*. Houston, Texas: American Rock Mechanics Association.
- Raj, J. K., Tan, D. N. K., and Hutchison, C. S. (2009). Cenozoic stratigraphy. *Geology in Peninsular Malaysia*. Petaling Jaya: The Geological Society of Malaysia.

- Reed, Hughes, and Singh. (1987). Backfill settlement of restored strip mine sites — case histories. *International Journal of Mining and Geological Engineering*, 5: 161–169.
- Richardson, D., and Long, J. D. (1987). The sieved slake durability test.pdf. *Bulletin of Association of Engineering Geologists*, XXIV(2): 247–258.
- Rowe, H., Hughes, N., and Robinson, K. (2012). The quantification and application of handheld energy-dispersive x-ray fluorescence (ED-XRF) in mudrock chemostratigraphy and geochemistry. *Chemical Geology*, 325: 122–131.
- Rutter, E., Mecklenburgh, J., and Taylor, K. (2017). Geomechanical and petrophysical properties of mudrocks: introduction. *Geological Society, London, Special Publications*, 454(1), 1–13.
- Sadisun, I. A. (2002). Improved Procedures for Evaluating Physical Deterioration of Argillaceous Rocks. Proceedings from 2nd *International Conference on New Development in Rock Mech. and Rock Eng.*
- Sadisun, I. A., Shimada, H., Ichinose, M., and Matsui, K. (2005). Study on the physical disintegration characteristics of Subang claystone subjected to a modified slaking index test. *Geotechnical and Geological Engineering*, 23(3): 199–218.
- Sakai, T., and Nakano, M. (2018). Effects of slaking and degree of compaction on the mechanical properties of mudstones with varying slaking properties. *Soils and Foundations*.
- Santi, P. M. (1998). Improving the jar slake, slake index, and slake durability tests for shales. *Environmental and Engineering Geoscience*.
- Santi, P. M., and Higgins, J. D. (1998). Methods for Predicting Shale Durability in the Field. *Geotechnical Testing Journal*.
- Shakoor, T. P. G. A. (2015). Comparing the Slaking of Clay-Bearing Rocks Under Laboratory Conditions to Slaking Under Natural Climatic Conditions. *Rock Mechanics and Rock Engineering*.
- Sharma, K., Kiyota, T., and Kyokawa, H. (2013). Effect of Slaking on the Engineering. *Bulletin of ERS*, (46): 73–82.
- Sharma, K., Kiyota, T., and Kyokawa, H. (2017). Effect of slaking on direct shear behaviour of crushed mudstones. *Soils and Foundations*, 57: 288–300.
- Sibanda, Z., and Mhlongo, S. E. (2013). Characterization and Evaluation of Magnesite Tailings for Their Potential Utilization : A Case Study of Nyala Magnesite Mine , Limpopo Province of South Africa. *Journal of*

- Sharma, K. 2012. *Slaking characteristics of geomaterials in direct shear test*, M.Eng Thesis, The University of Tokyo.
- Stead, D. (2015). The Influence of Shales on Slope Instability. *Rock Mechanics and Rock Engineering*.
- Streli, C., Wobrauschek, P., and Kregsamer, P. (2017). X-Ray Fluorescence Spectroscopy, Applications. In *Encyclopedia of Spectroscopy and Spectrometry* (3rd ed., pp. 707–715). Elsevier Ltd.
- Taylor, D. (2018, September 21). Can-do attitude on Heads of the Valleys. *The Construction Index*.
- Taylor, R. K., and Spears, D. A. (1981). Laboratory investigation of mudrocks. *Quarterly Journal of Engineering Geology and Hydrogeology*, 14(4): 291–309.
- Tiwari, B. (2010). Particle crushing in natural soil at large displacements. *Electronic Journal of Geotechnical Engineering*, 15(January): 1221–1242.
- Tovar, R. D., and Colmenares, J. E. (2011). Effect of drying and wetting cycles on the shear strength of argillaceous rocks. *Unsaturated Soils*, (1967), 1471–1476.
- Tsou, C. Y., Feng, Z. Y., and Chigira, M. (2011). Catastrophic landslide induced by Typhoon Morakot, Shiaolin, Taiwan. *Geomorphology*, 127(3–4): 166–178.
- Tsoy, P. (2018). Determination of deformation and strength characteristics of artificial geomaterial having step-shaped discontinuities under uniaxial compression. *Proceedings from IOP Conference Series: Geodynamics and Stress State of the Earth's Interior* (pp. 1–5). IOP Publishing.
- Tuffour, Y. A., Banini, S. Y., & Adams, C. A. (2016). Investigation of Afram Shale for Road Construction. *American Journal of Civil Engineering and Architecture*, 4(3): 80–83.
- U.S Department of Transportation. (1991). *Rock and Mineral Identification for Engineers. Federal Highway Administration*.
- Underwood, M. B., & Pickering, K. T. (1996). Clay-mineral provenance, sediment dispersal patterns, and mudrock diagenesis in the Nankai accretionary prism, southwest Japan. *Clays and Clay Minerals*, 44(3): 339–356.

- Vaniman, D. T., Bish, D. L., Ming, D. W., Bristow, T. F., Morris, R. V, Blake, D. F., and Newsom, H. E. (2014). Mineralogy of a Mudstone at Yellowknife Bay, Gale Crater, Mars D., 343(January): 1–8.
- Vernik, L., and Kachanov, M. (2010). Modeling elastic properties of siliciclastic rocks. *Geophysics*, 75(6): 171–182.
- Wagner, J. (2013). Mechanical Properties of Clays and Clay Minerals. In *Handbook of Clay Science* (2nd ed., Vol. 5, pp. 347–381). Trier, Germany: Elsevier Ltd.
- Walkinshaw, J. L., and Santi, P. M. (1996). Shale and other degradable materials. In *Landslides: Investigation and Mitigation* (pp. 555–576). Washington D.C.
- Wang, L. L., Bornert, M., Yang, D. S., Héripré, E., Chanchole, S., Halphen, B., Caldemaïson, D. (2015). Microstructural insight into the nonlinear swelling of argillaceous rocks. *Engineering Geology*, 193: 435–444.
- Wang, L. L., Yang, D. S., Yang, R. W., and Chanchole, S. (2016). Investigating the mechanical behavior of shale: A micro-scale approach. *Journal of Natural Gas Science and Engineering*, 1–8.
- Wang, X., Sanei, H., Dai, S., Ardakani, O. H., Kondla, D., Chen, Z., & Tang, Y. (2015). Mineral Components Inferred From Bulk Geochemical Data : A Preliminary Study Of Four Canadian Mudrocks. Proceedings from 32nd Annual Meeting of The Society for Organic Petrology. Java, Indonesia.
- Wetzel, A., and Einsele, G. (1991). On the physical weathering of various mudrocks. *Bulletin of the International Association of Engineering Geology*, 89–100.
- Wijeyesekera, D. C., Ho, M. H., Bai, X., and Bakar, I. (2016). Strength and Stiffness Development in Soft Soils: A FESEM aided Soil Microstructure Viewpoint. Proceedings from *IOP Conference Series: Materials Science and Engineering*,.
- Xiao, Y., Meng, M., Daouadji, A., Chen, Q., Wu, Z., and Jiang, X. (2018). Effects of particle size on crushing and deformation behaviors of rock fill materials. *Geoscience Frontiers*, ((in press)).
- Yagiz, S. (2001). Overview of Classification and Engineering Properties of Shales for Design Considerations. Proceedings from *Construction Institute Sessions at ASCE Civil Engineering Conference 2001* (pp. 156–165). Houston, Texas.
- Yin, Y., Zhang, B. Y., Zhang, J. H., and Sun, G. L. (2016). Effect of densification on shear strength behavior of argillaceous siltstone subjected to variations in weathering-related physical and mechanical

conditions. *Engineering Geology*, 208: 63–68.

Yoneda, T., Hayashi, K., and Kashiwaya, K. (2014). Mineralogical characterization of mudstone weathering: A case study in a landslide area, central Hokkaido, Japan. Proceedings from *ISRM International Symposium - 8th Asian Rock Mechanics Symposium*. Japan.

Yoshida, N., and Hosokawa, K. (2004). Compression and Shear Behavior of Mudstone Aggregates. *Journal of Geotechnical and Geoenvironmental Engineering*, 130(May): 519–525.

Yoshida, N., Enami, K., & Hosokawa, K. (2002). Staged compression-immersion direct shear test on compacted crushed mudstone. *Journal of Testing and Evaluation*, 30(3): 239–244.

Young, K. E., Evans, C. A., Hodges, K. V, Bleacher, J. E., and Graff, T. G. (2016). A review of the handheld X-ray fluorescence spectrometer as a tool for field geologic investigations on Earth and in planetary surface exploration. *Applied Geochemistry*, 72: 77–87.

BIODATA OF STUDENT

Ili Syazwani binti Che Mohd Rosley is a graduate of Civil Engineering from Universiti Kebangsaan Malaysia (UKM). Then, she pursued master's degree in Geotechnical and Geological Engineering under the supervision of Dr. Haslinda binti Nahazanan. Her interest is in geotechnical engineering, study of mudrocks. Interest in geotechnical engineering had grown since she was in her second year of bachelor's study whence she became a rescue volunteer for victims of a landslide in Hulu Langat. Prior to enrolling at Universiti Putra Malaysia (UPM), she worked as a research assistant under the same supervision for two months after gained her experience as a geotechnical engineer at Mohd Asbi and Associates Sdn. Bhd. from 2014 to 2015.



LIST OF PUBLICATIONS

- Rosley, I. S. , Nahazanan, H. 2017a. "Slaking Behaviour of Mudrocks at Precinct 5 , Putrajaya and Its Performance as Subgrade Material for Road Construction" *Journal of Engineering and Applied Sciences* 12(18), 4568–72.
- Rosley, I. S., Nahazanan, H. 2016. "Shear and Compression Behavior of Putrajaya Crushed Mudrocks at Optimum Moisture Content." Presented in *3rd International Seminar of Geotechnical Engineering and Geological Engineering*. Putrajaya, Malaysia.
- Nahazanan, H., Rosley, I. S. 2017. "Shear and Compression Behaviour of Putrajaya Mudrocks at Natural Moisture Content." Presented in *3rd Global Civil Engineering Conference*. Kuala Lumpur, Malaysia.
- Rosley, I. S, Nahazanan, H. 2017b. "The Mineralogical Effect on Durability of Semanggol Mudstones." In *4th International Seminar of Geotechnical Engineering and Geological Engineering*. Putrajaya, Malaysia.
- Rosley, I. S, Nahazanan, H. 2018. "Effect of Immersion on Shear Behavior of Claystone." In *5th 3rd International Seminar of Geotechnical Engineering and Geological Engineering*. Putrajaya, Malaysia.
- Rosley, I. S., Nahazanan, H. "Shear Behavior of Crushed Mudstone and Claystone under Macrostructural and Microstructural Approaches" *Journal of Testing and Evaluation*. Accepted.
- Rosley, I. S., Nahazanan, H. "Effect of fly ash and lime as stabiliser on Kundasang Shale" *Jurnal Teknologi*. Submitted.
- Rosley, I. S., Nahazanan, H. "Effects of immersion and degree of compaction on shear an compression behavior of crushed mudrocks" *Geotechnical Testing Journal*. Accepted.



UNIVERSITI PUTRA MALAYSIA

STATUS CONFIRMATION FOR THESIS / PROJECT REPORT AND COPYRIGHT

ACADEMIC SESSION : Second Semester 201/2019

TITLE OF THESIS / PROJECT REPORT :

SHEAR AND COMPRESSION BEHAVIOUR OF CRUSHED MUDROCKS IN MALAYSIA

NAME OF STUDENT: ILI SYAZWANI BINTI CHE MOHD ROSLEY

I acknowledge that the copyright and other intellectual property in the thesis/project report belonged to Universiti Putra Malaysia and I agree to allow this thesis/project report to be placed at the library under the following terms:

1. This thesis/project report is the property of Universiti Putra Malaysia.
2. The library of Universiti Putra Malaysia has the right to make copies for educational purposes only.
3. The library of Universiti Putra Malaysia is allowed to make copies of this thesis for academic exchange.

I declare that this thesis is classified as :

*Please tick (V)

☐

CONFIDENTIAL

(Contain confidential information under Official Secret Act 1972).

☐

RESTRICTED

(Contains restricted information as specified by the organization/institution where research was done).

☐

OPEN ACCESS

I agree that my thesis/project report to be published as hard copy or online open access.

This thesis is submitted for :

☐

PATENT

Embargo from _____ until _____
(date) (date)

Approved by:

(Signature of Student)
New IC No/ Passport No.:

Date :

(Signature of Chairman of Supervisory Committee)
Name:

Date :

[Note : If the thesis is **CONFIDENTIAL** or **RESTRICTED**, please attach with the letter from the organization/institution with period and reasons for confidentiality or restricted.]